

1 Default commands list.

1.1 Move commands.

Ctrl-a	Move to beginning of line.
Ctrl-b	Move to backward char.
Ctrl-e	Move to end of line.
Ctrl-f	Move to forward char.
Ctrl-n	Move to next line.
Ctrl-p	Move to previous line.
Ctrl-v	Move to next page.
Ctrl-x l	Move to line number.
Ctrl-x m	Move to mark.
Ctrl-x Ctrl-x	Exchange cursor/mark.
Esc v	Move to previous page.
Esc <	Move to first page.
Esc >	Move to last page.
Down arrow	Move to next line.
Left arrow	Move to backward char.
Right arrow	Move to forward char.
Up arrow	Move to previous line.

1.2 Modify commands.

Ctrl-d	Delete current character.
Ctrl-h	Delete previous character.
Ctrl-i	Insert tab.
Ctrl-j	Insert return.
Ctrl-k	Delete end of line.
Ctrl-m	Insert return.
Ctrl-o	Open space.

1.3 Mark and region commands.

Ctrl-space	Set mark.
Ctrl-x Ctrl-x	Exchange cursor/mark.
Ctrl-y	Paste previous kill.
Ctrl-w	Cut region.
Esc w	Copy region.
Esc e	Eval region.

1.4 Search commands.

Esc q	Query replace.
Esc r	Global replace.
Ctrl-s	Forward search.
Ctrl-r	Backward search.

1.5 Files commands.

Ctrl-x b	Display open files.
Ctrl-x i	Insert file.
Ctrl-x Ctrl-s	Save file.
Ctrl-x Ctrl-f	Read file.
Ctrl-x Ctrl-w	Write file as.

1.6 Windows commands.

Ctrl-l	Refresh current page.
Ctrl-x n	Open new edition area.
Ctrl-x Ctrl-c	Delete window.
Ctrl-x k	Clear buffer.

1.7 Misc commands.

Ctrl-c	Play macro.
Ctrl-g	Abort current command.
Ctrl-q	Quote char.
Ctrl-t	Redo.
Ctrl-u	Undo.
Ctrl-x (Learn macro.
Ctrl-x)	End macro.
Ctrl-x Ctrl-e	Eval expression.
Esc =	Current line number.
Esc digits	Get repeat number.

2 Minibuffer commands.

Ctrl-a	Go to beginning of line.
Ctrl-b	Backward char.
Ctrl-d	Delete current character.
Ctrl-e	Go to end of line.
Ctrl-f	Forward char.

3 Built-in functions.

3.1 Get information.

Ctrl-g	Abort.
Ctrl-h	Delete previous character.
Ctrl-k	Delete end of line.
Ctrl-p	Restore previous user answer.
Tab	Expand identifier.

int	at_end_of_file ()
int	beginning_of_line ()
char	current_char ()
int	current_line ()
int	re_match_beginning (int subs)
int	re_match_end (int subs)
char	next_char ()
char	previous_char ()
int	end_of_file ()
int	current_position ()
int	end_of_line ()
char	the_char (int pos)
int	line_count ()
char	last_key ()

3.2 Search.

int	backward_search (char *str)
int	forward_search (char *str)
void	replace_char (int c)
void	blink (int pos)
int	nssearch (char *chars, int end, int direction)
int	global_replace (char *old, char *new)
int	re_forward_search (char *regexp)
int	re_backward_search (char *regexp)
int	re_replace (char* newstring, [char *regexp])
int	re_match_beginning (int n)
int	re_match_end (int n)

3.3 Move.

void	current_line_to_top ()
void	goto_beginning_of_line ()
void	goto_char (int pos)
void	goto_next_char ()
void	goto_end_of_line ()
void	goto_end_of_file ()
void	goto_previous_char ()
void	goto_mark ()

3.4 Modify current buffer.

void	delete_char ()
void	insert_char (int c)
void	read_file (char *file_name)
int	insert_file (char *file_name)
void	insert_string (char *string)
void	kill_current_buffer ()

3.5 Window.

int	new_window ()
int	kill_window (int num)
void	lower_window ()
void	raise_window ()
int	current_window ()
int	window_width (int c)
int	window_height ()
void	select_window (int win_id)

3.6 Mode.

void	set_mode (char *name)
void	create_mode (char *mode_name)
char	*current_mode ()
void	key_def (char *m_name, char *keys, char *f_name)
void	set_mode_font (char *font_name)
void	*mode_name, char *font_name
void	set_mode_suffixes (char *mode_name, char *suf)

3.7 Mark.

void	set_mark (int pos)
void	goto_mark()
void	reset_mark()
void	copy_region()
void	paste_region()
void	cut_region()
int	mark_position()

3.8 Miscellaneous.

int	cmd_shell (char *str)
char	*shell_to_string (char *str)
void	redisplay ()
char	*filename ()
char	*fileselect ()
char	*getchar (char *prompt)
char	*gets (char *prompt)
void	save_file ()
void	set_font (char *fontname)
void	color_area (int start, int end, char *colorname)
void	watch_on ()
void	watch_off ()
int	monochrome()
void	usleep (int us)

4 Keybindings.

4.1 Global key bindings.

Esc space	just_one_blank
Esc /	complete_word
Esc \	delete_line_blanks
Esc k	delete_to_beginning_of_ line
Esc m	recenter
Ctrl-x #	sharp_comment
Ctrl-x %	percent_comment
Ctrl-x +	plus_comment
Ctrl-x -	minus_comment
Ctrl-x =	equal_comment
Ctrl-x C	CompareAgain
Ctrl-x a	color_buffer

Ctrl-x c	center_line
Ctrl-x d	dump_browser_data
Ctrl-x e	edir
Ctrl-x g	go_next
Ctrl-x r	restore_browser_data
Ctrl-x s	update_title_backup_ and_save_file
Ctrl-x t	transpose_chars
Ctrl-x y	transpose_forms
Ctrl-x z	update_title_and_save_ file

4.2 C/C++ mode key bindings.

)	c.insert_blink_unmatched_char_ and_indent
:	c.insert_and_indent
Vr	c.insert_and_indent
Vt	c.indent_line
J	c.insert_blink_unmatched_char_ and_indent
Esc \b	delete_previous_c_form
Esc \177	delete_previous_c_form
Esc a	goto_beginning_of_c_definition
Esc b	backward_c_form
Esc c	capitalize_word
Esc d	delete_next_c_form
Esc f	forward_c_form
Esc i	c.indent_region
Esc l	downcase_word
Esc u	upcase_word
Ctrl-x g	go_next
{	c.insert_and_indent
}	c.insert_blink_unmatched_char_ and_indent

4.3 Edir mode key bindings.

space	goto_next_line
!	edir_shell_command
<	edir_up
=	edir_diff

>	edir_up_new
?	edir_help
C	edir_copy
G	edir_change_group
H	edir_hardlink
L	edir_load
M	edir_change_mode
P	edir_print
R	edir_rename
S	edir_symlink
Z	edir_compress_uncompress
\177	goto_previous_line
Ctrl-h	goto_previous_line
Ctrl-x Ctrl-c	edir_quit
Ctrl-x d	edir

f	edir_find
g	edir_reread
n	edir_new
o	edir_new
q	edir_quit
r	edir_reread
s	edir_shell_command

4.4 Latex mode key bindings.

Vr	latex_newline_and_indent
Vt	latex_indent_line
Esc \177	delete_previous_word
Esc \b	delete_previous_word
Esc a	goto_beginning_of_latex_ definition
Esc b	backward_word
Esc c	capitalize_word
Esc d	delete_next_word
Esc f	forward_word
Esc i	latex_indent_region
Esc l	downcase_word
Esc u	upcase_word
Esc x	latex_back_indent
'	french_accent
^	french_accent
"	french_accent

4.5 Shell mode key bindings.

Esc \177	delete_previous_c_form
Esc \b	delete_previous_c_form
Esc b	backward_c_form
Esc d	delete_next_c_form
Esc f	forward_c_form
Ctrl-x Ctrl-c	quit_shell
Ctrl-x g	go_next

4.6 Default mode key bindings.

Esc \177	delete_previous_word
Esc \b	delete_previous_word
Esc b	backward_word
Esc c	capitalize_word
Esc d	delete_next_word
Esc f	forward_word
Esc l	downcase_word
Esc u	upcase_word
Ctrl-x g	go_next

4.7 French mode key bindings.

'	french_accent
^	french_accent
~	french_accent