

# DTD documentation

## 1. Top-level element(s)

- [document](#)
- [howto](#)
- [overview](#)

## 2. List of elements

- [abstract](#)
- [acronym](#)
- [anchor](#)
- [answer](#)
- [audience](#)
- [authors](#)
- [body](#)
- [br](#)
- [caption](#)
- [code](#)
- [dd](#)
- [dl](#)
- [document](#)
- [dt](#)
- [em](#)
- [extension](#)
- [faq](#)
- [faqs](#)
- [feedback](#)
- [figure](#)
- [fixme](#)
- [footer](#)
- [fork](#)
- [header](#)
- [howto](#)
- [icon](#)
- [img](#)

- [jump](#)
- [last-modified-content-date](#)
- [legal](#)
- [li](#)
- [link](#)
- [note](#)
- [notice](#)
- [ol](#)
- [overview](#)
- [p](#)
- [part](#)
- [person](#)
- [prerequisites](#)
- [purpose](#)
- [question](#)
- [references](#)
- [section](#)
- [source](#)
- [steps](#)
- [strong](#)
- [sub](#)
- [subtitle](#)
- [sup](#)
- [table](#)
- [td](#)
- [th](#)
- [tips](#)
- [title](#)
- [tr](#)
- [type](#)
- [ul](#)
- [version](#)
- [warning](#)

### 3. Element declarations

#### 3.1.

person	
Content model	EMPTY

## DTD documentation

Attributes	id	
	xml:lang	
	name	
	email	
Used inside	<a href="#">authors</a>	

### 3.2.

strong		
Content model	( #PCDATA   <a href="#">code</a> ) *	
Attributes	id	
	xml:lang	
Used inside	<a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>	

### 3.3.

em		
Content model	( #PCDATA   <a href="#">code</a> ) *	
Attributes	id	
	xml:lang	
Used inside	<a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>	

--

### 3.4.

code					
Content model	( #PCDATA )				
Attributes	<table border="1"> <tr> <td>id</td> <td></td> </tr> <tr> <td>xml:lang</td> <td></td> </tr> </table>	id		xml:lang	
id					
xml:lang					
Used inside	<a href="#">strong</a>   <a href="#">em</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>				

### 3.5.

sup					
Content model	( #PCDATA )				
Attributes	<table border="1"> <tr> <td>id</td> <td></td> </tr> <tr> <td>xml:lang</td> <td></td> </tr> </table>	id		xml:lang	
id					
xml:lang					
Used inside	<a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>				

### 3.6.

sub					
Content model	( #PCDATA )				
Attributes	<table border="1"> <tr> <td>id</td> <td></td> </tr> <tr> <td>xml:lang</td> <td></td> </tr> </table>	id		xml:lang	
id					
xml:lang					

## DTD documentation

Used inside	<a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">title</a>   <a href="#">subtitle</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>

### 3.7.

link											
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a> ) *										
Attributes	<table border="1"><tr><td>id</td><td></td></tr><tr><td>xml:lang</td><td></td></tr><tr><td>href</td><td></td></tr><tr><td>role</td><td></td></tr><tr><td>title</td><td></td></tr></table>	id		xml:lang		href		role		title	
id											
xml:lang											
href											
role											
title											
Used inside	<a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>										

### 3.8.

jump											
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a> ) *										
Attributes	<table border="1"><tr><td>id</td><td></td></tr><tr><td>xml:lang</td><td></td></tr><tr><td>href</td><td></td></tr><tr><td>role</td><td></td></tr><tr><td>title</td><td></td></tr></table>	id		xml:lang		href		role		title	
id											
xml:lang											
href											
role											
title											

Used inside	<a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>

### 3.9.

fork											
Content model	( <a href="#">#PCDATA</a>   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a> ) *										
Attributes	<table border="1"> <tr> <td>id</td> <td></td> </tr> <tr> <td>xml:lang</td> <td></td> </tr> <tr> <td>href</td> <td></td> </tr> <tr> <td>role</td> <td></td> </tr> <tr> <td>title</td> <td></td> </tr> </table>	id		xml:lang		href		role		title	
id											
xml:lang											
href											
role											
title											
Used inside	<a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>										

### 3.10.

br					
Content model	EMPTY				
Attributes	<table border="1"> <tr> <td>id</td> <td></td> </tr> <tr> <td>xml:lang</td> <td></td> </tr> </table>	id		xml:lang	
id					
xml:lang					
Used inside	<a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>				

### 3.11.

img	
Content model	EMPTY
Attributes	
	src
	alt
	height
	width
	usemap
	ismap
	id
	xml:lang
Used inside	<a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>

### 3.12.

icon	
Content model	EMPTY
Attributes	
	src
	alt
	height
	width

	id	
	xml:lang	
Used inside	<a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>	

### 3.13.

acronym		
Content model	(#PCDATA)*	
Attributes	title	
	id	
	xml:lang	
Used inside	<a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">caption</a>   <a href="#">th</a>   <a href="#">td</a>   <a href="#">li</a>   <a href="#">dt</a>   <a href="#">dd</a>   <a href="#">notice</a>   <a href="#">abstract</a>   <a href="#">legal</a>   <a href="#">question</a>	

### 3.14.

p		
Content model	(#PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *	
Attributes	id	
	xml:lang	
	xml:space	

Used inside	<a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>

### 3.15.

source	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *
Attributes	id
	xml:lang
	xml:space
Used inside	<a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>

### 3.16.

note	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *
Attributes	id
	xml:lang
Used inside	<a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>

### 3.17.

warning					
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *				
Attributes	<table border="1"> <tr> <td>id</td> <td></td> </tr> <tr> <td>xml:lang</td> <td></td> </tr> </table>	id		xml:lang	
id					
xml:lang					
Used inside	<a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>				

### 3.18.

fixme							
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *						
Attributes	<table border="1"> <tr> <td>author</td> <td></td> </tr> <tr> <td>id</td> <td></td> </tr> <tr> <td>xml:lang</td> <td></td> </tr> </table>	author		id		xml:lang	
author							
id							
xml:lang							
Used inside	<a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>						

### 3.19.

table	
Content model	( <a href="#">caption</a> ? , <a href="#">tr</a> + )

Attributes	id
	xml:lang
Used inside	<a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>

### 3.20.

caption	
Content model	( <a href="#">#PCDATA</a>   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *
Attributes	id
	xml:lang
Used inside	<a href="#">table</a>

### 3.21.

tr	
Content model	( <a href="#">th</a>   <a href="#">td</a> ) +
Attributes	id
	xml:lang
Used inside	<a href="#">table</a>

### 3.22.

th	
----	--

Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *	
Attributes	id	
	xml:lang	
	colspan	
	rowspan	
Used inside	<a href="#">tr</a>	

### 3.23.

td		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *	
Attributes	id	
	xml:lang	
	colspan	
	rowspan	
Used inside	<a href="#">tr</a>	

### 3.24.

li		
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a> )	

	)*	
Attributes	id	
	xml:lang	
Used inside	<a href="#">ul</a>   <a href="#">ol</a>	

### 3.25.

ul		
Content model	( <a href="#">li</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a> ) +	
Attributes	id	
	xml:lang	
	spacing	
Used inside	<a href="#">li</a>   <a href="#">ul</a>   <a href="#">ol</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>	

### 3.26.

ol		
Content model	( <a href="#">li</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a> ) +	
Attributes	id	
	xml:lang	
	spacing	

Used inside	<a href="#">li</a>   <a href="#">ul</a>   <a href="#">ol</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>

### 3.27.

dl					
Content model	( <a href="#">dt</a> , <a href="#">dd</a> ) +				
Attributes	<table border="1"> <tr> <td>id</td> <td></td> </tr> <tr> <td>xml:lang</td> <td></td> </tr> </table>	id		xml:lang	
id					
xml:lang					
Used inside	<a href="#">li</a>   <a href="#">ul</a>   <a href="#">ol</a>   <a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>				

### 3.28.

dt					
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *				
Attributes	<table border="1"> <tr> <td>id</td> <td></td> </tr> <tr> <td>xml:lang</td> <td></td> </tr> </table>	id		xml:lang	
id					
xml:lang					
Used inside	<a href="#">dl</a>				

### 3.29.

dd	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *

Attributes	id
	xml:lang
Used inside	<a href="#">dl</a>

### 3.30.

figure	
Content model	EMPTY
Attributes	src
	alt
	height
	width
	usemap
	ismap
	id
	xml:lang
Used inside	<a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>

### 3.31.

anchor	
Content model	EMPTY
Attributes	id

	xml:lang
Used inside	<a href="#">body</a>   <a href="#">section</a>   <a href="#">answer</a>   <a href="#">overview</a>   <a href="#">purpose</a>   <a href="#">prerequisites</a>   <a href="#">audience</a>   <a href="#">steps</a>   <a href="#">extension</a>   <a href="#">tips</a>   <a href="#">references</a>   <a href="#">feedback</a>

### 3.32.

document	
Content model	( <a href="#">header</a> , <a href="#">body</a> , <a href="#">footer</a> ? )
Attributes	id xml:lang

### 3.33.

header	
Content model	( <a href="#">title</a> , <a href="#">subtitle</a> ? , <a href="#">version</a> ? , <a href="#">type</a> ? , <a href="#">authors</a> ? , <a href="#">notice</a> * , <a href="#">abstract</a> ? , <a href="#">last-modified-content-date</a> )
Attributes	id xml:lang
Used inside	<a href="#">document</a>   <a href="#">howto</a>

### 3.34.

title	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a> ) *
Attributes	id

	xml:lang
Used inside	<a href="#">header</a>   <a href="#">section</a>   <a href="#">part</a>

### 3.35.

subtitle					
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a> ) *				
Attributes	<table border="1"> <tr> <td>id</td> <td></td> </tr> <tr> <td>xml:lang</td> <td></td> </tr> </table>	id		xml:lang	
id					
xml:lang					
Used inside	<a href="#">header</a>				

### 3.36.

version													
Content model	( #PCDATA )												
Attributes	<table border="1"> <tr> <td>id</td> <td></td> </tr> <tr> <td>xml:lang</td> <td></td> </tr> <tr> <td>major</td> <td></td> </tr> <tr> <td>minor</td> <td></td> </tr> <tr> <td>fix</td> <td></td> </tr> <tr> <td>tag</td> <td></td> </tr> </table>	id		xml:lang		major		minor		fix		tag	
id													
xml:lang													
major													
minor													
fix													
tag													
Used inside	<a href="#">header</a>												

### 3.37.

type	
Content model	( #PCDATA )
Attributes	
	id
	xml:lang
Used inside	
	<a href="#">header</a>

### 3.38.

authors	
Content model	( <a href="#">person</a> + )
Attributes	
	id
	xml:lang
Used inside	
	<a href="#">header</a>   <a href="#">faqs</a>

### 3.39.

notice	
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *
Attributes	
	id
	xml:lang
Used inside	
	<a href="#">header</a>

--

### 3.40.

abstract					
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *				
Attributes	<table border="1"> <tr> <td>id</td> <td> </td> </tr> <tr> <td>xml:lang</td> <td> </td> </tr> </table>	id		xml:lang	
id					
xml:lang					
Used inside	<a href="#">header</a>				

### 3.41.

body					
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) +				
Attributes	<table border="1"> <tr> <td>id</td> <td> </td> </tr> <tr> <td>xml:lang</td> <td> </td> </tr> </table>	id		xml:lang	
id					
xml:lang					
Used inside	<a href="#">document</a>				

### 3.42.

section					
Content model	( <a href="#">title</a> , ( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) * )				
Attributes	<table border="1"> <tr> <td>id</td> <td> </td> </tr> <tr> <td>xml:lang</td> <td> </td> </tr> </table>	id		xml:lang	
id					
xml:lang					

Used inside	<a href="#">body</a>   <a href="#">section</a>   <a href="#">prerequisites</a>   <a href="#">steps</a>   <a href="#">tips</a>   <a href="#">references</a>

### 3.43.

footer	
Content model	( <a href="#">legal</a> )
Used inside	<a href="#">document</a>

### 3.44.

legal					
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *				
Attributes	<table border="1"> <tr> <td>id</td> <td></td> </tr> <tr> <td>xml:lang</td> <td></td> </tr> </table>	id		xml:lang	
id					
xml:lang					
Used inside	<a href="#">footer</a>				

### 3.45.

faqs							
Content model	( <a href="#">authors</a> ? , ( <a href="#">faq</a>   <a href="#">part</a> ) + )						
Attributes	<table border="1"> <tr> <td>id</td> <td></td> </tr> <tr> <td>xml:lang</td> <td></td> </tr> <tr> <td>title</td> <td></td> </tr> </table>	id		xml:lang		title	
id							
xml:lang							
title							

Used inside	<a href="#">howto</a>

### 3.46.

part					
Content model	( <a href="#">title</a> , ( <a href="#">faq</a>   <a href="#">part</a> ) + )				
Attributes	<table border="1"> <tr> <td>id</td> <td></td> </tr> <tr> <td>xml:lang</td> <td></td> </tr> </table>	id		xml:lang	
id					
xml:lang					
Used inside	<a href="#">faqs</a>   <a href="#">part</a>				

### 3.47.

faq					
Content model	( <a href="#">question</a> , <a href="#">answer</a> )				
Attributes	<table border="1"> <tr> <td>id</td> <td></td> </tr> <tr> <td>xml:lang</td> <td></td> </tr> </table>	id		xml:lang	
id					
xml:lang					
Used inside	<a href="#">faqs</a>   <a href="#">part</a>				

### 3.48.

question					
Content model	( #PCDATA   <a href="#">strong</a>   <a href="#">em</a>   <a href="#">code</a>   <a href="#">sub</a>   <a href="#">sup</a>   <a href="#">br</a>   <a href="#">img</a>   <a href="#">icon</a>   <a href="#">acronym</a>   <a href="#">link</a>   <a href="#">jump</a>   <a href="#">fork</a> ) *				
Attributes	<table border="1"> <tr> <td>id</td> <td></td> </tr> <tr> <td>xml:lang</td> <td></td> </tr> </table>	id		xml:lang	
id					
xml:lang					

Used inside	<a href="#">faq</a>

### 3.49.

answer			
Content model	( <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *		
Attributes	<table border="1"> <tr> <td>author</td> <td> </td> </tr> </table>	author	
author			
Used inside	<a href="#">faq</a>		

### 3.50.

howto					
Content model	( <a href="#">header</a> , <a href="#">audience</a> ? , <a href="#">purpose</a> ? , <a href="#">prerequisites</a> ? , <a href="#">steps</a> , <a href="#">extension</a> ? , <a href="#">faqs</a> ? , <a href="#">tips</a> ? , <a href="#">references</a> ? , <a href="#">feedback</a> ? )				
Attributes	<table border="1"> <tr> <td>id</td> <td> </td> </tr> <tr> <td>xml:lang</td> <td> </td> </tr> </table>	id		xml:lang	
id					
xml:lang					

### 3.51.

overview							
Content model	( <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *						
Attributes	<table border="1"> <tr> <td>title</td> <td> </td> </tr> <tr> <td>id</td> <td> </td> </tr> <tr> <td>xml:lang</td> <td> </td> </tr> </table>	title		id		xml:lang	
title							
id							
xml:lang							

### 3.52.

purpose	
Content model	( <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	title
	id
	xml:lang
Used inside	<a href="#">howto</a>

### 3.53.

prerequisites	
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	title
	id
	xml:lang
Used inside	<a href="#">howto</a>

### 3.54.

audience	
Content model	( <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *

Attributes	title	
	id	
	xml:lang	
Used inside	<a href="#">howto</a>	

### 3.55.

steps		
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *	
Attributes	title	
	id	
	xml:lang	
Used inside	<a href="#">howto</a>	

### 3.56.

extension		
Content model	( <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *	
Attributes	title	
	id	
	xml:lang	

Used inside	<a href="#">howto</a>

### 3.57.

tips	
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	title
	id
	xml:lang
Used inside	<a href="#">howto</a>

### 3.58.

references	
Content model	( <a href="#">section</a>   <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *
Attributes	title
	id
	xml:lang
Used inside	<a href="#">howto</a>

### 3.59.

feedback
----------

Content model	( <a href="#">p</a>   <a href="#">source</a>   <a href="#">note</a>   <a href="#">warning</a>   <a href="#">fixme</a>   <a href="#">table</a>   <a href="#">ol</a>   <a href="#">ul</a>   <a href="#">dl</a>   <a href="#">figure</a>   <a href="#">anchor</a> ) *	
Attributes	title	
	id	
	xml:lang	
Used inside	<a href="#">howto</a>	

### 3.60.

last-modified-content-date		
Content model	EMPTY	
Attributes	date	
Used inside	<a href="#">header</a>	