

---

# The xmltool command-line utility

Hussein Shafie, Pixware <xmleditor-support@xmlmind.com>

October 28, 2010

## Abstract

This document is the reference manual of the **xmltool** command-line utility. This utility, like all the other command-line utilities, is found in `XXE_install_dir/bin/`.

1. Synopsis .....	1
2. validate options .....	2
3. indent options .....	2
4. schematron options .....	5
5. schemadoc options .....	5
6. Common options .....	6
A. Implementation limits .....	7
1. Limitations related to XML Schema Datatypes .....	7
2. Limitations related to XML Schema Structures .....	7
3. Limitations related to DTD support .....	10

## 1. Synopsis

Usage:

```
xmltool validate|indent|schematron|schemadoc ?options? arguments
```

The **xmltool** utility comprises 4 different processors:

validate [2]

Checks the validity of a document conforming to a DTD, W3C XML Schema or RELAX NG schema.

May also be used to check the validity of a DTD, W3C XML Schema or RELAX NG schema.

indent [2]

Saves one or more documents after reformatting their XML contents.

May be also used to *flatten* these documents, that is, to transclude XInclude elements or DITA conrefs.

schematron [5]

Checks the validity of a document against a Schematron schema.

May also be used to check the validity of a Schematron schema.

schemadoc [5]

Generates a reference manual in HTML format for a DTD, W3C XML Schema or RELAX NG schema.

The generated HTML reference manual, organized like "*DocBook: The Definitive Guide*" by Norman Walsh and al., lists all the elements and attributes specified in the schema.

This manual is intended to help content authors create instances conforming to a given schema. This manual is not intended to help schema authors document their design.

Note that, for now, this documentation generator cannot extract documentation contained in a schema (i.e. in annotation/documentation elements) and merge extracted documentation with automatically generated documentation.

## 2. **validate** options

Usage:

```
xmltool validate validate_options common_options [6] [6] [ xml_file ]*
```

Validates specified XML files. If no XML files are specified, it is the schemas specified using the "-s" option which are validated.

-s *schema*

Use specified schema file to validate all specified XML files.

*schema* must be a DTD having a ".dtd" extension or a W3C XML Schema having a ".xsd", ".xs", ".wxs" extension or a RELAX NG schema having a ".rng", ".rnc" (compact syntax) extension.

By default, the schema used for validation is found in each specified XML file (e.g. <!DOCTYPE>).

It is possible to specify several "-s" options:

- When no XML files are specified, each schema is individually validated.
- When several XML files are specified, the schemas are composed to form a compound schema (e.g. DocBook 5+MathML) and this compound schema is used to validate specified XML files.

-f

When validating a document, ignore false duplicate ID errors caused by multiple inclusions of the same element. When saving a document, replace such false duplicate IDs by automatically generated ones.

Example: Validate docbook-image.xml against the DTD specified in its <!DOCTYPE>.

```
/opt/xxe/demo$ xmltool validate docbook-image.xml
```

Example: Validate docbook-table.xml and docbook-image.xml against the DocBook 4.5 DTD.

```
/opt/xxe/demo$ xmltool validate -s ../addon/config/docbook/dtd/V4.5/docbookx.dtd \  
docbook-table.xml docbook-image.xml
```

Example: Validate the DocBook 4.5 DTD.

```
/opt/xxe/demo$ xmltool validate -s ../addon/config/docbook/dtd/V4.5/docbookx.dtd
```

Example: Validate sample.xml against the combined docbook.rng and mathml2.rng RELAX NG schemas.

```
/opt/xxe/addon/mathml_config/db5mml$ xmltool validate \  
-s ../../config/docbook5/rng/V5.0/docbook.rng \  
-s rng/mathml2.rng \  
sample.xml
```

Note that the combined schemas don't need to be of the same kind:

```
/opt/xxe/addon/mathml_config/db5mml$ xmltool validate \  
-s ../../config/docbook5/rng/V5.0/docbook.rng \  
-s ../standalone/xsd/mathml2.xsd \  
sample.xml
```

## 3. **indent** options

Usage:

```
xmltool indent indent_options validate_options [2] common_options [6] [ xml_file ]*
```

Save, possibly indenting and/or flattening<sup>1</sup>, specified XML files.

---

<sup>1</sup>That is, transclude references.

**-o** *save\_file\_or\_dir*

Specifies where to save all specified documents.

If a single document is to be saved, *save\_file\_or\_dir* may specify a file or an existing directory.

If multiple documents are to be saved, *save\_file\_or\_dir* must specify a directory. Such directory is automatically created if it does not already exist.

Default: reuse the original filename of each specified document after renaming this document using a ".BAK" filename.

**-flat**

Do not preserve inclusions. Instead ``flatten" a document.

Default: preserve inclusions.

**-indent** *integer*

Specifies the number of space characters used to indent a child element relatively to its parent element.

- A positive or null value means: indent always.
- Value "-1" means: never indent.
- Any other negative value means indent, but only if the document to be saved has an actual document type. In such case, the number of space characters is:  $(-2 - integer)$ .

Default: -4.

**-maxlinelength** *positive\_integer*

Specifies the maximum line length for elements containing text interspersed with child elements.

Default: 78.

**-noopenlines**

Do not add open lines between the child elements of elements having an ``element-only" content model.

Default: add open lines.

**-nolegacy**

Do no attempt to create an XML file which favors the interoperability with HTML/SGML.

Default: favor interoperability with HTML/SGML.

**-nocharentities**

Do not save characters not supported by the encoding as entity references. Instead, save them as numeric references.

Default: when possible and when needed to, save characters as entity references.

**-specialchars** *list\_of\_chars\_or\_char\_ranges*

Always save specified characters as entity references.

Example: `-specialchars "reg 174 0x00ae 0256 pound:yen 163:165 0xA3:0xA5 0243:0245"`.

No default.

**-cdatasections** *list\_of\_simple\_XPaths*

Save the textual contents of specified elements as CDATA sections.

XHTML example: `-cdatasections "htm:script htm:style"`.

No default.

**-prefix** *prefix namespace*

Associates a prefix to a namespace.

Multiple "-prefix" options are allowed.

This may be needed to allow parsing the XPath argument of the above "-cdatasections" option. Options "-prefix" must precede the "-cdatasections" option.

XHTML example: `-prefix htm http://www.w3.org/1999/xhtml`.

No default.

**-nooriginalprefixes**

Do not use the namespace prefixes originally specified in the document. Instead, generate prefixes.

Default: Reuse the original prefixes as much as possible.

**-nodefaultnamespace**

Do not use the default namespace originally specified in the document.

Default: Reuse the default namespace if any.

**-xmlversion** *1.0|1.1|original*

Specifies the "version" pseudo-attribute of the XML declaration. "original" means: reuse the XML version originally specified in the document.

Default: original.

**-encoding** *java\_supported\_encoding|original*

Specifies which encoding to use when saving a document. "original" means: reuse the encoding originally specified in the "encoding" pseudo-attribute of the XML declaration of the document.

Default: original.

**-standalone** *yes|no|original*

Specifies the "standalone" pseudo-attribute of the XML declaration. "original" means: reuse the "standalone" pseudo-attribute originally specified in the document.

No default: do not add a "standalone" pseudo-attribute to the XML declaration.

**-noinvalid**

Do not save specified documents if any of them is found to have validity errors (even harmless cross-reference errors).

Default: save documents even if some of them are found to be invalid.

Example: Indent `docbook-table.xml` using the default settings. The original `docbook-table.xml` is saved to `docbook-table.xml.BAK`.

```
/opt/xxe/demo$ xmltool indent docbook-table.xml
/opt/xxe/demo$ ls docbook-table.xml*
docbook-table.xml
docbook-table.xml.BAK
```

Example: Indent `docbook-table.xml` using specified settings. Save indented file to `out.xml`.

```
/opt/xxe/demo$ xmltool indent -indent 1 -noopenlines -nolegacy -o out.xml docbook-table.xml
```

Example: Force the indentation of schema-less file `xhtml_strict.xxe`.

```
/opt/xxe/addon/config/xhtml$ xmltool indent -indent 2 -o indented.xxe xhtml_strict.xxe
WARNING: Cannot determine which schema to use for validating "xhtml_strict.xxe".
```

Example: Indent all .xhtml files contained in current directory. Create save files in directory /tmp/out/.

```
/opt/xxe/demo$ xmltool indent -v [7] -encoding Windows-1252 -o /tmp/out *.xhtml
```

Example: Transclude all XInclude elements contained docbook-modular-book.xml (-f [2] is needed otherwise out.xml would contain a number of duplicate ID errors).

```
/opt/xxe/demo$ xmltool indent -xi [6] -f [2] -flat -o out.xml docbook-modular-book.xml
```

## 4. **schematron** options

Usage:

```
xmltool schematron schematron_options common_options [6] schematron [ xml_file ]*
```

Validate specified XML documents against specified Schematron.

Optionally validate the Schematron itself.

Unless the `-iso` option is used, the Schematron may be embedded in another type of XML document (e.g. a DocBook 5 RELAX NG grammar not using the compact syntax).

`-iso`

Fully validate the Schematron as an ISO Schematron schema.

Default: do not validate the Schematron, just load it.

Note that the Schematron loader is very lenient and accepts ISO Schematron as well as Schematron 1.5 schemas.

`-o out_schematron_file`

Save the Schematron to specified file. The written schema is in all cases an ISO Schematron schema using the minimal syntax.

`-phase phase_id`

Specifies the ID of the phase which is to be used for validation. May also be `#ALL` or `#DEFAULT`.

Default: `#DEFAULT`, if any, `#ALL` otherwise.

`-var name value`

Specify overrides for some of the let variables defined in the Schematron.

Note that value must be a valid XPath expression and not a plain string.

Example: Validate docbook.sch as an ISO Schematron schema. Additionally save a copy in /tmp/out.sch.

```
/opt/xxe/addon/config/docbook$ xmltool schematron -iso -o /tmp/out.sch docbook.sch
```

Example: Validate docbook-image.xml against docbook.sch.

```
/opt/xxe/demo$ xmltool schematron ../addon/config/docbook/docbook.sch \
docbook-image.xml
```

Example: Validate docbook-image.xml against docbook.sch, using phase `#ALL`. Pass to the Schematron variable `foo` having XPath string literal "bar" as its value.

```
/opt/xxe/demo$ xmltool schematron -phase '#ALL' -var foo '"bar"' \
../addon/config/docbook/docbook.sch \
docbook-image.xml
```

## 5. **schemadoc** options

Usage:

```
xmltool schemadoc schemadoc_options common_options [6] schema doc_dir
```

Generate in directory *doc\_dir* a reference manual in HTML format for schema file *schema*.

*Schema* must be a DTD having a ".dtd" extension or a W3C XML Schema having a ".xsd", ".xs" or ".wxs" extension or a RELAX NG schema having a ".rng" or ".rnc" (compact syntax) extension.

*doc\_dir* is automatically created if it does not exist.

**-css** *css\_url*

Specifies the URL of the CSS style sheet used for the generated HTML.

Default: generated HTML does not have a `<link rel="stylesheet">`.

**-charset** *encoding*

Specifies the charset used for the generated HTML.

Default: use platform default encoding and generated HTML does not have a `<meta http-equiv="Content-Type">`.

**-xxe**

Generate annotations which are meaningful when using the schema with XMLmind XML Editor.

Example:

```
/opt/xxe/demo$ xmltool schemadoc bugreport/bugreport.xsd /tmp/bugreport_doc
/opt/xxe/demo$ ls /tmp/bugreport_doc
a__6sv96.html
abbr__79rrv.html
...
index.html
...
workaround__jus1.html
```

## 6. Common options

**-xi**

When loading a document, transclude XInclude elements.

Default: XInclude elements are treated as any other element.

This option is equivalent to "`-inclscheme com.xmlmind.xml.xinclude.XIncludeScheme`".

**-inclscheme** *class\_name*

When loading a document, transclude nodes specifying an inclusion directive belonging to specified inclusion scheme.

Default: nodes specifying an inclusion directive are treated as any other node.

Specifying several `-inclscheme` options is permitted. Mixing `-xi` and `-inclscheme` options is permitted.

**-cache** *schema\_cache\_dir*

Specifies the directory to be used as a schema cache. This directory is automatically created if it does not exist.

Default: do not cache schemas.

RELAX NG schemas can be cached only in memory and not on disk.

**-rncencoding** *encoding*

Specifies the encoding used for RELAX NG compact syntax schemas.

Default: do not cache schemas.

-v

Verbose.

Example: Transclude all XInclude elements contained `docbook-modular-book.xml` (`-f [2]` is needed otherwise `out.xml` would contain a number of duplicate ID errors).

```
/opt/xxe/demo$ xmltool indent -xi -f [2] -flat -o out.xml docbook-modular-book.xml
```

Example: Transclude all conref elements contained in `topic1.dita`.

```
/tmp$ xmltool indent -inclscheme "com.xmlmind.xmleditext.dita.ConrefScheme" \
-f -flat -o out.dita topic1.dita
```

Example: Validate `docbook-table.xml`. Cache the DocBook DTD if it is not already cached. If it is already cached, use the cached copy.

```
/opt/xxe/demo$ xmltool validate -cache /tmp/cache docbook-table.xml
/opt/xxe/demo$ ls /tmp/cache
directory.txt
docbookx.ser
```

Example: Validate `mathml.pane` against `pane.rnc`, a RELAX NG schema using the compact syntax, encoded in ISO-8859-1.

```
/opt/xxe/addon/mathml_config/common/pane$ xmltool validate \
-rncencoding ISO-8859-1 -s pane.rnc mathml.pane
```

## A. Implementation limits

### 1. Limitations related to XML Schema Datatypes

Formal reference: XML Schema Part 2: Datatypes.

- A 32-bit signed integer is used rather than an arbitrary precision integer to implement the **length**, **minLength**, **maxLength**, **totalDigits** and **fractionDigits** facets.
- Similarly, the components of the **duration** datatype are implemented using 32-bit integers and double-precision floating-point numbers.
- The **length** facet of datatype **QName** is implemented as the number of characters in the local part of the name (that is, the prefix part is not taken into account by facet **length**).

### 2. Limitations related to XML Schema Structures

Formal reference: XML Schema Part 1: Structures.

Constraints on XML instances which are not checked:

- Entity Name: an attribute value of type **ENTITY** or **ENTITIES** must match the name of an unparsed entity declared in the DTD.

Constraints on XML schemas which are not checked:

- “The {model group} of the model group definition which corresponds to it per XML Representation of Model Group Definition Schema Components (§3.7.2) must be a valid restriction of the {model group} of that model group definition in I, as defined in Particle Valid (Restriction) (§3.9.6).” [src-redefine.6.2.2]

In this case, the implementation simply overwrites the previously defined **group**.

- ``The {attribute uses} and {attribute wildcard} of the attribute group definition which corresponds to it per XML Representation of Attribute Group Definition Schema Components (§3.6.2) must be ·valid restrictions· of the {attribute uses} and {attribute wildcard} of that attribute group definition in I." [src-redefine.7.2.2]

In this case, the implementation simply overwrites the previously defined **attributeGroup**.

- Attribute Group Definition Representation OK. [src-attribute\_group.2] [src-attribute\_group.3] Attribute Group Definition Properties Correct. [ag-props-correct.2] [ag-props-correct.3]

**attributeGroups** are not validated as such. If something is wrong, it is detected when the the **attributeGroup** is actually used.

Example 1: circular references are checked when the **attributeGroup** is actually used.

Example 2: duplicate attribute and several ID attributes in the same **attributeGroup** are checked when the **attributeGroup** is actually used.

- Model Group Definition Representation OK. [mgd-props-correct]

**groups** are not validated as such. If something is wrong, it is detected when the the **group** is actually used.

- Unique Particle Attribution. [cos-nonambig]
- Derivation Valid (Restriction, Simple). [cos-st-restricts.1.3] [cos-st-restricts.2.3.3] [cos-st-restricts.3.3.3]

The implementation allows to add facets not defined by the base type.

- ``It must in principle be possible to derive the complex type definition in two steps, the first an extension and the second a restriction (possibly vacuous), from that type definition among its ancestors whose {base type definition} is the ·ur-type definition·." [cos-ct-extends.1.5]
- ``The {content type} of the {base type definition} must be a simple type definition of which the {content type} is a ·valid restriction· as defined in Derivation Valid (Restriction, Simple) (§3.14.6)." [derivation-ok-restriction.5.1.1]
  - See above the limitations related to Derivation Valid (Restriction, Simple) [cos-st-restricts]
  - In this case, the implementation does not check that the new facet value actually restricts the facet value of the base type.
- ``No element member of the ·key-sequence· of any member of the ·qualified node set· was assessed as ·valid· by reference to an element declaration whose {nillable} is true." [cvc-identity-constraint.4.2.3]

Other specificities:

- The algorithm used to check *Particle Valid (Restriction)* [cos-particle-restrict] is more powerful than the one described in the spec.

Rationale: the schema for schemas is found invalid when the algorithm described in the spec is used.

- `<xs:complexType name="title" mixed="true" />` is mixed, not empty.
- Not being able to load a schema **include**-ed, **import**-ed or **redefine**-ed by another schema is considered to be a fatal error [x-src-include.1] [x-src-import.1] [x-src-redefine.1]. For the spec, it is just a warning.
- A **import** construct must almost always specify a **schemaLocation** [x-src-import].

However, the validation engine supports `xs:import` elements *without* a `schemaLocation` attribute, if an `xs:import` element for the same namespace but this time having a `schemaLocation` attribute has previously been processed.



Example:

```
<xs:import namespace="foo"
           schemaLocation="http://foo.com/schemal.xsd" />

<!-- Later, typically inside an included module. -->
<xs:import namespace="foo" />
```

Note that the other example below will not work because the validation engine cannot guess which of `schemal.xsd` or `schema2.xsd` contains the components to be imported.

```
<xs:import namespace="foo"
           schemaLocation="http://foo.com/schemal.xsd" />

<!-- Later, typically inside an included module. -->
<xs:import namespace="foo"
           schemaLocation="http://foo.com/schema2.xsd" />

<!-- Later, typically inside another included module. -->
<xs:import namespace="foo" />
```

- Identity-constraint definition identities must be unique within an XML Schema [x-c-props-correct].
- A regular expression such as "[a-zA-Z0-9-]" is not supported as is. It must be rewritten like this: "[a-zA-Z0-9\\-]".
- For readability, whitespace may be used in `selector` and `field` XPath expressions. But whitespace is only supported around `|` and not around all tokens as mandated by the W3C recommendation.

That is, it is possible to specify this:

```
<xs:key name="truck1" >
  <xs:selector xpath="." />
  <xs:field xpath="truck/@number | truck/@plate" />
</xs:key>
```

But not this:

```
<xs:key name="truck1" >
  <xs:selector xpath="." />
  <xs:field xpath="truck / @number | truck / @plate" />
</xs:key>
```

- The following *valid* element declaration is not supported.

```
<xs:element name="foo">
  <xs:complexType>
    <xs:sequence>
      <xs:element ref="bar" />
      <xs:element name="bar" form="qualified" type="xs:decimal" /> <!--NOT SUPPORTED-->
    </xs:sequence>
  </xs:complexType>
</xs:element>

<xs:element name="bar" type="xs:decimal" />
```

An *implementation limit* error `x-cos-element-consistent` is reported in that case.

- The following *valid* element declaration is not supported.

```
<xs:element name="foo">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="bar" type="xs:token" />
      <xs:element name="bar" type="xs:token" nillable="true" />
    </xs:sequence>
```

```
</xs:complexType>  
</xs:element>
```

An *implementation limit* error `x-cos-element-consistent` is reported in that case.

### 3. Limitations related to DTD support

Formal reference: Extensible Markup Language (XML) 1.1.

Constraints on XML instances which are not checked:

- Entity Name: an attribute value of type **ENTITY** or **ENTITIES** must match the name of an unparsed entity declared in the DTD.

Constraints on DTDs which are not checked:

- Notation Declared: in an unparsed entity, the name after **NDATA** must match the declared name of a notation.
- Standalone Document Declaration.
- Proper Declaration/PE Nesting.
- Proper Group/PE Nesting.
- Proper Conditional Section/PE Nesting.