

Onyx Manual, Version 4.1.0

Jason Evans

September 8, 2002

Preface

This manual primarily documents the Onyx programming language. However, Onyx is designed to be run either as a stand alone program or as an embeddable interpreter, so the manual also documents different aspects of the implementation that are important when embedding Onyx into another program.

For software distributions, news, and additional project information, see <http://www.canonware.com/>.

Contents

1	Onyx Language Tutorial	1
1.1	Syntax	1
1.2	Data types	2
1.3	Execution	3
1.4	Memory management	3
1.5	Stacks	4
1.5.1	Using stacks as queues	5
1.5.2	Using the operand stack as two stacks	5
1.5.3	Efficiency issues	5
1.6	Dictionaries	5
1.6.1	Efficiency issues	6
1.7	Code organization	6
1.7.1	Procedures	6
1.7.2	Modules	7
1.8	Error handling	7
1.9	Introspection	8
1.10	Threads	9
1.10.1	Implicit synchronization	9
1.10.2	General threading concerns	9
1.11	Optimization	10
1.12	Debugging	10
2	Onyx Language Reference	13
2.1	Objects	13

2.2	Syntax	17
2.3	Stacks	20
2.4	Standard I/O	21
2.5	Interpreter recursion	21
2.6	Error handling	22
2.7	Threads	22
2.7.1	Implicit synchronization	23
2.7.2	Explicit synchronization	24
2.8	Memory management	24
2.9	Dictionary reference	24
2.9.1	currenterror	25
2.9.2	envdict	29
2.9.3	errordict	29
2.9.4	gcdict	30
2.9.5	globaldict	34
2.9.6	onyxdict	34
2.9.7	outputsdict	35
2.9.8	sprintsdict	44
2.9.9	systemdict	52
2.9.10	threaddict	175
2.9.11	threadsdict	177
2.9.12	userdict	177
3	The onyx program	179
3.1	Usage	179
3.1.1	Options	179
3.2	Environment variables	179
3.3	Language differences	179
4	The libonyx library	181
4.1	Compilation	182
4.2	Types	182

4.3	Global variables	182
4.4	Threads	183
4.5	Garbage collection	183
4.6	Exceptions	183
4.7	Integration issues	183
4.7.1	Thread creation	183
4.7.2	Restarted interrupted system calls	184
4.7.3	Signals	184
4.8	Guidelines for writing extensions	184
4.9	API	185
4.10	Classes	188
4.10.1	ch	188
4.10.2	cnd	192
4.10.3	dch	193
4.10.4	mb	196
4.10.5	mem	197
4.10.6	mq	199
4.10.7	mtx	202
4.10.8	nx	203
4.10.9	nx_a	205
4.10.10	nxn	210
4.10.11	nxo	210
4.10.12	nxo_array	213
4.10.13	nxo_boolean	215
4.10.14	nxo_condition	215
4.10.15	nxo_dict	216
4.10.16	nxo_file	218
4.10.17	nxo_fino	225
4.10.18	nxo_hook	225
4.10.19	nxo_integer	227
4.10.20	nxo_mark	228

4.10.21	<code>nxo_mutex</code>	228
4.10.22	<code>nxo_name</code>	229
4.10.23	<code>nxo_no</code>	230
4.10.24	<code>nxo_null</code>	230
4.10.25	<code>nxo_operator</code>	230
4.10.26	<code>nxo_pmark</code>	231
4.10.27	<code>nxo_real</code>	231
4.10.28	<code>nxo_stack</code>	232
4.10.29	<code>nxo_string</code>	237
4.10.30	<code>nxo_thread</code>	239
4.10.31	<code>ql</code>	247
4.10.32	<code>qr</code>	251
4.10.33	<code>qs</code>	254
4.10.34	<code>hd</code>	256
4.10.35	<code>tsd</code>	259
4.10.36	<code>xep</code>	260
4.11	Dictionaries	263
4.11.1	<code>gedict</code>	263
4.11.2	<code>systemdict</code>	263

List of Tables

2.1	Simple and composite types	14
2.2	Interpretation of objects by type and attribute	15
2.3	Evaluation of objects by type and attribute	16
2.4	currenterror summary	25
2.5	errordict summary	29
2.6	gdict summary	31
2.7	onyxdict summary	34
2.8	outputsdict summary	36
2.9	sprintsdict summary	44
2.10	systemdict summary	52
2.11	threaddict summary	176

Chapter 1

Onyx Language Tutorial

This manual includes a comprehensive Onyx Language Reference chapter, which explains the details of what Onyx is. However, that chapter is rather dry, and more importantly, it does not discuss how to best utilize Onyx. This chapter introduces concepts that are important when designing and implementing Onyx programs, though it is not a complete language tutorial. You will need to read the first several sections of Chapter 2 in order to absorb all of the information in this chapter. However, you should be able to read this chapter first, then come back to it and glean additional understanding after having read later chapters.

Onyx is a stack-based language, so although the ideas that are important to program design in other more traditional languages still apply in many cases, there are different ways of approaching certain problems that integrate better with the facilities provided by Onyx. The most obvious example of this is that Onyx programs are more efficient if written to use named variables as little as possible, relying instead on the power of the operand stack. Another example is error handling. It is possible to write procedures that check for every error condition, but Onyx provides a form of exception handling that, if used correctly, can significantly improve code readability and performance.

Accomplished PostScript programmers will find little new in this chapter; Onyx differs from PostScript in the details, but the concepts are very similar. Accomplished Forth programmers will already be comfortable with stack management, but the rest of the chapter discusses concepts that either have no Forth equivalent, or that are significantly different from Forth, as is the case for dictionaries.

1.1 Syntax

Onyx syntax is extremely simple. Code is essentially composed of tokens that are delimited by whitespace or a list of self-delimiting tokens (see Section 2.2 for details). As such, there are very few ways for a syntax error to occur, but typographical mistakes may instead produce other errors. For example, say that a C programmer forgets he is writing Onyx code and types the following at the interactive *onyx* prompt:

```
onyx:0> 1000L { 'Hello\n' print } repeat
```

The intention is to print `Hello` 1000 times, but `1000L` is invalid syntax for an integer, so Onyx creates an executable name object instead, and then tries to execute the name, resulting in the following error:

```
Error $undefined
ostack: ()
dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..2):
0:      1000L
1:      -file-
2:      --start--
```

This is typical of the simple errors encountered when writing Onyx code. The Onyx scanner uses a simple state machine to try to create objects of various types, and when it fails, the input is instead used to create an executable name.

The scanner only deals with a few types (ignoring procedures for the moment): integers, reals, names, and strings. There are many other object types, but none of them are created directly by the scanner.

{ and } are used to delimit procedure bodies, which in actuality are executable arrays. { puts the scanner into deferred execution mode until the matching } is scanned. {} pairs can be nested, so execution is deferred until matching } characters have been scanned for all { characters. Deferred execution means that the scanner creates objects as it scans code, but does not execute any of them. While not a strictly necessary language feature, this greatly simplifies the task of constructing executable arrays, which can then be treated as procedures.

Following are equivalent examples of how a procedure associated with the name `double` can be defined:

```
onyx:0> $double {2 mul} def
onyx:0> $double [ 2 $mul load ] cvx def
```

As mentioned earlier, there are few ways of generating a syntax error, but it is possible. The most common syntax errors are due to unmatched ' and } characters. Generating other syntax errors is left as an exercise for the reader.

1.2 Data types

Onyx includes a rich set of data types. In fact, Onyx code is represented as data, which means that there is a whole range of possibilities when writing Onyx programs that are difficult or impossible with compiled languages such as C. This aspect of Onyx is discussed in Section 1.9.

Onyx is dynamically typed, which means that errors due to object type incompatibilities are detected during program execution. For example, the following code will always run without an error, even though the arguments that would be passed to the **add** operator are invalid.

```
false {
  'a string' [1] add
} {
  'This is always printed' 1 sprint
} ifelse
```

Dynamic typing has advantages in the flexibility that it offers, but it also means that type errors can go undetected in code for long periods of time before the invalid code is executed.

The Onyx type system is not extensible. There is no way to add new types in a program. However, there are techniques that can be combined with the built in types to simulate an extensible type system. For example, dictionaries can be created with, say, a `_type` field that indicates the type of the object:

```
<
    $_type  $fraction
    $num    3
    $den    4
>
```

Logical extensions of this can be used to create object hierarchies with single or multiple inheritance.

1.3 Execution

Onyx code is never compiled, nor is it preprocessed by the interpreter. Onyx code is simply consumed. This has some interesting implications, some of which are not typical of even other interpreted languages:

- If a source file is modified during interpreter execution, the changes may affect the currently running program, usually in unpleasant ways.
- Syntax errors are not discovered until the malformed code is scanned. In order to be sure that there are no syntax errors, a source file must be completely scanned.

In practice, these are only minor inconveniences, but it is important to keep them in mind when developing.

1.4 Memory management

Since Onyx includes an automatic mark and sweep garbage collector, memory management typically requires little thought. There is no risk of leaking memory in such a way that it cannot be freed. However, it is possible to consume large amounts of memory by creating objects, then keeping references to them long after they have outlived their usefulness.

Onyx objects fall into two categories according to type: simple and composite. Simple objects take up no virtual memory of their own; they are embedded into other composite objects. For example, an integer on the operand stack takes up only the space that the stack requires to store it. The same is true of an integer that is stored as an element of an array. Composite objects are composed of references that fit into the same places that an integer is stored, plus additional structures stored elsewhere in virtual memory. There can be multiple references to the same composite object, and as there is a chain of references that makes it possible to reach a composite object, the garbage collector will leave it alone.

It is usually pretty obvious how to remove references to objects. Objects on the operand stack can be popped off. Definitions in the dictionary stack can be undefined. However, there may be situations such as an array that contains references to various objects, and the array cannot be discarded as a whole, but individual elements are no longer needed. The null type is useful for clobbering such references, and

can even be effectively used to clobber portions of procedures, since when a null object is executed it does absolutely nothing. This unique aspect of null objects may not seem significant, but consider that all other objects, when executed, are either pushed onto the execution stack and executed, or pushed onto the operand stack. Doing nothing at all can be useful.

1.5 Stacks

Stacks in Onyx are pretty typical. Objects are implicitly or explicitly pushed onto stacks by operators, and the stack contents can be rearranged and removed. Although stacks are a first class object in Onyx, most Onyx programs are concerned only with the operand stack, often referred to as ostack, which is used as a place to store objects, pass arguments into operators and procedures, and return results.

Onyx is a postfix language, which means that code is written such that operands precede operators. For example, the following code Calculates $5 \times (3 + 4)$ and prints the result:

```
onyx:0> 5 3 4 add mul
onyx:1> 1 sprint
35
onyx:0>
```

There are no parentheses to clarify operator precedence, because precedence is implicit in the code.

Stacks are either written bottom to top on one line, or top to bottom on separate lines, as in the following examples. The example stack contains the numbers 0, 1, and 2, where 0 is the top object and 2 is the bottom object:

```
onyx:0> 2 1 0
onyx:3> ostack 1 sprint
(2 1 0)
onyx:3> pstack
0
1
2
onyx:3>
```

Learning to efficiently (and accurately) manage stacks is a mind-warping process that no amount of reading is likely to impress upon the reader. There are general concepts presented here, but ultimately, the reader will have to write a good bit of code to get a handle on stacks. Even the author of Onyx found himself stumbling over stacks well after Onyx was complete, despite limited exposure to stack-based languages beforehand. The problem seems to be that programmers learn to think in a different way that doesn't exercise the parts of the brain necessary for stack manipulation. Some people might argue that stack manipulation is the job of the compiler. In any case, stack manipulation is an acquired skill that requires practice.

1.5.1 Using stacks as queues

Stacks are implemented such that access to the top or bottom is very efficient, and efficiency decreases linearly, the farther into the stack an operation has to iterate. Since pushing and popping is efficient for both ends of stacks, this means that stacks are suitable for use as queues.

1.5.2 Using the operand stack as two stacks

The ability to efficiently manipulate both ends of the operand stack means that the operand stack can effectively be thought of as two stacks. This can be very useful in situations where more than a handful of objects are being manipulated, and an additional location to temporarily stash objects would be useful. If a program is repeatedly doing large stack rotations, using the bottom of the stack can often help to simplify the code and reduce stack manipulation overhead.

1.5.3 Efficiency issues

Since stacks are stored internally as doubly linked lists, the cost of indexed access to an object on a stack is proportional to its offset from the top or bottom of the stack, depending on the operator being used. Therefore, stacks are not ideal in situations where arbitrary access to an object is a common operation. An array is a better choice for indexed access, and a dictionary is a better choice for keyed access.

Indexed access doesn't just apply to operators like **idup**; operators like **nup** and **roll** are also affected. However, operators such as **rot** are not as heavily impacted, since they only need to index into the stack by the number of positions to rotate.

1.6 Dictionaries

Dictionaries are known by various other names, including hashes and associative arrays. Dictionaries in Onyx associate keys with values. Keys and values can be of any type, but for each dictionary, all keys are unique. For example, the following dictionary cannot exist:

```
<
  42 'Some value'
  42 'Another value'
>
```

To demonstrate this, the following example creates a dictionary with the first key/value pair listed above, then inserts the second key/value pair.

```
onyx:0> <42 'Some value'>
onyx:1> dup 1 sprint
<42 'Some value'>
onyx:1> dup 42 'Another value' put
onyx:1> dup 1 sprint
```

```
<42 'Another value'>  
onyx:1>
```

When the second key/value pair is inserted, it replaces the first pair.

1.6.1 Efficiency issues

Although dictionaries can handle keys of any type, they are optimized to use names as keys. The performance penalty for other key types is slight, but can be exacerbated by the cost of comparison for other types. Name comparison is a constant time operation, but string comparison is not. Therefore, use names rather than strings whenever possible.

1.7 Code organization

As mentioned earlier, Onyx does not have named variables in the same way as many other languages. However, it does have the dictionary stack (dstack), which is dynamically used for name lookups whenever an executable name is interpreted. This section talks about how to effectively manage the namespace provided by dstack.

When the Onyx interpreter is first initialized, there are four dictionaries on dstack:

- userdict
- globaldict
- systemdict
- threaddict

dstack can be manipulated any way the application sees fit, though it is generally dangerous to remove or significantly modify systemdict or threaddict, since there are definitions in those dictionaries that are critical to the correct functioning of the interpreter.

Each thread has its own userdict, which provides a thread-local namespace. globaldict is shared among all threads, so it provides a global namespace. systemdict contains all of the default global definitions, and threaddict contains the default thread-local definitions.

For some applications, it may be desirable to add definitions to systemdict, but care should be taken not to overwrite existing definitions unless you really know what you are doing. In most cases, using globaldict is a better way to go.

1.7.1 Procedures

Named procedures can be created by associating a name in one of the dictionaries on dstack with a procedure. There is nothing magical about this, but some care should be taken in choosing procedure names, and in deciding how to manage the namespace. Onyx uses only lower case letters in the names of its definitions on dstack, so it is easy to avoid namespace collisions by using some other character

in program definitions. There is nothing wrong with using all lowercase letters for names in your programs, though some extra care is warranted when doing so.

An important consideration in program design is determining what belongs in the global namespace. For an example of how Onyx partitions its namespace, look at `gcdict`. There are several operators defined in `gcdict` that are only of interest when manipulating the garbage collector, so those definitions are stashed out of the way. Your program can do the same for definitions that are not of regular interest.

1.7.2 Modules

Onyx provides the infrastructure for loadable modules, which can be implemented in Onyx and/or dynamically loaded machine code (shared libraries). See the **require** and **mrequire** documentation for details on how to load modules.

When writing a module that is meant as a library of additional functionality, some choices have to be made about how to organize the module. Some of the obvious choices for how to organize the loaded definitions are:

- Insert definitions into `globaldict`.
- Create a new dictionary full of definitions, and insert the dictionary into `globaldict` as, say, `foodict`.
- Create a new dictionary full of definitions, and put the dictionary on `dstack` somewhere, such as directly above or below `systemdict`. Note that this can be done by the application manually, so simply creating the dictionary and letting the application insert it where it pleases could be a better choice.
- Insert definitions into `systemdict` (questionable practice).

Depending on the nature of the module, any of the above solutions may be the right choice. There are tradeoffs between convenience and cleanliness that should be carefully weighed.

1.8 Error handling

Onyx includes a powerful generic error handling mechanism that can be extended and customized at several levels. The **throw** procedure is used to throw an error, and virtually every aspect of the error handling machinery can be customized, extended, or replaced, since it is all written in Onyx.

Errors have names, with which error handlers can be associated in `errordict`. `errordict`'s **handleerror** procedure can be modified or replaced. In fact, with some care, an entirely custom `errordict` can be defined, then undefined once it is no longer needed.

Following is the standard idiom for setting up and tearing down custom error handling:

```
# Set up custom error handling...
{
  # Do error-prone stuff...
} stopped {
```

```
# An error occurred.  Do additional cleanup...
} if
# Restore error handling machinery...
```

The possibilities are extensive. However, a word of caution is in order. If you mess something up in the error handling machinery, bad things will happen, and you will have a terrible time debugging the problem. Be careful.

1.9 Introspection

The following code defines a named procedure that calculates factorials.

```
# #n factorial #result
$factorial {
  dup 1 gt {
    # #n-1 factorial
    dup 1 sub factorial
  }{
    # Terminate recursion.
    1
  } ifelse

  mul
} def
```

What this code actually does is create an executable array, which can be examined and modified. The following transcript shows the effects of modifying the code.

```
onyx:0> 3 factorial 1 sprint
6
onyx:0> $factorial load 2 sprint
{dup 1 gt {dup 1 sub factorial} {1} ifelse mul}
onyx:0> $factorial load 4 {1 pstack} put
onyx:0> 3 factorial
1
1
2
3
onyx:1> 1 sprint
6
onyx:0>
```

First 3! is calculated. Then the “else” clause of the ifelse construct is modified to print the stack and 3! is recalculated. As can be seen, the stack is printed during the calculation.

1.10 Threads

The original impetus for Onyx's creation was the need for scalable threading. Onyx's threading is therefore truly powerful, though it comes at a cost. Threading makes asynchronous garbage collection a necessity, which in turn makes many aspects of Onyx's implementation a bit more heavyweight than would be necessary for a single-threaded interpreter.

1.10.1 Implicit synchronization

Onyx provides mechanisms for implicit object synchronization. To see why implicit object synchronization is necessary, consider what happens when two threads concurrently modify `globaldict` (a perfectly legitimate thing to do, by the way). The internals of a dictionary are rather complex, and if two modifications were interleaved, havoc would ensue. Therefore, `globaldict` is implicitly locked. That is a good thing, except that it slows down every access to `globaldict`. In contrast, `userdict` is a per-thread dictionary, so it is not implicitly locked.

Implicit locking for new objects is controlled via **setlocking**, and can be queried via **currentlocking**. Implicit locking is turned off by default when Onyx is started up, so if an application needs to create an object that is shared among threads, it should temporarily turn on implicit locking. For example, the following code creates a stack in `globaldict` that can be used as a simple message queue.

```
currentlocking # Save for later restoration.
true currentlocking

# Push globaldict onto dstack before calling def.
globaldict begin
$queue stack def
end # globaldict

# Restore implicit locking mode.
setlocking
```

For additional details on the mechanics of implicit synchronization, see Section 2.7.1.

1.10.2 General threading concerns

Onyx's basic threading mechanisms are typical of those found in modern threading implementations. One of the aspects of Onyx's threading implementation to be aware of is that since the operating system's threading implementation is used, there are many types of programming errors that can cause undefined behavior. With some effort, it is possible to crash the Onyx interpreter without the use of threads. However, it requires skill and discipline to *not* crash the Onyx interpreter when using threads. This was a conscious design decision for Onyx; doing otherwise would have limited the scalability of threading.

Now prepare for some discouraging pontification on why threaded programming is generally harmful. In the author's experience, the vast majority of developers do not have a solid enough grasp of threading concepts to be seriously engaging in the practice. As a first step to becoming proficient at threaded

programming, much reading and thought are necessary. The next step is to implement several non-trivial threaded programs that are doomed to be complete disasters. After that, it may be possible for a programmer to write threaded programs that do the right thing most of the time. However, even the most skilled developers still will be unable to consistently write code that is free of race conditions, deadlocks, livelocks, locksteps, etc. Finally, there are some developers who, despite being otherwise proficient, will *never* obtain a solid grasp of threaded programming, regardless of how many times the basic concepts are reviewed.

In summary, don't use threads unless there are significant measurable gains in performance or code complexity. Otherwise, threaded programming just is not worth the unavoidable pain that it inflicts.

1.11 Optimization

There are many fine points to optimizing Onyx code, but they can primarily be distilled down to the following simple rules:

- Avoid allocating composite objects, in order to reduce pressure on the garbage collector. This means being very careful about string manipulation in the fast path. The **cat** operator is convenient, but not friendly to the garbage collector.
- Write code with as few objects as possible, to reduce the number of times through the interpreter loop. This means getting very familiar with the stack manipulation operators.
- Use the operand stack rather than named variables.
- Use the **bind** operator for procedure definitions whenever possible, in order to reduce dstack lookups.
- Avoid the **exit**, **stop**, and **quit** operators when possible, since they are implemented via *longjmp()*.

1.12 Debugging

Onyx does not have an integrated interactive debugger per se, because the introspective power of Onyx is adequate for almost all debugging purposes. In cases where it is impractical to interactively debug an application via the main thread, it is possible to launch a thread that listens for connections on a socket (or a fifo pair) and provides an interactive session.

Following is a contrived example of debugging some bad code, interleaved with explanations. The intention is to calculate $1 + 5$.

```

onyx:0> 1 5L add
Error $undefined
ostack: (1)
dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..2):
0:      5L
1:      -file-
2:      --start--

```

```
onyx:2> pstack
5L
1
```

5L is not a number, nor is it defined in dstack. Try replacing 5L with \$five.

```
onyx:2> pop $five resume
Error $typecheck
ostack: (1 $five)
dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..2):
0:      --add--
1:      -file-
2:      --start--
onyx:3> pstack
--add--
$five
1
```

\$five is a literal name, so no errors occur directly due to scanning it. However, the **add** operator expects two numbers, and \$five is not a number. Replace it with 5 and evaluate the operator.

```
onyx:3> nip 5 exch eval
onyx:1> pstack
6
```

The result is as desired. However, we forgot to **resume** after the last error.

```
onyx:1> estack 1 sprint
(--start-- -file- --add-- --ifelse-- --eval-- -array- -file- --estack--)
onyx:1> resume
```

Now the estack contents should be back to normal.

```
onyx:1> estack 1 sprint
(--start-- -file- --estack--)
onyx:1>
```

The above example only demonstrates the flavor of typical interactive debugging, but there is no magic involved in debugging, so your debugging ability should improve automatically as you gain an improved understanding of Onyx.

Chapter 2

Onyx Language Reference

Onyx is a stack-based, threaded, interpreted language. Its closest relative is Adobe PostScript, followed by Forth. Experienced PostScript programmers should find most aspects of Onyx familiar, but there are significant differences that will prevent a knowledgeable PostScript programmer from programming in Onyx without first skimming this chapter. This chapter does not assume specific knowledge of other programming languages, so stands as a definitive reference for Onyx.

Onyx is different from most languages in that it is not compiled, but rather consumed. For example, there are mechanisms for creating the equivalent of named procedures that can be called at a later time, but behind the scenes, the code is actually being interpreted as it is scanned in such a way that an executable object is created. As such, Onyx is not suited for compilation, native or byte code. However, the language syntax is very simple and the scanner/parser is extremely fast. There is also an operator called **bind** that optimizes interpreted code execution to approximately the same performance level as would be expected of a byte code interpreter.

Onyx is implemented as a C library that can be embedded in other programs. Mechanisms are provided for extending the set of operators available. This manual only documents the base language; see application-specific documentation for any language extensions.

Following is a list of basic language features that are discussed in more detail later in this chapter:

- Stack-based. There are no named variables as in procedural languages. Operations are done using various stacks, so Onyx operations are coded in postfix order.
- Threaded. Onyx's threading uses the native POSIX threads implementation of the operating system (or GNU pth, if so configured).
- Interpreted. Onyx code is never compiled, but is instead interpreted as it is encountered.
- Garbage-collected. There is no need to manually track memory allocation, since the interpreter has an integrated automatic mark and sweep garbage collector.

2.1 Objects

An Onyx object has three aspects: type, attribute, and value.

Objects fall into two categories according to type: simple and composite. A simple object takes up no memory of its own; it uses space within a stack, array, or dictionary. A composite object requires space of its own in addition to the space taken up in stacks, arrays, or dictionaries to refer to the composite object. See Table 2.1 for object type classifications.

Simple	Composite
boolean	array
fino	condition
integer	dict
mark	file
name	hook
null	mutex
operator	stack
pmark	string
real	thread

Table 2.1: Simple and composite types

There can be multiple references that refer to the same memory backing composite objects. In most cases, composite objects that refer to the same memory are indistinguishable, but for arrays and strings, composite objects may only be able to access a subset of the total memory backing them. This behavior is described in detail later.

All objects have a literal, executable, or evaluatable attribute associated with them. Composite objects each have their own attribute, even for composite objects that share the same backing memory. Objects are “interpreted” when they are encountered directly by the interpreter. Objects can also be “evaluated”. One of two actions is taken when an object is interpreted or evaluated:

- The object may be treated as code (executed). When executed, an object is pushed onto the execution stack and executed.
- The object may be treated as data. A data object is push onto the operand stack.

Table 2.2 enumerates under what circumstances object interpretation results in execution. Table 2.3 enumerates under what circumstances object evaluation results in execution. Note that executable arrays are the only objects that behave differently when interpreted versus evaluated.

In practice, attributes are only useful for types that can be executed. Attributes are not considered in equality test operations.

array: An array is an ordered sequence of objects of any type. The sequence of objects contained in an array is indexed starting at 0. References to existing arrays may be constructed such that a contiguous subsequence is visible. The following code creates such an array:

```
[0 1 2 3 4]
1 3 getinterval
```

After the code executes, the array left on the operand stack looks like:

```
[1 2 3]
```


Type	Attribute		
	literal	executable	evaluatable
array	data	data	code
boolean	data	data	data
condition	data	data	data
dict	data	data	data
file	data	code	code
fino	data	data	data
hook	data	code	code
integer	data	data	data
mark	data	data	data
mutex	data	data	data
name	data	code	code
null	data	code	code
operator	data	code	code
pmark	data	data	data
real	data	data	data
stack	data	data	data
string	data	code	code
thread	data	data	data

Table 2.2: Interpretation of objects by type and attribute

Executable arrays are in effect procedures. When an array is executed, its elements are sequentially interpreted.

boolean: A boolean can have two values: true or false.

condition: A condition is used for thread synchronization. The standard operations on a condition are to wait and to signal.

dict: A dict (short for dictionary) is a collection of key/value pairs. Other names for dictionaries include “associative array” and “hash”. A key can be of any type, though in most cases, keys are of type name. A value can also be of any type.

file: A file is a handle to an ordered sequence of bytes with a current position. Read and write permissions are set when a file object is created.

When an executable file is executed, it is used as a source of Onyx code. Data are sequentially read from the file and interpreted until the end of the file is reached.

fino: A fino (first in, never out) is used as a stack marker when constructing stacks.

hook: The hook type is not used by the core Onyx language. It can be used by applications that extend the interpreter as a container object. Hooks can be executed, but the results are application dependent.

Each hook has a tag associated with it that can be used by C extension code as a form of type checking. By default, the tag is a null object. In most cases, an application that extends the interpreter using hook objects will set hook tags to be name objects.

integer: An integer is a signed integer in the range -2^{63} to $2^{63} - 1$.

mark: A mark is used as a stack marker for various stack operations.

Type	Attribute		
	literal	executable	evaluatable
array	data	code	code
boolean	data	data	data
condition	data	data	data
dict	data	data	data
file	data	code	code
fino	data	data	data
hook	data	code	code
integer	data	data	data
mark	data	data	data
mutex	data	data	data
name	data	code	code
null	data	code	code
operator	data	code	code
pmark	data	data	data
real	data	data	data
stack	data	data	data
string	data	code	code
thread	data	data	data

Table 2.3: Evaluation of objects by type and attribute

mutex: A mutex is a mutual exclusion lock. Mutexes cannot be acquired recursively, and the application must take care to unlock mutexes before allowing them to be garbage collected (whether during normal program execution or at program termination).

name: A name is a key that uniquely identifies a sequence of characters. Two name objects that correspond to the same sequence of characters can be compared for equality with the same approximate cost as comparing two integers for equality. Names are typically used as keys in dictionaries.

When an executable name is executed, the topmost value in the dictionary stack associated with the name is evaluated.

null: A null has no significance other than its existence. When an executable null is executed, it does nothing. Executable nulls can be useful as place holders that can later be replaced with useful code, or for replacing obsolete code so that the code is no longer executed.

operator: An operator is an operation that is built in to the interpreter. Operators can be executed.

pmark: A pmark is used as a stack marker when creating procedures in deferred execution mode (i.e. procedures that use the `{}` syntax). The application will only encounter pmarks in error conditions, and there is never a reason for an application to explicitly create a pmark.

real: A real is a double precision (64 bit) floating point number.

stack: A stack provides LIFO (last in, first out) access to objects that it contains, as well as some more advanced access methods. An application can create, then manipulate stacks in much the same way that the operand stack can be manipulated.

string: A string is an ordered sequence of 8 bit characters. The bytes contained in an string are indexed starting at 0. References to existing strings may be constructed such that a contiguous subsequence is visible. The following code creates such a string:

```
'abcde'
1 3 getinterval
```

After the code executes, the string left on the operand stack looks like:

```
'bcd'
```

When an executable string is executed, its contents are used as a source of Onyx code.

thread: A thread object serves as a handle for operations such as detaching and joining.

2.2 Syntax

Onyx's syntax is very simple in comparison to most languages. The scanner and parser are implemented as a human-understandable finite state machine (nested C switch statements with a couple of auxiliary variables), which should give the reader an idea of the simplicity of the language syntax.

CRNL (carriage return, newline) pairs are in all important cases converted to newlines during scanning.

The characters #, !, \$, ~, [,], {, }, (,), ' ', <, and > are special. In most cases, any of the special characters and whitespace (space, tab, newline, formfeed, null) terminate any preceding token. All other characters including non-printing characters are considered regular characters.

A comment starts with a # character outside of a string context and extends to the next newline or formfeed.

Procedures are actually executable arrays, but Onyx provides special syntax for declaring procedures. Procedures are delimited by { and }, and can be nested. Normally, the interpreter executes code as it is scanned, but inside of procedure declarations, execution is deferred. Instead of executing a procedure body as it is encountered, the tokens of the procedure body are pushed onto the operand stack until the closing } is encountered, at which time an executable array is constructed from the tokens in the procedure body and pushed onto the operand stack.

A partial grammar specification, using BNF notation (where convenient) is as follows:

<program> ::= <statement>

<statement> ::= <procedure> <statement> | <object> <statement> | ϵ

<procedure> ::= {<statement>}

<object> ::= <integer> | <real> | <name> | <string>

<integer> ::= <dec.integer> | <radix.integer>

<real> ::= <dec.real> | <exp.real>

<name> : Any token that cannot be interpreted as a number or a string is interpreted as an executable name. There are four syntaxes for names: executable, evaluable, literal, and immediately evaluated. Executable and evaluable names are looked up in the dictionary stack and executed (unless execution is deferred). Evaluable names behave the same as executable names, except when being processed by the **bind** operator. Literal names are simply pushed onto the operand stack. Immediately evaluated names are replaced by their values as defined in the dictionary stack, even if execution is deferred. Examples include:

```
foo      # executable
4noth3r  # executable
!bar     # evaluable
$biz     # literal
~baz     # immediately evaluated
```

If the result of an immediately evaluated name is an executable array, the evaluable attribute is set for the array so that when the array is interpreted, it is executed. This allows immediate evaluation to be indiscriminately used without concern for whether the result is an executable array or, say, an executable operator.

<string> ::= “-delimited string. Ticks may be embedded in the string without escaping them, as long as the unescaped ticks are balanced. The following sequences have special meaning when escaped by a \ character:

```
' ' character.
' ' character.
\ \ character.
0 Nul.
n Newline.
r Carriage return.
t Tab.
b Backspace.
f Formfeed.
a Alarm.
e Escape.
x[0-9a-fA-F][0-9a-fA-F] Hex encoding for a byte.
c[a-zA-Z] Control character.
\n (newline) Ignore.
\r\n (carriage return, newline) Ignore.
\ has no special meaning unless followed by a character in the above list.
Examples include:
```

```
' '
'A string.'
'An embedded \n newline.'
'Another embedded
newline.'
'An ignored \
```

```
newline.'  
'Balanced ` and ` are allowed.'  
'Manually escaped ` tick.'  
'Manually escaped ` tick and `balanced unescaped ticks`.'  
'An actual ` backslash.'  
'Another actual ` backslash.'
```

<dec_integer> : Signed integer in the range -2^{63} to $2^{63} - 1$. The sign is optional. Examples include:

```
0  
42  
-365  
+17
```

<radix_integer> : Signed integer with explicit base between 2 and 36, inclusive, in the range -2^{63} to $2^{63} - 1$. Integer digits are composed of decimal numbers and lower or upper case letters. The sign is optional. Examples include:

```
2@101  
16@ff  
16@Ff  
16@FF  
-10@42  
10@42  
+10@42  
9@18  
35@7r3x  
35@7R3x
```

<dec_real> : Double precision floating point number in decimal notation. At least one decimal digit and a decimal point are required. Examples include:

```
0.  
.0  
3.  
.141  
3.141  
42.75  
+3.50  
-5.0
```

<exp_real> : Floating point number in exponential notation. The format is the same as for **<dec_real>**, except that an exponent is appended. The exponent is composed of an “e” or “E”, an optional sign, and a base 10 integer that is limited by the precision of the floating point format (approximately -308 to 307). Examples include:

```
6.022e23  
60.22e22  
6.022e+23  
1.661e-24  
1.661E-24
```

Arrays do not have explicit syntactic support, but the `[` and `]` operators support their construction. Examples of array construction include:

```
[ ]
[0 'A string' 'Another string.' true]
[5
42
false]
```

Dictionaries do not have explicit syntactic support, but the `<` and `>` operators support their construction. Examples of dictionary construction include:

```
<>
<$answer 42 $question 'Who knows' $translate {babelfish} >
```

Stacks do not have explicit syntactic support, but the `(` and `)` operators support their construction. Examples of stack construction include:

```
( )
(1 2 mark 'a')
```

2.3 Stacks

Stacks in Onyx are the core data structure that programs act on. Stacks store objects in a last in, first out (LIFO) order. Onyx includes a number of operators that manipulate stacks.

Each Onyx thread has four program-visible stacks associated with it:

Operand stack (ostack): Most direct object manipulations are done using the operand stack. Operators use the operand stack for inputs and outputs, and code generally uses the operand stack for a place to store objects as they are being manipulated.

Dictionary stack (dstack): The dictionary stack is used for looking up names. Each thread starts with with four dictionaries on its dictionary stack, which are, from top to bottom:

- userdict
- globaldict
- systemdict
- threaddict

The dictionary stack is normally manipulated via the **begin** and **end** operators. The initial dictionaries on the dictionary stack should not generally be removed, since doing so can cause interpreter crashes.

Execution stack (estack): The interpreter uses the execution stack to store objects that are being executed. The application generally does not need to explicitly manipulate the execution stack, but its contents are accessible, mainly for debugging purposes.

Index stack (istack): The interpreter uses the index stack to store execution offsets for arrays that are being executed. There is a one to one correspondence of the elements of the execution stack to the elements of the index stack, even though the elements of the index stack that do not correspond to arrays have no meaning. The index stack does not affect execution, and exists purely to allow useful execution stack traces when errors occur.

The application can also create additional stacks and manipulate them in much the same way as the operand stack can be manipulated.

2.4 Standard I/O

Onyx provides operators to access the standard I/O file objects: **stdin**, **stdout**, and **stderr**. Under normal circumstances, these operators are adequate for all standard I/O operations. However, it may be desirable to replace these files on a per-thread basis. This can be accomplished using **setstdin**, **setstdout**, and **setstderr**. Furthermore, the file objects that are inherited by new threads can be accessed and modified via **gstdin**, **gstdout**, **gstderr**, **setgstdin**, **setgstdout**, and **setgstderr**.

2.5 Interpreter recursion

During typical Onyx interpreter initialization, the **start** operator is executed, which in turn executes a file object corresponding to **stdin**. However, depending on how the interpreter is invoked, the initial execution stack state may differ.

The interpreter can be recursively invoked. For example, if the following code is executed, the **eval** operator recursively invokes the interpreter to interpret the string.

```
`2 2 add' cvx eval
```

The depth of the execution stack directly corresponds to the recursion depth of the interpreter. Execution stack depth is limited in order to catch unbounded recursion.

Onyx converts tail calls in order to prevent unbounded execution stack growth due to tail recursion. For example, the following code does not cause the execution stack to grow:

```
$foo {foo} def  
foo
```

The following code will result in an execution stack overflow:

```
$foo {foo 'filler'} def  
foo
```

2.6 Error handling

The error handling mechanisms in Onyx are simple but flexible. When an error occurs, **throw** is called. An error can have any name, but only the following error names are generated internally by Onyx:

argcheck: Incorrect argument value.

estackoverflow: Maximum interpreter recursion was exceeded.

invalidaccess: Permission error.

invalidexit: The **exit** operator was called outside of any loop. This error is generated as a result of catching an exit, so the execution state for where the error really happened is gone.

invalidfileaccess: Insufficient file permissions.

ioerror: I/O error (read(), write(), etc.).

limitcheck: Value outside of legal range.

neterror: Network error (refused connection, timeout, unreachable net, etc.).

rangecheck: Out of bounds string or array access.

stackunderflow: Not enough objects on stack.

syntaxerror: Scanner syntax error.

typecheck: Incorrect argument type.

undefined: Name not defined in any of the dictionaries on dstack.

undefinedfilename: Bad filename.

undefinedresult: Attempt to divide by 0.

unmatchedfino: No fino on ostack.

unmatchedmark: No mark on ostack.

unregistered: Non-enumerated error.

The Onyx scanner handles syntax errors specially, in that it pushes an executable string onto the operand stack that represents the code that caused the syntax error and records the line and column numbers in `currenterror` before invoking **throw**.

The Onyx scanner also handles immediate name evaluation errors specially, in that it pushes the name that could not be evaluated onto ostack before invoking **throw**.

2.7 Threads

Onyx supports multiple threads of execution by using the operating system's native threading facilities. Along with threads comes the need for methods of synchronization between threads.

2.7.1 Implicit synchronization

Implicit synchronization is a mandatory language feature, since objects such as `globaldict` are implicitly accessed by the interpreter, which makes it impossible to require the user to explicitly handle all synchronization. Onyx provides optional implicit synchronization capabilities for composite objects on an object by object basis. Each thread has a setting which can be accessed via **currentlocking** (initially set to false) and set via **setlocking**. If implicit locking is active, then new objects will be created such that simple accesses are synchronized.

Implicit synchronization can be a source of deadlock, so care must be taken when accessing implicitly locked objects. For example, if two threads copy two implicitly locked strings to the other string, deadlock can result.

```
# Initialization.
$A 'aaaaaa'
$B 'bbbbbb'

...

# In thread A:
A B copy

...

# In thread B:
B A copy
```

The following are descriptions of the implicit locking semantics for each type of composite object:

array: Array copying is protected. Array element modifications are protected, but element reads are not protected.

condition: No implicit locking is done for conditions.

dict: All dict operations are protected.

file: All file operations are protected. There are no potential deadlocks due to implicit file locking.

hook: No implicit locking is done for hooks.

mutex: No implicit locking is done for mutexes.

stack: All stack operations are protected. There are no potential deadlocks due to implicit stack locking. However, there are races in stack copying, such that the results of copying a stack that is concurrently being modified are unpredictable. In addition, removing an object that is being concurrently accessed from a stack is unsafe.

string: String copying is protected. Character access is protected by many operators, but string copying is the only potential cause of deadlock for string access.

thread: Implicit locking is not done for thread operations, since other synchronization is adequate to protect thread objects.

2.7.2 Explicit synchronization

Onyx includes a foundation of mutexes and condition variables, with which all other synchronization primitives can be constructed.

2.8 Memory management

Onyx programs do not need to track memory allocations, since memory reclamation is done implicitly via automatic garbage collection. Onyx uses an atomic mark and sweep garbage collector.

The atomic nature of garbage collection may sound worrisome with regard to performance, but in fact there are tangible benefits and no significant negative impacts for most applications. Total throughput is improved, since minimal locking is necessary. Concurrent garbage collection would impose a significant locking overhead.

On the down side, atomic garbage collection cannot make strong real-time guarantees. However, the garbage collector is very efficient, and for typical applications, garbage collection delays are measured in microseconds up to tens of milliseconds on current hardware as of the year 2000. For interactive applications, anything under about 100 milliseconds is undetectable by the user, so under normal circumstances the user will not notice that garbage collection is happening.

There are three parameters that can be used to control garbage collection:

1. The garbage collector can be turned off for situations where many objects are being created over a short period of time.
2. The garbage collector runs whenever a certain number of bytes of memory have been allocated since the last collection. This threshold can be changed or disabled.
3. If no composite objects have been created for an extended period of time (seconds), the garbage collector will run if any composite objects have been allocated since the last collection. This idle timeout period can be changed or disabled.

There is one situation in which it is possible for garbage to never be collected, despite the garbage collector being properly configured. Suppose that a program creates some objects, the garbage collector runs, then the program enters a code path that clobbers object references, such that the objects could be collected, but no new objects are allocated. In such a situation, neither the allocation inactivity timer (period), nor the object allocation threshold will trigger a collection, and garbage will remain uncollected. In practice this situation is unlikely, and is not a significant problem since the program size is not growing.

Garbage collection is controlled via the `gcdict` dictionary, which is described in Section 2.9.4.

2.9 Dictionary reference

All operators built in to Onyx have corresponding names that are composed entirely of lower case letters (with the exception of syntax-supporting operators like []). In order to avoid any possibility of namespace collisions with names defined by current and future versions of Onyx, use at least one

character that is not a lower case letter in names (for example, capital letters, numbers, underscore, etc.). In practice, namespace collisions usually aren't a problem, even if they happen, since the only effect is that the program-defined definition shadows the built in definition during name lookups.

2.9.1 currenterror

Each thread has its own `currenterror` dictionary, which is used by the error handling machinery to store error state.

Table 2.4: `currenterror` summary

Input(s)	Op/Proc/Var	Output(s)	Description
–	newerror	boolean	Set to true during error handling.
–	errorname	name	Name of most recent error.
–	line	number	Get line number of syntax error.
–	column	number	Get column number of syntax error.
–	ostack	stack	ostack snapshot.
–	dstack	stack	dstack snapshot.
–	estack	stack	estack snapshot.
–	istack	stack	istack snapshot.

– `column integer`:

Input(s): None.

Output(s):

integer: Column number, valid only if the error was a `syntaxerror`. Column numbering starts at 0.

Errors(s): None.

Description: Get the column number that a `syntaxerror` occurred on.

Example(s):

```
onyx:0> '1 2 3}' cvx eval
At line 1, column 5: Error $syntaxerror
ostack: (1 2 3 '}' )
dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..3):
0:      '1 2 3}'
1:      --eval--
2:      -file-
3:      --start--
onyx:5> currenterror $column get 1 sprint
5
onyx:5>
```

– `dstack stack`:

Input(s): None.

Output(s):

stack: A `dstack` snapshot.

Errors(s): None.

Description: Get a stack that is a dstack snapshot as of the most recent error.

Example(s):

```
onyx:0> x
Error $undefined
ostack: ( )
dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..2):
0:      x
1:      -file-
2:      --start--
onyx:1> currenterror begin dstack end 1 sprint
(-dict- -dict- -dict- -dict-)
onyx:1>
```

- errorname *name*:

Input(s): None.

Output(s):

name: Name of the most recent error.

Errors(s): None.

Description: Get the name of the most recent error.

Example(s):

```
onyx:0> x
Error $undefined
ostack: ( )
dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..2):
0:      x
1:      -file-
2:      --start--
onyx:1> currenterror begin errorname end 1 sprint
$undefined
onyx:1>
```

- estack *stack*:

Input(s): None.

Output(s):

stack: An estack snapshot.

Errors(s): None.

Description: Get a stack that is an estack snapshot as of the most recent error.

Example(s):

```
onyx:0> x
Error $undefined
ostack: ( )
dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..2):
0:      x
1:      -file-
```

```

2:      --start--
onyx:1> currenterror begin estack end 1 sprint
(--start-- -file- x)
onyx:1>

```

- istack *stack*:**Input(s):** None.**Output(s):****stack:** An istack snapshot.**Errors(s):** None.**Description:** Get a stack that is an istack snapshot as of the most recent error.**Example(s):**

```

onyx:0> x
Error $undefined
ostack: ()
dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..2):
0:      x
1:      -file-
2:      --start--
onyx:1> currenterror begin istack end 1 sprint
(0 0 0)
onyx:1>

```

- newerror *boolean*:**Input(s):** None.**Output(s):****boolean:** False if there has been no error since the last time newerror was reset; true otherwise.**Errors(s):** None.**Description:** Get a boolean that represents whether there has been an error since the last time newerror was set to false (as during interpreter initialization). It is the application's responsibility to reset newerror after each error if it expects the value to be useful across multiple errors.**Example(s):**

```

onyx:0> currenterror begin
onyx:0> newerror 1 sprint
false
onyx:0> x
Error $undefined
ostack: ()
dstack: (-dict- -dict- -dict- -dict- -dict-)
estack/istack trace (0..2):
0:      x
1:      -file-
2:      --start--
onyx:1> newerror 1 sprint
true
onyx:1> $newerror false def

```

```

onyx:1> newerror 1 sprint
false
onyx:1> resume
onyx:1> y
Error $undefined
ostack: (x)
dstack: (-dict- -dict- -dict- -dict- -dict-)
estack/istack trace (0..2):
0:      y
1:      -file-
2:      --start--
onyx:2> newerror 1 sprint
true
onyx:2>

```

– line *integer*:

Input(s): None.

Output(s):

integer: Line number, valid only if the error was a syntaxerror. Line numbering starts at 1.

Errors(s): None.

Description: Get the line number that a syntaxerror occurred on.

Example(s):

```

onyx:0> '1 2 3}' cvx eval
At line 1, column 5: Error $syntaxerror
ostack: (1 2 3 '}')
dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..3):
0:      '1 2 3}'
1:      --eval--
2:      -file-
3:      --start--
onyx:5> currenterror $line get 1 sprint
1
onyx:5>

```

– ostack *stack*:

Input(s): None.

Output(s):

stack: An ostack snapshot.

Errors(s): None.

Description: Get a stack that is an ostack snapshot as of the most recent error.

Example(s):

```

onyx:0> x
Error $undefined
ostack: ()
dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..2):
0:      x

```

```

1:      -file-
2:      --start--
onyx:1> currenterror begin ostack end 1 sprint
()
onyx:1>

```

2.9.2 envdict

The envdict dictionary contains keys of type name and values of type string that correspond to the environment passed into the program. All threads share the same envdict, which is implicitly locked. Modifications to envdict should be made via the **setenv** and **unsetenv** operators. If envdict is modified directly, the changes will not be visible to programs such as *ps*.

2.9.3 errordict

Each thread has its own errordict, which is used by default by the error handling machinery.

Table 2.5: errordict summary

Input(s)	Op/Proc/Var	Output(s)	Description
–	handleerror	–	Print a state dump.
–	stop	–	Last operation during error handling.

– handleerror –:

Input(s): None.

Output(s): None.

Errors(s): Under normal conditions, no errors occur. However, it is possible for the application to corrupt the error handling machinery to the point that an error will occur. If that happens, the result is possible infinite recursion, and program crashes are a real possibility.

Description: Print a dump of the most recent error recorded in the currenterror dictionary.

Example(s):

```

onyx:0> {true {true 1 sprint x y} if} eval
true
Error $undefined
ostack: ()
dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..5):
0:      x
1:  {
      true
      1
      sprint
3:-->  x
      y
}

```

```

2:      --if--
3:      --eval--
4:      -file-
5:      --start--
onyx:1> errordict begin handleerror end
Error $undefined
ostack: ()
dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..5):
0:      x
1:  {
        true
        1
        sprint
    3:--> x
        y
    }
2:      --if--
3:      --eval--
4:      -file-
5:      --start--
onyx:1>

```

- stop -:

Input(s): None.

Output(s): None.

Errors(s): None.

Description: This is called as the very last operation when an error occurs. Initially, its value is the same as that for the **stop** operator in systemdict.

Example(s):

```

onyx:0> errordict begin
onyx:0> $stop {'Custom stop\n' print flush quit} def
onyx:0> x
Error $undefined
ostack: ()
dstack: (-dict- -dict- -dict- -dict- -dict-)
estack/istack trace (0..2):
0:      x
1:      -file-
2:      --start--
Custom stop

```

2.9.4 gcdict

The gcdict dictionary provides garbage collection control and status capabilities.

Table 2.6: gdict summary by functional group

Input(s)	Op/Proc/Var	Output(s)	Description
Control operators			
–	collect	–	Force a garbage collection.
boolean	setactive	–	Set whether the garbage collector is active.
seconds	setperiod	–	Set the inactivity period before the garbage collector will run.
count	setthreshold	–	Set the number of bytes of memory allocation that will trigger a garbage collection.
State and statistics operators			
–	active	boolean	Get whether the garbage collector is active.
–	period	seconds	Get the inactivity period before the garbage collector will run.
–	threshold	count	Get the number of bytes of memory allocation that will trigger a garbage collection.
–	stats	array	Get garbage collection statistics.

– active *boolean*:**Input(s):** None.**Output(s):****boolean:** If true, the garbage collector is active; otherwise it is not active.**Errors(s):** None.**Description:** Get whether the garbage collector is active.**Example(s):**

```
onyx:0> gdict begin active end 1 sprint
false
```

– collect –:**Input(s):** None.**Output(s):** None.**Errors(s):** None.**Description:** Force a garbage collection.**Example(s):**

```
onyx:0> gdict begin collect end
onyx:0>
```

– period *seconds*:**Input(s):** None.**Output(s):****seconds:** The minimum number of seconds since the last object allocation that the garbage collector will wait before doing a garbage collection. 0 is treated specially to mean forever.**Errors(s):** None.

Description: Get the minimum number of seconds of object allocation inactivity that the garbage collector will wait before doing a garbage collection. This setting is disjoint from the threshold setting, and does not prevent garbage collection due to the threshold having been reached.

Example(s):

```
onyx:0> gcdict begin period end 1 sprint
60
onyx:0>
```

boolean setactive -:

Input(s):

boolean: If true (initial setting), activate the garbage collector; otherwise deactivate the garbage collector.

Output(s): None.

Errors(s):

stackunderflow.
typecheck.

Description: Set whether the garbage collector is active. This setting takes effect asynchronously, so it is possible for the garbage collector to run even after it has been deactivated. This setting overrides the allocation inactivity period and allocation threshold settings, so that if this setting is set to false, the other settings have no effect.

Example(s):

```
onyx:0> gcdict begin false setactive end
onyx:0>
```

seconds setperiod -:

Input(s):

seconds: The minimum number of seconds since the last object allocation that the garbage collector will wait before doing a garbage collection. 0 is treated specially to mean forever.

Output(s): None.

Errors(s):

stackunderflow.
typecheck.
limitcheck.

Description: Set the minimum number of seconds of object allocation inactivity that the garbage collector will wait before doing a garbage collection. This setting is disjoint from the threshold setting, and does not prevent garbage collection due to the threshold having been reached.

Example(s):

```
onyx:0> gcdict begin 60 setperiod end
onyx:0>
```

count setthreshold -:

Input(s):

count: Number of bytes of memory allocation since the last garbage collection that will trigger a garbage collection. 0 is treated specially to mean infinity.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

limitcheck.

Description: Set the number of bytes of memory allocation since the last garbage collection that will trigger a garbage collection. This setting is disjoint from the inactivity period setting, and does not prevent garbage collection due to the allocation inactivity period having been exceeded.

Example(s):

```
onyx:0> gcdict begin 40000 setthreshold end
onyx:0>
```

– **stats array:**

Input(s): None.

Output(s):

array: An array with the format [collections count [ccount cmark csweep] [mcount mmark msweep] [scount smark ssweep]], where the fields have the following meanings:

collections: Total number of collections the garbage collector has performed.

count: Current number of bytes of memory allocated.

ccount: Number of bytes of memory allocated as of the end of the most recent garbage collection.

cmark: Number of microseconds taken by the most recent garbage collection mark phase.

csweep: Number of microseconds taken by the most recent garbage collection sweep phase.

mcount: Largest number of bytes of memory ever allocated at any point in time.

mmark: Maximum number of microseconds taken by any garbage collection mark phase.

msweep: Number of microseconds taken by any garbage collection sweep phase.

scount: Total number of bytes of memory ever allocated.

smark: Total number of microseconds taken by all garbage collection mark phases.

ssweep: Total number of microseconds taken by all garbage collection sweep phases.

Errors(s): None.

Description: Get statistics about the garbage collector.

Example(s):

```
onyx:0> gcdict begin
onyx:0> stats 2 sprint
[23 72673 [72268 754 3467] [4752223 930 36492] [51057886 17448 136807]]
onyx:0>
```

– **threshold count:**

Input(s): None.

Output(s):

count: Number of bytes of memory allocation since the last garbage collection that will trigger a garbage collection. 0 is treated specially to mean infinity.

Errors(s): None.

Description: Get the number of bytes of memory allocation since the last garbage collection that will trigger a garbage collection. This setting is disjoint from the inactivity period setting, and does not prevent garbage collection due to the allocation inactivity period having been exceeded.

Example(s):

```
onyx:0> gcdict begin threshold end 1 sprint
65536
onyx:0>
```

2.9.5 globaldict

All threads share the same globaldict, which is meant as a repository for globally shared objects. globaldict is empty when the Onyx interpreter is initialized, and is implicitly locked.

2.9.6 onyxdict

Various portions of Onyx use the onyxdict dictionary for storage of miscellaneous objects that normally should not be part of the namespace visible to dstack searches.

Table 2.7: onyxdict summary

Input(s)	Op/Proc/Var	Output(s)	Description
–	mpath_post	array	Get path searched by mrequire.
–	mpath_pre	array	Get path searched by mrequire.
–	rpath_post	array	Get path searched by require.
–	rpath_pre	array	Get path searched by require.

– **mpath_post array:**

Input(s): None.

Output(s):

array: An array of strings.

Errors(s): None.

Description: Get an array of strings used by mrequire as prefixes for file searches. The elements of the array are tried in the order listed.

Example(s):

```
onyx:0> onyxdict $mpath_post get 1 sprint
[ '/usr/local/share/onyx-3.0.0/nxm' ]
onyx:0>
```

– **mpath_pre array:**

Input(s): None.

Output(s):

array: An array of strings.

Errors(s): None.

Description: Get an array of strings used by `mrequire` as prefixes for file searches. The elements of the array are tried in the order listed.

Example(s):

```
onyx:0> onyxdict $mpath_pre get 1 sprint
[ ' ' \ '.' ]
onyx:0>
```

– rpath_post array:

Input(s): None.

Output(s):

array: An array of strings.

Errors(s): None.

Description: Get an array of strings used by `require` as prefixes for file searches. The elements of the array are tried in the order listed.

Example(s):

```
onyx:0> onyxdict $rpath_post get 1 sprint
[ '/usr/local/share/onyx-3.0.0/nx' ]
onyx:0>
```

– rpath_pre array:

Input(s): None.

Output(s):

array: An array of strings.

Errors(s): None.

Description: Get an array of strings used by `require` as prefixes for file searches. The elements of the array are tried in the order listed.

Example(s):

```
onyx:0> onyxdict $rpath_pre get 1 sprint
[ ' ' \ '.' ]
onyx:0>
```

2.9.7 outputsdict

The `outputsdict` dictionary is primarily used to support **outputs**, but its contents may be of use to an application that wishes to extend or modify formatted printing.

There is an entry in `outputsdict` for each Onyx type. Each entry renders objects that correspond to its name using optional flags stored in a dictionary. The following flags are supported for all types:

\$n: Maximum length, in bytes. Default: disabled.

\$w: Minimum length, in bytes. Default: disabled.

\$j: Justification. Legal values:

\$l: Left.

\$c: Center.

\$r: Right (default).

\$p: Padding character. Default: ` `.

\$r: Syntactic rendering recursion depth. Default: 1.

The following additional flags are supported for integers:

\$b: Base, from 2 to 36. Default: 10.

\$s: Sign. Legal values:

\$-: Only print sign if output is negative (default).

\$+: Always print sign.

The following additional flags are supported for reals:

\$d: Digits of precision past decimal point. Default: 6.

\$e: Exponential notation, if true. Default: false.

Table 2.8: outputsdict summary

Input(s)	Op/Proc/Var	Output(s)	Description
array flags	arraytype	string	Create formatted string from array.
boolean flags	booleantype	string	Create formatted string from boolean.
condition flags	conditiontype	string	Create formatted string from condition.
dict flags	dicttype	string	Create formatted string from dict.
file flags	filetype	string	Create formatted string from file.
fino flags	finotype	string	Create formatted string from fino.
hook flags	hooktype	string	Create formatted string from hook.
integer flags	integertype	string	Create formatted string from integer.
mark flags	marktype	string	Create formatted string from mark.
mutex flags	mutextype	string	Create formatted string from mutex.
name flags	nametype	string	Create formatted string from name.
null flags	nulltype	string	Create formatted string from null.
operator flags	operatortype	string	Create formatted string from operator.
pmark flags	pmarktype	string	Create formatted string from pmark.
real flags	realttype	string	Create formatted string from real.
stack flags	stacktype	string	Create formatted string from stack.
string flags	stringtype	string	Create formatted string from string.
thread flags	threadtype	string	Create formatted string from thread.

array flags arraytype string:

Input(s):

array: An array object.

flags: Formatting flags.

Output(s):

string: Formatted string representation of *array*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a formatted string representation of *array*.

Example(s):

```
onyx:0> outputsdict begin
onyx:0> [1 [2 3] 4]
onyx:1> dup <$w 9 $p '_' $r 0> arraytype print '\n' print flush
__-array-
onyx:1> dup <$w 9 $p '_' $r 1> arraytype print '\n' print flush
[1 -array- 4]
onyx:1>
```

***boolean flags* booleantype *string*:**

Input(s):

boolean: A boolean object.

flags: Formatting flags.

Output(s):

string: Formatted string representation of *boolean*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a formatted string representation of *boolean*.

Example(s):

```
onyx:0> outputsdict begin
onyx:0> false
onyx:1> dup <$n 3> booleantype print '\n' print flush
fal
onyx:1> dup <$n 7> booleantype print '\n' print flush
false
onyx:1>
```

***condition flags* conditiontype *string*:**

Input(s):

condition: A condition object.

flags: Formatting flags.

Output(s):

string: Formatted string representation of *condition*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a formatted string representation of *condition*.

Example(s):

```
onyx:0> outputsdict begin
onyx:0> condition
```

```

onyx:1> <$w 15 $p '_' $j $c> booleantype print '\n' print flush
__-condition-__
onyx:0>

```

dict flags dicttype string:

Input(s):

dict: A dict object.

flags: Formatting flags.

Output(s):

string: Formatted string representation of *dict*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a formatted string representation of *dict*.

Example(s):

```

onyx:0> outputsdict begin
onyx:0> <$foo 'foo'> <$w 30 $p '.' $j $r> dicttype print '\n' print flush
.....<$foo 'foo'>
onyx:0>

```

file flags filetype string:

Input(s):

file: A file object.

flags: Formatting flags.

Output(s):

string: Formatted string representation of *file*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a formatted string representation of *file*.

Example(s):

```

onyx:0> outputsdict begin
onyx:0> stdin
onyx:1> <$w 30 $p '.' $j $c> filetype print '\n' print flush
.....-file-.....
onyx:0>

```

fino flags finotype string:

Input(s):

fino: A fino object.

flags: Formatting flags.

Output(s):

string: Formatted string representation of *fino*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a formatted string representation of *fino*.

Example(s):

```
onyx:0> outputsdict begin
onyx:0> (
onyx:1> <$w 30 $p `.' $j $c> finotype print '\n' print flush
.....-fino-.....
onyx:0>
```

hook flags hooktype string:

Input(s):

hook: A hook object.

flags: Formatting flags.

Output(s):

string: Formatted string representation of *hook*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a formatted string representation of *hook*.

Example(s): The following example is a bit contrived, since there is no way to create a hook object with a stock onyx interpreter. Therefore, imagine that an operator named taggedhook exists that creates a hook with a tag that is the name “tagged”.

```
onyx:0> outputsdict begin
onyx:0> taggedhook
onyx:1> <$w 30 $p `.' $j $l hooktype print '\n' print flush
=tagged=.....
onyx:0>
```

integer flags integertype string:

Input(s):

integer: An integer object.

flags: Formatting flags.

Output(s):

string: Formatted string representation of *integer*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a formatted string representation of *integer*.

Example(s):

```
onyx:0> outputsdict begin
onyx:0> 42 <$w 6 $p `_' $j $c $s $-> integertype print '\n' print flush
__42__
onyx:0> 42 <$w 6 $p `_' $j $c $s $+> integertype print '\n' print flush
__+42__
onyx:0> `0x' print 42 <$w 6 $p `0' $b 16> integertype print '\n' print flush
0x00002a
onyx:0>
```

mark flags marktype string:**Input(s):**

mark: A mark object.
flags: Formatting flags.

Output(s):

string: Formatted string representation of *mark*.

Errors(s):

stackunderflow.
typecheck.

Description: Create a formatted string representation of *mark*.

Example(s):

```
onyx:0> outputsdict begin
onyx:0> mark
onyx:1> <$w 30 $p \. ' $j $c> marktype print '\n' print flush
.....-mark-.....
onyx:0>
```

mutex flags mutextype string:**Input(s):**

mutex: A mutex object.
flags: Formatting flags.

Output(s):

string: Formatted string representation of *mutex*.

Errors(s):

stackunderflow.
typecheck.

Description: Create a formatted string representation of *mutex*.

Example(s):

```
onyx:0> outputsdict begin
onyx:0> mutex
onyx:1> <$w 30 $p \. ' $j $c> mutextype print '\n' print flush
.....-mutex-.....
onyx:0>
```

name flags nametype string:**Input(s):**

name: A name object.
flags: Formatting flags.

Output(s):

string: Formatted string representation of *name*.

Errors(s):

stackunderflow.
typecheck.

Description: Create a formatted string representation of *name*.

Example(s):

```

onyx:0> outputsdict begin
onyx:0> $foo
onyx:1> <$w 30 $p `.' $j $c> nametype print '\n' print flush
.....$foo.....
onyx:0>

```

null flags nulltype string:**Input(s):****null:** A null object.**flags:** Formatting flags.**Output(s):****string:** Formatted string representation of *null*.**Errors(s):****stackunderflow.****typecheck.****Description:** Create a formatted string representation of *null*.**Example(s):**

```

onyx:0> outputsdict begin
onyx:0> null
onyx:1> <$w 30 $p `.' $j $c> nulltype print '\n' print flush
.....null.....
onyx:0>

```

operator flags operatortype string:**Input(s):****operator:** An operator object.**flags:** Formatting flags.**Output(s):****string:** Formatted string representation of *operator*.**Errors(s):****stackunderflow.****typecheck.****Description:** Create a formatted string representation of *operator*.**Example(s):** The following example shows an operator printed out with two leading and trailing dashes. If the interpreter cannot determine the name associated with an operator, as will be the case for custom operators, the operator will be printed as *-operator-*.

```

onyx:0> outputsdict begin
onyx:0> ~realtime
onyx:1> <$w 30 $p `.' $j $c> operatortype print '\n' print flush
.....--realtime--.....
onyx:0>

```

pmark flags pmarktype string:**Input(s):**

flags: Formatting flags.

Output(s):

string: Formatted string representation of *stack*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a formatted string representation of *stack*.

Example(s):

```
onyx:0> outputsdict begin
onyx:0> (1 (2 3) 4)
onyx:1> dup <$w 9 $p '_' $r 0> stacktype print '\n' print flush
__-stack-
onyx:1> <$w 9 $p '_' $r 1> stacktype print '\n' print flush
(1 -stack- 4)
onyx:0>
```

string flags stringtype string:

Input(s):

string: A string object.

flags: Formatting flags.

Output(s):

string: Formatted string representation of *string*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a formatted string representation of *string*.

Example(s):

```
onyx:0> outputsdict begin
onyx:0> 'A string'
onyx:1> <$w 30 $p '.' $j $c> stringtype print '\n' print flush
.....A string.....
onyx:0>
```

thread flags threadtype string:

Input(s):

thread: A thread object.

flags: Formatting flags.

Output(s):

string: Formatted string representation of *thread*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a formatted string representation of *thread*.

Example(s):

```
onyx:0> outputsdict begin
onyx:0> () {} thread
onyx:1> <$w 30 $p '.' $j $c> threadtype print '\n' print flush
.....-thread-.....
onyx:0>
```

2.9.8 sprintsdict

The sprintsdict dictionary is primarily used to support **sprints**, but its contents may be of use to an application that wishes to extend or modify syntactical printing.

There is an entry in sprintsdict for each Onyx type. If there is a syntactically valid representation for an object and the recursion depth is greater than 0, the corresponding operator creates a string that syntactically represents the object. Otherwise, a string with a non-syntactical representation of the object is created, except for booleans, integers, names, nulls, reals, and strings, for which the results are always syntactical. If the recursion depth is greater than 0, the operators will recursively convert any contained objects.

The implementation of **sprints** is useful in illustrating a useful method of doing type-dependent operations:

```
$sprints {
    1 idup type $sprintsdict load exch get eval
} def
```

Table 2.9: sprintsdict summary

Input(s)	Op/Proc/Var	Output(s)	Description
array depth	arraytype	string	Create syntactical string from array.
boolean depth	booleantype	string	Create syntactical string from boolean.
condition depth	conditiontype	string	Create syntactical string from condition.
dict depth	dicttype	string	Create syntactical string from dict.
file depth	filetype	string	Create syntactical string from file.
fino depth	finotype	string	Create syntactical string from fino.
hook depth	hooktype	string	Create syntactical string from hook.
integer depth	integertype	string	Create syntactical string from integer.
mark depth	marktype	string	Create syntactical string from mark.
mutex depth	mutextype	string	Create syntactical string from mutex.
name depth	nametype	string	Create syntactical string from name.
null depth	nulltype	string	Create syntactical string from null.
operator depth	operatortype	string	Create syntactical string from operator.
pmark depth	pmarktype	string	Create syntactical string from pmark.
real depth	realtype	string	Create syntactical string from real.
stack depth	stacktype	string	Create syntactical string from stack.
string depth	stringtype	string	Create syntactical string from string.
thread depth	threadtype	string	Create syntactical string from thread.

array depth arraytype string:

Input(s):

array: An array object.

depth: Recursion depth.

Output(s):

string: Syntactical string representation of *array*.

Errors(s):**stackunderflow.****typecheck.****Description:** Create a syntactical string representation of *array*.**Example(s):**

```
onyx:0> sprintsdict begin
onyx:0> [1 [2 3] 4]
onyx:1> dup 0 arraytype print '\n' print flush
-array-
onyx:1> dup 1 arraytype print '\n' print flush
[1 -array- 4]
onyx:1> dup 2 arraytype print '\n' print flush
[1 [2 3] 4]
onyx:1>
```

boolean depth booleantype string:**Input(s):****boolean:** A boolean object.**depth:** Recursion depth.**Output(s):****string:** Syntactical string representation of *boolean*.**Errors(s):****stackunderflow.****typecheck.****Description:** Create a syntactical string representation of *boolean*.**Example(s):**

```
onyx:0> sprintsdict begin
onyx:0> true
onyx:1> dup 0 booleantype print '\n' print flush
true
onyx:1>
```

condition depth conditiontype string:**Input(s):****condition:** A condition object.**depth:** Recursion depth.**Output(s):****string:** Syntactical string representation of *condition*.**Errors(s):****stackunderflow.****typecheck.****Description:** Create a syntactical string representation of *condition*.**Example(s):**

```
onyx:0> sprintsdict begin
onyx:0> condition
onyx:1> dup 0 conditiontype print '\n' print flush
```

```
-condition-
onyx:1> dup 1 conditiontype print '\n' print flush
-condition-
onyx:1>
```

dict depth dicttype string:

Input(s):

dict: A dict object.

depth: Recursion depth.

Output(s):

string: Syntactical string representation of *dict*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a syntactical string representation of *dict*.

Example(s):

```
onyx:0> sprintsdict begin
onyx:0> <$a 'a' $subdict <$b 'b'>>
onyx:1> dup 0 dicttype print '\n' print flush
-dict-
onyx:1> dup 1 dicttype print '\n' print flush
<$subdict -dict- $a 'a'>
onyx:1> dup 2 dicttype print '\n' print flush
<$subdict <$b 'b'> $a 'a'>
onyx:1>
```

file depth filetype string:

Input(s):

file: A file object.

depth: Recursion depth.

Output(s):

string: Syntactical string representation of *file*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a syntactical string representation of *file*.

Example(s):

```
onyx:0> sprintsdict begin
onyx:0> stdout
onyx:1> dup 0 filetype print '\n' print flush
-file-
onyx:1> dup 1 filetype print '\n' print flush
-file-
onyx:1>
```

fino depth finotype string:

Input(s):

fino: A fino object.

depth: Recursion depth.

Output(s):

string: Syntactical string representation of *fino*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a syntactical string representation of *fino*.

Example(s):

```
onyx:0> sprintsdict begin
onyx:0> (
onyx:1> dup 0 finotype print '\n' print flush
-fino-
onyx:1> dup 1 finotype print '\n' print flush
-fino-
onyx:1>
```

hook depth hooktype string:

Input(s):

hook: A hook object.

depth: Recursion depth.

Output(s):

string: Syntactical string representation of *hook*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a syntactical string representation of *hook*.

Example(s): The following example is a bit contrived, since there is no way to create a hook object with a stock onyx interpreter. Therefore, imagine that an operator named *taggedhook* exists that creates a hook with a tag that is the name “tagged”, and that an operator named *untaggedhook* exists that creates an untagged hook.

```
onyx:0> sprintsdict begin
onyx:0> taggedhook
onyx:1> dup 0 hooktype print '\n' print flush
=tagged=
onyx:1> 1 hooktype print '\n' print flush
=tagged=
onyx:0> untaggedhook
onyx:1> dup 0 hooktype print '\n' print flush
-hook-
onyx:1> 1 hooktype print '\n' print flush
-hook-
onyx:0>
```

integer depth integertype string:

Input(s):

integer: An integer object.

depth: Recursion depth.

Output(s):

string: Syntactical string representation of *integer*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a syntactical string representation of *integer*.

Example(s):

```
onyx:0> sprintsdict begin
onyx:0> 42
onyx:1> dup 0 integertype print '\n' print flush
42
onyx:1> dup 1 integertype print '\n' print flush
42
onyx:1>
```

mark depth marktype string:

Input(s):

mark: A mark object.

depth: Recursion depth.

Output(s):

string: Syntactical string representation of *mark*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a syntactical string representation of *mark*.

Example(s):

```
onyx:0> sprintsdict begin
onyx:0> mark
onyx:1> dup 0 marktype print '\n' print flush
-mark-
onyx:1> dup 1 marktype print '\n' print flush
-mark-
onyx:1>
```

mutex depth mutextype string:

Input(s):

mutex: A mutex object.

depth: Recursion depth.

Output(s):

string: Syntactical string representation of *mutex*.

Errors(s):

stackunderflow.

typecheck.

Description: Create a syntactical string representation of *mutex*.

Example(s):

```
onyx:0> sprintsdict begin
onyx:0> mutex
onyx:1> dup 0 mutextype print '\n' print flush
-mutex-
onyx:1> dup 1 mutextype print '\n' print flush
-mutex-
onyx:1>
```

name depth nametype string:**Input(s):**

name: A name object.
depth: Recursion depth.

Output(s):

string: Syntactical string representation of *name*.

Errors(s):

stackunderflow.
typecheck.

Description: Create a syntactical string representation of *name*.

Example(s):

```
onyx:0> sprintsdict begin
onyx:0> $foo
onyx:1> dup 0 nametype print '\n' print flush
$foo
onyx:1> dup 1 nametype print '\n' print flush
$foo
onyx:1>
```

null depth nulltype string:**Input(s):**

null: A null object.
depth: Recursion depth.

Output(s):

string: Syntactical string representation of *null*.

Errors(s):

stackunderflow.
typecheck.

Description: Create a syntactical string representation of *null*.

Example(s):

```
onyx:0> sprintsdict begin
onyx:0> null
onyx:1> dup 0 nulltype print '\n' print flush
-null-
onyx:1> dup 1 nulltype print '\n' print flush
-null-
onyx:1>
```

operator depth operatortype string:

Input(s):**operator:** An operator object.**depth:** Recursion depth.**Output(s):****string:** Syntactical string representation of *operator*.**Errors(s):****stackunderflow.****typecheck.****Description:** Create a syntactical string representation of *operator*.**Example(s):** The following example shows an operator printed out with two leading and trailing dashes. If the interpreter cannot determine the name associated with an operator, as will be the case for custom operators, the operator will be printed as *-operator-*.

```

onyx:0> sprintsdict begin
onyx:0> ~realtime
onyx:1> dup 0 operatortype print '\n' print flush
--realtime--
onyx:1> 1 operatortype print '\n' print flush
--realtime--
onyx:0>

```

pmark depth pmarktype string:**Input(s):****pmark:** A pmark object.**depth:** Recursion depth.**Output(s):****string:** Syntactical string representation of *pmark*.**Errors(s):****stackunderflow.****typecheck.****Description:** Create a syntactical string representation of *pmark*.**Example(s):**

```

onyx:0> sprintsdict begin
onyx:0> { ~x
Error $undefined
ostack: (-pmark- $x)
dstack: (-dict- -dict- -dict- -dict- -dict-)
estack/istack trace (0..1):
0:      -file-
1:      --start--
onyx:3> pop pop resume
onyx:1> dup 0 pmarktype print '\n' print flush
-pmark-
onyx:1> dup 1 pmarktype print '\n' print flush
-pmark-
onyx:1>

```

real depth realtype string:**Input(s):****real:** A real object.**depth:** Recursion depth.**Output(s):****string:** Syntactical string representation of *real*.**Errors(s):****stackunderflow.****typecheck.****Description:** Create a syntactical string representation of *real*.**Example(s):**

```
onyx:0> sprintsdict begin
onyx:0> 42.0
onyx:1> dup 0 realtype print '\n' print flush
4.200000e+01
onyx:1> dup 1 realtype print '\n' print flush
4.200000e+01
onyx:1>
```

stack depth stacktype string:**Input(s):****stack:** A stack object.**depth:** Recursion depth.**Output(s):****string:** Syntactical string representation of *stack*.**Errors(s):****stackunderflow.****typecheck.****Description:** Create a syntactical string representation of *stack*.**Example(s):**

```
onyx:0> sprintsdict begin
onyx:0> (1 (2 3) 4)
onyx:1> dup 0 stacktype print '\n' print flush
-stack-
onyx:1> dup 1 stacktype print '\n' print flush
(1 -stack- 4)
onyx:1> dup 2 stacktype print '\n' print flush
(1 (2 3) 4)
onyx:1>
```

string depth stringtype string:**Input(s):****string:** A string object.**depth:** Recursion depth.**Output(s):****string:** Syntactical string representation of *string*.

Errors(s):**stackunderflow.****typecheck.****Description:** Create a syntactical string representation of *string*.**Example(s):**

```

onyx:0> sprintsdict begin
onyx:0> 'abcd'
onyx:1> dup 0 stringtype print '\n' print flush
'abcd'
onyx:1> dup 1 stringtype print '\n' print flush
'abcd'
onyx:1>

```

thread depth threadtype string:**Input(s):****thread:** A thread object.**depth:** Recursion depth.**Output(s):****string:** Syntactical string representation of *thread*.**Errors(s):****stackunderflow.****typecheck.****Description:** Create a syntactical string representation of *thread*.**Example(s):**

```

onyx:0> sprintsdict begin
onyx:0> thread
onyx:1> dup 0 threadtype print '\n' print flush
-thread-
onyx:1> dup 1 threadtype print '\n' print flush
-thread-
onyx:1>

```

2.9.9 systemdict

The systemdict dictionary contains most of the operators that are of general use. Although there are no mechanisms that prevent modification of systemdict, programs should not normally need to modify systemdict, since globaldict provides a place for storing globally shared objects. All threads share the same systemdict, which is implicitly locked.

Table 2.10: systemdict summary by functional group

Input(s)	Op/Proc/Var	Output(s)	Description
Operand stack operators			
–	mark	mark	Create a mark.
,,,obj	aup	obj ,,,	Rotate stack up one position.

Continued on next page...

Table 2.10: *continued*

Input(s)	Op/Proc/Var	Output(s)	Description
obj ,,,	adn	,,,obj	Rotate stack down one position.
–	count	count	Get the number of objects on ostack.
mark ...	counttomark	mark ...count	Get the depth of the topmost mark on ostack.
obj	dup	obj dup	Duplicate an object.
obj ,,,	bdup	obj ,,,dup	Duplicate bottom object.
objects count	ndup	objects objects	Duplicate objects.
obj ... index	idup	obj ... dup	Duplicate object on ostack at index.
... obj ,,,index	ibdup	... obj ,,,dup	Duplicate object on ostack at index from bottom.
a b	tuck	b a b	Tuck duplicate of top object under second object.
a b	under	a a b	Duplicate second object.
a b	over	a b a	Duplicate second object.
a b	exch	b a	Exchange top two objects.
a b c	up	c a b	Roll top three objects up one.
a ... b count	nup	b a ...	Roll count objects up one.
a b c	dn	b c a	Roll top three objects down one.
a ... b count	ndn	... b a	Roll count objects down one.
... amount	rot	...	Rotate stack up by <i>amount</i> .
region count amount	roll	rolled	Roll <i>count</i> objects up by <i>amount</i> .
obj	pop	–	Remove object.
obj ,,,	bpop	,,,	Remove bottom object.
objects count	npop	–	Remove count objects.
objects ... count	nbpop	...	Remove count objects from bottom.
obj ... index	ipop	...	Remove object at index.
... obj ,,,index	ibpop	... ,,,	Remove object at index from bottom.
a b	nip	b	Remove second object.
objects	clear	–	Pop all objects off ostack.
mark ...	cleartomark	–	Remove objects from ostack through topmost mark.
–	ostack	stack	Get a current ostack snapshot.
thread	threadostack	stack	Get a reference to thread's ostack.
Execution, control, and execution stack operators			
obj	eval	–	Evaluate object.

Continued on next page...

Table 2.10: *continued*

Input(s)	Op/Proc/Var	Output(s)	Description
boolean obj	if	–	Conditionally evaluate object.
boolean a b	ifelse	–	Conditionally evaluate one of two objects.
init inc limit proc	for	–	Iterate with a control variable.
count proc	repeat	–	Iterate a set number of times.
cond proc	while	–	Loop while cond is true.
proc cond	until	–	Loop until cond is false.
proc	loop	–	Loop indefinitely.
array proc	foreach	–	Iterate on array elements.
dict proc	foreach	–	Iterate on dictionary key/value pairs.
stack proc	foreach	–	Iterate on stack elements.
string proc	foreach	–	Iterate on string elements.
–	exit	–	Terminate innermost looping context.
file/string	token	false	Scan for a token.
file/string	token	rem obj true	
obj	start	–	Evaluate object.
–	quit	–	Unwind to innermost start context.
obj	stopped	boolean	Evaluate object.
–	stop	–	Unwind to innermost stopped or start context.
name	throw	obj	Throw an error.
–	estack	stack	Get a current estack snapshot.
thread	threadestack	stack	Get a reference to thread's estack.
–	countestack	count	Get current estack depth.
–	istack	stack	Get a current istack snapshot.
thread	threadistack	stack	Get a reference to thread's istack.
status	die	–	Exit program.
path symbol	modload	–	Load a module.
file symbol	mrequire	–	Search for and load a module.
file	require	–	Search for and evaluate a source file.
args	exec	–	Overlay a new program and execute it.
args	forkexec	pid	Fork and exec a new process.

Continued on next page...

Table 2.10: *continued*

Input(s)	Op/Proc/Var	Output(s)	Description
pid	waitpid	status	Wait for a program to terminate.
args	system	status	Execute a program.
–	pid	pid	Get process ID.
–	ppid	pid	Get parent's process ID.
–	uid	uid	Get the process's user ID.
uid	setuid	boolean	Set the process's user ID.
–	euid	uid	Get the process's effective user ID.
uid	seteuid	boolean	Set the process's effective user ID.
–	gid	gid	Get the process's group ID.
gid	setgid	boolean	Set the process's group ID.
–	egid	gid	Get the process's effective group ID.
gid	setegid	boolean	Set the process's effective group ID.
–	realtime	nsecs	Get the number of nanoseconds since the epoch.
nanoseconds	nsleep	–	Nanosleep.
Stack operators			
–	(fino	Begin a stack declaration.
fino objects)	stack	Create a stack.
–	stack	stack	Create a stack.
stack obj	spush	–	Push object onto stack.
stack obj	sbpush	–	Push object onto bottom of stack.
stack	scount	count	Get the number of objects on a stack.
stack	scounttomark	count	Get the depth of the topmost mark on stack.
stack	sdup	–	Duplicate an object.
stack	sbdup	–	Duplicate bottom object.
stack count	sndup	–	Duplicate objects on stack.
stack index	sidup	–	Duplicate object on stack at index.
stack index	sibdup	–	Duplicate object on stack at index from bottom.
stack	stuck	–	Tuck duplicate of top object on stack under next object on stack.
stack	sunder	–	Duplicate second object on stack.
stack	sover	–	Duplicate second object on stack.

Continued on next page...

Table 2.10: *continued*

Input(s)	Op/Proc/Var	Output(s)	Description
stack	sexch	–	Exchange top objects on stack.
stack	sup	–	Roll top three objects on stack up one.
stack count	snup	–	Roll count objects on stack up one.
stack	saup	–	Roll objects on stack up one.
stack	sdn	–	Roll top three objects on stack down one.
stack count	sndn	–	Roll count objects on stack down one.
stack	sadn	–	Roll objects on stack down one.
stack amount	srot	–	Rotate objects on stack up by <i>amount</i> .
stack count amount	sroll	–	Roll objects on stack.
stack	spop	obj	Pop object off stack.
stack	sbpop	obj	Pop object off bottom of stack.
stack count	snpop	array	Pop count objects off stack.
stack count	sbnpop	array	Pop count objects off bottom of stack.
stack index	sipop	obj	Remove object on stack at index.
stack index	sibpop	obj	Remove object on stack at index from bottom.
stack	snip	obj	Remove second object on stack.
stack	sclear	–	Remove all objects on stack.
stack	scleartomark	–	Remove objects from stack down through topmost mark.
(a) (b)	cat	(a b)	Catenate two stacks.
stacks count	ncat	stack	Catenate stacks.
srcstack dststack	copy	dststack	Copy stack contents.
Number (integer, real) and math operators			
a b	add	r	Add a and b.
a	inc	r	Add 1 to a.
a b	sub	r	Subtract b from a.
a	dec	r	Subtract 1 from a.
a b	mul	r	Multiply a and b.
a b	div	r	Divide a by b.
a b	idiv	r	Divide a by b (integers).
a b	mod	r	Mod a by b (integers).
a b	exp	r	Raise a to the power of b.
a	sqrt	r	Square root.

Continued on next page...

Table 2.10: *continued*

Input(s)	Op/Proc/Var	Output(s)	Description
a	ln	r	Natural log.
a	log	r	Base 10 log.
a	abs	r	Get the absolute value of a.
a	neg	r	Get the negative of a.
a	ceiling	r	Integer ceiling of a real.
a	floor	r	Integer floor of a real.
a	round	r	Real rounded to integer.
a	trunc	r	Integer from real with truncated fractional.
a	sin	r	Sine in radians.
a	cos	r	Cosine in radians.
y x	atan	r	Arctangent in radians of y/x .
seed	srand	—	Seed pseudo-random number generator.
—	rand	integer	Get a pseudo-random number.
String operators			
length	string	string	Create a string.
string	length	count	Get string length.
string index	get	integer	Get string element.
string index integer	put	—	Set string element.
string index length	getinterval	substring	Get a string interval.
string index substring	putinterval	—	Copy substring into string.
'a' 'b'	cat	'ab'	Catenate two strings.
strings count	ncat	string	Catenate strings.
srcstring dststring	copy	dstsubstring	Copy string.
obj depth	sprints	string	Create syntactical string from object.
obj flags	outputs	string	Create formatted string from object.
string pattern	search	post pattern pre true	Successfully search for pattern.
string pattern	search	string false	Unsuccessfully search for pattern.
Name operators			
name	length	count	Get name length.
Array operators			
—	argv	args	Get program arguments.
—	[mark	Begin an array declaration.
mark objects]	array	Construct an array.
length	array	array	Create an array.
array	length	count	Get array length.
array index	get	obj	Get array element.
array index obj	put	—	Set array element.

Continued on next page...

Table 2.10: *continued*

Input(s)	Op/Proc/Var	Output(s)	Description
array index length	getinterval	subarray	Get an array interval.
array index subarray	putinterval	–	Copy subarray into array.
[a] [b]	cat	[a b]	Catenate two arrays.
arrays count	ncat	array	Catenate arrays.
srcarray dstarray	copy	dstsubarray	Copy array.
Dictionary and dictionary stack operators			
–	gdict	dict	Get gdict.
–	userdict	dict	Get userdict.
–	globaldict	dict	Get globaldict.
–	systemdict	dict	Get systemdict.
–	onyxdict	dict	Get onyxdict.
–	sprintsdict	dict	Get sprintsdict.
–	outputsdict	dict	Get outputsdict.
–	envdict	dict	Get envdict.
–	threadsdict	dict	Get threadsdict.
key val	setenv	–	Set environment variable.
key	unsetenv	–	Unset environment variable.
–	<	mark	Begin a dictionary declaration.
mark kvpairs	>	dict	Construct a dictionary.
–	dict	dict	Create a dictionary.
dict	begin	–	Pust dict onto dstack.
–	end	–	Pop a dictionary off dstack.
key val	def	–	Define key/value pair.
dict key	undef	–	Undefine key in dict.
key	load	val	Look up a key's value.
dict key	known	boolean	Check for key in dict.
key	where	false	Get topmost dstack dictionary that defines key.
key	where	dict true	
dict	length	count	Get number of dictionary key/value pairs.
dict key	get	value	Get dict value associate with key.
dict key value	put	–	Set dict key/value pair.
srcdict dstdict	copy	dstdict	Copy dictionary contents.
–	currentdict	dict	Get topmost dstack dictionary.
–	dstack	stack	Get dstack snapshot.
thread	threaddstack	stack	Get a reference to thread's dstack.
–	countdstack	count	Get number of stacks on dstack.
File and filesystem operators			

Continued on next page...

Table 2.10: *continued*

Input(s)	Op/Proc/Var	Output(s)	Description
filename flags	open	file	Open a file.
filename flags mode	open	file	Open a file, creation mode specified.
–	pipe	rfile wfile	Create a pipe.
file	close	–	Close file.
file	read	integer boolean	Read from file.
file string	read	substring boolean	
file	readline	string boolean	Read a line from file.
<file dict ...> timeout	poll	[file ...]	Wait for file(s) to change status.
file	bytesavailable	count	Get number of buffered readable bytes.
file	iobuf	count	Get size of I/O buffer.
file count	setiobuf	–	Set size of I/O buffer.
file	nonblocking	boolean	Get non-blocking mode.
file boolean	setnonblocking	–	Set non-blocking mode.
file integer/string	write	false	Write to file.
file integer/string	write	integer/substring true	
string	print	–	Print string to stdout.
obj depth	sprint	–	Syntactically print object to stdout.
obj flags	output	–	Formatted print to stdout.
–	pstack	–	Syntactically print ostack elements.
file	flushfile	–	Flush file buffer.
–	flush	–	Flush stdout buffer.
file length	truncate	–	Truncate file.
file offset	seek	–	Move file position pointer.
file	tell	offset	Get file position pointer offset.
path	mkdir	–	Create a directory.
path mode	mkdir	–	Create a directory, mode specified.
path	mkfifo	–	Create a named pipe.
path mode	mkfifo	–	Create a named pipe, mode specified.
old new	rename	–	Rename a file or directory.
file/filename mode	chmod	–	Change file permissions.
file/filename uid gid	chown	–	Change file owner and group.
filename linkname	link	–	Create a hard link.
filename linkname	symlink	–	Create a symbolic link.
filename	unlink	–	Unlink a file.
path	rmdir	–	Remove an empty directory.
file/filename flag	test	boolean	Test a file.
file/filename	status	dict	Get file information.

Continued on next page...

Table 2.10: *continued*

Input(s)	Op/Proc/Var	Output(s)	Description
linkname	readlink	string	Get symbolic link data.
path proc	dirforeach	–	Iterate on directory entries.
–	pwd	path	Get present working directory.
path	cd	–	Change present working directory.
path	chroot	–	Change root directory.
–	stdin	file	Get thread's stdin.
–	stdout	file	Get thread's stdout.
–	stderr	file	Get thread's stderr.
–	gstdin	file	Get global stdin.
–	gstdout	file	Get global stdout.
–	gstderr	file	Get global stderr.
file	setstdin	–	Set thread's stdin.
file	setstdout	–	Set thread's stdout.
file	setstderr	–	Set thread's stderr.
file	setgstdin	–	Set global stdin.
file	setgstdout	–	Set global stdout.
file	setgstderr	–	Set global stderr.
Socket and networking operators			
family type proto	socket	sock	Create a socket.
family type	socket	sock	Create a socket.
sock addr port	bindsocket	–	Bind socket to address/port.
sock addr	bindsocket	–	Bind socket to address.
sock path	bindsocket	–	Bind socket to port.
sock backlog	listen	–	Listen for socket connections.
sock	listen	–	Listen for socket connections.
sock	accept	sock	Accept a socket connection.
sock addr port	connect	–	Connect a socket.
sock path	connect	–	Connect a socket.
service	serviceport	port	Get port number for service name.
sock	sockname	dict	Get socket information.
sock level optname	sockopt	optval	Get socket option.
sock optname	sockopt	optval	Get socket option.
sock level optname optval	setsockopt	–	Set socket option.
sock optname optval	setsockopt	–	Set socket option.
sock	peername	dict	Get peer socket information.
sock mesg flags	send	nsend	Send a message.
sock mesg	send	count	Send a message.
sock string flags	recv	substring	Receive a message.
sock string	recv	substring	Receive a message.
family type proto	socketpair	sock sock	Create a socket pair.

Continued on next page...

Table 2.10: *continued*

Input(s) family type	Op/Proc/Var	Output(s)	Description
	socketpair	sock sock	Create a socket pair.
Logical and bitwise operators			
a b	lt	boolean	a less than b? (integer/real, string)
a b	le	boolean	a less than or equal to b? (integer/real, string)
a b	eq	boolean	a equal to b? (any type)
a b	ne	boolean	a not equal to b? (any type)
a b	ge	boolean	a greater than or equal to b? (integer/real, string)
a b	gt	boolean	a greater than b? (integer/real, string)
a b	and	r	Logical/bitwise and. (boolean/integer)
a b	or	r	Logical/bitwise or. (boolean/integer)
a b	xor	r	Logical/bitwise exclusive or. (boolean/integer)
a	not	r	Logical/bitwise not. (boolean/integer)
a shift	shift	integer	Bitwise shift.
–	false	false	Return true.
–	true	true	Return false.
Type, conversion, and attribute operators			
obj	type	name	Get object type.
obj	echeck	boolean	Evaluatable?
obj	xcheck	boolean	Executable?
obj	cve	obj	Set evaluatable attribute.
obj	cvx	obj	Set executable attribute.
obj	cvlit	obj	Set literal attribute.
string	cvn	name	Convert string to name.
obj	cvs	string	Convert object to string.
integer radix	cvrs	string	Convert integer to radix string.
real precision	cvds	string	Convert real to decimal string.
real precision	cves	string	Convert real to exponential string.
hook	hooktag	tag	Get hook tag.
Threading and synchronization operators			
stack entry	thread	thread	Create and run a thread.
–	self	thread	Get a thread object for the running thread.
thread	join	–	Wait for thread to exit.
thread	detach	–	Detach thread.

Continued on next page...

Table 2.10: *continued*

Input(s)	Op/Proc/Var	Output(s)	Description
–	yield	–	Voluntarily yield the processor.
–	mutex	mutex	Create a mutex.
mutex proc	monitor	–	Evaluate an object under the protection of a mutex.
mutex	lock	–	Acquire mutex.
mutex	trylock	boolean	Try to acquire mutex.
mutex	unlock	–	Release mutex.
–	condition	condition	Create a condition variable.
condition mutex	wait	–	Wait on condition.
condition mutex timeout	timedwait	boolean	Wait on condition with timeout.
condition	signal	–	Signal a condition waiter.
condition	broadcast	–	Signal all condition waiters.
–	currentlocking	boolean	Get implicit locking mode.
boolean	setlocking	–	Set implicit locking mode.
obj	lcheck	boolean	Implicitly locked?
Miscellaneous operators			
–	product	string	Get the product string.
–	version	string	Get the version string.
proc	bind	proc	Bind names to operators.
–	null	null	Create a null object.

– (*fino*:**Input(s):** None.**Output(s):****fino:** A fino object.**Errors(s):** None.**Description:** Push a fino object onto ostack to denote the bottom of a stack that has not yet been constructed.**Example(s):**

```

onyx:0> (
onyx:1> pstack
-fino-
onyx:1>

```

fino objects*) stack:*Input(s):****fino:** A fino object, usually created by the) operator.**objects:** 0 or more objects.**Output(s):****stack:** A stack object.**Errors(s):**

unmatchedfino.

Description: Create a stack object and move all objects from ostack down to the first fino object to the new stack.

Example(s):

```
onyx:0> ( )
onyx:1> 1 sprint
( )
onyx:0> (1 2
onyx:3> pstack
2
1
-fino-
onyx:3> )
onyx:1> 1 sprint
(1 2)
onyx:0>
```

- < mark:

Input(s): None.

Output(s):

mark: A mark object.

Errors(s): None.

Description: Begin a dictionary declaration. See the **!** operator documentation for more details on dictionary construction.

Example(s):

```
onyx:0> < 1 sprint
-mark-
onyx:0>
```

mark kvpairs > dict:**Input(s):**

mark: A mark object.

kvpairs: Zero or more pairs of non-mark objects, where the first is a key and the second is an associated value.

Output(s):

dict: A dictionary that contains *kvpairs*.

Errors(s):

rangecheck.

unmatchedmark.

Description: Construct a dictionary that contains *kvpairs*.

Example(s):

```
onyx:0> <
onyx:1> $foo 'foo'
onyx:3> $bar 'bar'
onyx:5> $biz 'biz'
onyx:7> $pop ~pop
onyx:9> >
```

```

onyx:1> pstack
<$pop --pop-- $biz 'biz' $bar 'bar' $foo 'foo'>
onyx:1>

```

- [*mark*:

Input(s): None.

Output(s):

mark: A mark object.

Errors(s): None.

Description: Begin an array declaration. See the] operator documentation for more details on array construction.

Example(s):

```

onyx:0> [ 1 sprint
-mark-
onyx:0>

```

mark objects] *array*:

Input(s):

mark: A mark object.

objects: Zero or more non-mark objects.

Output(s):

array: An array that contains *objects*.

Errors(s):

unmatchedmark.

Description: Construct an array that contains all *objects* on ostack down to the first *mark*.

Example(s):

```

onyx:0> mark 1 2 3 ] 1 sprint
[1 2 3]

```

a abs *r*:

Input(s):

a: An integer or real.

Output(s):

r: Absolute value of *a*.

Errors(s):

stackunderflow.

typecheck.

Description: Return the absolute value of *a*.

Example(s):

```

onyx:0> 5 abs 1 sprint
5
onyx:0> -5 abs 1 sprint
5
onyx:0> 3.14 abs 1 sprint
3.140000e+00
onyx:0> -3.14 abs 1 sprint
3.140000e+00
onyx:0>

```

sock* accept *sock*:*Input(s):**

sock: A listening socket.

Output(s):

sock: A socket that is connected to a client.

Errors(s):

argcheck.

invalidfileaccess.

ioerror.

neterror.

stackunderflow.

typecheck.

unregistered.

Description: Accept a connection and create a socket that is connected to a client.

Example(s):

```
onyx:0> $AF_INET $SOCK_STREAM socket
onyx:1> dup 'localhost' 7777 bindsocket
onyx:1> dup listen
onyx:1> dup accept
onyx:2> dup peername 1 sprint
<$family $AF_INET $address 2130706433 $port 33742>
onyx:2>
```

a b* add *r*:*Input(s):**

a: An integer or real.

b: An integer or real.

Output(s):

r: The sum of *a* and *b*.

Errors(s):

stackunderflow.

typecheck.

Description: Return the sum of *a* and *b*.

Example(s):

```
onyx:0> 2 2 add 1 sprint
4
onyx:0> -1 3 add 1 sprint
2
onyx:0> 2.0 3.1 add 1 sprint
5.100000e+00
onyx:0> -1.5 +3e1 add 1 sprint
2.850000e+01
onyx:0>
```

obj*,,, adn,,,*obj*:*Input(s):**

obj: An object.
,,,: Zero or more objects.

Output(s):

,,,: Zero or more objects.
obj: An object.

Errors(s):

stackunderflow.

Description: Rotate stack down one position.

Example(s):

```
onyx:0> 1 2 3 adn pstack
1
3
2
onyx:3>
```

***a b* and *r*:**

Input(s):

a: An integer or boolean.
b: The same type as *a*.

Output(s):

r: If *a* and *b* are integers, their bitwise and, otherwise their logical and.

Errors(s):

stackunderflow.
typecheck.

Description: Return the bitwise and of two integers, or the logical and of two booleans.

Example(s):

```
onyx:0> false true and 1 sprint
false
onyx:0> true true and 1 sprint
true
onyx:0> 5 3 and 1 sprint
1
onyx:0>
```

- argv *args*:

Input(s): None.

Output(s):

args: An array of strings. The first string in *args* is the path of this program, and any additional array elements are the arguments that were passed during invocation.

Errors(s): None.

Description: Get the argument vector that was used to invoke this program.

Example(s):

```
onyx:0> argv 1 sprint
[ '/usr/local/bin/onyx' ]
onyx:0>
```

***length* array *array*:**

Input(s):

length: Non-negative number of array elements.

Output(s):

array: An array of *length* elements.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Create an array of *length* elements. The elements are initialized to null objects.

Example(s):

```
onyx:0> 3 array 1 sprint
[null null null]
onyx:0> 0 array 1 sprint
[]
onyx:0>
```

y x atan r:**Input(s):**

y: An integer or real.

x: An integer or real.

Output(s):

r: Arctangent of y/x in radians.

Errors(s):

stackunderflow.

typecheck.

Description: Return the arctangent of y/x in radians.

Example(s):

```
onyx:0> 1 1 atan 1 sprint
7.853982e-01
onyx:0> 0 1 atan 1 sprint
0.000000e+00
onyx:0> -1.0 0 atan 1 sprint
-1.570796e+00
onyx:0>
```

,,,obj aup obj ,,,:**Input(s):**

,,,: Zero or more objects.

obj: An object.

Output(s):

obj: An object.

,,,: Zero or more objects.

Errors(s):

stackunderflow.

Description: Rotate stack up one position.

Example(s):

```

onyx:0> 1 2 3 aup pstack
2
1
3
onyx:3>

```

obj* ,, bdup *obj* ,,dup:*Input(s):**

obj: An object.
,,: Zero or more objects.

Output(s):

obj: An object.
,,: Zero or more objects.
dup: A duplicate of *obj*.

Errors(s):

stackunderflow.

Description: Create a duplicate of the bottom object on ostack and put it on top of ostack.

Example(s):

```

onyx:0> 1 2 3
onyx:3> bdup pstack
1
3
2
1
onyx:4>

```

dict* begin -:*Input(s):**

dict: A dictionary.

Output(s): None.**Errors(s):**

stackunderflow.
typecheck.

Description: Push *dict* onto dstack, thereby adding its keys to the namespace.

Example(s):

```

onyx:0> <$foo 'foo'> begin
onyx:0> foo 1 sprint
'foo'
onyx:0>

```

proc* bind *proc*:*Input(s):**

proc: A procedure (array). *proc* will be bound even if it is literal, but contained literal arrays will not be recursively bound.

Output(s):

proc: The same procedure as was passed in.

Errors(s):**stackunderflow.****typecheck.**

Description: Recursively bind unbound procedures. Executable names within a procedure are replaced with their values if defined in `dstack`, in any of the following cases:

- The value is a literal object.
- The value is an executable or evaluatable operator.
- The value is an executable or evaluatable hook.
- The value is an executable or evaluatable array.

Binding has a large positive impact on performance, since name lookups are thereafter avoided. However, binding is not done by default because there are situations where it is useful to leave procedures unbound:

- Debugging is easier, since the names associated with objects are still available.
- Behavior is more dynamic. It is possible to replace a definition on `dstack` and have it immediately take effect on unbound procedures. Note however that care must be taken when relying on this, since binding is recursive, and a lack of complete understanding of what procedures reference each other can result in undesired bound procedures. For this reason, it is generally best to make dynamic behavior explicit by using evaluatable names.
- There are situations where a program needs to do some setup before binding a procedure, and providing manual control over when binding happens allows more sophisticated use of binding.

Example(s):

```
onyx:0> {pop sprint {pop sprint}}
onyx:1> dup 2 sprint
{pop sprint {pop sprint}}
onyx:1> bind
onyx:1> dup 2 sprint
{--pop-- _{sprints --print-- '\n' --print-- --flush--}_ {--pop-- -array-}}
```

sock addr port bindsocket -:

sock addr bindsocket -:

sock path bindsocket -:

Input(s):**sock:** A socket.**addr:** An IPv4 address or DNS hostname.**port:** An IPv4 port number. If not specified, the OS chooses a port number.**path:** A filesystem path for a Unix-domain socket.

Output(s): None.

Errors(s):**argcheck.****invalidfileaccess.****neterror.****rangecheck.**

stackunderflow.
typecheck.
unregistered.

Description: Bind an address/port to an IPv4 socket, or a filesystem path to a Unix-domain socket.

Example(s):

```
onyx:0> $AF_INET $SOCK_STREAM socket
onyx:1> dup 'localhost' 7777 bindsocket
onyx:1> dup sockname 1 sprint
<$family $AF_INET $address 2130706433 $port 7777>
onyx:1> close
onyx:0> $AF_LOCAL $SOCK_STREAM socket
onyx:1> dup '/tmp/socket' bindsocket
onyx:1> dup sockname 1 sprint
<$family $AF_LOCAL $path '/tmp/socket'>
onyx:1>
```

obj,,, bpop,,,:

Input(s):

,,,: Zero or more objects.
obj: An object.

Output(s):

,,,: Zero or more objects.

Errors(s):

stackunderflow.

Description: Remove the bottom object from ostack and discard it.

Example(s):

```
onyx:0> 1 2
onyx:2> bpop pstack
2
onyx:1>
```

condition broadcast -:

Input(s):

condition: A condition object.

Output(s): None.

Errors(s):

stackunderflow.
typecheck.

Description: Signal all threads that are waiting on *condition*. If there are no waiters, this operator has no effect.

Example(s):

```
onyx:0> condition mutex dup lock ostack
onyx:3> {dup lock exch broadcast unlock}
onyx:4> thread 3 1 roll
onyx:3> dup 3 1 roll
onyx:4> wait unlock join
onyx:0>
```


file bytesavailable *count*:

Input(s):

file: A file object.

Output(s):

count: Number of buffered readable bytes.

Errors(s):

stackunderflow.

typecheck.

Description: Get the number of buffered readable bytes that can be read without the possibility of blocking.

Example(s):

```
onyx:0> '/tmp/foo' 'w+' open
onyx:1> dup 'Hello\n' write
onyx:1> dup 'Goodbye\n' write
onyx:1> dup 0 seek
onyx:1> dup readline 1 sprint 1 sprint
false
'Hello'
onyx:1> dup bytesavailable 1 sprint
8
onyx:1>
```

[a] *[b]* cat *[a b]*:

(a) *(b)* cat *(a b)*:

'a' *'b'* cat *'ab'*:

Input(s):

a: An array, stack, or string.

b: An array, stack, or string.

Output(s):

ab: The catenation of *a* and *b*.

Errors(s):

stackunderflow.

typecheck.

Description: Catenate two arrays, strings, or stacks.

Example(s):

```
onyx:0> ['a'] ['b'] cat
onyx:1> 1 sprint
['a' 'b']
onyx:0> ('a') ('b') cat
onyx:1> 1 sprint
('a' 'b')
onyx:0> 'a' 'b' cat
onyx:1> 1 sprint
'ab'
onyx:0>
```

path cd -:**Input(s):**

path: A string that represents a filesystem path.

Output(s): None.

Errors(s):

invalidaccess.

ioerror.

stackunderflow.

typecheck.

Description: Change the present working directory to *path*.

Example(s):

```
onyx:0> pwd 1 sprint
`/usr/local`
onyx:0> `bin` cd
onyx:0> pwd 1 sprint
`/usr/local/bin`
onyx:0>
```

a ceiling r:**Input(s):**

a: An integer or real.

Output(s):

r: Integer ceiling of *a*.

Errors(s):

stackunderflow.

typecheck.

Description: Return the integer ceiling of *a*.

Example(s):

```
onyx:0> -1.51 ceiling 1 sprint
-1
onyx:0> -1.49 ceiling 1 sprint
-1
onyx:0> 0 ceiling 1 sprint
0
onyx:0> 1.49 ceiling 1 sprint
2
onyx:0> 1.51 ceiling 1 sprint
2
onyx:0>
```

file/filename mode chmod -:**Input(s):**

file: A file object.

filename: A string that represents a filename.

mode: An integer that represents a Unix file mode.

Output(s): None.

Errors(s):

invalidfileaccess.
ioerror.
rangecheck.
stackunderflow.
typecheck.
unregistered.

Description:**Example(s):**

```
onyx:0> `/tmp/tdir' 8@755 mkdir
onyx:0> `/tmp/tdir' status $mode get 1 sprint
16877
onyx:0> `/tmp/tdir' `r' open
onyx:1> dup 8@555 chmod
onyx:1> `/tmp/tdir' status $mode get 1 sprint
16749
onyx:1>
```

file/filename uid gid chown -:**Input(s):**

file: A file object.
filename: A string that represents a filename.
uid: An integer that represents a user ID.
gid: An integer that represents a group ID.

Output(s): None.**Errors(s):**

invalidfileaccess.
ioerror.
rangecheck.
stackunderflow.
typecheck.
unregistered.

Description: Change the owner and group of a file.**Example(s):**

```
onyx:0> `/tmp/tdir' 8@755 mkdir
onyx:0> `/tmp/tdir' status
onyx:1> dup $uid get 1 sprint
1001
onyx:1> $gid get 1 sprint
0
onyx:0> `/tmp/tdir' 1001 1001 chown
onyx:0> `/tmp/tdir' status
onyx:1> dup $uid get 1 sprint
1001
onyx:1> $gid get 1 sprint
1001
onyx:0>
```

path* chroot -:*Input(s):**

path: A string that represents a filesystem path.

Output(s): None.

Errors(s):

invalidaccess.

ioerror.

stackunderflow.

typecheck.

Description: Change the root directory to *path*. This operator requires super-user privileges.

Example(s):

```
onyx:0> pwd 1 sprint
`/home/jasone/cw/devroot`
onyx:0> `/home/jasone` chroot
onyx:0> pwd 1 sprint
`/cw/devroot`
onyx:0>
```

objects* clear -:*Input(s):**

objects: All objects on ostack.

Output(s): None.

Errors(s): None.

Description: Pop all objects off of ostack.

Example(s):

```
onyx:0> 1 2 3 pstack
3
2
1
onyx:3> clear pstack
onyx:0>
```

mark ... cleartomark* -:*Input(s):**

...: Zero or more objects.

mark: A mark object.

Output(s): None.

Errors(s):

unmatchedmark.

Description: Remove objects from ostack down to and including the topmost mark.

Example(s):

```
onyx:0> 3 mark 1 0 pstack
0
1
-mark-
3
```

```
onyx:4> cleartomark pstack
3
onyx:1>
```

file close -:**Input(s):**

file: A file object.

Output(s): None.

Errors(s):

ioerror.

stackunderflow.

typecheck.

Description: Close a file.

Example(s):

```
onyx:0> `/tmp/foo' `w' open
onyx:1> close
onyx:0>
```

- condition condition:

Input(s): None.

Output(s):

condition: A condition object.

Errors(s): None.

Description: Create a condition object.

Example(s):

```
onyx:0> condition 1 sprint
-condition-
onyx:0>
```

sock addr port connect -:***sock path connect -:*****Input(s):**

sock: A socket.

addr: An IPv4 address or DNS hostname.

port: An IPv4 port number. If not specified, the OS chooses a port number.

path: A filesystem path for a Unix-domain socket.

Output(s): None.

Errors(s):

argcheck.

invalidfileaccess.

neterror.

stackunderflow.

typecheck.

unregistered.

Description: Connect *sock*.

Example(s):

```

onyx:0> $AF_INET $SOCK_STREAM socket
onyx:1> dup 'localhost' 7777 connect
onyx:1>

```

srcarray dstarray copy dstsubarray:

srcdict dstdict copy dstdict:

srcstack dststack copy dststack:

srcstring dststring copy dstsubstring:

Input(s):

srcarray: An array object.
srcdict: A dict object.
srcstack: A stack object.
srcstring: A string object.
dstarray: An array object, at least as long as *srcarray*.
dstdict: A dict object.
dststack: A stack object.
dststring: A string object, at least as long as *srcstring*.

Output(s):

dstsubarray: A subarray of *dstarray*, with the same contents as *srcarray*.
dstdict: The same object as the input *dstdict*, but with the contents of *srcdict* inserted.
dststack: The same object as the input *dststack*, but with the contents of *srcstack* pushed.
dstsubstring: A substring of *dststring*, with the same contents as *srcstring*.

Errors(s):

rangecheck.
stackunderflow.
typecheck.

Description: Copy from one object to another. Array and string copying are destructive; dictionary and stack copying are not.

Example(s):

```

onyx:0> ['a'] ['b' 'c'] copy 1 sprint
['a']
onyx:0> <$foo 'foo'> <$bar 'bar'> copy 1 sprint
<$bar 'bar' $foo 'foo'>
onyx:1> (1 2) (3 4) copy 1 sprint
(3 4 1 2)
onyx:1> 'a' 'bc' copy 1 sprint
'a'
onyx:1>

```

a cos r:**Input(s):**

a: An integer or real.

Output(s):

r: Cosine of *a* in radians.

Errors(s):**stackunderflow.****typecheck.****Description:** Return the cosine of a in radians.**Example(s):**

```
onyx:0> 0 cos 1 sprint
1.000000e+00
onyx:0> 3.14 cos 1 sprint
-9.999987e-01
onyx:0> 3.1415927 cos 1 sprint
-1.000000e+00
onyx:0>
```

– count *count*:**Input(s):** None.**Output(s):****count:** The number of objects on ostack.**Errors(s):** None.**Description:** Get the number of objects on ostack.**Example(s):**

```
onyx:0> 2 1 0 count pstack
3
0
1
2
onyx:4>
```

– countdstack *count*:**Input(s):** None.**Output(s):****count:** Number of dictionaries on dstack.**Errors(s):** None.**Description:** Get the number of dictionaries on dstack.**Example(s):**

```
onyx:0> countdstack 1 sprint
4
onyx:0> dict begin
onyx:0> countdstack 1 sprint
5
onyx:0>
```

– countestack *count*:**Input(s):** None.**Output(s):****count:** The number of objects currently on the execution stack (recursion depth).**Errors(s):** None.**Description:** Get the current number of objects on the execution stack.

Example(s):

```

onyx:0> countestack 1 sprint
3
onyx:0> estack 1 sprint
(--start-- -file- --estack--)
onyx:0>

```

mark ... counttomark mark ... count:**Input(s):**

...: Zero or more objects.

mark: A mark object.

Output(s):

...: *count* objects.

mark: The same mark that was passed in.

count: The depth of *mark* on ostack.

Errors(s):

unmatchedmark.

Description: Get the depth of the topmost mark on ostack.

Example(s):

```

onyx:0> 4 mark 2 1 0 counttomark 1 sprint
3
onyx:5>

```

– currentdict *dict*:

Input(s): None.

Output(s):

dict: Topmost stack on dstack.

Errors(s): None.

Description: Get the topmost dictionary on dstack.

Example(s):

```

onyx:0> <$foo 'foo'> begin
onyx:0> currentdict 1 sprint
<$foo 'foo'>
onyx:0>

```

– currentlocking *boolean*:

Input(s): None.

Output(s):

boolean: If false, new objects are created with implicit locking disabled. Otherwise, new objects are created with implicit locking enabled.

Errors(s): None.

Description: Get the current implicit locking mode. See Section 2.7.1 for implicit synchronization details.

Example(s):

```

onyx:0> currentlocking 1 sprint
false

```



```
onyx:0> true setlocking
onyx:0> currentlocking 1 sprint
true
onyx:0>
```

real precision cvds string:**Input(s):**

real: A real.

precision: Number of digits after the decimal point to show.

Output(s):

string: A string representation of *real* in decimal form with *precision* digits of decimal precision.

Errors(s):

stackunderflow.

typecheck.

Description: Convert *real* to a string representation in decimal notation, with *precision* digits of decimal precision.

Example(s):

```
onyx:0> 42.3 0 cvds 1 sprint
'42'
onyx:0> 42.3 1 cvds 1 sprint
'42.3'
onyx:0> -42.3 4 cvds 1 sprint
'-42.3000'
onyx:0>
```

obj cve obj:**Input(s):**

obj: An object.

Output(s):

obj: The same object that was passed in, but with the evaluable attribute set.

Errors(s):

stackunderflow.

Description: Set the evaluable attribute for *obj*.

Example(s):

```
onyx:0> [1 2 3] cve 1 sprint
_{1 2 3}_
onyx:0>
```

real precision cves string:**Input(s):**

real: A real.

precision: Number of digits after the decimal point to show.

Output(s):

string: A string representation of *real* in exponential form with *precision* digits of decimal precision.

Errors(s):

stackunderflow.

typecheck.

Description: Convert *real* to a string representation in exponential notation, with *precision* digits of decimal precision.

Example(s):

```
onyx:0> 42.3 0 cves 1 sprint
'4e+01'
onyx:0> 42.3 1 cves 1 sprint
'4.2e+01'
onyx:0> 42.3 2 cves 1 sprint
'4.23e+01'
onyx:0> -42.3 5 cves 1 sprint
'-4.23000e+01'
onyx:0>
```

obj cvlit obj:

Input(s):

obj: An object.

Output(s):

obj: The same object that was passed in, but with the literal attribute set.

Errors(s):

stackunderflow.

Description: Set the literal attribute for *obj*.

Example(s):

```
onyx:0> {1 2 3} cvlit 1 sprint
[1 2 3]
onyx:0>
```

string cvn name:

Input(s):

string: A string.

Output(s):

name: A literal name that corresponds to *string*.

Errors(s):

stackunderflow.

typecheck.

Description: Convert *string* to a literal name.

Example(s):

```
onyx:0> 'foo' cvn 1 sprint
$foo
onyx:0>
```

integer radix cvrs string:

Input(s):

integer: An integer.

radix: A numerical base, from 2 to 36, inclusive.

Output(s):

string: A string representation of *integer* in base *radix*.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Convert *integer* to a string representation in base *radix*.

Example(s):

```
onyx:0> 42 2 cvrs 1 sprint
'101010'
onyx:0> 42 16 cvrs 1 sprint
'2a'
onyx:0>
```

obj* cvs *string*:*Input(s):**

obj: An object.

Output(s):

string: A string representation of *obj*. The string depends on the type of *obj*:

boolean: 'true' or 'false'.

name: The string representation of the name.

integer: The integer in base 10.

operator: The string representation of the operator name or '-operator-'.

real: The real in exponential notation.

string: A printable representation of *obj*. The result can be evaluated to produce the original string.

Other types: '--nostringval--'.

Errors(s):

stackunderflow.

Description: Convert *obj* to a string representation.

Example(s):

```
onyx:0> true cvs 1 sprint
'true'
onyx:0> $foo cvs 1 sprint
'foo'
onyx:0> 42 cvs 1 sprint
'42'
onyx:0> ~pop cvs 1 sprint
'pop'
onyx:0> 42.0 cvs 1 sprint
'4.200000e+01'
onyx:0> 'foo\nbar\\biz\'baz' cvs 1 sprint
'\foo\nbar\\\\biz\\\'baz\'\'
onyx:0> mutex cvs 1 sprint
'--nostringval--'
onyx:0>
```

***obj* cvx *obj*:**

Input(s):**obj:** An object.**Output(s):****obj:** The same object that was passed in, but with the executable attribute set.**Errors(s):****stackunderflow.****Description:** Set the executable attribute for *obj*.**Example(s):**

```

onyx:0> [1 2 3] cvx 1 sprint
{1 2 3}
onyx:0>

```

a dec r:**Input(s):****a:** An integer.**Output(s):****r:** $a - 1$.**Errors(s):****stackunderflow.****typecheck.****Description:** Subtract one from *a*.**Example(s):**

```

onyx:0> 1 dec 1 sprint
0
onyx:0>

```

key val def –:**Input(s):****key:** An object.**val:** A value associated with *key*.**Output(s):** None.**Errors(s):****stackunderflow.****Description:** Define *key* with associated value *val* in the topmost dictionary on dstack. If *key* is already defined in that dictionary, the old definition is replaced.**Example(s):**

```

onyx:0> $foo 'foo' def
onyx:0> foo 1 sprint
'foo'
onyx:0> $foo 'FOO' def
onyx:0> foo 1 sprint
'FOO'
onyx:0>

```

thread detach –:**Input(s):**

thread: A thread object.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Detach *thread* so that its resources will be automatically reclaimed after it exits. A thread may only be detached or joined once; any attempt to do so more than once results in undefined behavior (likely crash).

Example(s):

```
onyx:0> (1 2) {add 1 sprint self detach} thread
3
onyx:1>
```

– **dict** *dict*:

Input(s): None.

Output(s):

dict: An empty dictionary.

Errors(s): None.

Description: Create an empty dictionary.

Example(s):

```
onyx:0> dict 1 sprint
<>
onyx:0>
```

status *die* –:

Input(s):

status: A integer from 0 to 255 that is used as the program exit code.

Output(s): None.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Exit the program with exit code *status*.

Example(s):

```
onyx:0> 1 die
```

path *proc* *dirforeach* –:

Input(s):

path: A string that represents a filesystem path.

proc: An object to be executed.

Output(s): None.

Errors(s):

invalidaccess.

ioerror.

stackunderflow.

typecheck.

Description: For each entry in the directory represented by *path* except for “.” and “..”, push a string that represents the entry onto ostack and execute *proc*. This operator supports the **exit** operator.

Example(s):

```
onyx:0> pwd {1 sprint} dirforeach
'CVS'
'.cvsignore'
'Cookfile'
'Cookfile.inc'
'latex'
'Cookfile.inc.in'
onyx:0> pwd {'Cookfile.inc' search
      {pop 'Yes: ' print 1 sprint pop exit}
      {'Not: ' print 1 sprint} ifelse
} dirforeach
Not: 'CVS'
Not: '.cvsignore'
Not: 'Cookfile'
Yes: 'Cookfile.inc'
onyx:0>
```

a b div r:**Input(s):**

- a:** An integer or real.
- b:** A non-zero integer or real.

Output(s):

- r:** The quotient of *a* divided by *b*.

Errors(s):

- stackunderflow.**
- typecheck.**
- undefinedresult.**

Description: Return the quotient of *a* divided by *b*.

Example(s):

```
onyx:0> 4 2 div 1 sprint
2.000000e+00
onyx:0> 5 2.0 div 1 sprint
2.500000e+00
onyx:0> 5.0 0 div
Error $undefinedresult
ostack: (5.000000e+00 0)
dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..2):
0:      --div--
1:      -file-
2:      --start--
onyx:3>
```

a b c dn b c a:

Input(s):**a:** An object.**b:** An object.**c:** An object.**Output(s):****b:** An object.**c:** An object.**a:** An object.**Errors(s):****stackunderflow.****Description:** Rotate the top three objects on ostack down one position.**Example(s):**

```

onyx:0> 'a' 'b' 'c' 'd' dn pstack
'b'
'd'
'c'
'a'
onyx:4>

```

– dstack *stack*:**Input(s):** None.**Output(s):****stack:** A snapshot of dstack.**Errors(s):** None.**Description:** Get a snapshot of dstack.**Example(s):**

```

onyx:0> dstack 1 sprint
(-dict- -dict- -dict- -dict-)
onyx:0>

```

obj dup obj dup*:*Input(s):****obj:** An object.**Output(s):****obj:** The same object that was passed in.**dup:** A duplicate of *obj*.**Errors(s):****stackunderflow.****Description:** Create a duplicate of the top object on ostack. For composite objects, the new object is a reference to the same composite object.**Example(s):**

```

onyx:0> 1 dup pstack
1
1
onyx:2>

```

obj* echeck *boolean*:*Input(s):****obj:** An object.**Output(s):****boolean:** True if *obj* has the evaluable attribute, false otherwise.**Errors(s):****stackunderflow.****Description:** Check *obj* for evaluable attribute.**Example(s):**

```

onyx:0> {1 2 3} cve
onyx:1> dup 1 sprint
_{1 2 3}_
onyx:1> echeck 1 sprint
true
onyx:0> {1 2 3} echeck 1 sprint
false
onyx:0> [1 2 3] echeck 1 sprint
false
onyx:0>

```

- egid *gid*:**Input(s):** None.**Output(s):****gid:** Process's effective group ID.**Errors(s):** None.**Description:** Get the process's effective group ID.**Example(s):**

```

onyx:0> egid 1 sprint
1001
onyx:0>

```

- end -:**Input(s):** None.**Output(s):** None.**Errors(s):****stackunderflow.****Description:** Pop the topmost dictionary off dstack, thereby removing its contents from the namespace.**Example(s):**

```

onyx:0> <$foo 'foo'> begin
onyx:0> foo 1 sprint
'foo'
onyx:0> end
onyx:0> foo 1 sprint
Error $undefined
ostack: ( )

```



```

dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..2):
0:      foo
1:      -file-
2:      --start--
onyx:1>

```

- envdict *dict*:**Input(s):** None.**Output(s):****dict:** A dictionary.**Errors(s):** None.**Description:** Get envdict. See Section 2.9.2 for details on envdict.**Example(s):**

```

onyx:0> envdict 0 sprint
-dict-
onyx:0>

```

a b eq boolean*:*Input(s):****a:** An object.**b:** An object.**Output(s):****boolean:** True if *a* is equal to *b*, false otherwise.**Errors(s):****stackunderflow.****Description:** Compare two objects for equality. Equality has the following meaning, depending on the types of *a* and *b*:**array, condition, dict, file, hook, mutex, stack, thread:** *a* and *b* are equal iff they refer to the same memory.**operator:** *a* and *b* are equal iff they refer to the same function.**name, string:** *a* and *b* are equal iff they are lexically equivalent. A name can be equal to a string.**boolean:** *a* and *b* are equal iff they are the same value.**integer, real:** *a* and *b* are equal iff they are the same value.**Example(s):**

```

onyx:0> mutex mutex eq 1 sprint
false
onyx:0> mutex dup eq 1 sprint
true
onyx:0> $foo 'foo' eq 1 sprint
true
onyx:0> true true eq 1 sprint
true
onyx:0> true false eq 1 sprint
false
onyx:0> 1 1 eq 1 sprint

```

```
true
onyx:0> 1 2 eq 1 sprint
false
onyx:0> 1.0 1 eq 1 sprint
true
onyx:0> 1.0 1.1 eq 1 sprint
false
onyx:0>
```

– **estack** *stack*:

Input(s): None.

Output(s):

stack: A current snapshot (copy) of the execution stack.

Errors(s): None.

Description: Get a current snapshot of the execution stack.

Example(s):

```
onyx:0> estack 1 sprint
(--start-- -file- --estack--)
onyx:0>
```

– **euid** *uid*:

Input(s): None.

Output(s):

uid: Process's effective user ID.

Errors(s): None.

Description: Get the process's effective user ID.

Example(s):

```
onyx:0> euid 1 sprint
1001
onyx:0>
```

obj eval –:

Input(s):

obj: An object.

Output(s): None.

Errors(s):

stackunderflow.

Description: Evaluate object. See Section 2.1 for details on object evaluation.

Example(s):

```
onyx:0> ``hi' 1 sprint' cvx eval
'hi'
onyx:0>
```

a b exch b a:

Input(s):

a: An object.

b: An object.

Output(s):**b:** The same object that was passed in.**a:** The same object that was passed in.**Errors(s):****stackunderflow.****Description:** Exchange the top two objects on ostack.**Example(s):**

```

onyx:0> 1 2 pstack
2
1
onyx:2> exch pstack
1
2
onyx:2>

```

args* exec -:*Input(s):****args:** An array of strings. The first string in *args* is the path of the program to invoke, and any additional array elements are passed as command line arguments to the invoked program.**Output(s):** None (this operator does not return).**Errors(s):****rangecheck.****stackunderflow.****typecheck.****Description:** Overlay a new program and execute it. The current contents of envdict are used to construct the new program's environment.**Example(s):**

```

onyx:0> 'Old program'
onyx:1> ['/usr/local/bin/onyx'] exec
Canonware Onyx, version 1.0.0.
onyx:0>

```

- exit -:**Input(s):** None.**Output(s):** None.**Errors(s):** None.**Description:** Exit the innermost enclosing looping context immediately. This operator can be called within the looping context of **for**, **repeat**, **while**, **until**, **loop**, **foreach**, and **dirforeach**.**Example(s):**

```

onyx:0> {'hi' 1 sprint exit 'bye' 1 sprint} loop
'hi'
onyx:0>

```

a b* exp r:*Input(s):**

a: An integer or real.

b: An integer or real.

Output(s):

r: a to the b power.

Errors(s):

stackunderflow.

typecheck.

Description: Return a to the b power. If a negative exponent is specified, the result will always be a real, even if both arguments are integers.

Example(s):

```
onyx:0> 5 0 exp 1 sprint
1
onyx:0> 5 1 exp 1 sprint
5
onyx:0> 5 2 exp 1 sprint
25
onyx:0> -5 3 exp 1 sprint
-125
onyx:0> 5 -3 exp 1 sprint
8.000000e-03
onyx:0> 2.1 3.5 exp 1 sprint
1.342046e+01
onyx:0> 100 .01 exp 1 sprint
1.000000e+02
onyx:0>
```

- false *false*:

Input(s): None.

Output(s):

false: The boolean value false.

Errors(s): None.

Description: Return false.

Example(s):

```
onyx:0> false 1 sprint
false
onyx:0>
```

a floor r :

Input(s):

a: An integer or real.

Output(s):

r: Integer floor of a .

Errors(s):

stackunderflow.

typecheck.

Description: Return the integer floor of a .

Example(s):

```
onyx:0> -1.51 floor 1 sprint
-2
onyx:0> -1.49 floor 1 sprint
-2
onyx:0> 0 floor 1 sprint
0
onyx:0> 1.49 floor 1 sprint
1
onyx:0> 1.51 floor 1 sprint
1
onyx:0>
```

- flush -:**Input(s):** None.**Output(s):** None.**Errors(s):****ioerror.****Description:** Flush any buffered data associated with stdout.**Example(s):**

```
onyx:0> 'Hi\n' print
onyx:0> flush
Hi
onyx:0>
```

file flushfile -:**Input(s):****file:** A file object.**Output(s):** None.**Errors(s):****ioerror.****stackunderflow.****typecheck.****Description:** Flush any buffered data associated with *file*.**Example(s):**

```
onyx:0> 'Hi\n' print
onyx:0> stdout flushfile
Hi
onyx:0>
```

init inc limit proc for -:**Input(s):****init:** Initial value of control variable.**inc:** Amount to increment control variable by at the end of each iteration.**limit:** Inclusive upper bound for control variable if less than or equal to *init*, otherwise inclusive lower bound for control variable.**proc:** An object.

Output(s): At the beginning of each iteration, the current value of the control variable is pushed onto ostack.

Errors(s):

stackunderflow.

typecheck.

Description: Iteratively evaluate *proc*, pushing a control variable onto ostack at the beginning of each iteration, until the control variable has exceeded *limit*. This operator supports the **exit** operator.

Example(s):

```
onyx:0> 0 1 3 {1 sprint} for
0
1
2
3
onyx:0> 0 -1 -3 {1 sprint} for
0
-1
-2
-3
onyx:0> 0 2 7 {1 sprint} for
0
2
4
6
onyx:0> 0 1 1000 {dup 1 sprint 3 eq {exit} if} for
0
1
2
3
onyx:0>
```

***array proc* foreach -:**

***dict proc* foreach -:**

***stack proc* foreach -:**

***string proc* foreach -:**

Input(s):

array: An array object.

dict: A dict object.

stack: A stack object.

string: A string object.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: For each entry in the first input argument (*array*, *dict*, *stack*, or *string*), push the entry onto ostack and execute *proc*. This operator supports the **exit** operator.

Example(s):

```

onyx:0> [1 2] {1 sprint} foreach
1
2
onyx:0> <$foo 'foo' $bar 'bar'> {pstack clear} foreach
'bar'
$bar
'foo'
$foo
onyx:0> (1 2) {pstack clear} foreach
2
1
onyx:0> 'ab' {pstack clear} foreach
97
98
onyx:0>

```

args forkexec pid:**Input(s):**

args: An array of strings. The first string in *args* is the path of the program to invoke, and any additional array elements are passed as command line arguments to the invoked program.

Output(s):

pid: Process identifier for the new process, or 0 if the child process.

Errors(s):

limitcheck.

rangecheck.

stackunderflow.

typecheck.

Description: Fork and exec a new process. The current contents of envdict are used to construct the new program's environment.

Example(s):

```

onyx:0> ['/bin/date'] forkexec dup 1 sprint waitpid 1 sprint
6516
Sat Jul 13 20:47:54 PDT 2002
0
onyx:0>

```

– gdict dict:

Input(s): None.

Output(s):

dict: A dictionary.

Errors(s): None.

Description: Get gdict. See Section 2.9.4 for details on gdict.

Example(s):

```

onyx:0> gdict 0 sprint
-dict-
onyx:0>

```

a b ge boolean:**Input(s):**

- a:** A number (integer or real) or string.
- b:** An object of a type compatible with *a*.

Output(s):

- boolean:** True if *a* is greater than or equal to *b*, false otherwise.

Errors(s):

- stackunderflow.**
- typecheck.**

Description: Compare two numbers or strings.

Example(s):

```
onyx:0> 1 2 ge 1 sprint
false
onyx:0> 1 1 ge 1 sprint
true
onyx:0> 2 1 ge 1 sprint
true
onyx:0> 1 1.1 ge 1 sprint
false
onyx:0> 1.1 1.1 ge 1 sprint
true
onyx:0> 1.1 1 ge 1 sprint
true
onyx:0> 'a' 'b' ge 1 sprint
false
onyx:0> 'a' 'a' ge 1 sprint
true
onyx:0> 'b' 'a' ge 1 sprint
true
onyx:0>
```

array index get obj:***dict key get value:******string index get integer:*****Input(s):**

- array:** An array object.
- dict:** A dict object.
- string:** A string object.
- index:** Offset of *array* element or *string* element.
- key:** A key in *dict*.

Output(s):

- obj:** The object in *array* at offset *index*.
- value:** The value in *dict* corresponding to *key*.
- integer:** The ascii value of the character in *string* at offset *index*.

Errors(s):

- rangecheck.**

stackunderflow.
typecheck.
undefined.

Description: Get an element of *array*, a value in *dict*, or an element of *string*.

Example(s):

```
onyx:0> ['a' 'b' 'c'] 1 get 1 sprint
'b'
onyx:0> <$foo 'foo' $bar 'bar'> $bar get 1 sprint
'bar'
onyx:0> 'abc' 1 get 1 sprint
98
onyx:0>
```

array index length getinterval subarray:

string index length getinterval substring:

Input(s):

array: An array object.
string: A string object.
index: The offset into *array* or *string* to get the interval from.
length: The length of the interval in *array* or *string* to get.

Output(s):

subarray: A subarray of *array* at offset *index* and of length *length*.
substring: A substring of *string* at offset *index* and of length *length*.

Errors(s):

rangecheck.
stackunderflow.
typecheck.

Description: Get an interval of *array* or *string*.

Example(s):

```
onyx:0> [0 1 2 3] 1 2 getinterval 1 sprint
[1 2]
onyx:0> 'abcd' 1 2 getinterval 1 sprint
'bc'
onyx:0>
```

– gid gid:

Input(s): None.

Output(s):

gid: Process's group ID.

Errors(s): None.

Description: Get the process's group ID.

Example(s):

```
onyx:0> gid 1 sprint
1001
onyx:0>
```

- globaldict *dict*:

Input(s): None.

Output(s):

dict: A dictionary.

Errors(s): None.

Description: Get globaldict. See Section 2.9.5 for details on globaldict.

Example(s):

```
onyx:0> globaldict 1 sprint
<>
onyx:0>
```

- gstderr *file*:

Input(s): None.

Output(s):

file: A file object corresponding to the global stderr.

Errors(s): None.

Description: Get the global stderr that is inherited by new threads. See Section 2.4 for standard I/O details.

Example(s):

```
onyx:0> gstderr pstack
-file-
onyx:1>
```

- gstdin *file*:

Input(s): None.

Output(s):

file: A file object corresponding to the global stdin.

Errors(s): None.

Description: Get the global stdin that is inherited by new threads. See Section 2.4 for standard I/O details.

Example(s):

```
onyx:0> gstdin pstack
-file-
onyx:1>
```

- gstdout *file*:

Input(s): None.

Output(s):

file: A file object corresponding to the global stdout.

Errors(s): None.

Description: Get the global stdout that is inherited by new threads. See Section 2.4 for standard I/O details.

Example(s):

```
onyx:0> gstdout pstack
-file-
onyx:1>
```

a b gt boolean:**Input(s):**

- a:** A number (integer or real) or string.
- b:** An object of a type compatible with *a*.

Output(s):

boolean: True if *a* is greater than *b*, false otherwise.

Errors(s):

stackunderflow.
typecheck.

Description: Compare two numbers or strings.

Example(s):

```
onyx:0> 1 1 gt 1 sprint
false
onyx:0> 2 1 gt 1 sprint
true
onyx:0> 1.1 1.1 gt 1 sprint
false
onyx:0> 1.1 1 gt 1 sprint
true
onyx:0> 'a' 'a' gt 1 sprint
false
onyx:0> 'b' 'a' gt 1 sprint
true
onyx:0>
```

hook hooktag tag:**Input(s):**

hook: A hook object.

Output(s):

tag: The tag associated with *hook*.

Errors(s):

stackunderflow.
typecheck.

Description: Get the tag associated with *hook*.

Example(s):***OPARGS hostname OPOUTS:*****Input(s):**

:

Output(s):

:

Errors(s):

stackunderflow.
typecheck.

Description:

Example(s):

... *obj* *,,,index* ibdup ... *obj* *,,,dup*:

Input(s):

...: *index* objects.

obj: An object.

,,,: Zero or more objects.

index: Offset from bottom of ostack, counting from 0.

Output(s):

...: *index* objects.

obj: An object.

,,,: Zero or more objects.

dup: Duplicate of *obj*.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Create a duplicate of the object on ostack that is at offset *index* from the bottom of ostack.

Example(s):

```
onyx:4> 2 ibdup pstack
2
3
2
1
0
onyx:5>
```

... *obj* *,,,index* ibpop ...,,,:

Input(s):

...: *index* objects.

obj: An object.

,,,: Zero or more objects.

index: Offset from bottom of ostack, counting from 0.

Output(s):

...: *index* objects.

,,,: Zero or more objects.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Remove the object from ostack that is at offset *index* from the bottom of ostack.

Example(s):

```
onyx:0> 0 1 2 3
onyx:4> 2 ibpop pstack
3
```

```

1
0
onyx:3>

```

a b idiv r:**Input(s):**

a: An integer.
b: A non-zero integer.

Output(s):

r: The integer quotient of *a* divided by *b*.

Errors(s):

stackunderflow.
typecheck.
undefinedresult.

Description: Return the integer quotient of *a* divided by *b*.

Example(s):

```

onyx:0> 4 2 idiv 1 sprint
2
onyx:0> 5 2 idiv 1 sprint
2
onyx:0> 5 0 idiv
Error $undefinedresult
ostack: (5 0)
dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..2):
0:      --idiv--
1:      -file-
2:      --start--
onyx:3>

```

obj ... index idup obj ... dup:**Input(s):**

obj: An object.
index: Offset from top of ostack, counting from 0, not counting *index*, of the object to duplicate on ostack.

Output(s):

obj: The same object that was passed in.
dup: A duplicate of *obj*.

Errors(s):

rangecheck.
stackunderflow.
typecheck.

Description: Create a duplicate of the object on ostack at *index*.

Example(s):

```

onyx:0> 3 2 1 0 2 idup pstack
2
0

```

```
1
2
3
onyx:5>
```

boolean obj if -:**Input(s):****boolean:** A boolean.**obj:** An object.**Output(s):** None.**Errors(s):****stackunderflow.****typecheck.****Description:** Evaluate *obj* if *boolean* is true.**Example(s):**

```
onyx:0> true {'yes' 1 sprint} if
'yes'
onyx:0> false {'yes' 1 sprint} if
onyx:0>
```

boolean a b ifelse -:**Input(s):****boolean:** A boolean.**a:** An object.**b:** An object.**Output(s):** None.**Errors(s):****stackunderflow.****typecheck.****Description:** Evaluate *a* if *boolean* is true, evaluate *b* otherwise. See Section 2.1 for details on object evaluation.**Example(s):**

```
onyx:0> true {'yes'}{'no'} ifelse 1 sprint
'yes'
onyx:0> false {'yes'}{'no'} ifelse 1 sprint
'no'
onyx:0>
```

a inc r:**Input(s):****a:** An integer.**Output(s):****r:** $a + 1$.**Errors(s):****stackunderflow.****typecheck.**

Description: Add one to *a*.

Example(s):

```
onyx:0> 1 inc 1 sprint
2
onyx:0>
```

***file* iobuf count:**

Input(s):

file: A file object.

Output(s):

count: The size in bytes of the I/O buffer associated with *file*.

Errors(s):

stackunderflow.

typecheck.

Description: Get the size of the I/O buffer associated with *file*.

Example(s):

```
onyx:0> stdout iobuf 1 sprint
512
onyx:0> stderr iobuf 1 sprint
0
onyx:0>
```

***obj ... index* ipop ...:**

Input(s):

obj: An object.

index: Offset from top of ostack, counting from 0, not counting *index*, of the object to remove from ostack.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Remove the *obj* at *index* from ostack.

Example(s):

```
onyx:0> 2 1 0
onyx:3> 1 ipop pstack
0
2
onyx:2>
```

– istack *stack*:

Input(s): None.

Output(s):

stack: A current snapshot (copy) of the index stack.

Errors(s): None.

Description: Get a current snapshot of the index stack.

Example(s):

```
onyx:0> istack 1 sprint
(0 0 0)
onyx:0>
```

thread join* -:*Input(s):**

thread: A thread object.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Wait for *thread* to exit. A thread may only be detached or joined once; any attempt to do so more than once results in undefined behavior (likely crash).

Example(s):

```
onyx:0> (1 2) {add 1 sprint} thread join 'Done\n' print flush
3
Done
onyx:0>
```

dict key known boolean*:*Input(s):**

dict: A dictionary.

key: A key to look for in *dict*.

Output(s):

boolean: True if *key* is defined in *dict*, false otherwise.

Errors(s):

stackunderflow.

typecheck.

Description: Check whether *key* is defined in *dict*.

Example(s):

```
onyx:1> <$foo 'foo'> $foo known 1 sprint
true
onyx:1> <$foo 'foo'> $bar known 1 sprint
false
onyx:1>
```

obj lcheck boolean*:*Input(s):**

obj: An array, dict, file, or string.

Output(s):

boolean: True if *obj* is implicitly locked, false otherwise.

Errors(s):

stackunderflow.

typecheck.

Description: Check if *obj* is implicitly locked.

Example(s):

```
onyx:0> false setlocking
onyx:0> [1 2 3] lcheck 1 sprint
false
onyx:0> true setlocking
onyx:0> [1 2 3] lcheck 1 sprint
true
onyx:0>
```

a b le boolean:**Input(s):**

- a:** A number (integer or real) or string.
- b:** An object of a type compatible with *a*.

Output(s):

boolean: True if *a* is less than or equal to *b*, false otherwise.

Errors(s):

stackunderflow.
typecheck.

Description: Compare two numbers or strings.

Example(s):

```
onyx:0> 1 2 le 1 sprint
true
onyx:0> 1 1 le 1 sprint
true
onyx:0> 2 1 le 1 sprint
false
onyx:0> 1 1.1 le 1 sprint
true
onyx:0> 1.1 1.1 le 1 sprint
true
onyx:0> 1.1 1 le 1 sprint
false
onyx:0> 'a' 'b' le 1 sprint
true
onyx:0> 'a' 'a' le 1 sprint
true
onyx:0> 'b' 'a' le 1 sprint
false
onyx:0>
```

array length count:***dict length count:******name length count:******string length count:*****Input(s):**

- array:** An array object.
- dict:** A dict object.

name: A name object.

string: A string object.

Output(s):

count: Number of elements in *array*, number of entries in *dict*, number of characters in *name*, or number of characters in *string*.

Errors(s):

stackunderflow.

typecheck.

Description: Get the number of elements in *array*, number of entries in *dict*, number of characters in *name*, or number of characters in *string*.

Example(s):

```
onyx:0> [1 2 3] length 1 sprint
3
onyx:0> <$foo 'foo' $bar 'bar'> length 1 sprint
2
onyx:0> $foo length 1 sprint
3
onyx:0> 'foo' length 1 sprint
3
onyx:0>
```

filename linkname link -:

Input(s):

filename: A string that represents a filename.

linkname: A string that represents a filename.

Output(s): None.

Errors(s):

invalidfileaccess.

ioerror.

stackunderflow.

typecheck.

undefinedfilename.

unregistered.

Description: Create a hard link from *linkname* to *filename*.

Example(s):

```
onyx:0> '/tmp/foo' 'w' open
onyx:1> dup 'Hello\n' write
onyx:1> dup flushfile
onyx:1> close
onyx:0> '/tmp/foo' '/tmp/bar' link
onyx:0> '/tmp/bar' 'r' open
onyx:1> readline
onyx:2> pstack
false
'Hello'
onyx:2>
```

sock backlog listen -:

Input(s):

sock: A socket.

backlog: Maximum backlog of connections to listen for. If not specified, the maximum backlog is used.

Output(s): None.**Errors(s):**

invalidfileaccess.

neterror.

stackunderflow.

typecheck.

unregistered.

Description: Listen for connections on a socket.

Example(s):

```
onyx:0> $AF_INET $SOCK_STREAM socket
onyx:1> dup 'localhost' 7777 bindsocket
onyx:1> dup listen
onyx:1>
```

a ln r:**Input(s):**

a: An integer or real.

Output(s):

r: Natural logarithm of *a*.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Return the natural logarithm of *a*.

Example(s):

```
onyx:0> 5 ln 1 sprint
1.609438e+00
onyx:0> 8.5 ln 1 sprint
2.140066e+00
onyx:0>
```

key load val:**Input(s):**

key: A key to look up in dstack.

Output(s):

val: The value associated with the topmost definition of *key* in dstack.

Errors(s):

stackunderflow.

undefined.

Description: Get the topmost definition of *key* in dstack.

Example(s):

```
onyx:1> <$foo 'foo'> begin
onyx:1> <$foo 'FOO'> begin
onyx:1> $foo load 1 sprint
'FOO'
onyx:1>
```

mutex lock* -:*Input(s):**

mutex: A mutex object.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Acquire *mutex*, waiting if necessary. Attempting to acquire *mutex* recursively will result in undefined behavior (likely deadlock or crash).

Example(s):

```
onyx:0> mutex dup lock unlock
onyx:0>
```

a log r*:*Input(s):**

a: An integer or real.

Output(s):

r: Base 10 logarithm of *a*.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Return the base 10 logarithm of *a*.

Example(s):

```
onyx:0> 5 log 1 sprint
6.989700e-01
onyx:0> 8.5 log 1 sprint
9.294189e-01
onyx:0>
```

proc loop* -:*Input(s):**

proc: An object to evaluate.

Output(s): None.

Errors(s):

stackunderflow.

Description: Repeatedly evaluate *proc* indefinitely. This operator supports the **exit** operator.

Example(s):

```

onyx:0> 0 {1 add dup 1 sprint dup 3 eq {pop exit} if} loop
1
2
3
onyx:0>

```

a b lt boolean:**Input(s):**

- a:** A number (integer or real) or string.
- b:** An object of a type compatible with *a*.

Output(s):

boolean: True if *a* is less than *b*, false otherwise.

Errors(s):

stackunderflow.
typecheck.

Description: Compare two numbers or strings.

Example(s):

```

onyx:0> 1 2 lt 1 sprint
true
onyx:0> 1 1 lt 1 sprint
false
onyx:0> 1 1.1 lt 1 sprint
true
onyx:0> 1.1 1.1 lt 1 sprint
false
onyx:0> 1.1 1 lt 1 sprint
false
onyx:0> 'a' 'b' lt 1 sprint
true
onyx:0> 'a' 'a' lt 1 sprint
false
onyx:0>

```

– mark *mark*:

Input(s): None.

Output(s):

mark: A mark object.

Errors(s): None.

Description: Push a mark onto ostack.

Example(s):

```

onyx:0> mark pstack
-mark-
onyx:1>

```

path mkdir -:***path mode mkdir -:***

Input(s):

path: A string object that represents a directory path.

mode: An integer that represents a Unix file mode.

Output(s): None.

Errors(s):

invalidfileaccess.

ioerror.

rangecheck.

stackunderflow.

typecheck.

unregistered.

Description: Create a directory.

Example(s):

```
onyx:0> `/tmp/tdir' 8@755 mkdir
onyx:0> `/tmp/tdir' {1 sprint} dirforeach
`.`
`..`
onyx:0>
```

***path* mkfifo -:**

***path mode* mkfifo -:**

Input(s):

path: A string object that represents a directory path.

mode: An integer that represents a Unix file mode.

Output(s): None.

Errors(s):

invalidfileaccess.

ioerror.

rangecheck.

stackunderflow.

typecheck.

unregistered.

Description: Create a named pipe.

Example(s):

```
onyx:0> `/tmp/fifo' mkfifo
onyx:0>
```

***a b* mod *r*:**

Input(s):

a: An integer.

b: A non-zero integer.

Output(s):

r: The modulus of *a* and *b*.

Errors(s):

stackunderflow.
typecheck.
undefinedresult.

Description: Return the modulus of a and b .

Example(s):

```
onyx:0> 4 2 mod 1 sprint
0
onyx:0> 5 2 mod 1 sprint
1
onyx:0> 5 0 mod
Error $undefinedresult
ostack: (5 0)
dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..2):
0:      --mod--
1:      -file-
2:      --start--
onyx:3>
```

path symbol modload -:

Input(s):

path: A string that represents a module filename.

symbol: A string that represents the symbol name of a module initialization function to be executed.

Output(s): None.

Errors(s):

invalidfileaccess.
stackunderflow.
typecheck.
undefined.

Description: Dynamically load a module, create a hook object that encapsulates the handle returned by `dlopen(3)` (hook data pointer) and the module initialization function (hook evaluation function), and evaluate the hook.

All objects that refer to code and/or data that are part of the module must directly and/or indirectly maintain a reference to the hook that is evaluated by this operator, since failing to do so would allow the garbage collector to unload the module, which could result in dangling pointers to unmapped memory regions.

Loadable modules present a problem for the garbage collector during the sweep phase. All objects that refer to memory that is dynamically mapped as part of the module must be destroyed before the module is unloaded. Destruction ordering constraints show up in other situations as well, but in the case of loadable modules, there is no reasonable solution except to explicitly order the destruction of objects. Therefore, by default, the hook that is evaluated by `modload` is destroyed during the second sweep pass. It is possible for a module to override what sweep pass the hook is destroyed on, in cases where there are additional ordering constraints for the objects created by a module. This isn't important from the Onyx language perspective, but is important to understand when implementing modules.

Example(s):

```
onyx:0> `/usr/local/share/onyx/nxmod/mdprompt.nxm' `modprompt_init'
```

```
onyx:2> modload
```

```
onyx:0>
```

mutex proc monitor -:

Input(s):

mutex: A mutex.

proc: Any object.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Execute *proc* while holding *mutex*.

Example(s):

```
onyx:0> mutex {'hello\n' print} monitor flush
```

```
hello
```

```
onyx:0>
```

file symbol mrequire -:

Input(s):

file: A string that represents a module filename.

symbol: A string that represents the symbol name of a module initialization function to be executed.

Output(s): None.

Errors(s):

invalidfileaccess.

stackunderflow.

typecheck.

undefined.

undefinedfilename.

Description: Search for and load a module. The module is searched for by catenating a prefix, a *"/"*, and *file* to form a file path. Prefixes are tried in the following order:

1. The ordered elements of the `mpath_pre` array, which is defined in `onyxdict`.
2. If defined, the ordered elements of the `ONYX_MPATH` environment variable, which is a colon-separated list.
3. The ordered elements of the `mpath_post` array, which is defined in `onyxdict`.

Example(s):

```
onyx:0> 'modgtk.nxm' 'modgtk_init' mrequire
```

```
onyx:0>
```

a b mul r:

Input(s):

a: An integer or real.

b: An integer or real.

Output(s):

r: The product of *a* and *b*.

Errors(s):

stackunderflow.

typecheck.

Description: Return the product of *a* and *b*.

Example(s):

```
onyx:0> 3 17 mul 1 sprint
51
onyx:0> -5 -6 mul 1 sprint
30
onyx:0> 3.5 4.0 mul 1 sprint
1.400000e+01
onyx:0> -1.5 3 mul 1 sprint
-4.500000e+00
onyx:0>
```

– **mutex *mutex*:**

Input(s): None.

Output(s):

mutex: A mutex object.

Errors(s): None.

Description: Create a mutex.

Example(s):

```
onyx:0> mutex 1 sprint
-mutex-
onyx:0>
```

objects ... count nbpop ...:

Input(s):

objects: Zero or more objects.

count: Number of *objects* to pop.

Output(s): None.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Remove the bottom *count* *objects* from ostack and discard them.

Example(s):

```
onyx:0> 'a' 'b' 'c' 2 nbpop pstack
'c'
onyx:1>
```

arrays count ncat array:

stacks count ncat stack:

strings count ncat string:

Input(s):

arrays: *count* arrays.

stacks: *count* stacks.

strings: *count* strings.

count: Number of *arrays*, *stacks*, or *strings* to catenate.

Output(s):

obj: The catenation of *arrays*, *stacks*, or *strings*.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Catenate *count* *arrays*, *stacks*, or *strings*.

Example(s):

```
onyx:0> ['a'] ['b'] ['c'] 3 ncat 1 sprint
['a' 'b' 'c']
onyx:0> ('a') ('b') ('c') 3 ncat 1 sprint
('a' 'b' 'c')
onyx:0> 'a' 'b' 'c' 3 ncat 1 sprint
'abc'
onyx:0>
```

a ... b count ndn ... b a:

Input(s):

a: An object.

...: *count* – 2 objects.

b: An object.

count: Number of objects to rotate downward.

Output(s):

...: *count* – 2 objects.

b: An object.

a: An object.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Rotate *count* objects on ostack down one position.

Example(s):

```
onyx:0> 'a' 'b' 'c' 'd' 'e' 4 ndn pstack
'b'
'e'
'd'
'c'
'a'
onyx:5>
```

objects count ndup objects objects:

Input(s):

objects: Zero or more objects.

count: The number of *objects* to duplicate.

Output(s):

objects: The same objects that were passed in.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Create duplicates of the top *count* objects on ostack. For composite objects, the new object is a reference to the same composite object.

Example(s):

```
onyx:0> 'a' 'b' 'c' 2 ndup pstack
'c'
'b'
'c'
'b'
'a'
onyx:5>
```

a b ne boolean:**Input(s):**

a: An object.

b: An object.

Output(s):

boolean: True if *a* is not equal to *b*, false otherwise.

Errors(s):

stackunderflow.

Description: Compare two objects for inequality. Inequality has the following meaning, depending on the types of *a* and *b*:

array, condition, dict, file, hook, mutex, stack, thread: *a* and *b* are not equal unless they refer to the same memory.

operator: *a* and *b* are not equal unless they refer to the same function.

name, string: *a* and *b* are not equal iff they are lexically equivalent. A name can be equal to a string.

boolean: *a* and *b* are not equal unless they are the same value.

integer, real: *a* and *b* are not equal unless they are the same value.

Example(s):

```
onyx:0> mutex mutex ne 1 sprint
true
onyx:0> mutex dup ne 1 sprint
false
onyx:0> $foo 'foo' ne 1 sprint
false
onyx:0> $foo $bar ne 1 sprint
true
onyx:0> true false ne 1 sprint
true
onyx:0> true true ne 1 sprint
false
```

```
onyx:0> 1 1 ne 1 sprint
false
onyx:0> 1 2 ne 1 sprint
true
onyx:0> 1.0 1 ne 1 sprint
false
onyx:0> 1.0 1.1 ne 1 sprint
true
onyx:0>
```

a neg r:**Input(s):**

a: An integer.

Output(s):

r: The negative of *a*.

Errors(s):

stackunderflow.

typecheck.

Description: Return the negative of *a*.

Example(s):

```
onyx:0> 0 neg 1 sprint
0
onyx:0> 5 neg 1 sprint
-5
onyx:0> -5 neg 1 sprint
5
onyx:0> 3.14 neg 1 sprint
-3.140000e+00
onyx:0> -3.14 neg 1 sprint
3.140000e+00
onyx:0>
```

a b nip b:**Input(s):**

a: An object.

b: An object.

Output(s):

b: An object.

Errors(s):

stackunderflow.

Description: Remove the second to top object from ostack.

Example(s):

```
onyx:0> 'a' 'b' 'c'
onyx:3> nip pstack
'c'
'a'
onyx:2>
```

file* nonblocking *boolean*:*Input(s):**

file: A file object.

Output(s):

boolean: Nonb-blocking mode for *file*.

Errors(s):

stackunderflow.

typecheck.

Description: Get non-blocking mode for *file*.

Example(s):

```
onyx:0> '/tmp/foo' 'w' open
onyx:1> dup nonblocking 1 sprint
false
onyx:1> dup true setnonblocking
onyx:1> dup nonblocking 1 sprint
true
onyx:1>
```

a* not *r*:*Input(s):**

a: An integer or boolean.

Output(s):

r: If *a* is an integer, the bitwise negation of *a*, otherwise the logical negation of *a*.

Errors(s):

stackunderflow.

typecheck.

Description: Return the bitwise negation of an integer, or the logical negation of a boolean.

Example(s):

```
onyx:0> true not 1 sprint
false
onyx:0> false not 1 sprint
true
onyx:0> 1 not 1 sprint
-2
onyx:0>
```

objects* count npop -:*Input(s):**

objects: Zero or more objects.

count: Number of *objects* to pop.

Output(s): None.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Remove the top *count* *objects* from ostack and discard them.

Example(s):

```

onyx:0> 'a' 'b' 'c' 2 npop pstack
'a'
onyx:1>

```

nanoseconds nsleep* –:*Input(s):**

nanoseconds: Minimum number of nanoseconds to sleep. Must be greater than 0.

Output(s): None.**Errors(s):**

rangecheck.
stackunderflow.
typecheck.

Description: Sleep for at least *nanoseconds* nanoseconds.

Example(s):

```

onyx:0> 1000 nsleep
onyx:0>

```

– null *null*:

Input(s): None.

Output(s):

null: A null object.

Errors(s): None.

Description: Create a null object.

Example(s):

```

onyx:0> null pstack
null
onyx:1>

```

a ... b count nup b a ...*:*Input(s):**

a: An object.
...: *count* – 2 objects.
b: An object.
count: Number of objects to rotate upward.

Output(s):

b: An object.
a: An object.
...: *count* – 2 objects.

Errors(s):

rangecheck.
stackunderflow.
typecheck.

Description: Rotate *count* objects on ostack up one position.

Example(s):

```

onyx:0> 'a' 'b' 'c' 'd' 'e' 4 nup pstack
'd'
'c'
'b'
'e'
'a'
onyx:5>

```

– onyxdict *dict*:**Input(s):** None.**Output(s):****dict:** A dictionary.**Errors(s):** None.**Description:** Get onyxdict. See Section 2.9.6 for details on onyxdict.**Example(s):**

```

onyx:0> onyxdict 1 sprint
<$rpath_pre -array- $rpath_post -array- $mpath_pre -array- $mpath_post -array->
onyx:0>

```

filename flags open file:***filename flags mode open file:*****Input(s):****filename:** A string that represents a filename.**flags:** A string that represents a file mode:**'r':** Read only.**'r+':** Read/write, starting at offset 0.**'w':** Write only. Create file if necessary. Truncate file if non-zero length.**'w+':** Read/write, starting at offset 0. Create file if necessary.**'a':** Write only, starting at end of file.**'a+':** Read/write, starting at end of file.**mode:** Mode to use when creating a new file (defaults to 0777). Note that the process's umask also affects creation mode.**Output(s):****file:** A file object.**Errors(s):****invalidfileaccess.****ioerror.****limitcheck.****rangecheck.****stackunderflow.****typecheck.****Description:** Open a file.

Example(s):

```
onyx:0> '/tmp/foo' 'w' open pstack
-file-
onyx:1>
```

a b or r:**Input(s):**

a: An integer or boolean.

b: The same type as *a*.

Output(s):

r: If *a* and *b* are integers, their bitwise or, otherwise their logical or.

Errors(s):

stackunderflow.

typecheck.

Description: Return the bitwise or of two integers, or the logical or of two booleans.

Example(s):

```
onyx:0> false false or 1 sprint
false
onyx:0> true false or 1 sprint
true
onyx:0> 5 3 or 1 sprint
7
onyx:0>
```

- ostack stack:

Input(s): None.

Output(s):

stack: A current snapshot (copy) of ostack.

Errors(s): None.

Description: Get a current snapshot of ostack.

Example(s):

```
onyx:0> 1 2 3 ostack pstack
(1 2 3)
3
2
1
onyx:4>
```

obj depth output -:**Input(s):**

obj: An object to print syntactically.

depth: Maximum recursion depth.

Output(s): None.

Errors(s):

ioerror.

stackunderflow.

typecheck.

Description: Syntactically print *obj*. See Section 2.9.7 for format specifier details.

Example(s):

```
onyx:0> [1 [2 3] 4] <$w 20 $p '_' $j $c $r 1> output '\n' print flush
____[1 -array- 4]_____
onyx:0> [1 [2 3] 4] <$w 20 $p '_' $j $c $r 2> output '\n' print flush
____[1 [2 3] 4]_____
onyx:0> 4242 <$s $+> output '\n' print flush
+4242
onyx:0> '0x' print 4242 <$b 16> output '\n' print flush
0x1092
onyx:0> '0x' 4242 <$b 16> outputs cat <$w 10 $p '.'>
onyx:2> output '\n' print flush
....0x1092
onyx:0> '0x' print 4242 <$w 8 $p '0' $b 16> output '\n' print flush
0x00001092
onyx:0>
```

obj flags outputs string:

Input(s):

obj: An object to print syntactically.

depth: Formatting flags. See Section 2.9.7 for details on the supported flags.

Output(s):

string: A formatted string representation of *obj*. See Section 2.9.7 for format specifier details.

Errors(s):

stackunderflow.

typecheck.

Description: Create a formatted string representation of *obj*.

Example(s):

```
onyx:0> [1 [2 3] 4] <$w 20 $p '_' $j $c $r 1> outputs print '\n' print flush
____[1 -array- 4]_____
onyx:0> [1 [2 3] 4] <$w 20 $p '_' $j $c $r 2> outputs print '\n' print flush
____[1 [2 3] 4]_____
onyx:0> 4242 <$s $+> outputs print '\n' print flush
+4242
onyx:0> '0x' print 4242 <$b 16> outputs print '\n' print flush
0x1092
onyx:0> '0x' 4242 <$b 16> outputs cat <$w 10 $p '.'> outputs
onyx:1> print '\n' print flush
....0x1092
onyx:0> '0x' print 4242 <$w 8 $p '0' $b 16> outputs print '\n' print flush
0x00001092
onyx:0>
```

– outputsdict dict:

Input(s): None.

Output(s):

dict: A dictionary.

Errors(s): None.

Description: Get outputsdict. See Section 2.9.7 for details on outputsdict.

Example(s):

```
onyx:0> outputsdict 0 sprint
-dict-
onyx:0>
```

a b over a b a:

Input(s):

a: An object.

b: An object.

Output(s):

a: An object.

b: An object.

Errors(s):

stackunderflow.

Description: Create a duplicate of the second object on ostack and push it onto ostack.

Example(s):

```
onyx:0> 0 1 2 over pstack
1
2
1
0
onyx:4>
```

sock peername dict:

Input(s):

sock: A socket.

Output(s):

dict: A dictionary of information about the peer end of *sock*. Depending on the socket family, the following entries may exist:

family: Socket family.

address: IPv4 address.

port: IPv4 port.

path: Unix-domain socket path.

Errors(s):

argcheck.

ioerror.

neterror.

stackunderflow.

typecheck.

unregistered.

Description: Get information about the peer end of *sock*.

Example(s):

```
onyx:0> $AF_INET $SOCK_STREAM socket
onyx:1> dup 'localhost' 7777 bindsocket
onyx:1> dup listen
onyx:1> dup accept
onyx:2> dup peername 1 sprint
<$family $AF_INET $address 2130706433 $port 33746>
onyx:2>
```

– pid *pid*:

Input(s): None.

Output(s):

pid: Process identifier.

Errors(s): None.

Description: Get the process ID of the running process.

Example(s):

```
onyx:0> pid 1 sprint
80624
onyx:0>
```

– pipe *rfile wfile*:

Input(s): None.

Output(s):

rfile: A readable file object. Data read from *rfile* were previously written to *wfile*.

wfile: A writeable file object. Data written to *wfile* can subsequently be read from *rfile*.

Errors(s):

ioerror.

unregistered.

Description: Create a pipe.

Example(s):

```
onyx:0> pipe
onyx:2> $wfile exch def
onyx:1> $rfile exch def
onyx:0> wfile 'foo\n' write
onyx:0> wfile flushfile
onyx:0> rfile readline pop 1 sprint
'foo'
onyx:0>
```

***obj* pop –:**

Input(s):

obj: An object.

Output(s): None.

Errors(s):

stackunderflow.

Description: Remove the top object from ostack and discard it.

Example(s):

```

onyx:0> 1 2
onyx:2> pstack
2
1
onyx:2> pop
onyx:1> pstack
1
onyx:1>

```

<file flags ...> timeout poll [file ...]:

Input(s):

<...>: A dictionary of *file/flags* key/value pairs.

file: A file object.

flags: A dictionary that contains keys corresponding to file status attributes to poll. The following keys are heeded:

\$POLLIN: Normal or priority data are available for reading.

\$POLLRDNORM: Normal data are available for reading.

\$POLLRDBAND: Priority data are available for reading.

\$POLLPRI: High-priority data are available for reading.

\$POLLOUT: Normal data can be written.

\$POLLWRNORM: Normal data can be written.

\$POLLWRBAND: Priority data can be written.

The values associated with the keys are disregarded, but are set appropriately before **poll** returns (true/false).

timeout: Timeout, in milliseconds (maximum $2^{31} - 1$). -1 is treated specially to mean infinite timeout.

Output(s):

[...]: An array containing a reference to each *file* in **<...>** for which a non-zero number of status attributes is set to true. A zero-length array indicates that the poll timed out.

file: A reference to a file object passed in that has one or more attributes set to true.

Although **<...>** is not returned, its contents are modified.

flags: The dictionary passed in. For recognized key that is defined, the associated value is set to true or false, depending on the status of *file*. In addition, the following keys may be defined (if not already defined) with a value of true in the case of errors:

\$POLLERR: An error has occurred.

\$POLLHUP: Hangup has occurred.

\$POLLNVAL: *file* is not an open file.

Errors(s):

stackunderflow.

rangecheck.

typecheck.

Description: Wait for any of the *flags* associated with a *file* in <...> to be true.

Example(s):

```
onyx:0> <stdout <$POLLOUT null> stderr <$POLLWRNORM null>> dup 0 poll
onyx:2> 2 sprint 2 sprint
[-file- -file-]
<-file- <$POLLWRNORM true> -file- <$POLLOUT true>>
onyx:0>
```

- ppid *pid*:

Input(s): None.

Output(s):

pid: Process identifier.

Errors(s): None.

Description: Get the process ID of the running process's parent.

Example(s):

```
onyx:0> ppid 1 sprint
352
onyx:0>
```

string* print -:*Input(s):**

string: A string object.

Output(s): None.

Errors(s):

ioerror.

stackunderflow.

typecheck.

Description: Print *string* to stdout.

Example(s):

```
onyx:0> 'Hi\n' print flush
Hi
onyx:0>
```

- product *string*:

Input(s): None.

Output(s):

string: A string that contains the product name, normally 'Canonware Onyx'.

Errors(s): None.

Description: Get the product string. The string returned is a reference to the original product string.

Example(s):

```
onyx:0> product pstack
'Canonware Onyx'
onyx:1>
```

- pstack -:

Input(s): None.

Output(s): None.

Errors(s):

ioerror.

Description: Syntactically print the elements of ostack, one per line.

Example(s):

```
onyx:0> 'a' 1 mark $foo [1 2 3] (4 5 6)
onyx:6> pstack
(4 5 6)
[1 2 3]
$foo
-mark-
1
'a'
onyx:6>
```

array index obj put -:

dict key value put -:

string index integer put -:

Input(s):

array: An array object.

dict: A dict object.

string: A string object.

index: Offset in *array* or *string* to put *obj* or *integer*, respectively.

key: An object to use as a key in *dict*.

obj: An object to insert into *array* at offset *index*.

value: An object to associate with *key* in *dict*.

integer: The ascii value of a character to insert into *string* at offset *index*.

Output(s): None.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Insert into *array*, *dict*, or *string*.

Example(s):

```
onyx:0> 3 array dup 1 'a' put 1 print
[null 'a' null]
onyx:0> dict dup $foo 'foo' put 1 print
<$foo 'foo'>
onyx:0> 3 string dup 1 97 put 1 print
'\x00a\x00'
onyx:0>
```

array index subarray putinterval -:

string index substring putinterval -:

Input(s):**array:** An array object.**string:** A string object.**index:** Offset into *array* or *string* to put *subarray* or *substring*, respectively.**subarray:** An array object to put into *array* at offset *index*. When inserted *subarray* must not extend past the end of *array*.**substring:** A string object to put into *string* at offset *index*. When inserted *substring* must not extend past the end of *string*.**Output(s):** None.**Errors(s):****rangecheck.****stackunderflow.****typecheck.****Description:** Replace a portion of *array* or *string*.**Example(s):**

```

onyx:0> 4 array dup 1 ['a' 'b'] putinterval 1 sprint
[null 'a' 'b' null]
onyx:0> 4 string dup 1 'ab' putinterval 1 sprint
'\x00ab\x00'
onyx:0>

```

- pwd *path*:**Input(s):** None.**Output(s):****path:** A string that represents the present working directory.**Errors(s):****invalidaccess.****Description:** Push a string onto ostack that represents the present working directory.**Example(s):**

```

onyx:0> pwd
onyx:1> pstack
'/usr/local/bin'
onyx:1>

```

- quit -:**Input(s):** None.**Output(s):** None.**Errors(s):** None.**Description:** Unwind the execution stack to the innermost **start** context. Under normal circumstances, there is always at least one such context.**Example(s):**

```

onyx:0> stdin cvx start
onyx:0> estack 1 sprint
(--start-- -file- --start-- -file- --estack--)
onyx:0> quit
onyx:0> estack 1 sprint
(--start-- -file- --estack--)
onyx:0>

```

– rand *integer*:

Input(s): None.

Output(s):

integer: A pseudo-random non-negative integer, with 63 bits of psuedo-randomness.

Errors(s): None.

Description: Return a pseudo-random integer.

Example(s):

```
onyx:0> 0 srand
onyx:0> rand 1 sprint
9018578418316157091
onyx:0> rand 1 sprint
8979240987855095636
onyx:0>
```

file read integer boolean:***file string read substring boolean:***

Input(s):

file: A file object.

string: A string object.

Output(s):

integer: An integer that represents the ascii value of a character that was read from *file*.

substring: A substring of *string* that contains data read from *file*.

boolean: If true, end of file reached during read.

Errors(s):

ioerror.

stackunderflow.

typecheck.

Description: Read from *file*.

Example(s):

```
onyx:0> '/tmp/foo' 'w+' open
onyx:1> dup 'Hello\n' write
onyx:1> dup flushfile
onyx:1> dup 0 seek
onyx:1> dup 10 string read
onyx:3> pop 1 sprint
'Hello\n'
```

file readline string boolean:

Input(s):

file: A file object.

Output(s):

string: A string that contains a line of text from *file*.

boolean: If true, end of file reached during read.

Errors(s):

ioerror.

stackunderflow.

typecheck.

Description: Read a line of text from *file*. Lines are separated by “\n” or “\r\n”, which is removed. The last line in a file may not have a newline at the end.

Example(s):

```
onyx:0> '/tmp/foo' 'w+' open
onyx:1> dup 'Hello\n' write
onyx:1> dup 'Goodbye\n' write
onyx:1> dup 0 seek
onyx:1> dup readline 1 sprint 1 sprint
false
'Hello'
onyx:1> dup readline 1 sprint 1 sprint
false
'Goodbye'
onyx:1> dup readline 1 sprint 1 sprint
true
''
onyx:1>
```

***linkname* readlink *string*:**

Input(s):

linkname: A string that represents the path of a symbolic link.

Output(s):

string: A string that represents the link data associated with *linkname*.

Errors(s):

invalidaccess.

invalidfileaccess.

ioerror.

stackunderflow.

typecheck.

undefinedfilename.

unregistered.

Description: Get the data for the symbolic link at *linkname*.

Example(s):

```
onyx:0> 'bar' 'foo' symlink
onyx:0> 'foo' readlink 1 sprint
'bar'
onyx:0>
```

– realtime *nsecs*:

Input(s): None.

Output(s):

nsecs: Number of nanoseconds since the epoch (midnight on 1 January 1970).

Errors(s): None.

Description: Get the number of nanoseconds since the epoch.

Example(s):

```
onyx:0> realtime 1 sprint
993539837806479000
onyx:0>
```

sock string flags recv substring:***sock string recv substring:*****Input(s):**

sock: A socket.

string: A string to use as a buffer for the message being received.

flags: An array of flag names. The following flags are supported:

\$MSG_OOB

\$MSG_PEEK

\$MSG_WAITALL

Output(s):

substring: A substring of *string* that contains message data.

Errors(s):

argcheck.

neterror.

stackunderflow.

typecheck.

unregistered.

Description:**Example(s):**

```
onyx:0> $AF_INET $SOCK_DGRAM socket
onyx:1> dup 'localhost' 7777 bindsocket
onyx:1> dup true setnonblocking
onyx:1> dup 10 string recv
onyx:2> 1 sprint
'hello'
onyx:1>
```

old new rename -:**Input(s):**

old: A string object that represents a file path.

new: A string object that represents a file path.

Output(s): None.**Errors(s):**

invalidfileaccess.

ioerror.

limitcheck.

stackunderflow.

typecheck.

undefinedfilename.

Description: Rename a file or directory from *old* to *new*.

Example(s):

```
onyx:0> '/tmp/tdir' 8@755 mkdir
onyx:0> '/tmp/tdir' '/tmp/ndir' rename
onyx:0> '/tmp/ndir' {1 sprint} dirforeach
'.'
'..'
onyx:0>
```

count proc repeat -:

Input(s):

count: Number of times to evaluate *proc* (non-negative).

proc: An object to evaluate.

Output(s): None.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Evaluate *proc* *count* times. This operator supports the **exit** operator.

Example(s):

```
onyx:0> 3 {'hi' 1 sprint} repeat
'hi'
'hi'
'hi'
onyx:0>
```

file require -:

Input(s):

file: A string that represents a module filename.

Output(s): None.

Errors(s):

invalidfileaccess.

stackunderflow.

typecheck.

undefined.

undefinedfilename.

Description: Search for and evaluate an Onyx source file. The file is searched for by concatenating a prefix, a *"*, and *file* to form a file path. Prefixes are tried in the following order:

1. The ordered elements of the `rpath_pre` array, which is defined in `onyxdict`.
2. If defined, the ordered elements of the `ONYX.RPATH` environment variable, which is a colon-separated list.
3. The ordered elements of the `rpath_post` array, which is defined in `onyxdict`.

Example(s):

```
onyx:0> 'modgtk/modgtk_defs.nx' require
onyx:0>
```

path rmdir -:

Input(s):

path: A string object that represents a directory path.

Output(s): None.

Errors(s):

invalidfileaccess.

ioerror.

stackunderflow.

typecheck.

unregistered.

Description: Remove an empty directory.

Example(s):

```
onyx:0> '/tmp/tdir' 8@755 mkdir
onyx:0> '/tmp/tdir' rmdir
onyx:0>
```

region count amount roll rolled:**Input(s):**

region: 0 or more objects to be rolled.

count: Number of objects in *region*.

amount: Amount by which to roll. If positive, roll upward. If negative, roll downward.

Output(s):

rolled: Rolled version of *region*.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Roll the top *count* objects on ostack (not counting *count* and *amount*) by *amount* positions. A positive *amount* indicates an upward roll, whereas a negative *amount* indicates a downward roll.

Example(s):

```
onyx:0> 3 2 1 0
onyx:4> pstack
0
1
2
3
onyx:4> 3 1 roll
onyx:4> pstack
1
2
0
3
onyx:4> 3 -2 roll
onyx:4> pstack
2
0
1
```

```

3
onyx:4> 4 0 roll
onyx:4> pstack
2
0
1
3
onyx:4>

```

***a* round *r*:**

Input(s):

a: An integer or real.

Output(s):

r: Integer round of *a*.

Errors(s):

stackunderflow.

typecheck.

Description: Round *a* to the nearest integer and return the result.

Example(s):

```

onyx:0> -1.51 round 1 sprint
-2
onyx:0> -1.49 round 1 sprint
-1
onyx:0> 0 round 1 sprint
0
onyx:0> 1.49 round 1 sprint
1
onyx:0> 1.51 round 1 sprint
2
onyx:0>

```

...amount* rot *...:

Input(s):

...: One or more objects.

amount: Number of positions to rotate the stack upward. A negative value causes downward rotation.

Output(s):

...: One or more objects.

Errors(s):

stackunderflow.

typecheck.

Description: Rotate the stack contents up *amount* positions.

Example(s):

```

onyx:0> 1 2 3 4 5 2 rot pstack clear
3
2
1

```

```
5
4
onyx:0> 1 2 3 4 5 -2 rot pstack clear
2
1
5
4
3
onyx:0>
```

stack sadn -:**Input(s):**

stack: A stack object.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Rotate the contents of *stack* down one position.

Example(s):

```
onyx:0> (1 2 3 4) dup sadn 1 sprint
(2 3 4 1)
onyx:0>
```

stack saup -:**Input(s):**

stack: A stack object.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Rotate the contents of *stack* up one position.

Example(s):

```
onyx:0> (1 2 3 4) dup saup 1 sprint
(4 1 2 3)
onyx:0>
```

stack sbdup -:**Input(s):**

stack: A stack object.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Duplicate the bottom object on *stack* and push it onto *stack*.

Example(s):

```
onyx:0> (2 1 0) dup sbdup pstack
(2 1 0 2)
onyx:1>
```

stack sbpop obj:**Input(s):**

stack: A stack object.

Output(s):

obj: An object.

Errors(s):

stackunderflow.

typecheck.

Description: Pop *obj* off the bottom of *stack*.

Example(s):

```
onyx:0> (1 2 3) dup sbpop pstack
1
(2 3)
onyx:2>
```

stack obj sbpush -:**Input(s):**

stack: A stack object.

obj: An object.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Push *obj* onto the bottom of *stack*.

Example(s):

```
onyx:0> (0) dup 1 sbpush
onyx:1> pstack
(1 0)
onyx:1>
```

stack sclear -:**Input(s):**

stack: A stack object.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Remove all objects on *stack*.

Example(s):

```
onyx:0> (1 2 3 4) dup sclear pstack
()
onyx:1>
```

stack scleartomark -:**Input(s):**

stack: A stack object.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

unmatchedmark.

Description: Remove objects from *stack* down to and including the topmost mark.

Example(s):

```
onyx:0> (3 mark 1 0) dup scleartomark pstack
(3)
onyx:1>
```

***stack* scout count:**

Input(s):

stack: A stack object.

Output(s):

count: The number of objects on *stack*.

Errors(s):

stackunderflow.

typecheck.

Description: Get the number of objects on *stack*.

Example(s):

```
onyx:0> (1 2) scout 1 sprint
2
onyx:0>
```

***stack* scouttomark count:**

Input(s):

stack: A stack object.

Output(s):

count: The depth of the topmost mark on *stack*.

Errors(s):

stackunderflow.

typecheck.

unmatchedmark.

Description: Get the depth of the topmost mark on *stack*.

Example(s):

```
onyx:0> (3 mark 1 0) scouttomark 1 sprint
2
onyx:0>
```

***stack* sdn -:**

Input(s):

stack: A stack object.

Output(s): None.

Errors(s):**stackunderflow.****typecheck.****Description:** Rotate the top three objects on *stack* down one position.**Example(s):**

```

onyx:0> (3 2 1 0) dup sdn pstack
(3 1 0 2)
onyx:1>

```

stack sdup -:**Input(s):****stack:** A stack object.**Output(s):** None.**Errors(s):****stackunderflow.****typecheck.****Description:** Duplicate the top object on *stack* and push it onto *stack*.**Example(s):**

```

onyx:0> (1) dup sdup 1 sprint
(1 1)
onyx:0>

```

string pattern search post pattern pre true:***string pattern search string false:*****Input(s):****string:** A string object.**pattern:** A string that represents a substring to search for in *string*.**Output(s):****post:** The substring of *string* that follows the match.**pattern:** The substring of *string* that matches the input *pattern*.**pre:** The substring of *string* that precedes the match.**true:** Success.**string:** The same object as the input *string*.**false:** Failure.**Errors(s):****stackunderflow.****typecheck.****Description:** Search for the first instance of *pattern* in *string*, and if found, return substrings that partition *string* into *pre*, *pattern*, and *post*.**Example(s):**

```

onyx:0> 'abcabc' 'ab' search pstack clear
true
'
'ab'
'cab'

```

```
onyx:0> 'abcabc' 'ca' search pstack clear
true
'ab'
'ca'
'bc'
onyx:0> 'abcabc' 'cb' search pstack clear
false
'abcabc'
onyx:0>
```

file offset seek -:**Input(s):**

file: A file object.

offset: Offset in bytes from the beginning of *file* to move the file position pointer to.

Output(s): None.

Errors(s):

ioerror.

stackunderflow.

typecheck.

Description: Move the file position pointer for *file* to *offset*.

Example(s):

```
onyx:0> '/tmp/foo' 'w+' open
onyx:1> dup 'Hello\n' write
onyx:1> dup 0 seek
onyx:1> readline pstack
false
'Hello'
onyx:2>
```

- self thread:

Input(s): None.

Output(s):

thread: A thread object that corresponds to the running thread.

Errors(s): None.

Description: Get a thread object for the running thread.

Example(s):

```
onyx:0> self 1 sprint
-thread-
onyx:0>
```

sock mesg flags send nsend:***sock mesg send nsend:*****Input(s):**

sock: A socket.

mesg: A message string.

flags: An array of flag names. The following flags are supported:

\$MSG_OOB
\$MSG_PEEK
\$MSG_WAITALL

Output(s):

nsend: Number of bytes of *mesg* actually sent.

Errors(s):

argcheck.
neterror.
stackunderflow.
typecheck.
unregistered.

Description: Send a message.

Example(s):

```
onyx:0> $AF_INET $SOCK_DGRAM socket
onyx:1> dup 'localhost' 7777 connect
onyx:1> dup 'hello' send
onyx:2> 1 sprint
5
onyx:1>
```

service serviceport port:**Input(s):**

service: A string that represents a network service name.

Output(s):

port: The port number corresponding to *service*, or 0 if the service is unknown.

Errors(s):

stackunderflow.
typecheck.

Description:**Example(s):**

```
onyx:0> 'ftp' serviceport 1 sprint
21
onyx:0>
```

gid setegid boolean:**Input(s):**

gid: A group ID.

Output(s):

boolean: If false, success, otherwise failure.

Errors(s):

rangecheck.
stackunderflow.
typecheck.

Description: Set the process's effective group ID to *gid*.

Example(s):

```
onyx:0> 1001 setegid 1 sprint
false
onyx:0> 0 setegid 1 sprint
true
onyx:0>
```

key val setenv -:**Input(s):**

key: A name object.

val: A value to associate with *key*.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Set an environment variable named *key* and associate *val* with it. If *val* is not a string, it is converted to a string using the **cvs** operator before the environment variable is set. A corresponding entry is also created in the envdict dictionary.

Example(s):

```
onyx:0> $foo 'foo' setenv
onyx:0> envdict $foo known 1 sprint
true
onyx:0> envdict $foo get 1 sprint
'foo'
onyx:0> $foo unsetenv
onyx:0> envdict $foo known 1 sprint
false
onyx:0>
```

uid seteuid boolean:**Input(s):**

uid: A user ID.

Output(s):

boolean: If false, success, otherwise failure.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Set the process's effective user ID to *uid*.

Example(s):

```
onyx:0> 1001 seteuid 1 sprint
false
onyx:0> 0 seteuid 1 sprint
true
onyx:0>
```

gid setgid boolean:**Input(s):**

gid: A group ID.

Output(s):

boolean: If false, success, otherwise failure.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Set the process's group ID to *gid*.

Example(s):

```
onyx:0> 1001 setgid 1 sprint
false
onyx:0> 0 setgid 1 sprint
true
onyx:0>
```

***file* setgstderr -:**

Input(s):

file: A file to set the global stderr to.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Set the global stderr to *file*. See Section 2.4 for standard I/O details.

Example(s):

```
onyx:0> '/tmp/stderr' 'w' open dup 0 setiobuf setgstderr
onyx:0> () {stderr 'Some text\n' write} thread join
onyx:0> '/tmp/stderr' 'r' open readline pop 1 sprint
'Some text'
onyx:0>
```

***file* setgstdin -:**

Input(s):

file: A file to set the global stdin to.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Set the global stdin to *file*. See Section 2.4 for standard I/O details.

Example(s): Under normal interactive operation, stdin is pushed onto estack during interpreter initialization and evaluated until EOF is reached. Therefore, changing stdin has no effect on the file descriptor already on estack. The following example recursively evaluates stdin after redefining it.

```
lawine:~> cat /tmp/stdin
1 2 3 pstack
lawine:~> onyx
```

```
Canonware Onyx, version 3.1.0.
onyx:0> '/tmp/stdin' 'r' open cvx setgstdin
onyx:0> () {stdin eval} thread join
3
2
1
onyx:0>
```

file setgstdout -:**Input(s):**

file: A file to set the global stdout to.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Set the global stdout to *file*. See Section 2.4 for standard I/O details.

Example(s): In the following example, the prompt continues to be printed, even though stdout has been redefined, because the prompt module was initialized to print to file descriptor 1. This demonstrates the only known exception in the stock Onyx interpreter where redefining stdout will not redirect output.

```
onyx:0> '/tmp/stdout' 'w' open dup 0 setiobuf setgstdout
onyx:0> () {'Some text\n' print} thread join
onyx:0> '/tmp/stdout' 'r' open readline pop 1 sprint
'Some text'
onyx:0>
```

file count setiobuf -:**Input(s):**

file: A file object.

count: The size in bytes to set the I/O buffer associated with *file* to.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Set the size of the I/O buffer associated with *file*.

Example(s):

```
onyx:0> stdout iobuf 1 sprint
512
onyx:0> stdout 0 setiobuf
onyx:0> stdout iobuf 1 sprint
0
onyx:0>
```

boolean setlocking -:**Input(s):**

boolean: A boolean to set the implicit locking mode to.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Set the current implicit locking mode. See Section 2.7.1 for implicit synchronization details.

Example(s):

```
onyx:0> currentlocking 1 sprint
false
onyx:0> true setlocking
onyx:0> currentlocking 1 sprint
true
onyx:0>
```

***file* boolean setnonblocking -:**

Input(s):

file: A file object.

boolean: Non-blocking mode to set *file* to.

Output(s): None.

Errors(s):

ioerror.

stackunderflow.

typecheck.

Description: Set non-blocking mode for *file* to *boolean*.

Example(s):

```
onyx:0> '/tmp/foo' 'w' open
onyx:1> dup nonblocking 1 sprint
false
onyx:1> dup true setnonblocking
onyx:1> dup nonblocking 1 sprint
true
onyx:1>
```

sock level optname optval setsockopt -:

sock optname optval setsockopt -:

Input(s):

sock: A socket.

level: Level at which to set the socket option. If not specified, \$SOL_SOCKET is used.

optname: Name of option to set the value of. The following option names are supported:

\$SO_DEBUG

\$SO_REUSEADDR

\$SO_REUSEPORT

\$SO_KEEPALIVE

\$SO_DONTROUTE

\$SO_BROADCAST

\$SO_OOINLINE

\$SO_SNDBUF

\$SO_RCVBUF

\$SO_SNDLOWAT

\$SO_RCVLOWAT

\$SO_TYPE

\$SO_ERROR: *optval* is an integer.

\$SO_LINGER: *optval* is a dictionary, and the following entries are defined:

\$on: Boolean.

\$time: Linger time in seconds.

\$SO_SNDTIMEO

\$SO_RCVTIMEO: *optval* is an integer, in nanoseconds.

optval: Value to associate with *optname*.

Output(s): None.

Errors(s):

argcheck.

stackunderflow.

typecheck.

unregistered.

Description: Set a socket option.

Example(s):

```
onyx:0> $AF_INET $SOCK_STREAM socket
onyx:1> dup $SO_OOINLINE sockopt 1 sprint
0
onyx:1> dup $SO_OOINLINE 1 setsockopt
onyx:1> dup $SO_OOINLINE sockopt 1 sprint
1
onyx:1>
```

***file* setstderr -:**

Input(s):

file: A file to set the calling thread's stderr to.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Set the thread's stderr to *file*. See Section 2.4 for standard I/O details.

Example(s):

```
onyx:0> '/tmp/stderr' 'w' open dup 0 setiobuf setstderr
onyx:0> stderr 'Some text\n' write
onyx:0> '/tmp/stderr' 'r' open readline pop 1 sprint
'Some text'
onyx:0>
```

***file* setstdin -:**

Input(s):

file: A file to set the calling thread's stdin to.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Set the thread's stdin to *file*. See Section 2.4 for standard I/O details.

Example(s): Under normal interactive operation, stdin is pushed onto estack during interpreter initialization and evaluated until EOF is reached. Therefore, changing stdin has no effect on the file descriptor already on estack. The following example recursively evaluates stdin after redefining it.

```
lawine:~> cat /tmp/stdin
1 2 3 pstack
lawine:~> onyx
Canonware Onyx, version 3.1.0.
onyx:0> '/tmp/stdin' 'r' open cvx setstdin
onyx:0> stdin eval
3
2
1
onyx:3>
```

***file* setstdout -:**

Input(s):

file: A file to set the calling thread's stdout to.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Set the thread's stdout to *file*. See Section 2.4 for standard I/O details.

Example(s): In the following example, the prompt continues to be printed, even though stdout has been redefined, because the prompt module was initialized to print to file descriptor 1. This demonstrates the only known exception in the stock Onyx interpreter where redefining stdout will not redirect output.

```
onyx:0> '/tmp/stdout' 'w' open dup 0 setiobuf setstdout
onyx:0> 'Some text\n' print
onyx:0> gstdout setstdout
onyx:0> '/tmp/stdout' 'r' open readline pop 1 sprint
'Some text'
onyx:0>
```

***uid* setuid boolean:**

Input(s):

uid: A user ID.

Output(s):

boolean: If false, success, otherwise failure.

Errors(s):

rangecheck.
stackunderflow.
typecheck.

Description: Set the process's user ID to *uid*.

Example(s):

```
onyx:0> 1001 setuid 1 sprint
false
onyx:0> 0 setuid 1 sprint
true
onyx:0>
```

***stack sexch* –:**

Input(s):

stack: A stack object.

Output(s): None.

Errors(s):

stackunderflow.
typecheck.

Description: Exchange the top two objects on *stack*.

Example(s):

```
onyx:0> (1 2 3) dup sexch pstack
(1 3 2)
onyx:1>
```

***– shift* –:**

Input(s):

a: An integer.

shift: An integer that represents a bitwise shift amount. Negative means right shift, and positive means left shift.

Output(s):

r: *a* shifted by *shift* bits.

Errors(s):

stackunderflow.
typecheck.

Description: Shift an integer bitwise.

Example(s):

```
onyx:0> 4 1 shift 1 sprint
8
onyx:0> 4 -1 shift 1 sprint
2
onyx:0>
```

***stack index sibdup* –:**

Input(s):

stack: A stack object.

index: Offset from bottom of *stack*, counting from 0, of the object to duplicate.

Output(s): None.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Create a duplicate of the object on *stack* that is at offset *index* from the bottom of *stack* and push it onto *stack*.

Example(s):

```
onyx:0> (3 2 1 0) dup 2 sibdup pstack
(3 2 1 0 1)
onyx:1>
```

stack index sibpop obj:

Input(s):

stack: A stack object.

index: Offset from bottom of *stack*, counting from 0, of the object to remove from *stack*.

Output(s):

obj: An object removed from *stack*.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Remove the *obj* from *stack* that is at offset *index* from the bottom of *stack*.

Example(s):

```
onyx:0> (0 1 2 3) dup 2 sibpop pstack
2
(0 1 3)
onyx:2>
```

stack index sidup -:

Input(s):

stack: A stack object.

index: Depth (count starts at 0) of the object to duplicate in *stack*.

Output(s): None.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Create a duplicate of the object on *stack* at depth *index* and push it onto *stack*.

Example(s):

```
onyx:0> (3 2 1 0) dup 2 sidup
onyx:1> 1 sprint
(3 2 1 0 2)
onyx:0>
```

condition* signal –:*Input(s):****condition:** A condition object.**Output(s):** None.**Errors(s):****stackunderflow.****typecheck.****Description:** Signal a thread that is waiting on *condition*. If there are no waiters, this operator has no effect.**Example(s):**

```

onyx:0> condition mutex dup lock ostack
onyx:3> {dup lock exch signal unlock}
onyx:4> thread 3 1 roll
onyx:3> dup 3 1 roll
onyx:4> wait unlock join
onyx:0>

```

a* sin *r*:*Input(s):****a:** An integer or real.**Output(s):****r:** Sine of *a* in radians.**Errors(s):****stackunderflow.****typecheck.****Description:** Return the sine of *a* in radians.**Example(s):**

```

onyx:0> 0 sin 1 sprint
0.000000e+00
onyx:0> 1.570796 sin 1 sprint
1.000000e+00
onyx:0> 0.7853982 sin 1 sprint
7.071068e-01
onyx:0>

```

stack* index sipop *obj*:*Input(s):****stack:** A stack object.**index:** Offset from top of *stack*, counting from 0, of the object to remove from *stack*.**Output(s):****obj:** An object removed from *stack*.**Errors(s):****rangecheck.****stackunderflow.****typecheck.****Description:** Remove the *obj* at *index* from *stack*.

Example(s):

```
onyx:0> (3 2 1 0) dup 2 sipop pstack
2
(3 1 0)
onyx:2>
```

stack count snbpop array:**Input(s):**

stack: A stack object.

count: Number of objects to pop off the bottom of *stack*.

Output(s):

array: An array of objects popped off the bottom of *stack*, with the same object ordering as when on *stack*.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Pop *count* objects off the bottom of *stack* and put them into an array.

Example(s):

```
onyx:0> (1 2 3 4) dup 2 snbpop pstack
[1 2]
(3 4)
onyx:2>
```

stack count sndn -:**Input(s):**

stack: A stack object.

count: Number of objects on *stack* to rotate down one position.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Rotate *count* objects on *stack* down one position.

Example(s):

```
onyx:0> (5 4 3 2 1 0) dup 4 sndn pstack
(5 4 2 1 0 3)
onyx:1>
```

stack count sndup -:**Input(s):**

stack: A stack object.

count: Number of objects on *stack* to duplicate.

Output(s): None.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Create duplicates of the top *count* objects on *stack*.

Example(s):

```
onyx:0> (3 2 1 0) dup 2 sndup pstack
(3 2 1 0 1 0)
onyx:1>
```

stack snip obj:

Input(s):

stack: A stack object.

Output(s):

obj: The object that was the second to top object on *stack*.

Errors(s):

stackunderflow.

typecheck.

Description: Remove the second to top object from *stack*.

Example(s):

```
onyx:0> (2 1 0) dup snip pstack
1
(2 0)
onyx:2>
```

stack count snpop array:

Input(s):

stack: A stack object.

count: Number of objects to pop off of *stack*.

Output(s):

array: An array of objects popped off of *stack*, with the same object ordering as when on *stack*.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Pop *count* objects off of *stack* and put them into an array.

Example(s):

```
onyx:0> (1 2 3 4) dup 2 snpop pstack
[3 4]
(1 2)
onyx:2>
```

stack count snup -:

Input(s):

stack: A stack object.

count: Number of objects on *stack* to rotate up one position.

Output(s): None.

Errors(s):

rangecheck.
stackunderflow.
typecheck.

Description: Rotate *count* objects on *stack* up one position.

Example(s):

```
onyx:0> (5 4 3 2 1 0) dup 4 snup pstack
(5 4 0 3 2 1)
onyx:1>
```

family type proto socket sock:

family type socket sock:

Input(s):

family: The name of a socket address family, either `$AF_INET` or `$AF_LOCAL`.
type: The name of a socket type, either `$SOCK_STREAM` or `$SOCK_DGRAM`.
proto: The name of a socket protocol. This argument is not useful, given the current limited choice of address families.

Output(s):

sock: A socket.

Errors(s):

argcheck.
invalidaccess.
stackunderflow.
typecheck.
unregistered.

Description: Create a socket.

Example(s):

```
onyx:0> $AF_INET $SOCK_STREAM socket
onyx:1> $AF_LOCAL $SOCK_DGRAM socket
onyx:2>
```

family type proto socketpair sock sock:

family type socketpair sock sock:

Input(s):

family: The name of a socket address family, either `$AF_INET` or `$AF_LOCAL`.
type: The name of a socket type, either `$SOCK_STREAM` or `$SOCK_DGRAM`.
proto: The name of a socket protocol. This argument is not useful, given the current limited choice of address families.

Output(s):

sock: A connected socket. There are no functional differences between the two sockets that are returned.

Errors(s):

argcheck.
invalidaccess.
stackunderflow.
typecheck.

unregistered.

Description: Create a pair of sockets that are connected to each other.

Example(s):

```
onyx:0> $AF_LOCAL $SOCK_STREAM socketpair
onyx:2> pstack
-file-
-file-
onyx:2>
```

sock sockname dict:

Input(s):

sock: A socket.

Output(s):

dict: A dictionary of information about *sock*. Depending on the socket family, the following entries may exist:

family: Socket family.

address: IPv4 address.

port: IPv4 port.

path: Unix-domain socket path.

Errors(s):

argcheck.

ioerror.

neterror.

stackunderflow.

typecheck.

unregistered.

Description: Get information about *sock*.

Example(s):

```
onyx:0> $AF_INET $SOCK_STREAM socket
onyx:1> dup 'localhost' bindsocket
onyx:1> dup sockname 1 sprint
<$family $AF_INET $address 2130706433 $port 33745>
onyx:1> close
onyx:0> $AF_LOCAL $SOCK_STREAM socket
onyx:1> dup '/tmp/socket' bindsocket
onyx:1> dup sockname 1 sprint
<$family $AF_LOCAL $path '/tmp/socket'>
onyx:1>
```

sock level optname sockopt optval:

sock optname sockopt optval:

Input(s):

sock: A socket.

level: Level at which to get the socket option. If not specified, \$SOL_SOCKET is used.

optname: Name of option to get the value of. The following option names are supported:

\$SO_DEBUG**\$SO_REUSEADDR****\$SO_REUSEPORT****\$SO_KEEPAVIVE****\$SO_DONTROUTE****\$SO_BROADCAST****\$SO_OOBINLINE****\$SO_SNDBUF****\$SO_RCVBUF****\$SO_SNDLOWAT****\$SO_RCVLOWAT****\$SO_TYPE****\$SO_ERROR:** *optval* is an integer.**\$SO_LINGER:** *optval* is a dictionary, and the following entries are defined:**\$on:** Boolean.**\$time:** Linger time in seconds.**\$SO_SNDTIMEO****\$SO_RCVTIMEO:** *optval* is an integer, in nanoseconds.**Output(s):****optval:** Value associated with *optname*.**Errors(s):****argcheck.****stackunderflow.****typecheck.****unregistered.****Description:** Get a socket option.**Example(s):**

```

onyx:0> $AF_INET $SOCK_STREAM socket
onyx:1> dup $SO_SNDBUF sockopt 1 sprint
16384
onyx:1>

```

stack sover* --:*Input(s):****stack:** A stack object.**Output(s):** None.**Errors(s):****stackunderflow.****typecheck.****Description:** Create a duplicate of the second object on *stack* and push it onto *stack*.**Example(s):**

```

onyx:0> (2 1 0) dup sover pstack
(2 1 0 1)
onyx:1>

```

stack spop obj:**Input(s):**

stack: A stack object.

Output(s):

obj: The object that was popped off of *stack*.

Errors(s):

stackunderflow.

typecheck.

Description: Pop an object off of *stack* and push it onto *ostack*.

Example(s):

```
onyx:0> (1 2) dup spop
onyx:2> pstack
2
(1)
onyx:2>
```

obj depth sprint -:**Input(s):**

obj: An object to print syntactically.

depth: Maximum recursion depth.

Output(s): None.

Errors(s):

ioerror.

stackunderflow.

typecheck.

Description: Syntactically print *obj*. See Section 2.9.8 for printing details.

Example(s):

```
onyx:0> [1 [2 3] 4]
onyx:1> dup 0 sprint
-array-
onyx:1> dup 1 sprint
[1 -array- 4]
onyx:1> dup 2 sprint
[1 [2 3] 4]
onyx:1>
```

obj depth sprints string:**Input(s):**

obj: An object to print syntactically.

depth: Maximum recursion depth.

Output(s):

string: A syntactical string representation of *obj*. See Section 2.9.8 for printing details.

Errors(s):

stackunderflow.

typecheck.

Description: Create a syntactical string representation of *obj*.

Example(s):

```
onyx:0> [1 [2 3] 4]
onyx:1> dup 0 sprints print '\n' print flush
-array-
onyx:1> dup 1 sprints print '\n' print flush
[1 -array- 4]
onyx:1> dup 2 sprints print '\n' print flush
[1 [2 3] 4]
onyx:1>
```

– **sprintsdict *dict*:**

Input(s): None.

Output(s):

dict: A dictionary.

Errors(s): None.

Description: Get sprintsdict. See Section 2.9.8 for details on sprintsdict.

Example(s):

```
onyx:0> sprintsdict 0 sprint
-dict-
onyx:0>
```

stack obj spush –:

Input(s):

stack: A stack object.

obj: An object.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Push *obj* onto *stack*.

Example(s):

```
onyx:0> (0) dup 1 spush
onyx:1> pstack
(0 1)
onyx:1>
```

a sqrt r:

Input(s):

a: A non-negative integer or real.

Output(s):

r: Square root of *a*.

Errors(s):

rangecheck.

stackunderflow.

typecheck.

Description: Return the square root of a .

Example(s):

```
onyx:0> 4 sqrt 1 sprint
2.000000e+00
onyx:0> 2.0 sqrt 1 sprint
1.414214e+00
onyx:0>
```

seed srand -:

Input(s):

seed: A non-negative integer.

Output(s): None.

Errors(s):

rangecheck.
stackunderflow.
typecheck.

Description: Seed the pseudo-random number generator with *seed*.

Example(s):

```
onyx:0> 5 srand
onyx:0>
```

stack count amount sroll -:

Input(s):

stack: A stack object.

count: Number of objects to roll in *stack*.

amount: Amount by which to roll. If positive, roll upward. If negative, roll downward.

Output(s): None.

Errors(s):

rangecheck.
stackunderflow.
typecheck.

Description: Roll the top *count* objects on *stack* by *amount* positions. A positive *amount* indicates an upward roll, whereas a negative *amount* indicates a downward roll.

Example(s):

```
onyx:0> (3 2 1 0)
onyx:1> dup 3 1 sroll pstack
(3 0 2 1)
onyx:1> dup 3 -2 sroll pstack
(3 1 0 2)
onyx:1> dup 4 0 sroll pstack
(3 1 0 2)
onyx:1>
```

stack amount srot -:

Input(s):

stack: One or more objects.

amount: Number of positions to rotate *stack* upward. A negative value causes downward rotation.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Rotate *stack* up *count* positions.

Example(s):

```
onyx:0> (1 2 3 4 5) dup 2 srot 1 sprint
(4 5 1 2 3)
onyx:0> (1 2 3 4 5) dup -2 srot 1 sprint
(3 4 5 1 2)
onyx:0>
```

– **stack stack:**

Input(s): None.

Output(s):

stack: An empty stack object.

Errors(s): None.

Description: Create a new stack object and push it onto ostack.

Example(s):

```
onyx:0> stack
onyx:1> pstack
()
```

obj start –:

Input(s):

obj: An object.

Output(s): None.

Errors(s):

stackunderflow.

Description: Evaluate *obj*. This operator provides a context that silently terminates execution stack unwinding due to the **exit**, **quit**, and **stop** operators.

Example(s):

```
onyx:0> stdin cvx start
onyx:0> quit
onyx:0>
```

file/filename status dict:

Input(s):

file: A file object.

filename: A string that represents a filename.

Output(s):

dict: A dictionary that contains the following entries:

dev: Inode's device.

ino: Inode's number.
mode: Inode permissions.
nlink: Number of hard links.
uid: User ID of the file owner.
gid: Group ID of the file owner.
rdev: Device type.
size: File size in bytes.
atime: Time of last access, in nanoseconds since the epoch.
mtime: Time of last modification, in nanoseconds since the epoch.
ctime: Time of last file status change, in nanoseconds since the epoch.
blksize: Optimal block size for I/O.
blocks: Number of blocks allocated.

Errors(s):

invalidfileaccess.
ioerror.
stackunderflow.
typecheck.
unregistered.

Description: Get status information about a file.

Example(s):

```
onyx:0> `/tmp' status 1 sprint
<$dev 134405 $ino 2 $mode 17407 $nlink 5 $uid 0 $gid 0 $rdev 952 $size 3584
$atime 994883041000000000 $mtime 994883041000000000 $ctime 994883041000000000
$blksize 0 $blocks 8>
onyx:0>
```

- stderr file:

Input(s): None.

Output(s):

file: A file object corresponding to the calling thread's stderr.

Errors(s): None.

Description: Get the thread's stderr. See Section 2.4 for standard I/O details.

Example(s):

```
onyx:0> stderr pstack
-file-
onyx:1>
```

- stdin file:

Input(s): None.

Output(s):

file: A file object corresponding to the calling thread's stdin.

Errors(s): None.

Description: Get the thread's stdin. See Section 2.4 for standard I/O details.

Example(s):

```
onyx:0> stdin pstack
-file-
onyx:1>
```

– stdout *file*:

Input(s): None.

Output(s):

file: A file object corresponding to the calling thread's stdout.

Errors(s): None.

Description: Get the thread's stdout. See Section 2.4 for standard I/O details.

Example(s):

```
onyx:0> stdout pstack
-file-
onyx:1>
```

– stop –:

Input(s): None.

Output(s): None.

Errors(s): None.

Description: Unwind the execution stack to the innermost **stopped** or **start** context.

Example(s):

```
onyx:0> {stop} stopped 1 sprint
true
onyx:0>
```

***obj* stopped *boolean*:**

Input(s):

obj: An object to evaluate.

Output(s):

boolean: True if stop operator was executed, false otherwise.

Errors(s):

invalidexit.

stackunderflow.

Description: Evaluate *obj*. This operator provides a context that terminates execution stack unwinding due to the **stop**. It will also terminate execution stack unwinding due to the **exit** operator, but will throw an **invalidexit** error, then do the equivalent of calling **quit**.

Example(s):

```
onyx:0> {stop} stopped 1 sprint
true
onyx:0> {} stopped 1 sprint
false
onyx:0>
```

***length* string *string*:**

Input(s):

length: Non-negative number of bytes.

Output(s):

string: A string of *length* bytes.

Errors(s):

rangecheck.
stackunderflow.
typecheck.

Description: Create a string of *length* bytes. The bytes are initialized to 0.

Example(s):

```
onyx:0> 3 string 1 sprint
'\x00\x00\x00'
onyx:0>
onyx:0> 0 string 1 sprint
''
onyx:0>
```

stack stuck -:

Input(s):

stack: A stack object.

Output(s): None.

Errors(s):

stackunderflow.
typecheck.

Description: Tuck duplicate of top object on *stack* under second object on *stack*.

Example(s):

```
onyx:0> (2 1 0) dup stuck pstack
(2 0 1 0)
onyx:1>
```

a b sub r:

Input(s):

a: An integer or real.
b: An integer or real.

Output(s):

r: The value of *b* subtracted from *a*.

Errors(s):

stackunderflow.
typecheck.

Description: Subtract *b* from *a* and return the result.

Example(s):

```
onyx:0> 5 3 sub 1 sprint
2
onyx:0> -3 4 sub 1 sprint
-7
onyx:0> 5.1 1.1 sub 1 sprint
4.000000e+00
onyx:0> 5 1.0 sub 1 sprint
4.000000e+00
onyx:0> -3.0 4.1 sub 1 sprint
-7.100000e+00
onyx:0>
```


stack sunder -:**Input(s):**

stack: A stack object.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Create a duplicate of the second object on *stack* and put it under the top object on *stack*.

Example(s):

```
onyx:0> (2 1 0) dup sunder pstack
(2 1 1 0)
onyx:1>
```

stack sup -:**Input(s):**

stack: A stack object.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Rotate the top three objects on *stack* up one position.

Example(s):

```
onyx:0> (3 2 1 0) dup sup pstack
(3 0 2 1)
onyx:1>
```

filename linkname symlink -:**Input(s):**

filename: A string that represents a filename.

linkname: A string that represents a filename.

Output(s): None.

Errors(s):

invalidfileaccess.

ioerror.

stackunderflow.

typecheck.

undefinedfilename.

unregistered.

Description: Create a symbolic link from *linkname* to *filename*.

Example(s):

```
onyx:0> '/tmp/foo' 'w' open
onyx:1> dup 'Hello\n' write
onyx:1> dup flushfile
onyx:1> close
```

```
onyx:0> `/tmp/foo' `/tmp/bar' symlink
onyx:0> `/tmp/bar' `r' open
onyx:1> readline
onyx:2> pstack
false
`Hello'
onyx:2>
```

args* system *status*:*Input(s):**

args: An array of strings. The first string in *args* is the path of the program to invoke, and any additional array elements are passed as command line arguments to the invoked program.

Output(s):

status: Exit code of terminated process. A negative value indicates that the process was terminated by a signal (use the **neg** operator to get the signal number), and a non-negative value is the exit code of a program that terminated normally.

Errors(s):

rangecheck.
stackunderflow.
typecheck.

Description: Execute a program as a child process and wait for it to terminate.

Example(s):

```
onyx:0> ['/usr/bin/which' `onyx'] system
/usr/local/bin/onyx
onyx:1> 1 sprint
0
onyx:0>
```

– *systemdict dict*:

Input(s): None.

Output(s):

dict: A dictionary.

Errors(s): None.

Description: Get *systemdict*. See Section 2.9.9 for details on *systemdict*.

Example(s):

```
onyx:0> systemdict 0 sprint
-dict-
onyx:0>
```

file* tell *offset*:*Input(s):**

fil: A file object.

Output(s):

offset: Offset of the file position pointer for *file*.

Errors(s):

ioerror.

stackunderflow.

typecheck.

Description: Get the file position pointer offset for *file*.

Example(s):

```
onyx:0> `/tmp/foo' `w+' open
onyx:1> dup tell 1 sprint
0
onyx:1> dup `Hello\n' write
onyx:1> dup tell 1 sprint
6
onyx:1>
```

file/filename flag test boolean:

Input(s):

file: A file object.

filename: A string that represents a filename.

flag: A single-character string that represents the test to do on *file* or *filename*:

- 'b':** Block special device?
- 'c':** Character special device?
- 'd':** Directory?
- 'e':** Exists?
- 'f':** Regular file?
- 'g':** Setgid?
- 'k':** Sticky?
- 'p':** Named pipe?
- 'r':** Readable?
- 's':** Size greater than 0?
- 't':** tty?
- 'u':** Setuid?
- 'w':** Write bit set?
- 'x':** Executable bit set?
- 'L':** Symbolic link?
- 'O':** Owner matches effective uid?
- 'G':** Group matches effective gid?
- 'S':** Socket?

Output(s):

boolean: If true, the test evaluated to true; false otherwise.

Errors(s):

invalidfileaccess.

ioerror.

rangecheck.

stackunderflow.

typecheck.

unregistered.

Description: Test a file for an attribute.

Example(s):

```
onyx:0> '/blah' 'e' test 1 sprint
false
onyx:0> '/tmp' 'e' test 1 sprint
true
onyx:0>
```

stack entry thread thread:

Input(s):

stack: A stack that contains the contents for the new thread's ostack.

entry: An initial object to execute in the new thread.

Output(s):

thread: A thread object that corresponds to the new thread.

Errors(s):

stackunderflow.

typecheck.

Description: Create and run a new thread.

Example(s):

```
onyx:0> (1 2) {add 1 sprint} thread join 'Done\n' print flush
3
Done
onyx:0>
```

thread threadddstack stack:

Input(s):

thread: A thread object.

Output(s):

stack: The dictionary stack belonging to *thread*.

Errors(s):

stackunderflow.

typecheck.

Description: Get a reference to the dictionary stack belonging to *thread*.

Example(s):

```
onyx:0> self threadddstack 1 sprint
(-dict- -dict- -dict- -dict-)
onyx:0>
```

thread threadddstack stack:

Input(s):

thread: A thread object.

Output(s):

stack: The execution stack belonging to *thread*.

Errors(s):

stackunderflow.

typecheck.

Description: Get a reference to the execution stack belonging to *thread*.

Example(s):

```
onyx:0> self threadestack 1 sprint
(-file- -array- --eval-- --ifelse-- -array- --for-- -array-)
onyx:0>
```

thread threadistack stack:

Input(s):

thread: A thread object.

Output(s):

stack: The index stack belonging to *thread*.

Errors(s):

stackunderflow.

typecheck.

Description: Get a reference to the index stack belonging to *thread*.

Example(s):

```
onyx:0> self threadistack 1 sprint
(0 0 0 0 7 0 3)
onyx:0>
```

thread threadostack stack:

Input(s):

thread: A thread object.

Output(s):

stack: The operand stack belonging to *thread*.

Errors(s):

stackunderflow.

typecheck.

Description: Get a reference to the operand stack belonging to *thread*.

Example(s):

```
onyx:0> self threadostack 1 sprint
(-stack- -stack- -stack- -stack-)
onyx:0>
```

- threadsdict *dict*:

Input(s): None.

Output(s):

dict: A dictionary. Each key is a thread reference. By default, each value is null, but this need not be so, and the value can be redefined for debugging purposes.

Errors(s): None.

Description: Get a dictionary containing references to all threads.

Example(s):

```
onyx:0> threadsdict 1 sprint
<-thread- null>
onyx:0>
```

name throw obj:**Input(s):**

name: The name of an error.

Output(s):

obj: The object that was being executed when the error was thrown.

Errors(s):

stackunderflow.

typecheck.

undefined.

Description: Throw an error, using the following steps:

1. Set `newerror` in the `currenterror` dictionary to true.
2. Set `errorname` in the `currenterror` dictionary to *name*.
3. Set `ostack`, `dstack`, `estack`, and `istack` in the `currenterror` dictionary to be current stack snapshots.
4. Push the object that was being executed before `throw` was called onto `ostack`.
5. If there is an error handler in the `errordict` dictionary that corresponds to *name*, evaluate it. Otherwise, evaluate `errordict`'s **handleerror** and **stop** operators.

Example(s):

```
onyx:0> $unregistered throw
Error $unregistered
ostack: ( )
dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..1):
0:      -file-
1:      --start--
onyx:1> pstack
-file-
onyx:1>
```

condition mutex timeout timedwait boolean:**Input(s):**

condition: A condition object.

mutex: A mutex object that this thread currently owns.

timeout: Minimum number of nanoseconds to wait for *condition*.

Output(s):

boolean: If false, success, otherwise timeout.

Errors(s):

stackunderflow.

typecheck.

Description: Wait on *condition* for at least *timeout* nanoseconds. *mutex* is atomically released when the current thread blocks, then acquired again before the current thread runs again. Using a mutex that the current thread does not own will result in undefined behavior (likely crash).

Example(s):

```
onyx:0> condition mutex dup lock ostack
onyx:3> {dup lock exch signal unlock}
```

```
onyx:4> thread 3 1 roll
onyx:3> dup 3 1 roll
onyx:4> 1000000000 timedwait 1 sprint unlock join
false
onyx:0> mutex condition 1 idup dup lock 1000000000 timedwait 1 sprint unlock
true
onyx:0>
```

file/string token false:

file/string token file/substring obj true:

Input(s):

file: A file that is used as onyx source code to scan a token from.

string: A string that is used as onyx source code to scan a token from.

Output(s):

file: The same file object that was passed in.

substring: The remainder of *string* after scanning a token.

obj: An object that was constructed by scanning a token.

false/true: If true, a token was successfully scanned, false otherwise.

Errors(s):

stackunderflow.

syntaxerror.

typecheck.

undefined.

Description: Scan a token from a file or string, using onyx syntax rules. If a token is followed by whitespace, one character of whitespace is consumed when the token is scanned.

Example(s):

```
onyx:0> '1 2' token pstack clear
true
1
'2'
onyx:0> 'foo' token pstack clear
true
foo
''
onyx:0> 'foo ' token pstack clear
true
foo
''
onyx:0> 'foo  ' token pstack clear
true
foo
''
onyx:0> 'foo$bar' token pstack clear
true
foo
'$bar'
onyx:0> 'foo{' token pstack clear
true
```

```

foo
'{'
onyx:0> ' ' token pstack clear
false
onyx:0>

```

a trunc r:**Input(s):****a:** An integer or real.**Output(s):****r:** Integer created from *a* by discarding the fractional portion.**Errors(s):****stackunderflow.****typecheck.****Description:** Discard the fractional portion of *a* to create an integer, and return the result.**Example(s):**

```

onyx:0> -1.51 trunc 1 sprint
-1
onyx:0> -1.49 trunc 1 sprint
-1
onyx:0> 0 trunc 1 sprint
0
onyx:0> 1.49 trunc 1 sprint
1
onyx:0> 1.51 trunc 1 sprint
1
onyx:0>

```

file length truncate -:**Input(s):****file:** A file object.**length:** New length for *file*.**Output(s):** None.**Errors(s):****ioerror.****rangecheck.****stackunderflow.****typecheck.****Description:** Set the length of *file* to *length*. If this causes the file to grow, the appended bytes will have the value zero.**Example(s):**

```

onyx:0> '/tmp/foo' 'w+' open
onyx:1> dup 'Hello\n' write
onyx:1> dup flushfile
onyx:1> dup 0 seek
onyx:1> dup 10 string read
onyx:3> pop 1 sprint

```



```
`Hello\n`
onyx:1> dup 3 truncate
onyx:1> dup 0 seek
onyx:1> dup 10 string read
onyx:3> pop 1 sprint
`Hel`
onyx:1>
```

– **true** *true*:

Input(s): None.

Output(s):

true: The boolean value true.

Errors(s): None.

Description: Return true.

Example(s):

```
onyx:0> true 1 sprint
true
onyx:0>
```

mutex trylock *boolean*:

Input(s):

mutex: A mutex object.

Output(s):

boolean: If false, *mutex* was successfully acquired. Otherwise the mutex acquisition failed.

Errors(s):

stackunderflow.

typecheck.

Description: Try to acquire *mutex*, but return a failure immediately if *mutex* cannot be acquired, rather than blocking.

Example(s):

```
onyx:0> mutex dup
onyx:2> trylock 1 sprint
false
onyx:1> trylock 1 sprint
true
onyx:0>
```

a b tuck *b a b*:

Input(s):

a: An object.

b: An object.

Output(s):

:

Errors(s):

stackunderflow.

typecheck.

Description: Create a duplicate of the top object on ostack and put it under the second object on ostack.

Example(s):

```
onyx:0> 'a' 'b' 'c'
oonyx:3> tuck pstack
'c'
'b'
'c'
'a'
onyx:4>
```

obj type name:

Input(s):

obj: An object.

Output(s):

name: An executable name that corresponds to the type of *obj*:

array: arraytype.
boolean: booleantype.
condition: conditiontype.
dict: dicttype.
file: filetype.
fino: finotype.
hook: hooktype.
integer: integertype.
mark: marktype.
mutex: mutextype.
name: nametype.
null: nulltype.
operator: operatortype.
pmark: pmarktype.
stack: stacktype.
string: stringtype.
thread: threadtype.

Errors(s):

stackunderflow.

Description: Get a name that represent the type of *obj*.

Example(s):

```
onyx:0> true type 1 sprint
booleantype
onyx:0>
```

– uid uid:

Input(s): None.

Output(s):

uid: Process's user ID.

Errors(s): None.

Description: Get the process's user ID.

Example(s):

```
onyx:0> uid 1 sprint
1001
onyx:0>
```

nmask umask omask:

Input(s):

nmask: Value to set umask to.

Output(s):

omask: Old umask.

Errors(s):

stackunderflow.

typecheck.

Description: Set the process's umask to *nmask* and return the old umask.

Example(s):

```
onyx:0> 8@777 umask <$b 8 $w 3 $p '0'> output '\n' print flush
022
onyx:0>
```

dict key undef -:

Input(s):

dict: A dictionary.

val: A key in *dict* to undefine.

Output(s): None

Errors(s):

stackunderflow.

typecheck.

Description: If *key* is defined in *dict*, undefine it.

Example(s):

```
onyx:0> $foo 'foo' def
onyx:0> currentdict $foo undef
onyx:0> currentdict $foo undef
onyx:0>
```

a b under a a b:

Input(s):

a: An object.

b: An object.

Output(s):

a: An object.

b: An object.

Errors(s):

stackunderflow.

Description: Create a duplicate of the second object on ostack and put it under the top object on ostack.

Example(s):

```

onyx:0> 0 1 2 under pstack
2
1
1
0
onyx:4>

```

filename* unlink -:*Input(s):**

filename: A string that represents a filename.

Output(s): None.

Errors(s):

invalidfileaccess.
ioerror.
stackunderflow.
typecheck.
undefinedfilename.
unregistered.

Description: Unlink *filename*.

Example(s):

```

onyx:0> '/tmp/foo' 'w' open
onyx:1> dup 'Hello\n' write
onyx:1> dup flushfile
onyx:1> close
onyx:0> '/tmp/foo' unlink
onyx:0> '/tmp/foo' 'r' open
Error $invalidfileaccess
ostack: ('/tmp/foo' 'r')
dstack: (-dict- -dict- -dict- -dict-)
estack/istack trace (0..2):
0:      --open--
1:      -file-
2:      --start--
onyx:3>

```

mutex* unlock -:*Input(s):**

mutex: A mutex object.

Output(s): None.

Errors(s):

stackunderflow.
typecheck.

Description: Unlock *mutex*. Unlocking a mutex that the running thread does not own will result in undefined behavior (likely crash).

Example(s):

```

onyx:0> mutex dup lock unlock
onyx:0>

```

key unsetenv –:

Input(s):

key: A name object.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Unset *key* in the environment and in the envdict dictionary, if *key* is defined.

Example(s):

```
onyx:0> $foo 'foo' setenv
onyx:0> envdict $foo known 1 sprint
true
onyx:0> envdict $foo get 1 sprint
'foo'
onyx:0> $foo unsetenv
onyx:0> envdict $foo known 1 sprint
false
onyx:0>
```

proc cond until –:

Input(s):

proc: An object to be repeatedly evaluated.

cond: An object that, when evaluated, places a boolean on ostack.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Repeatedly evaluate *proc* and *cond*, terminating the first time that *cond* places false on ostack. This operator supports the **exit** operator.

Example(s):

```
onyx:0> 0 {inc dup 1 sprint}{dup 3 lt} until pop
1
2
3
onyx:0> 0 {inc dup 1 sprint exit}{dup 3 lt} until pop
1
onyx:0>
```

a b c up c a b:

Input(s):

a: An object.

b: An object.

c: An object.

Output(s):

c: An object.

a: An object.

b: An object.

Errors(s):

stackunderflow.

Description: Rotate the top three objects on ostack up one position.

Example(s):

```
onyx:0> 'a' 'b' 'c' 'd' up pstack
'c'
'b'
'd'
'a'
onyx:4>
```

– **userdict *dict*:**

Input(s): None.

Output(s):

dict: A dictionary.

Errors(s): None.

Description: Get userdict. See Section 2.9.12 for details on userdict.

Example(s):

```
onyx:0> userdict 1 sprint
<>
onyx:0>
```

– **version *string*:**

Input(s): None.

Output(s):

string: A string that contains the version name.

Errors(s): None.

Description: Get the version string. The string returned is a reference to the original version string.

Example(s):

```
onyx:0> version pstack
'1.0.0'
onyx:1>
```

condition mutex wait –:

Input(s):

condition: A condition object.

mutex: A mutex object that this thread currently owns.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Wait on *condition*. *mutex* is atomically released when the current thread blocks, then acquired again before the current thread runs again. Using a mutex that the current thread does not own will result in undefined behavior (likely crash).

Example(s):

```

onyx:0> condition mutex dup lock ostack
onyx:3> {dup lock exch signal unlock}
onyx:4> thread 3 1 roll
onyx:3> dup 3 1 roll
onyx:4> wait unlock join
onyx:0>

```

pid* waitpid status:*Input(s):**

pid: Process identifier.

Output(s):

status: Exit code of terminated process. A negative value indicates that the process was terminated by a signal (use the **neg** operator to get the signal number), and a non-negative value is the exit code of a program that terminated normally.

Errors(s):

stackunderflow.

typecheck.

Description: Wait for the process with process ID *pid* to exit.

Example(s):

```

onyx:0> ['/bin/date'] forkexec dup 1 sprint waitpid 1 sprint
6516
Sat Jul 13 20:47:54 PDT 2002
0
onyx:0>

```

key* where false:**key* where dict true:****Input(s):**

key: A key to search for in dstack.

Output(s):

dict: The topmost dictionary in dstack that contains a definition for *key*.

false/true: If false, no definition of *key* was found in dstack. Otherwise *dict* is the topmost dictionary in dstack that contains a definition for *key*.

Errors(s):

stackunderflow.

Description: Get the topmost dictionary in dstack that defines *key*.

Example(s):

```

onyx:0> $foo where pstack clear
false
onyx:0> $threaddict where pstack clear
true
<$threaddict -dict- $userdict -dict- $currenterror -dict- $errordict -dict-
$resume --stop-->
onyx:0>

```

***cond proc while* -:**

Input(s):

cond: An object that, when evaluated, places a boolean on ostack.

proc: An object to be repeatedly evaluated.

Output(s): None.

Errors(s):

stackunderflow.

typecheck.

Description: Repeatedly evaluate *cond* and *proc*, terminating the first time that *cond* places false on ostack. This operator supports the **exit** operator.

Example(s):

```
onyx:0> 0 {dup 3 lt}{inc dup 1 sprint} while pop
1
2
3
onyx:0> 0 {dup 3 lt}{inc dup 1 sprint exit} while pop
1
onyx:0>
```

file integer/string write false:

file integer/string write integer/substring true:

Input(s):

file: A file object.

integer: An integer that represents an ascii character value.

string: A string object.

Output(s):

false: Successful complete write.

integer: The *integer* that was passed in.

substring: The substring of *string* that was not written.

true: Successful partial write.

Errors(s):

ioerror.

stackunderflow.

typecheck.

Description: Write *integer* or *string* to *file*. Partial writes can only happen for non-blocking files.

Example(s):

```
onyx:0> '/tmp/foo' 'w+' open
onyx:1> dup 'Hello\n' write pop
onyx:1> dup 0 seek
onyx:1> dup readline 1 sprint 1 sprint
false
'Hello'
onyx:1>
```

obj xcheck boolean:

Input(s):

obj: An object.

Output(s):

boolean: True if *obj* has the executable or evaluable attribute, false otherwise.

Errors(s):

stackunderflow.

Description: Check *obj* for executable or evaluable attribute.

Example(s):

```
onyx:0> {1 2 3} xcheck 1 sprint
true
onyx:0> [1 2 3] xcheck 1 sprint
false
onyx:0>
```

a b xor r:

Input(s):

a: An integer or boolean.

b: The same type as *a*.

Output(s):

r: If *a* and *b* are integers, their bitwise exclusive or, otherwise their logical exclusive or.

Errors(s):

stackunderflow.

typecheck.

Description: Return the bitwise exclusive or of two integers, or the logical exclusive or of two booleans.

Example(s):

```
onyx:0> true false xor 1 sprint
true
onyx:0> true true xor 1 sprint
false
onyx:0> 5 3 xor 1 sprint
6
onyx:0>
```

- yield -:

Input(s): None.

Output(s): None.

Errors(s): None.

Description: Voluntarily yield the processor, so that another thread or process may be run.

Example(s):

```
onyx:0> 0 100000 {1 add yield} repeat 1 sprint
100000
onyx:0>
```

2.9.10 threaddict

Each thread has its own threaddict, which is not shared with any other threads. threaddict is meant to be used for thread-specific definitions that would otherwise go in systemdict.

Table 2.11: threaddict summary

Input(s)	Op/Proc/Var	Output(s)	Description
–	threaddict	dict	Get threaddict.
–	userdict	dict	Get userdict.
–	currenterror	dict	Get currenterror.
–	errordict	dict	Get errordict.

– currenterror dict:**Input(s):** None.**Output(s):****dict:** The currenterror dictionary. See Section 2.9.1 for details on currenterror.**Errors(s):** None.**Description:** Get currenterror.**Example(s):**

```

onyx:0> currenterror 0 sprint
-dict-
onyx:0>

```

– errordict dict:**Input(s):** None.**Output(s):****dict:** The errordict dictionary. See Section 2.9.3 for details on errordict.**Errors(s):** None.**Description:** Get errordict.**Example(s):**

```

onyx:0> errordict 0 sprint
-dict-
onyx:0>

```

– threaddict dict:**Input(s):** None.**Output(s):****dict:** The threaddict dictionary.**Errors(s):** None.**Description:** Get threaddict.**Example(s):**

```

onyx:0> threaddict 0 sprint
-dict-
onyx:0>

```

– userdict dict:**Input(s):** None.**Output(s):**

dict: The userdict dictionary. See Section 2.9.12 for details on userdict.

Errors(s): None.

Description: Get userdict.

Example(s):

```
onyx:0> userdict 1 sprint
<>
onyx:0>
```

2.9.11 threaddict

There is one entry in threaddict for each thread. The key is the thread, and the value is null by default. The value can be safely changed, which can be useful when debugging. However, the key must not be changed, or garbage collection will trigger a horrible death, since the root set will not be complete.

2.9.12 userdict

Each thread has its own userdict, which is not shared with any other threads. userdict is meant to be used for general storage of definitions that do not need to be shared among threads. userdict starts out empty when a thread is created.

Chapter 3

The onyx program

onyx is a stand-alone Onyx interpreter, with an integrated command line editor. The Onyx language is documented in a separate chapter, so this chapter documents only the differences from the main Onyx language documentation.

3.1 Usage

onyx -h

onyx -V

onyx -e <expr>

onyx <file> [<args>]

3.1.1 Options

-e <expr>: Execute <expr> as Onyx code.

-h: Display usage information and exit.

-V: Display the version number and exit.

3.2 Environment variables

ONYX_EDITOR: By default, the command line editor uses emacs key bindings. Use this variable to explicitly set the key bindings to either “emacs” or “vi”.

3.3 Language differences

If *onyx* is being run interactively:

- The name “stop” is redefined in the initial thread’s `errordict` to recursively execute the `stdin` file in a stopped context in order to keep the interpreter from exiting on error. It is possible (though generally unlikely, since the user must type a very long line of code) for buffering of `stdin` to cause strange things to occur; any additional program execution after an error is a result of this.
- The name “resume” is defined in the initial thread’s `threaddict` as an alias to the `stop` operator. Thus, when an error occurs, when the user is ready to continue running after addressing any issues the error caused, `resume` can be called as a more intuitive name for resuming.
- The name “promptstring” is defined in `systemdict`; it takes no arguments and returns a string. The return string is used as the interactive prompt.

If *onyx* is being run non-interactively:

- The name “stop” in `errordict` is redefined to call the `die` operator with an argument of 1.

Chapter 4

The libonyx library

The *libonyx* library implements an embeddable Onyx interpreter. *libonyx* is designed to allow multiple interpreter instances in the same program, though since Onyx is a multi-threaded language, in most cases it makes more sense to use a single interpreter instance with multiple threads.

The Onyx language is described elsewhere in this manual, so this chapter documents the C API with as little information about the Onyx language as possible.

A minimal program that runs the Onyx interpreter interactively looks like:

```
#include <libonyx/libonyx.h>

int
main(int argc, char **argv, char **envp)
{
    cw_nx_t nx;
    cw_nxo_t thread, *nxo;

    /* Initialize libonyx and the Onyx interpreter. */
    libonyx_init();
    nx_new(&nx, NULL, argc, argv, envp);

    /* Create a thread. */
    nxo_thread_new(&thread, &nx);

    /* Set up stdin for evaluation. */
    nxo = nxo_stack_push(nxo_thread_ostack_get(&thread));
    nxo_dup(nxo, nxo_thread_stdin_get(&thread));
    nxo_attr_set(nxo, NXOA_EXECUTABLE);

    /* Start the thread. */
    nxo_thread_start(&thread);

    /* Clean up. */
    nx_delete(&nx);
    libonyx_shutdown();
}
```

```
    return 0;  
}
```

In most cases, an application will need to implement additional Onyx operators (and make them accessible from within the Onyx interpreter) in order to make the application accessible/controllable from the Onyx interpreter. If the application user interface is to be interaction with the Onyx interpreter, then little else needs to be done.

4.1 Compilation

Use the following compiler command line to compile applications with *libonyx*.

```
cc `onyx_config --cppflags` <file> `onyx_config --ldflags --libs`
```

4.2 Types

libonyx is careful to use the following data types rather than the built-in types (other than when using system library functions and string pointers (char *)) to allow easy porting and explicit knowledge of variable sizes:

cw_bool_t: Boolean, either FALSE or TRUE.

cw_sint8_t: Signed 8 bit variable.

cw_uint8_t: Unsigned 8 bit variable.

cw_sint16_t: Signed 16 bit variable.

cw_uint16_t: Unsigned 16 bit variable.

cw_sint32_t: Signed 32 bit variable.

cw_uint32_t: Unsigned 32 bit variable.

cw_sint64_t: Signed 64 bit variable.

cw_uint64_t: Unsigned 64 bit variable.

cw_fp64_t: 64 bit IEEE floating point variable.

4.3 Global variables

libonyx defines the following global variables, which can be used by the application:

cw_g_mem: *mem* instance, default memory allocator.

4.4 Threads

libonyx encapsulates each interpreter instance in an *nx* object. An *nx* object supports running multiple concurrent threads. Each thread context is encapsulated by an *nxo* thread object.

In general, each process thread should execute in its own *nxo* thread object context, though the only explicit restriction placed on *nxo* thread object operations is that only one thread can be executing in an *nxo* thread object context at a time. In other words, the *nxo* thread class does not synchronize access to its internals, since there is normally no reason for multiple threads to execute in the same *nxo* thread object context.

4.5 Garbage collection

Since there can be arbitrary threads executing in the interpreter concurrently, there are two ways to implement safe garbage collection: concurrent or atomic. *libonyx* uses atomic garbage collection, which means that the thread doing garbage collection suspends all other threads that are created via *thd_new(..., TRUE)* during the mark phase. In order for this to work, the garbage collector must not do any locking while the other threads are suspended, or else there is a high probability of eventual deadlock. *libonyx* itself meets these criteria, as must any C extensions to the interpreter that are executed by the garbage collector during the mark phase (reference iteration).

4.6 Exceptions

libonyx reserves *xep* exception numbers 0 to 127 and defines the following exceptions:

CW_ONYXX_OOM: Memory allocation error.

CW_ONYXX_EXIT: Internal use, for the exit operator.

CW_ONYXX_STOP: Internal use, for the stop operator.

CW_ONYXX_QUIT: Internal use, for the quit operator.

4.7 Integration issues

4.7.1 Thread creation

libonyx's garbage collector uses the *thd* class to suspend and resume all other threads during the mark phase of atomic collection. For this to work, all threads that have any contact with *libonyx* must be created as suspendible threads using the *thd* class.

This can cause integration headaches for existing threaded applications, but there is no other portable way to suspend and resume threads. The only alternative is to assure that only one thread is executing in the interpreter and to disable timeout-based (asynchronous) collection.

4.7.2 Restarted interrupted system calls

As mentioned above, *libonyx* uses thread suspension and resumption to implement garbage collection. This has the side-effect of making restarted interrupted system calls a real possibility. However, the operating system will return with a partial result if the system call was partially complete when it was interrupted. In practice, what this means is that short reads and writes are possible where they otherwise wouldn't happen, so the application should not make any assumptions about interruptible system calls always completing with a full result. See the *thd* class documentation for more details.

4.7.3 Signals

Depending on how *libonyx* is built, *SIGUSR1* and *SIGUSR2* may be reserved by the *thd* class for thread suspension and resumption. Additionally, the *SIGPIPE* signal is ignored by default, since socket operations can cause *SIGPIPE* signals, for which the library has no use.

4.8 Guidelines for writing extensions

When embedding *libonyx* in an application, it is usually desirable to add some operators so that the interpreter can interact with the rest of the application. The *libonyx* source code contains hundreds of operators that can be used as examples when writing new operators. However, there are some very important rules that operators must follow, some of which may not be obvious when reading the code.

- Manually managed (*malloc()/free()*) memory should not be allocated unless the code is very careful. If a function recurses into the interpreter (this includes calls to functions such as *nxo.thread.nerror()*), there is the very real possibility that control will never return to the operator due to an exception. Code must either catch all exceptions and clean up allocations, or not recurse into the interpreter.
- Composite objects should never be allocated on the C stack. The garbage collector has no knowledge of such objects, so if the only reference to an object is on the C stack, the object may be collected, which will lead to unpredictable program behavior. Instead of allocating objects on the C stack, use *tstack*, available via *nxo.thread.tstack.get()*, which is a per-thread stack that the garbage collector scans.
- For an object to be safe from garbage collection, there must always be at least one reference to it inside the interpreter. So, if C code obtains a pointer to a composite object, then destroys the last known internal Onyx reference (pops it off a stack, redefines it in a dict, replaces an element of an array, etc.), the pointer is no longer safe to use. The *libonyx* API is structured such that it is invalid to do such a thing, for this reason.
- *tstack* must be cleaned up before returning from a function. This constraint is placed on the code in order to avoid leaking space on *tstack*. In debug versions of *libonyx*, this is enforced by assertions. The one exception to this rule has to do with *xep* exceptions, in which case the catchers of the exceptions are responsible for cleaning up *tstack*. Therefore, it is not necessary to catch exceptions merely to avoid *tstack* leakage.

Since Onyx type checking is dynamic, it is the responsibility of the operators to assure objects are the correct type before calling any of the type-specific *nxo.*()* functions. Failure to do so will result in unpredictable behavior and likely crashes.

4.9 API

void *libonyx_init*(void):

Input(s): None.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Initialize various global variables. In particular, initialize *cw_g_mem*.

void *libonyx_shutdown*(void):

Input(s): None.

Output(s): None.

Exception(s): None.

Description: Clean up the global variables that are initialized by *libonyx_init*().

void **cw_opaque_alloc_t*(void *a_arg, size_t a_size, const char *a_filename, cw_uint32_t a_line_num):

Input(s):

a_arg: Opaque pointer.

a_size: Size of memory range to allocate.

a_filename: Should be `__FILE__`.

a_line_num: Should be `__LINE__`.

Output(s):

retval: Pointer to a memory range.

Exception(s):

CW_ONYXX_OOM.

Description: Allocate *a_size* of space and return a pointer to it.

void **cw_opaque_realloc_t*(void *a_arg, void *a_ptr, size_t a_size, const char *a_filename, cw_uint32_t a_line_num):

Input(s):

a_arg: Opaque pointer.

a_ptr: Pointer to memory range to be reallocated.

a_size: Size of memory range to allocate.

a_filename: Should be `__FILE__`.

a_line_num: Should be `__LINE__`.

Output(s):

retval: Pointer to a memory range.

Exception(s):

CW_ONYXX_OOM.

Description: Reallocate *a_size* of space and return a pointer to it.

void *cw_opaque_dealloc_t*(void *a_mem, void *a_ptr, size_t a_size, const char *a_filename, cw_uint32_t a_line_num):

Input(s):

a_arg: Opaque pointer.
a_ptr: Pointer to memory range to be freed.
a_size: Size of memory range pointed to by *a_ptr*.
a_filename: Should be `__FILE__`.
a_line_num: Should be `__LINE__`.

Output(s): None.

Exception(s): None.

Description: Deallocate the memory pointed to by *a_ptr*.

void * cw_opaque_alloc(cw_opaque_alloc_t *a_func, void *a_arg, size_t a_size):

Input(s):

a_func: Opaque allocator function pointer.
a_arg: Opaque pointer.
a_size: Size of memory range to allocate.

Output(s):

retval: Pointer to a memory range.

Exception(s):

CW_ONYXX_OOM.

Description: Allocate *a_size* of space and return a pointer to it.

void * cw_opaque_realloc(cw_opaque_realloc_t *a_func, void *a_arg, void *a_ptr, size_t a_size):

Input(s):

a_func: Opaque allocator function pointer.
a_arg: Opaque pointer.
a_ptr: Pointer to memory range to be reallocated.
a_size: Size of memory range to allocate.

Output(s):

retval: Pointer to a memory range.

Exception(s):

CW_ONYXX_OOM.

Description: Reallocate *a_size* of space and return a pointer to it.

void cw_opaque_dealloc(cw_opaque_dealloc_t *a_func, void *a_mem, void *a_ptr, size_t a_size):

Input(s):

a_func: Opaque allocator function pointer.
a_arg: Opaque pointer.
a_ptr: Pointer to memory range to be freed.
a_size: Size of memory range pointed to by *a_ptr*.

Output(s): None.

Exception(s): None.

Description: Deallocate the memory pointed to by *a_ptr*.

void cw_onyx_code(cw_nxo_t *a_thread, const char *a_code):

Input(s):

a_thread: Pointer to a thread *nxo*.

a_code: A "-delimited string constant.

Output(s): None.

Exception(s): Depends on actions of *a_code*.

Description: Convenience macro for static embedded Onyx code.

void *cw_assert*(expression):**Input(s):**

expression: C expression that evaluates to zero or non-zero.

Output(s): Possible error printed to *stderr*.

Exception(s): None.

Description: If the expression evaluates to zero, print an error message to *stderr* and *abort()*.

Note: This macro is only active if the *CW_ASSERT* cpp macro is defined.

void *cw_not_reached*(void):

Input(s): None.

Output(s): Error printed to *stderr*.

Exception(s): None.

Description: Abort with an error message.

Note: This macro is only active if the *CW_ASSERT* cpp macro is defined.

void *cw_check_ptr*(a_pointer):**Input(s):**

a_pointer: A pointer.

Output(s): Possible error printed to *stderr*.

Exception(s): None.

Description: If *a_pointer* is NULL, print an error message to *stderr* and *abort()*.

Note: This macro is only active if the *CW_ASSERT* cpp macro is defined.

void *cw_error*(const char *a_str):**Input(s):**

a_str: Pointer to a NULL-terminated character array.

Output(s): Contents of *a_str*, followed by a carriage return, printed to *stderr*.

Exception(s): None.

Description: Print the contents of *a_str*, followed by a carriage return, to *stderr*.

cw_uint64_t *cw_ntohq*(cw_uint64_t a_val):**Input(s):**

a_val: 64 bit integer.

Output(s):

retval: 64 bit integer.

Exception(s): None.

Description: Convert *a_val* from network byte order to host byte order and return the result.

`cw_uint64_t cw_htonq(cw_uint64_t a_val):`

Input(s):

a_val: 64 bit integer.

Output(s):

retval: 64 bit integer.

Exception(s): None.

Description: Convert *a_val* from host byte order to network byte order and return the result.

`cw_uint32_t cw_offsetof(<type> a_type, <field_name> a_field):`

Input(s):

a_type: C structure type name.

a_field: Name of a field within *a_type*.

Output(s):

retval: Offset of *a_field* into *a_type*.

Exception(s): None.

Description: Calculate the offset of *a_field* into *a_type* and return the result.

4.10 Classes

4.10.1 ch

The *ch* class implements chained hashing. It uses a simple bucket chaining hash table implementation. Table size is set at creation time, and cannot be changed, so performance will suffer if a *ch* object is over-filled. The main `cw_ch_t` data structure and the table are contiguously allocated, which means that care must be taken when manually pre-allocating space for the structure. Each item that is inserted into the *ch* object is encapsulated by a *chi* object, for which space can optionally be passed in as a parameter to *ch_insert()*. If no space for the *chi* object is passed in, the *mem* class is used internally for allocation.

Multiple entries with the same key are allowed and are stored in LIFO order.

Calling *ch_remove_iterate()* and *ch_get_iterate()* are guaranteed to operate on the oldest item in the hash table, which means that the hash code has an integrated FIFO queue.

The *ch* class is meant to be small and simple without compromising performance. Note that it is not well suited for situations where the number of items can vary wildly; the *dch* class is designed for such situations.

API

`cw_uint32_t CW_CH_TABLE2SIZEOF(cw_uint32_t a_table_size):`

Input(s):

a_table_size: Number of slots in the hash table.

Output(s):

retval: Size of a *ch* object with *a_table_size* slots.

Exception(s): None.

Description: Calculate the size of a *ch* object with *a_table_size* slots.

***ch_new*(*cw_ch_t* **a_ch*, *cw_opaque_alloc_t* **a_alloc*, *cw_opaque_dealloc_t* **a_dealloc*, *void* **a_arg*, *cw_uint32_t* *a_table_size*, *cw_ch_hash_t* **a_hash*, *cw_ch_key_comp_t* **a_key_comp*):**

Input(s):

a_ch: Pointer to space for a *ch* with *a_table_size* slots, or NULL. Use the *CW_CH_TABLE2SIZEOF()* macro to calculate the total space needed for a given table size.

a_alloc: Pointer to an allocation function to use internally.

a_dealloc: Pointer to a deallocation function to use internally.

a_arg: Opaque pointer to pass to *a_alloc()* and *a_dealloc()*.

a_table_size: Number of slots in the hash table.

a_hash: Pointer to a hashing function.

a_key_comp: Pointer to a key comparison function.

Output(s):

retval: Pointer to a *ch*.

Exception(s):

CW_ONYXX_OOM.

Description: Constructor.

***void ch_delete*(*cw_ch_t* **a_ch*):**

Input(s):

a_ch: Pointer to a *ch*.

Output(s): None.**Exception(s):** None.

Description: Destructor.

***cw_uint32_t ch_count*(*cw_ch_t* **a_ch*):**

Input(s):

a_ch: Pointer to a *ch*.

Output(s):

retval: Number of items in *a_ch*.

Exception(s): None.

Description: Return the number of items in *a_ch*.

***void ch_insert*(*cw_ch_t* **a_ch*, *const void* **a_key*, *const void* **a_data*, *cw_chi_t* **a_chi*):**

Input(s):

a_ch: Pointer to a *ch*.

a_key: Pointer to a key.

a_data: Pointer to data associated with *a_key*.

a_chi: Pointer to space for a *chi*, or NULL.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Insert *a_data* into *a_ch*, using key *a_key*. Use *a_chi* for the internal *chi* container if non-NULL.

cw_bool_t ch_remove(cw_ch_t *a_ch, const void *a_search_key, void **r_key, void **r_data, cw_chi_t **r_chi):

Input(s):

a_ch: Pointer to a *ch*.

a_search_key: Pointer to the key to search with.

r_key: Pointer to a key pointer, or NULL.

r_data: Pointer to a data pointer, or NULL.

r_chi: Pointer to a *chi* pointer, or NULL.

Output(s):

retval:

FALSE: Success.

TRUE: Item with key *a_search_key* not found.

***r_key:** If (*r_key* != NULL) and (retval == FALSE), pointer to a key. Otherwise, undefined.

***r_data:** If (*r_data* != NULL) and (retval == FALSE), pointer to data. Otherwise, undefined.

***r_chi:** If (*r_chi* != NULL) and (retval == FALSE), pointer to space for a *chi*, or NULL. Otherwise, undefined.

Exception(s): None.

Description: Remove the item from *a_ch* that was most recently inserted with key *a_search_key*. If successful, set **r_key* and **r_data* to point to the key, data, and externally allocated *chi*, respectively.

cw_bool_t ch_search(cw_ch_t *a_ch, const void *a_key, void **r_data):

Input(s):

a_ch: Pointer to a *ch*.

a_key: Pointer to a key.

r_data: Pointer to a data pointer, or NULL.

Output(s):

retval:

FALSE: Success.

TRUE: Item with key *a_key* not found in *a_ch*.

***r_data:** If (*r_data* != NULL) and (retval == FALSE), pointer to data.

Exception(s): None.

Description: Search for the most recently inserted item with key *a_key*. If found, **r_data* to point to the associated data.

cw_bool_t ch_get_iterate(cw_ch_t *a_ch, void **r_key, void **r_data):

Input(s):

a_ch: Pointer to a *ch*.

r_key: Pointer to a key pointer, or NULL.

r_data: Pointer to a data pointer, or NULL.

Output(s):

retval:

FALSE: Success.

TRUE: *a_ch* is empty.

***r_key:** If (*r_key* != NULL) and (retval == FALSE), pointer to a key. Otherwise, undefined.

***r_data:** If (*r_data* != NULL) and (retval == FALSE), pointer to data. Otherwise, undefined.

Exception(s): None.

Description: Set **r_key* and **r_data* to point to the oldest item in *a_ch*. Promote the item so that it is the newest item in *a_ch*.

cw_bool_t ch_remove_iterate(cw_ch_t *a_ch, void **r_key, void **r_data, cw_chi_t **r_chi):

Input(s):

a_ch: Pointer to a *ch*.

r_key: Pointer to a key pointer, or NULL.

r_data: Pointer to a data pointer, or NULL.

r_chi: Pointer to a *chi* pointer, or NULL.

Output(s):

retval:

FALSE: Success.

TRUE: *a_ch* is empty.

***r_key:** If (*r_key* != NULL) and (retval == FALSE), pointer to a key. Otherwise, undefined.

***r_data:** If (*r_data* != NULL) and (retval == FALSE), pointer to data. Otherwise, undefined.

***r_chi:** If (*r_chi* != NULL) and (retval == FALSE), pointer to a *chi*, or NULL. Otherwise, undefined.

Exception(s): None.

Description: Set **r_key* and **r_data* to point to the oldest item in *a_ch*, set **r_chi* to point to the item's container, if externally allocated, and remove the item from *a_ch*.

cw_uint32_t ch_string_hash(const void *a_key):

Input(s):

a_key: Pointer to a key.

Output(s):

retval: Hash result.

Exception(s): None.

Description: NULL-terminated string hashing function.

cw_uint32_t ch_direct_hash(const void *a_key):

Input(s):

a_key: Pointer to a key.

Output(s):

retval: Hash result.

Exception(s): None.

Description: Direct (pointer) hashing function.

`cw_bool_t ch_string_key_comp(const void *a_k1, const void *a_k2):`

Input(s):

a_k1: Pointer to a key.

a_k2: Pointer to a key.

Output(s):

retval:

FALSE: Not equal.

TRUE: Equal.

Exception(s): None.

Description: Test two keys (NULL-terminated strings) for equality.

`cw_bool_t ch_direct_key_comp(const void *a_k1, const void *a_k2):`

Input(s):

a_k1: Pointer to a key.

a_k2: Pointer to a key.

Output(s):

retval:

FALSE: Not equal.

TRUE: Equal.

Exception(s): None.

Description: Test two keys (pointers) for equality.

4.10.2 `cnd`

The `cnd` class implements condition variables, which can be used in conjunction with the `mtx` class to wait for a condition to occur.

API

`void cnd_new(cw_cnd_t *a_cnd):`

Input(s):

a_cnd: Pointer to space for a `cnd`.

Output(s): None.

Exception(s): None.

Description: Constructor.

`void cnd_delete(cw_cnd_t *a_cnd):`

Input(s):

a_cnd: Pointer to a *cnd*.

Output(s): None.

Exception(s): None.

Description: Destructor.

void *cnd_signal*(cw_cnd_t *a_cnd):

Input(s):

a_cnd: Pointer to a *cnd*.

Output(s): None.

Exception(s): None.

Description: Signal one thread waiting on *a_cnd*, if there are any waiters.

void *cnd_broadcast*(cw_cnd_t *a_cnd):

Input(s):

a_cnd: Pointer to a *cnd*.

Output(s): None.

Exception(s): None.

Description: Signal all threads waiting on *a_cnd*.

cw_bool_t *cnd_timedwait*(cw_cnd_t *a_cnd, cw_mtx_t *a_mtx, const struct timespec *a_timeout):

Input(s):

a_cnd: Pointer to a *cnd*.

a_mtx: Pointer to a *mtx*.

a_timeout: Timeout, specified as an absolute time interval.

Output(s):

retval:

FALSE: Success.

TRUE: Timeout.

Exception(s): None.

Description: Wait for *a_cnd* for at least *a_time*.

void *cnd_wait*(cw_cnd_t *a_cnd, cw_mtx_t *a_mtx):

Input(s):

a_cnd: Pointer to a *cnd*.

a_mtx: Pointer to a *mtx*.

Output(s): None.

Exception(s): None.

Description: Wait for *a_cnd*.

4.10.3 dch

The *dch* class implements dynamic chained hashing. The *dch* class is a wrapper around the *ch* class that enforces fullness/emptiness constraints and rebuilds the hash table when necessary. Other than this added functionality, the *dch* class behaves almost exactly like the *ch* class. See the *ch* class documentation for additional information.

API

dch_new(*cw_dch_t* **a_dch*, *cw_opaque_alloc_t* **a_alloc*, *cw_opaque_dealloc_t* **a_dealloc*, void **a_arg*, *cw_uint32_t* *a_base_table*, *cw_uint32_t* *a_base_grow*, *cw_uint32_t* *a_base_shrink*, *cw_ch_hash_t* **a_hash*, *cw_ch_key_comp_t* **a_key_comp*):

Input(s):

- a_dch:** Pointer to space for a *dch*, or NULL.
- a_alloc:** Pointer to an allocation function to use internally.
- a_dealloc:** Pointer to a deallocation function to use internally.
- a_arg:** Opaque pointer to pass to *a_alloc()* and *a_dealloc()*.
- a_base_table:** Number of slots in the initial hash table.
- a_base_grow:** Maximum number of items to allow in *a_dch* before doubling the hash table size. The same proportions (in relation to *a_base_table*) are used to decide when to double the table additional times.
- a_base_shrink:** Minimum proportional (with respect to *a_base_table*) emptiness to allow in the hash table before cutting the hash table size in half.
- a_hash:** Pointer to a hashing function.
- a_key_comp:** Pointer to a key comparison function.

Output(s):

- retval:** Pointer to a *dch*.

Exception(s):

CW_ONYXX_OOM.

Description: Constructor.

void dch_delete(*cw_dch_t* **a_dch*):

Input(s):

- a_dch:** Pointer to a *dch*.

Output(s): None.

Exception(s): None.

Description: Destructor.

cw_uint32_t dch_count(*cw_dch_t* **a_dch*):

Input(s):

- a_dch:** Pointer to a *dch*.

Output(s):

- retval:** Number of items in *a_dch*.

Exception(s): None.

Description: Return the number of items in *a_dch*.

void dch_insert(*cw_dch_t* **a_dch*, const void **a_key*, const void **a_data*, *cw_chi_t* **a_chi*):

Input(s):

- a_dch:** Pointer to a *dch*.
- a_key:** Pointer to a key.
- a_data:** Pointer to data associated with *a_key*.

a_chi: Pointer to space for a *chi*, or NULL.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Insert *a_data* into *a_dch*, using key *a_key*. Use *a_chi* for the internal *chi* container if non-NULL.

cw_bool_t dch_remove(cw_dch_t *a_dch, const void *a_search_key, void **r_key, void **r_data, cw_chi_t **r_chi):

Input(s):

a_dch: Pointer to a *dch*.

a_search_key: Pointer to the key to search with.

r_key: Pointer to a key pointer, or NULL.

r_data: Pointer to a data pointer, or NULL.

r_chi: Pointer to a *chi* pointer, or NULL.

Output(s):

retval:

FALSE: Success.

TRUE: Item with key *a_search_key* not found.

***r_key:** If (*r_key* != NULL) and (retval == FALSE), pointer to a key. Otherwise, undefined.

***r_data:** If (*r_data* != NULL) and (retval == FALSE), pointer to data. Otherwise, undefined.

***r_chi:** If (*r_chi* != NULL) and (retval == FALSE), pointer to space for a *chi*, or NULL. Otherwise, undefined.

Exception(s): None.

Description: Remove the item from *a_dch* that was most recently inserted with key *a_search_key*. If successful, set **r_key* and **r_data* to point to the key, data, and externally allocated *chi*, respectively.

cw_bool_t dch_search(cw_dch_t *a_dch, const void *a_key, void **r_data):

Input(s):

a_dch: Pointer to a *dch*.

a_key: Pointer to a key.

r_data: Pointer to a data pointer, or NULL.

Output(s):

retval:

FALSE: Success.

TRUE: Item with key *a_key* not found in *a_dch*.

***r_data:** If (*r_data* != NULL) and (retval == FALSE), pointer to data.

Exception(s): None.

Description: Search for the most recently inserted item with key *a_key*. If found, **r_data* to point to the associated data.

cw_bool_t dch_get_iterate(cw_dch_t *a_dch, void **r_key, void **r_data):

Input(s):

a_dch: Pointer to a *dch*.
r_key: Pointer to a key pointer, or NULL.
r_data: Pointer to a data pointer, or NULL.

Output(s):**retval:**

FALSE: Success.
TRUE: *a_dch* is empty.

***r_key:** If (*r_key* != NULL) and (retval == FALSE), pointer to a key. Otherwise, undefined.
***r_data:** If (*r_data* != NULL) and (retval == FALSE), pointer to data. Otherwise, undefined.

Exception(s): None.

Description: Set **r_key* and **r_data* to point to the oldest item in *a_dch*. Promote the item so that it is the newest item in *a_dch*.

cw_bool_t dch_remove_iterate(cw_dch_t *a_dch, void **r_key, void **r_data, cw_chi_t **r_chi):

Input(s):

a_dch: Pointer to a *dch*.
r_key: Pointer to a key pointer, or NULL.
r_data: Pointer to a data pointer, or NULL.
r_chi: Pointer to a *chi* pointer, or NULL.

Output(s):**retval:**

FALSE: Success.
TRUE: *a_dch* is empty.

***r_key:** If (*r_key* != NULL) and (retval == FALSE), pointer to a key. Otherwise, undefined.
***r_data:** If (*r_data* != NULL) and (retval == FALSE), pointer to data. Otherwise, undefined.
***r_chi:** If (*r_chi* != NULL) and (retval == FALSE), pointer to a *chi*, or NULL. Otherwise, undefined.

Exception(s): None.

Description: Set **r_key* and **r_data* to point to the oldest item in *a_dch*, set **r_chi* to point to the item's container, if externally allocated, and remove the item from *a_dch*.

4.10.4 mb

The *mb* class implements memory barriers. A memory barrier is a low level construct that is sometimes useful for guaranteeing the order in which memory operations take place, even when multiple microprocessors are involved. In most cases, mutexes are the best choice for synchronizing data access, but sometimes it is convenient (and critical to performance) to use memory barriers where weaker access constraints are adequate.

API

void mb_write(void):

Input(s): None.

Output(s): None.

Exception(s): None.

Description: Create a write barrier, so that any memory writes done before the memory barrier are guaranteed to be visible by the time any memory writes after the memory barrier become visible.

4.10.5 mem

The *mem* class implements a memory allocation (malloc) wrapper. For the debug version of *libonyx*, extra information is hashed for each memory allocation that allows tracking of the following:

- File/line number of allocation.
- Double allocation/deallocation of the same address.
- Memory leaks (memory left allocated at mem destruction time).

If any memory leaks are detected, diagnostic output is printed to *stderr*.

Also, the debug version of *libonyx* sets all newly allocated bytes to 0xa5, and all deallocated bytes to 0x5a (except in the case of *mem_calloc()*). This tends to cause things to break sooner when uninitialized or deallocated memory is referenced.

In general, the *mem* class doesn't need to be used directly. Instead, there are several preprocessor macros that can be used: *cw_malloc()*, *cw_calloc()*, *cw_realloc()*, and *cw_free()*.

API

`cw_mem_t * mem_new(cw_mem_t *a_mem, cw_mem_t *a_internal):`

Input(s):

a_mem: Pointer to space for a *mem*, or NULL.

a_internal: Pointer to a *mem* to use for internal memory allocation, or NULL.

Output(s):

retval: Pointer to a *mem*.

Exception(s):

CW_ONYXX_OOM.

Description: Constructor.

`void mem_delete(cw_mem_t *a_mem):`

Input(s):

a_mem: Pointer to a *mem*.

Output(s): None.

Exception(s): None.

Description: Destructor.

```
void * mem_malloc_e(cw_mem_t *a_mem, size_t a_size, const char *a_filename, cw_uint32_t  
a_line_num):  
void * mem_malloc(cw_mem_t *a_mem, size_t a_size):  
void * cw_malloc(size_t a_size):
```

Input(s):

a_mem: Pointer to a *mem*.
a_size: Size of memory range to allocate.
a_filename: Should be `__FILE__`.
a_line_num: Should be `__LINE__`.

Output(s):

retval: Pointer to a memory range.

Exception(s):

CW_ONYXX_OOM.

Description: *malloc()* wrapper.

```
void * mem_calloc_e(cw_mem_t *a_mem, size_t a_number, size_t a_size, const char *a_filename,  
cw_uint32_t a_line_num):  
void * mem_calloc(cw_mem_t *a_mem, size_t a_number, size_t a_size):  
void * cw_calloc(size_t a_number, size_t a_size):
```

Input(s):

a_mem: Pointer to a *mem*.
a_number: Number of elements to allocate.
a_size: Size of each element to allocate.
a_filename: Should be `__FILE__`.
a_line_num: Should be `__LINE__`.

Output(s):

retval: Pointer to a zeroed memory range.

Exception(s):

CW_ONYXX_OOM.

Description: *calloc()* wrapper.

```
void * mem_realloc_e(cw_mem_t *a_mem, void *a_ptr, size_t a_size, size_t a_old_size, const char  
*a_filename, cw_uint32_t a_line_num):  
void * mem_realloc(cw_mem_t *a_mem, void *a_ptr, size_t a_size):  
void * cw_realloc(void *a_ptr, size_t a_size):
```

Input(s):

a_mem: Pointer to a *mem*.
a_ptr: Pointer to memory range to be reallocated.
a_size: Size of memory range to allocate.
a_old_size: Size of memory range previously pointed to by *a_ptr*.
a_filename: Should be `__FILE__`.
a_line_num: Should be `__LINE__`.

Output(s):

retval: Pointer to a memory range.

Exception(s):

CW_ONYXX_OOM.

Description: *realloc()* wrapper.

void *mem_free_e*(cw_mem_t *a_mem, void *a_ptr, size_t a_size, const char *a_filename, cw_uint32_t a_line_num):

void *mem_free*(cw_mem_t *a_mem, void *a_ptr, size_t a_size):

void *cw_free*(void *a_ptr):

Input(s):

a_mem: Pointer to a *mem*.

a_ptr: Pointer to to memory range to be freed.

a_size: Sizef of memory range pointed to by *a_ptr*.

a_filename: Should be `__FILE__`.

a_line_num: Should be `__LINE__`.

Output(s): None.

Exception(s): None.

Description: *free()* wrapper.

4.10.6 mq

The *mq* class implements a simple unidirectional message queue. In addition to putting and getting messages, there are methods that control the ability to get or put. This provides a simple out of band state transition capability.

API

void *mq_new*(cw_mq_t *a_mq, cw_mem_t *a_mem, cw_uint32_t a_msg_size):

Input(s):

a_mq: Pointer to space for a *mq*.

a_mem: Pointer to the allocator to use internally.

a_msg_size: Size (in bytes) of messages used for all subsequent calls to *mq_*get()* and *mq_put()*.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Constructor.

void *mq_delete*(cw_mq_t *a_mq):

Input(s):

a_mq: Pointer to a *mq*.

Output(s): None.

Exception(s): None.

Description: Destructor.

`cw_bool_t mq_tryget(cw_mq_t *a_mq, ...):`

Input(s):

`a_mq`: Pointer to a *mq*.

`...`: Pointer to space to store a message.

Output(s):

`retval`:

FALSE: Success.

TRUE: No messages in the queue, or get is in the stop state.

***...:** If *retval* is FALSE, a message. Otherwise, undefined.

Exception(s): None.

Description: Try to get a message, but return TRUE if none are available.

`cw_bool_t mq_timedget(cw_mq_t *a_mq, const struct timespec *a_timeout, ...):`

Input(s):

`a_mq`: Pointer to a *mq*.

`a_timeout`: Timeout, specified as an absolute time interval.

`...`: Pointer to space to store a message.

Output(s):

`retval`:

FALSE: Success.

TRUE: No messages in the queue, or get is in the stop state.

***...:** If *retval* is FALSE, a message. Otherwise, undefined.

Exception(s): None.

Description: Get a message. If none are available, block until a message is available, or until timeout.

`cw_bool_t mq_get(cw_mq_t *a_mq, ...):`

Input(s):

`a_mq`: Pointer to a *mq*.

`...`: Pointer to space to store a message.

Output(s):

`retval`:

FALSE: Success.

TRUE: Get is in the stop state.

***...:** If *retval* is FALSE, a message. Otherwise, undefined.

Exception(s): None.

Description: Get a message. If none are available, block until a message is available.

`cw_bool_t mq_put(cw_mq_t *a_mq, ...):`

Input(s):

`a_mq`: Pointer to a *mq*.

`...`: A message.

Output(s):**retval:****FALSE:** Success.**TRUE:** Failure due to put being in the stop state.**Exception(s):****CW_ONYXX_OOM.****Description:** Put a message in *a.mq*.**cw_bool_t mq_get_start(cw_mq_t *a_mq):****Input(s):****a_mq:** Pointer to a *mq*.**Output(s):****retval:****FALSE:** Success.**TRUE:** Error (already in start state).**Exception(s):** None.**Description:** Change the get operation to the start state (*mq_get()* will not return TRUE).**cw_bool_t mq_get_stop(cw_mq_t *a_mq):****Input(s):****a_mq:** Pointer to a *mq*.**Output(s):****retval:****FALSE:** Success.**TRUE:** Error (already in stop state).**Exception(s):** None.**Description:** Change the get operation to the stop state (*mq_get()* will return TRUE).**cw_bool_t mq_put_start(cw_mq_t *a_mq):****Input(s):****a_mq:** Pointer to a *mq*.**Output(s):****retval:****FALSE:** Success.**TRUE:** Error (already in start state).**Exception(s):** None.**Description:** Change the put operation to the start state (*mq_put()* will not return TRUE).**cw_bool_t mq_put_stop(cw_mq_t *a_mq):****Input(s):****a_mq:** Pointer to a *mq*.**Output(s):****retval:**

FALSE: Success.

TRUE: Error (already in stop state).

Exception(s): None.

Description: Change the put operation to the stop state (*mq_put()* will return TRUE).

4.10.7 mtx

The *mtx* class implements typical mutual exclusion locks. Only one thread can hold a lock at a time, and attempting to attain the lock while already owning it has undefined results.

API

void *mtx_new*(cw_mtx_t *a_mtx):

Input(s):

a_mtx: Pointer to space for a *mtx*.

Output(s): None.

Exception(s): None.

Description: Constructor.

void *mtx_delete*(cw_mtx_t *a_mtx):

Input(s):

a_mtx: Pointer to a *mtx*.

Output(s): None.

Exception(s): None.

Description: Destructor.

void *mtx_lock*(cw_mtx_t *a_mtx):

Input(s):

a_mtx: Pointer to a *mtx*.

Output(s): None.

Exception(s): None.

Description: Lock *a_mtx*.

cw_bool_t *mtx_trylock*(cw_mtx_t *a_mtx):

Input(s):

a_mtx: Pointer to a *mtx*.

Output(s):

retval:

FALSE: Success.

TRUE: Failure.

Exception(s): None.

Description: Try to lock *a_mtx*, but return immediately instead of blocking if *a_mtx* is already locked.

void *mtx_unlock*(*cw_mtx_t* **a_mtx*):

Input(s):

a_mtx: Pointer to a *mtx*.

Output(s): None.

Exception(s): None.

Description: Unlock *a_mtx*.

4.10.8 nx

The *nx* class encapsulates an Onyx interpreter instance. It contains a number of interpreter-global objects, as well as the garbage collector. Reclamation all objects associated with an *nx* instance is managed by a garbage collector, so when an *nx* is destroyed, all associated objects are deallocated.

API

cw_nx_t **nx_new*(cw_nx_t **a_nx*, cw_op_t **a_thread_init*, int *a_argc*, char *a_argv*, char ***a_envp*):**

Input(s):

a_nx: Pointer to space for an *nx*, or NULL.

a_thread_init: Pointer to an initialization function to be called during thread initialization, or NULL.

a_argc: Number of command line arguments.

a_argv: Pointer to an array of command line argument strings.

a_envp: Pointer to an array of environment variable strings.

Output(s):

retval: Pointer to an *nx*.

Exception(s):

CW_ONYXX_OOM.

Description: Constructor.

void *nx_delete*(cw_nx_t **a_nx*):

Input(s): Pointer to an *nx*.

Output(s): None.

Exception(s): None.

Description: Destructor.

cw_nxa_t **nx_nxa_get*(cw_nx_t **a_nx*):

Input(s): Pointer to an *nx*.

Output(s):

retval: Pointer to an *nxa*.

Exception(s): None.

Description: Return a pointer to the garbage collector.

`cx_nxo_t * nx_systemdict_get(cx_nx_t *a_nx):`

Input(s):

a_nx: Pointer to an *nx*.

Output(s):

retval: Pointer to the *nxo* corresponding to *systemdict* .

Exception(s): None.

Description: Return a pointer to the *nxo* corresponding to *systemdict* .

`cx_nxo_t * nx_globaldict_get(cx_nx_t *a_nx):`

Input(s):

a_nx: Pointer to an *nx*.

Output(s):

retval: Pointer to the *nxo* corresponding to *globaldict* .

Exception(s): None.

Description: Return a pointer to the *nxo* corresponding to *globaldict* .

`cx_nxo_t * nx_envdict_get(cx_nx_t *a_nx):`

Input(s):

a_nx: Pointer to an *nx*.

Output(s):

retval: Pointer to the *nxo* corresponding to *envdict* .

Exception(s): None.

Description: Return a pointer to the *nxo* corresponding to *envdict* .

`cx_nxo_t * nx_stdin_get(cx_nx_t *a_nx):`

Input(s):

a_nx: Pointer to an *nx*.

Output(s):

retval: Pointer to the *nxo* corresponding to *stdin* .

Exception(s): None.

Description: Return a pointer to the *nxo* corresponding to *stdin* .

`void nx_stdin_set(cx_nx_t *a_nx, cx_nxo_t *a_stdin):`

Input(s):

a_nx: Pointer to an *nx*.

a_stdin: Pointer to a file *nxo*.

Output(s): None.

Exception(s): None.

Description: Set *a_nx*'s *stdin* to *a_stdin*.

`cx_nxo_t * nx_stdout_get(cx_nx_t *a_nx):`

Input(s):**a_nx:** Pointer to an *nx*.**Output(s):****retval:** Pointer to the *nxo* corresponding to *stdout* .**Exception(s):** None.**Description:** Return a pointer to the *nxo* corresponding to *stdout* .**void nx_stdout_set(cw_nx_t *a_nx, cw_nxo_t *a_stdout):****Input(s):****a_nx:** Pointer to an *nx*.**a_stdout:** Pointer to a file *nxo*.**Output(s):** None.**Exception(s):** None.**Description:** Set *a_nx*'s stdout to *a_stdout*.**cw_nxo_t * nx_stderr_get(cw_nx_t *a_nx):****Input(s):****a_nx:** Pointer to an *nx*.**Output(s):****retval:** Pointer to the *nxo* corresponding to *stderr* .**Exception(s):** None.**Description:** Return a pointer to the *nxo* corresponding to *stderr* .**void nx_stderr_set(cw_nx_t *a_nx, cw_nxo_t *a_stderr):****Input(s):****a_nx:** Pointer to an *nx*.**a_stderr:** Pointer to a file *nxo*.**Output(s):** None.**Exception(s):** None.**Description:** Set *a_nx*'s stderr to *a_stderr*.**4.10.9 nxa**

The *nxa* class implements garbage collection. The garbage collector runs a separate thread that is controlled via an asynchronous message queue. The collector thread is only responsible for doing asynchronous collection due to allocation inactivity and all sweeping; all other marking is synchronously done in the thread context of the mutator that triggers collection.

API

void * nxa_malloc_e(cw_nxa_t *a_nxa, size_t a_size, const char *a_filename, cw_uint32_t a_line_num):
void * nxa_malloc(cw_nxa_t *a_nxa, size_t a_size):

Input(s):

a_nxa: Pointer to a *nxa*.
a_size: Size of memory range to allocate.
a_filename: Should be `__FILE__`.
a_line_num: Should be `__LINE__`.

Output(s):

retval: Pointer to a memory range.

Exception(s):

CW_ONYXX_OOM.

Description: *malloc()* wrapper.

void * *nxa_realloc_e*(cw_nxa_t *a_nxa, size_t a_size, size_t a_old_size, const char *a_filename, cw_uint32_t a_line_num):

void * *nxa_realloc*(cw_nxa_t *a_nxa, size_t a_size):

Input(s):

a_nxa: Pointer to a *nxa*.
a_ptr: Pointer to memory range to be reallocated.
a_size: Size of memory range to allocate.
a_old_size: Size of memory range previously pointed to by *a_ptr*.
a_filename: Should be `__FILE__`.
a_line_num: Should be `__LINE__`.

Output(s):

retval: Pointer to a memory range.

Exception(s):

CW_ONYXX_OOM.

Description: *realloc()* wrapper.

void * *nxa_free_e*(cw_nxa_t *a_nxa, void *a_ptr, size_t a_size, const char *a_filename, cw_uint32_t a_line_num):

void * *nxa_free*(cw_nxa_t *a_nxa, void *a_ptr, size_t a_size):

Input(s):

a_nxa: Pointer to a *nxa*.
a_ptr: Pointer to memory range to be freed.
a_size: Size of memory range pointed to by *a_ptr*.
a_filename: Should be `__FILE__`.
a_line_num: Should be `__LINE__`.

Output(s): None.

Exception(s): None.

Description: *free()* wrapper.

void *nxa_collect*(cw_nxa_t *a_nxa):

Input(s):

a_nxa: Pointer to a *nxa*.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Do a synchronous garbage collection.

void *nxa_dump*(cw_nxa_t *a_nxa, cw_nxo_t *a_thread):

Input(s):

a_nxa: Pointer to a *nxa*.

a_thread: Pointer to a thread *nxo*.

Output(s): Output printed to *stdout* .

Exception(s):

CW_ONYXX_OOM.

Description: Print the internal state of *gcdict* to *stdout* .

cw_bool_t *nxa_active_get*(cw_nxa_t *a_nxa):

Input(s):

a_nxa: Pointer to a *nxa*.

Output(s):

retval:

FALSE: Garbage collector deactivated.

TRUE: Garbage collector active.

Exception(s): None.

Description: Return whether the garbage collector is active (runnable).

void *nxa_active_set*(cw_nxa_t *a_nxa, cw_bool_t a_active):

Input(s):

a_nxa: Pointer to a *nxa*.

a_active:

FALSE: Deactivate garbage collector.

TRUE: Activate garbage collector.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Send a message to the garbage collector to activate or deactivate. The asynchronous nature of the message means that it is possible for the garbage collector to run after this function returns, even if a deactivation message has been sent.

cw_nxoi_t *nxa_period_get*(cw_nxa_t *a_nxa):

Input(s):

a_nxa: Pointer to a *nxa*.

Output(s):

retval: Current inactivity period in seconds that the garbage collector waits before doing a collection.

Exception(s): None.

Description: Return the current inactivity period in seconds that the garbage collector waits before doing a collection.

void *nxa_period_set*(cw_nxa_t *a_nxa, cw_nxoi_t a_period):

Input(s):

a_nxa: Pointer to a *nxa*.

a_period: Inactivity period in seconds that the garbage collector should wait before doing a collection. If 0, the garbage collector will never run due to inactivity.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Set the inactivity period in seconds that the garbage collector should wait before doing a collection.

cw_nxoi_t *nxa_threshold_get*(cw_nxa_t *a_nxa):

Input(s):

a_nxa: Pointer to a *nxa*.

Output(s):

retval: Number of bytes of memory allocated since the last garbage collection that will trigger the garbage collector to run.

Exception(s): None.

Description: Return the number of bytes of memory allocated since the last garbage collection that will trigger the garbage collector to run.

void *nxa_threshold_set*(cw_nxa_t *a_nxa, cw_nxoi_t a_threshold):

Input(s):

a_nxa: Pointer to a *nxa*.

a_threshold: The number of bytes of memory allocated since the last garbage collection that will trigger the garbage collector to run.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Set the number of bytes of memory allocated since the last garbage collection that will trigger the garbage collector to run.

void *nxa_stats_get*(cw_nxa_t *a_nxa, cw_nxoi_t *r_collections, cw_nxoi_t *r_count, cw_nxoi_t *r_ccount, cw_nxoi_t *r_cmark, cw_nxoi_t *r_csweep, cw_nxoi_t *r_mcount, cw_nxoi_t *r_mmark, cw_nxoi_t *r_msweep, cw_nxoi_t *r_scount, cw_nxoi_t *r_smark, cw_nxoi_t *r_ssweep):

Input(s):

a_nxa: Pointer to a *nxa*.

r_collections: Pointer to an integer.

r_count: Pointer to an integer.

r_ccount: Pointer to an integer.

r_cmark: Pointer to an integer.

r_csweep: Pointer to an integer.

r_mcount: Pointer to an integer.
r_mmark: Pointer to an integer.
r_msweep: Pointer to an integer.
r_scount: Pointer to an integer.
r_smark: Pointer to an integer.
r_ssweep: Pointer to an integer.

Output(s):

***r_collections:** Number of times the garbage collector has run.
***r_count:** Current number of bytes of memory allocated.
***r_ccount:** Number of bytes of memory allocated as of the end of the most recent garbage collection.
***r_cmark:** Number of microseconds spent in the mark phase of the most recent garbage collection.
***r_csweep:** Number of microseconds spent in the sweep phase of the most recent garbage collection.
***r_mcount:** Largest number of bytes of memory ever allocated at any point in time.
***r_mmark:** Largest number of microseconds ever spent in the mark phase of a garbage collection.
***r_msweep:** Largest number of microseconds spent in the sweep phase of a garbage collection.
***r_scount:** Total number of bytes of memory ever allocated.
***r_smark:** Total number of microseconds spent in the mark phase of all garbage collections.
***r_ssweep:** Total number of microseconds spent in the sweep phase of all garbage collections.

Exception(s): None.

Description: Return garbage collector statistics.

cw_nx_t * *nxa_nx_get*(cw_nxa_t **a_nxa*):

Input(s):

a_nxa: Pointer to a *nxa*.

Output(s):

retval: Pointer to a *nx*.

Exception(s): None.

Description: Return a pointer to the *nx* associated with *a_nxa*.

cw_nxo_t * *nxa_gcdict_get*(cw_nxa_t **a_nxa*):

Input(s):

a_nxa: Pointer to a *nxa*.

Output(s):

retval: Pointer to a dict *nxo*.

Exception(s): None.

Description: Return a pointer to the dict *nxo* corresponding to *gcdict* .

4.10.10 `nxn`

The *nxn* class provides access to a table of string constants. The main reason for this class's existence is that multiple C files often use identical string constants, and this saves memory by allowing all to refer to a single string.

API

`const cw_uint8_t * nxn_str(cw_nxn_t a_nxn):`

Input(s):

`a_nxn`: A number that corresponds to an entry in the string table.

Output(s):

`retval`: Pointer to a string constant.

Exception(s): None.

Description: Return a pointer to the string constant associated with *a_nxn*.

`cw_uint32_t nxn_len(cw_nxn_t a_nxn):`

Input(s):

`a_nxn`: A number that corresponds to an entry in the string table.

Output(s):

`retval`: String length of a string constant.

Exception(s): None.

Description: Return the string length of the string constant associated with *a_nxn*.

4.10.11 `nxo`

The *nxo* class is the basis for the Onyx type system. *nxo* objects can be any of the following types, as determined by the `cw_nxot_t` type:

`NXOT_NO`: *nxo_no*

`NXOT_ARRAY`: *nxo_array*

`NXOT_BOOLEAN`: *nxo_boolean*

`NXOT_CONDITION`: *nxo_condition*

`NXOT_DICT`: *nxo_dict*

`NXOT_FILE`: *nxo_file*

`NXOT_FINO`: *nxo_fino*

`NXOT_HOOK`: *nxo_hook*

`NXOT_INTEGER`: *nxo_integer*

`NXOT_MARK`: *nxo_mark*

NXOT_MUTEX: *nxo_mutex*

NXOT_NAME: *nxo_name*

NXOT_NULL: *nxo_null*

NXOT_OPERATOR: *nxo_operator*

NXOT_PMARK: *nxo_pmark*

NXOT_REAL: *nxo_real*

NXOT_STACK: *nxo_stack*

NXOT_STRING: *nxo_string*

NXOT_THREAD: *nxo_thread*

Due to limitations of the C programming language, it is the responsibility of the application to do type checking to assure that an incompatible *nxo* object is not passed to a type-specific function. For example, passing a file *nxo* to *nxo_string_get()* is prohibited, and will result in undefined behaviour (including crashes).

Composite objects contain a reference to an *nxoe* object. For the most part, the application does not need to be aware of this. The only exception is when writing extensions with the hook type. Hook objects need to be able to iterate over the objects they reference internally, and return *nxoe* references to the garbage collector.

The following functions are applicable to all types of *nxo* objects.

API

cw_sint32_t nxo_compare(const cw_nxo_t *a_a, const cw_nxo_t *a_b):

Input(s):

a_a: Pointer to an *nxo*.

a_b: Pointer to an *nxo*.

Output(s):

retval:

-1: For types which it is meaningful (integer, string), *a_a* is less than *a_b*.

0: *a_a* and *a_b* are equal.

1: For types which it is meaningful (integer, string), *a_a* is greater than *a_b*.

2: Incompatible types, or not the same composite object.

Exception(s): None.

Description: Compare *a_a* and *a_b*.

void nxo_dup(cw_nxo_t *a_to, cw_nxo_t *a_from):

Input(s):

a_to: Pointer to an *nxo*.

a_from: Pointer to an *nxo*.

Output(s): None.

Exception(s): None.

Description: Duplicate *a_from* to *a_to*. This does not do a copy of composite objects; rather it creates a new reference to the value of a composite object.

`cw_nxot_t nxo_type_get(const cw_nxo_t *a_nxo):`

Input(s):

`a_nxo`: Pointer to an *nxo*.

Output(s):

`retval`:

`NXOT_NO`: *nxo_no*

`NXOT_ARRAY`: *nxo_array*

`NXOT_BOOLEAN`: *nxo_boolean*

`NXOT_CONDITION`: *nxo_condition*

`NXOT_DICT`: *nxo_dict*

`NXOT_FILE`: *nxo_file*

`NXOT_FINO`: *nxo_fino*

`NXOT_HOOK`: *nxo_hook*

`NXOT_INTEGER`: *nxo_integer*

`NXOT_MARK`: *nxo_mark*

`NXOT_MUTEX`: *nxo_mutex*

`NXOT_NAME`: *nxo_name*

`NXOT_NULL`: *nxo_null*

`NXOT_OPERATOR`: *nxo_operator*

`NXOT_PMARK`: *nxo_pmark*

`NXOT_REAL`: *nxo_real*

`NXOT_STACK`: *nxo_stack*

`NXOT_STRING`: *nxo_string*

`NXOT_THREAD`: *nxo_thread*

Exception(s): None.

Description: Return the type of *a_nxo*.

`cw_nxoe_t * nxo_nxoe_get(const cw_nxo_t *a_nxo):`

Input(s):

`a_nxo`: Pointer to an *nxo*.

Output(s):

`retval`: Pointer to the *nxoe* associated with *a_nxo*, or NULL if *a_nxo* is not composite.

Exception(s): None.

Description: Return a pointer to the *nxoe* associated with *a_nxo*.

`cw_bool_t nxo_lcheck():`

Input(s):

`a_nxo`: Pointer to an array, dict, file, stack, or string *nxo*.

Output(s):

`retval`:

FALSE: *a_nxo* is not implicitly locked.

TRUE: *a_nxo* is implicitly locked.

Exception(s): None.

Description: For array, dict, file, stack, or string *nxos*, return whether *a_nxo* is implicitly locked.

`cx_nxoa_t nxo_attr_get(const cx_nxo_t *a_nxo):`

Input(s):

a_nxo: Pointer to an *nxo*.

Output(s):

retval:

NXOA_LITERAL: *a_nxo* is literal.

NXOA_EXECUTABLE: *a_nxo* is executable.

Exception(s): None.

Description: Return the attribute for *a_nxo*.

`void nxo_attr_set(cx_nxo_t *a_nxo, cx_nxoa_t a_attr):`

Input(s):

a_nxo: Pointer to an *nxo*.

a_attr: Value of attribute to set for *a_nxo*.

Output(s): None.

Exception(s): None.

Description: Set the attribute for *a_nxo* to *a_attr*.

4.10.12 nxo.array

The *nxo.array* class is a subclass of the *nxo* class.

API

`void nxo_array_new(cx_nxo_t *a_nxo, cx_nx_t *a_nx, cx_bool_t a_locking, cx_uint32_t a_len):`

Input(s):

a_nxo: Pointer to an array *nxo*.

a_nx: Pointer to an *nx*.

a_locking: Implicit locking mode.

a_len: Number of array elements.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Constructor.

`void nxo_array_subarray_new(cx_nxo_t *a_nxo, cx_nxo_t *a_array, cx_nx_t *a_nx, cx_uint32_t a_offset, cx_uint32_t a_len):`

Input(s):

a_nxo: Pointer to an array *nxo*.
a_array: Pointer to an array *nxo* to create a subarray of.
a_nx: Pointer to an *nx*.
a_offset: Offset into *a_array*.
a_len: Number of array elements.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Subarray constructor.

void *nxo_array_copy*(cw_nxo_t *a_to, cw_nxo_t *a_from):

Input(s):

a_to: Pointer to an array *nxo*.
a_from: Pointer to an array *nxo*.

Output(s): None.

Exception(s): None.

Description: Copy the contents of *a_from* to *a_to*. The length of *a_to* must be at least that of *a_from*.

cw_uint32_t *nxo_array_len_get*(const cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to an array *nxo*.

Output(s):

retval: Number of elements in *a_nxo*.

Exception(s): None.

Description: Return the number of elements in *a_nxo*.

void *nxo_array_el_get*(const cw_nxo_t *a_nxo, cw_nxoi_t a_offset, cw_nxo_t *r_el):

Input(s):

a_nxo: Pointer to an array *nxo*.
a_offset: Offset of element to get.
r_el: Pointer to space to dup an object to.

Output(s):

***r_el:** A dup of the element of *a_nxo* at offset *a_offset*.

Exception(s): None.

Description: Get a dup of the element of *a_nxo* at offset *a_offset*.

void *nxo_array_el_set*(cw_nxo_t *a_nxo, cw_nxo_t *a_el, cw_nxoi_t a_offset):

Input(s):

a_nxo: Pointer to an array *nxo*.
a_el: Pointer to an *nxo*.
a_offset: Offset of element in *a_nxo* to replace with *a_el*.

Output(s): None.

Exception(s): None.

Description: Dup *a_el* into the element of *a_nxo* at offset *a_offset*.

4.10.13 nxo_boolean

The *nxo_boolean* class is a subclass of the *nxo* class.

API

void *nxo_boolean_new*(cw_nxo_t *a_nxo, cw_bool_t a_val):

Input(s):

a_nxo: Pointer to a boolean *nxo*.

a_val: Initial value.

Output(s): None.

Exception(s): None.

Description: Constructor.

cw_bool_t *nxo_boolean_get*(const cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a boolean *nxo*.

Output(s):

retval: Value of *a_nxo*.

Exception(s): None.

Description: Return the value of *a_nxo*.

void *nxo_boolean_set*(cw_nxo_t *a_nxo, cw_bool_t a_val):

Input(s):

a_nxo: Pointer to a boolean *nxo*.

a_val: Value to set *a_nxo* to.

Output(s): None.

Exception(s): None.

Description: Set the value of *a_nxo* to *a_val*.

4.10.14 nxo_condition

The *nxo_condition* class is a subclass of the *nxo* class.

API

void *nxo_condition_new*(cw_nxo_t *a_nxo, cw_nx_t *a_nx):

Input(s):

a_nxo: Pointer to a condition *nxo*.

a_nx: Pointer to an *nx*.

Output(s): None.

Exception(s):
CW_ONYXX_OOM.

Description: Constructor.

void *nxo_condition_signal*(cw_nxo_t *a_nxo):

Input(s):
a_nxo: Pointer to a condition *nxo*.

Output(s): None.

Exception(s): None.

Description: Signal one thread waiting on *a_nxo*, if there are any waiters.

void *nxo_condition_broadcast*(cw_nxo_t *a_nxo):

Input(s):
a_nxo: Pointer to a condition *nxo*.

Output(s): None.

Exception(s): None.

Description: Signal all threads waiting on *a_nxo*.

void *nxo_condition_wait*(cw_nxo_t *a_nxo, cw_nxo_t *a_mutex):

Input(s):
a_nxo: Pointer to a condition *nxo*.
a_mutex: Pointer to a mutex *nxo*.

Output(s): None.

Exception(s): None.

Description: Wait for *a_nxo*.

cw_bool_t *nxo_condition_timedwait*(cw_nxo_t *a_nxo, cw_nxo_t *a_mutex, const struct timespec *a_timeout):

Input(s):
a_nxo: Pointer to a condition *nxo*.
a_mutex: Pointer to a mutex *nxo*.
a.timeout: Timeout, specified as an absolute time interval.

Output(s):
retval:
FALSE: Success.
TRUE: Timeout.

Exception(s): None.

Description: Wait for *a_nxo* for at least *a_timeout*.

4.10.15 nxo_dict

The *nxo_dict* class is a subclass of the *nxo* class.

API

void *nxo_dict_new*(cw_nxo_t *a_nxo, cw_nx_t *a_nx, cw_bool_t a_locking, cw_uint32_t a_dict_size):

Input(s):

a_nxo: Pointer to a dict *nxo*.

a_nx: Pointer to an *nx*.

a_locking: Implicit locking mode.

a_dict_size: Initial number of slots. Dictionaries dynamically grow and shrink as needed, but if the maximum size of *a_nxo* is known, it should be specified here to save space.

Output(s): None

Exception(s):

CW_ONYXX_OOM.

Description: Constructor.

***nxo_dict_copy*(cw_nxo_t *a_to, cw_nxo_t *a_from, cw_nx_t *a_nx):**

Input(s):

a_to: Pointer to a dict *nxo*.

a_from: Pointer to a dict *nxo*.

a_nx: Pointer to an *nx*.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Do a deep copy (actual contents are copied) of *a_from* to *a_to*.

void *nxo_dict_def*(cw_nxo_t *a_nxo, cw_nx_t *a_nx, cw_nxo_t *a_key, cw_nxo_t *a_val):

Input(s):

a_nxo: Pointer to a dict *nxo*.

a_nx: Pointer to an *nx*.

a_key: Pointer to an *nxo*.

a_val: Pointer to an *nxo*.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Define *a_key* with value *a_val* in *a_nxo*.

void *nxo_dict_undef*(cw_nxo_t *a_nxo, cw_nx_t *a_nx, cw_nxo_t *a_key):

Input(s):

a_nxo: Pointer to a dict *nxo*.

a_nx: Pointer to an *nx*.

a_key: Pointer to an *nxo*.

Output(s): None.

Exception(s): None.

Description: Undefine *a_key* in *a_nxo*, if defined.

cw_bool_t *nxo_dict_lookup*(const cw_nxo_t *a_nxo, const cw_nxo_t *a_key, cw_nxo_t *r_nxo):

Input(s):**a_nxo:** Pointer to a dict *nxo*.**a_key:** Pointer to an *nxo*.**r_nxo:** Pointer to an *nxo*.**Output(s):****retval:****FALSE:** Success.**TRUE:** *a_key* not found.**r_nxo:** If *retval* is FALSE, value associated with *a_key* in *a_nxo*, otherwise unmodified.**Exception(s):** None.**Description:** Find *a_key* in *a_nxo* and dup its associated value to *r_nxo*.**cw_uint32_t nxo_dict_count(const cw_nxo_t *a_nxo):****Input(s):****a_nxo:** Pointer to a dict *nxo*.**Output(s):****retval:** The number of key/value pairs in *a_nxo*.**Exception(s):** None.**Description:** Return the number of key/value pairs in *a_nxo*.**void nxo_dict_iterate(cw_nxo_t *a_nxo, cw_nxo_t *r_nxo):****Input(s):****a_nxo:** Pointer to a dict *nxo*.**r_nxo:** Pointer to an *nxo*.**Output(s):****FALSE:** Success.**TRUE:** *a_nxo* is empty.**r_nxo:** If *retval* is FALSE, A key in *a_nxo*, otherwise unmodified.**Exception(s):** None.**Description:** Iteratively get a key in *a_nxo*. Each successive call to this function will get the next key, and wrap back around to the first key when all keys have been returned.

4.10.16 nxo_file

The *nxo_file* class is a subclass of the *nxo* class.

API

cw_sint32_t cw_nxo_file_read_t(void *a_arg, cw_nxo_t *a_file, cw_uint32_t a_len, cw_uint8_t *r_str):**Input(s):****a_arg:** Opaque data pointer.**a_file:** Pointer to a file *nxo*.

a.len: Length of *r_str*.

r_str: Pointer to space to put read data.

Output(s):

retval:

-1: Read error.

>= 0: Number of bytes stored in *r_str*.

r_str: If *retval* is non-negative, *retval* bytes of read data, otherwise undefined.

Exception(s): Application specific.

Description: Read up to *a.len* bytes of data from *a_file* and store the result in *r_str*.

`cw_bool_t cw_nxo_file_write_t(void *a_arg, cw_nxo_t *a_file, const cw_uint8_t *a_str, cw_uint32_t a_len):`

Input(s):

a_arg: Opaque data pointer.

a_file: Pointer to a file *nxo*.

a_str: Pointer to data to write.

a.len: Length of *a_str*.

Output(s):

retval:

FALSE: Success.

TRUE: Write error.

Exception(s): Application specific.

Description: Write *a.len* bytes of data from *a_str* to *a_file*.

`cw_nxoe_t * cw_nxo_file_ref_iter_t(void *a_arg, cw_bool_t a_reset):`

Input(s):

a_arg: Opaque data pointer.

a_reset:

FALSE: At least one iteration has already occurred.

TRUE: First iteration.

Output(s):

retval:

non-NULL: Pointer to an *nxoe*.

NULL: No more references.

Exception(s): None.

Description: Reference iterator function typedef.

`void cw_nxo_file_delete_t(void *a_arg, cw_nx_t *a_nx):`

Input(s):

a_arg: Opaque data pointer.

a_nx: Pointer to an *nx*.

Output(s): None.

Exception(s): None.

Description: Destructor function typedef.

void *nxo_file_new*(cw_nxo_t *a_nxo, cw_nx_t *a_nx, cw_bool_t a_locking):

Input(s):

a_nxo: Pointer to a file *nxo*.

a_nx: Pointer to an *nx*.

a_locking: Implicit locking mode.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Constructor.

void *nxo_file_fd_wrap*(cw_nxo_t *a_nxo, cw_uint32_t a_fd):

Input(s):

a_nxo: Pointer to a file *nxo*.

a_fd: File descriptor number.

Output(s): None.

Exception(s): None.

Description: Wrap file descriptor *a_fd* so that operations on *a_nxo* will be backed by the file descriptor.

void *nxo_file_synthetic*(cw_nxo_t *a_nxo, cw_nxo_file_read_t *a_read, cw_nxo_file_write_t *a_write, cw_nxo_file_ref_iter_t *a_ref_iter, cw_nxo_file_delet_t *a_delete, void *a_arg):

Input(s):

a_nxo: Pointer to a file *nxo*.

a_read: Pointer to a read function.

a_write: Pointer to a write function.

a_ref_iter: Pointer to a reference iterator function.

a_delete: Pointer to a destructor function.

a_arg: Opaque pointer to be passed to the read and write functions.

Output(s): None.

Exception(s): None.

Description: Set up *a_nxo* to call the specified read and write functions to satisfy file operations.

cw_nxn_t *nxo_file_open*(cw_nxo_t *a_nxo, const cw_uint8_t *a_filename, cw_uint32_t a_nlen, const cw_uint8_t *a_flags, cw_uint32_t a_flen):

Input(s):

a_nxo: Pointer to a file *nxo*.

a_filename: Pointer to a string (not required to be '\0' terminated) that represents a filename.

a_nlen: Length in bytes of *a_filename*.

a_flags: Pointer to a string (not required to be '\0' terminated) that represents a file mode:

“r”: Read only.

“r+”: Read/write, starting at offset 0.

“w”: Write only. Create file if necessary. Truncate file if non-zero length.

“w+”: Read/write, starting at offset 0. Create file if necessary.

“a”: Write only, starting at end of file.

“a+”: Read/write, starting at end of file.

aflen: Length in bytes of *a.flags*.

Output(s):

retval:

NXN_ZERO.

NXN_ioerror.

NXN_invalidfileaccess.

NXN_limitcheck.

Exception(s): None.

Description: Open a file.

cw_nxn_t nxo_file_close(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a file *nxo*.

Output(s):

retval:

NXN_ZERO.

NXN_ioerror.

Exception(s): None.

Description: Close a file.

cw_sint32_t nxo_file_fd_get(const cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a file *nxo*.

Output(s):

retval:

-1: Invalid or synthetic file.

>= 0: File descriptor number.

Exception(s): None.

Description: Return the file descriptor associated with *a_nxo*.

cw_bool_t nxo_file_nonblocking_get(const cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a file *nxo*.

Output(s):

retval:

FALSE: Blocking file.

TRUE: Non-blocking file.

Exception(s): None.

Description: Return the non-blocking mode for *a_nxo*.

`cw_bool_t nxo_file_nonblocking_set(cw_nxo_t *a_nxo, cw_bool_t a_nonblocking):`

Input(s):

a_nxo: Pointer to a file *nxo*.

a_nonblocking: Non-blocking mode to set *nxo* to.

Output(s):

retval:

FALSE: Success.

TRUE: I/O error or non-POSIX file.

Exception(s): None.

Description: Set the non-blocking mode for *a_nxo* to *a_nonblocking*.

`cw_sint32_t nxo_file_read(cw_nxo_t *a_nxo, cw_uint32_t a_len, cw_uint8_t *r_str):`

Input(s):

a_nxo: Pointer to a file *nxo*.

a_len: Length in bytes of *r_str*.

r_str: Pointer to a string to store read data into.

Output(s):

retval:

-1: NXN_ioerror.

>= 0: Number of bytes of data read into *r_str*.

r_str: If *retval* is non-negative, *retval* bytes of read data.

Exception(s): None.

Description: Read data.

`cw_nxn_t nxo_file_readline(cw_nxo_t *a_nxo, cw_nx_t *a_nx, cw_bool_t a_locking, cw_nxo_t *r_string, cw_bool_t *r_eof):`

Input(s):

a_nxo: Pointer to a file *nxo*.

a_nx: Pointer to an *nx*.

a_locking: Implicit locking mode.

r_string: Pointer to an *nxo*.

r_eof: Pointer to a *cw_bool_t*.

Output(s):

retval:

NXN_ZERO.

NXN_ioerror.

r_string: If *retval* is NXN_ZERO, a string object, otherwise unmodified.

***r_eof:**

FALSE: End of file not reached.

TRUE: End of file reached.

Exception(s):**CW_ONYXX_OOM.****Description:** Read a line, terminated by “\r”, “\r\n”, or EOF.**`cw_nxn_t nxo_file_write(cw_nxo_t *a_nxo, const cw_uint8_t *a_str, cw_uint32_t a_len, cw_uint32_t *r_count):`****Input(s):****a_nxo:** Pointer to a file *nxo*.**a_str:** Pointer to data to write.**a_len:** Length of *a_str*.**r_count:** Pointer to a location to store the number of bytes written, or NULL.**Output(s):****retval:****NXN_ZERO.****NXN_ioerror.*****r_count:** If *r_count* is non-NULL, and *retval* is **NXN_ZERO**, number of bytes written, otherwise undefined.**Exception(s):** None.**Description:** Write the *a_len* bytes of data pointed to *a_str*. If the file is in non-blocking mode, it is possible for **r_count* to be as small as 0 for a successful write.**`cw_nxn_t nxo_file_truncate(cw_nxo_t *a_nxo, off_t a_length):`****Input(s):****a_nxo:** Pointer to a file *nxo*.**a_length:** Length to set file to.**Output(s):****retval:****NXN_ZERO.****NXN_ioerror.****Exception(s):** None.**Description:** Truncate or extend the file associated with *a_nxo* so that it is *a_length* bytes long.**`cw_nxoi_t nxo_file_position_get(cw_nxo_t *a_nxo):`****Input(s):****a_nxo:** Pointer to a file *nxo*.**Output(s):****retval:****-1:** **NXN_ioerror**.**>= 0:** Current file position.**Exception(s):** None.**Description:** Get the current file position.**`cw_nxn_t nxo_file_position_set(cw_nxo_t *a_nxo, cw_nxoi_t a_position):`**

Input(s):

a_nxo: Pointer to a file *nxo*.

a_position: File position.

Output(s):

retval:

NXN_ZERO.

NXN_ioerror.

Exception(s): None.

Description: Move the current file position to *a_position*.

`cw_uint32_t nxo_file_buffer_size_get(const cw_nxo_t *a_nxo):`

Input(s):

a_nxo: Pointer to a file *nxo*.

Output(s):

retval: Size in bytes of the internal data buffer.

Exception(s): None.

Description: Return the size of the internal data buffer.

`void nxo_file_buffer_size_set(cw_nxo_t *a_nxo, cw_uint32_t a_size):`

Input(s):

a_nxo: Pointer to a file *nxo*.

a_size: Size in bytes of internal buffer to use.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Use an internal buffer of *a_size* bytes.

`cw_nxoi_t nxo_file_buffer_count(const cw_nxo_t *a_nxo):`

Input(s):

a_nxo: Pointer to a file *nxo*.

Output(s):

retval: Current number of buffered bytes available for reading.

Exception(s): None.

Description: Return the current number of buffered bytes available for reading.

`cw_nxn_t nxo_file_buffer_flush(cw_nxo_t *a_nxo):`

Input(s):

a_nxo: Pointer to a file *nxo*.

Output(s):

retval:

NXN_ZERO.

NXN_ioerror.

Exception(s): None.

Description: Flush any buffered write data to disk, and discard any buffered read data.

4.10.17 `nxo_fino`

The `nxo_fino` class is a subclass of the `nxo` class.

API

`void nxo_fino_new(cw_nxo_t *a_nxo):`

Input(s):

a_nxo: Pointer to an `nxo`.

Output(s): None.

Exception(s): None.

Description: Constructor.

4.10.18 `nxo_hook`

The `nxo_hook` class is a subclass of the `nxo` class.

API

`void cw_nxo_hook_eval_t(void *a_data, cw_nxo_t *a_thread):`

Input(s):

a_data: Opaque data pointer.

a_thread: Pointer to a thread `nxo`.

Output(s): None.

Exception(s): Hook-dependent.

Description: Evaluation function typedef.

`cw_nxoe_t * cw_nxo_hook_ref_iter_t(void *a_data, cw_bool_t a_reset):`

Input(s):

a_data: Opaque data pointer.

a_reset:

FALSE: At least one iteration has already occurred.

TRUE: First iteration.

Output(s):

retval:

non-NULL: Pointer to an `nxoe`.

NULL: No more references.

Exception(s): None.

Description: Reference iterator function typedef.

`cw_bool_t cw_nxo_hook_delete_t(void *a_data, cw_nx_t *a_nx, cw_uint32_t a_iter):`

Input(s):

a.data: Opaque data pointer.

a.nx: Pointer to an *nx*.

a.iter: Garbage collector sweep iteration count (starts at 0). This value can be used to impose ordering of dependent object deletions.

Output(s):

retval:

FALSE: Success.

TRUE: Defer deletion until a later garbage collector sweep iteration.

Exception(s): None.

Description: Destructor function typedef.

void *nxo_hook_new*(*cx_nxo_t* **a_nxo*, *cx_nx_t* **a_nx*, void **a_data*, *cx_nxo_hook_eval_t* **a_eval_f*, *cx_nxo_hook_ref_iter_t* **a_ref_iter_f*, *cx_nxo_hook_delete_t* **a_delete_f*):

Input(s):

a_nxo: Pointer to a hook *nxo*.

a_nx: Pointer to an *nx*.

a.data: Opaque data pointer to be passed to *a_eval_f*, *a_ref_iter_f*, and *a_delete_f*.

a_eval_f: Pointer to an evaluation function.

a_ref_iter_f: Pointer to a reference iterator function.

a_delete_f: Pointer to a destructor function.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Constructor.

***cx_nxo_t* **nxo_hook_tag_get*(const *cx_nxo_t* **a_nxo*):**

Input(s):

a_nxo: Pointer to a hook *nxo*.

Output(s):

retval: Pointer to the tag object associated with *a_nxo*.

Exception(s): None.

Description: Return a pointer to the tag object associated with *a_nxo*. This object pointer can safely be used for modifying the tag object.

void **nxo_hook_data_get*(const *cx_nxo_t* **a_nxo*):

Input(s):

a_nxo: Pointer to a hook *nxo*.

Output(s):

retval: Opaque data pointer.

Exception(s): None.

Description: Return the opaque data pointer associated with *a_nxo*.

void *nxo_hook_data_set*(*cx_nxo_t* **a_nxo*, void **a_data*):

Input(s):

a_nxo: Pointer to a hook *nxo*.

a_data: Opaque data pointer.

Output(s): None.

Exception(s): None.

Description: Set the opaque data pointer associated with *a_nxo*.

void *nxo_hook_eval*(cw_nxo_t *a_nxo, cw_nxo_t *a_thread):

Input(s):

a_nxo: Pointer to a hook *nxo*.

a_thread: Pointer to a thread *nxo*.

Output(s): None.

Exception(s): Hook-specific.

Description: Evaluate the *a_nxo*. If there is no evaluation function associated with *a_nxo*, it is pushed onto ostack.

4.10.19 *nxo_integer*

The *nxo_integer* class is a subclass of the *nxo* class.

API

void *nxo_integer_new*(cw_nxo_t *a_nxo, cw_nxoi_t a_val):

Input(s):

a_nxo: Pointer to an integer *nxo*.

a_val: Initial value.

Output(s): None.

Exception(s): None.

Description: Constructor.

cw_nxoi_t *nxo_integer_get*(const cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to an integer *nxo*.

Output(s):

retval: Value of *a_nxo*.

Exception(s): None.

Description: Return the value of *a_nxo*.

void *nxo_integer_set*(cw_nxo_t *a_nxo, cw_nxoi_t a_val):

Input(s):

a_nxo: Pointer to an integer *nxo*.

a_val: Integer value.

Output(s): None.

Exception(s): None.

Description: Set the value of *a_nxo* to *a_val*.

4.10.20 nxo_mark

The *nxo_mark* class is a subclass of the *nxo* class.

API

void *nxo_mark_new*(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to an *nxo*.

Output(s): None.

Exception(s): None.

Description: Constructor.

4.10.21 nxo_mutex

The *nxo_mutex* class is a subclass of the *nxo* class.

API

void *nxo_mutex_new*(cw_nxo_t *a_nxo, cw_nx_t *a_nx):

Input(s):

a_nxo: Pointer to a mutex *nxo*.

a_nx: Pointer to an *nx*.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Constructor.

void *nxo_mutex_lock*(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a mutex *nxo*.

Output(s): None.

Exception(s): None.

Description: Lock *a_nxo*.

cw_bool_t *nxo_mutex_trylock*(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a mutex *nxo*.

Output(s):

retval:

FALSE: Success.

TRUE: Failure.

Exception(s): None.

Description: Try to lock *a_nxo*, but return immediately with an error if unable to do so.

void *nxo_mutex_unlock*(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a mutex *nxo*.

Output(s): None.

Exception(s): None.

Description: Unlock *a_nxo*.

4.10.22 *nxo_name*

The *nxo_name* class is a subclass of the *nxo* class.

API

void *nxo_name_new*(cw_nxo_t *a_nxo, cw_nx_t *a_nx, const cw_uint8_t *a_str, cw_uint32_t a_len, cw_bool_t a_is_static):

Input(s):

a_nxo: Pointer to a name *nxo*.

a_nx: Pointer to an *nx*.

a_str: Pointer to a character string (not required to be '\0' terminated).

a_len: Length in bytes of *a_str*.

a_is_static:

FALSE: *a_str* may be modified or deallocated during the lifetime of the program.

TRUE: *a_str* will not be modified for the lifetime of the program.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Constructor.

const cw_uint8_t * *nxo_name_str_get*(const cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a name *nxo*.

Output(s):

retval: Pointer to a string that represents *a_nxo*.

Exception(s): None.

Description: Return a pointer to a string that represents *a_nxo*.

cw_uint32_t *nxo_name_len_get*(const cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a name *nxo*.

Output(s):

retval: Length in bytes of the name associated with *a_nxo*.

Exception(s): None.

Description: Return the length in bytes of the name associated with *a_nxo*.

4.10.23 nxo_no

The *nxo_no* class is a subclass of the *nxo* class.

API

void *nxo_no_new*(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to an *nxo*.

Output(s): None.

Exception(s): None.

Description: Constructor.

4.10.24 nxo_null

The *nxo_null* class is a subclass of the *nxo* class.

API

void *nxo_null_new*(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to an *nxo*.

Output(s): None.

Exception(s): None.

Description: Constructor.

4.10.25 nxo_operator

The *nxo_operator* class is a subclass of the *nxo* class.

API

void *nxo_operator_new*(cw_nxo_t *a_nxo, cw_op_t *a_op, cw_nxn_t a_nxn):

Input(s):

- a_nxo:** Pointer to an operator *nxo*.
- a_op:** Pointer to an operator function.
- a_nxn:** NXN_ZERO, or an *nxn*.

Output(s): None.

Exception(s): None.

Description: Constructor.

cw_op_t * *nxo_operator_f*(const cw_nxo_t *a_nxo):

Input(s):

- a_nxo:** Pointer to an operator *nxo*.

Output(s):

- retval:** Pointer to an operator function.

Exception(s): None.

Description: Return the operator function associated with *a_nxo*.

4.10.26 *nxo_pmark*

The *nxo_pmark* class is a subclass of the *nxo* class.

API

void *nxo_pmark_new*(cw_nxo_t *a_nxo):

Input(s):

- a_nxo:** Pointer to an *nxo*.

Output(s): None.

Exception(s): None.

Description: Constructor.

4.10.27 *nxo_real*

The *nxo_real* class is a subclass of the *nxo* class.

API

void *nxo_real_new*(cw_nxo_t *a_nxo, cw_nxor_t a_val):

Input(s):

- a_nxo:** Pointer to a real *nxo*.

a_val: Initial value.

Output(s): None.

Exception(s): None.

Description: Constructor.

`cw_nxor_t nxo_real_get(const cw_nxo_t *a_nxo):`

Input(s):

a_nxo: Pointer to a real *nxo*.

Output(s):

retval: Value of *a_nxo*.

Exception(s): None.

Description: Return the value of *a_nxo*.

`void nxo_real_set(cw_nxo_t *a_nxo, cw_nxor_t a_val):`

Input(s):

a_nxo: Pointer to a real *nxo*.

a_val: Real value.

Output(s): None.

Exception(s): None.

Description: Set the value of *a_nxo* to *a_val*.

4.10.28 nxo_stack

The *nxo_stack* class is a subclass of the *nxo* class.

API

`void nxo_stack_new(cw_nxo_t *a_nxo, cw_nx_t *a_nx, cw_bool_t a_locking):`

Input(s):

a_nxo: Pointer to a stack *nxo*.

a_nx: Pointer to an *nx*.

a_locking: Implicit locking mode.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Constructor.

`void nxo_stack_copy(cw_nxo_t *a_to, cw_nxo_t *a_from):`

Input(s):

a_to: Pointer to a stack *nxo*.

a_from: Pointer to a stack *nxo*.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Copy the objects in *a_from* onto *a_to*.

cw_uint32_t nxo_stack_count(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a stack *nxo*.

Output(s):

retval: Number of objects on *a_nxo*.

Exception(s): None.

Description: Return the number of objects on *a_nxo*.

cw_nxo_t * nxo_stack_push(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a stack *nxo*.

Output(s):

retval: Pointer to a no *nxo* that has been pushed onto *a_nxo*.

Exception(s):

CW_ONYXX_OOM.

Description: Push a no *nxo* onto *a_nxo* and return a pointer to it.

cw_nxo_t * nxo_stack_bpush(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a stack *nxo*.

Output(s):

retval: Pointer to a no *nxo* that has been pushed onto the bottom of *a_nxo*.

Exception(s):

CW_ONYXX_OOM.

Description: Push a no *nxo* onto the bottom of *a_nxo* and return a pointer to it.

cw_nxo_t * nxo_stack_under_push(cw_nxo_t *a_nxo, cw_nxo_t *a_object):

Input(s):

a_nxo: Pointer to a stack *nxo*.

a_object: Pointer to an *nxo* on *a_nxo*.

Output(s):

retval: Pointer to a no *nxo* that has been pushed under *a_object* on *a_nxo*.

Exception(s):

CW_ONYXX_OOM.

Description: Push a no *nxo* under *a_object* on *a_nxo*.

cw_bool_t nxo_stack_pop(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a stack *nxo*.

Output(s):**retval:****FALSE:** Success.**TRUE:** Stack underflow.**Exception(s):** None.**Description:** Pop an object off of *a_nxo*.**cw_bool_t nxo_stack_bpop(cw_nxo_t *a_nxo):****Input(s):****a_nxo:** Pointer to a stack *nxo*.**Output(s):****retval:****FALSE:** Success.**TRUE:** Stack underflow.**Exception(s):** None.**Description:** Pop an object off the bottom of *a_nxo*.**cw_bool_t nxo_stack_npop(cw_nxo_t *a_nxo, cw_uint32_t a_count):****Input(s):****a_nxo:** Pointer to a stack *nxo*.**a_count:** Number of objects to pop off of *a_nxo*.**Output(s):****retval:****FALSE:** Success.**TRUE:** Stack underflow.**Exception(s):** None.**Description:** Pop *a_count* objects off of *a_nxo*.**cw_bool_t nxo_stack_nbpop(cw_nxo_t *a_nxo, cw_uint32_t a_count):****Input(s):****a_nxo:** Pointer to a stack *nxo*.**a_count:** Number of objects to pop off the bottom of *a_nxo*.**Output(s):****retval:****FALSE:** Success.**TRUE:** Stack underflow.**Exception(s):** None.**Description:** Pop *a_count* objects off the bottom of *a_nxo*.**void nxo_stack_remove(cw_nxo_t *a_nxo, cw_nxo_t *a_object):****Input(s):****a_nxo:** Pointer to a stack *nxo*.**a_object:** Pointer to an object on *a_nxo*.

Output(s): None.

Exception(s): None. Remove *a_object* from *a_nxo*.

Description:

`cw_nxo_t * nxo_stack_get(const cw_nxo_t *a_nxo):`

Input(s):

a_nxo: Pointer to a stack *nxo*.

Output(s):

retval:

non-NULL: Pointer to the top *nxo* on *a_nxo*.

NULL: Stack underflow.

Exception(s): None.

Description: Return a pointer to the top *nxo* on *a_nxo*.

`cw_nxo_t * nxo_stack_bget(const cw_nxo_t *a_nxo):`

Input(s):

a_nxo: Pointer to a stack *nxo*.

Output(s):

retval:

non-NULL: Pointer to the bottom *nxo* on *a_nxo*.

NULL: Stack underflow.

Exception(s): None.

Description: Return a pointer to the bottom *nxo* on *a_nxo*.

`cw_nxo_t * nxo_stack_nget(const cw_nxo_t *a_nxo, cw_uint32_t a_index):`

Input(s):

a_nxo: Pointer to a stack *nxo*.

a_index: Index of object in *a_nxo* to return a pointer to.

Output(s):

retval:

non-NULL: Pointer to the *nxo* on *a_nxo* at index *a_index*.

NULL: Stack underflow.

Exception(s): None.

Description: Return a pointer to the *nxo* on *a_nxo* at index *a_index*.

`cw_nxo_t * nxo_stack_nbget(const cw_nxo_t *a_nxo, cw_uint32_t a_index):`

Input(s):

a_nxo: Pointer to a stack *nxo*.

a_index: Index, counting from the bottom, of object in *a_nxo* to return a pointer to.

Output(s):

retval:

non-NULL: Pointer to the *nxo* on *a_nxo* at index *a_index*, counting from the bottom.

NULL: Stack underflow.

Exception(s): None.

Description: Return a pointer to the *nxo* on *a_nxo* at index *a_index*, counting from the bottom.

`cw_nxo_t * nxo_stack_down_get(const cw_nxo_t *a_nxo, cw_nxo_t *a_object):`

Input(s):

a_nxo: Pointer to a stack *nxo*.

a_object: Pointer to an object on *a_nxo*, or NULL for the top object on *a_nxo*.

Output(s):

retval:

non-NULL: Pointer to the *nxo* on *a_nxo* under *a_object*.

NULL: Stack underflow.

Exception(s): None. Return a pointer to the *nxo* on *a_nxo* under *a_object*.

Description:

`cw_nxo_t * nxo_stack_up_get(const cw_nxo_t *a_nxo, cw_nxo_t *a_object):`

Input(s):

a_nxo: Pointer to a stack *nxo*.

a_object: Pointer to an object on *a_nxo*, or NULL for the bottom object on *a_nxo*.

Output(s):

retval:

non-NULL: Pointer to the *nxo* on *a_nxo* over *a_object*.

NULL: Stack underflow.

Exception(s): None. Return a pointer to the *nxo* on *a_nxo* over *a_object*.

Description:

`cw_bool_t nxo_stack_exch(cw_nxo_t *a_nxo):`

Input(s):

a_nxo: Pointer to a stack *nxo*.

Output(s):

retval:

FALSE: Success.

TRUE: Stack underflow.

Exception(s): None.

Description: Exchange the top two objects on *a_nxo*.

`void nxo_stack_rot(cw_nxo_t *a_nxo, cw_sint32_t a_amount):`

Input(s):

a_nxo: Pointer to a stack *nxo*.

a_amount: Amount to rotate upward. A negative value rotates downward.

Output(s): None.

Exception(s): None.

Description: Rotate *a_nxo* up by *a_amount*.

`cw_bool_t nxo_stack_roll(cw_nxo_t *a_nxo, cw_uint32_t a_count, cw_sint32_t a_amount):`

Input(s):**a_nxo:** Pointer to a stack *nxo*.**a_count:** Number of objects in roll region.**a_amount:** Amount to roll upward. A negative value rolls downward.**Output(s):****retval:****FALSE:** Success.**TRUE:** Stack underflow.**Exception(s):** None.**Description:** Roll the top *a_count* objects on *a_nxo* up by *a_amount*.**4.10.29 nxo_string**

The *nxo_string* class is a subclass of the *nxo* class. Strings are not ‘\0’-terminated, mainly since substrings are references to other strings, and the termination character wouldn’t be consistently useful. *nxo_string_cstring()* is useful for creating ‘\0’-terminated copies of strings for situations where other C functions expect terminated strings.

API

void *nxo_string_new*(cw_nxo_t *a_nxo, cw_nx_t *a_nx, cw_bool_t a_locking, cw_uint32_t a_len):

Input(s):**a_nxo:** Pointer to a string *nxo*.**a_nx:** Pointer to an *nx*.**a_locking:** Implicit locking mode.**a_len:** Length in bytes of string to create.**Output(s):** None.**Exception(s):****CW_ONYXX_OOM.****Description:** Constructor.

void *nxo_string_substring_new*(cw_nxo_t *a_nxo, cw_nxo_t *a_string, cw_nx_t *a_nx, cw_uint32_t a_offset, cw_uint32_t a_len):

Input(s):**a_nxo:** Pointer to a string *nxo*.**a_string:** Pointer to a string *nxo* to create a substring of.**a_nx:** Pointer to an *nx*.**a_offset:** Offset into *a_string*.**a_len:** Length in bytes of substring to create.**Output(s):** None.**Exception(s):****CW_ONYXX_OOM.**

Description: Substring constructor.

void *nxo_string_copy*(cw_nxo_t *a_to, cw_nxo_t *a_from):

Input(s):

a_to: Pointer to a string *nxo*.

a_from: Pointer to a string *nxo*.

Output(s): None.

Exception(s): None.

Description: Copy the contents of *a_from* to *a_to*. The length of *a_to* must be at least that of *a_from*.

void *nxo_string_cstring*(cw_nxo_t *a_to, cw_nxo_t *a_from, cw_nxo_t *a_thread):

Input(s):

a_to: Pointer to an *nxo*.

a_from: Pointer to a string or name *nxo*.

a_thread: Pointer to a thread *nxo*.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Create a copy of *a_from*, but append a ‘\0’ character to make it usable in calls to typical C functions that expect a terminated string.

cw_uint32_t *nxo_string_len_get*(const cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a string *nxo*.

Output(s):

retval: Length of *a_nxo*.

Exception(s): None.

Description: Return the length of *a_nxo*.

void *nxo_string_el_get*(const cw_nxo_t *a_nxo, cw_nxoi_t a_offset, cw_uint8_t *r_el):

Input(s):

a_nxo: Pointer to a string *nxo*.

a_offset: Offset of character to get.

r_el: Pointer to space to copy a character to.

Output(s):

***r_el:** A copy of the character of *a_nxo* at offset *a_offset*.

Exception(s): None.

Description: Get a copy of the character of *a_nxo* at offset *a_offset*.

void *nxo_string_el_set*(cw_nxo_t *a_nxo, cw_uint8_t a_el, cw_nxoi_t a_offset):

Input(s):

a_nxo: Pointer to a string *nxo*.

a_el: A character.

a_offset: Offset of character in *a_nxo* to replace with *a_el*.

Output(s): None.

Exception(s): None.

Description: Copy *a_el* into the element of *a_nxo* at offset *a_offset*.

void *nxo_string_lock*(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a string *nxo*.

Output(s): None.

Exception(s): None.

Description: If implicit locking is activated for *a_nxo*, lock it.

void *nxo_string_unlock*(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a string *nxo*.

Output(s): None.

Exception(s): None.

Description: If implicit locking is activated for *a_nxo*, unlock it.

cw_uint8_t * *nxo_string_get*(const cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a string *nxo*.

Output(s):

retval: Pointer to the string internal to *a_nxo*.

Exception(s): None.

Description: Return a pointer to the string internal to *a_nxo*.

void *nxo_string_set*(cw_nxo_t *a_nxo, cw_uint32_t a_offset, const cw_uint8_t *a_str, cw_uint32_t a_len):

Input(s):

a_nxo: Pointer to a string *nxo*.

a_offset: Offset into *a_nxo* to replace.

a_str: String to replace a range of *a_nxo* with.

a_len: Length in bytes of *a_str*.

Output(s): None.

Exception(s): None.

Description: Replace *a_len* bytes of *a_nxo* at offset *a_offset* with *a_str*.

4.10.30 *nxo_thread*

The *nxo_thread* class is a subclass of the *nxo* class.

The *threadp* class is a helper class that contains scanner position information. The *threadp* state is used when recording syntax errors.

API

void *nxo_threadp_new*(cw_nxo_threadp_t *a_threadp):

Input(s):

a_threadp: Pointer to space for a *threadp*.

Output(s): None.

Exception(s): None.

Description: Constructor.

void *nxo_threadp_delete*(cw_nxo_threadp_t *a_threadp, cw_nxo_t *a_thread):

Input(s):

a_threadp: Pointer to a *threadp*.

a_thread: Pointer to a thread *nxo*.

Output(s): None.

Exception(s): None.

Description: Destructor.

void *nxo_threadp_position_get*(const cw_nxo_threadp_t *a_threadp, cw_uint32_t *r_line, cw_uint32_t *r_column):

Input(s):

a_threadp: Pointer to space for a *threadp*.

r_line: Pointer to a location to store a line number.

r_column: Pointer to a location to store a column number.

Output(s):

***r_line:** Line number.

***r_column:** Column number.

Exception(s): None.

Description: Retrieve the line number and column number.

void *nxo_threadp_position_set*(cw_nxo_threadp_t *a_threadp, cw_uint32_t a_line, cw_uint32_t a_column):

Input(s):

a_threadp: Pointer to space for a *threadp*.

a_line: Line number.

a_column: Column number.

Output(s): None.

Exception(s): None.

Description: Set the line number and column number.

void *nxo_thread_new*(cw_nxo_t *a_nxo, cw_nx_t *a_nx):

Input(s):

a_nxo: Pointer to a thread *nxo*.

a_nx: Pointer to an *nx*.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Constructor.

void *nxo_thread_start*(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s): None.

Exception(s): Application dependent.

Description: Start a thread running by calling the **start** operator such that the top object on ostack will be executed.

void *nxo_thread_exit*(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s): None.

Exception(s): None.

Description: Terminate the thread. This has the same effect as a detached thread exiting. Calling this function may is necessary (depending on the application) to allow the thread to be garbage collected, much the same way as the **detach** and **join** operators do.

void *nxo_thread_thread*(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s): None.

Exception(s):

CW_ONYXX_OOM.

Description: Create a new thread. The new thread calls *nxo_thread_start*().

void *nxo_thread_detach*(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s): None.

Exception(s): None.

Description: Detach *a_nxo* so that when it exits it can be garbage collected.

void *nxo_thread_join*(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s): None.

Exception(s): None.

Description: Wait for *a_nxo* to exit.

cw_nxo_threadts_t *nxo_thread_state*(const cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s):

retval: The current scanner state of *a_nxo*.

THREADTS_START: Start state.

THREADTS_COMMENT: '%' seen, but no line break yet.

THREADTS_INTEGER: Scanning an integer.

THREADTS_INTEGER_RADIX: Scanning a radix integer.

THREADTS_REAL_FRAC: Scanning the fractional portion of a real.

THREADTS_REAL_EXP: Scanning the exponent portion of a real.

THREADTS_STRING: Scanning a string.

THREADTS_STRING_NEWLINE_CONT: '\r' seen in a string.

THREADTS_STRING_PROT_CONT: '\\ ' seen in a string.

THREADTS_STRING_CRLF_CONT: '\r' seen in a string.

THREADTS_STRING_CTRL_CONT: '\c' seen in a string.

THREADTS_STRING_HEX_CONT: '\x' seen in a string.

THREADTS_STRING_HEX_FINISH: First hex digit of a "\xDD" string escape sequence seen.

THREADTS_NAME_START: '?', '\$', or '~' seen.

THREADTS_NAME: Scanning a name.

Exception(s): None.

Description: Return the current scanner state. In general this is only useful when implementing an interactive environment for which the prompt behaves differently depending on what state the scanner is in. For example the interactive *onyx* shell needs only to know whether the scanner is in the start state.

cw_bool_t nxo_thread_deferred(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s):

retval:

FALSE: Execution is not deferred.

TRUE: Execution is deferred.

Exception(s): None.

Description: Return whether the scanner is currently in deferred execution mode. See Section 2.2 for information on deferred execution. In general this is only useful when implementing an interactive environment for which the prompt behaves differently depending on what state the scanner is in.

void nxo_thread_reset(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s): None.

Exception(s): None.

Description: Reset the scanner to the start state, and turn deferral off. This is a dangerous feature that should be used with great care. *nxo_no* objects should never be visible from inside the interpreter, so the caller must assure that any *nxo_no* objects are removed before further processing is done in the context of *a_nxo*.

void *nxo_thread_loop*(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s): None.

Exception(s): Application specific.

Description: Execute the top object on estack. The caller is responsible for placing the object on estack, but it is removed before this function returns.

void *nxo_thread_interpret*(cw_nxo_t *a_nxo, cw_nxo_threadp_t *a_threadp, const cw_uint8_t *a_str, cw_uint32_t a_len):

Input(s):

a_nxo: Pointer to a thread *nxo*.

a_threadp: A *threadp*.

a_str: Pointer to a string to interpret.

a_len: Length in bytes of *a_str*.

Output(s): None.

Exception(s): Application specific.

Description: Interpret the string pointed to by *a_str*.

void *nxo_thread_flush*(cw_nxo_t *a_nxo, cw_nxo_threadp_t *a_threadp):

Input(s):

a_nxo: Pointer to a thread *nxo*.

a_threadp: A *threadp*.

Output(s): None.

Exception(s): Application specific.

Description: Do the equivalent of interpreting a carriage return in order to force acceptance of the previous token if no whitespace has yet followed.

void *nxo_thread_nerror*(cw_nxo_t *a_nxo, cw_nxn_t a_nxn):

Input(s):

a_nxo: Pointer to a thread *nxo*.

a_nxn: An *nxn* corresponding to the name of an error.

Output(s): None.

Exception(s): Application dependent.

Description: Throw an error.

void *nxo_thread_serror*(cw_nxo_t *a_nxo, const cw_uint8_t a_str, cw_uint32_t a_len):

Input(s):

a_nxo: Pointer to a thread *nxo*.

a_str: Pointer to a string that represents the name of an error.

a_len: The length of *a_str*.

Output(s): None.

Exception(s): Application dependent.

Description: Throw an error.

`cw_bool_t nxo_thread_dstack_search(cw_nxo_t *a_nxo, cw_nxo_t *a_key, cw_nxo_t *r_value):`

Input(s):

a_nxo: Pointer to a thread *nxo*.

a_key: Pointer to an *nxo*.

r_value: Pointer to an *nxo*.

Output(s):

retval:

FALSE: Success.

TRUE: *a_key* not found on dstack.

r_value: Top value in dstack associated with *a_key*.

Exception(s): None.

Description: Search dstack for the topmost definition of *a_key* and dup its value to *r_value*.

`cw_bool_t nxo_thread_currentlocking(const cw_nxo_t *a_nxo):`

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s):

retval:

FALSE: Implicit locking deactivated for new objects.

TRUE: Implicit locking activated for new objects.

Exception(s): None.

Description: Return whether implicit locking is activated for new objects.

`void nxo_thread_setlocking(cw_nxo_t *a_nxo, cw_bool_t a_locking):`

Input(s):

a_nxo: Pointer to a thread *nxo*.

a_locking:

FALSE: Do not implicitly lock new objects.

TRUE: Implicitly lock new objects.

Output(s): None.

Exception(s): None.

Description: Activate or deactivate implicit locking for new objects.

`cw_nx_t * nxo_thread_nx_get(cw_nxo_t *a_nxo):`

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s):

retval: Pointer to an *nx*.

Exception(s): None.

Description: Return the *nx* associated with *a_nxo*.

cw_nxo_t * nxo_thread_userdict_get(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s):

retval: Pointer to an *nxo* that can safely be used without risk of being garbage collected.

Exception(s): None.

Description: Return a pointer to the userdict associated with *a_nxo*.

cw_nxo_t * nxo_thread_errordict_get(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s):

retval: Pointer to an *nxo* that can safely be used without risk of being garbage collected.

Exception(s): None.

Description: Return a pointer to the errordict associated with *a_nxo*.

cw_nxo_t * nxo_thread_currenterror_get(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s):

retval: Pointer to an *nxo* that can safely be used without risk of being garbage collected.

Exception(s): None.

Description: Return a pointer to the currenterror associated with *a_nxo*.

cw_nxo_t * nxo_thread_ostack_get(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s):

retval: Pointer to an *nxo* that can safely be used without risk of being garbage collected.

Exception(s): None.

Description: Return a pointer to the ostack associated with *a_nxo*.

cw_nxo_t * nxo_thread_dstack_get(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s):

retval: Pointer to an *nxo* that can safely be used without risk of being garbage collected.

Exception(s): None.

Description: Return a pointer to the dstack associated with *a_nxo*.

cw_nxo_t * nxo_thread_estack_get(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s):

retval: Pointer to an *nxo* that can safely be used without risk of being garbage collected.

Exception(s): None.

Description: Return a pointer to the estack associated with *a_nxo*.

cw_nxo_t * nxo_thread_istack_get(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s):

retval: Pointer to an *nxo* that can safely be used without risk of being garbage collected.

Exception(s): None.

Description: Return a pointer to the istack associated with *a_nxo*.

cw_nxo_t * nxo_thread_tstack_get(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s):

retval: Pointer to an *nxo* that can safely be used without risk of being garbage collected.

Exception(s): None.

Description: Return a pointer to the tstack associated with *a_nxo*.

cw_nxo_t * nxo_thread_stdin_get(cw_nxo_t *a_nxo):

Input(s):

a_nxo: Pointer to a thread *nxo*.

Output(s):

retval: Pointer to an *nxo* that can safely be used without risk of being garbage collected.

Exception(s): None.

Description: Return a pointer to the stdin associated with *a_nxo*.

void nxo_thread_stdin_set(cw_nxo_t *a_nxo, cw_nxo_t *a_stdin):

Input(s):

a_nxo: Pointer to a thread *nxo*.

a_stdin: Pointer to a file *nxo*.

Output(s): None.

Exception(s): None.

Description: Set *a_nxo*'s stdin to *a_stdin*.

cw_nxo_t * nxo_thread_stdout_get(cw_nxo_t *a_nxo):

Input(s):**a_nxo:** Pointer to a thread *nxo*.**Output(s):****retval:** Pointer to an *nxo* that can safely be used without risk of being garbage collected.**Exception(s):** None.**Description:** Return a pointer to the stdout associated with *a_nxo*.**void *nxo_thread_stdout_set*(*cx_nxo_t* **a_nxo*, *cx_nxo_t* **a_stdout*):****Input(s):****a_nxo:** Pointer to a thread *nxo*.**a_stdout:** Pointer to a file *nxo*.**Output(s):** None.**Exception(s):** None.**Description:** Set *a_nxo*'s stdout to *a_stdout*.***cx_nxo_t* * *nxo_thread_stderr_get*(*cx_nxo_t* **a_nxo*):****Input(s):****a_nxo:** Pointer to a thread *nxo*.**Output(s):****retval:** Pointer to an *nxo* that can safely be used without risk of being garbage collected.**Exception(s):** None.**Description:** Return a pointer to the stderr associated with *a_nxo*.**void *nxo_thread_stderr_set*(*cx_nxo_t* **a_nxo*, *cx_nxo_t* **a_stderr*):****Input(s):****a_nxo:** Pointer to a thread *nxo*.**a_stderr:** Pointer to a file *nxo*.**Output(s):** None.**Exception(s):** None.**Description:** Set *a_nxo*'s stderr to *a_stderr*.

4.10.31 ql

The *ql* macros implement operations on a list. The type of the list elements and which field of the elements to use are determined by arguments that are passed into the macros. The macros are optimized for speed and code size, which means that there is minimal error checking built in. As a result, care must be taken to assure that these macros are used as intended, or strange things can happen.

Internally, the list is represented as a ring, so with some care, the *ql* and *qr* interfaces can be used in conjunction with each other.

Since a *ql* is actually a ring, it is possible to have multiple *ql* heads that share the same ring. This works just fine, with the caveat that operations on one *ql* can have side-effects on another.

API

***ql_head*(*<ql_type> a_type*):**

Input(s):

a_type: Data type for the *ql* elements.

Output(s): A data structure that can be used as a *ql* head.

Exception(s): None.

Description: Generate code for a *ql* head data structure.

***ql_head_initializer*(*<ql_type> *a_head*):**

Input(s):

a_head: Pointer to a *ql* head.

Output(s): None.

Exception(s): None.

Description: Statically initialize a *ql* head.

***ql_elm*(*<ql_type> a_type*):**

Input(s):

a_type: Data type for the *ql* elements.

Output(s): A data structure that can be used as a *ql* element.

Exception(s): None.

Description: Generate code for a *ql* element data structure.

***void ql_new*(*<ql_head> *a_head*):**

Input(s):

a_head: Pointer to a *ql* head.

Output(s): None.

Exception(s): None.

Description: Constructor.

***void ql_elm_new*(*<ql_type> *a_elm, <field_name> a_field*):**

Input(s):

a_elm: Pointer to an element.

a_field: Field within the *ql* elements to use.

Output(s): None.

Exception(s): None.

Description: Constructor.

***<ql_type> *ql_first*(*<ql_head> *a_head*):**

Input(s):

a_head: Pointer to a *ql* head.

Output(s):

retval:

non-NULL: Pointer to the first element in *a_head*.

NULL: *a_head* is empty.

Exception(s): None.

Description: Return a pointer to the first element in the *ql*.

<ql_type> *ql_last(<ql_head> *a_head, <field_name> a_field):

Input(s):

a_head: Pointer to a *ql* head.

a_field: Field within the *ql* elements to use.

Output(s):

retval:

non-NULL: Pointer to the last element in *a_head*.

NULL: *a_head* is empty.

Exception(s): None.

Description: Return a pointer to the last element in the *ql*.

<ql_type> *ql_next(<ql_head> *a_head, <ql_type> *a_elm, <field_name> a_field):

Input(s):

a_head: Pointer to a *ql* head.

a_elm: Pointer to an element.

a_field: Field within the *ql* elements to use.

Output(s):

retval:

non-NULL: Pointer to the element after *a_elm*.

NULL: *a_elm* is the last element in *a_head*.

Exception(s): None.

Description: Return a pointer to the element in *a_head* after *a_elm*.

<ql_type> *ql_prev(<ql_head> *a_head, <ql_type> *a_elm, <field_name> a_field):

Input(s):

a_head: Pointer to a *ql* head.

a_elm: Pointer to an element.

a_field: Field within the *ql* elements to use.

Output(s):

retval:

non-NULL: Pointer to the element before *a_elm*.

NULL: *a_elm* is the first element in *a_head*.

Exception(s): None.

Description: Return a pointer to the element in *a_head* before *a_elm*.

void ql_before_insert(<ql_head> *a_head, <ql_type> *a_qlelm, <ql_type> *a_elm, <field_name> a_field):

Input(s):

a_head: Pointer to a *ql* head.

a_qlelm: Pointer to an element within *a_head*.

a_elm: Pointer to an element.

a_field: Field within the *ql* elements to use.

Output(s): None.

Exception(s): None.

Description: Insert *a_elm* into *a_head* before *a_qlelm*.

void ql_after_insert(<ql_type> *a_qlelm, <ql_type> *a_elm, <field_name> a_field):

Input(s):

a_qlelm: Pointer to an element within *a_head*.

a_elm: Pointer to an element.

a_field: Field within the *ql* elements to use.

Output(s): None.

Exception(s): None.

Description: Insert *a_elm* into *a_head* after *a_qlelm*.

void ql_head_insert(<ql_head> *a_head, <ql_type> *a_elm, <field_name> a_field):

Input(s):

a_head: Pointer to a *ql* head.

a_elm: Pointer to an element.

a_field: Field within the *ql* elements to use.

Output(s): None.

Exception(s): None.

Description: Insert *a_elm* at the head of *a_head*.

void ql_tail_insert(<ql_head> *a_head, <ql_type> *a_elm, <field_name> a_field):

Input(s):

a_head: Pointer to a *ql* head.

a_elm: Pointer to an element.

a_field: Field within the *ql* elements to use.

Output(s): None.

Exception(s): None.

Description: Insert *a_elm* at the tail of *a_head*.

void ql_remove(<ql_head> *a_head, <ql_type> *a_elm, <field_name> a_field):

Input(s):

a_head: Pointer to a *ql* head.

a_elm: Pointer to an element.

a_field: Field within the *ql* elements to use.

Output(s): None.

Exception(s): None.

Description: Remove *a_elm* from *a_head*.

void ql_head_remove(<ql_head> *a_head, <ql_type> a_type, <field_name> a_field):

Input(s):

- a_head:** Pointer to a *ql* head.
- a_type:** Data type for the *ql* elements.
- a_field:** Field within the *ql* elements to use.

Output(s): None.**Exception(s):** None.**Description:** Remove the head element of *a_head*.**void *ql_tail_remove*(*<ql_head> *a_head, <ql_type> a_type, <field_name> a_field*):****Input(s):**

- a_head:** Pointer to a *ql* head.
- a_type:** Data type for the *ql* elements.
- a_field:** Field within the *ql* elements to use.

Output(s): None.**Exception(s):** None.**Description:** Remove the tail element of *a_head*.***ql_foreach*(*<ql_type> *a_var, <ql_type> *a_head, <field_name> a_field*):****Input(s):**

- a_var:** The name of a temporary variable to use for iteration.
- a_head:** Pointer to a *ql* head.
- a_field:** Field within the *ql* elements to use.

Output(s): None.**Exception(s):** None.**Description:** Iterate through the *ql*, storing a pointer to each element in *a_var* along the way.***ql_reverse_foreach*(*<ql_type> *a_var, <ql_type> *a_head, <field_name> a_field*):****Input(s):**

- a_var:** The name of a temporary variable to use for iteration.
- a_head:** Pointer to a *ql* head.
- a_field:** Field within the *ql* elements to use.

Output(s): None.**Exception(s):** None.**Description:** Iterate through the *ql* in the reverse direction, storing a pointer to each element in *a_var* along the way.**4.10.32 qr**

The *qr* macros implement operations on a ring. The type of the ring elements and which field of the elements to use are determined by arguments that are passed into the macros. The macros are optimized for speed and code size, which means that there is minimal error checking built in. As a result, care must be taken to assure that these are used as intended, or strange things can happen.

API

qr(**<qr_type>** **a_type**):

Input(s):

a_type: Data type for the *qr*.

Output(s): A data structure that can be used for a *qr*.

Exception(s): None.

Description: Generate code for a *qr* data structure.

void *qr_new*(**<qr_type>** ***a_qr**, **<field_name>** **a_field**):

Input(s):

a_qr: Pointer to a *qr*.

a_field: Field within the *qr* elements to use.

Output(s): None.

Exception(s): None.

Description: Constructor.

<qr_type> * *qr_next*(**<qr_type>** ***a_qr**, **<field_name>** **a_field**):

Input(s):

a_qr: Pointer to a *qr*.

a_field: Field within the *qr* elements to use.

Output(s):

retval: Pointer to the next element in the *qr*.

Exception(s): None.

Description: Return a pointer to the next element in the *qr*.

<qr_type> * *qr_prev*(**<qr_type>** ***a_qr**, **<field_name>** **a_field**):

Input(s):

a_qr: Pointer to a *qr*.

a_field: Field within the *qr* elements to use.

Output(s):

retval: Pointer to the previous element in the *qr*.

Exception(s): None.

Description: Return a pointer to the previous element in the *qr*.

void *qr_before_insert*(**<qr_type>** ***a_qrelm**, **<qr_type>** ***a_qr**, **<field_name>** **a_field**):

Input(s):

a_qrelm: Pointer to an element in a *qr*.

a_qr: Pointer to an element that is the only element in its ring.

a_field: Field within the *qr* elements to use.

Output(s): None.

Exception(s): None.

Description: Insert *a_qr* before *a_qrelm*.

void *qr_after_insert*(*<qr_type> *a_qrelm, <qr_type> *a_qr, <field_name> a_field*):

Input(s):

a_qrelm: Pointer to an element in a *qr*.

a_qr: Pointer to an element that is the only element in its ring.

a_field: Field within the *qr* elements to use.

Output(s): None.

Exception(s): None.

Description: Insert *a_qr* after *a_qrelm*.

void *qr_meld*(*<qr_type> *a_qr_a, <qr_type> *a_qr_b, <field_name> a_field*):

Input(s):

a_qr_a: Pointer to a *qr*.

a_qr_b: Pointer to a *qr*.

a_field: Field within the *qr* elements to use.

Output(s): None.

Exception(s): None.

Description: Meld *a_qr_a* and *a_qr_b* into one ring.

void *qr_split*(*<qr_type> *a_qr_a, <qr_type> *a_qr_b, <field_name> a_field*):

Input(s):

a_qr_a: Pointer to a *qr*.

a_qr_b: Pointer to a *qr*.

a_field: Field within the *qr* elements to use.

Output(s): None.

Exception(s): None.

Description: Split a ring at *a_qr_a* and *a_qr_b*.

void *qr_remove*(*<qr_type> *a_qr, <field_name> a_field*):

Input(s):

a_qr: Pointer to a *qr*.

a_field: Field within the *qr* elements to use.

Output(s): None.

Exception(s): None.

Description: Remove *a_qr* from the ring.

***qr_foreach*(*<qr_type> *a_var, <qr_type> *a_qr, <field_name> a_field*):**

Input(s):

a_var: The name of a temporary variable to use for iteration.

a_qr: Pointer to a *qr*.

a_field: Field within the *qr* elements to use.

Output(s): None.

Exception(s): None.

Description: Iterate through the *qr*, storing a pointer to each element in *a_var* along the way.

qr_reverse_foreach(*<qr_type> *a_var, <qr_type> *a_qr, <field_name> a_field*):

Input(s):

a_var: The name of a temporary variable to use for iteration.

a_qr: Pointer to a *qr*.

a_field: Field within the *qr* elements to use.

Output(s): None.

Exception(s): None.

Description: Iterate through the *qr* in the reverse direction, storing a pointer to each element in *a_var* along the way.

4.10.33 *qs*

The *qs* macros implement operations on a stack. The type of the stack elements and which field of the elements to use are determined by arguments that are passed into the macros. The macros are optimized for speed and code size, which means that there is minimal error checking built in. As a result, care must be taken to assure that these macros are used as intended, or strange things can happen.

API

qs_head(*<qs_type> a_type*):

Input(s):

a_type: Data type for the *qs*.

Output(s): A data structure that can be used as a *qs* head.

Exception(s): None.

Description: Generate code for a *qs* head data structure.

qs_head_initializer(*<qs_type> *a_head*):

Input(s):

a_head: Pointer to a *qs* head.

Output(s): None.

Exception(s): None.

Description: Statically initialize a *qs* head.

qs_elm(*<qs_elm_type> a_type*):

Input(s):

a_type: Data type for the *qs* elements.

Output(s): A data structure that can be used as a *qs* element.

Exception(s): None.

Description: Generate code for a *qs* element data structure.

void *qs_new*(<qs_type> *a_head):

Input(s):

a_head: Pointer to a *qs* head.

Output(s): None.

Exception(s): None.

Description: Constructor.

void *qs_elm_new*(<qs_elm_type> *a_elm, <field_name> a_field):

Input(s):

a_head: Pointer to a *qs* element.

a_field: Field within the *qs* elements to use.

Output(s): None.

Exception(s): None.

Description: Constructor.

<qs_type> **qs_top*(<qs_type> *a_head):

Input(s):

a_head: Pointer to a *qs* head.

Output(s):

retval: Pointer to the top element in the *qs*.

Exception(s): None.

Description: Return a pointer to the top element in the *qs*.

<qs_type> **qs_down*(<qs_elm_type> *a_elm, <field_name> a_field):

Input(s):

a_elm: Pointer to a *qs* element.

a_field: Field within the *qs* elements to use.

Output(s):

retval:

non-NULL: Pointer to the next element in the *qs*.

NULL: *a_elm* is the bottom element in the *qs*.

Exception(s): None.

Description: Return a pointer to the next element in the *qs* below *a_elm*.

void *qs_push*(<qs_type> *a_head, <qs_elm_type> *a_elm, <field_name> a_field):

Input(s):

a_head: Pointer to a *qs* head.

a_elm: Pointer to an element.

a_field: Field within the *qs* elements to use.

Output(s): None.

Exception(s): None.

Description: Push *a_elm* onto the *qs*.

void *qs_under_push*(*<qs_elm_type> *a_qselm, <qs_elm_type> *a_elm, <field_name> a_field*):

Input(s):

a_qselm: Pointer to a *qs* element.

a_elm: Pointer to an element.

a_field: Field within the *qs* elements to use.

Output(s): None.

Exception(s): None.

Description: Push *a_elm* under *a_qselm*.

void *qs_pop*(*<qs_type> *a_head, <field_name> a_field*):

Input(s):

a_head: Pointer to a *qs* head.

a_field: Field within the *qs* elements to use.

Output(s): None.

Exception(s): None.

Description: Pop an element off of *a_head*.

***qs_foreach*(*<qs_elm_type> *a_var, <qs_type> *a_head, <field_name> a_field*):**

Input(s):

a_var: The name of a temporary variable to use for iteration.

a_head: Pointer to a *qs* head.

a_field: Field within the *qs* elements to use.

Output(s): None.

Exception(s): None.

Description: Iterate down the *qs*, storing a pointer to each element in *a_var* along the way.

4.10.34 *thd*

The *thd* class implements a wrapper around the system POSIX threads library or GNU pth library. In most regards, this is a thin wrapper around the normal threading functionality, but some extra information is kept in order to allow implementation of thread suspension/resumption, “critical sections”, and “single sections”.

The suspendibility of each thread is determined by the arguments passed to *thd_new*(). The initial thread is always suspendible. Other threads that are created via some mechanism other than *thd_new*() are not suspendible.

Depending on how *libonyx* is built, the additional functionality is implemented with the aid of the *SIGUSR1* and *SIGUSR2* signals. As a result, system calls may be interrupted by signals. The system calls will be automaticalaly restarted if they have made no progress at the time of interruption, but will return a partial result otherwise. Therefore, if any of the additional functionality is utilized, the application must be careful to handle partial system call results. At least the following system calls can be interrupted: *read*(), *write*(), *sendto*(), *recvfrom*(), *sendmsg*(), *recvmsg*(), *ioctl*(), and *wait*(). See the system documentation for additional information.

API

`cw_thd_t * thd_new(void *(*a_start_func)(void *), void *a_arg, cw_bool_t a_suspendible):`

Input(s):

a_start_func: Pointer to a start function.

a_arg: Argument passed to *a_start_func()*.

a_suspendible:

FALSE: Not suspendible.

TRUE: Suspendible.

Output(s):

retval: Pointer to a *thd*.

Exception(s):

CW_ONYXX_OOM.

Description: Constructor (creates a new thread).

`void thd_delete(cw_thd_t *a_thd):`

Input(s):

a_thd: Pointer to a *thd*.

Output(s): None.

Exception(s): None.

Description: Destructor.

`void * thd_join(cw_thd_t *a_thd):`

Input(s):

a_thd: Pointer to a *thd*.

Output(s):

retval: Return value from thread entry function.

Exception(s): None.

Description: Join (wait for) the thread associated with *a_thd*.

`cw_thd_t * thd_self(void):`

Input(s): None.

Output(s):

retval: Pointer to the calling thread's *thd* structure.

Exception(s): None.

Description: Return a pointer to the *thd* structure that corresponds to the calling thread.

`void thd_yield(void):`

Input(s): None.

Output(s): None.

Exception(s): None.

Description: Give up the rest of the calling thread's time slice.

`int thd_sigmask(int a_how, const sigset_t *a_set, sigset_t *r_oset):`

Input(s):**a.how:**

SIG_BLOCK: Block signals in *a.set*.

SIG_UNBLOCK: Unblock signals in *a.set*.

SIG_SETMASK: Set signal mask to *a.set*.

a.set: Pointer to a signal set.

r.oset:

non-NULL: Pointer space to store the old signal mask.

NULL: Ignored.

Output(s):

retval: Always zero, unless the arguments are invalid.

***r.oset:** Old signal set.

Exception(s): None.

Description: Set the calling thread's signal mask.

void *thd_crit_enter*(void):

Input(s): None.

Output(s): None.

Exception(s): None.

Description: Enter a critical region where the calling thread may not be suspended by *thd_suspend()*, *thd_trysuspend()*, or *thd_single_enter()*.

void *thd_crit_leave*(void):

Input(s): None.

Output(s): None.

Exception(s): None.

Description: Leave a critical section; the calling thread may once again be suspended.

void *thd_single_enter*(void):

Input(s): None.

Output(s): None.

Exception(s): None.

Description: Enter a critical region where all other suspendible threads must be suspended.

void *thd_single_leave*(void):

Input(s): None.

Output(s): None.

Exception(s): None.

Description: Leave a critical section where all other threads must be suspended. All threads that were suspended in *thd_single_enter()* are resumed.

void *thd_suspend*(*ew_thd_t* **a.thd*):

Input(s):

a.thd: Pointer to a *thd*.

Output(s): None.

Exception(s): None.

Description: Suspend *a.thd*.

cw_bool_t *thd_trysuspend*(cw_thd_t *a.thd):

Input(s):

a.thd: Pointer to a *thd*.

Output(s):

retval:

FALSE: Success.

TRUE: Failure.

Exception(s): None.

Description: Try to suspend *a.thd*, but fail if it is in a critical section.

void *thd_resume*(cw_thd_t *a.thd):

Input(s):

a.thd: Pointer to a *thd*.

Output(s): None.

Exception(s): None.

Description: Resume (make runnable) *a.thd*.

4.10.35 tsd

The *tsd* class implements thread-specific data. A *tsd* instance can be created, then any number of threads can use that same instance to store and retrieve a thread-specific pointer to data.

API

void *tsd_new*(cw_tsd_t *a.tsd, void (*a.func)(void *):

Input(s):

a.tsd: Pointer to space for a *tsd*.

a.func: Pointer to a cleanup function, or NULL.

Output(s): None.

Exception(s): None.

Description: Constructor.

void *tsd_delete*(cw_tsd_t *a.tsd):

Input(s):

a.tsd: Pointer to a *tsd*.

Output(s): None.

Exception(s): None.

Description: Destructor.

void * *tsd_get*(*cw_tsd_t* **a_tsd*):

Input(s):

a_tsd: Pointer to a *tsd*.

Output(s):

retval: Pointer to thread-specific data.

Exception(s): None.

Description: Get thread-specific data pointer.

***tsd_set*(*cw_tsd_t* **a_tsd*, void **a_val*):**

Input(s):

a_tsd: Pointer to a *tsd*.

a_val: Pointer to thread-specific data.

Output(s): None.

Exception(s): None.

Description: Set thread-specific data pointer.

4.10.36 xep

The *xep* class implements exception handling, with support for *xep_try* and *xep_catch*() blocks. Minimal use must include at least:

```
xep_begin();
xep_try {
    /* Code that might throw an exception. */
}
xep_end();
```

A more complete skeleton looks like:

```
xep_begin();
xep_try {
    /* Code that might throw an exception. */
}
xep_catch(SOME_EXCEPTION) {
    /* Handle exception... */
    xep_handled();
}
xep_catch(ANOTHER_EXCEPTION)
xep_mcatch(YET_ANOTHER) {
    /* React to exception, but propagate... */
}
xep_acatch {
    /* Handle all exceptions not explicitly handled above... */
}
```

```
        xep_handled();  
    }  
    xep_end();
```

Note that there is some serious `cpp` macro magic behind the *xep* interface, and as such, if usage deviates significantly from the above templates, compiler errors may result.

Exception values are of type `cw_xepv_t`. 0 to 127 are reserved by *libonyx*, and other ranges may be reserved by other libraries. See their documentation for details.

An exception is not implicitly handled if an exception handler is executed for that exception. Instead, *xep_handled()* must be manually called to avoid propagating the exception up the handler chain.

It is not legal to return from a function within an exception handling code block; doing so will corrupt the exception handler chain.

API

`void xep_begin(void):`

Input(s): None.

Output(s): None.

Exception(s): None.

Description: Begin an exception handling code block.

`void xep_end(void):`

Input(s): None.

Output(s): None.

Exception(s): None.

Description: End an exception handling block.

`xep_try ...:`

Input(s): None.

Output(s): None.

Exception(s): None.

Description: Begin a block of code that is to be executed, with the possibility that an exception might be thrown.

`xep_catch(cw_xepv_t a_xepv) ...:`

Input(s):

a_xepv: Exception number.

Output(s): None.

Exception(s): None.

Description: Begin a block of code that catches an exception. The exception is not considered handled unless *xep_handled()* is called.

`xep_mcatch(cw_xepv_t a_xepv) ...:`

Input(s):**a_xepv:** Exception number.**Output(s):** None.**Exception(s):** None.

Description: Begin a block of code that catches an exception. Must immediately follow a *xep_catch()* call. This interface is used for the case where more than one exception type is to be handled by the same code block. The exception is not considered handled unless *xep_handled()* is called.

xep_acatch ...:**Input(s):** None.**Output(s):** None.**Exception(s):** None.

Description: Begin a block of code that catches all exceptions not explicitly caught by *xep_catch()* and *xep_mcatch()* blocks. There may only be one *xep_acatch* block within a try/catch block. The exception is not considered handled unless *xep_handled()* is called.

cw_xepv_t xep_value(void):**Input(s):** None.**Output(s):****retval:** Value of the current exception being handled.**Exception(s):** None.

Description: Return the value of the current exception being handled.

void xep_throw_e(cw_xepv_t a_xepv, const char *a_filename, cw_uint32_t a_line_num):***void xep_throw(cw_xepv_t a_xepv):*****Input(s):****a_xepv:** Exception number to throw.**a_filename:** Should be *__FILE__*.**a_line_num:** Should be *__LINE__*.**Output(s):** None.**Exception(s):****a_xepv.**

Description: Throw an exception.

void xep_retry(void):**Input(s):** None.**Output(s):** None.**Exception(s):** None.

Description: Implicitly handle the current exception and retry the *xep_try* code block.

void xep_handled(void):**Input(s):** None.**Output(s):** None.**Exception(s):** None.

Description: Mark the current exception as handled.

4.11 Dictionaries

4.11.1 *gcdict*

The *gcdict* functions implement the operators contained in **gcdict**. Only the C API is documented here; see Section 2.9.4 for operator semantics.

API

```
void gcdict_active(cw_nxo_t *a_thread):
void gcdict_collect(cw_nxo_t *a_thread):
void gcdict_period(cw_nxo_t *a_thread):
void gcdict_setactive(cw_nxo_t *a_thread):
void gcdict_setperiod(cw_nxo_t *a_thread):
void gcdict_setthreshold(cw_nxo_t *a_thread):
void gcdict_stats(cw_nxo_t *a_thread):
void gcdict_threshold(cw_nxo_t *a_thread):
```

Input(s):

a_thread: Pointer to a thread.

Output(s):

None.

Exception(s):

CW_ONYXX_OOM.

Description: C interfaces to Onyx operators that control garbage collection.

4.11.2 *systemdict*

The *systemdict* functions implement the operators contained in **systemdict**. Only the C API is documented here; see Section 2.9.9 for operator semantics.

API

```
void systemdict_abs(cw_nxo_t *a_thread):
void systemdict_accept(cw_nxo_t *a_thread):
void systemdict_add(cw_nxo_t *a_thread):
void systemdict_adn(cw_nxo_t *a_thread):
void systemdict_and(cw_nxo_t *a_thread):
void systemdict_array(cw_nxo_t *a_thread):
void systemdict_atan(cw_nxo_t *a_thread):
void systemdict_aup(cw_nxo_t *a_thread):
void systemdict_bdup(cw_nxo_t *a_thread):
void systemdict_begin(cw_nxo_t *a_thread):
void systemdict_bind(cw_nxo_t *a_thread):
void systemdict_bindsocket(cw_nxo_t *a_thread):
void systemdict_bpop(cw_nxo_t *a_thread):
void systemdict_broadcast(cw_nxo_t *a_thread):
```

```
void systemdict_bytesavailable(cw_nxo_t *a_thread):
void systemdict_cat(cw_nxo_t *a_thread):
void systemdict_cd(cw_nxo_t *a_thread):
void systemdict_ceiling(cw_nxo_t *a_thread):
void systemdict_chmod(cw_nxo_t *a_thread):
void systemdict_chown(cw_nxo_t *a_thread):
void systemdict_chroot(cw_nxo_t *a_thread):
void systemdict_clear(cw_nxo_t *a_thread):
void systemdict_cleartomark(cw_nxo_t *a_thread):
void systemdict_close(cw_nxo_t *a_thread):
void systemdict_condition(cw_nxo_t *a_thread):
void systemdict_connect(cw_nxo_t *a_thread):
void systemdict_copy(cw_nxo_t *a_thread):
void systemdict_cos(cw_nxo_t *a_thread):
void systemdict_count(cw_nxo_t *a_thread):
void systemdict_countdstack(cw_nxo_t *a_thread):
void systemdict_countestack(cw_nxo_t *a_thread):
void systemdict_counttomark(cw_nxo_t *a_thread):
void systemdict_currentdict(cw_nxo_t *a_thread):
void systemdict_currentlocking(cw_nxo_t *a_thread):
void systemdict_cvs(cw_nxo_t *a_thread):
void systemdict_cve(cw_nxo_t *a_thread):
void systemdict_cves(cw_nxo_t *a_thread):
void systemdict_cvlit(cw_nxo_t *a_thread):
void systemdict_cvn(cw_nxo_t *a_thread):
void systemdict_cvrs(cw_nxo_t *a_thread):
void systemdict_cvs(cw_nxo_t *a_thread):
void systemdict_cvx(cw_nxo_t *a_thread):
void systemdict_dec(cw_nxo_t *a_thread):
void systemdict_def(cw_nxo_t *a_thread):
void systemdict_detach(cw_nxo_t *a_thread):
void systemdict_dict(cw_nxo_t *a_thread):
void systemdict_die(cw_nxo_t *a_thread):
void systemdict_dirforeach(cw_nxo_t *a_thread):
void systemdict_div(cw_nxo_t *a_thread):
void systemdict_dn(cw_nxo_t *a_thread):
void systemdict_dstack(cw_nxo_t *a_thread):
void systemdict_dup(cw_nxo_t *a_thread):
void systemdict_echeck(cw_nxo_t *a_thread):
void systemdict_egid(cw_nxo_t *a_thread):
void systemdict_end(cw_nxo_t *a_thread):
void systemdict_eq(cw_nxo_t *a_thread):
void systemdict_estack(cw_nxo_t *a_thread):
void systemdict_euid(cw_nxo_t *a_thread):
void systemdict_eval(cw_nxo_t *a_thread):
void systemdict_exch(cw_nxo_t *a_thread):
void systemdict_exec(cw_nxo_t *a_thread):
void systemdict_exit(cw_nxo_t *a_thread):
void systemdict_exp(cw_nxo_t *a_thread):
void systemdict_floor(cw_nxo_t *a_thread):
void systemdict_flush(cw_nxo_t *a_thread):
```

```
void systemdict_flushfile(cw_nxo_t *a_thread):
void systemdict_for(cw_nxo_t *a_thread):
void systemdict_foreach(cw_nxo_t *a_thread):
void systemdict_forkexec(cw_nxo_t *a_thread):
void systemdict_ge(cw_nxo_t *a_thread):
void systemdict_get(cw_nxo_t *a_thread):
void systemdict_getinterval(cw_nxo_t *a_thread):
void systemdict_gid(cw_nxo_t *a_thread):
void systemdict_gstderr(cw_nxo_t *a_thread):
void systemdict_gstdin(cw_nxo_t *a_thread):
void systemdict_gstdout(cw_nxo_t *a_thread):
void systemdict_gt(cw_nxo_t *a_thread):
void systemdict_hooktag(cw_nxo_t *a_thread):
void systemdict_ibdup(cw_nxo_t *a_thread):
void systemdict_ibpop(cw_nxo_t *a_thread):
void systemdict_idiv(cw_nxo_t *a_thread):
void systemdict_idup(cw_nxo_t *a_thread):
void systemdict_if(cw_nxo_t *a_thread):
void systemdict_ifelse(cw_nxo_t *a_thread):
void systemdict_inc(cw_nxo_t *a_thread):
void systemdict_iobuf(cw_nxo_t *a_thread):
void systemdict_ipop(cw_nxo_t *a_thread):
void systemdict_istack(cw_nxo_t *a_thread):
void systemdict_join(cw_nxo_t *a_thread):
void systemdict_known(cw_nxo_t *a_thread):
void systemdict_lcheck(cw_nxo_t *a_thread):
void systemdict_le(cw_nxo_t *a_thread):
void systemdict_length(cw_nxo_t *a_thread):
void systemdict_link(cw_nxo_t *a_thread):
void systemdict_listen(cw_nxo_t *a_thread):
void systemdict_ln(cw_nxo_t *a_thread):
void systemdict_load(cw_nxo_t *a_thread):
void systemdict_lock(cw_nxo_t *a_thread):
void systemdict_log(cw_nxo_t *a_thread):
void systemdict_loop(cw_nxo_t *a_thread):
void systemdict_lt(cw_nxo_t *a_thread):
void systemdict_mkdir(cw_nxo_t *a_thread):
void systemdict_mkfifo(cw_nxo_t *a_thread):
void systemdict_mod(cw_nxo_t *a_thread):
void systemdict_modload(cw_nxo_t *a_thread):
void systemdict_monitor(cw_nxo_t *a_thread):
void systemdict_mul(cw_nxo_t *a_thread):
void systemdict_mutex(cw_nxo_t *a_thread):
void systemdict_nbpop(cw_nxo_t *a_thread):
void systemdict_ncat(cw_nxo_t *a_thread):
void systemdict_ndn(cw_nxo_t *a_thread):
void systemdict_ndup(cw_nxo_t *a_thread):
void systemdict_ne(cw_nxo_t *a_thread):
void systemdict_neg(cw_nxo_t *a_thread):
void systemdict_nip(cw_nxo_t *a_thread):
void systemdict_nonblocking(cw_nxo_t *a_thread):
```

```
void systemdict_not(cw_nxo_t *a_thread):
void systemdict_npop(cw_nxo_t *a_thread):
void systemdict_nsleep(cw_nxo_t *a_thread):
void systemdict_nup(cw_nxo_t *a_thread):
void systemdict_open(cw_nxo_t *a_thread):
void systemdict_or(cw_nxo_t *a_thread):
void systemdict_ostack(cw_nxo_t *a_thread):
void systemdict_over(cw_nxo_t *a_thread):
void systemdict_peername(cw_nxo_t *a_thread):
void systemdict_pid(cw_nxo_t *a_thread):
void systemdict_pipe(cw_nxo_t *a_thread):
void systemdict_poll(cw_nxo_t *a_thread):
void systemdict_pop(cw_nxo_t *a_thread):
void systemdict_ppid(cw_nxo_t *a_thread):
void systemdict_print(cw_nxo_t *a_thread):
void systemdict_put(cw_nxo_t *a_thread):
void systemdict_putinterval(cw_nxo_t *a_thread):
void systemdict_pwd(cw_nxo_t *a_thread):
void systemdict_quit(cw_nxo_t *a_thread):
void systemdict_rand(cw_nxo_t *a_thread):
void systemdict_read(cw_nxo_t *a_thread):
void systemdict_readline(cw_nxo_t *a_thread):
void systemdict_readlink(cw_nxo_t *a_thread):
void systemdict_realtime(cw_nxo_t *a_thread):
void systemdict_recv(cw_nxo_t *a_thread):
void systemdict_rename(cw_nxo_t *a_thread):
void systemdict_repeat(cw_nxo_t *a_thread):
void systemdict_rmdir(cw_nxo_t *a_thread):
void systemdict_roll(cw_nxo_t *a_thread):
void systemdict_rot(cw_nxo_t *a_thread):
void systemdict_round(cw_nxo_t *a_thread):
void systemdict_sadn(cw_nxo_t *a_thread):
void systemdict_saup(cw_nxo_t *a_thread):
void systemdict_sbdup(cw_nxo_t *a_thread):
void systemdict_sbpop(cw_nxo_t *a_thread):
void systemdict_sbpush(cw_nxo_t *a_thread):
void systemdict_sclear(cw_nxo_t *a_thread):
void systemdict_scleartomark(cw_nxo_t *a_thread):
void systemdict_scount(cw_nxo_t *a_thread):
void systemdict_scounttomark(cw_nxo_t *a_thread):
void systemdict_sdn(cw_nxo_t *a_thread):
void systemdict_sdup(cw_nxo_t *a_thread):
void systemdict_seek(cw_nxo_t *a_thread):
void systemdict_self(cw_nxo_t *a_thread):
void systemdict_send(cw_nxo_t *a_thread):
void systemdict_serviceport(cw_nxo_t *a_thread):
void systemdict_setegid(cw_nxo_t *a_thread):
void systemdict_setenv(cw_nxo_t *a_thread):
void systemdict seteuid(cw_nxo_t *a_thread):
void systemdict_setgid(cw_nxo_t *a_thread):
void systemdict_setgstderr(cw_nxo_t *a_thread):
```

```
void systemdict_setgstdin(cw_nxo_t *a_thread):
void systemdict_setgstdout(cw_nxo_t *a_thread):
void systemdict_setiobuf(cw_nxo_t *a_thread):
void systemdict_setlocking(cw_nxo_t *a_thread):
void systemdict_setnonblocking(cw_nxo_t *a_thread):
void systemdict_setsockopt(cw_nxo_t *a_thread):
void systemdict_setstderr(cw_nxo_t *a_thread):
void systemdict_setstdin(cw_nxo_t *a_thread):
void systemdict_setstdout(cw_nxo_t *a_thread):
void systemdict_setuid(cw_nxo_t *a_thread):
void systemdict_sexch(cw_nxo_t *a_thread):
void systemdict_shift(cw_nxo_t *a_thread):
void systemdict_sibdup(cw_nxo_t *a_thread):
void systemdict_sibpop(cw_nxo_t *a_thread):
void systemdict_sidup(cw_nxo_t *a_thread):
void systemdict_signal(cw_nxo_t *a_thread):
void systemdict_sin(cw_nxo_t *a_thread):
void systemdict_sipop(cw_nxo_t *a_thread):
void systemdict_snbpop(cw_nxo_t *a_thread):
void systemdict_sndn(cw_nxo_t *a_thread):
void systemdict_sndup(cw_nxo_t *a_thread):
void systemdict_snip(cw_nxo_t *a_thread):
void systemdict_snpop(cw_nxo_t *a_thread):
void systemdict_snup(cw_nxo_t *a_thread):
void systemdict_socket(cw_nxo_t *a_thread):
void systemdict_socketpair(cw_nxo_t *a_thread):
void systemdict_sockname(cw_nxo_t *a_thread):
void systemdict_sockopt(cw_nxo_t *a_thread):
void systemdict_sover(cw_nxo_t *a_thread):
void systemdict_spop(cw_nxo_t *a_thread):
void systemdict_spush(cw_nxo_t *a_thread):
void systemdict_sqrt(cw_nxo_t *a_thread):
void systemdict_srand(cw_nxo_t *a_thread):
void systemdict_sroll(cw_nxo_t *a_thread):
void systemdict_srot(cw_nxo_t *a_thread):
void systemdict_stack(cw_nxo_t *a_thread):
void systemdict_start(cw_nxo_t *a_thread):
void systemdict_status(cw_nxo_t *a_thread):
void systemdict_stderr(cw_nxo_t *a_thread):
void systemdict_stdin(cw_nxo_t *a_thread):
void systemdict_stdout(cw_nxo_t *a_thread):
void systemdict_stop(cw_nxo_t *a_thread):
void systemdict_stopped(cw_nxo_t *a_thread):
void systemdict_string(cw_nxo_t *a_thread):
void systemdict_stuck(cw_nxo_t *a_thread):
void systemdict_sub(cw_nxo_t *a_thread):
void systemdict_sunder(cw_nxo_t *a_thread):
void systemdict_sup(cw_nxo_t *a_thread):
void systemdict_sym_lp(cw_nxo_t *a_thread) (“”):
void systemdict_sym_rp(cw_nxo_t *a_thread) (“”):
void systemdict_sym_gt(cw_nxo_t *a_thread) (“>”):
```

```
void systemdict_sym_rb(cw_nxo_t *a_thread) (“”);
void systemdict_symlink(cw_nxo_t *a_thread):
void systemdict_tell(cw_nxo_t *a_thread):
void systemdict_test(cw_nxo_t *a_thread):
void systemdict_thread(cw_nxo_t *a_thread):
void systemdict_threadsdict(cw_nxo_t *a_thread):
void systemdict_threaddstack(cw_nxo_t *a_thread):
void systemdict_threadestack(cw_nxo_t *a_thread):
void systemdict_threadistack(cw_nxo_t *a_thread):
void systemdict_threadostack(cw_nxo_t *a_thread):
void systemdict_timedwait(cw_nxo_t *a_thread):
void systemdict_token(cw_nxo_t *a_thread):
void systemdict_trunc(cw_nxo_t *a_thread):
void systemdict_truncate(cw_nxo_t *a_thread):
void systemdict_trylock(cw_nxo_t *a_thread):
void systemdict_tuck(cw_nxo_t *a_thread):
void systemdict_type(cw_nxo_t *a_thread):
void systemdict_uid(cw_nxo_t *a_thread):
void systemdict_umask(cw_nxo_t *a_thread):
void systemdict_undef(cw_nxo_t *a_thread):
void systemdict_under(cw_nxo_t *a_thread):
void systemdict_unlink(cw_nxo_t *a_thread):
void systemdict_unlock(cw_nxo_t *a_thread):
void systemdict_unsetenv(cw_nxo_t *a_thread):
void systemdict_until(cw_nxo_t *a_thread):
void systemdict_up(cw_nxo_t *a_thread):
void systemdict_wait(cw_nxo_t *a_thread):
void systemdict_waitpid(cw_nxo_t *a_thread):
void systemdict_where(cw_nxo_t *a_thread):
void systemdict_while(cw_nxo_t *a_thread):
void systemdict_write(cw_nxo_t *a_thread):
void systemdict_xcheck(cw_nxo_t *a_thread):
void systemdict_xor(cw_nxo_t *a_thread):
void systemdict_yield(cw_nxo_t *a_thread):
```

Input(s):

a_thread: Pointer to a thread.

Output(s): None.**Exception(s):**

CW_ONYXX_OOM.

Description: C interfaces to onyx operators.

Index

(, 62
) , 62
<, 63
>, 63
[, 64
], 64

abs, 64
accept, 64
active, 31
add, 65
adn, 65
and, 66
argcheck, 22
argv, 66
array, 66
arraytype, 36, 44
atan, 67
aup, 67

bdup, 68
begin, 68
bind, 68
bindsocket, 69
booleantype, 37, 45
bpop, 70
broadcast, 70
bytesavailable, 70

cat, 71
cd, 71
ceiling, 72
ch, 188
ch_count(), 189
ch_delete(), 189
ch_direct_hash(), 191
ch_direct_key_comp(), 192
ch_get_iterate(), 190
ch_insert(), 189
ch_new(), 189
ch_remove(), 190
ch_remove_iterate(), 191
ch_search(), 190
ch_string_hash(), 191
ch_string_key_comp(), 192
chmod, 72
chown, 73
chroot, 73
clear, 74
cleartomark, 74
close, 75
cnd, 192
cnd_broadcast(), 193
cnd_delete(), 192
cnd_new(), 192
cnd_signal(), 193
cnd_timedwait(), 193
cnd_wait(), 193
collect, 31
column, 25
condition, 75
conditiontype, 37, 45
connect, 75
copy, 76
cos, 76
count, 77
countdstack, 77
countestack, 77
counttomark, 78
currentdict, 78
currenterror, 25, 176
currentlocking, 78
cvds, 79
cve, 79
cves, 79
cvlit, 80
cvn, 80
cvrs, 80
cvs, 81
cvx, 81
cw_assert(), 187
cw_calloc(), 198
CW_CH_TABLE2SIZEOF(), 188
cw_check_ptr(), 187
cw_error(), 187

cw_free(), 199
cw_htonq(), 188
cw_malloc(), 198
cw_not_reached(), 187
cw_ntohq(), 187
cw_nxo_file_delete_t(), 219
cw_nxo_file_read_t(), 218
cw_nxo_file_ref_iter_t(), 219
cw_nxo_file_write_t(), 219
cw_nxo_hook_delete_t(), 225
cw_nxo_hook_eval_t(), 225
cw_nxo_hook_ref_iter_t(), 225
cw_offsetof(), 188
cw_onyx_code(), 186
cw_opaque_alloc(), 186
cw_opaque_alloc_t(), 185
cw_opaque_dealloc(), 186
cw_opaque_dealloc_t(), 185
cw_opaque_realloc(), 186
cw_opaque_realloc_t(), 185
cw_realloc(), 198

dch, 193
dch_count(), 194
dch_delete(), 194
dch_get_iterate(), 195
dch_insert(), 194
dch_new(), 194
dch_remove(), 195
dch_remove_iterate(), 196
dch_search(), 195

dec, 82
def, 82
detach, 82
dict, 83
dicttype, 38, 46
die, 83
dirforeach, 83
div, 84
dn, 84
dstack, 25, 85
dup, 85

echeck, 85
egid, 86
end, 86
envdict, 29, 87
eq, 87
errordict, 29, 176
errorname, 26
estack, 26, 88
estackoverflow, 22

euid, 88
eval, 88
exch, 88
exec, 89
exit, 89
exp, 89

false, 90
filetype, 38, 46
finotype, 38, 46
floor, 90
flush, 91
flushfile, 91
for, 91
foreach, 92
forkexec, 93

gcdict, 263
gcdict, 30, 93
gcdict_active(), 263
gcdict_collect(), 263
gcdict_period(), 263
gcdict_setactive(), 263
gcdict_setperiod(), 263
gcdict_setthreshold(), 263
gcdict_stats(), 263
gcdict_threshold(), 263
ge, 93
get, 94
getinterval, 95
gid, 95
globaldict, 34, 95
gstderr, 96
gstdin, 96
gstdout, 96
gt, 96

handleerror, 29
hooktag, 97
hooktype, 39, 47
hostbyname, 97

ibdup, 98
ibpop, 98
idiv, 99
idup, 99
if, 100
ifelse, 100
inc, 100
integertype, 39, 47
invalidaccess, 22
invalidexit, 22

- invalidfileaccess, 22
- iobuf**, 101
- ioerror, 22
- ipop**, 101
- istack**, 27, 101
- join**, 102
- known**, 102
- lcheck**, 102
- le**, 103
- length**, 103
- libonyx_init()*, 185
- libonyx_shutdown()*, 185
- limitcheck, 22
- line**, 28
- link**, 104
- listen**, 104
- ln**, 105
- load**, 105
- lock**, 106
- log**, 106
- loop**, 106
- lt**, 107
- mark**, 107
- marktype**, 39, 48
- mb*, 196
- mb_write()*, 196
- mem*, 197
- mem_calloc()*, 198
- mem_calloc_e()*, 198
- mem_delete()*, 197
- mem_free()*, 199
- mem_free_e()*, 199
- mem_malloc()*, 198
- mem_malloc_e()*, 198
- mem_new()*, 197
- mem_realloc()*, 198
- mem_realloc_e()*, 198
- mkdir**, 107
- mkfifo**, 108
- mod**, 108
- modload**, 109
- monitor**, 110
- mpath_post**, 34
- mpath_pre**, 34
- mq*, 199
- mq_delete()*, 199
- mq_get()*, 200
- mq_get_start()*, 201
- mq_get_stop()*, 201
- mq_new()*, 199
- mq_put()*, 200
- mq_put_start()*, 201
- mq_put_stop()*, 201
- mq_timedget()*, 200
- mq_tryget()*, 200
- mrequire**, 110
- mtx*, 202
- mtx_delete()*, 202
- mtx_lock()*, 202
- mtx_new()*, 202
- mtx_trylock()*, 202
- mtx_unlock()*, 203
- mul**, 110
- mutex**, 111
- mutextype**, 40, 48
- nametype**, 40, 49
- nbpop**, 111
- ncat**, 111
- ndn**, 112
- ndup**, 112
- ne**, 113
- neg**, 114
- neterror, 22
- newerror**, 27
- nip**, 114
- nonblocking**, 114
- not**, 115
- npop**, 115
- nsleep**, 116
- null**, 116
- nulltype**, 41, 49
- nup**, 116
- nx*, 203
- nx_delete()*, 203
- nx_envdict_get()*, 204
- nx_globaldict_get()*, 204
- nx_new()*, 203
- nx_nxa_get()*, 203
- nx_stderr_get()*, 205
- nx_stderr_set()*, 205
- nx_stdin_get()*, 204
- nx_stdin_set()*, 204
- nx_stdout_get()*, 204
- nx_stdout_set()*, 205
- nx_systemdict_get()*, 204
- nxa*, 205
- nxa_active_get()*, 207
- nxa_active_set()*, 207

-
- nxa_collect()*, 206
 - nxa_dump()*, 207
 - nxa_free()*, 206
 - nxa_free_e()*, 206
 - nxa_gcdict_get()*, 209
 - nxa_malloc()*, 205
 - nxa_malloc_e()*, 205
 - nxa_nx_get()*, 209
 - nxa_period_get()*, 207
 - nxa_period_set()*, 208
 - nxa_malloc()*, 206
 - nxa_realloc_e()*, 206
 - nxa_stats_get()*, 208
 - nxa_threshold_get()*, 208
 - nxa_threshold_set()*, 208
 - nxn*, 210
 - nxn_len()*, 210
 - nxn_str()*, 210
 - nxo*, 210
 - nxo_array*, 213
 - nxo_array_copy()*, 214
 - nxo_array_el_get()*, 214
 - nxo_array_el_set()*, 214
 - nxo_array_len_get()*, 214
 - nxo_array_new()*, 213
 - nxo_array_subarray_new()*, 213
 - nxo_attr_get()*, 213
 - nxo_attr_set()*, 213
 - nxo_boolean*, 215
 - nxo_boolean_get()*, 215
 - nxo_boolean_new()*, 215
 - nxo_boolean_set()*, 215
 - nxo_compare()*, 211
 - nxo_condition*, 215
 - nxo_condition_broadcast()*, 216
 - nxo_condition_new()*, 215
 - nxo_condition_signal()*, 216
 - nxo_condition_timedwait()*, 216
 - nxo_condition_wait()*, 216
 - nxo_dict*, 216
 - nxo_dict_copy()*, 217
 - nxo_dict_count()*, 218
 - nxo_dict_def()*, 217
 - nxo_dict_iterate()*, 218
 - nxo_dict_lookup()*, 217
 - nxo_dict_new()*, 217
 - nxo_dict_undef()*, 217
 - nxo_dup()*, 211
 - nxo_file*, 218
 - nxo_file_buffer_count()*, 224
 - nxo_file_buffer_flush()*, 224
 - nxo_file_buffer_size_get()*, 224
 - nxo_file_buffer_size_set()*, 224
 - nxo_file_close()*, 221
 - nxo_file_fd_get()*, 221
 - nxo_file_fd_wrap()*, 220
 - nxo_file_new()*, 220
 - nxo_file_nonblocking_get()*, 221
 - nxo_file_nonblocking_set()*, 222
 - nxo_file_open()*, 220
 - nxo_file_position_get()*, 223
 - nxo_file_position_set()*, 223
 - nxo_file_read()*, 222
 - nxo_file_readline()*, 222
 - nxo_file_synthetic()*, 220
 - nxo_file_truncate()*, 223
 - nxo_file_write()*, 223
 - nxo_fino*, 225
 - nxo_fino_new()*, 225
 - nxo_hook*, 225
 - nxo_hook_data_get()*, 226
 - nxo_hook_data_set()*, 226
 - nxo_hook_eval()*, 227
 - nxo_hook_new()*, 226
 - nxo_hook_tag_get()*, 226
 - nxo_integer*, 227
 - nxo_integer_get()*, 227
 - nxo_integer_new()*, 227
 - nxo_integer_set()*, 227
 - nxo_lcheck()*, 212
 - nxo_mark*, 228
 - nxo_mark_new()*, 228
 - nxo_mutex*, 228
 - nxo_mutex_lock()*, 228
 - nxo_mutex_new()*, 228
 - nxo_mutex_trylock()*, 228
 - nxo_mutex_unlock()*, 229
 - nxo_name*, 229
 - nxo_name_len_get()*, 229
 - nxo_name_new()*, 229
 - nxo_name_str_get()*, 229
 - nxo_no*, 230
 - nxo_no_new()*, 230
 - nxo_null*, 230
 - nxo_null_new()*, 230
 - nxo_nxoe_get()*, 212
 - nxo_operator*, 230
 - nxo_operator_f()*, 231
 - nxo_operator_new()*, 231
 - nxo_pmark*, 231
 - nxo_pmark_new()*, 231
 - nxo_real*, 231

nxo_real_get(), 232
nxo_real_new(), 231
nxo_real_set(), 232
nxo_stack, 232
nxo_stack_bget(), 235
nxo_stack_bpop(), 234
nxo_stack_bpush(), 233
nxo_stack_copy(), 232
nxo_stack_count(), 233
nxo_stack_down_get(), 236
nxo_stack_exch(), 236
nxo_stack_get(), 235
nxo_stack_nbget(), 235
nxo_stack_nbpop(), 234
nxo_stack_new(), 232
nxo_stack_nget(), 235
nxo_stack_npop(), 234
nxo_stack_pop(), 233
nxo_stack_push(), 233
nxo_stack_remove(), 234
nxo_stack_roll(), 236
nxo_stack_rot(), 236
nxo_stack_under_push(), 233
nxo_stack_up_get(), 236
nxo_string, 237
nxo_string_copy(), 238
nxo_string_cstring(), 238
nxo_string_el_get(), 238
nxo_string_el_set(), 238
nxo_string_get(), 239
nxo_string_len_get(), 238
nxo_string_lock(), 239
nxo_string_new(), 237
nxo_string_set(), 239
nxo_string_substring_new(), 237
nxo_string_unlock(), 239
nxo_thread, 239
nxo_thread_currenterror_get(), 245
nxo_thread_currentlocking(), 244
nxo_thread_deferred(), 242
nxo_thread_detach(), 241
nxo_thread_dstack_get(), 245
nxo_thread_dstack_search(), 244
nxo_thread_errordict_get(), 245
nxo_thread_estack_get(), 246
nxo_thread_exit(), 241
nxo_thread_flush(), 243
nxo_thread_interpret(), 243
nxo_thread_istack_get(), 246
nxo_thread_join(), 241
nxo_thread_loop(), 243

nxo_thread_nerror(), 243
nxo_thread_new(), 240
nxo_thread_nx_get(), 244
nxo_thread_ostack_get(), 245
nxo_thread_reset(), 242
nxo_thread_serror(), 243
nxo_thread_setlocking(), 244
nxo_thread_start(), 241
nxo_thread_state(), 241
nxo_thread_stderr_get(), 247
nxo_thread_stderr_set(), 247
nxo_thread_stdin_get(), 246
nxo_thread_stdin_set(), 246
nxo_thread_stdout_get(), 246
nxo_thread_stdout_set(), 247
nxo_thread_thread(), 241
nxo_thread_tstack_get(), 246
nxo_thread_userdict_get(), 245
nxo_threadp_delete(), 240
nxo_threadp_new(), 240
nxo_threadp_position_get(), 240
nxo_threadp_position_set(), 240
nxo_type_get(), 212

onxydict, 34, 117
open, 117
operatorotype, 41, 49
or, 118
ostack, 28, 118
output, 118
outputs, 119
outputsdict, 35, 119
over, 120

peername, 120
period, 31
pid, 121
pipe, 121
pmarktype, 41, 50
poll, 122
pop, 121
ppid, 123
print, 123
product, 123
promptstring, 180
pstack, 123
put, 124
putinterval, 124
pwd, 125

ql, 247
ql_after_insert(), 250

ql_before_insert(), 249
ql_elm(), 248
ql_elm_new(), 248
ql_first(), 248
ql_foreach(), 251
ql_head(), 248
ql_head_initializer(), 248
ql_head_insert(), 250
ql_head_remove(), 250
ql_last(), 249
ql_new(), 248
ql_next(), 249
ql_prev(), 249
ql_remove(), 250
ql_reverse_foreach(), 251
ql_tail_insert(), 250
ql_tail_remove(), 251
qr, 251
qr(), 252
qr_after_insert(), 253
qr_before_insert(), 252
qr_foreach(), 253
qr_meld(), 253
qr_new(), 252
qr_next(), 252
qr_prev(), 252
qr_remove(), 253
qr_reverse_foreach(), 254
qr_split(), 253
qs, 254
qs_down(), 255
qs_elm(), 254
qs_elm_new(), 255
qs_foreach(), 256
qs_head(), 254
qs_head_initializer(), 254
qs_new(), 255
qs_pop(), 256
qs_push(), 255
qs_top(), 255
qs_under_push(), 256
quit, 125

rand, 125
rangecheck, 22
read, 126
readline, 126
readlink, 127
realtime, 127
realtype, 42, 50
recv, 128

rename, 128
repeat, 129
require, 129
resume, 180
rmdir, 129
roll, 130
rot, 131
round, 131
rpath_post, 35
rpath_pre, 35

sadn, 132
saup, 132
sbdup, 132
sbpop, 132
sbpush, 133
sclear, 133
scleartomark, 133
scount, 134
scounttomark, 134
sdn, 134
sdup, 135
search, 135
seek, 136
self, 136
send, 136
serviceport, 137
setactive, 32
setegid, 137
setenv, 138
seteuid, 138
setgid, 138
setgstderr, 139
setgstdin, 139
setgstdout, 140
setiobuf, 140
setlocking, 140
setnonblocking, 141
setperiod, 32
setsockopt, 141
setstderr, 142
setstdin, 142
setstdout, 143
setthreshold, 32
setuid, 143
sexch, 144
shift, 144
sibdup, 144
sibpop, 145
sidup, 145
signal, 145

- sin**, 146
- sipop**, 146
- snbpop**, 147
- sndn**, 147
- sndup**, 147
- snip**, 148
- snpop**, 148
- snup**, 148
- socket**, 149
- socketpair**, 149
- sockname**, 150
- sockopt**, 150
- sover**, 151
- spop**, 151
- sprint**, 152
- sprints**, 152
- sprintsdict**, 44, 153
- spush**, 153
- sqr**, 153
- srand**, 154
- sroll**, 154
- srot**, 154
- stack**, 155
- stacktype**, 42, 51
- stackunderflow, 22
- start**, 155
- stats**, 33
- status**, 155
- stderr**, 156
- stdin**, 156
- stdout**, 156
- stop**, 30, 157, 179, 180
- stopped**, 157
- string**, 157
- stringtype**, 43, 51
- stuck**, 158
- sub**, 158
- sunder**, 158
- sup**, 159
- symlink**, 159
- syntaxerror, 22
- system**, 160
- systemdict*, 263
- systemdict**, 52, 160
- systemdict_abs()*, 263
- systemdict_accept()*, 263
- systemdict_add()*, 263
- systemdict_adn()*, 263
- systemdict_and()*, 263
- systemdict_array()*, 263
- systemdict_atan()*, 263
- systemdict_aup()*, 263
- systemdict_bdup()*, 263
- systemdict_begin()*, 263
- systemdict_bind()*, 263
- systemdict_bindsocket()*, 263
- systemdict_bpop()*, 263
- systemdict_broadcast()*, 263
- systemdict_bytesavailable()*, 263
- systemdict_cat()*, 264
- systemdict_cd()*, 264
- systemdict_ceiling()*, 264
- systemdict_chmod()*, 264
- systemdict_chown()*, 264
- systemdict_chroot()*, 264
- systemdict_clear()*, 264
- systemdict_clearbookmark()*, 264
- systemdict_close()*, 264
- systemdict_condition()*, 264
- systemdict_connect()*, 264
- systemdict_copy()*, 264
- systemdict_cos()*, 264
- systemdict_count()*, 264
- systemdict_countdownstack()*, 264
- systemdict_countteststack()*, 264
- systemdict_counttomark()*, 264
- systemdict_currentdict()*, 264
- systemdict_currentlocking()*, 264
- systemdict_cvds()*, 264
- systemdict_cve()*, 264
- systemdict_cves()*, 264
- systemdict_cvlit()*, 264
- systemdict_cvn()*, 264
- systemdict_cvrs()*, 264
- systemdict_cvs()*, 264
- systemdict_cvx()*, 264
- systemdict_dec()*, 264
- systemdict_def()*, 264
- systemdict_detach()*, 264
- systemdict_dict()*, 264
- systemdict_die()*, 264
- systemdict_dirforeach()*, 264
- systemdict_div()*, 264
- systemdict_dn()*, 264
- systemdict_dstack()*, 264
- systemdict_dup()*, 264
- systemdict_echeck()*, 264
- systemdict_egid()*, 264
- systemdict_end()*, 264
- systemdict_eq()*, 264
- systemdict_estack()*, 264
- systemdict_euid()*, 264

systemdict_eval(), 264
systemdict_exch(), 264
systemdict_exec(), 264
systemdict_exit(), 264
systemdict_exp(), 264
systemdict_floor(), 264
systemdict_flush(), 264
systemdict_flushfile(), 264
systemdict_for(), 265
systemdict_foreach(), 265
systemdict_forkexec(), 265
systemdict_ge(), 265
systemdict_get(), 265
systemdict_getinterval(), 265
systemdict_gid(), 265
systemdict_gstderr(), 265
systemdict_gstdin(), 265
systemdict_gstdout(), 265
systemdict_gt(), 265
systemdict_hooktag(), 265
systemdict_ibdup(), 265
systemdict_ibpop(), 265
systemdict_idiv(), 265
systemdict_idup(), 265
systemdict_if(), 265
systemdict_ifelse(), 265
systemdict_inc(), 265
systemdict_iobuf(), 265
systemdict_ipop(), 265
systemdict_istack(), 265
systemdict_join(), 265
systemdict_known(), 265
systemdict_lcheck(), 265
systemdict_le(), 265
systemdict_length(), 265
systemdict_link(), 265
systemdict_listen(), 265
systemdict_ln(), 265
systemdict_load(), 265
systemdict_lock(), 265
systemdict_log(), 265
systemdict_loop(), 265
systemdict_lt(), 265
systemdict_mkdir(), 265
systemdict_mkfifo(), 265
systemdict_mod(), 265
systemdict_modload(), 265
systemdict_monitor(), 265
systemdict_mul(), 265
systemdict_mutex(), 265
systemdict_nbpop(), 265
systemdict_ncat(), 265
systemdict_ndn(), 265
systemdict_ndup(), 265
systemdict_ne(), 265
systemdict_neg(), 265
systemdict_nip(), 265
systemdict_nonblocking(), 265
systemdict_not(), 265
systemdict_npop(), 266
systemdict_nsleep(), 266
systemdict_nup(), 266
systemdict_open(), 266
systemdict_or(), 266
systemdict_ostack(), 266
systemdict_over(), 266
systemdict_peername(), 266
systemdict_pid(), 266
systemdict_pipe(), 266
systemdict_poll(), 266
systemdict_pop(), 266
systemdict_ppid(), 266
systemdict_print(), 266
systemdict_put(), 266
systemdict_putinterval(), 266
systemdict_pwd(), 266
systemdict_quit(), 266
systemdict_rand(), 266
systemdict_read(), 266
systemdict_readline(), 266
systemdict_readlink(), 266
systemdict_realtime(), 266
systemdict_recv(), 266
systemdict_rename(), 266
systemdict_repeat(), 266
systemdict_rmdir(), 266
systemdict_roll(), 266
systemdict_rot(), 266
systemdict_round(), 266
systemdict_sadn(), 266
systemdict_saup(), 266
systemdict_sbdup(), 266
systemdict_sbpop(), 266
systemdict_sbpush(), 266
systemdict_sclear(), 266
systemdict_scleartomark(), 266
systemdict_scount(), 266
systemdict_scounttomark(), 266
systemdict_sdn(), 266
systemdict_sdup(), 266
systemdict_seek(), 266
systemdict_self(), 266

-
- systemdict_send()*, 266
systemdict_serviceport(), 266
systemdict_setegid(), 266
systemdict_setenv(), 266
systemdict seteuid(), 266
systemdict_setgid(), 266
systemdict_setgstderr(), 266
systemdict_setgstdin(), 266
systemdict_setgstdout(), 267
systemdict_setiobuf(), 267
systemdict_setlocking(), 267
systemdict_setnonblocking(), 267
systemdict_setsockopt(), 267
systemdict_setstderr(), 267
systemdict_setstdin(), 267
systemdict_setstdout(), 267
systemdict_setuid(), 267
systemdict_ssexch(), 267
systemdict_shift(), 267
systemdict_sibdup(), 267
systemdict_sibpop(), 267
systemdict_sidup(), 267
systemdict_signal(), 267
systemdict_sin(), 267
systemdict_sipop(), 267
systemdict_snbpop(), 267
systemdict_sndn(), 267
systemdict_sndup(), 267
systemdict_snip(), 267
systemdict_snpop(), 267
systemdict_snpop(), 267
systemdict_socket(), 267
systemdict_socketpair(), 267
systemdict_sockname(), 267
systemdict_sockopt(), 267
systemdict_ Dover(), 267
systemdict_spop(), 267
systemdict_spush(), 267
systemdict_sqrt(), 267
systemdict_srand(), 267
systemdict_sroll(), 267
systemdict_srot(), 267
systemdict_stack(), 267
systemdict_start(), 267
systemdict_status(), 267
systemdict_stderr(), 267
systemdict_stdin(), 267
systemdict_stdout(), 267
systemdict_stop(), 267
systemdict_stopped(), 267
systemdict_string(), 267
systemdict_stuck(), 267
systemdict_sub(), 267
systemdict_sunder(), 267
systemdict_sup(), 267
systemdict_sym_gt(), 267
systemdict_sym_lp(), 267
systemdict_sym_rb(), 267
systemdict_sym_rp(), 267
systemdict_symlink(), 268
systemdict_tell(), 268
systemdict_test(), 268
systemdict_thread(), 268
systemdict_threaddstack(), 268
systemdict_threadestack(), 268
systemdict_threadistack(), 268
systemdict_threadostack(), 268
systemdict_threadsdict(), 268
systemdict_timedwait(), 268
systemdict_token(), 268
systemdict_trunc(), 268
systemdict_truncate(), 268
systemdict_trylock(), 268
systemdict_tuck(), 268
systemdict_type(), 268
systemdict_uid(), 268
systemdict_umask(), 268
systemdict_undef(), 268
systemdict_under(), 268
systemdict_unlink(), 268
systemdict_unlock(), 268
systemdict_unsetenv(), 268
systemdict_until(), 268
systemdict_up(), 268
systemdict_wait(), 268
systemdict_waitpid(), 268
systemdict_where(), 268
systemdict_while(), 268
systemdict_write(), 268
systemdict_xcheck(), 268
systemdict_xor(), 268
systemdict_yield(), 268

tell, 160
test, 161
thd, 256
thd_crit_enter(), 258
thd_crit_leave(), 258
thd_delete(), 257
thd_join(), 257
thd_new(), 257
thd_resume(), 259

thd_self(), 257
thd_sigmask(), 257
thd_single_enter(), 258
thd_single_leave(), 258
thd_suspend(), 258
thd_trysuspend(), 259
thd_yield(), 257
thread, 162
threaddict, 175, 176
threaddstack, 162
threadestack, 162
threadistack, 163
threadostack, 163
threadsdict, 163, 177
threadtype, 43, 52
threshold, 33
throw, 163
timedwait, 164
token, 165
true, 167
trunc, 166
truncate, 166
trylock, 167
tsd, 259
tsd_delete(), 259
tsd_get(), 260
tsd_new(), 259
tsd_set(), 260
tuck, 167
type, 168
typecheck, 22

uid, 168
umask, 169
undef, 169
undefined, 22
undefinedfilename, 22
undefinedresult, 22
under, 169
unlink, 170
unlock, 170
unmatchedfino, 22
unmatchedmark, 22
unregistered, 22
unsetenv, 170
until, 171
up, 171
userdict, 172, 176, 177

version, 172

wait, 172
waitpid, 173
where, 173
while, 173
write, 174

xcheck, 174
xep, 260
xep_acatch, 262
xep_begin(), 261
xep_catch(), 261
xep_end(), 261
xep_handled(), 262
xep_mcatch(), 261
xep_retry(), 262
xep_throw(), 262
xep_throw_e(), 262
xep_try, 261
xep_value(), 262
xor, 175

yield, 175