

# Sympa, a Mailing List Management Software - Reference manual

---

**Software version:** 5.3

**Authors:** Serge Aumont, Olivier Salaün, Christophe Wolfhugel

**Manual release date:** May, 29th, 2007

---

## Presentation

- [Presentation](#)
- [License](#)
- [Features](#)
- [Project directions](#)
- [History](#)
- [Mailing lists and support](#)

## Organization

- [Organization](#)
- [Binaries](#)
- [Configuration files](#)
- [Spools](#)
- [Roles and privileges](#)
  - [\(Super\) listmasters](#)
  - [\(Robot\) listmasters](#)
  - [Privileged list owners](#)
  - [\(Basic\) list owners](#)
  - [Moderators \(also called Editors\)](#)
  - [Subscribers \(or list members\)](#)

## Installing Sympa

- [Installing Sympa](#)
- [Obtaining Sympa, related links](#)
- [Prerequisites](#)
  - [System requirements](#)
  - [Installing Perl and CPAN modules](#)
  - [Required CPAN modules](#)
  - [Create a UNIX user](#)
- [Compilation and installation](#)
  - [Choosing directory locations](#)
- [Robot aliases](#)

- [Logs](#)

## Running Sympa

- [sympa.pl](#)
- [INIT script](#)
- [Stopping Sympa and signals](#)

## Upgrading Sympa

- [Upgrading Sympa](#)
- [Incompatible changes](#)
- [CPAN modules update](#)
- [Database structure update](#)
- [Preserving your customizations](#)
- [Running two Sympa versions on a single server](#)
- [Moving to another server](#)

## Mail aliases

- [Mail aliases](#)
- [Robot aliases](#)
- [List aliases](#)
- [Alias manager](#)
- [Virtual domains](#)

## sympa.conf parameters index

- [sympa.conf parameters](#)

## sympa.conf parameters part1

- [sympa.conf parameters](#)
- [Site customization](#)
  - [domain](#)
  - [email](#)
  - [listmaster](#)
  - [listmaster\\_email](#)
  - [wwsympa\\_url](#)
  - [soap\\_url](#)
  - [spam\\_protection](#)
  - [web\\_archive\\_spam\\_protection](#)
  - [color\\_0, color\\_1, ..., color\\_15](#)
  - [Color parameters](#)
  - [logo\\_html\\_definition](#)
  - [css\\_path](#)
  - [css\\_url](#)

- static\_content\_path
- static\_content\_url
- pictures\_feature
- pictures\_max\_size
- cookie
- create\_list
- automatic\_list\_feature
- automatic\_list\_creation
- automatic\_list\_removal
- global\_remind

## sympa.conf parameters part2

- sympa.conf parameters
- Directories
  - home
  - etc
- System related
  - syslog
  - log\_level
  - log\_socket\_type
  - pidfile
  - pidfile\_creation
  - umask
- Sending related
  - distribution\_mode
  - maxsmtp
  - log\_smtp
  - use\_blacklist
  - max\_size
  - misaddressed\_commands
  - misaddressed\_commands\_regexp
  - nrcpt
  - avg
  - sendmail
  - sendmail\_args
  - sendmail\_aliases
  - rfc2369\_header\_fields
  - remove\_headers
  - anonymous\_headers\_fields
  - list\_check\_smtp
  - list\_check\_suffixes
  - urlize\_min\_size
- Quotas
  - default\_shared\_quota
  - default\_archive\_quota

- Spool related
  - spool
  - queue
  - queuedistribute
  - queuemod
  - queuedigest
  - queueauth
  - queueoutgoing
  - queuetopic
  - queuebounce
  - queuetask
  - queueautomatic
  - tmpdir
  - sleep
  - clean\_delay\_queue
  - clean\_delay\_queuemod
  - clean\_delay\_queueauth
  - clean\_delay\_queuesubscribe
  - clean\_delay\_queuetopic
  - clean\_delay\_queueautomatic

## sympa.conf parameters part3

- sympa.conf parameters
- Internationalization related
  - localedir
  - supported\_lang
  - lang
  - web\_recode\_to
  - filesystem\_encoding
- Bounce related
  - verp\_rate
  - welcome\_return\_path
  - remind\_return\_path
  - return\_path\_suffix
  - expire\_bounce\_task
  - purge\_orphan\_bounces\_task
  - eval\_bouncers\_task
  - process\_bouncers\_task
  - minimum\_bouncing\_count
  - minimum\_bouncing\_period
  - bounce\_delay
  - default\_bounce\_level1\_rate
  - default\_bounce\_level2\_rate
  - bounce\_email\_prefix
  - bounce\_warn\_rate
  - bounce\_halt\_rate

- default\_remind\_task
- Tuning
  - cache\_list\_config
  - lock\_method
  - sympa\_priority
  - request\_priority
  - owner\_priority
  - default\_list\_priority
- Database related
  - update\_db\_field\_types
  - db\_type
  - db\_name
  - db\_host
  - db\_port
  - db\_user
  - db\_passwd
  - db\_timeout
  - db\_options
  - db\_env
  - db\_additional\_subscriber\_fields
  - db\_additional\_user\_fields
  - purge\_user\_table\_task
- Loop prevention
  - loop\_command\_max
  - loop\_command\_sampling\_delay
  - loop\_command\_decrease\_factor
  - loop\_prevention\_regex
- S/MIME configuration
  - openssl
  - capath
  - cafile
  - key\_passwd
  - chk\_cert\_expiration\_task
  - crl\_update\_task
- Antivirus plug-in
  - antivirus\_path
  - antivirus\_args
  - antivirus\_notify

## Sympa and its database

- Sympa and its database
- Prerequisites
- Installing PERL modules
- Creating a Sympa DataBase
  - Database structure

- [Database creation](#)
- [Setting database privileges](#)
- [Importing subscriber data](#)
  - [Importing data from a text file](#)
  - [Importing data from subscribers files](#)
- [Management of the include cache](#)
- [Extending database table format](#)
- [Sympa configuration](#)

## WWSympa, Sympa's web interface

- [WWSympa, Sympa's web interface](#)
- [Organization](#)
- [Web server setup](#)
  - [wwsympa.fcgi access permissions](#)
  - [Installing wwsympa.fcgi in your Apache server](#)
  - [Using FastCGI](#)
- [wwsympa.conf parameters](#)
  - [arc\\_path](#)
  - [archive\\_default\\_index\\_thrd\\_mail](#)
  - [archived\\_pidfile](#)
  - [bounce\\_path](#)
  - [bounced\\_pidfile](#)
  - [cookie\\_expire](#)
  - [cookie\\_domain](#)
  - [default\\_home](#)
  - [icons\\_url](#)
  - [log\\_facility](#)
  - [mhonarc](#)
  - [htmlarea\\_url](#)
  - [insensitive | password\\_case\\_sensitive | insensitive](#)
  - [title](#)
  - [1 | use\\_fast\\_cgi 0|1](#)
- [Database configuration](#)
- [Logging in as listmaster](#)

## Web archives

- [Web archive](#)
  - [Features](#)
  - [MHonArc tool](#)
  - [Archives structure](#)
  - [Configuration parameters](#)
  - [Archived.pl daemon](#)
  - [Rebuilding web archive](#)
  - [Importing archives](#)

## Sympa Internationalization

- [Sympa Internationalization](#)
- [Catalogs and templates](#)
- [Translating Sympa GUI in your language](#)
- [Defining language-specific templates](#)
- [Translating topics titles](#)
- [Handling of charsets](#)

## Sympa RSS channel

- [Sympa RSS channel](#)
- [latest\\_lists](#)
- [active\\_lists](#)
- [latest\\_arc](#)
- [latest\\_d\\_read](#)

## Sympa SOAP server

- [Sympa SOAP server](#)
- [Introduction](#)
- [Supported functions](#)
- [Web server setup](#)
- [Sympa setup](#)
- [Trust remote applications](#)
- [The WSDL service description](#)
- [Client-side programming](#)
  - [Writing a Java client with Axis](#)

## Authentication

- [Authentication](#)
- [S/MIME and HTTPS authentication](#)
- [Authentication with email address, uid or alternate email address](#)
- [Generic SSO authentication](#)
- [CAS-based authentication](#)
- [auth.conf](#)
  - [user\\_table paragraph](#)
  - [ldap paragraph](#)
  - [generic\\_sso paragraph](#)
  - [cas paragraph](#)
- [Sharing WWSympa's authentication with other applications](#)
- [Provide a Sympa login form in another application](#)

## Authorization scenarios

- Authorization scenarios
  - Location of scenario file
- Scenario structure
  - Rules specifications
- Named Filters
  - LDAP Named Filters Definition
  - SQL Named Filters Definition
  - Search condition
- Scenario inclusion
- Scenario implicit inclusion
- Blacklist implicit rule
- Custom Perl package conditions
- Hiding scenario files

## virtual host

- Virtual host
- How to create a virtual host
- robot.conf
  - Robot customization
- Managing multiple virtual hosts

## Interaction between Sympa and other applications

- Interaction between Sympa and other applications
- Soap
- RSS channel
- Sharing WWSympa's authentication with other applications
- Sharing data with other applications
- Subscriber count

## Customizing Sympa

- Customizing Sympa/WWSympa
- Template file format
- Site template files
  - helpfile.tt2
  - lists.tt2
  - global\_remind.tt2
  - your\_infected\_msg.tt2
- Web template files
  - Sympa colors customization guide
- CSS files
  - css\_path and css\_url parameters
  - What stylesheet will be used ?

- Using wwsympa CSS generation process
- Use custom stylesheets only
- Internationalization
  - Sympa internationalization
  - List internationalization
  - User internationalization
- Topics
- Authorization scenarios
- Custom parameters
- Loop detection
- Tasks
  - List task creation
  - Global task creation
  - Model file format
  - Model file examples

## Mailing list definition

- Mailing list definition
- Mail aliases
- List configuration file
- Examples of configuration files
- Subscribers file
- Info file
- Homepage file
- Data inclusion file
- List template files
  - welcome.tt2
  - bye.tt2
  - removed.tt2
  - reject.tt2
  - invite.tt2
  - remind.tt2
  - summary.tt2
  - list\_aliases.tt2
- Stats file
- List model files
  - remind.annual.task
  - expire.annual.task
- Message header and footer
  - Archive directory

## List creation, edition and removal

- List creation, editing and removal
- List creation

- Data for list creation
- XML file format
- List families
- List creation on command line with sympa.pl
- Creating and editing mailing lists using the Web
  - List creation on the web interface
  - Who can create lists on the web interface
  - Typical list profile and web interface
  - List editing
- Removing a list

## Lists Families

- List families
- Family concept
- Using family
  - Definition
  - Instantiation
  - Modification
  - Closure
  - Adding a list to a list family
  - Removing a list from a list family
  - Modifying a family list
  - Editing list parameters in a family context
- Automatic list creation
  - Configuring your MTA
  - Defining the list family
  - Configuring Sympa

## List configuration parameters

- List configuration parameters

## List definition

- List parameters: definition
  - subject
  - visibility
  - owner
  - owner\_include
  - editor
  - editor\_include
  - topics
  - host
  - lang
  - family\_name

- latest\_instantiation

## Sending/receiving setup

- send
- digest
- digest\_max\_size
- available\_user\_options
- default\_user\_options
- msg\_topic
- msg\_topic\_keywords\_apply\_on
- msg\_topic\_tagging
- reply\_to\_header
- anonymous\_sender
- custom\_header
- rfc2369\_header\_fields
- custom\_subject
- footer\_type

## Privileges

- info
- subscribe
- unsubscribe
- add
- del
- invite
- review
- remind
- shared\_doc

## Archives

- Archive related
  - archive
  - web\_archive
  - archive\_crypted\_msg

## Bounce management

- Bounce related
  - bounce
  - bouncers\_level1
  - bouncers\_level2
  - welcome\_return\_path
  - remind\_return\_path
  - verp\_rate

## Data sources setup

- Data source related
  - user data source
  - ttl
  - include list
  - include remote sympa list
  - include sql query
  - include ldap query
  - include ldap 2level query
  - include file
  - include remote file

## Others

- Command related
  - remind task
  - expire task
  - review
- List tuning
  - max\_size
  - loop\_prevention\_regex
  - pictures\_feature
  - cookie
  - priority
- Spam protection
  - spam protection
  - web\_archive\_spam\_protection

## Reception mode

- Message topics
  - Message topic definition in a list
  - Subscribing to message topics for list subscribers
  - Message tagging

## Shared documents

- Shared documents
  - The three kinds of operations on a document
  - The description file
  - The predefined authorization scenarios
  - Access control
  - Shared document actions
  - Template files
  - d\_upload.tt2

- [d\\_properties.tt2](#)

## Bounce management

- [Bounce management](#)
- [VERP](#)
- [ARF](#)

## Antivirus

- [Antivirus](#)

## Using Sympa with LDAP

- [Using Sympa with LDAP](#)

## Sympa with S/MIME and HTTPS

- [Sympa with S/MIME and HTTPS](#)
- [Signed message distribution](#)
- [Use of S/MIME signatures by Sympa itself](#)
- [Use of S/MIME encryption](#)
- [S/Sympa configuration](#)
  - [Installation](#)
  - [Managing user certificates](#)
  - [Configuration in sympa.conf](#)
  - [Configuration to recognize S/MIME signatures](#)
  - [distributing encrypted messages](#)
- [Managing certificates with tasks](#)
  - [chk\\_cert\\_expiration.daily.task model](#)
  - [crl\\_update.daily.task model](#)

## Using Sympa commands

- [Using Sympa commands](#)
- [User commands](#)
- [Owner commands](#)
- [Moderator commands](#)

## About this document ...

Edit

## Presentation

---

Sympa is an electronic mailing list manager. It is used to automate list management functions such as subscription, moderation, archive and shared document management. It also includes management functions which would normally require a substantial amount of work (time-consuming and costly for the list owner). These functions include automatic management of subscription renewals, list maintenance, and many others.

Sympa manages many different kinds of lists. It includes a web interface for all list functions including management. It allows a precise definition of each list feature, such as sender authorization, moderating process, etc. Sympa defines, for each feature of each list, exactly who is authorized to perform the relevant operations, along with the authentication method to be used. Currently, authentication can be based on either an SMTP `From` header, a password, or an S/MIME signature.

Sympa is also able to extract electronic addresses from an LDAP directory or SQL server and to include them dynamically in a list.

Sympa manages the dispatching of messages, and makes it possible to reduce the load on the computer system where it is installed. In configurations with sufficient memory, Sympa is especially well adapted to handle large lists: for a list of 20,000 subscribers, it requires less than 6 minutes to send a message to 95 % of the subscribers, assuming that the network is available (tested on a 300 MHz, 256 MB i386 server with Linux).

This guide covers the installation, configuration and management of the current release (5.3a.10) of Sympa [<http://www.sympa.org>].

## License

---

Sympa is free software; you may distribute it under the terms of the GNU General Public License Version 2 [<http://www.gnu.org/copyleft/gpl.html>].

You may make and give away verbatim copies of the Source form of this package without restriction, provided that you duplicate all of the original copyright notices and associated disclaimers.

## Features

---

Sympa provides all the basic features that any mailing list management robot should include. While most Sympa features have their equivalents in other mailing list applications, Sympa is unique in including features in a single software package. These features are:

- **High speed distribution processing and load control.** Sympa can be tuned to allow the system administrator to control the amount of computer resources used. Its optimized algorithm allows:
  - the use of your preferred SMTP engine, e.g. Sendmail, qmail or Postfix,
  - tuning of the maximum number of SMTP child processes,
  - grouping of messages according to recipients' domains, and tuning of the grouping factor,
  - detailed logging;
- **Multilingual** user interface. The full user/admin interface (mail and web) is internationalized. Translations are

gathered in a standard PO file;

- **Template-based** user interface. Every web page and service message can be customized through the **TT2** template format;
- **MIME support**. Sympa naturally respects MIME in the distribution process, and in addition it allows list owners to configure their lists with welcome, goodbye and other predefined messages using complex MIME structures. For example, a welcome message can be in **multipart/alternative** format, using **text/html**, **audio/x-wav** 🎵, or whatever (Note that Sympa commands in multipart messages are successfully processed, provided that one part is **text/plain**);
- The **sending process is controlled** on a per-list basis. The list definition allows a number of different actions for each incoming message. A `private` list is a list where only subscribers can send messages. A list configured using `privateeditorkey` mode accepts incoming messages from subscribers, but will forward any other message (i.e. sent by non-subscribers) to the editor with a unique secret numeric key that will be used by the editor to *reject* or *distribute* the message. For details about the different sending modes, refer to the send parameter. The sending process configuration (as well as most other list operations) is defined using an **authorization scenario**. Any listmaster can define new authorization scenarios in order to complement the 20 predefined configurations included in the distribution (Example: forward multipart messages to the list editor, while distributing others without requiring any further authorization);
- **Privileged operations** can be performed by list editors or list owners (or any other user category), as defined in the list `config` file or by the robot administrator, the listmaster, defined in the `/etc/sympa.conf` global configuration file (a listmaster can also be defined for a particular virtual host). Privileged operations include the usual `ADD`, `DELETE` and `REVIEW` commands, which can be authenticated through a unique password or an S/MIME signature;
- **Web interface**: *WWSympa* is a global Web interface to all Sympa functions (including administration). It provides:
  - a classification of lists, along with a search index,
  - an access control to all functions, including the list of lists (which makes *WWSympa* particularly well suited to be the main groupware tool within an intranet),
  - the management of shared documents (download, upload, specific access control for each document),
  - an HTML presentation personalized for each user with the list of his/her current subscriptions, including access to message archives, subscription options, etc
  - management tools for list managers (bounce processing, changing of list parameters, moderating incoming messages),
  - tools for the robot administrator (list creation, global robot configuration);To know more, refer to WWSympa, Sympa's web interface.
- **RDBMS**: the internal subscriber and administrative data structure can be stored in a database or, for compatibility with versions 1.x, in text files for subscriber data. The introduction of databases came out of the *WWSympa* project. The database ensures a secure access to shared data. The PERL database API `DBI/DBD` enables interoperability with various RDBMS (MySQL, SQLite, PostgreSQL, Oracle, Sybase). To know more, refer to Sympa and its database;
- **Virtual hosting**: a single Sympa installation can provide multiple virtual robots with both email and web interface customization (see Virtual host);
- **LDAP-based mailing lists**: e-mail addresses can be retrieved dynamically from a database accepting SQL queries, or from an LDAP directory. In order to maintain reasonable response times, Sympa retains the data source in an internal cache controlled by a TTL (Time To Live) parameter (see include-ldap-query);
- **LDAP authentication**: via uid and emails stored in LDAP Directories. Alternative email addresses, extracted from a LDAP directory, may be used to “unify” subscriptions (see Authentication with email address, uid or alternate email address);

- **Antivirus scanner:** Sympa extracts attachments from incoming messages and runs a virus scanner on them. Currently working with McAfee/uvscan, Fsecure/fsav, Sophos, AVP, Trend Micro/VirusWall and Clam Antivirus (see [Antivirus](#));
- **Inclusion of the subscribers** of one list among the subscribers of another. This is real inclusion, not the dirty, multi-level cascading one might otherwise obtain by simply “subscribing list B to list A”
- **RSS channel.**

## Project directions

---

Sympa is a very active project: check the [release notes](#). Thus it is not possible to maintain multiple documents about the Sympa project directions anymore. Please refer to the Future Sympa developments page for information about the project directions.

## History

---

Sympa development started from scratch in 1995. The goal was to ensure continuity with the TULP list manager, produced partly by the initial author of Sympa: Christophe Wolfhugel.

New features were required, which the TULP code was just not able to handle. The initial version of Sympa brought authentication, the flexible management of commands, high performances in internal data access, and object oriented code for easy code maintenance.

It took nearly two years to produce the first market releases.

Other dates:

- Mar 1999 Internal use of a database (MySQL), definition of list subscriber with external data source (RDBMS or LDAP).
- Oct 1999 Stable version of WWSympa, introduction of authorization scenarios.
- Feb 2000 Web bounce management.
- Apr 2000 Archive search engine and message removal.
- May 2000 List creation feature from the web
- Jan 2001 Support for S/MIME (signing and encryption), list setup through the web interface, shared document repository for each list. Full rewrite of HTML look and feel.
- Jun 2001 Auto-install of aliases at list creation time, antivirus scanner plugin.
- Jan 2002 Virtual hosting, LDAP authentication.
- Aug 2003 Automatic bounce management.
- Sep 2003 CAS-based and Shibboleth-based authentication.
- Dec 2003 Sympa SOAP server.
- Aug 2004 Changed for TT2 template format and PO catalogue format.
- 2005 Changed HTML to XHTML + CSS, RSS, list families, ...

## Mailing lists and support

---

If you wish to contact the authors of Sympa, please use the address `sympa-authors@cr.ufr.fr`.

There are also a few mailing-lists about Sympa [<http://listes.cru.fr/sympa/lists/informatique/sympa>]:

- `sympa-users (@) cru.fr` general information list
- `sympa-fr (@) cru.fr`, for French-speaking users
- `sympa-announce (@) cru.fr`, Sympa announcements
- `sympa-dev (@) cru.fr`, Sympa developers
- `sympa-translation (@) cru.fr`, Sympa translators

To join, send the following message to `sympa (@) cru.fr`:

```
subscribe Listname Firstname Name
```

(replace *Listname*, *Firstname* and *Name* by the list name, your first name and your last name).

You may also refer to the Sympa homepage [<http://www.sympa.org>]; there you will find the latest version [[http://www.sympa.org/distribution/latest version](http://www.sympa.org/distribution/latest%20version)], the [FAQ](#) and so on.

Edit

## Organization

---

Here is a snapshot of what Sympa looks like once installed on your system. This also illustrates the Sympa philosophy, we guess. Almost all configuration files can be defined for a particular list, for a virtual host or for the entire site, and most of them have a reasonable default value provided by Sympa distribution.

The following reference manual assumes a particular location for all files and directories. Note that binary distributions usually change those locations according to the operating system file organization. When installing Sympa from source kit, `configure` can be called with command options in order to change all default file locations.

- `/home/sympa`  
The root directory of Sympa. You will find almost everything related to Sympa under this directory, except logs and main configuration files.
- `/home/sympa/bin`  
This directory contains the binaries, including the CGI. It also contains the default authorization scenarios, templates and configuration files as in the distribution. `/home/sympa/bin` may be completely overwritten by the `make install` so you must not customize templates and authorization scenarios under `/home/sympa/bin`.
- `/home/sympa/bin/etc`  
Here Sympa stores the default versions of what it will otherwise find in `/home/sympa/etc` (task models, authorization scenarios, templates and configuration files, recognized S/Mime certificates, families).
- `/home/sympa/etc`  
This is your site's configuration directory. Consult `/home/sympa/bin/etc` when drawing up your own.
- `/home/sympa/etc/create_list_templates/`  
List templates (suggested at list creation time).
- `/home/sympa/etc/scenari/`  
This directory will contain your authorization scenarios. If you don't know what the hell an authorization scenario is, refer to [Authorization scenarios](#). Those authorization scenarios are default scenarios but you may look at `/home/sympa/etc/my.domain.org/scenari/` for default scenarios of `my.domain.org` virtual host and `/home/sympa/expl/mylist/scenari` for scenarios specific to a particular list.
- `/home/sympa/etc/data_sources/`  
This directory will contain your `.incl` files (see [Data inclusion file](#)). At the moment it only deals with files required by

paragraphs `owner_include` and `editor_include` in the config file.

- `/home/sympa/etc/list_task_models/`

This directory will store your own list task models (see [Customizing tasks](#)).

- `/home/sympa/etc/global_task_models/`

Contains your global task models (see [Customizing tasks](#)).

- `/home/sympa/etc/web_tt2/` (used to be `/home/sympa/etc/wws_templates/`)

The web interface (*WWSympa*) is composed of template HTML files parsed by the CGI program. Templates can also be defined for a particular list in `/home/sympa/expl/mylist/web_tt2/` or in `/home/sympa/etc/my.domain.org/web_tt2/`

- `/home/sympa/etc/mail_tt2/` (used to be `/home/sympa/etc/templates/`)

Some of the mail robot's replies are defined by templates (`welcome.tt2` for SUBSCRIBE). You can overload these template files in the individual list directories or for each virtual host, but these are the defaults.

- `/home/sympa/etc/families/`

Contains your family directories (see [Mailing list creation](#)). Family directories can also be created in `/home/sympa/etc/my.domain.org/families/`

- `/home/sympa/etc/my.domain.org`

The directory to define the virtual host `my.domain.org` dedicated to management of all lists of this domain (list description of `my.domain.org` are stored in `/home/sympa/expl/my.domain.org`). Those directories for virtual hosts have the same structure as `/home/sympa/etc` which is the configuration dir of the default robot.

- `/home/sympa/expl`

Sympa's working directory.

- `/home/sympa/expl/mylist`

The list directory (refer to [Mailing list definition](#)). Lists stored in this directory belong to the default robot as defined in `sympa.conf` file, but a list can be stored in `/home/sympa/expl/my.domain.org/mylist` directory and it is managed by `my.domain.org` virtual host.

- `/home/sympa/expl/X509-user-certs`

The directory where Sympa stores all user's certificates.

- `/home/sympa/locale`

Internationalization directory. It contains message catalogues in the GNU `.po` format.

- `/home/sympa/spool`

Sympa uses 9 different spools (see [Spools](#)).

- `/home/sympa/src/`

Sympa sources.

## Binaries

---

- `sympa.pl`

The main daemon; it processes commands and delivers messages. Continuously scans the `msg/` spool.

- `sympa_wizard.pl`

A wizard to edit `sympa.conf` and `wwsympa.conf`. Maybe it is a good idea to run it at the beginning, but these files can also be edited with your favorite text editor.

- `wwsympa.fcgi`

The CGI program offering a complete web interface to mailing lists. It can work in both classical CGI and FastCGI modes, although we recommend FastCGI mode, being up to 10 times faster.

- `bounced.pl`

This daemon processes bounces (non-delivered messages), looking for bad addresses. List owners will later access

bounce information via *WWSympa*. Continuously scans the `bounce/` spool.

- `archived.pl`

This daemon feeds the web archives, converting messages to HTML format and linking them. It uses the amazing *MhOnArc*. Continuously scans the `outgoing/` spool.

- `task_manager.pl`

The daemon which manages the tasks: creation, checking, execution. It regularly scans the `task/` spool.

- `sympa_soap_server.fcgi`

The server will process SOAP (web services) request. This server requires FastCGI; it should be referenced from within your HTTPS config.

- `queue`

This small program gets the incoming messages from the aliases and stores them in `msg/` spool.

- `bouncequeue`

Same as `queue` for bounces. Stores bounces in `bounce/` spool.

## Configuration files

---

- `/etc/sympa.conf`

The main configuration file. See [Sympa.conf parameters](#).

- `/etc/wwsympa.conf`

*WWSympa* configuration file. See [the description of WWSympa](#).

- `edit_list.conf`

Defines which parameters/files are editable by owners. See [List editing](#).

- `topics.conf`

Contains the declarations of your site's topics (classification in *WWSympa*), along with their titles. A sample is provided in the `sample/` directory of the Sympa distribution. See [Topics](#).

- `auth.conf`

Defines authentication backend organization (LDAP-based authentication, CAS-based authentication and Sympa internal).

- `robot.conf`

It is a subset of `sympa.conf` defining a Virtual host (one per Virtual host).

- `nrcpt_by_domain`

This file is used to limit the number of recipients per SMTP session. Some ISPs trying to block spams reject sessions with too many recipients. In such case you can set the `nrcpt` `robot.conf` parameter to a lower value but this will affect all SMTP sessions with any remote MTA. This file is used to limit the number of recipients for some particular domains. The file must contain a list of domains followed by the maximum number of recipients per SMTP session. Example:

- `data_structure.version`

This file is automatically created and maintained by Sympa itself. It contains the current version of your Sympa service and is used to detect upgrades and trigger maintenance procedures such as database structure changes.

```
yohaa.com 3
oal.com 5
```

## Spools

---

See [Spool related](#) for spool definition in `sympa.conf`.

- `/home/sympa/spool/auth/`  
For storing messages until they have been confirmed.
- `/home/sympa/spool/bounce/`  
For storing incoming bouncing messages.
- `/home/sympa/spool/digest/`  
For storing message digests before they are sent.
- `/home/sympa/spool/mod/`  
For storing unmoderated messages.
- `/home/sympa/spool/msg/`  
For storing incoming messages (including commands).
- `/home/sympa/spool/msg/bad/`  
Sympa stores rejected messages in this directory
- `/home/sympa/spool/distribute/`  
For storing messages ready for distribution. This spool is used only if the installation runs 2 `sympa.pl` daemons, one for commands, one for messages.
- `/home/sympa/spool/distribute/bad/`  
Sympa stores rejected messages in this directory.
- `/home/sympa/spool/task/`  
For storing all tasks created.
- `/home/sympa/spool/outgoing/`  
`sympa.pl` dumps messages in this spool to await archiving by `archived.pl`.
- `/home/sympa/spool/topic/`  
For storing topic information files.

## Roles and privileges

---

You can assign roles to users (identified via their email addresses) at different levels in Sympa; privileges are associated (or can be associated) to these roles. We list these roles below (from the most powerful to the least), along with the relevant privileges.

### (Super) listmasters

---

These are the persons administrating the service, defined in the `sympa.conf` file. They inherit the listmaster role in virtual hosts and are the default set of listmasters for virtual hosts.

### (Robot) listmasters

---

You can define a different set of listmasters at a virtual host level (in the `robot.conf` file). They are responsible for moderating mailing lists creation (if list creation is configured this way), editing default templates, providing help to list owners and moderators. Users defined as listmasters get a privileged access to the Sympa web interface. Listmasters also inherit the privileges of list owners (for any list defined in the virtual host), but not the moderator privileges.

### Privileged list owners

---

The first defined privileged owner is the person who requested the list creation. Later it can be changed or extended. They inherit (basic) owner privileges and are also responsible for managing the list owners and editors themselves (through the web interface). With Sympa's default behavior, privileged owners can edit more list parameters than (basic) owners can do; but this can be customized via the `edit-list.conf` file.

## (Basic) list owners

---

They are responsible for managing the members of the list, editing the list configuration and templates. Owners (and privileged owners) are defined in the list config file.

## Moderators (also called Editors)

---

Moderators are responsible for the messages distributed in the mailing list (as opposed to owners who look after list members). Moderators are active if the list has been setup as a moderated mailing list. If no moderator is defined for the list, then list owners will inherit the moderator role.

## Subscribers (or list members)

---

Subscribers are the persons who are members of a mailing list; they either subscribed, or got added directly by the listmaster or via a data source (LDAP, SQL, another list, ...). These subscribers receive messages posted in the list (unless they have set the `nomail` option) and have special privileges to post in the mailing list (unless it is a newsletter). Most privileges a subscriber may have are not hard coded in Sympa but expressed via the so-called authorization scenarios (see [Scenarios](#)).

Edit

## sympa.pl

---

`sympa.pl` is the main daemon; it processes mail commands and is in charge of messages distribution.

`sympa.pl` recognizes the following command line arguments:

- - `add_list familyname - - robot robotname - - input_file /path/to/list_file.xml`  
Adds the list described in the XML file to the *familyname* family. See: [Adding a list to a list family](#).
- - `close_family familyname - - robot robotname`  
Closes the *familyname* family. See: [List family closure](#).
- - `close_list listname@robot`  
Closes the list (changing its status to closed), removes aliases (if `sendmail_aliases` parameter was set) and removes subscribers from DB (a dump is created in the list directory to allow the list restoration). When you are in a family context, refer to: [List family closure](#).
- - `close_unknown`  
When instanciating a family, this option tells Sympa to silently close lists unknown to the family.
- - `config config_file|-f config_file`  
Forces Sympa to use an alternative configuration file. The default behavior is to use the configuration file as defined

in the Makefile (\$CONFIG).

- `- create_list - robot robotname - - input_file /path/to/list_file.xml`  
Creates the list described by the xml file, see: [List creation on command line with sympa.pl](#).
- `- debug|-d`  
Sets Sympa in debug mode and keeps it attached to the terminal. Debugging information is output to STDERR, along with standard log information. Each function call is traced. Useful while reporting a bug.
- `- dump listname | ALL`  
Dumps subscribers, either of the list *listname* or of all lists. Subscribers are dumped in `subscribers.db.dump`.
- `- help|-h`  
Prints `sympa.pl` usage.
- `- import listname`  
Imports subscribers in the *listname* list. Data are read from STDIN.
- `- instantiate_family familyname robotname - - input_file /path/to/family_file.xml`  
Instantiates the family *familyname*. See [Lists families](#).
- `- keepcopy recipient_directory|-k recipient_directory`  
Tells Sympa to keep a copy of every incoming message instead of deleting them. *recipient\_directory* is the directory to store messages.
- `- lang catalog|-l catalog`  
Set this option to use a language catalog for Sympa. The corresponding catalog file must be located in `~sympa/locale` directory.
- `- lowercase`  
Lowercases e-mail addresses in database.
- `- mail|-m`  
Sympa will log calls to sendmail, including recipients. Useful to keep track of each mail sent (log files may grow faster though).
- `- make_alias_file`  
Creates an aliases file in `/tmp/` with all list aliases (only lists whose status is 'open'). It uses the `list_aliases.tt2` template.
- `- modify_list familyname - - robot robotname - - input_file /path/to/list_file.xml`  
Modifies the existing family list, with description contained in the XML file. See: [Modifying a family list](#).
- `-quiet`  
When instantiating a family, this option tells Sympa to skip output to STDOUT.
- `- reload_list_config - -list=mylist@dom`  
Recreates all `configbin` files. You should run this command if you edit authorization scenarios. The `list` parameter is optional.
- `service process_command | process_message | process_creation`  
Sets Sympa daemon to process only message distribution (`process_message`) or only commands (`process_command`) or list creation requests (`process_creation`).
- `- sync_include listaddress`  
Triggers an update of list members, useful if the list uses external data sources.
- `- upgrade - - from=X - -to=Y`  
Runs Sympa maintenance script to upgrade from version X to version Y.
- `- version|-v`  
Prints current version of Sympa.

## INIT script

---

The `make install` step should have installed a sysV init script in your `/etc/rc.d/init.d/` directory (you can change this at `configure` time with the `-with-initdir` option). You should edit your runlevels to make sure Sympa starts after Apache and MySQL. Note that MySQL should also start before Apache because of `wwsympa.fcgi`.

This script starts these daemons: `sympa.pl`, `task_manager.pl`, `archived.pl` and `bounced.pl`.

## Stopping Sympa and signals

---

### kill -TERM

When this signal is sent to `sympa.pl` (`kill -TERM`), the daemon is stopped, ending message distribution in progress and this can be long (for big lists). If `kill -TERM` is used, `sympa.pl` will stop immediately whatever a distribution message is in progress. In this case, when `sympa.pl` restarts, messages will be distributed many times.

### kill -HUP

When this signal is sent to `sympa.pl` (`kill -HUP`), it switches of the `-mail` login option and continues current task.

Edit

## Upgrading Sympa

---

Sympa upgrade is a relatively riskless operation, mainly because the install process preserves your customizations (templates, configuration, authorization scenarios, ...) and also because Sympa automates a few things (DB update, CPAN modules installation).

Upgrading Sympa means that you follow these steps:

1. retrieve the latest source version of Sympa
2. stop Sympa
3. install it :

```
./configure ; make ; make install
```

4. run the following command.

```
sympa.pl --upgrade
```

And that' it!

This command will perform all the required DB changes (if running MySQL) and will update the configuration files if required.

## Incompatible changes

---

New features, changes and bug fixes are summarized in the NEWS file, part of the tar.gz (the Changelog file is a complete log file of CVS changes).

For example, note that, starting from Sympa 5.3b.4, the minimum version for MySQL is 4.1.

Sympa is a long-term project, so some major changes may need some extra work. The following list consists of well known changes that require some attention:

- version 5.1 (August 2005) uses XHTML and CSS in web templates;
- version 4.2b3 (August 2004) introduces TT2 template format;
- version 4.0a5 (September 2003) changes `auth.conf` (no default anymore so you may have to create this file);
- version 3.3.6b2 (May 2002) the list parameter `user_data_source` as a new value `include2` which is the recommended value for any list.

The file NEWS lists all changes and of course, all changes that may require some attention from the installer. As mentioned at the beginning of this file, incompatible changes are preceded by `*****`. While running the `make install` Sympa will detect the previously installed version and will prompt you with incompatible changes between both versions of the software. You can interrupt the install process at that stage if you are too frightened. Output of the `make install`:

```
-----
You are upgrading from Sympa 4.2
You should read CAREFULLY the changes listed below; they might be incompatible changes:
<RETURN>

*****  require new perlmodule XML-LibXML

*****  You should update your DB structure (automatically performed by Sympa with MySQL), adding the following:
*****  CREATE TABLE admin_table (
*****  list_admin          varchar(50) NOT NULL,
*****  user_admin          varchar(100) NOT NULL,
*****  role_admin          enum('listmaster','owner','editor') NOT NULL,
*****  date_admin          datetime NOT NULL,
*****  update_admin        datetime,
*****  reception_admin    varchar(20),
*****  comment_admin      varchar(150),
*****  subscribed_admin    enum('0','1'),
*****  included_admin      enum('0','1'),
*****  include_sources_admin varchar(50),
*****  info_admin          varchar(150),
*****  profile_admin       enum('privileged','normal'),
*****  PRIMARY KEY (list_admin, user_admin, role_admin),
*****  INDEX (list_admin, user_admin, role_admin)
*****  );

*****  Extend the generic_sso feature; Sympa is now able to retrieve the user email address in a LDAP directory.
<RETURN>
-----
```

## CPAN modules update

---

The installation of required and optional Perl modules (CPAN) is automatically handled at the `make` time. You are asked before each module is installed. For optional modules, associated features are listed.

## Output of the make command:

```
-----
Checking for REQUIRED modules:
-----
perl module          from CPAN          STATUS
-----
Archive::Zip         Archive-Zip        OK (1.09  >= 1.05)
CGI                  CGI                OK (2.89  >= 2.52)
DB_File             DB_FILE           OK (1.806 >= 1.75)
Digest::MD5         Digest-MD5        OK (2.20  >= 2.00)
FCGI                FCGI              OK (0.67  >= 0.67)
File::Spec          File-Spec         OK (0.83  >= 0.8)
IO::Scalar          IO-stringy        OK (2.104 >= 1.0)
LWP                 libwww-perl       OK (5.65  >= 1.0)
Locale::TextDomain libintl-perl      OK (1.10  >= 1.0)
MHonArc::UTF8       MHonArc           version is too old ( < 2.4.6).
>>>>>> You must update 'MHonArc' to version '' <<<<<<.
Setting FTP Passive mode
Description:
Install module MHonArc::UTF8 ? n
MIME::Base64        MIME-Base64       OK (3.05  >= 3.03)
MIME::Tools         MIME-tools        OK (5.411 >= 5.209)
Mail::Internet      MailTools         OK (1.60  >= 1.51)
Regexp::Common      Regexp-Common     OK (2.113 >= 1.0)
Template            Template-Toolkit  OK (2.13  >= 1.0)
XML::LibXML         XML-LibXML        OK (1.58  >= 1.0)
-----

Checking for OPTIONAL modules:
-----
perl module          from CPAN          STATUS
-----
Bundle::LWP         LWP               OK (1.09  >= 1.09)
Constant subroutine CGI::XHTML_DTD    redefined at /usr/lib/perl5/5.8.0/constant.pm line 108, <STDIN> line 1.
CGI::Fast           CGI               CGI::Fast doesn't return 1 (check it).
Crypt::CipherSaber CipherSaber       OK (0.61  >= 0.50)
DBD::Oracle         DBD-Oracle       was not found on this system.
Description: Oracle database driver, required if you connect to a Oracle database.
Install module DBD::Oracle ?
-----
```

## Database structure update

Whatever RDBMS you are using (MySQL, SQLite, Pg, Sybase or Oracle), Sympa will check every database tables and fields. If one is missing, `sympa.pl` will not start. If you are using MySQL, Sympa will also check field types and will try to change them (or create them) automatically, assuming that the DB user configured has sufficient privileges. If you are not using MySQL or if the DB user configured in `sympa.conf` does have sufficient privileges, then you should change the database structure yourself, as mentioned in the NEWS file (database structure is describe in the `src/etc/script/` directory of distribution).

### Output of Sympa logs :

```
-----
Table admin_table created in database sympa
Field 'comment_admin' (table 'admin_table' ; database 'sympa') was NOT found. Attempting to add it...
Field comment_admin added to table admin_table
Field 'date_admin' (table 'admin_table' ; database 'sympa') was NOT found. Attempting to add it...
Field date_admin added to table admin_table
Field 'include_sources_admin' (table 'admin_table' ; database 'sympa') was NOT found. Attempting to add it...
Field include_sources_admin added to table admin_table
Field 'included_admin' (table 'admin_table' ; database 'sympa') was NOT found. Attempting to add it...
Field included_admin added to table admin_table
Field 'info_admin' (table 'admin_table' ; database 'sympa') was NOT found. Attempting to add it...
Field info_admin added to table admin_table
Field 'list_admin' (table 'admin_table' ; database 'sympa') was NOT found. Attempting to add it...
-----
```

```
Field list_admin added to table admin_table
Field 'profile_admin' (table 'admin_table' ; database 'sympa') was NOT found. Attempting to add it...
Field profile_admin added to table admin_table
Field 'reception_admin' (table 'admin_table' ; database 'sympa') was NOT found. Attempting to add it...
Field reception_admin added to table admin_table
Field 'role_admin' (table 'admin_table' ; database 'sympa') was NOT found. Attempting to add it...
Field role_admin added to table admin_table
Field 'subscribed_admin' (table 'admin_table' ; database 'sympa') was NOT found. Attempting to add it...
Field subscribed_admin added to table admin_table
Field 'update_admin' (table 'admin_table' ; database 'sympa') was NOT found. Attempting to add it...
Field update_admin added to table admin_table
Field 'user_admin' (table 'admin_table' ; database 'sympa') was NOT found. Attempting to add it...
Setting list_admin,user_admin,role_admin fields as PRIMARY
Field user_admin added to table admin_table
```

You might need, for some reason, to make Sympa run the migration procedure from version X to version Y. This procedure is run automatically by `sympa.pl -upgrade` when it detects that `/data_structure.version` is older than the current version, but you can also run trigger this procedure yourself:

```
sympa.pl --upgrade --from=4.1 --to=5.2
```

## Preserving your customizations

---

Sympa comes with default configuration files (templates, scenarios,...) that will be installed in the `/home/sympa/bin` directory. If you need to customize some of them, you should copy the file first in a safe place, i.e. in the `/home/sympa/etc` directory. If you do so, the Sympa upgrade process will preserve your site customizations.

## Running two Sympa versions on a single server

---

This can be very convenient to have a stable version of Sympa and a fresh version for test purpose, both running on the same server.

Both Sympa instances must be completely partitioned, unless you want to make production mailing lists visible through the test service.

The biggest part of the partitioning is achieved while running the `./configure`. Here is a sample call to `./configure` on the test server side:

```
./configure --prefix=/home/sympa-dev \  
--with-confdir=/home/sympa-dev/etc \  
--with-mandir=/home/sympa-dev/man \  
--with-initdir=/home/sympa-dev/init \  
--with-piddir=/home/sympa-dev/pid \  
--with-lockdir=/home/sympa-dev/lock \  
--with-sendmail_aliases=/home/sympa-dev/etc/sympa_aliases
```

You can also customize more parameters via the `/home/sympa-dev/etc/sympa.conf` file.

If you wish to share the same lists in both Sympa instances, then some parameters should have the same value : `home`, `db_name`, `arc_path`.

## Moving to another server

---

If you're upgrading and moving to another server at the same time, we recommend you first to stop the operational service, move your data and then upgrade Sympa on the new server. This will guarantee that Sympa upgrade procedures have been applied on the data.

The migration process requires that you move the following data from the old server to the new one:

- the user database. If using MySQL you can probably just stop `mysqld` and copy the `/var/lib/mysql/sympa/` directory to the new server;
- the `/home/sympa/exp1` directory that contains list config;
- the directory that contains the spools;
- the directory `/etc/sympa.conf` and `wwsympa.conf`. Sympa new installation creates a file `/etc/sympa.conf` (see [sympa.conf parameters](#)) and randomly initializes the cookie parameter. Changing this parameter will break all passwords. When upgrading Sympa on a new server, take care that you start with the same value of this parameter, otherwise you might have problems!
- the web archive.

In some cases, you may want to install the new version and run it for a few days before switching the existing service to the new Sympa server. In this case, perform a new installation with an empty database and play with it. When you decide to move the existing service to the new server:

1. stop all sympa processes on both servers;
2. transfer the database;
3. edit the `/data_structure.version` on the new server; change the version value to reflect the old number;
4. start "sympa.pl -upgrade", it will upgrade the database structure according to the hop you do.

Edit

## Mail aliases

---

Mail aliases are required in Sympa for `sympa.pl` to receive mail commands and list messages. Management of these aliases will depend on the MTA (`sendmail`, `qmail`, `postfix`, `exim`) you're using, where you store aliases and whether you are managing virtual domains or not.

## Robot aliases

---

An electronic list manager such as Sympa is built around two processing steps:

- A message sent to a list or to Sympa itself (commands such as `subscribe` or `unsubscribe`) is received by the SMTP server. When receiving the message, the SMTP server runs the `queue` program (supplied in this package) to store the message in a spool.
- The `sympa.pl` daemon, set in motion at system startup, scans this spool. As soon as it detects a new message, it processes it and performs the requested action (distribution or processing of a command).

To separate the processing of commands (subscription, unsubscription, help requests, etc.) from the processing of

messages destined to mailing lists, a special mail alias is reserved for administrative requests, so that Sympa can be permanently accessible to users. The following lines must therefore be added to the `sendmail` alias file (often `/etc/aliases`):

```
-----  
sympa: '| /home/sympa/bin/queue sympa@my.domain.org''  
listmaster: '| /home/sympa/bin/queue listmaster@my.domain.org''  
bounce+*: '| /home/sympa/bin/bouncequeue sympa@my.domain.org''  
abuse-feedback-report: '| /home/sympa/bin/bouncequeue sympa@my.domain.org''  
sympa-request: postmaster  
sympa-owner: postmaster  
-----
```

Note: if you run Sympa virtual hosts, you will need one `sympa` alias entry per virtual host (see [Virtual host](#)).

`sympa-request` should be the address of the robot administrator, i.e. a person who manages Sympa (here `postmaster (@) cru.fr`).

`sympa-owner` is the return address for Sympa error messages.

The alias `bounce+*` is dedicated to collect bounces where VERP (variable envelope return path) was active. It is useful if `welcome_return_path unique` or `remind_return_path unique` or the `verp_rate` parameter is no null for at least one list.

The alias `abuse-feedback-report` is used for processing automatically feedback that respect ARF format (Abuse Report Feedback), which is a draft to specify how end users can complain about spam. It is mainly used by AOL.

Don't forget to run `newaliases` after any change to the `/etc/aliases` file!

Note: aliases based on `listserv` (in addition to those based on `sympa`) can be added for the benefit of users accustomed to the `listserv` and `majordomo` names. For example:

```
-----  
listserv:          sympa  
listserv-request: sympa-request  
majordomo:         sympa  
listserv-owner:   sympa-owner  
-----
```

## List aliases

---

For each new list, it is necessary to create up to six mail aliases (at least three). If you managed to setup the alias manager (see [Alias manager](#)), then Sympa will install automatically the following aliases for you.

For example, to create the `mylist` list, the following aliases must be added:

```
-----  
mylist:           | /home/sympa/bin/queue mylist@my.domain.org  
mylist-request:  | /home/sympa/bin/queue mylist-request@my.domain.org  
mylist-editor:   | /home/sympa/bin/queue mylist-editor@my.domain.org  
mylist-owner:    | /home/sympa/bin/bouncequeue mylist@my.domain.org  
mylist-subscribe: | /home/sympa/bin/queue mylist-subscribe@my.domain.org  
mylist-unsubscribe: | /home/sympa/bin/queue mylist-unsubscribe@my.domain.org  
-----
```

The address `mylist-request` should correspond to the person responsible for managing `mylist` (the owner). Sympa will forward messages sent to `mylist-request` to the owner of `mylist`, as defined in the

`/home/sympa/expl/mylist/config` file. Using this feature means you will not need to modify the alias file if the list owner were to change.

Similarly, the address `mylist-editor` can be used to contact the list editors, if defined in `/home/sympa/expl/mylist/config`. This address definition is not compulsory.

The address `mylist-owner` is the address receiving non-delivery reports (note that the `-owner` suffix can be customized, see [return path suffix](#)). The `bouncequeue` program stores these messages in the `queuebounce` directory. *WWSympa* (see [WWSympa presentation](#)) may then analyze them and provide a web access to them.

The address `mylist-subscribe` is an address enabling users to subscribe in a manner which can easily be explained to them. Beware: subscribing this way is so straightforward that you may find spammers subscribing to your list by accident.

The address `mylist-unsubscribe` is the equivalent for unsubscribing. By the way, the easier it is for users to unsubscribe, the easier it will be for you to manage your list!

## Alias manager

---

The `alias_manager.pl` script does aliases management. It is run by *WWSympa* and will install aliases for a new list and delete aliases for closed lists.

The script expects the following arguments :

1. `add|del`
2. `<list name>`
3. `<list domain>`

Example:

```
/home/sympa/bin/alias_manager.pl add mylistcru.fr
```

`/home/sympa/bin/alias_manager.pl` works on the alias file (as defined in `sympa.conf`) through the `sendmail_aliases` variable (default is `/etc/mail/sympa_aliases`). You must refer to this aliases file in your `sendmail.mc` (if using `sendmail`):

```
define(`ALIAS_FILE', `/etc/aliases,/etc/mail/sympa_aliases')dnl
```

Note that `sendmail` has requirements regarding the ownership and rights on both `sympa_aliases` and `sympa_aliases.db` files (the later being created by `sendmail` via the `newaliases` command). Anyhow, these two files should be located in a directory, every path component of which being owned by and writable only by the root user.

`/home/sympa/bin/alias_manager.pl` runs a `newaliases` command (via `aliaswrapper`), after any changes to aliases file.

If you manage virtual domains with your mail server, then you might want to change the form of aliases used by the alias manager. You can customize the `list_aliases` template that is parsed to generate list aliases (see

list\_aliases.tt2).

Note that you do not need alias management if you use MTA functionalities such as Postfix' `virtual_transport`. Then you can disable alias management in Sympa by positioning the `sendmail_aliases` parameter to `none`.

Ludovic Marcotte has written a version of `ldap_alias_manager.pl` that is LDAP enabled. This script is distributed with Sympa distribution; it needs to be customized with your own LDAP parameters.

## Virtual domains

---

When using virtual domains with `sendmail` or `postfix`, you can not refer to `mylist@my.domain.org` on the right-hand side of a `/etc/aliases` entry. You need to define an additional entry in a virtual table. You can also add a unique entry, with a regular expression, for your domain.

With Postfix, you should edit the `/etc/postfix/virtual.regexp` file as follows:

```
/^(.*)@my.domain.org$/ my.domain.org-$1
```

Entries in the 'aliases' file will look like this:

```
my.domain.org-sympa: /home/sympa/bin/queue
sympa@my.domain.org ..... my.domain.org-listA: /home/sympa/bin/queue listA@my.domain.org
```

With Sendmail, add the following entry to `/etc/mail/virtusertable` file:

```
@my.domain.org my.domain.org-%1%3
```

Edit

## sympa.conf parameters

---

The `/etc/sympa.conf` configuration file contains numerous parameters which are read on start-up of Sympa. If you change this file, do not forget that you will need to restart Sympa afterwards.

The `/etc/sympa.conf` file contains directives in the following format:

*keyword value*

Comments start with the `#` character at the beginning of a line. Empty lines are also considered as comments and are ignored. There should only be one directive per line, but their order in the file is of no importance.

### conf-parameters part1

- sympa.conf parameters

- Site customization
  - domain
  - email
  - listmaster
  - listmaster\_email
  - wwsympa\_url
  - soap\_url
  - spam\_protection
  - web\_archive\_spam\_protection
  - color\_0, color\_1, ..., color\_15
  - Color parameters
  - logo\_html\_definition
  - css\_path
  - css\_url
  - static\_content\_path
  - static\_content\_url
  - pictures\_feature
  - pictures\_max\_size
  - cookie
  - create\_list
  - automatic\_list\_feature
  - automatic\_list\_creation
  - automatic\_list\_removal
  - global\_remind

## conf-parameters part2

- sympa.conf parameters
- Directories
  - home
  - etc
- System related
  - syslog
  - log\_level
  - log\_socket\_type
  - pidfile
  - pidfile\_creation
  - umask
- Sending related
  - distribution\_mode
  - maxsmtp
  - log\_smtp
  - use\_blacklist
  - max\_size
  - misaddressed\_commands
  - misaddressed\_commands\_regexp
  - nrpt

- avg
- sendmail
- sendmail\_args
- sendmail\_aliases
- rfc2369\_header\_fields
- remove\_headers
- anonymous\_headers\_fields
- list\_check\_smt
- list\_check\_suffixes
- urlize\_min\_size
- Quotas
  - default\_shared\_quota
  - default\_archive\_quota
- Spool related
  - spool
  - queue
  - queuedistribute
  - queuemod
  - queuedigest
  - queueauth
  - queueoutgoing
  - queuetopic
  - queuebounce
  - queuetask
  - queueautomatic
  - tmpdir
  - sleep
  - clean\_delay\_queue
  - clean\_delay\_queuemod
  - clean\_delay\_queueauth
  - clean\_delay\_queuesubscribe
  - clean\_delay\_queuetopic
  - clean\_delay\_queueautomatic

## conf-parameters part3

- sympa.conf parameters
- Internationalization related
  - localedir
  - supported\_lang
  - lang
  - web\_recode\_to
  - filesystem\_encoding
- Bounce related
  - verp\_rate
  - welcome\_return\_path

- remind\_return\_path
- return\_path\_suffix
- expire\_bounce\_task
- purge\_orphan\_bounces\_task
- eval\_bouncers\_task
- process\_bouncers\_task
- minimum\_bouncing\_count
- minimum\_bouncing\_period
- bounce\_delay
- default\_bounce\_level1\_rate
- default\_bounce\_level2\_rate
- bounce\_email\_prefix
- bounce\_warn\_rate
- bounce\_halt\_rate
- default\_remind\_task
- Tuning
  - cache\_list\_config
  - lock\_method
  - sympa\_priority
  - request\_priority
  - owner\_priority
  - default\_list\_priority
- Database related
  - update\_db\_field\_types
  - db\_type
  - db\_name
  - db\_host
  - db\_port
  - db\_user
  - db\_passwd
  - db\_timeout
  - db\_options
  - db\_env
  - db\_additional\_subscriber\_fields
  - db\_additional\_user\_fields
  - purge\_user\_table\_task
- Loop prevention
  - loop\_command\_max
  - loop\_command\_sampling\_delay
  - loop\_command\_decrease\_factor
  - loop\_prevention\_regex
- S/MIME configuration
  - openssl
  - capath
  - cafile
  - key\_passwd

- chk\_cert\_expiration\_task
- crl\_update\_task
- Antivirus plug-in
  - antivirus\_path
  - antivirus\_args
  - antivirus\_notify

Edit

## sympa.conf parameters

---

The `/etc/sympa.conf` configuration file contains numerous parameters which are read on start-up of Sympa. If you change this file, do not forget that you will need to restart Sympa afterwards.

The `/etc/sympa.conf` file contains directives in the following format:

*keyword value*

Comments start with the `#` character at the beginning of a line. Empty lines are also considered as comments and are ignored. There should only be one directive per line, but their order in the file is of no importance.

## Site customization

---

### domain

---

This keyword is **mandatory**. It is the domain name used in the `From:` header in replies to administrative requests. So the SMTP engine (qmail, sendmail, postfix or whatever) must recognize this domain as a local address. The old keyword `host` is still recognized but should not be used anymore.

Example:

```
domain cru.fr
```

### email

---

(Default value: `sympa`)

Username (the part of the address preceding the `@` sign) used in the `From:` header in replies to administrative requests.

Example:

```
email listserv
```

## listmaster

---

The list of the email addresses of the listmasters (users authorized to perform global server commands). Listmasters can be defined for each virtual host.

Example:

```
listmaster postmaster@cru.fr,root@cru.fr
```

## listmaster\_email

---

(Default value: `listmaster`)

Username (the part of the address preceding the @ sign) used in the listmaster email. This parameter is useful if you want to run more than one sympa on the same host (a sympa test for example).

If you change the default value, you must modify the sympa aliases too.

For example, if you put:

```
listmaster listmaster-test
```

you must modify the sympa aliases like this:

```
listmaster-test: | /home/sympa/bin/queue listmaster@my.domain.org
```

See [Robot aliases](#) for all aliases.

## wwsympa\_url

---

(Default value: `http://host/wws`)

This is the root URL of *WWSympa*.

Example:

```
wwsympa_url https://my.server/sympa
```

## soap\_url

---

This is the root URL of Sympa's SOAP server. Sympa's WSDL document refers to this URL in its service section.

Example:

```
soap_url http://my.server/sympasoap
```

## spam\_protection

---

(Default value: javascript)

There is a need to protect Sympa website against spambot which collect email addresses in public websites. Various methods are available within Sympa, and you can choose between the `spam_protection` and `web_archive_spam_protection` parameters. Possible values are:

- `javascript`: the address is hidden using a javascript. Users who enable Javascript can see nice mailto addresses where others have nothing.
- `at`: the “@” char is replaced by the string “AT”.
- `none`: no protection against spammers.

## web\_archive\_spam\_protection

(Default value: cookie)

The same as `spam_protection`, but restricted to the web archive. An additional value is available: `cookie`, which means that users must submit a small form in order to receive a cookie before browsing the web archive. This block all robots, including search engine robots.

## color\_0, color\_1, ..., color\_15

They are the color definition parameters for the web interface. These parameters can be overwritten in each virtual host definition. Colors are used in the CSS files and unfortunately they are also in use in some web templates. The sympa admin interface shows all colors in use.

To know the exact role of each `color_x` parameter please consult [the color customization guide](#).

## Color parameters

A few color parameters were used in the past for color definition of the web interface:

`dark_color`, `light_color`, `text_color`, `bg_color`, `error_color`, `selected_color`, `shaded_color`.

These parameters are not used in version 5.1 and higher anymore, but still available in `style.css`, `print.css`, `print-preview.css` and `fullPage.css`.

*Note*: `light_color` is still used for the header color of the New lists presentation array.

## logo\_html\_definition

This parameter allows you to insert in the upper left corner of the page a piece of HTML code, usually to insert a logo in the page. This is a very basic but easy customization. Example:

```
logo_html_definition <a href='http://www.mycompany.com'><img style="float: left; margin-top: 7px; margin-left
```

## css\_path

Pre-parsed CSS files (let's say static CSS files) can be installed using the Sympa server skin module. These CSS files are installed in a part of the web server that can be reached without using the Sympa web engine. In order to do this, edit the `robot.conf` file and set the `css_path` parameter. Then restart the server and use the skin module from the "Admin sympa" page to install prepared CSS file. In order to replace dynamic CSS files by these static files, set the `css_url` parameter.

**After an upgrade, `sympa.pl` automatically updates the static CSS files with the newly installed `css.tt2`. Therefore, this is not a good place to store customized CSS files.**

## css\_url

---

By default, CSS files `style.css`, `print.css`, `print-preview.css` and `fullPage.css` are delivered by the Sympa web interface itself using a Sympa action named `css`. URLs look like "`http://foo.org/sympa/css/style.css`". CSS file are made parsing a `web_tt2` file named `css.tt2`. This allows dynamic definition of colors, and in a near future a complete definition of the skin, user preference skins, etc.

In order to make Sympa web interface faster, it is strongly recommended to install static CSS files somewhere in your website. This way, Sympa will deliver only one page instead of one page and four CSS files at each click. This can be done using the `css_url` parameter. The parameter must contain the URL of the directory where `style.css`, `print.css`, `print-preview.css` and `fullPage.css` are installed. You can make your own sophisticated new skin by editing these files. The server admin module includes a CSS administration page that can help you to install static CSS files.

## static\_content\_path

---

Some content may be delivered by the HTTP server (Apache) without any need to be controlled or parsed by Sympa. It is stored in the directory chosen through the `static_content_dir` parameter. The current Sympa version stores subscribers' pictures in this directory. Later updates will add stylesheets, icons, ... The directory is created by `sympa.pl` when started. This parameter can be defined also in `robot.conf`.

## static\_content\_url

---

Content stored in the directory specified by parameter `static_content_url` must be served by the HTTP server under the URL specified by `static_content_url`. Check Apache configuration in order to make this directory available. This parameter can be defined in `robot.conf`.

## pictures\_feature

---

(Default value: `off`)

Example:

```
-----  
pictures_feature on  
-----
```

Subscribers can upload their picture (from the 'Subscriber option' page) so that reviewing subscribers shows a gallery.

This parameter defines the default for corresponding list parameter but it does NOT allow to disable the feature overall. If you want to disable the feature for your entire site, you need to customize the `edit-list.conf` file to deny editing of the corresponding list parameter.

Pictures are stored in a directory specified by the `static_content_path` parameter.

## pictures\_max\_size

---

The maximum size of the uploaded picture file (bytes).

## cookie

---

This string is used to generate MD5 authentication keys. It allows generated authentication keys to differ from a site to another. It is also used for reversible encryption of user passwords stored in the database. The presence of this string is one reason why access to `sympa.conf` needs to be restricted to the `sympa` user.

Note that changing this parameter will break all HTTP cookies stored in users' browsers, as well as all user passwords and lists X509 private keys. To prevent a catastrophe, `sympa.pl` refuses to start if the `cookie` parameter was changed.

Example:

```
cookie gh869jku5
```

## create\_list

---

(Default value: `public_listmaster`)

The `create_list` parameter is defined by an authorization scenario (see [Authorization scenarios](#)).

Defines who can create lists (or request list creations). Sympa will use the corresponding authorization scenario.

Example:

```
create_list intranet
```

## automatic\_list\_feature

---

(Default value: `off`)

Example:

```
automatic_list_feature on
```

If set to `on`, Sympa will enable automatic list creation through family instantiation (see [Automatic list creation](#)).

## automatic\_list\_creation

---

(Default value: none)

The `automatic_list_creation` parameter is defined by an authorization scenario (see [Authorization scenarios](#)).

If `automatic_list_feature` is activated, this parameter (corresponding to an authorization scenario) defines who is allowed to use the automatic list creation feature.

## automatic\_list\_removal

---

(Default value:

Example:

```
automatic_list_feature if_empty
```

If set to `if_empty`, then Sympa will remove automatically created mailing lists just after their creation, if they contain no list member (see [Automatic list creation](#)).

## global\_remind

---

(Default value: listmaster)

The `global_remind` parameter refers to an authorization scenario (see [Authorization scenarios](#)).

Defines who can run a `REMININD * command`.

Edit

## sympa.conf parameters

---

### Directories

---

#### home

---

(Default value: /home/sympa/expl)

The directory whose subdirectories correspond to the different lists.

Example: home /home/sympa/expl

## etc

---

(Default value: `/home/sympa/etc`)

This is the local directory for configuration files (such as `edit_list.conf`). It contains 5 subdirectories:

- `scenari` for local authorization scenarios;
- `mail_tt2` for the site's local mail templates and default list templates;
- `web_tt2` for the site's local HTML templates;
- `global_task_models` for local global task models;
- `list_task_models` for local list task models.

Example:

```
etc /home/sympa/etc
```

## System related

---

### syslog

---

(Default value: `LOCAL1`)

Name of the sub-system (facility) for logging messages.

Example:

```
syslog LOCAL2
```

### log\_level

---

(Default value: `0`)

This parameter sets the verbosity of Sympa processes (including) in log files. With level `0` only main operations are logged, in level `3` almost everything is logged.

Example:

```
log_level 2
```

### log\_socket\_type

---

(Default value: `unix`)

Sympa communicates with `syslogd` using either UDP or UNIX sockets. Set `log_socket_type` to `inet` to use UDP, or `unix` for UNIX sockets.

## pidfile

---

(Default value: `/home/sympa/etc/sympa.pid`)

The file where the `sympa.pl` daemon stores its process number. Warning: the `sympa` user must be able to write to this file, and to create it if it does not exist.

Example:

```
pidfile /var/run/sympa.pid
```

## pidfile\_creation

---

(Default value: `/home/sympa/etc/sympa-creation.pid`)

The file where the automatic list creation dedicated `sympa.pl` daemon stores its process number. Warning: the `sympa` user must be able to write to this file, and to create it if it does not exist.

Example:

```
pidfile_creation /var/run/sympa-creation.pid
```

## umask

---

(Default value: `027`)

Default mask for file creation (see `umask`). Note that it will be interpreted as an octal value.

Example:

```
umask 007
```

## Sending related

---

### distribution\_mode

---

(Default value: `single`)

Use this parameter to determine whether your installation runs only one `sympa.pl` daemon that processes both messages to distribute and commands (`single`), or if `sympa.pl` will fork to run two separate processes, one dedicated to message distribution and one dedicated to commands and message pre-processing (`fork`). The second choice makes a better priority processing for message distribution and faster command response, but it requires a bit more computer resources.

Example:

```
distribution_mode fork
```

---

## maxsmtp

(Default value: 20)

Maximum number of SMTP delivery child processes spawned by Sympa. This is the main load control parameter.

Example:

```
maxsmtp 500
```

---

## log\_smtp

(Default value: off)

Set logging of each MTA call. Can be overwritten by `-m sympa` option.

Example:

```
log_smtp on
```

---

## use\_blacklist

(Default value: send, create\_list")

Sympa provides a blacklist feature available for list editors and owners. The `use_blacklist` parameter defines which operations use the blacklist. Search in blacklist is mainly useful for the `send` service (distribution of a message to the subscribers). You may use blacklist for other operations such as review, archive, etc., but be aware that those web services need fast response and blacklist may require some resources.

If you do not want blacklist at all, define `use_blacklist` to `none` so that the user interface to manage blacklist will disappear from the web interface.

---

## max\_size

(Default value: 5 Mb)

Maximum size (in bytes) allowed for messages distributed by Sympa. This may be customized per virtual host or per list by setting the `max_size` robot or list parameter.

Example:

```
max_size 2097152
```

---

## misaddressed\_commands

(Default value: `reject`)

When a robot command is sent to a list, by default Sympa rejects this message. This feature can be turned off setting this parameter to ignore.

## misaddressed\_commands\_regexp

---

(Default value: `(subscribe|unsubscribe|signoff)`)

This is the Perl regular expression applied on messages subject and body to detect misaddressed commands, see [misaddressed\\_commands](#) parameter.

## nrcpt

---

(Default value: 25)

Maximum number of recipients per `sendmail` call. This grouping factor makes it possible for the (`sendmail`) MTA to optimize the number of SMTP sessions for message distribution. If needed, you can limit the number of recipients for a particular domain. Check the `nrcpt_by_domain` configuration file (see [nrcpt\\_by\\_domain](#)).

## avg

---

(Default value: 10)

Maximum number of different Internet domains within addresses per `sendmail` call.

## sendmail

---

(Default value: `/usr/sbin/sendmail`)

Absolute path to SMTP message transfer agent binary. Sympa expects this binary to be `sendmail` compatible (`postfix`, `Qmail` and `Exim` binaries all provide `sendmail` compatibility).

Example:

```
sendmail /usr/sbin/sendmail
```

## sendmail\_args

---

(Default value: `-oi -odi -oem`)

Arguments passed to the SMTP message transfer agent.

## sendmail\_aliases

---

(Default value: defined by makefile, sendmail\_aliases | none)

Path of the alias file that contains all list related aliases. It is recommended to create a specific alias file so that Sympa never overwrites the standard alias file, but only a dedicated file. You must refer to this aliases file in your sendmail.mc: set this parameter to none if you want to disable alias management in Sympa (e.g. if you use virtual\_transport with Postfix).

## rfc2369\_header\_fields

---

(Default value: help, subscribe, unsubscribe, post, owner, archive)

RFC2369 compliant header fields (List-xxx) to be added to distributed messages. These header fields should be implemented by MUA's, adding menus.

## remove\_headers

---

(Default value: Return-Receipt-To, Precedence, X-Sequence, Disposition-Notification-To)

This is the list of headers that Sympa should remove from outgoing messages. Use it, for example, to ensure some privacy for your users by discarding anonymous options. It is (for the moment) site-wide. It is applied before the Sympa rfc2369\_header\_fields, and custom\_header fields are added.

Example:

```
remove_headers Resent-Date, Resent-From, Resent-To, Resent-Message-Id, Sender, Delivered-To"
```

## anonymous\_headers\_fields

---

(Default value: Sender, X-Sender, Received, Message-id, From, X-Envelope-To, Resent-From, Reply-To)

This parameter defines the list of SMTP header fields that should be removed when a mailing list is setup in anonymous mode (see [anonymous\\_sender](#)).

## list\_check\_smtp

---

(Default value: NONE)

If this parameter is set with a SMTP server address, Sympa will check if alias with the same name as the list you are creating already exists on the SMTP server. It is robot specific, i.e. you can specify a different SMTP server for every virtual host you are running. This is needed if you are running Sympa on somehost.foo.org, but you handle all your mail on a separate mail relay.

## list\_check\_suffixes

---

(Default value: `request,owner,unsubscribe`)

This parameter is a comma-separated list of admin suffixes you are using for Sympa aliases, i.e. `mylist-request,mylist-owner`, etc. This parameter is used with the `list_check_smtp` parameter. It is also used to check list names at list creation time.

## urlize\_min\_size

---

(Default value: `10240`)

This parameter is related to the `URLIZE` subscriber delivery mode; it defines the minimum size (in bytes) for MIME attachments to be urlized.

## **Quotas**

---

### default\_shared\_quota

---

The default disk quota (the unit is Kbytes) for lists' document repositories.

### default\_archive\_quota

---

The default disk quota (the unit is Kbytes) for lists' web archive.

## **Spool related**

---

### spool

---

(Default value: `/home/sympa/spool`)

The parent directory which contains all the other spools.

### queue

---

The absolute path of the directory which contains the queue, used both by the `queue` program and the `sympa.pl` daemon. This parameter is mandatory.

Example:

```
/home/sympa/spool/msg
```

### queuedistribute

---

(Default value: `/home/sympa/spool/distribute`)

This parameter is optional and retained solely for backward compatibility.

## queuemod

---

(Default value: `/home/sympa/spool/moderation`)

This parameter is optional and retained solely for backward compatibility.

## queuedigest

---

This parameter is optional and retained solely for backward compatibility.

## queueauth

---

(Default value: `/home/sympa/spool/auth`)

This parameter is optional and retained solely for backward compatibility.

## queueoutgoing

---

(Default value: `/home/sympa/spool/outgoing`)

This parameter is optional and retained solely for backward compatibility.

## queuetopic

---

(Default value: `/home/sympa/spool/topic`)

This parameter is optional and retained solely for backward compatibility.

## queuebounce

---

(Default value: `/home/sympa/spool/bounce`)

Spool to store bounces (non-delivery reports) received by the `bouncequeue` program via the `mylist-owner` (unless this suffix was customized) or `bounce+*` addresses (VERP) . This parameter is mandatory and must be an absolute path.

## queuetask

---

(Default value: `/home/sympa/spool/task`)

Spool to store task files created by the task manager. This parameter is mandatory and must be an absolute path.

## queueautomatic

---

(Default value: none)

The absolute path of the directory which contains the queue for automatic list creation, used by both the `familyqueue` program and the `sympa.pl` daemon. This parameter is mandatory when enabling `automatic_list_creation`.

Example:

```
/home/sympa/spool/msg
```

## tmpdir

---

(Default value: `/home/sympa/spool/tmp`)

Temporary directory used by OpenSSL and antiviruses.

## sleep

---

(Default value: 5)

Waiting period (in seconds) between each scan of the main queue. Never set this value to 0!

## clean\_delay\_queue

---

(Default value: 1)

Retention period (in days) for “bad” messages in spool (as specified by `queue`). Sympa keeps messages rejected for various reasons (badly formatted, looping, etc.) in this directory, with a name prefixed with `BAD`. This configuration variable controls the number of days these messages are kept.

Example:

```
clean_delay_queue 3
```

## clean\_delay\_queuemod

---

(Default value: 10)

Expiration delay (in days) in the moderation spool (as specified by `queuemod`). Beyond this deadline, messages that have not been processed are deleted. For moderated lists, the contents of this spool can be consulted using a key along with the `MODINDEX` command.

## clean\_delay\_queueauth

(Default value: 3)

Expiration delay (in days) in the authentication queue. Beyond this deadline, messages not enabled are deleted.

## clean\_delay\_queuesubscribe

(Default value: 10)

Expiration delay (in days) in the subscription requests queue. Beyond this deadline, requests not validated are deleted.

## clean\_delay\_queuetopic

(Default value: 7)

Delay for keeping message topic files (in days) in the topic queue. Beyond this deadline, files are deleted.

## clean\_delay\_queueautomatic

(Default value: 10)

Retention period (in days) for “bad” messages in automatic spool (as specified by `queueautomatic`). Sympa keeps messages rejected for various reasons (badly formatted, looping, etc.) in this directory, with a name prefixed with `BAD`. This configuration variable controls the number of days these messages are kept.

Edit

## sympa.conf parameters

### Internationalization related

#### localedir

(Default value: `/home/sympa/locale`)

The location of multilingual catalog files. Must correspond to `~src/locale/Makefile`.

#### supported\_lang

Example:

```
supported_lang fr,en_US,de,es
```

This parameter lists all supported languages (comma separated) for the user interface. The default value will include all message catalogs but it can be narrowed by the listmaster.

## lang

---

(Default value: en\_US)

This is the default language for Sympa. The message catalog (`.po`, compiled as a `.mo` file) located in the corresponding locale directory will be used.

## web\_recode\_to

---

(OBSOLETE)

All web pages now use UTF-8 charset

## filesystem\_encoding

---

OBSOLETE

Now all files (including configuration files, templates, authorization scenarios,...) must use UTF-8 charset.

## Bounce related

---

### verp\_rate

---

(Default value: 0%)

See VERP for more information on VERP in Sympa.

When `verp_rate` is null, VERP is not used; if `verp_rate` is 100%, VERP is always in use.

VERP requires plussed aliases to be supported and the `bounce+*` alias to be installed.

### welcome\_return\_path

---

(Default value: owner)

If set to string unique, Sympa enables VERP for welcome messages and bounce processing will remove the subscription if a bounce is received for the welcome message. This prevents to add bad address in the subscriber list.

### remind\_return\_path

---

(Default value: owner)

Like `welcome_return_path`, but relates to the remind message.

## return\_path\_suffix

---

(Default value: -owner)

This defines the suffix that is appended to the list name to build the return-path of messages sent to the lists. This is the address that will receive all non delivery reports (also called bounces).

## expire\_bounce\_task

---

(Default value: daily)

This parameter tells what task will be used by `task_manager.pl` to perform bounce expiration. This task resets bouncing information for addresses not bouncing in the last 10 days after the latest message distribution.

## purge\_orphan\_bounces\_task

---

(Default value: Monthly)

This parameter tells what task will be used by `task_manager.pl` to perform bounce cleaning. This task deletes bounce archive for unsubscribed users.

## eval\_bouncers\_task

---

(Default value: daily)

The task `eval_bouncers` evaluates all bouncing users for all lists, and fill the field `bounce_score_suscriber` in table `suscriber_table` with a score. This score allows the auto-management of bouncing users.

## process\_bouncers\_task

---

(Default value: monthly)

The task `process_bouncers` executes configured actions on bouncing users, according to their score. The association between score and actions has to be done in List configuration. This parameter defines the frequency of execution for this task.

## minimum\_bouncing\_count

---

(Default value: 10)

This parameter is for the bounce-score evaluation: the bounce-score is a mark that allows the auto-management of bouncing users. This score is evaluated with, in particular, the number of message bounces received for the user. This parameter sets the minimum number of these messages to allow the bounce-score evaluation for a user.

## minimum\_bouncing\_period

---

(Default value: 10)

Determine the minimum bouncing period for a user to allow his bounce-score evaluation. Like previous parameter, if this value is too low, bounce-score will be 0.

## bounce\_delay

---

(Default value: 0)

Another parameter for the bounce-score evaluation: this one represents the average time (in days) for a bounce to come back to the Sympa server after a post was send to a list. Usually bounces are delivered on the same day as the original message.

## default\_bounce\_level1\_rate

---

(Default value: 45)

This is the default value for `bouncerslevel1 rate` entry (see `bouncers_level1`).

## default\_bounce\_level2\_rate

---

(Default value: 75)

This is the default value for `bouncerslevel2 rate` entry ( see `bouncers_level2`).

## bounce\_email\_prefix

---

(Default value: `bounce`)

The prefix string used to build variable envelope return path (VERP). In the context of VERP enabled, the local part of the address starts with a constant string specified by this parameter. The email is used to collect bounce. Plussed aliases are used in order to introduce the variable part of the email that encodes the subscriber address. This parameter is useful if you want to run more than one Sympa on the same host (a test Sympa for example).

If you change the default value, you must modify the sympy aliases too.

For example, if you set it as:

```
-----  
bounce_email_prefix bounce-test  
-----
```

you must modify the sympa aliases like this:

```
-----  
bounce-test+*: | /home/sympa/bin/queuebounce sympa@my.domain.org  
-----
```

See Robot aliases for all aliases.

## bounce\_warn\_rate

(Default value: 30)

Site default value for bounce. The list owner receives a warning whenever a message is distributed and the number of bounces exceeds this value.

## bounce\_halt\_rate

(Default value: 50)

FOR FUTURE USE

Site default value for bounce. Messages will cease to be distributed if the number of bounces exceeds this value.

## default\_remind\_task

(Default value: 2month)

This parameter defines the default `remind_task` list parameter.

## Tuning

### cache\_list\_config

Format: none | `binary_file` (Default value: none)

If this parameter is set to `binary_file`, then Sympa processes will maintain a binary version of the list config structure on disk (`config.bin` file). This file is bypassed whenever the `config` file changes on disk. Thanks to this method, the startup of Sympa processes is much faster because it saves the time of parsing all config files. The drawback of this method is that the list config cache can live for a long time (not recreated when the Sympa processes restart); the Sympa processes could still use authorization scenario rules or default for list parameters (set in `sympa.conf`) that have changed on disk in the meantime. You can work this problem out by frequently running `sympa.pl --reload_list_config` using the crontab. In the long term, Sympa should update `config.bin` files via the `task_manager`.

You should use list config cache if you are managing a big amount of lists (1000+).

## lock\_method

---

Format: `flock` | `nfs` (Default value: `flock`)

This parameter will tell Sympa how it should perform locks when required (updating DB, updating config file,...). The default method uses the standard `flock` function. Another option is to use NFS locking ; it requires that you install `File::NFSLock` perl module first.

## sympa\_priority

---

(Default value: 1)

Priority applied to Sympa commands while running the spool.

Available since release 2.3.1.

## request\_priority

---

(Default value: 0)

Priority for processing of messages for `mylist-request`, i.e. for owners of the list.

Available since release 2.3.3.

## owner\_priority

---

(Default value: 9)

Priority for processing messages for `mylist-owner` in the spool. This address will receive non-delivery reports (bounces) and should have a low priority.

Available since release 2.3.3.

## default\_list\_priority

---

(Default value: 5)

Default priority for messages if not defined in the list configuration file.

Available since release 2.3.1.

## Database related

---

The following parameters are needed when using a RDBMS, but are otherwise not required.

## update\_db\_field\_types

---

Format:

```
update_db_field_types auto | disabled
```

(Default value: auto)

This parameter defines whether Sympa automatically updates database structure to match the expected datafield types. This feature is only available with MySQL. Note however that since version 5.3b.5, Sympa will not alter DB files that have a bigger size (if `update_db_fields_types` is set to `auto`).

## db\_type

---

Format:

```
db_type mysql | SQLite | Pg | Oracle | Sybase
```

Database management system used (e.g. MySQL, Pg, Oracle)

This corresponds to the PERL DataBase Driver (DBD) name and is therefore case-sensitive.

## db\_name

---

(Default value: sympa)

Name of the database containing user information. If you are using SQLite, then this parameter is the DB file name.

## db\_host

---

Database host name.

## db\_port

---

Database port.

## db\_user

---

User with read access to the database.

## db\_passwd

---

Password for `db_user`.

## db\_timeout

---

This parameter is used for SQLite only.

## db\_options

---

If these options are defined, they will be appended to the database connect string.

Example for MySQL:

```
db_options      mysql_read_default_file=/home/joe/my.cnf;mysql_socket=tmp/mysql.sock-test
```

Check the related DBD documentation to learn about the available options.

## db\_env

---

Gives a list of environment variables to set before database connection. This is a ‘;’ separated list of variable assignments.

Example for Oracle:

```
db_env  ORACLE_TERM=vt100;ORACLE_HOME=/var/hote/oracle/7.3.4
```

## db\_additional\_subscriber\_fields

---

If your `subscriber_table` database table has more fields than required by Sympa (because other programs access this table), you can make Sympa recognize these fields. You will then be able to use them from within mail/web templates and authorization scenarios (as `[subscriber→field]`). These fields will also appear in the list members review page and will be editable by the list owner. This parameter is a comma-separated list.

Example:

```
db_additional_subscriber_fields      billing_delay,subscription_expiration
```

## db\_additional\_user\_fields

---

If your `user_table` database table has more fields than required by Sympa (because other programs access this table), you can make Sympa recognize these fields. You will then be able to use them from within mail/web templates (as `[user→field]`). This parameter is a comma-separated list.

Example:

```
db_additional_user_fields      address,gender
```

## purge\_user\_table\_task

---

This parameter refers to the name of the task (Example: `monthly`) that will be regularly run by the `task_manager.pl` to remove entries in the `user_table` table that have no corresponding entries in the `subscriber_table` table.

## Loop prevention

---

The following define your loop prevention policy for commands (see Loop detection).

### loop\_command\_max

---

(Default value: 200)

The maximum number of command reports sent to an email address. When it is reached, messages are stored with the BAD prefix, and reports are no longer sent.

### loop\_command\_sampling\_delay

---

(Default value: 3600)

This parameter defines the delay in seconds before decrementing the counter of reports sent to an email address.

### loop\_command\_decrease\_factor

---

(Default value: 0.5)

The decrementation factor (from 0 to 1), used to determine the new report counter after expiration of the delay.

### loop\_prevention\_regex

---

(Default value: `mailer-daemon|sympa|listserv|majordomo|smartlist|mailman`)

This regular expression is applied to message sender addresses. If the sender address matches the regular expression, then the message is rejected. The goal of this parameter is to prevent loops between Sympa and other robots.

## S/MIME configuration

---

Sympa can optionally check and use S/MIME signatures for security purposes. In this case, the three first following parameters must be set by the listmaster (see Configuration in `sympa.conf`). The two others are optional.

### openssl

---

The path for the OpenSSL binary file.

## capath

---

The directory path use by OpenSSL for trusted CA certificates.

A directory of trusted certificates. The certificates should have names of the form `hash.0` or have symbolic links of this form to them (`hash` is the hashed certificate subject name: see the `-hash` option of the OpenSSL `x509` utility). This directory should be the same as the directory `SSLCACertificatePath` specified for the `mod_ssl` module for Apache.

## cafile

---

This parameter sets the all-in-one file where you can assemble the Certificates of Certification Authorities (CA) whose clients you deal with. These are used for Client Authentication. Such a file is simply the concatenation of the various PEM-encoded Certificate files, in order of preference. This can be used alternatively and/or additionally to `capath`.

## key\_passwd

---

The password for list private key encryption. If not defined, Sympa assumes that list private keys are not encrypted.

## chk\_cert\_expiration\_task

---

States the model version used to create the task, which regularly checks the certificate expiration dates and warns users whose certificate have expired or are going to. To know more about tasks, see Tasks.

## crl\_update\_task

---

Specifies the model version used to create the task which regularly updates the certificate revocation lists.

## Antivirus plug-in

---

Sympa can optionally check incoming messages before delivering them, using an external antivirus solution. You must then set two parameters.

## antivirus\_path

---

The path to your favorite antivirus binary file (including the binary file).

Example:

```
antivirus_path      /usr/local/bin/uvscan
```

## antivirus\_args

---

The arguments used by the antivirus software to look for viruses. You must set them so as to get the virus name. You should use, if available, the `unzip` option and check all extensions.

Example with `uvscan`:

```
antivirus_args      --summary --secure
```

Example with `fsav`:

```
antivirus_args      --dumb --archive
```

Example with `AVP`:

```
antivirus_path      /opt/AVP/kavscanner
antivirus_args      -Y -O- -MP -I0
```

Example with `Sophos`:

```
antivirus_path      /usr/local/bin/sweep
antivirus_args      -nc -nb -ss -archive
```

Example with `Clam`:

```
antivirus_path      /usr/local/bin/clamscan
antivirus_args      --stdout
```

## antivirus\_notify

---

sender | nobody

(Default value: sender)

This parameter defines whether Sympa should notify the email sender when a virus has been detected.

Edit

## Sympa and its database

---

Sympa requires a RDBMS to run. Currently you can use one of the following RDBMS: MySQL (version 4.1 minimum), SQLite, PostgreSQL, Oracle, Sybase. Interfacing with other RDBMS requires only a few changes in the code, since the API used, DBI [<http://www.symbolstone.org/technology/perl/DBI/>] (DataBase Interface), has DBD (DataBase Drivers) for many RDBMS.

Sympa stores three kinds of information in the database, each in one table:

- user preferences and passwords are stored in the `user_table` table;
- list subscription information is stored in the `subscriber_table` table, along with subscription options. This table also contains the cache for included users (if using `include2` mode);
- list administrative information is stored in the `admin_table` table if using `include2` mode, along with owner

and editor options. This table also contains the cache for included owners and editors.

- logs events are stored in the `logs_table` ; list owners can browse the events for their list through the web interface.

## Prerequisites

---

You need to have a DataBase System installed (not necessarily on the same host as Sympa), and the client libraries for that Database installed on the Sympa host; provided, of course, that a PERL DBD (DataBase Driver) is available for the RDBMS you chose! Check the "DBI" Module Availability [<http://www.symbolstone.org/technology/perl/DBI/>].

## Installing PERL modules

---

Sympa will use DBI to communicate with the database system and therefore requires the DBD for your database system. DBI and DBD::YourDB (`Mysql-MySQL-modules` for MySQL) are distributed as CPAN modules. Refer to [Installing PERL and CPAN modules](#) for installation details of these modules.

## Creating a Sympa DataBase

---

### Database structure

---

The Sympa database structure is slightly different from the structure of a `subscribers` file. A `subscribers` file is a text file based on paragraphs (similar to the `config` file); each paragraph completely describes a subscriber. If somebody is subscribed to two lists, he/she will appear in both `subscribers` files.

The DataBase distinguishes between information relating to a person (email, real name, password) and his/her subscription options (list concerned, date of subscription, delivery mode, visibility option). This results in a separation of the data into two tables : the `user_table` and the `subscriber_table`, linked by a user/subscriber email.

The table concerning owners and editors, the `admin_table`, is built on the same model as the `subscriber_table` but is used only in `include2` mode. It contains owner and editor options (list concerned, administrative role, date of "subscription", delivery mode, private information, gecos and profile option for owners).

### Database creation

---

The `create_db` script below will create the Sympa database for you. You can find it in the `script/` directory of the distribution (currently scripts are available for MySQL, SQLite, PostgreSQL, Oracle and Sybase).

- MySQL database creation script:

```
## MySQL Database creation script
CREATE DATABASE sympa;
## Connect to DB
\r sympa
CREATE TABLE user_table (
    email_user          varchar (100) NOT NULL,
```

```

gecos_user          varchar (150),
password_user       varchar (40),
cookie_delay_user   int,
lang_user           varchar (10),
attributes_user     varchar(255),
PRIMARY KEY (email_user)
);
CREATE TABLE subscriber_table (
list_subscriber     varchar (50) NOT NULL,
user_subscriber     varchar (100) NOT NULL,
robot_subscriber    varchar (80) NOT NULL,
date_subscriber     datetime NOT NULL,
update_subscriber   datetime,
visibility_subscriber varchar (20),
reception_subscriber varchar (20),
topics_subscriber   varchar (200),
bounce_subscriber   varchar (35),
bounce_score_subscriber smallint (6),
bounce_address_subscriber varchar (100),
comment_subscriber  varchar (150),
subscribed_subscriber int(1),
included_subscriber int(1),
include_sources_subscriber varchar(50),
PRIMARY KEY (list_subscriber, user_subscriber, robot_subscriber),
INDEX (user_subscriber, list_subscriber, robot_subscriber)
);
CREATE TABLE admin_table (
list_admin          varchar(50) NOT NULL,
user_admin          varchar(100) NOT NULL,
robot_admin         varchar(80) NOT NULL,
role_admin          enum('listmaster','owner','editor') NOT NULL,
date_admin          datetime NOT NULL,
update_admin        datetime,
reception_admin     varchar(20),
comment_admin       varchar(150),
subscribed_admin    int(1),
included_admin      int(1),
include_sources_admin varchar(50),
info_admin          varchar(150),
profile_admin       enum('privileged','normal'),
PRIMARY KEY (list_admin, user_admin, robot_admin, role_admin),
INDEX (list_admin, user_admin, robot_admin, role_admin)
);
CREATE TABLE netidmap_table (
netid_netidmap      varchar (100) NOT NULL,
serviceid_netidmap varchar (100) NOT NULL,
robot_netidmap      varchar (80) NOT NULL,
email_netidmap      varchar (100),
PRIMARY KEY (netid_netidmap, serviceid_netidmap, robot_netidmap)
);
CREATE TABLE logs_table (
id_logs             bigint(20) NOT NULL,
date_logs           int(11) NOT NULL,
robot_logs          varchar(80),
list_logs           varchar(50),
action_logs         varchar(50) NOT NULL,
parameters_logs     varchar(100),
target_email_logs   varchar(100),
user_email_logs     varchar(100),
msg_id_logs         varchar(255),
status_logs         varchar(10) NOT NULL,
error_type_logs     varchar(150),
client_logs         varchar(100),
daemon_logs         varchar(10) NOT NULL,
PRIMARY KEY (id_logs)
);

```

■ SQLiteL database creation script:

```

CREATE TABLE user_table (
    email_user          varchar (100) NOT NULL,
    gecos_user          varchar (150),
    password_user       varchar (40),
    cookie_delay_user   integer,
    lang_user           varchar (10),
    attributes_user     varchar(255),
    PRIMARY KEY (email_user)
);
CREATE TABLE subscriber_table (
    list_subscriber     varchar (50) NOT NULL,
    user_subscriber     varchar (100) NOT NULL,
    robot_subscriber    varchar (80) NOT NULL,
    date_subscriber     timestamp NOT NULL,
    update_subscriber   timestamp,
    visibility_subscriber varchar (20),
    reception_subscriber varchar (20),
    topics_subscriber   varchar (200),
    bounce_subscriber   varchar (35),
    bounce_address_subscriber varchar (100),
    comment_subscriber  varchar (150),
    subscribed_subscriber boolean,
    included_subscriber boolean,
    include_sources_subscriber varchar(50),
    bounce_score_subscriber integer,
    PRIMARY KEY (list_subscriber, user_subscriber, robot_subscriber)
);
CREATE INDEX subscriber_idx ON subscriber_table (user_subscriber,list_subscriber,robot_subscriber);
CREATE TABLE admin_table (
    list_admin          varchar(50) NOT NULL,
    user_admin          varchar(100) NOT NULL,
    robot_admin         varchar(80) NOT NULL,
    role_admin          varchar(15) NOT NULL,
    date_admin          timestamp NOT NULL,
    update_admin        timestamp,
    reception_admin     varchar(20),
    comment_admin       varchar(150),
    subscribed_admin    boolean,
    included_admin      boolean,
    include_sources_admin varchar(50),
    info_admin          varchar(150),
    profile_admin       varchar(15),
    PRIMARY KEY (list_admin, user_admin, robot_admin, role_admin)
);
CREATE INDEX admin_idx ON admin_table(list_admin, user_admin, robot_admin, role_admin);
CREATE TABLE netidmap_table (
    netid_netidmap      varchar (100) NOT NULL,
    serviceid_netidmap  varchar (100) NOT NULL,
    robot_netidmap      varchar (80) NOT NULL,
    email_netidmap      varchar (100),
    PRIMARY KEY (netid_netidmap, serviceid_netidmap, robot_netidmap)
);
CREATE INDEX netidmap_idx ON netidmap_table(netid_netidmap, serviceid_netidmap, robot_netidmap);
CREATE TABLE logs_table (
    id_logs             integer NOT NULL,
    date_logs           integer NOT NULL,
    robot_logs          varchar(80),
    list_logs           varchar(50),
    action_logs         varchar(50) NOT NULL,
    parameters_logs     varchar(100),
    target_email_logs   varchar(100),
    user_email_logs     varchar(100),
    msg_id_logs         varchar(255),
    status_logs         varchar(10) NOT NULL,
    error_type_logs     varchar(150),
    client_logs         varchar(100),
    daemon_logs         varchar(10) NOT NULL,
    PRIMARY KEY (id_logs)
);
CREATE INDEX logs_idx ON logs_table(id_logs);

```

## ■ PostgreSQL database creation script:

```
-- PostgreSQL Database creation script
CREATE DATABASE sympy;
-- Connect to DB
\connect sympy
DROP TABLE user_table;
CREATE TABLE user_table (
    email_user          varchar (100) NOT NULL,
    gecos_user          varchar (150),
    cookie_delay_user   int4,
    password_user       varchar (40),
    lang_user           varchar (10),
    attributes_user     varchar (255),
    CONSTRAINT ind_user PRIMARY KEY (email_user)
);
DROP TABLE subscriber_table;
CREATE TABLE subscriber_table (
    list_subscriber     varchar (50) NOT NULL,
    user_subscriber     varchar (100) NOT NULL,
    robot_subscriber    varchar (80) NOT NULL,
    date_subscriber     timestamp with time zone NOT NULL,
    update_subscriber   timestamp with time zone,
    visibility_subscriber varchar (20),
    reception_subscriber varchar (20),
    topics_subscriber   varchar (200),
    bounce_subscriber   varchar (35),
    bounce_score_subscriber int4,
    bounce_address_subscriber varchar (100),
    comment_subscriber  varchar (150),
    subscribed_subscriber smallint,
    included_subscriber smallint,
    include_sources_subscriber varchar(50),
    CONSTRAINT ind_subscriber PRIMARY KEY (list_subscriber, user_subscriber, robot_subscriber)
);
CREATE INDEX subscriber_idx ON subscriber_table (user_subscriber,list_subscriber,robot_subscriber);
DROP TABLE admin_table;
CREATE TABLE admin_table (
    list_admin          varchar(50) NOT NULL,
    user_admin          varchar(100) NOT NULL,
    robot_admin         varchar(80) NOT NULL,
    role_admin          varchar(15) NOT NULL,
    date_admin          timestamp with time zone NOT NULL,
    update_admin        timestamp with time zone,
    reception_admin     varchar(20),
    comment_admin       varchar(150),
    subscribed_admin    smallint,
    included_admin      smallint,
    include_sources_admin varchar(50),
    info_admin          varchar(150),
    profile_admin       varchar(15),
    CONSTRAINT ind_admin PRIMARY KEY (list_admin, user_admin, robot_admin, role_admin)
);
CREATE INDEX admin_idx ON admin_table(list_admin, user_admin,robot_admin, role_admin);
DROP TABLE netidmap_table;
CREATE TABLE netidmap_table (
    netid_netidmap      varchar (100) NOT NULL,
    serviceid_netidmap  varchar (100) NOT NULL,
    robot_netidmap      varchar (80) NOT NULL,
    email_netidmap      varchar (100),
    CONSTRAINT ind_netidmap PRIMARY KEY (netid_netidmap, serviceid_netidmap, robot_netidmap)
);
CREATE INDEX netidmap_idx ON netidmap_table(netid_netidmap, serviceid_netidmap, robot_netidmap);
DROP TABLE logs_table;
CREATE TABLE logs_table (
    id_logs             bigint NOT NULL,
    date_logs           int4 NOT NULL,
    robot_logs          varchar (80),
    list_logs           varchar (50),
```

```

    action_logs          varchar (50) NOT NULL,
    parameters_logs     varchar (100),
    target_email_logs   varchar (100),
    user_email_logs     varchar (100),
    msg_id_logs         varchar (255),
    status_logs         varchar (10) NOT NULL,
    error_type_logs     varchar (150),
    client_logs         varchar (100),
    daemon_logs         varchar (10) NOT NULL,
    CONSTRAINT ind_logs PRIMARY KEY (id_logs)
);
CREATE      INDEX logs_idx ON logs_table(id_logs);

```

## ■ Sybase database creation script:

```

/* Sybase Database creation script 2.5.2 */
/* Thierry Charles <tcharles@electron-libre.com> */
/* 15/06/01 : extend password_user */
/* sympa database must have been created */
/* eg: create database sympa on your_device_data=10 log on your_device_log=4 */
use sympa
go
create table user_table
(
    email_user          varchar(100)          not null,
    gecos_user          varchar(150)          null ,
    password_user       varchar(40)           null ,
    cookie_delay_user   numeric                null ,
    lang_user           varchar(10)           null ,
    attributes_user     varchar(255)          null ,
    constraint ind_user primary key (email_user)
)
go
create index email_user_fk on user_table (email_user)
go
create table subscriber_table
(
    list_subscriber     varchar(50)           not null,
    user_subscriber     varchar(100)          not null,
    robot_subscriber    varchar(80)           not null,
    date_subscriber     datetime              not null,
    update_subscriber   datetime              null ,
    visibility_subscriber varchar(20)         null ,
    reception_subscriber varchar(20)         null ,
    topics_subscriber   varchar(200)          null ,
    bounce_subscriber   varchar(35)           null ,
    bounce_score_subscriber numeric           null ,
    comment_subscriber  varchar(150)          null ,
    subscribed_subscriber numeric            null ,
    included_subscriber numeric              null ,
    include_sources_subscriber varchar(50)     null ,
    constraint ind_subscriber primary key (list_subscriber, user_subscriber, robot_subscriber)
)
go
create index list_subscriber_fk on subscriber_table (list_subscriber)
go
create index user_subscriber_fk on subscriber_table (user_subscriber)
go
create index robot_subscriber_fk on subscriber_table (robot_subscriber)
go
create table admin_table
(
    list_admin          varchar(50)           not null,
    user_admin          varchar(100)          not null,
    robot_admin         varchar(80)           not null,
    role_admin          varchar(15)           not null,
    date_admin          datetime              not null,
    update_admin        datetime              null ,
    reception_admin     varchar(20)           null ,

```

```

        comment_admin          varchar(150)      null,
        subscribed_admin       numeric              null,
        included_admin         numeric              null,
        include_sources_admin   varchar(50)        null,
        info_admin              varchar(150)        null,
        profile_admin           varchar(15)         null,
        constraint ind_admin primary key (list_admin, user_admin, robot_admin, role_admin)
    )
go
create index list_admin_fk on admin_table (list_admin)
go
create index user_admin_fk on admin_table (user_admin)
go
create index robot_admin_fk on admin_table (robot_admin)
go
create index role_admin_fk on admin_table (role_admin)
go
create table netidmap_table
(
    netid_netidmap             varchar (100) NOT NULL,
    serviceid_netidmap         varchar (100) NOT NULL,
    robot_netidmap             varchar (80) NOT NULL,
    email_netidmap             varchar (100),
    constraint ind_netidmap primary key (netid_netidmap, serviceid_netidmap, robot_netidmap)
)
go
create index netid_netidmap_fk on netidmap_table (netid_netidmap)
go
create index serviceid_netidmap_fk on netidmap_table (serviceid_netidmap)
go
create index robot_netidmap_fk on netidmap_table (robot_netidmap)
go
CREATE TABLE logs_table (
    id_logs                    numeric NOT NULL,
    date_logs                   numeric NOT NULL,
    robot_logs                  varchar(80),
    list_logs                   varchar(50),
    action_logs                 varchar(50) NOT NULL,
    parameters_logs            varchar(100),
    target_email_logs           varchar(100),
    user_email_logs             varchar(100),
    msg_id_logs                 varchar(255),
    status_logs                 varchar(10) NOT NULL,
    error_type_logs             varchar(150),
    client_logs                 varchar(100),
    daemon_logs                 varchar(10) NOT NULL,
    constraint ind_logs primary key (id_logs)
)
go
create index id_logs_fk on logs_table (id_logs)
go

```

#### ■ Oracle database creation script:

```

## Oracle Database creation script
## Fabien Marquois <fmarquoi@univ-lr.fr>
/Bases/oracle/product/7.3.4.1/bin/sqlplus loginsystem/passwdoracle <<-!
create user SYMPA identified by SYMPA default tablespace TABLESP
temporary tablespace TEMP;
grant create session to SYMPA;
grant create table to SYMPA;
grant create synonym to SYMPA;
grant create view to SYMPA;
grant execute any procedure to SYMPA;
grant select any table to SYMPA;
grant select any sequence to SYMPA;
grant resource to SYMPA;
!
/Bases/oracle/product/7.3.4.1/bin/sqlplus SYMPA/SYMPA <<-!

```

```

CREATE TABLE user_table (
    email_user          varchar2(100) NOT NULL,
    gecos_user          varchar2(150),
    password_user       varchar2(40),
    cookie_delay_user   number,
    lang_user           varchar2(10),
    attributes_user     varchar2(500),
    CONSTRAINT ind_user PRIMARY KEY (email_user)
);
CREATE TABLE subscriber_table (
    list_subscriber     varchar2(50) NOT NULL,
    user_subscriber     varchar2(100) NOT NULL,
    robot_subscriber    varchar2(80) NOT NULL,
    date_subscriber     date NOT NULL,
    update_subscriber   date,
    visibility_subscriber varchar2(20),
    reception_subscriber varchar2(20),
    topics_subscriber   varchar2(200),
    bounce_subscriber   varchar2(35),
    bounce_score_subscriber number,
    bounce_address_subscriber varchar2(100),
    comment_subscriber  varchar2(150),
    subscribed_subscriber number NULL    constraint cons_subscribed_subscriber CHECK (subscribed_subscriber < 0),
    included_subscriber number NULL    constraint cons_included_subscriber CHECK (included_subscriber < 0),
    include_sources_subscriber varchar2(50),
    CONSTRAINT ind_subscriber PRIMARY KEY (list_subscriber,user_subscriber,robot_subscriber)
);
CREATE TABLE admin_table (
    list_admin          varchar2(50) NOT NULL,
    user_admin          varchar2(100) NOT NULL,
    robot_admin         varchar2(80) NOT NULL,
    role_admin          varchar2(20) NOT NULL,
    date_admin          date NOT NULL,
    update_admin        date,
    reception_admin     varchar2(20),
    comment_admin       varchar2(150),
    subscribed_admin     number NULL    constraint cons_subscribed_admin CHECK (subscribed_admin in (0,1)),
    included_admin      number NULL    constraint cons_included_admin CHECK (included_admin in (0,1)),
    include_sources_admin varchar2(50),
    info_admin          varchar2(150),
    profile_admin       varchar2(20),
    CONSTRAINT ind_admin PRIMARY KEY (list_admin,user_admin,robot_admin,role_admin)
);
CREATE TABLE netidmap_table (
    netid_netidmap      varchar2(100) NOT NULL,
    serviceid_netidmap  varchar2(100) NOT NULL,
    robot_netidmap      varchar2(80) NOT NULL,
    email_netidmap      varchar2(100),
    CONSTRAINT ind_netidmap PRIMARY KEY (netid_netidmap, serviceid_netidmap, robot_netidmap)
);
CREATE TABLE logs_table (
    id_logs             number NOT NULL,
    date_logs           number NOT NULL,
    robot_logs          varchar2(80),
    list_logs           varchar2(50),
    action_logs         varchar2(50) NOT NULL,
    parameters_logs     varchar2(100),
    target_email_logs   varchar2(100),
    user_email_logs     varchar2(100),
    msg_id_logs         varchar2(255),
    status_logs         varchar2(10) NOT NULL,
    error_type_logs     varchar2(150),
    client_logs         varchar2(100),
    daemon_logs         varchar2(10) NOT NULL,
    CONSTRAINT ind_admin PRIMARY KEY (id_logs)
);
!

```

You can execute the script using a simple SQL shell such as mysql, psql or sqlplus.

Example:

```
# mysql < create_db.mysql
```

## Setting database privileges

---

We strongly recommend that you restrict access to the Sympa database. You will then set `db_user` and `db_passwd` in `sympa.conf`.

With MySQL:

```
grant all on sympa.* to sympa@localhost identified by 'your_password';
flush privileges;
```

## Importing subscriber data

---

### Importing data from a text file

---

You can import subscribers data into the database from a text file having one entry per line: the first field is an email address, the second (optional) field is the free form name. Fields are space-separated.

Example:

```
## Data to be imported
## email      gecos
john.steward@some.company.com      John - accountant
mary.blacksmith@another.company.com  Mary - secretary
```

To import data into the database:

```
cat /tmp/my_import_file | sympa.pl --import=my_list
```

(see [sympa.pl](#)).

## Importing data from subscribers files

---

If a mailing list was previously set up to store subscribers into a `subscribers` file (the default mode in versions older than 2.2b), you can load subscriber data into the Sympa database. The easiest way is to edit the list configuration using `WWSympa` (this requires `listmaster` privileges) and change the data source from `file` to `database`; subscriber data will be loaded into the database at the same time.

If the `subscribers` file is large, a timeout may occur during the FastCGI execution (note that you can set a longer timeout with the `-idle-timeout` option of the `FastCgiServer` Apache configuration directive). In this case, or if you have not installed `WWSympa`, you should use the `load_subscribers.pl` script.

## Management of the include cache

---

You may dynamically add a list of subscribers, editors or owners to a list with Sympa's `include2` user data source. Sympa is able to query multiple data sources (RDBMS, LDAP directory, flat file, local list, remote list) to build a mailing list.

Sympa used to manage the cache of such *included* subscribers in a DB File (`include` mode), but now stores subscribers, editors and owners in the database (`include2` mode). These changes brought the following advantages:

- Sympa processes are smaller when dealing with big mailing lists (in `include` mode).
- Cache update is now performed regularly by a dedicated process, the task manager.
- Mixed lists (`included` + `subscribed` users) can now be created.
- Sympa can now provide delivery options for *included* members.
- Bounce information can be managed for *included* members.
- Sympa keeps track of the data sources of a member (available on the web REVIEW page).
- *Included* members can also subscribe to the list. It allows them to remain in the list in case they might not be included anymore.

## Extending database table format

---

You can easily add other fields to the three tables, they will not disturb Sympa because it lists explicitly the field it expects in SELECT queries.

Moreover, you can access these database fields from within Sympa (in templates), as far as you list these additional fields in `sympa.conf` (see [db additional subscriber fields](#) and [db additional user fields](#)).

## Sympa configuration

---

To store subscriber information in your newly created database, you first need to tell Sympa what kind of database to work with, then you must configure your list to access the database.

You'll need to tell Sympa where is located its database through the [related sympa.conf parameters](#) : `db_type`, `db_name`, `db_host`, `db_user`, `db_passwd`.

If you are interfacing Sympa with an Oracle database, note that :

1. the `db_name` corresponds to the Oracle SID.
2. you'll need to set the `ORACLE_HOME` environment variable through the [db env sympa.conf parameter](#) All your lists are now configured to use the database, unless you set the list parameter `user_data_source` to `file` or `include`. Sympa will now extract and store user information for this list using the database instead of the `subscribers` file. Note however that subscriber information is dumped to `subscribers.db.dump` at every shutdown, to allow a manual rescue restart (by renaming `subscribers.db.dump` to `subscribers` and changing the `user_data_source` parameter), in case the database were to become inaccessible.

Edit

## WWSympa, Sympa's web interface

---

*WWSympa* is Sympa's web interface.

### Organization

---

*WWSympa* is fully integrated with Sympa. It uses `sympa.conf` and Sympa's libraries. The default Sympa installation will also install *WWSympa*.

Every single piece of HTML in *WWSympa* is generated by the CGI code using template files (See [Template file format](#)). This makes internationalization of pages, as well as per-site customization, easier.

The code consists of one single PERL CGI script, `wwsympa.fcgi`. To enhance performances you can configure *WWSympa* to use [FastCGI](#); the CGI will be persistent in memory.

All data will be accessed through the CGI, including web archives. This is required to allow the authentication scheme to be applied systematically.

Authentication is based on passwords stored in the database table `user_table`; if the appropriate `Crypt::CipherSaber` is installed, passwords are encrypted in the database using reversible encryption based on RC4. Otherwise, they are stored in clear text. In both cases, reminding of passwords is possible.

To keep track of authentication information, *WWSympa* uses HTTP cookies stored on the client side. The HTTP cookie only indicates that a specified email address has been authenticated; permissions are evaluated when an action is requested.

The same web interface is used by the listmaster, list owners, subscribers and others. Depending on permissions, the same URL may generate a different view.

*WWSympa*'s main loop algorithm is roughly the following:

1. check authentication information returned by the HTTP cookie;
2. evaluate user's permissions for the requested action;
3. process the requested action;
4. set up variables resulting from the action;
5. parse the HTML template files.

### Web server setup

---

#### wwsympa.fcgi access permissions

---

Because Sympa and *WWSympa* share a lot of files, `wwsympa.fcgi` must run with the same uid/gid as `archived.pl`, `bounced.pl` and `sympa.pl`. There are different ways to achieve this:

- `SetuidPerl`: this is the default method but might be insecure. If you don't set the `-enable_secure` configuration option, `wwsympa.fcgi` is installed with the `SetUID` bit set. On most systems, you will need to install the `suidperl`

package;

- Sudo: use `sudo` to run `wwsympa.fcgi` as user `sympa`. Your Apache configuration should use `wwsympa_sudo_wrapper.pl` instead of `wwsympa.fcgi`. You should edit your `/etc/sudoers` file (with `visudo` command) as follows:

```
apache ALL = (sympa) NOPASSWD: /home/sympa/bin/wwsympa.fcgi
```

You should also check that the **requiretty** option is commented in the `sudoers` configuration file :

```
#Defaults    requiretty
```

- Dedicated Apache server: run a dedicated Apache server with `sympa.sympa` as `uid.gid` (the Apache default is `apache.apache`);
- Apache suExec: use an Apache virtual host with `sympa.sympa` as `uid.gid`; Apache needs to be compiled with `suexec`. Be aware that the Apache `suexec` usually define a lowest UID/GID allowed to be a target user for `suEXEC`. For most systems, including binaries distribution of Apache, the default value `100` is common. So Sympa UID (and Sympa GID) must be higher than `100` or `suexec` must be tuned in order to allow lower UID/GID. Check <http://httpd.apache.org/docs/suexec.html#install> [<http://httpd.apache.org/docs/suexec.html#install>] for details. The User and Group directive have to be set before the `FastCgiServer` directive is encountered;
- C wrapper: otherwise, you can overcome restrictions on the execution of `suid` scripts by using a short C program, owned by Sympa and with the `suid` bit set, to start `wwsympa.fcgi`. Here is an example (with no guarantee attached):

```
#include <unistd.h>
#define WWSYMPA '/home/sympa/bin/wwsympa.fcgi'
int main(int argn, char **argv, char **envp) {
    argv[0] = WWSYMPA;
    execve(WWSYMPA, argv, envp);
}
```

## Installing `wwsympa.fcgi` in your Apache server

---

You first need to set an alias to the directory where Sympa stores static contents (CSS, member pictures, documentation) directly delivered by Apache.

Example:

```
Alias /static-sympa /home/sympa/static_content
```

If you chose to run `wwsympa.fcgi` as a simple CGI, you simply need to script alias it.

Example:

```
ScriptAlias /sympa /home/sympa/bin/wwsympa.fcgi
```

Running `FastCGI` will provide much faster responses from your server and reduce load (to understand why, read <http://www.fastcgi.com/devkit/doc/fcgi-perf.htm> [<http://www.fastcgi.com/devkit/doc/fcgi-perf.htm>]).

If you are using `mod_fcgid` Apache module :

```
IPCCCommTimeout 120
MaxProcessCount 2

<Location /sympa>
  SetHandler fcgid-script
</Location>

ScriptAlias /sympa /home/sympa/bin/wwsympa.fcgi
```

If you are using *mod\_fastcgi* Apache module :

```
FastCgiServer /home/sympa/bin/wwsympa.fcgi -processes 2
<Location /sympa>
  SetHandler fastcgi-script
</Location>

ScriptAlias /sympa /home/sympa/bin/wwsympa.fcgi
```

If you are using `sudo` (see [wwsympa.fcgi access permissions](#)), then replace `wwsympa.fcgi` calls with `wwsympa_sudo_wrapper.pl`.

If you run virtual hosts, then each `FastCgiServer(s)` can serve as multiple hosts. Therefore you need to define it in the common section of your Apache configuration file.

## Using FastCGI

---

FastCGI [<http://www.fastcgi.com/>] is an extension to CGI, that provides persistency for CGI programs. It is extremely useful with *WWSympa*, since source code interpretation and all initialisation tasks are performed only once when `wwsympa.fcgi` processes start. These processes then work as a servlet/daemon, endlessly waiting for client requests.

*WWSympa* can also work without FastCGI, (check the [use fast cgi - 1](#) configuration parameter), but with poor performances.

To run *WWSympa* with FastCGI, you need to install:

- The FCGI Perl module (see [installing perl and cpan modules](#))
- An Apache module that provides FastCGI features. You can choose between 2 such implementations :
  - `mod_fastcgi` [<http://www.fastcgi.com/>], the *historical* one. Note that it was not extended to work with Apache 2. You can however apply the patch provided here [<http://hack.emilykwan.com/node/95>].
  - `mod_fcgid` [<http://fastcgi.coremail.cn/>], an alternate implementation. The main difference between this module and `mod_fastcgi` is that `fastcgi` scripts are not launched at Apache startup, but when the first client request happens.

## wwsympa.conf parameters

---

### arc\_path

---

(Default value: `/home/httpd/html/arc`)

Where to store HTML archives. This parameter is used by the `archived.pl` daemon. It is a good idea to install the

archive outside the web hierarchy to prevent possible backdoors in the access control powered by *WWSympa*. However, if Apache is configured with a chroot, you may have to install the archive in the Apache directory tree.

## archive\_default\_index thrd - mail

---

(Default value: `thrd`)

The default index organization when entering the web archive: either threaded or in chronological order.

## archived\_pidfile

---

(Default value: `archived.pid`)

The file containing the PID of `archived.pl`.

## bounce\_path

---

(Default value: `/var/bounce`)

Root directory for storing bounces (non-delivery reports). This parameter is mainly used by the `bounced.pl` daemon.

## bounced\_pidfile

---

(Default value: `bounced.pid`)

The file containing the PID of `bounced.pl`.

## cookie\_expire

---

(Default value: `0`)

Lifetime (in minutes) of HTTP cookies. This is the default value when not set explicitly by users.

## cookie\_domain

---

(Default value: `localhost`)

Domain for the HTTP cookies. If beginning with a dot (`.`), the cookie is available within the specified internet domain. Otherwise, for the specified host. Example:

```
-----  
cookie_domain cru.fr  
cookie is available for host 'cru.fr'  
  
cookie_domain .cru.fr  
cookie is available for any host within 'cru.fr' domain  
-----
```

The only reason for replacing the default value would be where *WWSympa*'s authentication process is shared with an application running on another host.

## default\_home

---

(Default value: `home`)

Organization of the *WWSympa* home page. If you have only a few lists, the default value `home` (presenting a list of lists organized by topic) should be replaced by `lists` (a simple alphabetical list of lists).

## icons\_url

---

(Default value: `/icons`)

URL of *WWSympa*'s icon directory.

## log\_facility

---

*WWSympa* will log using this facility. Defaults to Sympa's syslog facility. Configure your syslog according to this parameter.

## mhonarc

---

(Default value: `/usr/bin/mhonarc`)

Path to the (superb) MhOnArc program [<http://www.oac.uci.edu/indiv/ehood/mhonarc.html>]. Required for the HTML archive.

## htmlarea\_url

---

(Default value: `undefined`)

Relative URL to the (superb) online HTML editor HTMLarea. If you have installed Javascript application you can use it when editing HTML documents in the shared document repository. In order to activate this plugin, the value of this parameter should point to the root directory where HTMLarea is installed. HTMLarea is a free opensource software you can download here: <http://sf.net/projects/itools-htmlarea> [<http://sf.net/projects/itools-htmlarea>]

## password\_case sensitive | insensitive

---

(Default value: `insensitive`)

If set to `insensitive`, *WWSympa*'s password check will be insensitive. This only concerns passwords stored in the Sympa database, not the ones in LDAP.

**Be careful:** in previous 3.xx versions of Sympa, passwords were lowercased before database insertion. Therefore changing to case-sensitive password checking could bring you some password checking problems.

## title

---

(Default value: `Mailing List Service`)

The name of your mailing list service. It will appear in the Title section of *WWSympa*.

## use\_fast\_cgi 0|1

---

(Default value: 1)

Choice of whether or not to use FastCGI. On <http://listes.cru.fr> [<http://listes.cru.fr>], using FastCGI increases *WWSympa*'s performance by as much as a factor of 10. Refer to <http://www.fastcgi.com> [<http://www.fastcgi.com>] and the Apache config section of this document for details about FastCGI.

## Database configuration

---

*WWSympa* needs an RDBMS (Relational Database Management System) in order to run. All database access is performed via the Sympa API. Sympa currently interfaces with MySQL [<http://www.mysql.net/>], SQLite [<http://sqlite.org/>], PostgreSQL [<http://www.postgresql.pyrenet.fr/>], Oracle [<http://www.oracle.com/database/>] and Sybase [[http://www.sybase.com/index\\_sybase.html](http://www.sybase.com/index_sybase.html)].

A database is needed to store user passwords and preferences. The database structure is documented in the Sympa documentation; scripts for creating it are also provided with the Sympa distribution (in `script`).

User information (password and preferences) are stored in the `User` table. User passwords stored in the database are encrypted using reversible RC4 encryption controlled with the `cookie` parameter, since *WWSympa* might need to remind users of their passwords. The security of *WWSympa* rests on the security of your database.

## Logging in as listmaster

---

Once Sympa is running, you should log in on the web interface as a privileged user (`listmaster`) to explore the admin interface, create mailing lists, etc.

Multiple email addresses can be declared as listmasters via the `sympa.conf` (or `robot.conf`) `listmaster` configuration parameter (see [sympa.conf parameters](#)). Note that listmasters on the main robot (declared in `sympa.conf`) also have listmaster privileges on virtual hosts, but they will not receive the various mail notifications (list creations, warnings,...) regarding these virtual hosts.

The listmasters should log in with their canonical email address as an identifier (not `listmaster@my.host`). The associated password is not declared in `sympa.conf`; it will be allocated by Sympa when first hitting the `Send me a password` button on the web interface. As for any user, the password can then be modified via the `Preferences` menu.

Note that you must start the `sympa.pl` process with the web interface; it is responsible for delivering mail messages including password reminders.

Edit

## Sympa Internationalization

---

## Catalogs and templates

---

Sympa is designed to allow easy internationalization of its user interface (service mail messages and web interface). All translations for one language are gathered in a single .PO file that can be manipulated by standard GNU gettext tools [<http://www.gnu.org/software/gettext/#TOCintroduction>].

Documentation and resources about software translations : <http://translate.sourceforge.net/doc>  
[<http://translate.sourceforge.net/doc>]

Sympa previously (until Sympa 4.1.x) used the XPG4 message catalogue format. Web and mail templates were language-specific. The new organization provides both a unique file to work on for translators and a standard format supported by many software. Sympa templates refer to translatable strings using the `loc` TT2 filter.

Examples:

```
[%|loc%]User Email[% END %]  
[%|loc(list.name,user.email)%]You have subscribed to list %1 with email address %2[% END %]
```

Sympa had previously been translated into 15 languages more or less completely. We have automatically extracted the translatable strings from previous templates but this process is awkward and is only seen as a bootstrap for translators. Therefore Sympa distribution will not include previous translations until a skilled translator has reviewed and updated the corresponding .PO file.

## Translating Sympa GUI in your language

---

Instructions for translating Sympa are maintained on the Sympa website: <http://www.sympa.org/howtotranslate.html>  
[<http://www.sympa.org/howtotranslate.html>].

## Defining language-specific templates

---

The default Sympa templates are language independant, referring to catalogue entries for translations. When customizing either web or mail templates, you can define different templates for different languages. The template should be located in a `ll_CC` subdirectory of `web_tt2` or `mail_tt2` with the language code.

Example :

```
/web_tt2/home.tt2  
/web_tt2/de_DE/home.tt2  
/web_tt2/fr_FR/home.tt2
```

This mechanism also applies to `comment.tt2` files used by create list templates.

Web templates can also make use of the `locale` variable to make templates multi-lingual:

Example :

```
[% IF locale == 'fr_FR' %]  
Personnalisation  
[% ELSE %]  
Customization
```

## Translating topics titles

---

Topics are defined in a `topics.conf` file. In this file, each entry can be given a title in different languages, see [Topics](#).

## Handling of charsets

---

Until version 5.3, Sympa web pages were using in each language's charset (iso-8859-1 for French, utf-8 for Japanese, ...) whereas every web page now uses utf-8. Sympa also expects every file to be UTF-8 including : configuration files, templates, authorization scenarios, PO files.

Note that the shared documents (see [Shared documents](#)) filenames are Q-encoded to make their storage encoding neutral. This encoding is transparent for end users.

Edit

## Sympa RSS channel

---

This service is provided by *WWSympa* (Sympa's web interface). Here is the root of *WWSympa*'s RSS channel:

(Default value: `http://<host>/wws/rss`)

Example: `https://my.server/wws/rss`

The access control of RSS queries proceed on the same way as *WWSympa* actions referred to. Sympa provides the following RSS features:

- the latest created lists on a robot (`latest_lists`);
- the most active lists on a robot(`active_lists`);
- the latest messages of a list (`active_arc`);
- the latest shared documents of a list (`latest_d_read`).

## latest\_lists

---

This provides the latest created lists.

Example: `http://my.server/wws/rss/latest_lists?for=3&count=6`

This provides the 6 latest created lists for the last 3 days.

Example: `http://my.server/wws/rss/latest_lists/computing?count=6`

This provides the 6 latest created lists with topic `computing`.

Parameters:

- `for`: period of interest (expressed in days). This is a CGI parameter. It is optional but one of the two parameters `for` or `count` is required.

- `count`: maximum number of expected records. This is a CGI parameter. It is optional but one of the two parameters `for` or `count` is required.
- `topic`: the topic is indicated in the path info (see example below with `topic computing`). This parameter is optional.

## active\_lists

---

This provides the most active lists, based on the number of distributed messages (number of messages received).

Example: `http://my.server/wws/rss/active_lists?for=3&count=6`

This provides the 6 most active lists for the last 3 days.

Example: `http://my.server/wws/rss/active_lists/computing?count=6`

This provides the 6 most active lists with topic `computing`.

Parameters:

- `for`: period of interest (expressed in days). This is a CGI parameter. It is optional but one of the two parameters `for` or `count` is required.
- `count`: maximum number of expected records. This is a CGI parameter. It is optional but one of the two parameters `for` or `count` is required.
- `topic` : the topic is indicated in the path info (see example below with `topic computing`). This parameter is optional.

## latest\_arc

---

This provides the latest messages of a list.

Example: `http://my.server/wws/rss/latest_arc/mylist?for=3&count=6`

This provides the 6 latest messages received on the *mylist* list for the last 3 days.

Parameters:

- `list`: the list is indicated in the path info. This parameter is mandatory.
- `for`: period of interest (expressed in days). This is a CGI parameter. It is optional but one of the two parameters `for` or `count` is required.
- `count`: maximum number of expected records. This is a CGI parameter. It is optional but one of the two parameters `for` or `count` is required.

## latest\_d\_read

---

This provides the latest updated and uploaded shared documents of a list.

Example: `http://my.server/wws/rss/latest_d_read/mylist?for=3&count=6`

This provides the 6 latest documents uploaded or updated on the *mylist* list for the last 3 days.

Parameters:

- `list`: the list is indicated in the path info. This parameter is mandatory.

- `for`: period of interest (expressed in days). This is a CGI parameter. It is optional but one of the two parameters `for` or `count` is required.
- `count`: maximum number of expected records. This is a CGI parameter. It is optional but one of the two parameters `for` or `count` is required.

Edit

## Sympa SOAP server

---

### Introduction

---

SOAP [<http://www.w3.org/2002/ws/>] is a protocol (generally over HTTP) that can be used to provide **web services**. Sympa SOAP server allows to access a Sympa service from within another program, written in any programming language and on any computer. SOAP encapsulates procedure calls, input parameters and resulting data in an XML data structure. The Sympa SOAP server's API is published in a **WSDL** document, retrieved through Sympa's web interface.

The SOAP server provides a limited set of high level functions, see [supported functions](#). Other functions might be implemented in the future. One of the important implementation constraint is to provide services for proxy application with a correct authorization evaluation process where authentication may differ from classic web methods. The following cases can be used to access the service:

- The client sends credentials and then requests a service providing a cookie with id `sympa-user`.
- The client authenticates the end user providing the `sympa-user` HTTP cookie. This can be used in order to share an authenticated session between Sympa and other applications running on the same server as *WWSympa*. The SOAP method used is `getUserEmailByCookieRequest`.
- The client provides user email and password and requests a service in a single SOAP access using the `authenticateAndRun` SOAP service.
- The client is trusted by Sympa as a proxy application and is authorized to set some variables that will be used by Sympa during the authorization scenario evaluation. Trusted applications have own password there, and the variables they can set are listed in a configuration file named `trusted_applications.conf`. See [Trust remote applications](#).

In any case, scenario authorization is used with the same rules as mail interface or usual web interface.

The SOAP server uses the SOAP::Lite [<http://www.soaplite.com/>] Perl library. The server is running as a daemon (thanks to FastCGI), receiving the client SOAP requests via a web server (Apache for example).

### Supported functions

---

Note that all functions accessible through the SOAP interface apply the appropriate access control rules, given the user's privileges.

The following functions are currently available through the Sympa SOAP server :

- `login` : user email and passwords are checked against Sympa user DB, or another backend.
- `casLogin` : this function will verify CAS proxy tickets against the CAS server
- `authenticateAndRun` : usefull for SOAP clients that can't set an HTTP cookie ; they can provide both the Sympa

session cookie and the requested command in a single call

- `authenticateRemoteAppAndRun` : equivalent of the previous command used in a trusted context (see [trust\\_remote\\_applications](#))
- `lists` : provides a list of available lists (authorization scenarios are applied)
- `complexLists` : same as the previous feature, but provides a complex structure for each list
- `info` : provides description informations about a given list
- `which` : gets the list of subscription of a given user
- `complexWhich` : same as previous command, but provides a complex structure for each list
- `aml` : tells if a given user is member of a given list
- `review` : lists the members of a given list
- `subscribe` : subscribes the current user to a given list
- `signoff` : current user is removed from a given list
- `add` : used to add a given user to a given list (admin feature)
- `del` : removes a given user from a given list (admin feature)
- `createList` : creates a new mailing list (requires appropriate privileges)
- `closeList` : closes a given mailing list (admin feature)

Check the [wsdl\\_service\\_description](#) for detailed API informations.

## Web server setup

---

You **need to install FastCGI** for the SOAP server to work properly, because it will run as a daemon.

Here is a sample piece of your Apache `httpd.conf` with a SOAP server configured:

```
FastCgiServer /home/sympa/bin/sympa_soap_server.fcgi -processes 1
ScriptAlias /sympasoaop /home/sympa/bin/sympa_soap_server.fcgi

<Location /sympasoaop>
    SetHandler fastcgi-script
</Location>
```

## Sympa setup

---

The only mandatory parameter you need to set in the `sympa.conf/robot.conf` files is the `soap_url`, that defines the URL of the SOAP service corresponding to the `ScriptAlias` you have previously set up in the Apache configuration.

This parameter is used to publish the SOAP service URL in the WSDL file (defining the API), but also for the SOAP server to deduce what Virtual Host is concerned by the current SOAP request (a single SOAP server will serve all Sympa virtual hosts).

## Trust remote applications

---

The SOAP service `authenticateRemoteAppAndRun` is used in order to allow some remote applications such as a web portal to request the Sympa service as a proxy for the end user. In such cases, Sympa will not authenticate

the end user itself, but instead it will trust a particular application to act as a proxy.

This configuration file `trusted_applications.conf` can be created in the `robot/etc/` subdirectory or in the `/home/sympa/etc` directory depending on the scope you want for it (the source package include a sample of file `trusted_applications.conf` in the `soap` directory). This file is made of paragraphs separated by empty lines and starting with keyword `trusted_application`. A sample `trusted_applications.conf` file is provided with Sympa sources. Each paragraph defines a remote trusted application with keyword/value pairs:

- `name`: the name of the application. Used with `password` for authentication; the `remote_application_name` variable is set for use in authorization scenarios;
- `md5password`: the MD5 digest of the application password. You can compute the digest as follows:  
`sympa.pl -md5_digest=<the password>`.
- `proxy_for_variables`: a comma separated list of variables that can be set by the remote application and that will be used by the Sympa SOAP server when evaluating an authorization scenario. If you list `USER_EMAIL` in this parameter, then the remote application can act as a user. Any other variable such as `remote_host` can be listed.

You can test your SOAP service using the `sympa_soap_client.pl` sample script as follows:

```
/home/sympa/bin/sympa_soap_client.pl --soap_url=http://my.server/sympasoa --service=createList --trusted_app
/home/sympa/bin/sympa_soap_client.pl --soap_url=http://myserver/sympasoa --service=add --trusted_applicatio
```

Below is a sample Perl code that does a SOAP procedure call (for a `SUBSCRIBE` sympa command) using the `trusted_application` feature :

```
my $soap = new SOAP::Lite();
$soap->uri('urn:sympasoa');
$soap->proxy('http://myserver/sympasoa');

my $response = $soap->authenticateRemoteAppAndRun('myTestApp', 'myTestAppPwd', 'USER_EMAIL=userProxy@my.server')
```

## The WSDL service description

Here is what the WSDL file looks like before it is parsed by *WWSympa*:

```
<?xml version='1.0'?>
<definitions name='Sympa'
  xmlns:xsd='http://www.w3.org/2001/XMLSchema'
  xmlns:soap='http://schemas.xmlsoap.org/wsdl/soap/'
  targetNamespace="[% conf.wwsympa_url %]/wsdl"
  xmlns:tns="[% conf.wwsympa_url %]/wsdl"
  xmlns='http://schemas.xmlsoap.org/wsdl/'
  xmlns:xsdl="[% conf.soap_url %]/wsdl">

<!-- types part -->

<types>
<schema targetNamespace="[% conf.wwsympa_url %]/wsdl"
  xmlns:SOAP-ENC='http://schemas.xmlsoap.org/soap/encoding/'
  xmlns:wsdl='http://schemas.xmlsoap.org/wsdl/'
  xmlns='http://www.w3.org/2001/XMLSchema'>
```

```

    <complexType name='ArrayOfLists'>
      <complexContent>
        <restriction base='SOAP-ENC:Array'>
          <attribute ref='SOAP-ENC:arrayType' wsdl:arrayType='tns:listType[]' />
        </restriction>
      </complexContent>
    </complexType>

    <complexType name='ArrayOfString'>
      <complexContent>
        <restriction base='SOAP-ENC:Array'>
          <attribute ref='SOAP-ENC:arrayType' wsdl:arrayType='string[]' />
        </restriction>
      </complexContent>
    </complexType>

    <complexType name='listType'>
      <all>
        <element name='listAddress' minOccurs='1' type='string' />
        <element name='homepage' minOccurs='0' type='string' />
        <element name='isSubscriber' minOccurs='0' type='boolean' />
        <element name='isOwner' minOccurs='0' type='boolean' />
        <element name='isEditor' minOccurs='0' type='boolean' />
        <element name='subject' minOccurs='0' type='string' />
      </all>
    </complexType>
  </schema>
</types>

<!-- message part -->

<message name='infoRequest'>
  <part name='listName' type='xsd:string' />
</message>

<message name='infoResponse'>
  <part name='return' type='tns:listType' />
</message>

<message name='complexWhichRequest'>
</message>

<message name='complexWhichResponse'>
  <part name='return' type='tns:ArrayOfLists' />
</message>

<message name='whichRequest'>
</message>

<message name='whichResponse'>
  <part name='return' type='tns:ArrayOfString' />
</message>

<message name='amIRequest'>
  <part name='list' type='xsd:string' />
  <part name='function' type='xsd:string' />
  <part name='user' type='xsd:string' />
</message>

<message name='amIResponse'>
  <part name='return' type='xsd:boolean' />
</message>

<message name='reviewRequest'>
  <part name='list' type='xsd:string' />
</message>

<message name='reviewResponse'>
  <part name='return' type='tns:ArrayOfString' />
</message>

```

```

<message name='signoffRequest'>
  <part name='list' type='xsd:string' />
  <part name='email' type='xsd:string' xsd:minOccurs='0' />
</message>

<message name='signoffResponse'>
  <part name='return' type='xsd:boolean' />
</message>

<message name='subscribeRequest'>
  <part name='list' type='xsd:string' />
  <part name='gecos' type='xsd:string' xsd:minOccurs='0' />
</message>

<message name='addRequest'>
  <part name='list' type='xsd:string' />
  <part name='email' type='xsd:string' />
  <part name='gecos' type='xsd:string' xsd:minOccurs='0' />
  <part name='quiet' type='xsd:boolean' xsd:minOccurs='0' />
</message>

<message name='addResponse'>
  <part name='return' type='xsd:boolean' />
</message>

<message name='delRequest'>
  <part name='list' type='xsd:string' />
  <part name='email' type='xsd:string' />
  <part name='quiet' type='xsd:boolean' xsd:minOccurs='0' />
</message>

<message name='delResponse'>
  <part name='return' type='xsd:boolean' />
</message>

<message name='createListRequest'>
  <part name='list' type='xsd:string' />
  <part name='subject' type='xsd:string' />
  <part name='template' type='xsd:string' />
  <part name='description' type='xsd:string' />
  <part name='topics' type='xsd:string' />
</message>

<message name='createListResponse'>
  <part name='return' type='xsd:boolean' />
</message>

<message name='closeListRequest'>
  <part name='list' type='xsd:string' />
</message>

<message name='closeListResponse'>
  <part name='return' type='xsd:boolean' />
</message>

<message name='subscribeResponse'>
  <part name='return' type='xsd:boolean' />
</message>

<message name='loginRequest'>
  <part name='email' type='xsd:string' />
  <part name='password' type='xsd:string' />
</message>

<message name='loginResponse'>
  <part name='return' type='xsd:string' />
</message>

<message name='getUserEmailByCookieRequest'>
  <part name='cookie' type='xsd:string' />
</message>

```

```

<message name='getUserEmailByCookieResponse'>
  <part name='return' type='xsd:string' />
</message>

<message name='authenticateAndRunRequest'>
  <part name='email' type='xsd:string' />
  <part name='cookie' type='xsd:string' />
  <part name='service' type='xsd:string' />
  <part name='parameters' type='tns:ArrayOfString' xsd:minOccurs='0' />
</message>

<message name='authenticateAndRunResponse'>
  <part name='return' type='tns:ArrayOfString' xsd:minOccurs='0' />
</message>

<message name='authenticateRemoteAppAndRunRequest'>
  <part name='appname' type='xsd:string' />
  <part name='apppassword' type='xsd:string' />
  <part name='vars' type='xsd:string' />
  <part name='service' type='xsd:string' />
  <part name='parameters' type='tns:ArrayOfString' xsd:minOccurs='0' />
</message>

<message name='authenticateRemoteAppAndRunResponse'>
  <part name='return' type='tns:ArrayOfString' xsd:minOccurs='0' />
</message>

<message name='casLoginRequest'>
  <part name='proxyTicket' type='xsd:string' />
</message>

<message name='casLoginResponse'>
  <part name='return' type='xsd:string' />
</message>

<message name='listsRequest'>
  <part name='topic' type='xsd:string' xsd:minOccurs='0' />
  <part name='subtopic' type='xsd:string' xsd:minOccurs='0' />
</message>

<message name='listsResponse'>
  <part name='listInfo' type='xsd:string' />
</message>

<message name='complexListsRequest'>
</message>

<message name='complexListsResponse'>
  <part name='return' type='tns:ArrayOfLists' />
</message>

<message name='checkCookieRequest'>
</message>

<message name='checkCookieResponse'>
  <part name='email' type='xsd:string' />
</message>

<!-- portType part -->

<portType name='SympaPort'>
  <operation name='info'>
    <input message='tns:infoRequest' />
    <output message='tns:infoResponse' />
  </operation>
  <operation name='complexWhich'>
    <input message='tns:complexWhichRequest' />
    <output message='tns:complexWhichResponse' />
  </operation>
  <operation name='which'>

```

```

        <input message='tns:whichRequest' />
        <output message='tns:whichResponse' />
</operation>
<operation name='amI'>
    <input message='tns:amIRequest' />
    <output message='tns:amIResponse' />
</operation>
<operation name='add'>
    <input message='tns:addRequest' />
    <output message='tns:addResponse' />
</operation>
<operation name='del'>
    <input message='tns:delRequest' />
    <output message='tns:delResponse' />
</operation>
<operation name='createList'>
    <input message='tns:createListRequest' />
    <output message='tns:createListResponse' />
</operation>
<operation name='closeList'>
    <input message='tns:closeListRequest' />
    <output message='tns:closeListResponse' />
</operation>
<operation name='review'>
    <input message='tns:reviewRequest' />
    <output message='tns:reviewResponse' />
</operation>
<operation name='subscribe'>
    <input message='tns:subscribeRequest' />
    <output message='tns:subscribeResponse' />
</operation>
<operation name='signoff'>
    <input message='tns:signoffRequest' />
    <output message='tns:signoffResponse' />
</operation>
<operation name='login'>
    <input message='tns:loginRequest' />
    <output message='tns:loginResponse' />
</operation>
<operation name='casLogin'>
    <input message='tns:casLoginRequest' />
    <output message='tns:casLoginResponse' />
</operation>
<operation name='getUserEmailByCookie'>
    <input message='tns:getUserEmailByCookieRequest' />
    <output message='tns:getUserEmailByCookieResponse' />
</operation>
<operation name='authenticateAndRun'>
    <input message='tns:authenticateAndRunRequest' />
    <output message='tns:authenticateAndRunResponse' />
</operation>
<operation name='authenticateRemoteAppAndRun'>
    <input message='tns:authenticateRemoteAppAndRunRequest' />
    <output message='tns:authenticateRemoteAppAndRunResponse' />
</operation>
<operation name='lists'>
    <input message='tns:listsRequest' />
    <output message='tns:listsResponse' />
</operation>
<operation name='complexLists'>
    <input message='tns:complexListsRequest' />
    <output message='tns:complexListsResponse' />
</operation>
<operation name='checkCookie'>
    <input message='tns:checkCookieRequest' />
    <output message='tns:checkCookieResponse' />
</operation>
</portType>
<!-- Binding part -->

```

```

<binding name='SOAP' type='tns:SympaPort'>
<soap:binding style='rpc' transport='http://schemas.xmlsoap.org/soap/http'>
  <operation name='info'>
    <soap:operation soapAction='urn:sympasoap#info'>
      <input>
        <soap:body use='encoded'
          namespace='urn:sympasoap'
          encodingStyle='http://schemas.xmlsoap.org/soap/encoding'>
      </input>
      <output>
        <soap:body use='encoded'
          namespace='urn:sympasoap'
          encodingStyle='http://schemas.xmlsoap.org/soap/encoding'>
      </output>
    </operation>
    <operation name='complexWhich'>
      <soap:operation soapAction='urn:sympasoap#complexWhich'>
        <input>
          <soap:body use='encoded'
            namespace='urn:sympasoap'
            encodingStyle='http://schemas.xmlsoap.org/soap/encoding'>
        </input>
        <output>
          <soap:body use='encoded'
            namespace='urn:sympasoap'
            encodingStyle='http://schemas.xmlsoap.org/soap/encoding'>
        </output>
      </operation>
      <operation name='which'>
        <soap:operation soapAction='urn:sympasoap#which'>
          <input>
            <soap:body use='encoded'
              namespace='urn:sympasoap'
              encodingStyle='http://schemas.xmlsoap.org/soap/encoding'>
          </input>
          <output>
            <soap:body use='encoded'
              namespace='urn:sympasoap'
              encodingStyle='http://schemas.xmlsoap.org/soap/encoding'>
          </output>
        </operation>
        <operation name='amI'>
          <soap:operation soapAction='urn:sympasoap#amI'>
            <input>
              <soap:body use='encoded'
                namespace='urn:sympasoap'
                encodingStyle='http://schemas.xmlsoap.org/soap/encoding'>
            </input>
            <output>
              <soap:body use='encoded'
                namespace='urn:sympasoap'
                encodingStyle='http://schemas.xmlsoap.org/soap/encoding'>
            </output>
          </operation>
          <operation name='createList'>
            <soap:operation soapAction='urn:sympasoap#createList'>
              <input>
                <soap:body use='encoded'
                  namespace='urn:sympasoap'
                  encodingStyle='http://schemas.xmlsoap.org/soap/encoding'>
              </input>
              <output>
                <soap:body use='encoded'
                  namespace='urn:sympasoap'
                  encodingStyle='http://schemas.xmlsoap.org/soap/encoding'>
              </output>
            </operation>
            <operation name='review'>
              <soap:operation soapAction='urn:sympasoap#review'>
                <input>
                  <soap:body use='encoded'

```

```

                namespace='urn:sympassoap''
                encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
        </input>
        <output>
                <soap:body use='encoded''
                namespace='urn:sympassoap''
                encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
        </output>
</operation>
<operation name='subscribe'>
        <soap:operation soapAction='urn:sympassoap#subscribe'/>
        <input>
                <soap:body use='encoded''
                namespace='urn:sympassoap''
                encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
        </input>
        <output>
                <soap:body use='encoded''
                namespace='urn:sympassoap''
                encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
        </output>
</operation>
<operation name='signoff'>
        <soap:operation soapAction='urn:sympassoap#signoff'/>
        <input>
                <soap:body use='encoded''
                namespace='urn:sympassoap''
                encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
        </input>
        <output>
                <soap:body use='encoded''
                namespace='urn:sympassoap''
                encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
        </output>
</operation>
<operation name='login'>
        <soap:operation soapAction='urn:sympassoap#login'/>
        <input>
                <soap:body use='encoded''
                namespace='urn:sympassoap''
                encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
        </input>
        <output>
                <soap:body use='encoded''
                namespace='urn:sympassoap''
                encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
        </output>
</operation>
<operation name='casLogin'>
        <soap:operation soapAction='urn:sympassoap#casLogin'/>
        <input>
                <soap:body use='encoded''
                namespace='urn:sympassoap''
                encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
        </input>
        <output>
                <soap:body use='encoded''
                namespace='urn:sympassoap''
                encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
        </output>
</operation>
<operation name='getUserEmailByCookie'>
        <soap:operation soapAction='urn:sympassoap#getUserEmailByCookie'/>
        <input>
                <soap:body use='encoded''
                namespace='urn:sympassoap''
                encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
        </input>
        <output>
                <soap:body use='encoded''
                namespace='urn:sympassoap''

```

```

        encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
    </output>
</operation>
<operation name='authenticateAndRun'>
    <soap:operation soapAction='urn:sympassoap#authenticateAndRun' />
    <input>
        <soap:body use='encoded'
            namespace='urn:sympassoap'
            encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
    </input>
    <output>
        <soap:body use='encoded'
            namespace='urn:sympassoap'
            encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
    </output>
</operation>
<operation name='authenticateRemoteAppAndRun'>
    <soap:operation soapAction='urn:sympassoap#authenticateRemoteAppAndRun' />
    <input>
        <soap:body use='encoded'
            namespace='urn:sympassoap'
            encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
    </input>
    <output>
        <soap:body use='encoded'
            namespace='urn:sympassoap'
            encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
    </output>
</operation>
<operation name='lists'>
    <soap:operation soapAction='urn:sympassoap#lists' />
    <input>
        <soap:body use='encoded'
            namespace='urn:sympassoap'
            encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
    </input>
    <output>
        <soap:body use='encoded'
            namespace='urn:sympassoap'
            encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
    </output>
</operation>
<operation name='complexLists'>
    <soap:operation soapAction='urn:sympassoap#complexLists' />
    <input>
        <soap:body use='encoded'
            namespace='urn:sympassoap'
            encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
    </input>
    <output>
        <soap:body use='encoded'
            namespace='urn:sympassoap'
            encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
    </output>
</operation>
<operation name='checkCookie'>
    <soap:operation soapAction='urn:sympassoap#checkCookie' />
    <input>
        <soap:body use='encoded'
            namespace='urn:sympassoap'
            encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
    </input>
    <output>
        <soap:body use='encoded'
            namespace='urn:sympassoap'
            encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'/>
    </output>
</operation>
</binding>
<!-- service part -->

```

```
<service name='SympaSOAP'>
  <port name='SympaPort' binding='tns:SOAP'>
    <soap:address location="[% conf.soap_url %]"/>
  </port>
</service>

</definitions>
```

## Client-side programming

---

Sympa is distributed with 2 sample clients written in Perl and in PHP. The Sympa SOAP server has also been successfully tested with a UPortal Channel as a Java client (using Axis). The sample PHP SOAP client has been installed on our demo server: <http://demo.sympa.org/sampleClient.php> [<http://demo.sympa.org/sampleClient.php>].

Depending on your programming language and the SOAP library you are using, you will either directly contact the SOAP service (as with the Perl SOAP::Lite library), or first load the WSDL description of the service (as with PHP nusoap or Java Axis). Axis is able to create a stub from the WSDL document.

The WSDL document describing the service should be fetch through *WWSympa's* dedicated URL: <http://your.server/sympa/wSDL>.

Note: the `login()` function maintains a login session using HTTP cookies. If you are not able to maintain this session by analyzing and sending appropriate cookies under SOAP, then you should use the `authenticateAndRun()` function that does not require cookies to authenticate.

## Writing a Java client with Axis

---

First, download jakarta-axis (<http://ws.apache.org/axis> [<http://ws.apache.org/axis>]).

You must add the libraries provided with jakarta axis (v >1.1) to you CLASSPATH. These libraries are:

- axis.jar;
- saaj.jar;
- commons-discovery.jar;
- commons-logging.jar;
- xercesImpl.jar;
- jaxrpc.jar;
- xml-apis.jar;
- jaas.jar;
- wsdl4j.jar;
- soap.jar.

Next, you have to generate client Java class files from the sympa WSDL URL. Use the following command:

```
java org.apache.axis.wsdl.WSDL2Java -av WSDL_URL
```

For example:

```
java org.apache.axis.wsdl.WSDL2Java -av http://demo.sympa.org/sympa/wSDL
```

Exemple of screen output during generation of Java files:

```
Parsing XML file: http://demo.sympa.org/sympa/wsdl
Generating org/sympa/demo/sympa/msdl/ListType.java
Generating org/sympa/demo/sympa/msdl/SympaPort.java
Generating org/sympa/demo/sympa/msdl/SOAPStub.java
Generating org/sympa/demo/sympa/msdl/SympaSOAP.java
Generating org/sympa/demo/sympa/msdl/SympaSOAPLocator.java
```

If you need more information or more generated classes (to have the server-side classes or junit testcase classes for example), you can get a list of switches:

```
java org.apache.axis.wsdl.WSDL2Java -h
```

The reference page is: <http://ws.apache.org/axis/java/reference.html> [<http://ws.apache.org/axis/java/reference.html>].

Take care of Test classes generated by axis, there are not useable as are. You have to stay connected between each test. To use junit testcases, before each SOAP operation tested, you must call the authenticated connexion to Sympa instance.

Here is a simple Java code that invokes the generated stub to perform a `casLogin()` and a `which()` on the remote Sympa SOAP server:

```
SympaSOAP loc = new SympaSOAPLocator();
((SympaSOAPLocator)loc).setMaintainSession(true);
SympaPort tmp = loc.getSympaPort();
String _value = tmp.casLogin(_ticket);
String _cookie = tmp.checkCookie();
String[] _abonnements = tmp.which();
```

Edit

## Authentication

---

Sympa needs to authenticate users (subscribers, owners, moderators, listmasters) on both its mail and web interface, and then apply appropriate privileges (authorization process) to subsequent requested actions. Sympa is able to cope with multiple authentication means on the client side, and when using user+password, it can validate these credentials against LDAP authentication backends.

When contacted on the mail interface, Sympa has 3 authentication levels. Lower level is to trust the `From:` SMTP header field. A higher level of authentication will require that the user confirms his/her message. The strongest supported authentication method is S/MIME (note that Sympa also deals with S/MIME encrypted messages).

On the Sympa web interface (*WWWsympa*) the user can authenticate in 4 different ways (if appropriate setup has been done on the Sympa server). Default authentication is performed through the user's email address and a password managed by Sympa itself. If an LDAP authentication backend (or multiple) has been defined, then the user can authenticate with his/her LDAP uid and password. Sympa is also able to delegate the authentication job to a web Single SignOn system; currently CAS [<http://www.yale.edu/tp/auth/>] (the Yale University system) or a generic SSO setup, adapted to SSO products providing an Apache module. When contacted via HTTPS, Sympa can make use of X509 client certificates to authenticate users.

The authorization process in Sympa (authorization scenarios) refers to authentication methods. The same authorization scenarios are used for both mail and web access; therefore some authentication methods are considered to be equivalent: mail confirmation (on the mail interface) is equivalent to password authentication (on the web interface); S/MIME authentication is equivalent to HTTPS with client certificate authentication. Each rule in authorization scenarios requires an authentication method (`smtp`, `md5` or `smime`); if the required authentication method was not used, a higher authentication mode can be requested.

## S/MIME and HTTPS authentication

---

Chapter [Use of S/MIME signature by Sympa itself](#) deals with Sympa and S/MIME signature. Sympa uses the OpenSSL library to work on S/MIME messages, you need to configure some related Sympa parameters: [S/X509 Sympa configuration](#).

Sympa HTTPS authentication is based on Apache+`mod_ssl` that provide the required authentication information through CGI environment variables. You will need to edit the Apache configuration to allow HTTPS access and require X509 client certificate. Here is a sample Apache configuration:

```
SSLEngine on
SSLVerifyClient optional
SSLVerifyDepth 10
...
<Location /sympa>
  SSLOptions +StdEnvVars
  SetHandler fastcgi-script
</Location>
```

If you are using the `SubjAltName`, then you additionally need to export the certificate data because of a `mod_ssl` bug. You will also need to install the `textindex Crypt-OpenSSL-X509` CPAN module. Add this option to the Apache configuration file:

```
SSLOptions +ExportCertData
```

## Authentication with email address, uid or alternate email address

---

Sympa stores the data relative to the subscribers in a DataBase. Among these data: password, email address exploited during the web authentication. The module of LDAP authentication allows to use Sympa in an intranet without duplicating user passwords.

This way users can indifferently authenticate with their `ldap_uid`, their `alternate_email` or their canonic email stored in the LDAP directory.

Sympa gets the canonic email in the LDAP directory with the `ldap_uid` or the `alternate_email`. Sympa will first attempt an anonymous bind to the directory to get the user's DN, then Sympa will bind with the DN and the user's `ldap_password` in order to perform an efficient authentication. This last bind will work only if the right `ldap_password` is provided. Indeed the value returned by the `bind(DN,ldap_password)` is tested.

Example: a person is described by

```
Dn:cn=Fabrice Rafart,
```

```
ou=Siege ,
o=MyCompany,
c=FR Objectclass:
person Cn: Fabrice Rafart
Title: Network Responsible
O: Siege
Or: Data processing
Telephonenumber: 01-00-00-00-00
Facsimiletelephonenumber:01-00-00-00-00
L:Paris
Country: France
    uid: frafart
    mail: Fabrice.Rafart@MyCompany.fr
alternate_email: frafart@MyCompany.fr
alternate:rafart@MyCompany.fr
```

So Fabrice Rafart can be authenticated with: frafart, Fabrice.Rafart@MyCompany.fr, frafart@MyCompany.fr, Rafart@MyCompany.fr. After this operation, the address in the FROM field will be the Canonic email, in this case Fabrice.Rafart@MyCompany.fr. That means that Sympa will get this email and use it during all the session until you clearly ask Sympa to change your email address via the two pages: which and pref.

## Generic SSO authentication

---

The authentication method has first been introduced to allow interaction with Shibboleth [<http://shibboleth.internet2.edu/>], Internet2's inter-institutional authentication system. But it should be usable with any SSO system that provides an Apache authentication module being able to protect a specified URL on the site (not the whole site). Here is a sample `httpd.conf` that shib-protects the associated Sympa URL:

```
...
<Location /sympa/sso_login/inqueue>
  AuthType shibboleth
  require affiliation ~ ^member@.+
</Location>
...
```

Sympa will get user attributes via environment variables. In the most simple case, the SSO will provide the user email address. If not, Sympa can be configured to check an email address provided by the user, or to look for the user email address in a LDAP directory (the search filter will make use of user information inherited from the SSO Apache module).

To plug a new SSO server in your Sympa server, you should add a `generic_sso` paragraph (describing the SSO service) in your `auth.conf` configuration file (see [generic\\_sso paragraph](#)). Once this paragraph has been added, the SSO service name will be automatically added to the web login menu.

Apart from the user email address, the SSO can provide other user attributes that Sympa will store in the `user_table` DB table (for persistancy), and make available in the `[user_attributes]` structure that you can use within authorization scenarios (see [Rules specifications](#)) or in web templates via the `[% user.attributes %]` structure.

## CAS-based authentication

---

CAS is the Yale University SSO software. Sympa can use the CAS authentication service.

Listmasters should define at least one or more CAS servers (`cas` paragraph) in `auth.conf`. If the

`non_blocking_redirection` parameter was set for a CAS server, then Sympa will try a transparent login on this server when the user accesses the web interface. If a CAS server redirects the user to Sympa with a valid ticket, Sympa receives a user ID from the CAS server. Then, it connects to the related LDAP directory to get the user email address. If no CAS server returns a valid user ID, Sympa will let the user either select a CAS server to login or perform a Sympa login.

## auth.conf

---

The `/home/sympa/etc/auth.conf` configuration file contains numerous parameters which are read on start-up of Sympa. If you change this file, do not forget that you will need to restart `wwsympa.fcgi` afterwards.

The `/home/sympa/etc/auth.conf` is organized in paragraphs. Each paragraph describes an authentication service with all parameters required to perform an authentication using this service. Sympa's current version can perform authentication through LDAP directories, using an external Single Sign-On Service (like CAS or Shibboleth), or using the internal `user_table` table.

The login page contains 2 forms: the login form and the SSO. When users hit the login form, each `ldap` or `user_table` authentication paragraph is applied unless email address input from form matches the `negative_regexp` or do not match `regexp`. `negative_regexp` and `regexp` can be defined for each `ldap` or `user_table` authentication service so that administrators can block some authentication methods for a class of users.

The second form in the login page contains the list of CAS servers so that users can choose explicitly their CAS service.

Each paragraph starts with one of the keyword `cas`, `ldap` or `user_table`.

The `/home/sympa/etc/auth.conf` file contains directives in the following format:

```
paragraphs
keyword value

paragraphs
keyword value
```

Comments start with the `#` character at the beginning of a line.

Empty lines are also considered as comments and are ignored at the beginning. After the first paragraph, they are considered as paragraph separators. There should only be one directive per line, but their order in the paragraph is of no importance.

Example:

```
#Configuration file auth.conf for the LDAP authentication
#Description of parameters for each directory

cas
    base_url             https://sso-cas.cru.fr
    non_blocking_redirection  on
    auth_service_name    cas-cru
    ldap_host            ldap.cru.fr:389
```

```

    ldap_get_email_by_uid_filter    (uid=[uid])
ldap_timeout                      7
ldap_suffix                       dc=cru,dc=fr
ldap_scope                        sub
ldap_email_attribute              mail

## The URL corresponding to the service_id should be protected by the SSO (Shibboleth in the exampl)
## The URL would look like http://yourhost.yourdomain/sympa/sso_login/inqueue in the following example
generic_sso
    service_name      InQueue Federation
    service_id        inqueue
    http_header_prefix HTTP_SHIB
    email_http_header HTTP_SHIB_EMAIL_ADDRESS

## The email address is not provided by the user home institution
generic_sso
    service_name      Shibboleth Federation
    service_id        myfederation
    http_header_prefix HTTP_SHIB
    netid_http_header HTTP_SHIB_EMAIL_ADDRESS
internal_email_by_netid          1
force_email_verify              1

ldap
    regexp            univ-rennes1\.fr
    host              ldap.univ-rennes1.fr:389
    timeout           30
    suffix            dc=univ-rennes1,dc=fr
    get_dn_by_uid_filter (uid=[sender])
    get_dn_by_email_filter (|(mail=[sender])(mailalternateaddress=[sender]))
    email_attribute    mail
    alternative_email_attribute mailalternateaddress,urlmail
    scope              sub
    use_ssl            1
    ssl_version        sslv3
    ssl_ciphers        MEDIUM:HIGH

ldap
    host              ldap.univ-nancy2.fr:392,ldap1.univ-nancy2.fr:392,ldap2.univ-nancy2.fr:392
    timeout           20
    bind_dn           cn=sympa,ou=people,dc=cru,dc=fr
    bind_password     sympapASSWD
    suffix            dc=univ-nancy2,dc=fr
    get_dn_by_uid_filter (uid=[sender])
    get_dn_by_email_filter (|(mail=[sender])(n2atraliasmail=[sender]))
    alternative_email_attribute n2atrmaildrop
    email_attribute    mail
    scope              sub
    authentication_info_url http://sso.univ-nancy2.fr/

user_table
    negative_regexp    ((univ-rennes1)|(univ-nancy2))\.fr

```

## user\_table paragraph

The `user_table` paragraph is related to Sympa internal authentication by email and password. It is the simplest one. The only parameters are `regexp` or `negative_regexp` which are Perl regular expressions applied on an email address provided, to select or block this authentication method for a subset of email addresses.

## ldap paragraph

- `regexp` and `negative_regexp`

Same as in the `user_table` paragraph: if an email address is provided (this does not apply to an uid), then the

regular expression will be applied to find out if the LDAP directory can be used to authenticate a subset of users.

- **host**

This keyword is **mandatory**. It is the domain name used in order to bind to the directory and then to extract information. You must mention the port number after the server name. Server replication is supported by listing several servers separated by commas.

Example:

```
host ldap.univ-rennes1.fr:389
host ldap0.university.com:389,ldap1.university.com:389,ldap2.university.com:389
```

- **timeout**

It corresponds to the `timelimit` in the Search fonction. A `timelimit` that restricts the maximum time (in seconds) allowed for a search. A value of 0 (the default) means that no `timelimit` will be requested.

- **suffix**

The root of the DIT (Directory Information Tree). The DN that is the base object entry relative to which the search is to be performed.

Example: `dc=university,dc=fr`

- **bind\_dn**

If anonymous bind is not allowed on the LDAP server, a DN and password can be used.

- **bind\_password**

This password is used, combined with the `bind_dn` above.

- **get\_dn\_by\_uid\_filter**

Defines the search filter corresponding to the `ldap_uid`. (RFC 2254 compliant). If you want to apply the filter on the user, use the variable ' `[sender]` '. It will work with every type of authentication (`uid`, `alternate_email`, ...).

Example:

```
(Login = [sender])
(|(ID = [sender])(UID = [sender]))
```

- **get\_dn\_by\_email\_filter**

Defines the search filter corresponding to the email addresses (canonic and alternative - this is RFC 2254 compliant). If you want to apply the filter on the user, use the variable ' `[sender]` '. It will work with every type of authentication (`uid`, `alternate_email`..).

Example: a person is described by

```
Dn:cn=Fabrice Rafart,
ou=Siege ,
o=MaSociete ,
c=FR Objectclass:
person Cn: Fabrice Rafart
Title: Network Responsible
O: Siege
Or: Data processing
Telephonenumber: 01-00-00-00-00
Facsimiletelephonenumber:01-00-00-00-00
L:Paris
Country: France
uid: frafart
mail: Fabrice.Rafart@MaSociete.fr
alternate_email: frafart@MaSociete.fr
alternate:rafart@MaSociete.fr
```

The filters can be:

```
(mail = [sender]) (| (mail = [sender])(alternate_email = [sender]) )
(| (mail = [sender])(alternate_email = [sender])(alternate = [sender]) )
```

- `email_attribute`

The name of the attribute for the canonic email in your directory: for instance `mail`, `canonic_email`, `canonic_address`, ... In the previous example, the canonic email is `mail`.

- `alternative_email_attribute`

The name of the attribute for the alternate email in your directory: for instance `alternate_email`, `mailalternateaddress`, ... You make a list of these attributes separated by commas.

With this list, Sympa creates a cookie which contains various information: whether the user is authenticated via LDAP or not, his alternate email. Storing the alternate email is interesting when you want to canonify your preferences and subscriptions, that is to say you want to use a unique address in `user_table` and `subscriber_table`, which is the canonic email.

- `scope` (Default value: `sub`)

By default, the search is performed on the whole tree below the specified base object. This may be changed by specifying a scope:

- `base`: search only the base object,
- `one`: search the entries immediately below the base object,
- `sub`: search the whole tree below the base object. This is the default.

- `authentication_info_url`

Defines the URL of a document describing LDAP password management. When hitting Sympa's *Send me a password* button, LDAP users will be redirected to this URL.

- `use_ssl`

If set to 1, connection to the LDAP server will use SSL (LDAPS).

- `ssl_version`

This defines the version of the SSL/TLS protocol to use. Defaults of Net::LDAPS to `sslv2/3`, other possible values are `sslv2`, `sslv3`, and `tlsv1`.

- `ssl_ciphers`

Specify which subset of cipher suites are permissible for this connection, using the standard OpenSSL string format. The default value of Net::LDAPS for ciphers is `ALL`, which permits all ciphers, even those that do not encrypt!

## generic\_sso paragraph

---

- `service_name`

This is the SSO service name that will be offered to the user in the login banner menu.

- `service_id`

This service ID is used as a parameter by Sympa to refer to the SSO service (instead of the service name).

A corresponding URL on the local web server should be protected by the SSO system; this URL would look like `http://yourhost.yourdomain/sympa/sso_login/inqueue` if the `service_id` is `inqueue`.

- `http_header_prefix`

Sympa gets user attributes from environment variables coming from the web server. These variables are then stored in the `user_table` DB table for later use in authorization scenarios (in structure). Only environment variables starting with the defined prefix will be kept.

- `email_http_header`

This parameter defines the environment variable that will contain the authenticated user's email address.

- `logout_url`

This optional parameter allows to specify the SSO logout URL. If defined, Sympa will redirect the user to this URL after the Sympa logout has been performed.

The following parameters define how Sympa can check the user email address, either provided by the SSO or by the user himself:

- `internal_email_by_netid`

If set to 1, this parameter makes Sympa use its `netidmap` table to associate NetIDs to user email addresses.

- `netid_http_header`

This parameter defines the environment variable that will contain the user's identifier. This netid will then be associated with an email address provided by the user.

- `force_email_verify`

If set to 1, this parameter makes Sympa check the user's email address. If the email address was not provided by the authentication module, then the user is requested to provide a valid email address.

The following parameters define how Sympa can retrieve the user email address; **these are useful only in case the `email_http_header` entry was not defined:**

- `ldap_host`

The LDAP host Sympa will connect to fetch user email. The `ldap_host` include the port number and it may be a comma separated list of redondant hosts.

- `ldap_bind_dn`

The DN used to bind to this server. Anonymous bind is used if this parameter is not defined.

- `ldap_bind_password`

The password used unless anonymous bind is used.

- `ldap_suffix`

The LDAP suffix used when searching user email.

- `ldap_scope`

The scope used when searching user email. Possible values are `sub`, `base` and `one`.

- `ldap_get_email_by_uid_filter`

The filter used to perform the email search. It can refer to any environment variables inherited from the SSO module, as shown below. Example:

```
ldap_get_email_by_uid_filter (mail=[SSL_CLIENT_S_DN_Email])
```

- `ldap_email_attribute`

The attribute name to be used as user canonical email. In the current version of Sympa, only the first value returned by the LDAP server is used.

- `ldap_timeout`

The time out for the search.

- `ldap_use_ssl`

If set to 1, connection to the LDAP server will use SSL (LDAPS).

- `ldap_ssl_version`

This defines the version of the SSL/TLS protocol to use. Defaults of Net::LDAPS to `sslv2/3`, other possible values are `sslv2`, `sslv3`, and `tlsv1`.

- `ldap_ssl_ciphers`

Specifies which subset of cipher suites are permissible for this connection, using the OpenSSL string format. The default value of Net::LDAPS for ciphers is `ALL`, which permits all ciphers, even those that do not encrypt!

## cas paragraph

---

- `auth_service_name`

The friendly user service name as shown by Sympa in the login page.

- `host` (OBSOLETE)

This parameter has been replaced by `base_url` parameter

- `base_url`

The base URL of the CAS server.

- `non_blocking_redirection`

This parameter only concerns the first access to Sympa services by a user, it activates or not the non blocking redirection to the related CAS server to check automatically if the user has been previously authenticated with this CAS server. Possible values are `on` and `off`, default is `on`. The redirection to CAS is used with the CGI parameter `gateway=1` that specifies to CAS server to always redirect the user to the original URL, but just check if the user is logged. If active, the SSO service is effective and transparent, but in case the CAS server is out of order, the access to Sympa services is impossible.

- `login_uri` (OBSOLETE)

This parameter has been replaced by the `login_path` parameter.

- `login_path` (OPTIONAL)

The login service path.

- `check_uri` (OBSOLETE)

This parameter has been replaced by the `service_validate_path` parameter.

- `service_validate_path` (OPTIONAL)

The ticket validation service path.

- `logout_uri` (OBSOLETE)

This parameter has been replaced by the `logout_path` parameter.

- `logout_path` (OPTIONAL)

The logout service path.

- `proxy_path` (OPTIONAL)

The proxy service path, only used by the Sympa SOAP server.

- `proxy_validate_path` (OPTIONAL)

The proxy validate service path, only used by the Sympa SOAP server.

- `ldap_host`

The LDAP host Sympa will connect to fetch user email when user uid is returned by CAS service. The `ldap_host` includes the port number and it may be a comma separated list of redundant hosts.

- `ldap_bind_dn`

The DN used to bind to this server. Anonymous bind is used if this parameter is not defined.

- `ldap_bind_password`

The password used unless anonymous bind is used.

- `ldap_suffix`

The LDAP suffix used when searching user email.

- `ldap_scope`

The scope used when searching user email. Possible values are `sub`, `base` and `one`.

- `ldap_get_email_by_uid_filter`

The filter used to perform the email search.

- `ldap_email_attribute`

The attribute name to be used as user canonical email. In the current version of Sympa, only the first value returned by the LDAP server is used.

- `ldap_timeout`

The time out for the search.

- `ldap_use_ssl`

If set to 1, connection to the LDAP server will use SSL (LDAPS).

- `ldap_ssl_version`

This defines the version of the SSL/TLS protocol to use. Defaults of Net::LDAPS to `sslv2/3`, other possible values are `sslv2`, `sslv3`, and `tlsv1`.

- `ldap_ssl_ciphers`

Specifies which subset of cipher suites are permissible for this connection, using the OpenSSL string format. The default value of Net::LDAPS for ciphers is `ALL`, which permits all ciphers, even those that do not encrypt!

## Sharing WWSympa's authentication with other applications

---

If you are not using a web Single Sign On system, you might want to make other web applications collaborate with Sympa and share the same authentication system. Sympa uses HTTP cookies to carry users' authentication information from page to page. This cookie contains no information about privileges. To make your application work with Sympa, you have two possibilities:

- Delegating authentication operations to *WWSympa*

If you want to avoid spending a lot of time programming a CGI to do Login, Logout and Remindpassword, you can copy *WWSympa's* login page to your application, and then make use of the cookie information within your application. The cookie format is:

```
sympauser=<user_email>:<checksum>
```

where `<user_email>` is the user's complete e-mail address, and `<checksum>` represents the 8 last bytes of the MD5 checksum of the `<user_email>+Sympa cookie configuration parameter`. Your application needs to know what the `cookie` parameter is, so it can check the HTTP cookie validity; this is a secret shared between *WWSympa* and your application. *WWSympa's* `loginrequest` page can be called to return to the referer URL when an action is performed. Here is a sample HTML anchor:

```
<A HREF='' /sympa/loginrequest/referer''>Login page</A>
```

You can also have your own HTML page submitting data to `wwsympa.fcgi` CGI. If you do so, you can set the `referer` variable to another URI. You can also set the `failure_referer` to make *WWSympa* redirect the client to a different URI if login fails.

## ■ Using *WWSympa*'s HTTP cookie format within your authentication module

To cooperate with *WWSympa*, you simply need to adopt its HTTP cookie format and share the secret it uses to generate MD5 checksums, i.e. the `cookie` configuration parameter. In this way, *WWSympa* will accept users authenticated through your application without further authentication.

## Provide a Sympa login form in another application

---

You can easily trigger a Sympa login from another web page. The login form should look like this:

```
<FORM ACTION='http://listes.cru.fr/sympa' method='post'>
  <input type='hidden' name='previous_action' value='arc' />
  Access web archives of list
  <select name='previous_list'>
    <option value='sympa-users' >sympa-users</option>
  </select><br/>
  <input type='hidden' name='action' value='login' />
  <label for='email'>email address:</label>
  <input type='text' name='email' id='email' size='18' value='' /></label><br />
  <label for='passwd' >password:</label>
  <input type='password' name='passwd' id='passwd' size='8' /></label> <br/>
  <input class='MainMenuLinks' type='submit' name='action_login' value="Login and access web archi
</FORM>
```

The example above does not only perform the login action, but also redirects the user to another Sympa page, a list web archive here. The `previous_action` and `previous_list` variables define the action that will be performed after the login is done.

Edit

## Authorization scenarios

---

An authorization scenario is a small configuration language to describe who can perform an operation and which authentication method is requested for it. An authorization scenario is an ordered set of rules. The goal is to provide a simple and flexible way to configure authorization and required authentication method for each operation.

## Location of scenario file

---

List parameters controlling the behavior of commands are linked to different authorization scenarios. For example: the `send private` parameter is related to the `send.private` scenario. There are four possible locations for an authorization scenario. When Sympa seeks to apply an authorization scenario, it first looks in the related list directory `/home/sympa/expl/<list>/scenari`. If it does not find the file there, it scans the current robot configuration directory `/home/sympa/etc/my.domain.org/scenari`, then the site's configuration directory `/home/sympa/etc/scenari`, and finally `/home/sympa/bin/etc/scenari`, which is the directory installed by the Makefile.

When customizing scenario for your own site, robot or list, don't modify `.../sympa/bin/scenari` content or next Sympa update will overwrite it (you must never modify anything in `.../sympa/bin/` unless your are patching Sympa). You can modify Sympa behavior if you create new scenario which name is the same as one of the scenario included in the distribution but with a location related to target site, robot or list. You can also add a new scenario ; it will automatically add an accepted value for the related parameter.

When modifying a existing scenario you need to restart Sympa or touch list config file before Sympa use it.

## Scenario structure

---

Each authorization scenario rule contains:

- **a condition:** the condition is evaluated by Sympa. It can use variables such as `sender` for the sender's email, `list` for the list name, etc.
- **an authentication method.** The authentication method can be `smtp`, `md5` or `smime`. The rule is applied by Sympa if both the condition and authentication method match the runtime context.
  - `smtp` is used if Sympa uses the SMTP `From:` header ,
  - `md5` is used if a unique MD5 key as been returned by the requestor to validate the message,
  - `smime` is used for signed messages (see [configuration to recognize S/MIME signatures](#));
- **a returned atomic action** that will be executed by Sympa if the rule matches.

Example:

```
del.auth

title.us deletion performed only by list owners, need authentication
title.fr suppression r'\eserv\`ee au propri\`etaire avec authentication
title.es eliminacin reservada slo para el propietario, necesita autentificacin

is_owner([listname],[sender]) smtp -> request_auth
is_listmaster([sender]) smtp -> request_auth
true() md5,smime -> do_it
```

## Rules specifications

---

An authorization scenario consists of rules, evaluated in order beginning with the first. Rules are defined as follows:

```
<rule> ::= <condition> <auth_list> -> <action>

<condition> ::= [!] <condition
  | true ()
  | equal (<var>, <var>)
  | match (<var>, /perl_regex/)
  | search (<named_filter_file>)
  | is_subscriber (<listname>, <var>)
  | is_owner (<listname>, <var>)
  | is_editor (<listname>, <var>)
  | is_listmaster (<var>)
  | older (<date>, <date>) # true if first date is anterior to the second date
  | newer (<date>, <date>) # true if first date is posterior to the second date
  | CustomCondition::<<package_name> (<var>*)

<var> ::= [email] | [sender] | [user-><user_key_word>] | [previous_email]
  | [remote_host] | [remote_addr] | [user_attributes-><user_attributes_keyword>]
  | [subscriber-><subscriber_key_word>] | [list-><list_key_word>] | [env-><env_var>]
  | [conf-><conf_key_word>] | [msg_header-><smtp_key_word>] | [msg_body]
  | [msg_part->type] | [msg_part->body] | [msg_encrypted] | [is_bcc] | [current_date]
  | [topic-auto] | [topic-sender,] | [topic-editor] | [topic] | [topic-needed]
  | [custom_vars-><custom_var_name>] | <string>

[is_bcc] ::= set to 1 if the list is neither in To: nor Cc:
```

```

[sender] ::= email address of the current user (used on web or mail interface). Default value is 'nobody'

[previous_email] ::= old email when changing subscription email in preference page.

[msg_encrypted] ::= set to 'smime' if the message was S/MIME encrypted

[topic-auto] ::= topic of the message if it has been automatically tagged

[topic-sender] ::= topic of the message if it has been tagged by sender

[topic-editor] ::= topic of the message if it has been tagged by editor

[topic] ::= topic of the message

[topic-needed] ::= the message has not got any topic and message topic are required for the list

/perl_regex/ ::= a perl regular expression. Don't forget to escape special characters (^, $, \{, \{, ...)
Check http://perldoc.perl.org/perlre.html for regular expression syntax.

<date> ::= '<date_element> [ +|- <date_element>]'

<date_element> ::= <epoch_date> | <var> | <date_expr>

<epoch_date> ::= <integer>

<date_expr> ::= <integer>y<integer>m<integer>d<integer>h<integer>min<integer>sec

<custom_var_name> ::= name of the custom parameter you want to use.

<listname> ::= [listname] | <listname_string>

<auth_list> ::= <auth>,<auth_list> | <auth>

<auth> ::= smtp|md5|smime

<action> ::= do_it [,notify]
            | do_it [,quiet]
            | reject(reason=<reason_key>) [,quiet]
            | reject(tt2=<tpl_name>) [,quiet]
            | request_auth
            | owner
            | editor
            | editorkey[,quiet]
            | listmaster

<reason_key> ::= match a key in mail_tt2/authorization_reject.tt2 template corresponding to
               an information message about the reason of the reject of the user

<tpl_name> ::= corresponding template (<tpl_name>.tt2) is send to the sender

<user_key_word> ::= email | gecos | lang | password | cookie_delay_user
                 | <additional_user_fields>

<user_attributes_key_word> ::= one of the user attributes provided by the SSO system via environment variable

<subscriber_key_word> ::= email | gecos | bounce | reception
                       | visibility | date | update_date
                       | <additional_subscriber_fields>

<list_key_word> ::= name | host | lang | max_size | priority | reply_to |
                  status | subject | account | total

<conf_key_word> ::= domain | email | listmaster | default_list_priority |
                  sympa_priority | request_priority | lang | max_size

<named_filter_file> ::= filename ending with .ldap , .sql or .txt

<package_name> ::= name of a perl package in /etc/custom_conditions/ (small letters)

```

(Refer to Tasks for date format definition)

The function to evaluate scenario is described in section [internals](#).

`custom_vars` allows you to introduce [custom parameters](#) in your scenario.

`perl_regex` can contain the string `[host]` (interpreted at run time as the list or robot domain). The variable notation `[msg_header-><smtp_key_word>]` is interpreted as the SMTP header value only when evaluating the authorization scenario for sending messages. It can be used, for example, to require editor validation for multipart messages. `[msg_part->type]` and `[msg_part->body]` are the MIME part content-types and bodies; the body is available for MIME parts in text/xxx format only.

The difference between `editor` and `editorkey` is that, with `editor`, the message is simply forwarded to moderators, who can then forward it to the list if they like. `editorkey` assigns a key to the message and sends it to moderators together with the message. So moderators can just send back the key to distribute the message. Please note that moderation from the web interface is only possible when using `editorkey`, because otherwise there is no copy of the message saved on the server.

A bunch of authorization scenarios is provided with the Sympa distribution; they provide a large set of configuration that allow to create lists for most usages. But you will probably create authorization scenarios for your own need. In this case, do not forget to restart Sympa and *WWSympa*, because authorization scenarios are not reloaded dynamically.

These standard authorization scenarios are located in the `/home/sympa/bin/etc/scenari/` directory. Default scenarios are named `<command>.default`.

You may also define and name your own authorization scenarios. Store them in the `/home/sympa/etc/scenari` directory. They will not be overwritten by newer Sympa releases. Scenarios can also be defined for a particular virtual host (using directory `/home/sympa/etc/<robot>/scenari`) or for a list (`/home/sympa/expl/<robot>/<list>/scenari`). **Sympa will not dynamically detect that a list configuration should be reloaded after a scenario has been changed on disk.**

Example: copy the previous scenario to `scenari/subscribe.rennes1`:

```
equal([sender], 'userxxx@univ-rennes1.fr') smtp,smime -> reject
match([sender], /univ-rennes1\.fr$/) smtp,smime -> do_it
true() smtp,smime -> owner
```

You may now refer to this authorization scenario in any list configuration file, for example:

```
subscribe rennes1
```

## Named Filters

---

At the moment, Named Filters are only used in authorization scenarios. They enable to select a category of people who will be authorized or not to realize some actions.

As a consequence, you can grant privileges in a list to people belonging to an LDAP directory, an SQL database or a flat text file, thanks to an authorization scenario.

Note that only a subset of variables available in the scenario context are available here (including `[sender]` and

[listname]).

## LDAP Named Filters Definition

---

People are selected through an LDAP filter defined in a configuration file. This file must have the extension '.ldap'. It is stored in `/home/sympa/etc/search_filters/`.

You must give a few information in order to create a LDAP Named Filter:

- `host`  
A list of host:port LDAP directories (replicates) entries.
- `suffix`  
Defines the naming space covered by the search (optional, depending on the LDAP server).
- `filter`  
Defines the LDAP search filter (RFC 2254 compliant). But you must absolutely take into account the first part of the filter which is: `(mail_attribute = [sender])`, as shown in the example. You will have to replace `mail_attribute` by the name of the attribute for the email. Sympa checks whether the user belongs to the category of people defined in the filter.
- `scope`  
By default, the search is performed on the whole tree below the specified base object. This may be changed by specifying a scope:
  - `base`: search only the base object.
  - `one`: search the entries immediately below the base object.
  - `sub`: search the whole tree below the base object. This is the default option.
- `bind_dn`  
If anonymous bind is not allowed on the LDAP server, a DN and password can be used.
- `bind_password`  
This password is used, combined with the `bind_dn` above.

example.ldap: we want to select the teachers of mathematics in the University of Rennes 1 in France:

```
host          ldap.univ-rennes1.fr:389,ldap2.univ-rennes1.fr:390
suffix        dc=univ-rennes1.fr,dc=fr
filter        (&(canonic_mail = [sender])(EmployeeType = prof)(subject = math))
scope         sub
```

## SQL Named Filters Definition

---

People are selected through an SQL filter defined in a configuration file. This file must have the extension '.sql'. It is stored in `/home/sympa/etc/search_filters/`.

To create an SQL Named Filter, you have to configure SQL host, database and options, the same way you did it for the main Sympa database in `sympa.conf`. Of course, you can use different database and options. Sympa will open a new Database connection to execute your statement.

Please refer to section [Database related](#) for a detailed explanation of each parameter.

Here, all database parameters have to be grouped in one `sql_named_filter_query` paragraph.

- `db_type`  
Format: `db_type mysql|SQLite|Pg|Oracle|Sybase`; Database management system used.  
Mandatory and case sensitive.
- `db_host`  
Database host name. Mandatory.
- `db_name`  
Name of database to query. Mandatory.
- `statement`  
Mandatory. The SQL statement to execute to verify authorization. This statement must returns 0 to refuse the action, or anything else to grant privileges. The `SELECT COUNT(*) . . .` statement is the perfect query for this parameter. The keyword in the SQL query will be replaced by the sender's email.
- Optional parameters  
Please refer to main `sympa.conf` section for description.
  - `db_user`
  - `db_password`
  - `db_options`
  - `db_env`
  - `db_port`
  - `db_timeout`

`example.sql`: we want to select the teachers of mathematics in the University of Rennes 1 in France:

```
sql_named_filter_query
db_type      mysql
db_name      people
db_host      dbserver.rennes1.fr
db_user      sympa
db_passwd    pw_sympa_mysqluser
statement    SELECT count(*) as c FROM users WHERE mail=[sender] AND EmployeeType='PROFESSOR' AND c
```

## Search condition

---

The search condition is used in authorization scenarios.

The syntax of this rule is:

```
search(example.ldap)      smtp,smime,md5    -> do_it
search(blacklist.txt)     smtp,smime,md5    -> do_it
```

The variable used by `search` is the name of the LDAP configuration file or a txt matching enumeration.

Note that Sympa processes maintain a cache of processed search conditions to limit access to the LDAP directory or SQL server; each entry has a lifetime of one hour in the cache.

When using the `.txt` file extension, the file is read looking for a line that matches the second parameter (usually the user email address). Each line is a string where the char `*` can be used once to mach any block. This feature is used by the blacklist implicit scenario rule (see Blacklist).

The method of authentication does not change.

## Scenario inclusion

---

Scenarios can also contain includes:

```
subscribe
  include commonreject
  match(/cru\.fr$/)      smtp,smime -> do_it
  true()                 smtp,smime -> owner
```

In this case, Sympa applies recursively the scenario named `include.commonreject` before introducing the other rules. This possibility was introduced in order to facilitate the administration of common rules.

## Scenario implicit inclusion

---

You can define a set of common scenario rules, used by all lists. `include.<action>.header` is automatically added to evaluated scenarios. Note that you will need to restart Sympa processes to force reloading of list config files.

## Blacklist implicit rule

---

For each service listed in parameter `use_blacklist` (see [use\\_blacklist](#)), the following implicit scenario rule is added at the beginning of the scenario:

```
search(blacklist.txt) smtp,md5,pgp,smime -> reject,quiet
```

The goal is to block messages or other service requests from unwanted users. The blacklist can be defined for the robot or for the list. At the list level, the blacklist is to be managed by list owner or list editor via the web interface.

## Custom Perl package conditions

---

You can use a Perl package of your own to evaluate a custom condition. It can be useful if you have very complex tasks to carry out to evaluate your condition (web services queries...). In this case, you should write a Perl module, place it in the `CustomCondition` namespace, with one `verify` fonction that has to return `1` to grant access, `undef` to warn of an error, or anything else to refuse the authorization.

This Perl module:

- must be placed in a subdirectory `custom_conditions` of the `etc` directory of your Sympa installation, or of a robot;
- its filename must be lowercase;
- must be placed in the `CustomCondition` namespace;
- must contain one `verify` static fonction;
- will receive all condition arguments as parameters.

For example, lets write the smallest custom condition that always returns 1.

```
/home/sympa/etc/custom_conditions/yes.pm :  
  
#!/usr/bin/perl  
  
package CustomCondition::yes;  
  
use strict;  
use Log; # optional : we log parameters  
  
sub verify {  
    my @args = @_;  
    foreach my $arg (@args) {  
        do_log ('debug3', 'arg: ', $arg);  
    }  
    # I always say 'yes'  
    return 1;  
}  
## Packages must return true.  
1;
```

We can use this custom condition that way:

```
CustomCondition::yes(,,)    smtp,smime,md5    -> do_it  
true()                     smtp,smime    -> reject
```

Note that the `, ,` are optional, but it is the way you can pass information to your package. Our `yes.pm` will print the values in the logs.

Remember that the package name has to be lowercase, but the `CustomCondition` namespace is case sensitive. If your package returns `undef`, the sender will receive an 'internal error' mail. If it returns anything else but `1`, the sender will receive a 'forbidden' error.

## Hiding scenario files

---

Because Sympa is distributed with many default scenario files, you may want to hide some of them to list owners (to make list administration menus shorter and readable). To hide a scenario file, you should create an empty file with the `:ignore` suffix. Depending on where this file has been created, it will make it be ignored at either a global, robot or list level.

Example:

```
/home/sympa/etc/my.domain.org/scenari/send.intranetorprivate:ignore
```

The `intranetorprivate send` scenario will be hidden (on the web admin interface), at the `my.domain.org` robot level only.

Edit

## Virtual host

---

Sympa is designed to manage multiple distinct mailing list servers on a single host with a single Sympa installation.

Sympa virtual hosts are like Apache virtual hosting. Sympa virtual host definition includes a specific email address for the robot itself and its lists and also a virtual HTTP server. Each robot provides access to a set of lists, each list is related to only one robot.

Most configuration parameters can be redefined for each robot, except for general Sympa installation parameters (binary and spool location, SMTP engine, antivirus plugin, ...).

The virtual host name as defined in Sympa documentation and configuration file refers to the Internet domain of the virtual host.

Note that Sympa allows you to manage 2 lists with the same name (local part) among different virtual domains. It used to be a limitation until Sympa 5.2.

## How to create a virtual host

---

You do not need to install several Sympa servers. A single `sympa.pl` daemon and one or more fastcgi servers can serve all virtual host. Just configure the server environment in order to accept the new domain definition.

- **The DNS** must be configured to define a new mail exchanger record (MX) to route message to your server. A new host (A record) or alias (CNAME) are mandatory to define the new web server.
- Configure your **MTA** (sendmail, postfix, exim, ...) to accept incoming messages for the new robot domain. Add mail aliases for the robot. Examples (with sendmail):

```
sympa@your.virtual.domain:      "| /home/sympa/bin/queue sympa@your.virtual.domain"
listmaster@your.virtual.domain: "| /home/sympa/bin/queue listmaster@your.virtual.domain"
bounce+*@your.virtual.domain:  "| /home/sympa/bin/bouncequeue sympa@your.virtual.domain"
```

- Define a **virtual host in your HTTPD server**. The fastcgi servers defined in the common section of your HTTPD server can be used by each virtual host. You do not need to run dedicated fastcgi server for each virtual host. Examples:

```
FastCgiServer /home/sympa/bin/wwsympa.fcgi -processes 3 -idle-timeout 120
.....
<VirtualHost 195.215.92.16>
  ServerAdmin webmaster@your.virtual.domain
  DocumentRoot /var/www/your.virtual.domain
  ServerName your.virtual.domain
  <Location /sympa>
    SetHandler fastcgi-script
  </Location>
  ScriptAlias /sympa /home/sympa/bin/wwsympa.fcgi
  Alias /static-sympa /home/sympa/your.virtual.domain/static_content
</VirtualHost>
```

- Create a `/home/sympa/etc/your.virtual.domain/robot.conf` configuration file for the virtual host. Its format is a subset of `sympa.conf` and is described in the next section; a sample `robot.conf` is provided.
- Create a `/home/sympa/expl/your.virtual.domain/` directory that will contain the virtual host mailing lists directories. This directory should have the `sympa` user as its owner and must have read and write access for this user.

```
# su sympa -c 'mkdir /home/sympa/expl/your.virtual.domain'  
# chmod 750 /home/sympa/expl/your.virtual.domain
```

## robot.conf

---

A robot is named by its domain, let's say `my.domain.org`, and defined by a directory `/home/sympa/etc/my.domain.org`. This directory must contain at least a `robot.conf` file. This file has the same format as `/etc/sympa.conf` (have a look at `robot.conf` in the sample dir). Only the following parameters can be redefined for a particular robot:

- `http_host`

This hostname will be compared with the `SERVER_NAME` environment variable in `wwsympa.fcgi` to determine the current Virtual Host. You can add a path at the end of this parameter if you are running multiple virtual hosts on the same host. Examples:

```
http_host myhost.mydom  
http_host myhost.mydom/sympa
```

- `host`

This is the equivalent of the `host sympa.conf` parameter. The default for this parameter is the name of the virtual host (i.e. the name of the subdirectory);

- `wwsympa_url`

The base URL of *WWSympa*;

- `soap_url`

The base URL of Sympa's SOAP server (if it is running; see [soap](#));

- `cookie_domain`;

- `email`;

- `title`;

- `default_home`;

- `create_list`;

- `lang`;

- `supported_lang`;

- `log_smtp`;

- `listmaster`;

- `max_size`;

- `css_path`;

- `css_url`;

- `static_content_path`;

- `static_content_url`;

- `pictures_feature`;

- `pictures_max_size`;

- `logo_html_definition`;

- `color_0, color_1 ... color_15`;

- deprecated color definition: `dark_color, light_color, text_color, bg_color, error_color, selected_color, shaded_color`.

These settings overwrite the equivalent global parameter defined in `/etc/sympa.conf` for the `my.domain.org` robot; the main `listmaster` still has privileges on Virtual Robots though. The `http_host` parameter is compared by *WWSympa* with the `SERVER_NAME` environment variable to recognize which robot is in use.

## Robot customization

---

In order to customize the web look and feel, you may edit the CSS definition. CSS are defined in a template named `css.tt2`. Any robot can use static CSS file for making Sympa web interface faster. Then you can edit this static definition and change web style. Please refer to `css_path` and `css_url`. You can also quickly introduce a logo in the upper left corner of all pages by configuring the `logo_html_definition` parameter in the `robot.conf` file.

In addition, if needed, you can customize each virtual host using its set of templates and authorization scenarios.

The `/home/sympa/etc/my.domain.org/web_tt2/`, `/home/sympa/etc/my.domain.org/mail_tt2/` and `/home/sympa/etc/my.domain.org/scenari/` directories are searched when loading templates or scenarios before searching into `/home/sympa/etc` and `/home/sympa/bin/etc`. This allows to define different privileges and a different GUI for a Virtual Host.

## Managing multiple virtual hosts

---

If you are managing more than 2 virtual hosts, then you might consider moving all the mailing lists in the default robot to a dedicated virtual host located in the `/home/sympa/expl/my.domain.org/` directory. The main benefit of this organisation is the ability to define default configuration elements (templates or authorization scenarios) for this robot without inheriting them within other virtual hosts.

To create such a virtual host, you need to create the `/home/sympa/expl/my.domain.org/` and `/home/sympa/etc/my.domain.org/` directories; customize the `host`, `http_host` and `wwsympa_url` parameters in the `/home/sympa/etc/my.domain.org/robot.conf`, with the same values as the default robot (as defined in `sympa.conf` and `wwsympa.conf` files).

Edit

## Interaction between Sympa and other applications

---

### Soap

---

See [Sympa SOAP server](#).

### RSS channel

---

See [Sympa's RSS channel](#).

## Sharing WWSympa's authentication with other applications

---

See [Sharing WWSympa's authentication with other applications](#).

## Sharing data with other applications

---

You may extract subscribers, owners and editors for a list from any of:

- a text file;
- a relational database;
- a LDAP directory.

See the [user\\_data\\_source](#) list parameter.

The three tables can have more fields than the one used by Sympa, by defining these additional fields, they will be available from within Sympa's authorization scenarios and templates (see [db\\_additional\\_subscriber\\_fields](#) and [db\\_additional\\_user\\_fields](#)).

See [Data inclusion file](#).

## Subscriber count

---

The number of subscribers of a list can be obtained from an external application by requesting function `subscriber_count` on the Web interface.

Example:

```
http://my.server/wws/subscriber_count/mylist
```

Edit

## Customizing Sympa/WWSympa

---

### Template file format

---

Template files within Sympa used to be in a proprietary format that has been replaced with the TT2 [<http://www.tt2.org>] template format.

You will find detailed documentation about the TT2 syntax on the web site: <http://www.tt2.org> [<http://www.tt2.org>]

Here are some aspects regarding templates that are specific to Sympa:

- References to PO catalogues are noted with the `[% loc %]` tag that may include parameters. Example:

```
[%|loc(list.name,list.host)%]Welcome to list %1 %2[%END%]
```

- Few exceptions apart, templates cannot insert or parse a file given its full or relative path, for security reasons. Only the file name should be provided; the TT2 parser will then use the `INCLUDE_PATH` provided by Sympa to find the relevant file to insert/parse.

- The **gencode** filter should be used if a template includes SMTP header fields that should be Q-encoded. Example:

```
[% FILTER gencode %]Message à modérer[%END%]
```

- You can write different versions of a template file in different languages, each of them being located in a subdirectory of the `tt2` directory. Example: `/mail_tt2/fr_FR/helpfile.tt2`.
- Your templates can include custom parameters.

## Site template files

---

These files are used by Sympa as service messages for the `HELP`, `LISTS` and “`REMINDE`” commands. These files are interpreted (parsed) by Sympa and respect the TT2 template format; every file has a `.tt2` extension. See [Template file format](#).

Sympa looks for these files in the following order (where `<list>` is the listname if defined, `<action>` is the name of the command, and `<lang>` is the preferred language of the user):

1. `/home/sympa/expl/<list>/mail_tt2/<lang>/<action>.tt2`.
2. `/home/sympa/expl/<list>/mail_tt2/<action>.tt2`.
3. `/home/sympa/etc/my.domain.org/mail_tt2/<lang>/<action>.tt2`.
4. `/home/sympa/etc/my.domain.org/mail_tt2/<action>.tt2`.
5. `/home/sympa/etc/mail_tt2/<lang>/<action>.tt2`.
6. `/home/sympa/etc/mail_tt2/<action>.tt2`.
7. `/home/sympa/bin/etc/mail_tt2/<lang>/<action>.tt2`.
8. `/home/sympa/bin/etc/mail_tt2/<action>.tt2`.

If the file starts with a `From:` line, it is considered as a full message and will be sent (after parsing) without adding SMTP headers. Otherwise, the file is treated as a text/plain message body.

The following variables may be used in these template files:

- `[% conf.email %]`: sympa email address local part;
- `[% conf.domain %]`: sympa robot domain name;
- `[% conf.sympa %]`: sympa’s complete email address;
- `[% conf.wwsympa_url %]`: *WWSympa*’s root URL;
- `[% conf.listmaster %]`: listmaster email addresses;
- `[% user.email %]`: user email address;
- `[% user.gecos %]`: user `gecos` field (usually his/her name);
- `[% user.password %]`: user password;
- `[% user.lang %]`: user language.

## helpfile.tt2

---

This file is sent in response to a HELP command. You may use additional variables:

- [% is\_owner %]: TRUE if the user is list owner;
- [% is\_editor %]: TRUE if the user is list editor.

## lists.tt2

---

File returned by the LISTS command. An additional variable is available:

- [% lists %]: this is a hash table indexed by list names and containing lists' subjects. Only lists visible to the user (according to the `visibility` list parameter) are listed.

Example:

```
-----  
These are the public lists for [conf->email]@[conf->domain]  
  
[% FOREACH l = lists %]  
[% l.key %]@[% l.value.host %] : [% l.value.subject %] ([% l.value.topics.0 %])  
  
[% END %]  
-----
```

## global\_remind.tt2

---

This file is sent in response to a REMIND \* command. (see [Owner commands](#)) You may use additional variables:

-[% lists %]: this is an array containing the names of the lists the user is subscribed to.

Example:

```
-----  
This is a subscription reminder.  
  
You are subscribed to the following lists:  
[% FOREACH l = lists %]  
  
[% l %]: [% conf.wwsympa\_url \%]/info/[% l %]  
  
[% END %]  
  
Your subscriber e-mail: [% user.email %]  
Your password: [% user.password %]  
-----
```

## your\_infected\_msg.tt2

---

This message is sent to warn the sender of a virus infected mail, indicating the name of the virus found (see [Antivirus](#)).

## Web template files

---

You may define your own web template files, different from the standard ones. *WWSympa* first looks for list specific web templates, then for site web templates, before falling back on its defaults.

Your list web template files should be placed in the `/home/sympa/expl/mylist/web_tt2` directory, and your site web templates in the `~/home/sympa/etc/web_tt2` directory.

## Sympa colors customization guide

---

Sympa colors are managed using `color_x` parameters in `Sympa.conf`.

You will find below how these parameters are interpreted in the Sympa web interface. Note that if you activated the static CSS, you will need to hit the “install static css” button once again to see the changes in your color definitions.

**Install time:** web colors are defined in Sympa’s main Makefile (see Compilation and installation).

### What are the colors used for?

- `color_0`: background color of:
  - one out of two lines in tables, alternated with `color_5`. It is intended to be the darkest shade, as `color_5` has other uses.
- `color_1`: background color of:
  - main navigation tabs
  - most of the buttons (those corresponding to the `MainMenuLinks` CSS class)
- `color_2`: font and border color of:
  - almost everything. Exceptions for borders are `<TD/>` borders; exceptions for fonts are links, buttons and some titles.
- `color_3`: background color of:
  - top box
  - footer box
- `color_4`: background color of:
  - page
  - table headers (at the very exception of the table displaying new lists)
  - the rest of the buttons (which are in fact hyperlinks, corresponding to the `actionMenuLinks` CSS class)
- `color_5`: background color of:
  - all the main interface boxes
  - the lightest color for the table lines, contrasting with `color_0`
- `color_6`: background color of:
  - active action (for example, the section of the admin options which is currently viewed, or the header corresponding to the data following which an array is currently sorted)
  - hovered actions
  - hovered buttons corresponding to the `actionMenuLinks` CSS class
  - hovered navigation tabs
- `color_7`: background color of:
  - error messages

- just edited area in the administrative management section.
- `color_8`: dotted underscore color of:
  - hyperlinks
- `color_9`:
  - border color for active action (for example, the section of the admin options which is currently viewed, or the header corresponding to the data following which an array is currently sorted)
  - border color for hovered hyperlinks corresponding to actions
  - background color for clicked links (corresponding to the `.active` state in a CSS)
- `color_10`: inactive buttons color. Rarely used. Don't bother.
- `color_11`: font color for:
  - active navigation tab
  - H2 titles
  - hovered links
  - some hovered buttons action(which are in fact hyperlinks, corresponding to the `actionMenuLinks` CSS class)
- `color_12`: Font color for the class `smallblack`. Not sure it is used.
- `color_13`: Background color of:
  - editable form areas (text areas, selection lists, ...)
  - the rest of hovered buttons (those corresponding to the `MainMenuLinks` CSS class)
- `color_14`: Unused
- `color_15`: Unused

## What colors have the objects?

Here are gathered informations about the color parameters used for specific parts of the web interface. Take care to have a look to the precedent section as changing a parameter for an object is likely to change it for a few similar objects.

### Main backgrounds

There are for different backgrounds in the web interface:

- The page: `color_4`; below all the rest. Just the base on which all the rest is stacked.
- The main boxes: `color_5`; This is where most of the text, buttons and links are displayed.
- The top box and footer: `color_3`; the top box is where your service name and main navigation tabs are displayed. The footer contains the version of Sympa.
- The editable forms areas: `color_13`; This is the color in all the form widgets which can be edited by users (text areas, selection lists).

### Buttons

The buttons color management can be confusing, so let's just stress it a little:

Color attribute	MainMenuLinks CSS class	actionMenuLinks CSS class
Default background color	<code>color_1</code>	<code>color_4</code>
Hovered background color	<code>color_13</code>	<code>color_6</code>

Default font color	color_2	color_2
Hovered font color	color_1	color_11
Default border color	color_2	color_2
Hovered border color	color_2	color_2

## Links

Hyperlinks have the same attributes as plain text, except:

1. They are always underscored by a dotted line of color `color_8`
2. When hovered, they take the color `color_11`

## Menu links

They have the following attributes:

State	Font	Background	Border
Default	color_2	None	None
Hovered	color_11	color_6	color_9
Clicked	color_2	color_9	color_6
Active	color_2	color_6	color_9

## Miscellaneous

Note these additional informations:

1. navigation tabs have the same default parameters as the class `MainMenuLinks` but the same parameters as `actionMenuLinks` when hovered;
2. except for the `MainMenuLinks` button, *anything* likely to do something if clicked takes the font color `color_11` when hovered;
3. the menu links (Info, Admin, Edit list config...) are the only objects whose color actually changes on click.

## CSS files

---

Sympa has four CSS stylesheets : `style.css`, `print.css`, `print-preview.css` and `fullPage.css`.

It will use a stylesheet or the other regarding the kind of request the user addressed.

But, for each stylesheet, what is sent to users varies regarding the values of two parameters : `css_path` and `css_url`.

## css\_path and css\_url parameters

---

- `css_path` defines the directory in which `wwsympa` can find static CSS files;
- `css_url` defines the URL used by web clients to request the web server for stylesheets.

These parameters values are looked for in `robot.conf` first, then `sympa.conf`, and then, if not found, set to hard-coded defaults.

- If `css_path` isn't defined, its default is set to : `${static_content_path}/css`.

`static_content_path` is the parameter defining the root path to all static content for Sympa. If `static_content_path` is undefined in `sympa.conf` or `robot.conf`, its value is set to : `sympa_home_dir/static_content`.

- If `css_url` isn't defined, its default is set to : `${static_content_url}/css`.

`static_content_url` is the parameter defining the root url to all static content in Sympa. If `static_content_url` is undefined in `sympa.conf` or `robot.conf`, its value is set to : `/static-sympa`.

This way :

- the default path to static stylesheet is : `sympa_home_dir/static_content/css/style.css`
- the default URL to the static stylesheet is : `http://host.name/static-sympa/css/style.css`  
[`http://host.name/static-sympa/css/style.css`]

The `sympa_wizard.pl` script, run at install, can set both `static_content_path` and `static_content_url` values.

## What stylesheet will be used ?

---

- Case 1 : if the directory defined by `css_path` exists, the value of `css_url` will be the one defined in Sympa config.
- Case 2 : if this directory doesn't exist, the value of `css_url` will be that of the `css` action (i.e. `http://url.to.wwsympa/css/` [`http://url.to.wwsympa/css/`]).

The content delivered varies greatly according to which case happens.

- 
- **Case 1:** the stylesheet received by the client is the **file** found in the directory that your Apache server configuration associates to this URL. It is up to you to decide whether this directory must correspond to the `css_path` value or not. If it corresponds to the `css_path` value, you must use the files generated by `wwsympa`. If not, you will use whichever stylesheet you want to define. Whatever solution you choose, take note that `wwsympa` will not, opposite to case 2, be involved in the stylesheet delivery, as it won't be addressed the HTTP request. This way, your stylesheet is served directly by Apache and remains in cache, thus saving bandwidth.
  - **Case 2:** the stylesheet received by the client is the result of a **wwsympa action** called `css`. `wwsympa` parses a file named `css.tt2` that it finds in the relevant `web_tt2` folder and generates on the fly a stylesheet that it returns to the client. In this case, the action is triggered any time a page is requested to `wwsympa` and the four stylesheets are sent along with the page. This is more bandwidth consuming than case 1, but any change in `css.tt2` will be applied at once, without static content generation. This is particularly usefull when experimenting a new stylesheet.

## Using wwsympa CSS generation process

---

The CSS generation described in the case 2 of the previous section has two purposes :

1. Serve CSS files generated on the fly for each request
1. Generate static CSS files stored in the directory defined by the `css_path` parameter. This is done by hitting the “Install static CSS” button in the skins administration page of `wwsympa`. These files are subsequently used as static content.

The following explanations apply whichever you use static (but `sympa`-generated) or dynamic CSS. Both operations use the same template file and data.

- **Colors** are defined in either `sympa.conf` or `robot.conf`. The role of each color parameter is explained in the [color customization guide](#).

For the particular case of colors, though, note that the colors used are those from the `robot.conf` or `sympa.conf`, whichever is relevant. `wwsympa` uses those loaded in memory at the time the CSS generation is requested, being to generate a static stylesheet or to deliver a dynamic one directly. That means that if you change colors in your configuration file, these changes must be taken into account by `wwsympa` prior to regenerating CSS.

- **Any other CSS information** is defined in `css.tt2` template. As any other template, take care not to modify the default file (in `sympa_home/bin/etc/web_tt2`) but to copy it in `sympa_home/etc/web_tt2` or `sympa_home/etc/robot_dir/web_tt2` and modify the copies. In these copies, you can add/change/delete anything you like, it is not supposed to suffer from upgrades.

## Use custom stylesheets only

---

Nothing prevents you from configuring your Apache server in order that requests to URL containing `css_url` be answered by serving the content of a directory different from the one corresponding to `css_path`. This way, you can directly edit the `style.css` file, and this file won't be overwritten during the next update. The drawback is that you can't use the `color_x` parameters defined in your `robot.conf/sympa.conf` file. Indeed, they are used only when parsing `css.tt2`.

## Internationalization

---

`Sympa` was originally designed as a multilingual Mailing List Manager. Even in its earliest versions, `Sympa` separated messages from the code itself, messages being stored in NLS catalogues (according to the XPG4 standard). Later a `lang` list parameter was introduced. Nowadays, `Sympa` is able to keep track of individual users' language preferences.

If you are willing to provide `Sympa` into your native language, please check the **translation howto**: <http://www.sympa.org/howtotranslate.html> [<http://www.sympa.org/howtotranslate.html>].

## Sympa internationalization

---

Every message sent by `Sympa` to users, owners and editors is outside the code, in a message catalog. These catalogs are located in the `/home/sympa/locale` directory.

To tell Sympa to use a particular message catalog, you can should set the `lang` parameter in `sympa.conf`.

## List internationalization

---

The `lang` list parameter defines the language for a list. It is currently used by *WWSympa* and to initialize users' language preferences at subscription time.

In future versions, all messages returned by Sympa concerning a list should be in the list's language.

## User internationalization

---

The user language preference is currently used by *WWSympa* only. There is no email-based command for a user to set his/her language. The language preference is initialized when the user subscribes to his/her first list. *WWSympa* allows the user to change it.

## Topics

---

*WWSympa*'s homepage shows a list of topics for classifying mailing lists. This is dynamically generated using the different lists' `topics` configuration parameters. A list may appear in multiple categories.

This parameter is different from the `msg_topic` parameter used to tag list messages.

The list of topics is defined in the `topics.conf` configuration file, located in the `/home/sympa/etc` directory. The format of this file is as follows:

```
<topic1_name>
title <topic1 title>
title.fr <topic french title>
visibility <topic1 visibility>
....
<topicn_name/subtopic_name>
title <topicn title>
title.de <topicn german title>
```

You will notice that subtopics can be used, the separator being `/`. The topic name is composed of alphanumeric (0-1a-zA-Z) or underscores (`_`). The order in which the topics are listed is respected in *WWSympa*'s homepage. The `visibility` line defines who can view the topic and subtopics. It refers to the associated `topics_visibility` authorization scenario. You will find a sample `topics.conf` in the `sample` directory; `NONE` is installed as the default.

A default topic is hard-coded in Sympa: `default`. This default topic contains all lists for which a topic has not been specified.

## Authorization scenarios

---

See [Authorization scenarios](#).

## Custom parameters

---

You can create an unlimited number of custom parameters to be used with [authorization scenarios](#), [web templates](#) and [mail templates](#).

These parameters are defined in each list configuration through the web interface by using the form in *Admin* → *Edit list config* → *Miscellaneous* page. There, you add a parameter in the **custom parameters (custom\_vars)** section.

The **var name** field corresponds to your custom parameter name, the **var value** field corresponds to your custom parameter value.

You can later access this parameter:

- in scenarios : with the syntax `[custom_vars→your_custom_var_name]`
- in web or mail templates : with the syntax `custom_vars.your_custom_var_name`

### Example

You define a custom parameter with the following values:

- var name : `sisterList`
- var value : `math-teachers`

You can use it as follows:

- in scenarios : with the syntax `[custom_vars→sisterList]`, which will correspond to “math-teachers”
- in web or mail templates : with the syntax `custom_vars.sisterList`, which will correspond to “math-teachers”

## Loop detection

---

Sympa uses multiple heuristics to avoid loops in Mailing lists.

First, it rejects messages coming from a robot (as indicated by the `From:` and other header fields) and messages containing commands.

Second, every message sent by Sympa includes an `X-Loop` header field set to the listname. If the message comes back, Sympa will detect that it has already been sent (unless `X-Loop` header fields have been erased).

Third, Sympa keeps track of Message IDs and will refuse to send multiple messages with the same message ID to the same mailing list.

Finally, Sympa detect loops arising from command reports (i.e. sympa-generated replies to commands). This sort of loop might occur as follows:

1. X sends a command to Sympa
2. Sympa sends a command report to X
3. X has installed a home-made vacation program replying to messages
4. Sympa processes the reply and sends a report

## 5. Looping to step 3

Sympa keeps track (via an internal counter) of reports sent to any particular address. The loop detection algorithm is:

- increment the counter
- If we are within the sampling period (as defined by the `loop_command_sampling_delay` parameter)
  - If the counter exceeds the `loop_command_max` parameter, then do not send the report, and notify listmasters
  - Else, start a new sampling period and reinitialize the counter, i.e. multiply it by the `loop_command_decrease_factor` parameter

## Tasks

---

A task is a sequence of simple actions which realize a complex routine. It is executed in the background by the task manager daemon and allows listmasters to automate the processing of recurring tasks. For example, a task sends to a list's subscribers a message to remind them of their subscription on a yearly basis.

A task is created with a task model. It is a text file which describes a sequence of simple actions. It may have different versions (for instance reminding subscribers every year or semester). A task model file name has the following format: `<model name>.<model version>.task`. For instance `remind.annual.task` or `remind.semestrial.task`.

Sympa provides several task models stored in the `/home/sympa/bin/etc/global_task_models` and `/home/sympa/bin/etc/list_task_models` directories. Others can be designed by listmasters.

A task can be either global or related to a list.

## List task creation

---

You define in the list configuration file the model and the version you want to use (see [list task parameters](#)). Then the task manager daemon will automatically create the task by looking for the appropriate model file in different directories in the following order:

1. `/home/sympa/exp1/" <list name>" /;`
2. `/home/sympa/etc/list_task_models/;`
3. `/home/sympa/bin/etc/list_task_models/.`

See also [List model files](#) to know more about standard list models provided with Sympa.

## Global task creation

---

The task manager daemon checks if a version of a global task model is specified in `sympa.conf` and then creates a task as soon as it finds the model file by looking in different directories in the following order:

1. `/home/sympa/etc/global_task_models/;`
2. `/home/sympa/bin/etc/global_task_models/.`

## Model file format

---

Model files are composed of comments, labels, references, variables, date values and commands. All those syntactical elements are composed of alphanumeric (0-9a-zA-Z) and underscores (\_).

- Comment lines begin by '#' and are not interpreted by the task manager.
- Label lines begin by '/' and are used by the next command (see below).
- References are enclosed between brackets '[]'. They refer to a value depending on the object of the task (for instance [list→name]). Those variables are instantiated when a task file is created from a model file. The list of available variables is the same as for templates (see [List template files](#)) plus [creation\_date] (see below).
- Variables store results of some commands and are parameters for others. Their names begin with '@'.
- A date value may be written in two ways:
  - Absolute dates follow the format: xxxxYxxMxxDxxHxxMin. Y is the year, M the month (1-12), D the day (1-28|30|31, leap-years are not managed), H the hour (0-23), Min the minute (0-59). H and Min are optional. For instance, 2001y12m4d44min is the 4th of December 2001 at 00h44.
  - Relative dates use the [creation\_date] or [execution\_date] references. [creation\_date] is the date when the task file is created, [execution\_date] when the command line is executed. A duration may follow with the '+' or '-' operators. The duration is expressed like an absolute date whose all parameters are optional. Examples: [creation\_date], [execution\_date]+1y, [execution\_date]-6m4d.
- Command arguments are separated by commas and enclosed between parenthesis '()'.

Here is the list of the currently available commands:

- stop ()  
Stops the execution of the task and deletes the task file.
- next (<date value>, <label>)  
Stops the execution. The task will go on at the date value and begin at the label line.
- <@deleted\_users> = delete\_subs (@<user\_selection>)  
Deletes the @user\_selection email list and stores user emails successfully deleted in @deleted\_users.
- send\_msg (<@user\_selection>, <template>)  
Sends the template message to emails stored in @user\_selection.
- @user\_selection = select\_subs (<condition>)  
Stores emails which match the condition in @user\_selection. See [Authorization Scenarios](#) to know how to write conditions. Only available for list models.
- create (global | list (<list name>), <model type>, <model>)  
Creates a task for object with model file ~model type.model.task.
- chk\_cert\_expiration (<template>, <date value>)  
Sends the template message to emails whose certificate has expired or will expire before the date value.
- update\_crl (<file name>, <date value>)  
Updates certificate revocation lists (CRL) which are expired or will expire before the date value. The file stores the CRL's URLs.
- purge\_orphan\_bounces ()  
Cleans bounces by removing the unsubscribed users' archive.
- eval\_bouncers ()  
Evaluates all bouncing users of all lists and gives them a score from 0 to 100. (0 is for non bouncing users and 100

is for users who should be removed).

- `process_bouncers()`

Executes actions defined in list configuration on all bouncing users, according to their score.

Model files may have a scenario-like title line at the beginning.

When you change a configuration file by hand, and a task parameter is created or modified, it is up to you to remove existing task files in the `task/` spool if needed. Task file names have the following format:

`<date>.<label>.<model name>.<list name | global>` where:

- `date` represents the time when the task is executed, it is an epoch date;
- `label` states where in the task file the execution begins. If empty, it starts at the beginning.

## Model file examples

---

- `remind.annual.task;`
- `expire.annual.task;`
- `crl_update.daily.task.`

`<code>`

```
title.gettext daily update of the certificate revocation list
/ACTION
update_crl (CA_list, [execution_date]+1d)
next ([execution_date] + 1d, ACTION)
```

`</CODE>`

Edit

## Mailing list definition

---

This chapter describes what a mailing list is made of within a Sympa environment.

## Mail aliases

---

See list aliases section, [Mail aliases](#).

## List configuration file

---

The configuration file for the `mylist` list is named `/home/sympa/expl/my.domain.org/mylist/config` (or `/home/sympa/expl/mylist/config` if no virtual host is defined). Sympa reloads it into memory whenever this file has changed on disk. The file can either be edited via the web interface or directly via your favourite text editor.

If you have set the `cache_list_config` `sympa.conf` parameter (see `cache_list_config`), a binary version of

the config (/home/sympa/expl/my.domain.org/mylist/config.bin is maintained to allow a faster restart of daemons (this is especially useful for sites managing lots of lists).

Be careful to provide read access for Sympa user to this file!

You will find a few configuration files in the sample directory.

List configuration parameters are described in the list creation section, [List configuration parameters](#).

## Examples of configuration files

---

This first example is for a list open to everyone:

```
subject First example (an open list)

visibility noconceal

owner
email Pierre.David@prism.uvsq.fr

send public

review public
```

The second example is for a moderated list with authenticated subscription:

```
subject Second example (a moderated list)

visibility noconceal

owner
email moi@ici.fr

editor
email big.prof@ailleurs.edu

send editor

subscribe auth

review owner

reply_to_header
value list

cookie 142cleliste
```

The third example is for a moderated list, with subscription controlled by the owner, and running in digest mode. Subscribers who are in digest mode receive messages on Mondays and Thursdays.

```
owner
email moi@ici.fr

editor
email prof@ailleurs.edu

send editor
```

```
subscribe owner
review owner
reply_to_header
value list

digest 1,4 12:00
```

## Subscribers file

---

**Be careful:** since version 3.3.6 of Sympa, a RDBMS is required for internal data storage. Flat files should not be use anymore except for testing purpose. Sympa will not use these files if the list is configured with `include`, `database` or `user_data_source`.

The `/home/sympa/expl/mylist/subscribers` file is automatically created and populated. It contains information about list subscribers. It is not advisable to edit this file. Main parameters are:

- `email address`  
Email address of the subscriber.
- `gecos data`  
Information about the subscriber (last name, first name, etc.) This parameter is optional at subscription time.
- `reception | nomail | digest | summary | notice | txt | html | urlize | not_me`  
Special delivery modes which the subscriber may select. Special modes can be either `nomail`, `digest`, `summary`, `notice`, `txt`, `html`, `urlize` and `not_me`. In normal delivery mode, the delivery attribute for a subscriber is not displayed. In this mode, subscription to message topics is available. See the [SET LISTNAME SUMMARY](#) command, the [SET LISTNAME NOMAIL](#) command and the `digest` parameter.
- `visibility conceal`  
Special mode which allows the subscriber to remain invisible when a `REVIEW` command is issued for the list. If this parameter is not declared, the subscriber will be visible for `REVIEW`. Note: this option does not affect the results of a `REVIEW` command issued by an owner. See the [SET LISTNAME CONCEAL](#) command for details.

## Info file

---

`/home/sympa/expl/mylist/info` should contain a detailed text description of the list, to be displayed by the `INFO` command. It can also be referenced from template files for service messages.

## Homepage file

---

`/home/sympa/expl/mylist/homepage` is the HTML text on the *WWSympa* info page for the list.

## Data inclusion file

---

Sympa will use these files only if the list is configured in `include2 user_data_source` mode. Every file has the `.incl` extension. Moreover, these files must be declared in paragraphs `owner_include` or

`editor_include` in the list configuration file without the `.incl` extension (see [List configuration parameters](#)). This files can be template files.

Sympa looks for them in the following order:

1. `/home/sympa/expl/mylist/data_sources/<file>.incl;`
2. `/home/sympa/etc/data_sources/<file>.incl;`
3. `/home/sympa/etc/my.domain.org/data_sources/<file>.incl.`

These files are used by Sympa to load administrative data in a relational database: owners or editors are defined *intensively* (definition of criteria owners or editors must satisfy). Includes can be performed by extracting email addresses using an SQL or LDAP query, or by including other mailing lists.

A data inclusion file is made of paragraphs separated by blank lines and introduced by a keyword. Valid paragraphs are `include_file`, `include_list`, `include_remote_sympa_list`, `include_sql_query` and `include_ldap_query`. They are described in the [List configuration parameters](#) chapter.

When this file is a template, the variables used are array elements (`param` array). This array is instantiated by values contained in the subparameter `source_parameter` of `owner_include` or `editor_include`.

Example:

- in the list configuration file:

```
owner_include
source myfile
source_parameters mysql,rennes1,stduser,mysecret,studentbody,student
```

- in `myfile.incl`:

```
include_sql_query
db_type [% param.0 %]
host sqlserv.admin.univ-[% param.1 %].fr
user [% param.2 %]
passwd [% param.3 %]
    db_name [% param.4 %]
sql_query SELECT DISTINCT email FROM [% param.5 %]
```

- resulting data inclusion file:

```
include_sql_query
db_type mysql
host sqlserv.admin.univ-rennes1.fr
    user stduser
    passwd mysecret
    db_name studentbody
    sql_query SELECT DISTINCT email FROM student
```

## List template files

---

These files are used by Sympa as service messages for commands such as `SUB`, `ADD`, `SIG`, `DEL`, `REJECT`. These files are interpreted (parsed) by Sympa and respect the template format; every file has the `.tt2` extension. See [Template](#)

## file format.

Sympa looks for these files in the following order:

1. /home/sympa/expl/mylist/mail\_tt2/<file>.tt2;
2. /home/sympa/etc/mail\_tt2/<file>.tt2;
3. /home/sympa/bin/etc/mail\_tt2/<file>.tt2.

If the file starts with a `From:` line, it is considered to be a full message and will be sent (after parsing) without the addition of SMTP headers. Otherwise the file is treated as a text/plain message body.

The following variables may be used in list template files:

- [% conf.email %]: Sympa email address local part;
- [% conf.domain %]: Sympa's robot domain name;
- [% conf.sympa %]: Sympa's complete email address;
- [% conf.wwsympa\_url %]: *WWSympa*'s root URL;
- [% conf.listmaster %]: listmasters' email addresses;
- [% list.name %]: list name;
- [% list.host %]: list hostname (default is Sympa robot domain name);
- [% list.lang %]: list language;
- [% list.subject %]: list subject;
- [% list.owner %]: list owners table hash;
- [% user.email %]: user email address;
- [% user.gecos %]: user geccos field (usually his/her name);
- [% user.password %]: user password;
- [% user.lang %]: user language;
- [% execution\_date %]: the date when the scenario is executed.

You may also dynamically include a file from a template using the [% INSERT %] directive.

Example:

```
Dear [% user.email %],

Welcome to list [% list.name %]@[% list.host %].

Presentation of the list:
[% INSERT 'info' %]

The owners of [% list.name %] are:
[% FOREACH ow = list.owner %]
  [% ow.value.gecos %] <[% ow.value.email %]>
[% END %]
```

---

welcome.tt2

Sympa will send a welcome message for every subscription. The welcome message can be customized for each list.

## bye.tt2

---

Sympa will send a farewell message for each `SIGNOFF` mail command received.

## removed.tt2

---

This message is sent to users who have been deleted (using the `DELETE` command) from the list by the list owners.

## reject.tt2

---

Sympa will send a reject message to the senders of messages rejected by the list editors. If they prefix their `REJECT` with the keyword `QUIET`, the reject message will not be sent.

## invite.tt2

---

This message is sent to users who have been invited (using the `INVITE` command) to subscribe to a list.

You may use additional variables

- [% requested\_by %]: email of the person who sent the `INVITE` command;
- [% url %]: the `mailto:` URL to subscribe to the list.

## remind.tt2

---

This file contains a message sent to each subscriber when one of the list owners sends the `REMIND` command.

## summary.tt2

---

Template for summaries (reception mode close to digest), see the `SET LISTNAME SUMMARY` command.

## list\_aliases.tt2

---

Template that defines list mail aliases. It is used by the `alias_manager` script.

## Stats file

---

`/home/sympa/exp1/mylist/stats` is a text file containing statistics about the list. Data are numerics separated by white space within a single line:

- number of messages sent, used to generate X-sequence headers;

- number of messages X number of recipients;
- number of bytes X number of messages;
- number of bytes X number of messages X number of recipients;
- number of subscribers;
- last update date (epoch format) of the subscribers cache in DB, used by lists in **include2** mode only.

## List model files

---

These files are used by Sympa to create task files. They are interpreted (parsed) by the task manager and respect the task format. See [Tasks](#).

### remind.annual.task

---

Every year Sympa will send a message (the template `remind.tt2`) to all subscribers of the list to remind them of their subscription.

### expire.annual.task

---

Every month Sympa will delete subscribers older than one year who haven't answered two warning messages.

## Message header and footer

---

You may create the `/home/sympa/expl/mylist/message.header` and `/home/sympa/expl/mylist/message.footer` files. Their content is added, respectively at the beginning and at the end of each message before the distribution process. You may also include the content-type of the appended part (when `footer_type` list parameter is set to `mime`) by renaming the files to `message.header.mime` and `message.footer.mime`.

The `footer_type` list parameter defines whether to attach the header/footer content as a MIME part (except for multipart/alternative messages), or to append them to the message body (for text/plain messages).

Under certain circumstances, Sympa will NOT add headers/footers, here is its algorithm:

```
if message is not multipart/signed
  if footer_type==append
    if message is text/plain
      append header/footer to it
    else if message is multipart AND first part is text/plain
      append header/footer to first part

  if footer_type==mime
    if message is not multipart/alternative
      add header/footer as a new MIME part
```

## Archive directory

---

The `/home/sympa/expl/mylist/archives/` directory contains the messages archived for lists which are archived; see [archive](#). The files are named in accordance with the archiving frequency defined by the `archive` parameter.

Edit

## List creation, editing and removal

---

The list creation can be done in two ways, according to listmaster needs:

- family instantiation, to create and manage a large number of related lists. In this case, lists are linked to their family all along their life (moreover, you can let Sympa automatically create lists when needed. See [Automatic list creation](#)).
- command line creation of individual list with `sympa.pl` or on the web interface according to privileges defined by listmasters. In this case, lists are free from their creation model.

Management of mailing lists by list owners is usually done through the web interface: when a list is created, whatever its status (`pending` or `open`), the owners can use *WWSympa* administration features to modify list parameters, to edit the welcome message, and so on.

*WWSympa* keeps logs of the creation and all modifications to a list as part of the list's `config` file (old configuration files are archived). A complete installation requires some careful planning, although default values should be acceptable for most sites.

## List creation

---

Mailing lists can have many different uses. Sympa offers a wide choice of parameters to adapt a list behavior to different situations. Users might have difficulty selecting all the correct parameters to make the list configuration, so instead of selecting each parameters, list configuration is made with a list profile. This is an almost complete list configuration, but with a number of unspecified fields (such as owner email) to be replaced by Sympa at list creation time. It is easy to create new list templates by modifying existing ones.

*Please note that contributions to the distribution are welcome to complete the set of existing templates... 😊*

## Data for list creation

---

To create a list, some data concerning list parameters are required:

- **listname** : name of the list;
- **subject**: subject of the list (a short description);
- **owner(s)**: by static definition and/or dynamic definition. In case of static definition, the parameter `owner` and its subparameter `email` are required. For dynamic definition, the parameter `owner_include` and its subparameter `source` are required, indicating source file of data inclusion;
- **list creation template**: the typical list profile.

in addition to these required data, provided values are assigned to vars being in the list creation template. Then the result is the list configuration file:

On the web interface, these data are given by the list creator in the web form. On command line, these data are given through an XML file.

## XML file format

---

The XML file provides information on:

- the list name;
- values to assign vars in the list creation template;
- the list description in order to be written in the list file information;
- the name of the list creation template (only for list creation on command line with `sympa.pl`; in a family context, the template is specified by the family name).

Here is an example of XML document that you can map with the following example of list creation template.:

```
<?xml version="1.0" ?>
<list>
  <listname>example</listname>
  <type>my_profile</type>
  <subject>a list example</subject>
  <description/>
  <status>open</status>
  <shared_edit>editor</shared_edit>
  <shared_read>private</shared_read>
  <language>fr</language>
  <owner multiple="1">
    <email>serge.aumont@cru.fr</email>
    <gecos>C.R.U.</gecos>
  </owner>
  <owner multiple="1">
    <email>olivier.salaun@cru.fr</email>
  </owner>
  <owner_include multiple="1">
    <source>my_file</source>
  </owner_include>
  <sql>
    <type>oracle</type>
    <host>sqlserv.admin.univ-x.fr</host>
    <user>stdutilisateur</user>
    <pwd>monsecret</pwd>
    <name>les_etudiants</name>
    <query>SELECT DISTINCT email FROM etudiant</query>
  </sql>
</list>

subject [% subject %]

status [% status %]

[% IF topic %]
topics [% topic %]

[% END %]
visibility noconceal

send privateoreditorkey

Web_archive
  access public

subscribe open_notify
```

```

shared_doc
  d_edit [% shared_edit %]
  d_read [% shared_read %]

lang [% language %]

[% FOREACH o = owner %]
owner
  email [% o.email %]
  profile privileged
  [% IF o.gecos %]
  geccos [% o.gecos %]
  [% END %]

[% END %]
[% IF moderator %]
  [% FOREACH m = moderator %]
editor
  email [% m.email %]

  [% END %]
[% END %]

[% IF sql %]
include_sql_query
  db_type [% sql.type %]
  host [% sql.host %]
  user [% sql.user %]
  passwd [% sql.pwd %]
  db_name [% sql.name %]
  sql_query [% sql.query %]

[% END %]
ttl 360

```

The XML file format should comply with the following rules:

- The root element is `<list>`.
- One XML element is mandatory: `<listname>` contains the name of the list. That does not exclude mandatory parameters for list creation ("`listname, subject,owner.email` and/or `owner_include.source`").
- `<type>`: this element contains the name of template list creation, it is used for list creation on command line with `sympa.pl`. In a family context, this element is no used.
- `<description>`: the text contained in this element is written in list `info` file (it can be a CDATA section).
- For other elements, the name is the name of the var to assign in the list creation template.
- Each element concerning multiple parameters must have the `multiple` attribute set to 1, example: `<owner multiple="1">`
- For composed and multiple parameters, sub-elements are used. Example for the `owner` parameter: `<email>` and `<gecos>` elements are contained in the `<owner>` element. An element can only have homogeneous content.
- A list requires at least one owner, defined in the XML input file with one of the following elements:
  - `<owner multiple="1"> <email> ... </email> </owner>`
  - `<owner_include multiple="1"> <source> ... </source> </owner_include>`

## List families

---

See chapter [Lists families](#).

## List creation on command line with `sympa.pl`

---

This way to create lists is independent of family.

Here is a sample command to create one list:

```
sympa.pl -create_list -robot my.domain.org-input_file /path/to/my_file.xml
```

The list is created under the `my_robot` robot and the list is described in the file `my_file.xml`. The XML file is described before, see [XML file format](#).

By default, the status of the list created is `open`.

### Typical list profile (list template creation)

The list creator has to choose a profile for the list and put its name in the XML element `<type>`.

List profiles are stored in `/home/sympa/etc/create_list_templates` or in `/home/sympa/bin/etc/create_list_templates` (default of `distrib`).

You might want to hide or modify profiles (not useful, or dangerous for your site). If a profile exists both in the local site directory `/home/sympa/etc/create_list_templates` and in the `/home/sympa/bin/etc/create_list_templates` directory, then the local profile will be used by *WWSympa*.

## Creating and editing mailing lists using the Web

---

The management of mailing lists is based on a strict definition of privileges which pertain respectively to the listmaster, to the main list owner, and to basic list owners. The goal is to allow each listmaster to define who can create lists, and which parameters may be set by owners.

### List creation on the web interface

---

Listmasters are responsible for validating new mailing lists and, depending on the configuration chosen, might be the only ones who can fill out the create list form. The listmaster is defined in `sympa.conf` and others are defined at the virtual host level. By default, any authenticated user can request a list creation, but newly created lists are then validated by the listmaster.

The list rejection message and list creation notification message are both templates you can customize (`list_rejected.tt2` and `list_created.tt2`).

### Who can create lists on the web interface

---

This is defined by the `create_list` `sympa.conf` parameter. This parameter refers to a `create_list` authorization scenario. It will determine whether the `create list` button is displayed and whether list creation requires a listmaster

confirmation.

The authorization scenario can accept any condition concerning the [sender] (i.e. *WWSympa* user), and it returns `reject`, `do_it` or `listmaster` as an action.

Only in cases where a user is authorized by the `create_list` authorization scenario will the `create` button be available in the main menu. If the scenario returns `do_it`, the list will be created and installed. If the scenario returns `listmaster`, the user is allowed to create a list, but the list is created with the `pending` status, which means that only the list owner may view or use it. The listmaster will need to open the list of pending lists using the `pending list` button in the `server admin` menu in order to install or refuse a pending list.

## Typical list profile and web interface

---

As on command line creation, the list creator has to choose a list profile and to fill in the owner's email and the list subject together with a short description. But in this case, you do not need any XML file. Concerning these typical list profiles, they are described before, see [Typical list profile \(list template creation\)](#). You can check available profiles. On the web interface, another way to control publicly available profiles is to edit the `create_list.conf` file (the default for this file is in the `/home/sympa/bin/etc` directory, and you may create your own customized version in `/home/sympa/etc`). This file controls which of the available list templates are to be displayed. Example:

```
# Do not allow the public_anonymous profile
public_anonymous hidden
* read
```

## List editing

---

For each parameter, you may specify (through the `/home/sympa/etc/edit_list.conf` configuration file) who has the right to edit the parameter concerned; the default `/home/sympa/bin/etc/edit_list.conf` is reasonably safe.

Each line is a set of 3 field.

```
<Parameter> <Population> <Privilege>
<Population>: <listmaster|privileged_owner|owner>
<Privilege>: <write|read|hidden>
```

**Parameter** can be any list config parameter or the name of a template (thus controlling the edition of the template through the *customize* web admin feature. You can refer to a subentry of a structured list parameter using the '.' as a separator (examples: **owner.email** or **web\_archive.quota**). **default** is a reserved parameter name that means *any other parameter*.

There is no hierarchical relationship between populations in this configuration file. You need to explicitly list populations.

For example, `listmaster` will not match rules referring to `owner` or `privileged_owner`.

Examples:

```

# only listmaster can edit user_data_source, priority, ...
user_data_source listmaster write

priority      owner,privileged_owner      read
priority      listmaster                write

# only privileged owner can modify editor parameter, send, ...
editor privileged_owner write

send          owner                    read
send          privileged_owner,listmaster write

# other parameters can be changed by simple owners
default       owner                    write

```

Privileged owners are defined in the list's `config` file as follows:

```

owner
email owners.email@foo.bar
profile privileged

```

The following rules are hard coded in *WWSympa*:

- Only the listmaster can edit the `profile privileged` owner attribute.
- Owners can edit their own attributes (except `profile` and `email`).
- The person creating a new list becomes its privileged owner.
- Privileged owners can edit any `gecos/reception/info` attribute of any owner.
- Privileged owners can edit owners' email addresses (but not privileged owners' email addresses).

Sympa aims at defining two levels of trust for owners (some being entitled simply to edit secondary parameters such as `custom_subject`, others having the right to manage more important parameters), while leaving control of crucial parameters (such as the list of privileged owners and `user_data_sources`) in the hands of the listmaster. Consequently, privileged owners can change owners' emails, but they cannot grant the responsibility of list management to others without referring to the listmaster.

Concerning list editing in a family context, see [editing list parameters in a family context](#).

## Removing a list

---

You can remove a list either from the command line or by using the web interface.

`sympa.pl` provides an option to remove a mailing list, see the example below:

```
sympa.pl -remove_list=mylist@mydomain
```

Privileged owners can remove a mailing list through the list administration part of the web interface. Removing the mailing list consists in removing its subscribers from the database and setting its status to *closed*. Once removed, the list can still be restored by the listmaster; list members are saved in a `subscribers.closed.dump` file.

Edit

## List families

---

A list can have from three up to dozens of parameters. Some listmasters need to create a set of lists that have the same profile. In order to simplify the apprehension of these parameters, list families define a lists typology. Families provide a new level for defaults: in the past, defaults in Sympa were global and most sites using Sympa needed multiple defaults for different groups of lists. Moreover, families allow listmasters to delegate a part of configuration list to owners, in a controlled way according to family properties. Distribution will provide defaults families.

## Family concept

---

A family provides a model for all of its lists. It is specified by the following characteristics:

- a list creation template providing a common profile for each list configuration file;
- a degree of independence between the lists and the family: list parameters editing rights and constraints on these parameters can be `free` (no constraint), `controlled` (a set of available values defined for these parameters) or `fixed` (the value for the parameter is imposed by the family). That prevents lists from diverging from the original and it allows list owner customizations in a controlled way;
- a filiation kept between lists and family all along the list life: family modifications are applied on lists while keeping listowners customizations.

Here is a list of operations performed on a family:

- definition: definition of the list creation template, the degree of independence and family customizations;
- instantiation: list creation or modifications of existing lists while respecting family properties. The set of data defining the lists is an XML document;
- modification: modification of family properties. The modification is effective at the next instantiation time and has consequences on every list;
- closure: closure of each list;
- adding a list to a family;
- closing a family list;
- modifying a family list.

## Using family

---

### Definition

---

Families can be defined at the robot level, at the site level or on the distribution level (where default families are provided). So, you have to create a sub directory named after the family's name in a `families` directory:

Examples:

```
/home/sympa/etc/families/my_family  
/home/sympa/etc/my_robot/families/my_family
```

In this directory, you must provide the following files:

- `config.tt2` (mandatory);
- `param_constraint.conf` (mandatory);

- edit\_list.conf;
- customizable files.

## config.tt2

This is a list creation template, this file is mandatory. It provides default values for parameters. This file is an almost complete list configuration, with a number of missing fields (such as owner email) to be replaced by data obtained at the time of family instantiation. It is easy to create new list templates by modifying existing ones. See [List template files](#) and [Template file format](#).

Example:

```

subject [% subject %]

status [% status %]

[% IF topic %]
topics [% topic %]

[% END %]
visibility noconceal

send privateeditorkey

web_archive
  access public

subscribe open_notify

shared_doc
  d_edit [% shared_edit %]
  d_read [% shared_read %]

lang [% language %]

[% FOREACH o = owner %]
owner
  email [% o.email %]
  profile privileged
  [% IF o.gecos %]
  geccos [% o.gecos %]
  [% END %]

[% END %]
[% IF moderator %]
  [% FOREACH m = moderator %]
editor
  email [% m.email %]

  [% END %]
[% END %]

[% IF sql %]
include_sql_query
  db_type [% sql.type %]
  host [% sql.host %]
  user [% sql.user %]
  passwd [% sql.pwd %]
  db_name [% sql.name %]
  sql_query [% sql.query %]

[% END %]
ttl 360

```

## param\_constraint.conf

This file is mandatory. It defines constraints on parameters. There are three kinds of constraints:

- **free parameters:** no constraint on these parameters, they are not written in the `param_constraint.conf` file.
- **controlled parameters:** these parameters must select their values in a set of available values indicated in the `param_constraint.conf` file.
- **fixed parameters:** these parameters must have the imposed value indicated in the `param_constraint.conf` file.

The parameters constraints will be checked at every list loading.

**WARNING:** Some parameters cannot be constrained, they are: `msg_topic.keywords` (see [msg-topic](#)), `owner_include.source_parameter` (see [owner include](#)) and `editor_include.source_parameter` (see [editor include](#)). About `digest` parameter (see [digest](#)), only `days` can be constrained.

Example:

```
lang                fr,us
archive.period      days,week,month
visibility           conceal,noconceal
shared_doc.d_read   public
shared_doc.d_edit   editor
```

## edit\_list.conf

This is an optional file. It defines which parameters/files are editable by owners. See [List editing](#). If the family does not have this file, Sympa will look for the one defined on robot level, server site level or distribution level (this file already exists without family context).

Note that by default, the `family_name` parameter is not writable, you should not change this editing right.

## customizable files

Families provide a new level of customization for scenarios (see [Authorization scenarios](#)), templates for service messages (see [Site template files](#)) and templates for web pages (see [Web template files](#)). Sympa looks for these files in the following level order: list, family, robot, server site or distribution.

Example of custom hierarchy:

```
/home/sympa/etc/families/myfamily/mail_tt2/
/home/sympa/etc/families/myfamily/mail_tt2/bye.tt2
/home/sympa/etc/families/myfamily/mail_tt2/welcome.tt2
```

## Instantiation

---

Instantiation allows to generate lists. You must provide an XML file made of list descriptions, the root element being `family` and which is only composed of `list` elements. List elements are described in section [XML file format](#). Each list is described by the set of values for affectation list parameters.

Here is a sample command to instantiate a family:

```
sympa.pl --instantiate\_family my_family --robot \samplerobot --input\_file /path/to/my\_file.xml
```

This means lists that belong to family `my_family` will be created under the robot `my_robot` and these lists are described in the file `my_file.xml`. Sympa will split this file into several XML files describing lists. Each list XML file is put in each list directory.

Example:

```
<?xml version="1.0" ?>
<family>
  <list>
    <listname>liste1</listname>
    <subject>a list example</subject>
    <description/>
    <status>open</status>
    <shared_edit>editor</shared_edit>
    <shared_read>private</shared_read>
    <language>fr</language>
    <owner multiple="1">
      <email>foo@cru.fr</email>
      <gecos>C.R.U.</gecos>
    </owner>
    <owner multiple="1">
      <email>foo@emnsp.fr</email>
    </owner>
    <owner_include multiple="1">
      <source>my_file</source>
    </owner_include>
    <sql>
      <type>oracle</type>
      <host>sqlserv.admin.univ-x.fr</host>
      <user>stdutilisateur</user>
      <pwd>monsecret</pwd>
      <name>les_etudiants</name>
      <query>SELECT DISTINCT email FROM etudiant</query>
    </sql>
  </list>
  <list>
    <listname>liste2</listname>
    <subject>a list example</subject>
    <description/>
    <status>open</status>
    <shared_edit>editor</shared_edit>
    <shared_read>private</shared_read>
    <language>fr</language>
    <owner multiple="1">
      <email>foo@cru.fr</email>
      <gecos>C.R.U.</gecos>
    </owner>
    <owner multiple="1">
      <email>foo@enmsp.fr</email>
    </owner>
    <owner_include multiple="1">
      <source>my_file</source>
    </owner_include>
    <sql>
      <type>oracle</type>
```

```

    <host>sqlserv.admin.univ-x.fr</host>
    <user>stdutilisateur</user>
    <pwd>monsecret</pwd>
    <name>les_etudiants</name>
    <query>SELECT DISTINCT email FROM etudiant</query>
  </sql>
</list>
  ...
</family>

```

Each instantiation describes lists. Compared with the previous instantiation, there are three cases:

- list creation: new lists described by the new instantiation;
- list modification: lists already existing but possibly changed because of changed parameters values in the XML file or because of changed family properties;
- list removal: lists no more described by the new instantiation. In this case, the listmaster must validate his choice on command line. If the list is removed, it is set in status `family_closed`, or if the list is recovered, the list XML file from the previous instantiation is got back to go on as a list modification then.

After list creation or modification, parameters constraints are checked:

- `fixed` parameter: the value must be the one imposed;
- `controlled` parameter: the value must be one of the set of available values;
- `free` parameter: there is no checking.

diagram

In case of modification (see diagram), allowed customizations can be preserved:

- (1): for all parameters modified (through the web interface), indicated in the `config_changes` file, values can be collected in the old list configuration file, according to new family properties:
  - `fixed` parameter: the value is not collected,
  - `controlled` parameter: the value is collected only if constraints are respected,
  - `free` parameter: the value is collected;
- (2): a new list configuration file is made with the new family properties;
- (3): collected values are set in the new list configuration file.

Notes:

- For each list problem (as family file error, error parameter constraint, error instantiation, etc.), the list is set in status `error_config` and listmasters are notified. Then they will have to perform any necessary action in order to put the list in use.
- For each list closure in family context, the list is set in status `family_closed` and owners are notified.
- For each overwritten list customization, owners are notified.

## Modification

---

To modify a family, you have to edit family files manually. The modification will be effective while the next instantiation.

**WARNING:** The family modification must be done just before an instantiation. Otherwise, alive lists would not respect new family properties and they would be set in status `error_config` immediately.

## Closure

---

Closes every list (installed under the indicated robot) of this family: list status is set to `family_closed`, aliases are removed and subscribers are removed from DB (a dump is created in the list directory to allow restoration of the list).

Here is a sample command to close a family:

```
sympa.pl --close_family my_family --robot \samplerobot
```

## Adding a list to a list family

---

Adds a list to the family without instantiating the whole family. The list is created as if it was created during an instantiation, under the indicated robot. The XML file describes the list and the root element is `<list>`. List elements are described in section [List creation on command line with sympy.pl](#).

Here is a sample command to add a list to a family:

```
sympa.pl --add_list my_family --robot \samplerobot --input_file /path/to/my_file.xml
```

## Removing a list from a list family

---

Closes the list installed under the indicated robot: the list status is set to `family_closed`, aliases are removed and subscribers are removed from DB (a dump is created in the list directory to allow restoring the list).

Here is a sample command to close a list family (same as an orphan list):

```
sympa.pl --close_list my_list@\samplerobot
```

## Modifying a family list

---

Modifies a family list without instantiating the whole family. The list (installed under the indicated robot) is modified as if it was modified during an instantiation. The XML file describes the list and the root element is `<list>`. List elements are described in section [List creation on command line with sympy.pl](#).

Here is a sample command to modify a list to a family:

```
sympa.pl --modify_list my_family --robot \samplerobot --input_file /path/to/my_file.xml
```

## Editing list parameters in a family context

---

According to file `edit_list.conf`, editing rights are controlled. See [List editing](#). But in a family context, constraints parameters are added to editing right as it is summarized in this array:

array

Note: in order to preserve list customization for instantiation, every parameter modified (through the web interface) is indicated in the `config_changes` file.

## Automatic list creation

---

You can benefit from the family concept to let Sympa automatically create lists for you. Let us assume that you want to open a list according to specified criteria (age, geographical location, ...) within your organization. Maybe that would result in too many lists, and many of them would never be used.

Automatic list creation allows you to define those potential lists through family parameters, but they will not be created yet. The mailing list creation is triggered when Sympa receives a message addressed to this list.

To enable automatic list creation, you will have to:

- configure your MTA to queue messages for these lists in an appropriate spool;
- define a family associated to such lists;
- configure Sympa to enable the feature.

## Configuring your MTA

---

To do so, you have to configure your MTA for it to add a custom header field to messages. The easiest way is to customize your aliases manager, so that mails for automatic lists are not delivered to the normal `queue` program, but to the `familyqueue` dedicated one. For example, you can decide that the name of those lists will start with the `auto-` pattern, so you can process them separately from other lists you are hosting.

`familyqueue` expects 2 arguments: the list name and family name (whereas the `queue` program only expects the list address).

Now let's start with a use case: we need to communicate to groups of co-workers, depending on their age and their occupation. We decide that, for example, if we need to write to all CTOs who are fifty years old, we will use the `auto-cto.50@lists.domain.com` mailing list. The occupation and age informations are stored in our LDAP directory (but of course we could use any Sympa data source: SQL, files...). We will create the `age-occupation` family.

First of all we configure our MTA to deliver mail to `'auto-*` to `familyqueue` for the `age-occupation` family.

```
/etc/postfix/main.cf
...
transport_maps = regexp:/etc/postfix/transport_regexp

/etc/postfix/transport_regexp
/^.*+owner@lists\.domain\.com$/      sympabounce:
/^auto-.*@lists\.domain\.com$/      sympafamily:
/^.*@lists\.domain\.com$/           sympafamily:

/etc/postfix/master.cf
sympa      unix      -       n       n       -       -       pipe
          flags=R user=sympa argv=/home/sympa/bin/queue ${recipient}
```

```

sympabounce unix - n n - - pipe
 flags=R user=sympa argv=/home/sympa/bin/bouncequeue ${user}
sympafamily unix - n n - - pipe
 flags=R user=sympa argv=/home/sympa/bin/familyqueue ${user} age-occupation

```

A mail sent to `auto-cto.50@lists.domain.com` will be queued to the `/home/sympa/spool/automatic` spool, defined by the `queueautomatic sympa.conf` parameter (see [queueautomatic](#)). The mail will first be processed by an instance of the `sympa.pl` process dedicated to automatic list creation, then the mail will be sent to the newly created mailing list.

## Defining the list family

We need to create the appropriate `etc/families/age-occupation/config.tt2`. All the magic comes from the TT2 language capabilities. We define on-the-fly the LDAP source, thanks to TT2 macros.

```

/home/sympa/etc/families/age-occupation/config.tt2
...
user_data_source include2

[%
occupations = {
  cto = { title=>"chief technical officer", abbr=>"CHIEF TECH OFF" },
  coo = { title=>"chief operating officer", abbr=>"CHIEF OPER OFF" },
  cio = { title=>"chief information officer", abbr=>"CHIEF INFO OFF" },
}
nemes = listname.split('-');
THROW autofamily "SYNTAX ERROR: listname must begin with 'auto-' " IF (nemes.size != 2 || nemes.0 != 'aut
tokens = nemes.1.split('\.');
THROW autofamily "SYNTAX ERROR: wrong listname syntax" IF (tokens.size != 2 || ! occupations.${tokens.0}
age = tokens.1 div 10;
%]

custom_subject [[% occupations.${tokens.0}.abbr %] OF [% tokens.1 %]]

subject Every [% tokens.1 %] years old [% occupations.${tokens.0}.title %]

include_ldap_query
attrs mail
filter (&(objectClass=inetOrgPerson)(employeeType=[% occupations.${tokens.0}.abbr %])(personAge=[% age %]
name ldap
port 389
host ldap.domain.com
passwd ldap_passwd
suffix dc=domain,dc=com
timeout 30
user cn=root,dc=domain,dc=com
scope sub
select all

```

The main variable you get is the name of the current mailing list via the `listname` variable as used in the example above.

## Configuring Sympa

Now we need to enable automatic list creation in Sympa. To do so, we have to:

- set the `automatic_list_feature` parameter to `on` and define who can create automatic lists via the `automatic_list_creation` (points to an `automatic_list_creation` scenario);

- set the `queueautomatic` `sympa.conf` parameter to the spool location where we want these messages to be stored (it has to be different from the `/home/sympa/spool/msg` spool).

You can make Sympa delete automatic lists that were created with zero list members; to do so, you should set the `automatic_list_removal` parameter to `if_empty`.

```
/home/sympa/etc/sympa.conf
...
automatic_list_feature on
automatic_list_creation public
queueautomatic /home/sympa/spool/automatic
automatic_list_removal if_empty
```

While writing your own `automatic_list_creation` scenarios, be aware that:

- when the scenario is evaluated, the list is not yet created; therefore you can not use the list-related variables;
- you can only use the `smtp` and `smime` authentication methods in scenario rules (you cannot request the `md5` challenge). Moreover, only the `do_it` and `reject` actions are available.

Now you can send message to `auto-cio.40` or `auto-cto.50`, and the lists will be created on the fly.

You will receive an 'unknown list' error if either the syntax is incorrect or the number of subscriber is zero.

Edit

## List configuration parameters

---

The configuration file is made of paragraphs separated by blank lines and introduced by a keyword.

Even though there is a very large number of possible parameters, the minimal list definition is very short. The only parameters required are `owner` (or `owner_include`) and `subject`. All other parameters have a default value.

Configuration parameters must be separated by blank lines and **BLANK LINES ONLY!**

Using the web interface the following categories are used to organize the large number of parameters :

- List definition;
- Sending/receiving setup;
- Privileges;
- Archives;
- Bounce management;
- Data sources setup;
- Others.

Edit

## List parameters: definition

---

## subject

---

`subject` *subject-of-the-list*

This parameter indicates the subject of the list, which is sent in response to the `LISTS` mail command. The subject is a free form text limited to one line.

## visibility

---

(Default value: `conceal`)

The `visibility` parameter is defined by an authorization scenario (see [Authorization scenarios](#)).

This parameter indicates whether the list should feature in the output generated in response to a `LISTS` command.

- `visibility conceal` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/visibility.conceal>])
- `visibility intranet` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/visibility.intranet>])
- `visibility noconceal` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/visibility.noconceal>])
- `visibility secret` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/visibility.secret>])

## owner

---

The `config` file contains one `owner` paragraph per owner. It concerns static owner definition. For dynamic definition, see [owner include](#).

Example:

```
owner
email serge.aumont@cru.fr
gecos C.R.U.
info Tel: 02 99 76 45 34
reception nomail
```

The list owner is usually the person who has the authorization to send `ADD` and `DELETE` commands (see [Owner commands](#)) on behalf of other users.

When the [subscribe parameter](#) specifies a restricted list, it is the owner who has the exclusive right to subscribe users, and it is therefore to the owner that `SUBSCRIBE` requests will be forwarded.

There may be several owners of a single list; in this case, each owner is declared in a paragraph starting with the `owner` keyword.

The `owner` directive is followed by one or several lines giving details regarding the owner's characteristics:

- `email address`  
Owner's e-mail address;
- `reception nomail`  
Optional attribute for an owner who does not wish to receive emails. Useful to define an owner with multiple email

addresses: they are all recognized when Sympa receives mail, but thanks to `reception nomail`, not all of these addresses need to receive administrative email from Sympa;

- `gecos data`

Public information about the owner;

- `info data`

Available since release 2.3. Private information about the owner;

- `profile privileged | normal`

Available since release 2.3.5. Profile of the owner. This is currently used to restrict access to some features of *WWSympa*, such as adding new owners to a list.

## owner\_include

---

The `config` file contains one `owner_include` paragraph per data inclusion file (see [Data inclusion file](#)). It concerns dynamic owner definition: inclusion of external data. For static owner definition and more information about owners see [par-owner](#).

Example:

```
owner_include
source myfile
source_parameters a,b,c
reception nomail
profile normal
```

The `owner_include` directive is followed by one or several lines giving details regarding the owner(s) included characteristics:

- `source myfile`

This is an mandatory field: it indicates the data inclusion file `myfile.incl`. This file can be a template. In this case, it will be interpreted with values given by subparameter `source_parameter`. Note that the `source` parameter should NOT include the `.incl` file extension; the `myfile.incl` file should be located in the `data_sources` directory.

- `source_parameters a,b,c`

It contains an enumeration of the values that will be affected to the `param` array used in the template file (see [Data inclusion file](#)). This parameter is not mandatory.

- `reception nomail`

Optional attribute for owner(s) who does not wish to receive emails.

- `profile privileged | normal`

Profile of the owner(s).

## editor

---

The `config` file contains one `editor` paragraph per moderator (or editor). It concerns static editor definition. For dynamic definition and more information about editors see [editor\\_include](#).

Example:

```
editor
email Pierre.Paul@myuniversity.edu
gecos Pierre paul (Computer center director)
```

Only the editor of a list is authorized to send messages to the list when the send is set to either `editor`, `editorkey`, or `editorkeyonly`. The `editor` parameter is also consulted in certain other cases (`privateeditorkey`).

The syntax of this directive is the same as that of the owner parameter, even when several moderators are defined.

## editor\_include

---

The `config` file contains one `editor_include` paragraph per data inclusion file (see Data inclusion file). It concerns dynamic editor definition: inclusion of external data. For static editor definition and more information about moderation see editor.

Example:

```
editor_include
reception mail
source myfile
source_parameters a,b,c
```

The syntax of this directive is the same as that of the owner\_include" parameter, even when several moderators are defined.

## topics

---

```
topics computing/internet,education/university
```

This parameter allows the classification of lists. You may define multiple topics as well as hierarchical ones. *WWSympa's* list of public lists uses this parameter. This parameter is different from the `msg_topic` parameter used to tag emails.

## host

---

(Default value: `domain robot parameter`)

```
host fully-qualified-domain-name
```

Domain name of the list, default is the robot domain name set in the related `robot.conf` file or in file `/etc/sympa.conf`.

## lang

---

(Default value: `lang robot parameter`)

Example:

```
lang en_US
```

This parameter defines the language used for the list. It is used to initialize a user's language preference; Sympa command reports are extracted from the associated message catalog.

See [Internationalization](#) for available languages.

## family\_name

---

This parameter indicates the name of the family that the list belongs to.

Example:

```
family_name my_family
```

## latest\_instantiation

---

This parameter indicates the date of the latest instantiation.

Example:

```
latest_instantiation
email joe.bar@cru.fr
date 27 jui 2004 at 09:04:38
date_epoch 1090911878
```

Edit

## send

---

(Default value: `private`)

The `send` parameter is defined by an authorization scenario (see [Authorization scenarios](#)).

This parameter specifies who can send messages to the list. Valid values for this parameter are pointers to *scenarios*.

- `send closed` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.closed>])
- `send editorkey` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.editorkey>])
- `send editorkeyonly` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.editorkeyonly>])
- `send editorkeyonlyauth` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.editorkeyonlyauth>])
- `send intranet` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.intranet>])
- `send intranetorprivate` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.intranetorprivate>])
- `send newsletter` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.newsletter>])
- `send newsletterkeyonly` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.newsletterkeyonly>])
- `send private` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.private>])

- `send private_smime` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/send.private\\_smime](http://www.sympa.org/distribution/current/src/etc/scenari/send.private_smime)])
- `send privateandeditorkey` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.privateandeditorkey>])
- `send privateandnomultipartoreditorkey` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.privateandnomultipartoreditorkey>])
- `send privatekey` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.privatekey>])
- `send privatekeyandeditorkeyonly` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.privatekeyandeditorkeyonly>])
- `send privateoreditorkey` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.privateoreditorkey>])
- `send privateorpublickey` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.privateorpublickey>])
- `send public` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.public>])
- `send public_nobcc` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/send.public\\_nobcc](http://www.sympa.org/distribution/current/src/etc/scenari/send.public_nobcc)])
- `send publickey` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.publickey>])
- `send publicnoattachment` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.publicnoattachment>])
- `send publicnomultipart` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/send.publicnomultipart>])

## digest

---

`digest` *daylist hour.minutes*

Definition of `digest` mode. If this parameter is present, subscribers can select the option of receiving messages in multipart/digest MIME format. Messages are then grouped together, and compilations of messages are sent to subscribers in accordance with the rythm selected with this parameter.

`Daylist` designates a list of days in the week in numeric format (from 0 for Sunday to 6 for Saturday), separated by commas.

Example:

```
digest 1,2,3,4,5 15:30
```

In this example, Sympa sends digests at 3:30 PM from Monday to Friday.

**WARNING:** if the sending time is too late (i.e. around midnight), Sympa may not be able to process it in time. Therefore do not set a digest time later than 23:00.

N.B.: In family context, `digest` can be constrained only on days.

## digest\_max\_size

---

(Default value: 25)

Maximum number of messages in a digest. If the number of messages exceeds this limit, then multiple digest messages are sent to each recipient.

## available\_user\_options

---

The `available_user_options` parameter starts a paragraph to define available options for the subscribers of the list.

- `reception modelist`

(Default value: `reception mail,notice,digest,summary,nomail,txt,html,urlize,not_me`)

`modelist` is a list of modes (mail, notice, digest, summary, nomail, txt,html, urlize, not\_me, topics), separated by commas. Only these modes will be allowed for the subscribers of the list. If a subscriber has a delivery mode other than those specified in that list, Sympa uses the mode specified in the `default_user_options` paragraph.

Example:

```
## Nomail reception mode is not available
available_user_options
reception    digest,mail
```

## default\_user\_options

---

The `default_user_options` parameter starts a paragraph to define a default profile for the subscribers of the list.

- `reception notice | digest | summary | nomail | mail`

Mail reception mode.

- `visibility conceal | noconceal`

Visibility of the subscriber with the REVIEW command.

Example:

```
default_user_options
reception    digest
visibility    noconceal
```

## msg\_topic

---

The `msg_topic` parameter starts a paragraph to define a message topic used to tag a message. For each message topic, you have to define a new paragraph (see [Message topics](#)).

Example:

```
msg_topic
name os
keywords linux,mac-os,nt,xp
title Operating System
```

Parameters `msg_topic.name` and `msg_topic.title` are mandatory. `msg_topic.title` is used on the web interface (other is not allowed for the `msg_topic.name` parameter). The `msg_topic.keywords` parameter allows to select automatically message topic by searching keywords in the message.

N.B.: in a family context, `msg_topic.keywords` parameter is not mandatory.

## msg\_topic\_keywords\_apply\_on

The `msg_topic_keywords_apply_on` parameter defines which part of the message is used to perform automatic tagging (see [Message topics](#)).

Example:

```
msg_topic_key_apply_on subject
```

Its values can be: `subject`, `body` and `subject_and_body`.

## msg\_topic\_tagging

The `msg_topic_tagging` parameter indicates if tagging is optional or required for a list. (See [Message topics](#))

Example:

```
msg_topic_tagging optional
```

Its values can be “optional“, “required\_moderator” or “required\_sender“. When topic is required, a tagging request is sent to the list moderator or to the message sender depending of this parameter value.

## reply\_to\_header

The `reply_to_header` parameter starts a paragraph defining what Sympa will place in the Reply-To: SMTP header field of the messages it distributes.

- `value sender | list | all | other_email` (Default value: `sender`)

This parameter indicates whether the Reply-To: field should indicate the sender of the message (`sender`), the list itself (`list`), both list and sender (`all`) or an arbitrary email address (defined by the `other_email` parameter).

Note: it is inadvisable to change this parameter, and particularly inadvisable to set it to `list`. Experience has shown it to be almost inevitable that users, mistakenly believing that they are replying only to the sender, will send private messages to a list. This can lead, at the very least, to embarrassment, and sometimes to more serious consequences.

- `other_email an_email_address`

If value was set to `other_email`, this parameter indicates the email address to be used.

- `apply respect | forced` (Default value: `respect`).

The default is to respect (preserve) the existing Reply-To: SMTP header field in incoming messages. If set to

forced, the Reply-To: SMTP header field will be overwritten.

Example:

```
reply_to_header
value other_email
other_email listowner@my.domain
apply forced
```

## anonymous\_sender

---

`anonymous_sender` *value*

If this parameter is set for a list, all messages distributed through the list are made anonymous. SMTP From: headers in distributed messages are altered to contain the value of the `anonymous_sender` parameter. Various other fields are removed (Received:, Reply-To:, Sender:, X-Sender:, Message-id:, Resent-From:).

## custom\_header

---

`custom_header` *header-field: value*

This parameter is optional. The headers specified will be added to the headers of messages distributed via the list. As of release 1.2.2 of Sympa, it is possible to put several custom header lines in the configuration file at the same time.

Example:

```
custom_header X-url: http://www.cru.fr/listes/apropos/sedesabonner.faq.html
```

## rfc2369\_header\_fields

---

`rfc2369_header_fields` *help,archive* (Default value: `rfc2369_header_fields` `sympa.conf` parameter)

RFC2369 compliant header fields (List-xxx) to be added to distributed messages. These header-fields should be implemented by MUA's, adding menus.

## custom\_subject

---

`custom_subject` *value*

This parameter is optional. It specifies a string which is added to the subject of distributed messages (intended to help users who do not use automatic tools to sort incoming messages). This string will be surrounded by '[' characters.

The custom subject can also refer to list variables ([list->sequence] in the example below).

Example:

```
custom_subject sympa-users
```

Other example:

```
custom_subject newsletter num [list->sequence]
```

## footer\_type

---

footer\_type mime | append (Default value: mime)

This parameter is optional. List owners may decide to add message headers or footers to messages sent through the list. This parameter defines the way a footer/header is added to a message.

- `footer_type mime`  
The default value. Sympa will add the footer/header as a new MIME part. If the message is in multipart/alternative format, no action is taken (since this would require another level of MIME encapsulation).
- `footer_type append`  
Sympa will not create new MIME parts, but will try to append the header/footer to the body of the message. `/home/sympa/exp1/mylist/message.footer.mime` will be ignored. Headers/footers may be appended to text/plain messages only.

Edit

## info

---

The scenario definition of who can view the info page of a list.

## subscribe

---

(Default value: open)

The `subscribe` parameter is defined by an authorization scenario (see [Authorization scenarios](#)).

The `subscribe` parameter defines the rules for subscribing to the list. Predefined authorization scenarios are:

- `subscribe auth` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/subscribe.auth>]);
- `subscribe auth_notify` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/subscribe.auth\\_notify](http://www.sympa.org/distribution/current/src/etc/scenari/subscribe.auth_notify)]);
- `subscribe auth_owner` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/subscribe.auth\\_owner](http://www.sympa.org/distribution/current/src/etc/scenari/subscribe.auth_owner)]);
- `subscribe closed` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/subscribe.closed>]);
- `subscribe intranet` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/subscribe.intranet>]);
- `subscribe intranetorowner` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/subscribe.intranetorowner>]);
- `subscribe open` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/subscribe.open>]);
- `subscribe open_notify` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/subscribe.open\\_notify](http://www.sympa.org/distribution/current/src/etc/scenari/subscribe.open_notify)]);
- `subscribe open_quiet` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/subscribe.open\\_quiet](http://www.sympa.org/distribution/current/src/etc/scenari/subscribe.open_quiet)]);
- `subscribe owner` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/subscribe.owner>]);
- `subscribe smime` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/subscribe.smime>]);

- `subscribe` `smimeorowner` (view [http://www.sympa.org/distribution/current/src/etc/scenari/subscribe.smimeorowner]).

## unsubscribe

---

(Default value: `open`)

The `unsubscribe` parameter is defined by an authorization scenario (see [Authorization scenarios](#)).

This parameter specifies the unsubscription method for the list. Use `open_notify` or `auth_notify` to allow owner notification of each unsubscribe command. Predefined authorization scenarios are:

- `unsubscribe auth` (view [http://www.sympa.org/distribution/current/src/etc/scenari/unsubscribe.auth]);
- `unsubscribe` `auth_notify` (view [http://www.sympa.org/distribution/current/src/etc/scenari/unsubscribe.auth\_notify]);
- `unsubscribe closed` (view [http://www.sympa.org/distribution/current/src/etc/scenari/unsubscribe.closed]);
- `unsubscribe open` (view [http://www.sympa.org/distribution/current/src/etc/scenari/unsubscribe.open]);
- `unsubscribe` `open_notify` (view [http://www.sympa.org/distribution/current/src/etc/scenari/unsubscribe.open\_notify]);
- `unsubscribe owner` (view [http://www.sympa.org/distribution/current/src/etc/scenari/unsubscribe.owner]).

## add

---

(Default value: `owner`)

`add` parameter is defined by an authorization scenario (see [Authorization scenarios](#)).

This parameter specifies who is authorized to use the `ADD` command. Predefined authorization scenarios are:

- `add auth` (view [http://www.sympa.org/distribution/current/src/etc/scenari/add.auth]);
- `add closed` (view [http://www.sympa.org/distribution/current/src/etc/scenari/add.closed]);
- `add owner` (view [http://www.sympa.org/distribution/current/src/etc/scenari/add.owner]);
- `add owner_notify` (view [http://www.sympa.org/distribution/current/src/etc/scenari/add.owner\_notify]).

## del

---

(Default value: `owner`)

The `del` parameter is defined by an authorization scenario (see [Authorization scenarios](#)).

This parameter specifies who is authorized to use the `DEL` command. Predefined authorization scenarios are:

- `del auth` (view [http://www.sympa.org/distribution/current/src/etc/scenari/del.auth]);
- `del closed` (view [http://www.sympa.org/distribution/current/src/etc/scenari/del.closed]);
- `del owner` (view [http://www.sympa.org/distribution/current/src/etc/scenari/del.owner]);
- `del owner_notify` (view [http://www.sympa.org/distribution/current/src/etc/scenari/del.owner\_notify]).

## invite

---

(Default value: owner)

The `invite` command is used to invite someone to subscribe. It should be preferred to the `add` command in most cases. This parameter defines who can use it. The privilege uses scenario specification.

## review

---

(Default value: owner)

`review` parameter is defined by an authorization scenario (see [Authorization scenarios](#)).

This parameter specifies who can use `REVIEW` (see [User commands](#)), administrative requests.

Predefined authorization scenarios are:

- `review closed` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/review.closed>]);
- `review intranet` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/review.intranet>]);
- `review listmaster` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/review.listmaster>]);
- `review owner` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/review.owner>]);
- `review private` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/review.private>]);
- `review public` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/review.public>]).

## remind

---

(Default value: owner)

The `remind` parameter is defined by an authorization scenario (see [Authorization scenarios](#)).

This parameter specifies who is authorized to use the `remind` command. Predefined authorization scenarios are:

- `remind listmaster` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/remind.listmaster>]);
- `remind owner` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/remind.owner>]).

## shared\_doc

---

This paragraph defines read and edit access to the shared document repository.

## d\_read

(Default value: private)

The `d_read` parameter is defined by an authorization scenario (see [Authorization scenarios](#)).

This parameter specifies who can read shared documents (access the contents of a list's `shared` directory).

Predefined authorization scenarios are:

- `d_read owner` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/d\\_read.owner](http://www.sympa.org/distribution/current/src/etc/scenari/d_read.owner)]);
- `d_read private` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/d\\_read.private](http://www.sympa.org/distribution/current/src/etc/scenari/d_read.private)]);
- `d_read p` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/d\\_read.p](http://www.sympa.org/distribution/current/src/etc/scenari/d_read.p)]);
- `d_read public` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/d\\_read.public](http://www.sympa.org/distribution/current/src/etc/scenari/d_read.public)]).

## d\_edit

(Default value: `owner`)

The `d_edit` parameter is defined by an authorization scenario (see [Authorization scenarios](#)).

This parameter specifies who can perform changes within a list's shared directory (i.e. upload files and create subdirectories).

Predefined authorization scenarios are:

- `d_edit editor` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/d\\_edit.editor](http://www.sympa.org/distribution/current/src/etc/scenari/d_edit.editor)]);
- `d_edit owner` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/d\\_edit.owner](http://www.sympa.org/distribution/current/src/etc/scenari/d_edit.owner)]);
- `d_edit private` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/d\\_edit.private](http://www.sympa.org/distribution/current/src/etc/scenari/d_edit.private)]);
- `d_edit p` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/d\\_edit.p](http://www.sympa.org/distribution/current/src/etc/scenari/d_edit.p)]);
- `d_edit public` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/d\\_edit.public](http://www.sympa.org/distribution/current/src/etc/scenari/d_edit.public)]).

Example:

```
-----  
shared_doc  
d_read           public  
d_edit           private  
-----
```

## quota

`quota` *number-of-Kbytes*

This parameter specifies the disk quota for the document repository, in kilobytes. If quota is exceeded, file uploads fail.

Edit

## Archive related

---

Sympa show archive both by email and web interface. In versions prior to 5.2, archives were duplicated. Mail archives were stored in the `/home/sympa/expl/mylist/archives/` directory.

Web archives are accessed through the web interface (with access control), they are stored in a directory defined in "wvsympa.conf" ([parameter arc\\_path](#)). Version 5.2 and later use only this archive repository.

## archive

---

If the “config” file contains an “archive” paragraph, Sympa will manage an archive for this list.

Example:

```
archive
period week
access private
```

If the `archive` parameter is specified, archives are accessible to users through the `GET` [command](#), and the index of the list archives is provided in reply to the `INDEX` command (the last message of a list can be consulted using the `LAST` command).

`period day | week | month | quarter | year`

This parameter specifies how archiving is organized: by day, week, month, quarter or year. Generation of automatic list archives requires the creation of an archive directory at the root of the list directory (`/home/sympa/expl/mylist/archives/`), used to store these documents.

`access private | public | owner | closed`

This parameter specifies who is authorized to use the `GET`, `LAST` and `INDEX` [commands](#).

## web\_archive

---

If the `config` file contains a `web_archive` paragraph, Sympa will copy all messages distributed via the list to the `queueoutgoing` spool. It is intended to be used with *WWSympa*'s HTML archive tools. This paragraph must contain at least the `access` parameter to control who can browse the web archive.

Example:

```
web_archive
access private
quota 10000
```

## web\_archive.access

The `access_web_archive` parameter is defined by an authorization scenario (see [Authorization scenarios](#)).

Predefined authorization scenarios are:

- `access closed` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/access\\_web\\_archive.closed](http://www.sympa.org/distribution/current/src/etc/scenari/access_web_archive.closed)]);
- `access intranet` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/access\\_web\\_archive.intranet](http://www.sympa.org/distribution/current/src/etc/scenari/access_web_archive.intranet)]);
- `access listmaster` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/access\\_web\\_archive.listmaster](http://www.sympa.org/distribution/current/src/etc/scenari/access_web_archive.listmaster)]);
- `access owner` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/access\\_web\\_archive.owner](http://www.sympa.org/distribution/current/src/etc/scenari/access_web_archive.owner)]);
- `access private` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/access\\_web\\_archive.private](http://www.sympa.org/distribution/current/src/etc/scenari/access_web_archive.private)]);
- `access public` (view [[http://www.sympa.org/distribution/current/src/etc/scenari/access\\_web\\_archive.public](http://www.sympa.org/distribution/current/src/etc/scenari/access_web_archive.public)]).

## web\_archive.quota

*quota number-of-Kbytes*

This parameter specifies the disk quota for the list's web archive, in kilobytes. This parameter's default is the `default_archive_quota` `sympa.conf` parameter. If quota is exceeded, messages are no more archived and list owners are notified. When the archive reaches 95%, list owners are warnet.

## web\_archive.max\_month

"max\_month" parameter specify the maximum number of archives packet created. Old month are removed when new month is created.

## archive\_crypted\_msg

---

(Default value: `cleartext`)

`archive_crypted_msg` `cleartext` | `decrypted`

This parameter defines Sympa's behavior when archiving S/MIME encrypted messages. If set to `cleartext`, the original encrypted form of the message will be archived; if set to `decrypted`, a decrypted message will be archived. Note that this applies to both mail and web archives, and also to digests.

Edit

## Bounce related

---

### bounce

---

This paragraph defines bounce management parameters:

- `warn_rate`  
(Default value: `bounce_warn_rate` robot parameter)  
The list owner receives a warning whenever a message is distributed and the number (percentage) of bounces exceeds this value.
- `halt_rate`  
(Default value: `bounce_halt_rate` robot parameter)  
"NOT USED YET"  
If bounce rate reaches the `halt_rate`, messages for the list will be halted, i.e. they are retained for subsequent moderation. Once the number of bounces exceeds this value, messages for the list are no longer distributed.
- `expire_bounce_task`  
(Default value: `daily`)  
Name of the task template used to remove old bounces. Useful to remove bounces for a subscriber email if some messages are distributed without receiving new bounces. In this case, the subscriber email seems to be OK again. Active if `task_manager.pl` is running.

Example:

```
## Owners are warnt with 10% bouncing addresses
## message distribution is halted with 20% bouncing rate
bounce
warn_rate      10
halt_rate      20
```

## bouncers\_level1

---

### ■ rate

(Default value: `bouncers_level1_rate` config parameter)

Each bouncing user has a score (from 0 to 100). This parameter defines the lower score for a user to be a level 1 bouncing user. For example, with default values, users with a score between 45 and 80 are level 1 bouncers.

### ■ action

(Default value: `bouncers_level1_action` config parameter)

This parameter defines which task is automatically applied on level 1 bouncing users: for example, automatically notify all level 1 bouncers.

### ■ Notification

(Default value: `owner`)

When an automatic task is performed on level 1 bouncers, a notification email can be sent to listowners or listmasters. This email contains the addresses of the users concerned and the name of the action perform.

## bouncers\_level2

---

### ■ rate

(Default value: `bouncers_level2_rate` config parameter)

Each bouncing user has a score (from 0 to 100). This parameter defines the lower score for a user to be a level 2 bouncing user. For example, with default values, users with a score between 75 and 100 are level 2 bouncers.

### ■ action

(Default value: `bouncers_level1_action` config parameter)

This parameter defines which task is automatically applied on level 2 bouncing users: for example, automatically notify all level 2 bouncers.

### ■ Notification

(Default value: `owner`)

When an automatic task is performed on level 2 bouncers, a notification email can be sent to listowners or listmasters. This email contains the addresses of the users concerned and the name of the action performed.

### Example:

```
## All bouncing addresses with a score between 75 and 100
## will be unsubscribed, and listmaster will receive an email
Bouncers level 2
rate:75 Points
action: remove\_bouncers
Notification: Listmaster
```

## welcome\_return\_path

---

welcome\_return\_path unique | owner

(Default value: welcome\_return\_path robot parameter)

If set to unique, the welcome message is sent using a unique return path in order to remove the subscriber immediately in case of bounce. See the [welcome\\_return\\_path sympa.conf parameter](#).

---

## remind\_return\_path

remind\_return\_path unique | owner

(Default value: remind\_return\_path robot parameter)

Same as welcome\_return\_path, but applied to remind messages. See the [remind\\_return\\_path sympa.conf parameter](#).

---

## verp\_rate

(Default value: verp\_rate host parameter)

See [VERP](#) for more information on VERP in Sympa.

When verp\_rate is null, VERP is not used; if verp\_rate is 100% VERP is always in use.

VERP requires plusned aliases to be supported and the bounce+\* alias to be installed.

Edit

---

## Data source related

---

### user\_data\_source

(Default value: file|database, if using an RDBMS)

user\_data\_source file | database | include | include2

Sympa allows the mailing list manager to choose how Sympa loads subscriber and administrative data. User information can be stored in a text file or relational database, or included from various external sources (list, flat file, result of LDAP or SQL query).

- user\_data\_source file

When this value is used, subscriber data are stored in a file whose name is defined by the subscribers parameter in `sympa.conf`. This is maintained for backward compatibility.

- user\_data\_source database

This mode was introduced to allow data to be stored in a relational database. This can be used for instance to share subscriber data with an HTTP interface, or simply to ease the administration of very large mailing lists. It has been tested with MySQL, using a list of 200,000 subscribers. We strongly recommend the use of a database instead of text files. It will improve performance and solve possible conflicts between Sympa and *WWSympa*. Please refer to [Sympa and its database](#).

- user\_data\_source include

Here, subscribers are not defined *extensively* (enumeration of their email addresses) but *intensively* (definition of criteria subscribers must satisfy). Includes can be performed by extracting email addresses using an SQL or LDAP query, or by including other mailing lists. At least one include paragraph, defining a data source, is needed. Valid include paragraphs (see below) are `include_file`, `include_list`, `include_remote_sympa_list`, `include_sql_query` and `include_ldap_query`.

- `user_data_source include2`

This is a replacement for the include mode. In this mode, the members cache is no more maintained in a DB File but in the main database instead. The behavior of the cache is detailed in the database chapter (see [Management of the include cache](#)). This is the only mode that runs the database for administrative data in the database.

## ttl

---

(Default value: 3600)

```
ttdelay_in_seconds
```

Sympa caches user data extracted using the include parameter. Their TTL (time-to-live) within Sympa can be controlled using this parameter. The default value is 3600.

## include\_list

---

```
include_list listname
```

This parameter will be interpreted only if `user_data_source` is set to `include` or `include2`. All subscribers of list `listname` become members of the current list. You may include as many lists as required, using one `include_list listname` line for each included list. Any list at all may be included; the `user_data_source` definition of the included list is irrelevant, and you may therefore include lists which are also defined by the inclusion of other lists. Be careful, however, not to include list A in list B and then list B in list A, since this would result in an infinite loop.

Example:

```
include_list local-list
```

Other example:

```
include_list other-local-list@other-local-robot
```

## include\_remote\_sympa\_list

---

```
include_remote_sympa_list
```

Sympa can contact another Sympa service using HTTPS to fetch a remote list in order to include each member of a remote list as a subscriber. You may include as many lists as required, using one `include_remote_sympa_list` paragraph for each included list. Be careful, however, not to give rise to an infinite loop making cross includes.

For this operation, one Sympa site acts as a server while the other acts as a client. On the server side, the only setting needed is to give permission to the remote Sympa to review the list. This is controlled by the review authorization scenario.

From the client side you must define the remote list dump URI.

- `remote_host` *remote\_host\_name*;
- `port` *port* (Default 443);
- `path` *absolute path* (in most cases, for a list name foo `/sympa/dump/foo`).

Because HTTPS offers an easy and secure client authentication, HTTPS is the only protocol currently supported. An additional parameter is needed: the name of the certificate (and the private key) to be used:

- `cert list`  
The certificate to be used is the list certificate (the certificate subject distinguished name email is the list address). The certificate and private key are located in the list directory.
- `cert robot`  
The certificate used is then related to Sympa itself: the certificate subject distinguished name email looks like `sympa@my.domain` and files are located in the virtual host `etc` directory if a virtual host is used; otherwise, they are located in `/home/sympa/etc`.

## include\_sql\_query

---

### include\_sql\_query

This parameter will be interpreted only if the `user_data_source` value is set to `include`. It is used to start a paragraph defining the SQL query parameters:

- `db_type` *dbd\_name*  
The database type (mysql, SQLite, Pg, Oracle, Sybase, CSV, ...). This value identifies the Perl DataBase Driver (DBD) to be used, and is therefore case-sensitive.
- `host` *hostname*  
The Database Server Sympa will try to connect to.
- `db_port` *port*  
If not using the default RDBMS port, you can specify it.
- `db_name` *sympa\_db\_name*  
The hostname of the database system.
- `user` *user\_id*  
The user id to be used when connecting to the database.
- `passwd` *some secret*  
The user passwd for `user`.
- `sql_query` *a query string*  
The SQL query string. No fields other than email addresses should be returned by this query!
- `connect_options` *option1=x;option2=y*  
This parameter is optional and specific to each RDBMS.  
These options are appended to the connect string.  
Example:

```
include_sql_query
  db_type mysql
  host sqlserv.admin.univ-x.fr
  user stduser
  passwd mysecret
  db_name studentbody
  sql_query SELECT DISTINCT email FROM student
  connect_options mysql_connect_timeout=5
```

Connexion timeout is set to 5 seconds.

#### ■ `db_env list_of_var_def`

This parameter is optional; it is needed for some RDBMS (Oracle).

Sets a list of environment variables to set before database connection. This is a ';' separated list of variable assignment.

Example for Oracle:

```
db_env      ORACLE_TERM=vt100;ORACLE_HOME=/var/hote/oracle/7.3.4
```

#### ■ `name short name`

This parameter is optional. It provides a human-readable name to this data source. It will be used within the REVIEW page to indicate from which datasource each list member comes (useful when having multiple data sources).

#### ■ `f_dir /var/csvdir`

This parameter is optional. It is only used when accessing a CSV data source. When connecting to a CSV data source, this parameter indicates the directory where the CSV files are located.

Example:

```
include_sql_query
  db_type oracle
  host sqlserv.admin.univ-x.fr
  user stduser
  passwd mysecret
  db_name studentbody
  sql_query SELECT DISTINCT email FROM student
```

## include\_ldap\_query

---

### include\_ldap\_query

This paragraph defines parameters for a LDAP query returning a list of subscribers. This paragraph is used only if `user_data_source` is set to `include`. This feature requires the `Net::LDAP (perlldap)` PERL module.

#### ■ `host ldap_directory_hostname`

Name of the LDAP directory host or a comma separated list of host:port. The second form is useful if you are using some replication LDAP host.

Example:

```
host ldap.cru.fr:389,backup-ldap.cru.fr:389
```

- `port ldap_directory_port` (OBSOLETE)  
Port on which the Directory accepts connections.
- `user ldap_user_name`  
Username with read access to the LDAP directory.
- `passwd LDAP_user_password`  
Password for user.
- `use_ssl yes/no`  
If set to `yes`, the LDAPS protocol is used.
- `ssl_version sslv2/sslv3/tls` (Default value: `sslv3`)  
If using SSL, this parameter defines whether SSL or TLS is used.
- `ssl_ciphers ciphers used` (Default value: `ALL`)  
If using SSL, this parameter specifies which subset of cipher suites are permissible for this connection, using the standard OpenSSL string format. The default value of `Net::LDAPS` for ciphers is `ALL`, which allows all ciphers, even those that do not encrypt!
- `suffix directory name`  
Defines the naming space covered by the search (optional, depending on the LDAP server).
- `timeout delay_in_seconds`  
Timeout when connecting the remote server.
- `filter search_filter`  
Defines the LDAP search filter (RFC 2254 compliant).
- `attrs mail_attribute` (Default value: `mail`)  
The attribute containing the email address(es) in the object returned.
- `select first | all` (Default value: `first`)  
Defines whether to use only the first address, or all the addresses, in case multiple values are returned.
- `scope base | one | sub` (Default value: `sub`)  
By default, the search is performed on the whole tree below the specified base object. This may be changed by specifying a scope parameter with one of the following values:
  - **base**: search only the base object,
  - **one**: search the entries immediately below the base object,
  - **sub**: search the whole tree below the base object.

Example:

```
include_ldap_query
host ldap.cru.fr
suffix dc=cru, dc=fr
timeout 10
filter (&(cn=aumont) (c=fr))
attrs mail
select first
scope one
```

## include\_ldap\_2level\_query

---

`include_ldap_2level_query`

This paragraph defines parameters for a two-level LDAP query returning a list of subscribers. Usually, the first-level query returns a list of DNs and the second-level queries convert the DNs into email addresses. This paragraph is used

only if `user_data_source` is set to `include`. This feature requires the `Net::LDAP` (perlldap) Perl module.

■ `host ldap_directory_hostname`

Name of the LDAP directory host or a comma separated list of `host:port`. The second form is useful if you are using some replication LDAP host.

Example:

```
host ldap.cru.fr:389,backup-ldap.cru.fr:389
```

■ `port ldap_directory_port` (OBSOLETE)

Port on which the Directory accepts connections (this parameter is ignored if host definition includes port specification).

■ `user ldap_user_name`

Username with read access to the LDAP directory.

■ `passwd LDAP_user_password`

Password for `user`.

■ `use_ssl yes/no`

If set to `yes`, the LDAPS protocol is used.

■ `ssl_version sslv2/sslv3/tls` (Default value: `sslv3`)

If using SSL, this parameter defines whether SSL or TLS is used.

■ `ssl_ciphers ciphers used` (Default value: `ALL`)

If using SSL, this parameter specifies which subset of cipher suites are permissible for this connection, using the standard OpenSSL string format. The default value of `Net::LDAPS` for ciphers is `ALL`, which allows all ciphers, even those that do not encrypt!

■ `suffix1 directory name`

Defines the naming space covered by the first-level search (optional, depending on the LDAP server).

■ `timeout1 delay_in_seconds`

Timeout for the first-level query when connecting to the remote server.

■ `filter1 search_filter`

Defines the LDAP search filter for the first-level query (RFC 2254 compliant).

■ `attrs1 attribute`

The attribute containing the data in the object returned, that will be used for the second-level query. This data is referenced using the syntax `[attrs1]`.

■ `select1 first | all | regex` (Default value: `first`)

Defines whether to use only the first attribute value, all the values, or only those values matching a regular expression.

■ `regex1 regular_expression` (Default value: )

The Perl regular expression to use if `select1` is set to `regex`.

■ `scope1 base | one | sub` (Default value: `sub`)

By default the first-level search is performed on the whole tree below the specified base object. This may be changed by specifying a scope parameter with one of the following values:

- **base**: search only the base object,
- **one**: search the entries immediately below the base object,
- **sub**: search the whole tree below the base object.

■ `suffix2 directory name`

Defines the naming space covered by the second-level search (optional, depending on the LDAP server). The `[attrs1]` syntax may be used to substitute data from the first-level query into this parameter.

■ `timeout2 delay_in_seconds`

Timeout for the second-level queries when connecting to the remote server.

■ `filter2 search_filter`

Defines the LDAP search filter for the second-level queries (RFC 2254 compliant). The `[attrs1]` syntax may be used to substitute data from the first-level query into this parameter.

■ `attrs2 mail_attribute` (Default value: `mail`)

The attribute containing the email address(es) in the objects returned from the second-level queries.

■ `select2 first | all | regex` (Default value: `first`)

Defines whether to use only the first address, all the addresses, or only those addresses matching a regular expression in the second-level queries.

■ `regex2 regular_expression` (Default value: )

The Perl regular expression to use if `select2` is set to `regex`.

■ `scope2 base | one | sub` (Default value: `sub`)

By default the second-level search is performed on the whole tree below the specified base object. This may be changed by specifying a `scope2` parameter with one of the following values:

- **base**: search only the base object,
- **one**: search the entries immediately below the base object,
- **sub**: search the whole tree below the base object.

Example:

```
(cn=testgroup,dc=cru,dc=fr should be a groupOfUniqueNames here)

include_ldap_2level_query
host ldap.univ.fr
port 389
suffix1 ou=Groups,dc=univ,dc=fr
scope1 one
filter1 (&(objectClass=groupOfUniqueNames) (| (cn=cru) (cn=ufrmi)))
attrs1 uniquemember
select1 all
suffix2 [attrs1]
scope2 base
filter2 (objectClass=n2pers)
attrs2 mail
select2 first
```

## include\_file

---

`include_file path_to_file`

This parameter will be interpreted only if the `user_data_source` value is set to `include`. The file should contain one email address per line with an optional user description, separated from the email address by spaces (lines beginning with a `#` are ignored).

Sample included file:

```
## Data for Sympa member import
john.smith@sample.edu John Smith - math department
```

## include\_remote\_file

---

### include\_remote\_file

This parameter (organized as a paragraph) does the same as the `include_file` parameter, except that it gets a remote file. This paragraph is used only if `user_data_source` is set to `include`. Using this method you should be able to include any *exotic* data source that is not supported by Sympa. The paragraph is made of the following entries:

- `url` *url\_of\_remote\_file*  
This is the URL of the remote file to include.
- `user` *user\_name*  
This entry is optional. It is only used if HTTP basic authentication is required to access the remote file.
- `passwd` *user\_passwd*  
This entry is optional. It is only used if HTTP basic authentication is required to access the remote file.

Example:

```
include_remote_file
url      http://www.myserver.edu/myfile
user     john_netid
passwd   john_passwd
```

[Edit](#)

## Command related

---

### remind\_task

---

(Default value: no default value)

This parameter states which model is used to create a `remind` task. A `remind` task regularly sends to the subscribers a message which reminds them of their subscription to the list.

Example:

```
remind annual
```

### expire\_task

---

(Default value: no default value)

This parameter states which model is used to create a `remind` task. An `expire` task regularly checks the inscription or reinscription date of subscribers and asks them to renew their subscription. If they do not, they are

deleted.

Example:

```
expire annual
```

## review

---

(Default value: owner)

The `review` parameter is defined by an authorization scenario (see [Authorization scenarios](#)).

This parameter specifies who can use the `REVIEW` command (see [User commands](#)), administrative requests.

Predefined authorization scenarios are:

- `review closed` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/review.closed>]);
- `review intranet` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/review.intranet>]);
- `review listmaster` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/review.listmaster>]);
- `review owner` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/review.owner>]);
- `review private` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/review.private>]);
- `review public` (view [<http://www.sympa.org/distribution/current/src/etc/scenari/review.public>]).

## List tuning

---

### max\_size

---

(Default value: `max_size robot` parameter)

`max_size` *number-of-bytes*

Maximum size of a message in 8-bit bytes. The default value is set in the `/etc/sympa.conf` file.

### loop\_prevention\_regex

---

(Default value: `loop_prevention_regex sympa.conf` parameter)

`loop_prevention_regex` *mailer-daemon|sympa|listserv|majordomo|smartlist|mailman*

This regular expression is applied to message sender addresses. If the sender address matches the regular expression, then the message is rejected. The goal of this parameter is to prevent loops between Sympa and other robots.

### pictures\_feature

---

(Default value: `pictures_feature robot` parameter)

`pictures_feature on / off`

This enables the feature that allows list members to upload a picture that will be shown on the review page.

## cookie

---

(Default value: `cookie robot` parameter)

`cookie random-numbers-or-letters`

This parameter is a confidential item for generating authentication keys for administrative commands (ADD, DELETE, etc.). This parameter should remain concealed, even for owners. The cookie is applied to all list owners, and is only taken into account when the owner has the `auth` parameter (see [owner](#)).

Example:

```
-----  
cookie secret22  
-----
```

## priority

---

(Default value: `default_list_priority robot` parameter)

`priority 0-9`

The priority with which Sympa will process messages for this list. This level of priority is applied while the message is going through the spool.

0 is the highest priority. The following priorities can be used: 0 . . . 9 z. z is a special priority causing messages to remain spooled indefinitely (useful to hang up a list).

Available since release 2.3.1.

## Spam protection

---

### spam\_protection

---

(Default value: `spam_protection robot` parameter)

There is a need to protect the Sympa website against spambot which collect email addresses in public websites. Various methods are available into Sympa and you can choose from the `spam_protection` and `web_archive_spam_protection` parameters. Possible value are:

- `javascript`: the address is hidden using a Javascript. Users who enable Javascript can see nice mailto addresses where others have nothing.
- `at`: the '@' char is replaced by the string 'AT'.
- `none`: no protection against spammers.

## web\_archive\_spam\_protection

---

(Default value: `web_archive_spam_protection robot parameter`)

The same as `spam_protection`, but restricted to the web archive. An additional value is available: `cookie`, which means that users must submit a small form in order to receive a cookie before browsing the archive. This blocks all robots, even those from search engines.

Edit

## Message topics

---

A list can be configured to have message topics (this notion is different from topics used to class mailing lists). Users can subscribe to these message topics in order to receive a subset of distributed messages: a message can have one or more topics and subscribers will receive only messages that have been tagged with a topic they are subscribed to. A message can be tagged automatically, by the message sender or by the list moderator.

### Message topic definition in a list

---

Available message topics are defined by list parameters. For each new message topic, create a new `msg_topic` paragraph that defines the name and the title of the topic. If a thread is identified for the current message, then the automatic procedure is performed. Otherwise, to use automatic tagging, you should define keywords (see [msg\\_topic](#)). To define which part of the message is used for automatic tagging, you have to define the `msg_topic_keywords_apply_on` list parameter (see [msg\\_topic\\_keywords\\_apply\\_on](#)). Tagging a message can be optional or required, depending on the [msg\\_topic\\_tagging\\_list](#) parameter.

### Subscribing to message topics for list subscribers

---

This feature is only available with the `normal` delivery mode. Subscribers can select a message topic to receive messages tagged with this topic. To receive messages that were not tagged, users can subscribe to the topic `other`. The message topics selected by a subscriber are stored in the Sympa database (`subscriber_table` table).

## Message tagging

---

First of all, if one or more `msg_topic.keywords` are defined, Sympa tries to tag messages automatically. To trigger manual tagging, by message sender or list moderator, on the web interface, Sympa uses authorization scenarios: if the resulting action is `editorkey` (for example in scenario `send.editorkey`), the list moderator is asked to tag the message. If the resulted action is `request_auth` (for example in scenario `send.privatekey`), the message sender is asked to tag the message. The following variables are available as scenario variables to customize tagging: `topic`, `topic-sender`, `topic-editor`, `topic-auto`, `topic-needed` (see [Authorization scenarios](#)). If message tagging is required and if it was not yet performed, Sympa will ask the list moderator.

Tagging a message will create a topic information file in the `/home/sympa/spool/topic/ spool`. Its name is

based on the listname and the Message-ID. For message distribution, a `X-Sympa-Topic` field is added to the message, to allow members to use email filters.

Edit

## Shared documents

---

Shared documents are documents that different users can manipulate online via the web interface of Sympa, provided that they are authorized to do so. A shared document web space is associated with the list, and users can upload, download, delete, etc documents in that web space.

*WWSympa's* shared web features are fairly rudimentary. It is not our aim to provide a sophisticated tool for web publishing, such as those provided by products like *Rearsite*. It is nevertheless very useful to be able to define privileges on web documents in relation to list attributes such as *subscribers*, *list owners* or *list editors*.

All file and directory names are lowercased by Sympa. It is consequently impossible to create two different documents whose names differ only in their case. The reason why Sympa does this is to allow correct URL links even when using an HTML document generator (typically Powerpoint) which uses random case for file names!

In order to have better control over the documents and to enforce security in the shared document web space, each document is linked to a set of specific control information: its access rights.

A list's shared documents are stored in the `/home/sympa/exp1/mylist/shared` directory. This directory is either created via the `Create shared` web admin feature, or at list creation time, if the list `shared_doc` parameter is set. If you don't want the document repository to be created, you should remove the `shared_doc` parameter from the corresponding `create_list_templates/xx/config.tt2` files.

This chapter describes how the shared documents are managed, especially as regards their access rights. We will see:

- the kind of operations which can be performed on shared documents;
- access rights management;
- access rights control specifications;
- actions on shared documents;
- template files.

## The three kinds of operations on a document

---

Where shared documents are concerned, there are three kinds of operations which have the same constraints relating to access control:

- the read operation;
- the edit operation;
- the control operation.

### The read operation

If applied to a directory, it opens it and lists its contents (only the sub-documents the user is authorized to "see").

If applied to a file, it downloads it, and in the case of a viewable file (*text/plain*, *text/html*, or image), displays it.

## The edit operation

It allows:

- subdirectory creation;
- file uploading;
- file unzipping;
- description of a document (title and basic information);
- online editing of a text file;
- document (file or directory) deletion. Directories can be deleted only if they are empty.

These different edit actions are equivalent as regards access rights. Users who are authorized to edit a directory can create a subdirectory or upload a file to it, as well as describe or delete it. Users authorized to edit a file can edit it online, describe it, replace or remove it.

## The control operation

The control operation is directly linked to the notion of access rights. If we want shared documents to be secure, we have to control the access to them. Not everybody must be authorized to perform every operation on them. Consequently, each document has specific access rights for reading and editing. Performing a control action on a document involves changing its Read/Edit rights.

The control operation has more restrictive access rights than the other two operations. Only the owner of a document, the privileged owner of the list and the listmaster have control rights over a document. Another possible control action on a document is therefore specifying who owns it.

## The description file

---

The information (title, owner, access rights...) related to each document must be stored, and so each shared document is linked to a special file called a description file, whose name includes the `.desc` prefix.

The description file of a directory having the path `mydirectory/mysubdirectory` has the path `mydirectory/mysubdirectory/.desc`. The description file of a file having the path `mydirectory/mysubdirectory/myfile.myextension` has the path `mydirectory/mysubdirectory/.desc.myfile.myextension`.

## Structure of description files

The structure of a document (file or directory) description file is given below. You should *never* have to edit a description file.

```
title
  <description of the file in a few words>

creation
  email      <email of the owner of the document>
  date_epoch <date_epoch of the creation of the document>
```

```
access
  read <access rights for read>
  edit <access rights for edit>
```

The following example is for a document that subscribers can read, but that only the owner of the document and the owner of the list can edit.

```
title
  module C++ which uses the class List

creation
  email foo@some.domain.com
  date_epoch 998698638

access
  read private
  edit owner
```

## The predefined authorization scenarios

---

### The public scenario

The `public` scenario is the most permissive scenario. It enables anyone (including unknown users) to perform the corresponding action.

### The private scenario

The `private` scenario is the basic scenario for a shared space. Every subscriber of the list is authorized to perform the corresponding action. The `private` scenario is the default read scenario for `shared` when this shared space is created. This can be modified by editing the list configuration file.

### The scenario owner

The scenario `owner` is the most restrictive scenario for a shared space. Only the listmaster, list owners and the owner of the document (or those of a parent document) are allowed to perform the corresponding action. The `owner` scenario is the default scenario for editing.

### The scenario editor

The scenario `editor` is for a moderated shared space for editing. Every subscriber of the list is allowed to edit a document. But this document will have to be installed or rejected by the editor of the list. Documents awaiting for moderation are visible by their author and the editor(s) of the list in the shared space. The editor has also an interface with all documents awaiting. When there is a new document, the editor is notified and when the document is installed, the author is notified too. In case of reject, the editor can notify the author or not.

## Access control

---

Access control is an important operation performed every time a document is accessed within the shared space.

The access control related to a document in the hierarchy involves an iterative operation on all its parent directories.

## Listmaster and privileged owners

The listmaster and privileged list owners are special users as regards the shared document web space. They are allowed to perform every action on every document. This privilege enables control over the shared space to be maintained. It is impossible to prevent the listmaster and privileged owners from performing any action they please on any document in the shared space.

## Special case of the shared directory

In order to allow access to a root directory to be more restrictive than that of its subdirectories, the `shared` directory (root directory) is a special case as regards access control. The access rights for read and edit are those specified in the list configuration file. Control of the root directory is specific. Only the users authorized to edit a list's configuration may change access rights on its `shared` directory.

## General case

`mydirectory/mysubdirectory/myfile` is an arbitrary document in the shared space, but not in the `root` directory. A user **X** wishes to perform one of the three operations (read, edit, control) on this document. The access control will proceed as follows:

### ■ Read operation

To be authorized to perform a read action on `mydirectory/mysubdirectory/myfile`, **X** must be authorized to read every document making up the path; in other words, he/she must be allowed to read `myfile` (the authorization scenario of the description file of `myfile` must return `do_it` for user **X**), and the same goes for `mysubdirectory` and `mydirectory`).

In addition, given that the owner of a document or of its parent directories is allowed to perform **all actions on that document**, `mydirectory/mysubdirectory/myfile` may also have read operations performed on it by the owners of `myfile`, `mysubdirectory`, and `mydirectory`.

This can be schematized as follows:

```
X can read <a/b/c>
if
(X can read <c>
AND X can read <b>
AND X can read <a>)
OR
(X owner of <c>
OR X owner of <b>
OR X owner of <a>)
```

### ■ Edit operation

The access algorithm for edit is identical to the algorithm for read:

```
X can edit <a/b/c>
if
```

```
(X can edit <c>
AND X can edit <b>
AND X can edit <a>)
OR
(X owner of <c>
OR X owner of <b>
OR X owner of <a>)
```

### ■ Control operation

The access control which precedes a control action (change rights or set the owner of a document) is much more restrictive. Only the owner of a document or the owners of a parent document may perform a control action:

```
X can control <a/b/c>
if
(X owner of <c>
OR X owner of <b>
OR X owner of <a>)
```

## Shared document actions

---

The shared web feature has called for some new actions.

### ■ action `D_ADMIN`

Creates the shared space, closes it or restore it. The `d_admin` action is accessible from a list's **admin** page.

### ■ action `D_READ`

Reads the document after read access control. If the document is a folder, it lists all the subdocuments that can be read. If it is a file, it displays it if it is viewable, else downloads it to disk. If the document to be read contains a file named `index` or `index.htm`, and if the user has no permissions other than read on all subdocuments contained, the read action will consist in displaying the index. The `d_read` action is accessible from a list's **info** page.

### ■ action `D_CREATE_DIR`

Creates a new subdirectory in a directory that can be edited without moderation. The creator is the owner of the directory. The access rights are those of the parent directory.

### ■ action `D_DESCRIBE`

Describes a document that can be edited.

### ■ action `D_DELETE`

Deletes a document after edit access control. If applied to a folder, it has to be empty.

### ■ action `D_UPLOAD`

Uploads a file into a directory that can be edited.

### ■ action `D_UNZIP`

Unzips a file into a directory that can be edited without moderation. The whole file hierarchy contained in the ZIP file is installed into the directory.

### ■ action `D_OVERWRITE`

Overwrites a file if it can be edited. The new owner of the file is the one who has done the overwriting operation.

### ■ actions `D_EDIT_FILE` and `D_SAVE_FILE`

Edits a file and saves it after edit access control. The new owner of the file is the one who has done the saving operation.

### ■ action `D_CHANGE_ACCESS`

Changes the access rights of a document (read or edit), provided that control of this document is authorized.

### ■ action `D_SET_OWNER`

Changes the owner of a directory, provided that control of this document is authorized. The directory must be empty. The new owner can be anyone, but authentication is necessary before any action can be performed on the document.

## Template files

---

The following template files have been created for the shared document web space.

### d\_read.tt2

The default page for reading a document. If for a file, displays it (if viewable) or downloads it. If for a directory, displays all readable subdocuments, each of which will feature buttons corresponding to the different actions this subdocument allows. If the directory is editable, displays buttons to describe it or upload a file into it. If the directory is editable without moderation, it displays buttons to create a new subdirectory or to upload a ZIP file in order to install a file hierarchy. If access to the document is editable, displays a button to edit the access to it.

### d\_editfile.tt2

The page used to edit a file. If for a text file, allows it to be edited online. This page also enables another file to be substituted in its place.

### d\_control.tt2

The page to edit the access rights and the owner of a document.

### d\_upload.tt2

---

The page to upload a file is only used when the name of the file already exists.

### d\_properties.tt2

---

This page is used to edit the description file and to rename it.

Edit

## Bounce management

---

Sympa allows bounce (non-delivery report) management. This prevents list owners from receiving each bounce (1 per message sent to a bouncing subscriber) in their own mailbox. Without automatic processing of bounces, list owners either go mad, or just delete them without further attention.

Bounces are received at the `mylist-owner` address (note that the `-owner` suffix can be customized, see [return\\_path\\_suffix](#)), which should be sent to the `bouncequeue` program through aliases:

```
samplelist-owner: "|/home/sympa/bin/bouncequeue samplelist"
```

bouncequeue (see [Binaries](#)) stores bounces in a `/home/sympa/spool/bounce/` spool.

Bounces are then processed by the `bounced.pl` daemon. This daemon analyses bounces to find out which email addresses are concerned and what kind of error was generated. If bouncing addresses match a subscriber's address, information is stored in the Sympa database (in `subscriber_table`). Moreover, the most recent bounce itself is archived in `bounce_path/mylist/email` (where `bounce_path` is defined in a `wwsympa.conf` parameter and `email` is the user email address).

When reviewing a list, bouncing addresses are tagged as bouncing. You may access further information such as dates of first and last bounces, number of bounces received for the address, the last bounce, etc.

With this information, the automatic bounce management is possible:

The automatic task `eval_bouncer` gives a score for each bouncing user. The score, between 0 to 100, allows the classification of bouncing users in two levels (level 1 or 2). According to the level, automatic actions are executed periodically by the `process_bouncers` task.

The score evaluation main parameters are:

- `Bounces count`: the number of bouncing messages received by Sympa for the user.
- `Type rate`: bounces are classified depending on the type of errors generated on the user side. If the error type is `mailbox is full` (i.e. a temporary 4.2.2 error type), the type rate will be 0.5, whereas permanent errors (5.x.x) have a type rate equal to 1.
- `Regularity rate`: this rate tells whether bounces were received regularly, compared to list traffic. The list traffic is deduced from the `msg_count` file data.

The score formula is:

```
Score = bounce_count * type_rate * regularity_rate
```

To avoid making decisions (i.e. defining a score) without enough relevant data, the score is not evaluated if:

- The number of received bounces is lower than `minimum_bouncing_count` (see [minimum\\_bouncing\\_count](#)).
- The bouncing period is shorter than `minimum_bouncing_period` (see [minimum\\_bouncing\\_period](#)).

Bouncing list member entries expire after a given period of time. The default period is 10 days, but it can be customized if you write a new `expire_bounce` task (see [expire\\_bounce\\_task](#)).

You can define the limit between each level through the **List configuration panel**, in subsection **Bounce settings** (see [bouncers\\_level1](#)). The principle consists in associating a score interval with a level.

You can also define which action must be applied on each category of user (see [bouncers\\_level1](#)). Each time an action will be performed, a notification email will be sent to the person of your choice (see [bouncers\\_level1](#)).

## VERP

---

VERP (Variable Envelop Return Path) is used to ease automatic recognition of subscribers email addresses when receiving a bounce. If VERP is enabled, the subscriber address is encoded in the return path itself, so that the Sympa

bounce management process (bounced) will use the address the bounce was received for to retrieve the subscriber email. This is very useful because sometimes, non delivery report do not contain the initial subscriber email address but an alternative address where messages are forwarded. VERP is the only solution to detect automatically these subscriber errors. However, the cost of VERP is significant, indeed VERP requires to distribute a separate message for each subscriber and breaks the bulk emailer grouping optimization.

In order to benefit from VERP and keep the distribution process fast, Sympa enables VERP only for a share of the list members. If `texttt verp_rate` (see `verp_rate`) is 10%, then after 10 messages distributed in the list all subscribers have received at least one message where VERP was enabled. Later, distribution message enables VERP also for all users where some bounces were collected and analyzed by the previous VERP mechanism.

If VERP is enabled, the format of the messages return path are as follows:

```
Return-Path: <bounce+user==a==userdomain==listname@listdomain>
```

Note that you need to set a mail alias for the generic `bounce+*` alias (see [Robot aliases](#)).

## ARF

---

ARF (Abuse Feedback Reporting Format) is a standard for reporting abuse. It is implemented mainly in the AOL email user interface. AOL servers propose to mass mailer to received automatically the users complain by formatted messages. Because many subscribers do not remember how to unsubscribe they use ARF when provided by their user interface. It may be useful to configure the ARF management in Sympa. It is really simple: all what you have to do is to create a new alias for each virtual robot as the following:

```
abuse-feedback-report: " | /home/sympa/bin/bouncequeue sympa@samplerobot "
```

Then register this address as your loop back email address with ISP (for exemple AOL). This way, messages to that email adress are processed by the bounced daemon and opt-out opt-out-list abuse and automatically processed. If the bounce service can remove a user, the message report feedback is forwarded to the list owner. Unrecognized messages are forwarded to the listmaster.

Edit

## Antivirus

---

Sympa lets you use an external antivirus solution to check incoming mails. In this case you must set the `antivirus_path` and `antivirus_args` configuration parameters (see [Antivirus plug-in](#)). Sympa is already compatible with McAfee/uvscan, Fsecure/fsav, Sophos, AVP, Trend Micro/VirusWall and Clam Antivirus. For each email received, Sympa extracts its MIME parts in the `/home/sympa/spool/tmp/antivirus` directory and then calls the antivirus software to check them. When a virus is detected, Sympa looks for the virus name in the virus scanner STDOUT and sends a `your_infected_msg.tt2` warning to the sender of the email. The dmail is saved as 'bad' and the working directory is deleted (except if Sympa is running in debug mode).

Edit

## Using Sympa with LDAP

---

LDAP is a client-server protocol for accessing a directory service. Sympa provide various features based on access to one or more LDAP directories:

- authentication using LDAP directory instead of the Sympa internal storage of password (see [auth.conf](#));
- named filters used in authorization scenario condition (see [Named Filters](#));
- LDAP extraction of list subscribers (see [user\\_data\\_source](#));
- LDAP extraction of list owners or editors (see [Data inclusion file](#));
- mail aliases stored in LDAP (see [Alias manager](#)).

Edit

## Sympa with S/MIME and HTTPS

---

S/MIME is a cryptographic method for MIME messages based on X509 certificates. Before installing Sympa S/MIME features (which we call S/Sympa), you should be under no illusion about what the S stands for: S/MIME means *Secure* MIME. That S certainly does not stand for *Simple*.

The aim of this chapter is simply to describe what security level is provided by Sympa while using S/MIME messages, and how to configure Sympa for it. It is not intended to teach anyone what S/MIME is and why it is so complex! RFCs number 2311, 2312, 2632, 2633 and 2634, along with a lot of literature about S/MIME, PKCS#7 and PKI is available on the Internet. Sympa 2.7 is the first version of Sympa to include S/MIME features as beta-testing features.

## Signed message distribution

---

No action required. You probably imagine that any mailing list manager (or any mail forwarder) is compatible with S/MIME signatures, as long as it respects the MIME structure of incoming messages. You are right. Even Majordomo can distribute a signed message! As Sympa provides MIME compatibility, you do not need to do anything in order to allow subscribers to check signed messages distributed through a list. This is not an issue at all, since any process that distributes messages is compatible with end user signing processes. Sympa simply skips the message footer attachment (see [Message header and footer](#)) to prevent any body corruption which would break the signature.

## Use of S/MIME signatures by Sympa itself

---

Sympa is able to check S/MIME signatures in order to apply S/MIME authentication methods for message handling. Currently, this feature is limited to the distribution process as well as to any commands Sympa might find in the message body. The reasons for this restriction are related to current S/MIME usage. S/MIME signature structure is based on the encryption of a digest of the message. Most S/MIME agents do not include any part of the message headers in the message digest, so anyone can modify the message header without signature corruption! This is easy to do: for example, anyone can edit a signed message with their preferred message agent, modify whatever header they want (for example `Subject:`, `Date:` and `To:`, and redistribute the message to a list or to the robot without breaking the signature.

So Sympa cannot apply the S/MIME authentication method to a command parsed in the `Subject:` field of a message or through the `-subscribe` or `-unsubscribe` email addresses.

## Use of S/MIME encryption

---

S/Sympa is not an implementation of the S/MIME Symmetric Key Distribution internet draft. This sophisticated scheme is required for large lists with encryption. So, there is still some scope for future developments 😊

We assume that S/Sympa distributes message as received, i.e. unencrypted when the list receives an unencrypted message, but otherwise encrypted.

In order to be able to send encrypted messages to a list, the sender needs to use the X509 certificate of the list. Sympa will send an encrypted message to each subscriber using the subscriber's certificate. To provide this feature, Sympa needs to manage one certificate for each list and one for each subscriber. This is available in Sympa version 2.8 and above.

## S/Sympa configuration

---

### Installation

---

The only requirement is OpenSSL (<http://www.openssl.org> [<http://www.openssl.org>]) version 0.9.5a and above. OpenSSL is used by Sympa as an external plugin (like sendmail or postfix), so it must be installed with the appropriate access (x for `sympa.sympa`).

### Managing user certificates

---

User certificates are automatically caught by Sympa when receiving a signed S/MIME message, so if Sympa needs to send encrypted messages to this user, it can perform encryption using this certificate. This works fine, but it is not compliant with the PKI theory: Sympa should be able to search for user certificates using a PKI certificate directory (LDAP).

That's why Sympa tests the key usage certificate attribute to know if the certificate allows both encryption and signature.

Certificates are stored as PEM files in the `/home/sympa/exp1/x509-user-certs/` directory. Files are named `user@some.domain@enc` or `user@some.domain@sign` (the `@enc` and `@sign` suffixes are used according to certificates usage). No other tool is provided by Sympa in order to collect this certificate repository, but you can easily imagine your own tool to create those files.

### Configuration in `sympa.conf`

---

The S/Sympa configuration is very simple. If you are used to Apache SSL, you should not feel lost. If you are an OpenSSL guru, you will feel at home, and there may even be changes you will wish to suggest to us.

The basic requirement is to let Sympa know where to find the binary file for the OpenSSL program and the certificates of the trusted certificate authority. This is made using the optional parameters `openssl` and `capath` and `/` or `cafile`.

- `openssl`: the path for the OpenSSL binary file, usually `/usr/local/ssl/bin/openssl`;
- `cafile` (or `capath`): the path of a bundle (or path of the directory) of trusted CA certificates. The file

~/home/sympa/bin/etc/cabundle.crt included in Sympa distribution can be used.

The cafile file (or the capath directory) should be shared with your Apache+mod\_ssl configuration. This is required because Sympa's web interface gets user certificates information from Apache mod\_ssl module;

- key\_password: the password used to protect all list private keys.

## Configuration to recognize S/MIME signatures

---

Once OpenSSL has been installed and sympy.conf configured, your S/Sympa is ready to use S/MIME signatures for any authentication operation. You simply need to use the appropriate authorization scenario for the operation you want to secure (see [Authorization scenarios](#)).

When receiving a message, Sympa applies the authorization scenario with the appropriate authentication method parameter. In most cases, the authentication method is smtp, but in cases where the message is signed and the signature has been checked and matches the sender email, Sympa applies the smime authentication method.

It is essential to ensure that if the authorization scenario does not recognize this authentication method, the operation requested will be rejected. Consequently, authorization scenarios distributed prior to version 2.7 are not compatible with the OpenSSL configuration of Sympa. All standard authorization scenarios (those distributed with sympy) now include the smime method. The following example is named send.private\_smime, and restricts sending to subscribers using an S/mime signature:

```
title.us restricted to subscribers check SMIME signature
title.fr limité aux abonnés, vérif de la signature SMIME

is_subscriber([listname],[sender])      smime -> do_is_editor([listname],[sender])
is_owner([listname],[sender])           smime -> do_it
```

It is also possible to mix various authentication methods in a single authorization scenario. The following example, send.private\_key, requires either an MD5 return key or an S/MIME signature:

```
title.us restricted to subscribers with previous MD5 authentication
title.fr réservé aux abonnés avec authentification MD5 préalable

is_subscriber([listname],[sender]) smtp      -> request_auth
true()                               md5,smime -> do_it
```

## distributing encrypted messages

---

In this section, we describe S/Sympa encryption features. The goal is to use S/MIME encryption for distribution of a message to subscribers whenever the message has been received encrypted from the sender.

Why is S/Sympa concerned by the S/MIME encryption distribution process ? It is because encryption is performed using the **recipient** X509 certificate, whereas the signature requires the sender's private key. Thus, an encrypted message can be read by the recipient only if he or she is the owner of the private key associated with the certificate. Consequently, the only way to encrypt a message for a list of recipients is to encrypt and send the message for each recipient. This is what S/Sympa does when distributing an encrypted message.

The S/Sympa encryption feature in the distribution process assumes that Sympa has received an encrypted message for some list. To be able to encrypt a message for a list, the sender must have some access to an X509 certificate for

the list. So the first requirement is to install a certificate and a private key for the list. The mechanism whereby certificates are obtained and managed is complex. Current versions of S/Sympa assume that list certificates and private keys are installed by the listmaster using the `/home/sympa/bin/p12topem.pl` script. This script allows you to install a PKCS#12 bundle file containing a private key and a certificate using the appropriate format.

It is a good idea to have a look at the OpenCA documentation (<http://www.openssl.org> [<http://www.openssl.org>]) and/or PKI providers' web documentation. You can use commercial certificates or home-made ones. Of course, the certificate must be approved of for email applications, and issued by one of the trusted CA's described in the `cafile` file or the `capath` Sympa configuration parameter.

The list private key must be installed in a file named `/home/sympa/expl/mylist/private_key`. All the list private keys must be encrypted using a single password defined by the `password` parameter in `sympa.conf`.

## Use of navigator to obtain X509 list certificates

In many cases email X509 certificates are distributed through a web server and loaded into the browser using your mouse: Mozilla or internet Explorer allow certificates to be exported to a file.

Here is a way to install a certificat for a list:

- Get a list certificate is to obtain a personal email certificate for the canonical list address in your browser as if it was your personal certificate.
- Export the intended certificate it. The format used by Netscape is `pkcs#12`. Copy this file to the list home directory.
- Convert the `pkcs#12` file into a pair of PEM files: `cert.pem` and `private_key`, using the `/home/sympa/bin/p12topem.pl` script. Use `p12topem.pl -help` for details.
- Be sure that `cert.pem` and `private_key` are owned by `sympa` with `r` access.
- As soon as a certificate is installed for a list, the list homepage includes a new link to load the certificate in the user's browser, and the welcome message is signed by the list.

## Managing certificates with tasks

---

You may automate the management of certificates with two global task models provided with Sympa. See [Tasks](#) to know more about tasks. Report to the [chk\\_cert\\_expiration\\_task](#) and [crl\\_update\\_task](#) `sympa.conf` parameters to configure your Sympa to use these facilities.

### chk\_cert\_expiration.daily.task model

---

A task created with the model `chk_cert_expiration.daily.task` checks every day the expiration date of certificates stored in the `/home/sympa/expl/X509-user-certs/` directory. The user is warnt with the `daily_cert_expiration` template when his/her certificate has expired or is going to expire within three days.

### crl\_update.daily.task model

---

You may use the model `crl_update.daily.task` to create a task which daily updates the certificate

revocation lists when needed.

Edit

## Using Sympa commands

---

Users interact with Sympa, of course, when they send messages to one of the lists, but also indirectly through administrative requests (subscription, list of users, etc.).

This section describes administrative requests, as well as interaction modes in the case of private and moderated lists. Administrative requests are messages whose body contains commands understood by Sympa, one per line. These commands can be indiscriminately placed in the `Subject:` or in the body of the message. The `To:` address is generally the `SympaDomain` alias, although it is also advisable to recognize the `listservdomain` address.

Example:

```
-----  
From: pda@prism.uvsq.fr  
To: Sympa@cru.fr  
  
LISTS  
INFO Sympa-users  
REVIEW Sympa-users  
QUIT  
-----
```

Most user commands have three-letter abbreviations (e.g. `REV` instead of `REVIEW`).

## User commands

---

### ■ HELP

Provides instructions for the use of Sympa commands. The result is the content of the `helpfile.tt2` template file.

### ■ INFO *listname*

Provides the parameters of the list specified (owner, subscription mode, etc.) and its description. The result is the content of `~welcome[.mime]`.

### ■ LISTS

Provides the names of lists managed by Sympa. This list is generated dynamically, using the `visibility` parameter (see [Visibility](#)). The `lists.tt2` template defines the message returned by the `LISTS` command.

### ■ REVIEW *listname*

Provides the addresses of subscribers if the run mode authorizes it. See the [review parameter](#) for the configuration file of each list, which controls read authorizations for the subscriber list. Since subscriber addresses can be abused by spammers, it is strongly recommended that you **only authorize owners to access the subscriber list**.

### ■ WHICH

Returns the list of lists to which one is subscribed, as well as the configuration of his or her subscription to each of the lists (`DIGEST`, `NOMAIL`, `SUMMARY`, `CONCEAL`).

### ■ STATS *listname*

Provides statistics for the specified list: number of messages received, number of messages sent, megabytes received, megabytes sent. This is the contents of the `stats` file.

Access to this command is controlled through the `review` parameter.

- INDEX *listname*

Provides index of archives for the list specified. Access rights to this function are the same as for the GET command.
- GET *listname archive*

To retrieve archives for list (see above). Access rights are the same as for the REVIEW command. See the [review parameter](#).
- LAST *listname*

To receive the last message distributed in a list (see above). Access rights are the same as for the GET command.
- SUBSCRIBE *listname firstname name*

Requests sign-up to the specified list. The *firstname* and *name* parameters are optional. If the list is configured with a restricted subscription (see the [subscribe parameter](#)), this command is sent to the list owner for approval.
- INVITE *listname user@host name*

Invites someone to subscribe to the list specified. The *name* parameter is optional. The command is similar to ADD, but the person specified is not added to the list but invited to subscribe to it in accordance with the [subscribe parameter](#).
- SIGNOFF *listname* [ *user@host* ]

Requests unsubscription from the specified list. SIGNOFF \* means unsubscription from all lists.
- SET *listname* DIGEST

Puts the subscriber in *digest* mode for the *listname* list. Instead of receiving email from the list in a normal manner, the subscriber will periodically receive it in a digest. This digest compiles a group of messages from the list, using multipart/digest mime format. The sending period for these digests is regulated by the list owner using the [digest parameter](#). See the [SET LISTNAME MAIL command](#) and the [reception parameter](#).
- SET *listname* SUMMARY

Puts the subscriber in *summary* mode for the *listname* list. Instead of receiving email from the list in a normal manner, the subscriber will periodically receive the list of messages. This mode is very close to the DIGEST reception mode, but the subscriber only receives the list of messages. This option is available only if the digest mode is set.
- SET *listname* NOMAIL

Puts subscriber in *nomail* mode for the *listname* list. This mode is used when a subscriber no longer wants to receive email from the list, but nevertheless wishes to retain the possibility of posting to the list. This mode therefore prevents the subscriber from unsubscribing and subscribing later on. See the [SET LISTNAME MAIL command](#) and the [reception parameter](#).
- SET *listname* TXT

Puts subscriber in *txt* mode for the *listname* list. This mode is used when a subscriber wishes to receive emails sent in both format, txt/html and txt/plain only, in txt/plain format. See the [reception parameter](#).
- SET *listname* HTML

Puts subscriber in *html* mode for the *listname* list. This mode is used when a subscriber wishes to receive emails sent in both format, txt/html and txt/plain only, in txt/html format. See the [reception parameter](#).
- SET *listname* URLIZE

Puts subscriber in *urlize* mode for the *listname* list. This mode is used when a subscriber wishes not to receive attached files. The attached files are replaced by a URL leading to the file stored on the list site. See the [reception parameter](#).
- SET *listname* NOT\_ME

Puts subscriber in *not\_me* mode for the *listname* list. This mode is used when a subscriber wishes not to receive back the message that he/she has sent to the list. See [reception parameter](#).
- SET *listname* MAIL

Puts the subscriber in `normal` mode (default) for the *listname* list. This option is mainly used to cancel the `nomail`, `summary` or `digest` modes. If the subscriber was in `nomail` mode, he or she will receive email from the list in a normal manner again. See the [SET LISTNAME NOMAIL command](#) and the [reception parameter](#). Moreover, this mode allows message topic subscription (see [Message topics](#)).

- `SET listname CONCEAL`

Puts the subscriber in `conceal` mode for the *listname* list. The subscriber will then become invisible during `REVIEW` on this list. Only owners will see the whole subscriber list. See the [SET LISTNAME NOCONCEAL command](#) and the [Visibility parameter](#).

- `SET listname NOCONCEAL`

Puts the subscriber in `noconceal` mode (default) for the *listname* list. The subscriber will then become visible during `REVIEW` of this list. The `conceal` mode is therefore cancelled. See the [SET LISTNAME CONCEAL command](#) and the [Visibility parameter](#).

- `QUIT`

Ends acceptance of commands. This can be useful when the message contains additional lines, as for example in the case where a signature is automatically added by the user's email program (MUA).

- `CONFIRM key`

If the `send` parameter of a list is set to `privatekey`, `publickey` or `privateorpublickey`, messages are only distributed in the list after an authentication phase by return mail, using a one-time password (numeric key). For this authentication, the sender of the message is requested to post the `CONFIRM key` command to Sympa.

- `QUIET`

This command is used for silent (mute) processing: no performance report is returned for commands prefixed with `QUIET`.

## Owner commands

---

Some administrative requests are only available to list owners. They are essential for all procedures in limited access mode, and to perform requests in place of users. These commands are:

- `ADD listname user@host firstname name`

Add command similar to `SUBSCRIBE`. You can avoid user notification by using the `QUIET` prefix (i.e.: `QUIET ADD`).

- `DELETE listname user@host`

Delete command similar to `SIGNOFF`. You can avoid user notification by using the `QUIET` prefix (i.e.: `QUIET DELETE`).

- `REMIND listname`

`REMIND` is used by list owners in order to send an individual service reminder message to each subscriber. This message is made by parsing the `remind.tt2` file.

- `REMIND *`

`REMIND *` is used by the listmaster to send to each subscriber of any list a single message with a summary of his/her subscriptions. In this case, the message sent is built by parsing the `global_remind.tt2` file. For each list, Sympa tests whether the list is configured as hidden to each subscriber (parameter `lparam visibility`). By default, the use of this command is restricted to listmasters. Processing may take a lot of time!

These commands can be prefixed with `QUIET` to indicate processing without acknowledgment of receipt.

## Moderator commands

---

If a list is moderated, Sympa only distributes messages enabled by one of its moderators (editors). Moderators have several methods for enabling message distribution, depending on the send parameter.

- `DISTRIBUTE listname key`

If the `send` parameter of a list is set to `editorkey` or `editorkeyonly`, each message queued for moderation is stored in a spool (see queuemod), and linked to a key. The moderator must use this command to enable message distribution.

- `REJECT listname key`

The message with the `key` key will be deleted from the moderation spool of the *listname* list.

- `MODINDEX listname`

This command returns the list of messages queued for moderation for the *listname* list. The result is presented in the form of an index, which supplies, for each message, its sending date, its sender, its size, and its associated key, as well as all messages in the form of a digest.

Edit

test.txt · Last modified: 2007/02/20 15:04 by olivier.lumineau@cru.fr