

# **STDLIB**

**version 1.14**

Typeset in L<sup>A</sup>T<sub>E</sub>X from SGML source using the DocBuilder-0.9 Document System.

# Contents

<b>1</b>	<b>STDLIB Reference Manual</b>	<b>1</b>
1.1	STDLIB . . . . .	53
1.2	base64 . . . . .	54
1.3	beam_lib . . . . .	55
1.4	c . . . . .	63
1.5	calendar . . . . .	67
1.6	dets . . . . .	72
1.7	dict . . . . .	88
1.8	digraph . . . . .	93
1.9	digraph_utils . . . . .	100
1.10	epp . . . . .	104
1.11	erl_eval . . . . .	106
1.12	erl_expand_records . . . . .	109
1.13	erl_id_trans . . . . .	110
1.14	erl_internal . . . . .	111
1.15	erl_lint . . . . .	113
1.16	erl_parse . . . . .	115
1.17	erl_pp . . . . .	118
1.18	erl_scan . . . . .	121
1.19	erl_tar . . . . .	123
1.20	ets . . . . .	129
1.21	file_sorter . . . . .	150
1.22	filelib . . . . .	155
1.23	filename . . . . .	158
1.24	gb_sets . . . . .	164
1.25	gb_trees . . . . .	170
1.26	gen_event . . . . .	175
1.27	gen_fsm . . . . .	185
1.28	gen_server . . . . .	196
1.29	io . . . . .	205

1.30	io_lib . . . . .	216
1.31	lib . . . . .	220
1.32	lists . . . . .	222
1.33	log_mf_h . . . . .	237
1.34	math . . . . .	238
1.35	ms.transform . . . . .	240
1.36	orddict . . . . .	251
1.37	ordsets . . . . .	256
1.38	pg . . . . .	259
1.39	pool . . . . .	261
1.40	proc_lib . . . . .	263
1.41	proplists . . . . .	268
1.42	qlc . . . . .	273
1.43	queue . . . . .	290
1.44	random . . . . .	294
1.45	regexp . . . . .	296
1.46	sets . . . . .	301
1.47	shell . . . . .	304
1.48	shell_default . . . . .	314
1.49	slave . . . . .	315
1.50	sofs . . . . .	318
1.51	string . . . . .	341
1.52	supervisor . . . . .	347
1.53	supervisor_bridge . . . . .	354
1.54	sys . . . . .	357
1.55	timer . . . . .	364
1.56	win32reg . . . . .	368
1.57	zip . . . . .	372

# STDLIB Reference Manual

## Short Summaries

- Application **STDLIB** [page 53] – The STDLIB Application
- Erlang Module **base64** [page 54] – Implements base 64 encode and decode, see RFC2045.
- Erlang Module **beam.lib** [page 55] – An Interface To the BEAM File Format
- Erlang Module **c** [page 63] – Command Interface Module
- Erlang Module **calendar** [page 67] – Local and universal time, day-of-the-week, date and time conversions
- Erlang Module **dets** [page 72] – A Disk Based Term Storage
- Erlang Module **dict** [page 88] – Key-Value Dictionary
- Erlang Module **digraph** [page 93] – Directed Graphs
- Erlang Module **digraph\_utils** [page 100] – Algorithms for Directed Graphs
- Erlang Module **epp** [page 104] – An Erlang Code Preprocessor
- Erlang Module **erl\_eval** [page 106] – The Erlang Meta Interpreter
- Erlang Module **erl\_expand\_records** [page 109] – Expands Records in a Module
- Erlang Module **erl\_id\_trans** [page 110] – An Identity Parse Transform
- Erlang Module **erl\_internal** [page 111] – Internal Erlang Definitions
- Erlang Module **erl\_lint** [page 113] – The Erlang Code Linter
- Erlang Module **erl\_parse** [page 115] – The Erlang Parser
- Erlang Module **erl\_pp** [page 118] – The Erlang Pretty Printer
- Erlang Module **erl\_scan** [page 121] – The Erlang Token Scanner
- Erlang Module **erl\_tar** [page 123] – Unix 'tar' utility for reading and writing tar archives
- Erlang Module **ets** [page 129] – Built-In Term Storage
- Erlang Module **file\_sorter** [page 150] – File Sorter
- Erlang Module **filelib** [page 155] – File utilities, such as wildcard matching of filenames
- Erlang Module **filename** [page 158] – Filename Manipulation Functions
- Erlang Module **gb\_sets** [page 164] – General Balanced Trees
- Erlang Module **gb\_trees** [page 170] – General Balanced Trees
- Erlang Module **gen\_event** [page 175] – Generic Event Handling Behaviour
- Erlang Module **gen\_fsm** [page 185] – Generic Finite State Machine Behaviour

- Erlang Module **gen\_server** [page 196] – Generic Server Behaviour
- Erlang Module **io** [page 205] – Standard IO Server Interface Functions
- Erlang Module **io\_lib** [page 216] – IO Library Functions
- Erlang Module **lib** [page 220] – A number of useful library functions
- Erlang Module **lists** [page 222] – List Processing Functions
- Erlang Module **log\_mf\_h** [page 237] – An Event Handler which Logs Events to Disk
- Erlang Module **math** [page 238] – Mathematical Functions
- Erlang Module **ms\_transform** [page 240] – Parse\_transform that translates fun syntax into match specifications.
- Erlang Module **orddict** [page 251] – Key-Value Dictionary as Ordered List
- Erlang Module **ordsets** [page 256] – Functions for Manipulating Sets as Ordered Lists
- Erlang Module **pg** [page 259] – Distributed, Named Process Groups
- Erlang Module **pool** [page 261] – Load Distribution Facility
- Erlang Module **proc\_lib** [page 263] – Functions for asynchronous and synchronous start of processes adhering to the OTP design principles.
- Erlang Module **proplists** [page 268] – Support functions for property lists
- Erlang Module **qlc** [page 273] – Query Interface to Mnesia, ETS, Dets, etc
- Erlang Module **queue** [page 290] – Abstract Data Type for FIFO Queues
- Erlang Module **random** [page 294] – Pseudo random number generation
- Erlang Module **regexp** [page 296] – Regular Expression Functions for Strings
- Erlang Module **sets** [page 301] – Functions for Set Manipulation
- Erlang Module **shell** [page 304] – The Erlang Shell
- Erlang Module **shell\_default** [page 314] – Customizing the Erlang Environment
- Erlang Module **slave** [page 315] – Functions to Starting and Controlling Slave Nodes
- Erlang Module **sofs** [page 318] – Functions for Manipulating Sets of Sets
- Erlang Module **string** [page 341] – String Processing Functions
- Erlang Module **supervisor** [page 347] – Generic Supervisor Behaviour
- Erlang Module **supervisor\_bridge** [page 354] – Generic Supervisor Bridge Behaviour.
- Erlang Module **sys** [page 357] – A Functional Interface to System Messages
- Erlang Module **timer** [page 364] – Timer Functions
- Erlang Module **win32reg** [page 368] – win32reg provides access to the registry on Windows
- Erlang Module **zip** [page 372] – Utility for reading and creating 'zip' archives.

## STDLIB

No functions are exported.

## base64

The following functions are exported:

- `encode(Data) -> Base64`  
[page 54] Encodes data into base64.
- `encode_to_string(Data) -> Base64String`  
[page 54] Encodes data into base64.
- `decode(Base64) -> Data`  
[page 54] Decodes a base64 encoded string to data.
- `decode_to_string(Base64) -> DataString`  
[page 54] Decodes a base64 encoded string to data.
- `mime_decode(Base64) -> Data`  
[page 54] Decodes a base64 encoded string to data.
- `mime_decode_string(Base64) -> DataString`  
[page 54] Decodes a base64 encoded string to data.

## beam\_lib

The following functions are exported:

- `chunks(Beam, [ChunkRef]) -> {ok, {Module, [ChunkData]}} | {error, beam_lib, Reason}`  
[page 58] Read selected chunks from a BEAM file or binary
- `chunks(Beam, [ChunkRef], [Option]) -> {ok, {Module, [ChunkResult]}} | {error, beam_lib, Reason}`  
[page 58] Read selected chunks from a BEAM file or binary
- `version(Beam) -> {ok, {Module, [Version]}} | {error, beam_lib, Reason}`  
[page 58] Read the BEAM file's module version
- `md5(Beam) -> {ok, {Module, MD5}} | {error, beam_lib, Reason}`  
[page 59] Read the BEAM file's module version
- `info(Beam) -> [{Item, Info}] | {error, beam_lib, Reason1}`  
[page 59] Information about a BEAM file
- `cmp(Beam1, Beam2) -> ok | {error, beam_lib, Reason}`  
[page 60] Compare two BEAM files
- `cmp_dirs(Dir1, Dir2) -> {Only1, Only2, Different} | {error, beam_lib, Reason1}`  
[page 60] Compare the BEAM files in two directories
- `diff_dirs(Dir1, Dir2) -> ok | {error, beam_lib, Reason1}`  
[page 60] Compare the BEAM files in two directories
- `strip(Beam1) -> {ok, {Module, Beam2}} | {error, beam_lib, Reason1}`  
[page 60] Removes chunks not needed by the loader from a BEAM file
- `strip_files(Files) -> {ok, [{Module, Beam2}]} | {error, beam_lib, Reason1}`  
[page 60] Removes chunks not needed by the loader from BEAM files

- `strip_release(Dir) -> {ok, [{Module, Filename}]} | {error, beam_lib, Reason1}`  
[page 61] Removes chunks not needed by the loader from all BEAM files of a release
- `format_error(Reason) -> Chars`  
[page 61] Return an English description of a BEAM read error reply
- `crypto_key_fun(CryptoKeyFun) -> ok | {error, Reason}`  
[page 61] Register a fun that provides a crypto key
- `clear_crypto_key_fun() -> {ok, Result}`  
[page 62] Unregister the current crypto key fun

## C

The following functions are exported:

- `bt(Pid) -> void()`  
[page 63] Stack backtrace for a process
- `c(File) -> {ok, Module} | error`  
[page 63] Compile and load code in a file
- `c(File, Options) -> {ok, Module} | error`  
[page 63] Compile and load code in a file
- `cd(Dir) -> void()`  
[page 63] Change working directory
- `flush() -> void()`  
[page 64] Flush any messages sent to the shell
- `help() -> void()`  
[page 64] Help information
- `i() -> void()`  
[page 64] Information about the system
- `ni() -> void()`  
[page 64] Information about the system
- `i(X, Y, Z) -> void()`  
[page 64] Information about pid <X.Y.Z>
- `l(Module) -> void()`  
[page 64] Load or reload module
- `lc(Files) -> ok`  
[page 64] Compile a list of files
- `ls() -> void()`  
[page 64] List files in the current directory
- `ls(Dir) -> void()`  
[page 64] List files in a directory
- `m() -> void()`  
[page 65] Which modules are loaded
- `m(Module) -> void()`  
[page 65] Information about a module
- `memory() -> [{Type, Size}]`  
[page 65] Memory allocation information

- `memory(Type) -> Size`  
[page 65] Memory allocation information
- `memory([Type]) -> [{Type, Size}]`  
[page 65] Memory allocation information
- `nc(File) -> {ok, Module} | error`  
[page 65] Compile and load code in a file on all nodes
- `nc(File, Options) -> {ok, Module} | error`  
[page 65] Compile and load code in a file on all nodes
- `nl(Module) -> void()`  
[page 65] Load module on all nodes
- `pid(X, Y, Z) -> pid()`  
[page 65] Convert X,Y,Z to a pid
- `pwd() -> void()`  
[page 66] Print working directory
- `q() -> void()`  
[page 66] Quit - shorthand for `init:stop()`
- `regs() -> void()`  
[page 66] Information about registered processes
- `nregs() -> void()`  
[page 66] Information about registered processes
- `xm(ModSpec) -> void()`  
[page 66] Cross reference check a module
- `y(File) -> YeccRet`  
[page 66] Generate an LALR-1 parser
- `y(File, Options) -> YeccRet`  
[page 66] Generate an LALR-1 parser

## calendar

The following functions are exported:

- `date_to_gregorian_days(Date) -> Days`  
[page 68] Compute the number of days from year 0 up to the given date
- `date_to_gregorian_days(Year, Month, Day) -> Days`  
[page 68] Compute the number of days from year 0 up to the given date
- `datetime_to_gregorian_seconds({Date, Time}) -> Seconds`  
[page 68] Compute the number of seconds from year 0 up to the given date and time
- `day_of_the_week(Date) -> DayNumber`  
[page 68] Compute the day of the week
- `day_of_the_week(Year, Month, Day) -> DayNumber`  
[page 68] Compute the day of the week
- `gregorian_days_to_date(Days) -> Date`  
[page 68] Compute the date given the number of gregorian days
- `gregorian_seconds_to_datetime(Seconds) -> {Date, Time}`  
[page 68] Compute the date given the number of gregorian days

- `is_leap_year(Year) -> bool()`  
[page 68] Check if a year is a leap year
- `last_day_of_the_month(Year, Month) -> int()`  
[page 68] Compute the number of days in a month
- `local_time() -> {Date, Time}`  
[page 69] Compute local time
- `local_time_to_universal_time({Date1, Time1}) -> {Date2, Time2}`  
[page 69] Convert from local time to universal time (deprecated)
- `local_time_to_universal_time_dst({Date1, Time1}) -> [{Date, Time}]`  
[page 69] Convert from local time to universal time(s)
- `now_to_local_time(Now) -> {Date, Time}`  
[page 69] Convert now to local date and time
- `now_to_universal_time(Now) -> {Date, Time}`  
[page 70] Convert now to date and time
- `now_to_datetime(Now) -> {Date, Time}`  
[page 70] Convert now to date and time
- `seconds_to_daystime(Seconds) -> {Days, Time}`  
[page 70] Compute days and time from seconds
- `seconds_to_time(Seconds) -> Time`  
[page 70] Compute time from seconds
- `time_difference(T1, T2) -> {Days, Time}`  
[page 70] Compute the difference between two times (deprecated)
- `time_to_seconds(Time) -> Seconds`  
[page 70] Compute the number of seconds since midnight up to the given time
- `universal_time() -> {Date, Time}`  
[page 70] Compute universal time
- `universal_time_to_local_time({Date1, Time1}) -> {Date2, Time2}`  
[page 71] Convert from universal time to local time
- `valid_date(Date) -> bool()`  
[page 71] Check if a date is valid
- `valid_date(Year, Month, Day) -> bool()`  
[page 71] Check if a date is valid

## dets

The following functions are exported:

- `all() -> [Name]`  
[page 73] Return a list of the names of all open Dets tables on this node.
- `bchunk(Name, Continuation) -> {Continuation2, Data} | '$end_of_table' | {error, Reason}`  
[page 73] Return a chunk of objects stored in a Dets table.
- `close(Name) -> ok | {error, Reason}`  
[page 74] Close a Dets table.
- `delete(Name, Key) -> ok | {error, Reason}`  
[page 74] Delete all objects with a given key from a Dets table.

- `delete_all_objects(Name) -> ok | {error, Reason}`  
[page 74] Delete all objects from a Dets table.
- `delete_object(Name, Object) -> ok | {error, Reason}`  
[page 74] Delete a given object from a Dets table.
- `first(Name) -> Key | '$end_of_table'`  
[page 74] Return the first key stored in a Dets table.
- `foldl(Function, Acc0, Name) -> Acc1 | {error, Reason}`  
[page 75] Fold a function over a Dets table.
- `foldr(Function, Acc0, Name) -> Acc1 | {error, Reason}`  
[page 75] Fold a function over a Dets table.
- `from_ets(Name, EtsTab) -> ok | {error, Reason}`  
[page 75] Replace the objects of a Dets table with the objects of an Ets table.
- `info(Name) -> InfoList | undefined`  
[page 75] Return information about a Dets table.
- `info(Name, Item) -> Value | undefined`  
[page 76] Return the information associated with a given item for a Dets table.
- `init_table(Name, InitFun [, Options]) -> ok | {error, Reason}`  
[page 76] Replace all objects of a Dets table.
- `insert(Name, Objects) -> ok | {error, Reason}`  
[page 77] Insert one or more objects into a Dets table.
- `insert_new(Name, Objects) -> Bool`  
[page 77] Insert one or more objects into a Dets table.
- `is_compatible_bchunk_format(Name, BchunkFormat) -> Bool`  
[page 78] Test compatibility of a table's chunk data.
- `is_dets_file(FileName) -> Bool | {error, Reason}`  
[page 78] Test for a Dets table.
- `lookup(Name, Key) -> [Object] | {error, Reason}`  
[page 78] Return all objects with a given key stored in a Dets table.
- `match(Continuation) -> {[Match], Continuation2} | '$end_of_table' | {error, Reason}`  
[page 78] Match a chunk of objects stored in a Dets table and return a list of variable bindings.
- `match(Name, Pattern) -> [Match] | {error, Reason}`  
[page 79] Match the objects stored in a Dets table and return a list of variable bindings.
- `match(Name, Pattern, N) -> {[Match], Continuation} | '$end_of_table' | {error, Reason}`  
[page 79] Match the first chunk of objects stored in a Dets table and return a list of variable bindings.
- `match_delete(Name, Pattern) -> N | {error, Reason}`  
[page 79] Delete all objects that match a given pattern from a Dets table.
- `match_object(Continuation) -> {[Object], Continuation2} | '$end_of_table' | {error, Reason}`  
[page 80] Match a chunk of objects stored in a Dets table and return a list of objects.
- `match_object(Name, Pattern) -> [Object] | {error, Reason}`  
[page 80] Match the objects stored in a Dets table and return a list of objects.

- `match_object(Name, Pattern, N) -> {[Object], Continuation} | '$end_of_table' | {error, Reason}`  
[page 80] Match the first chunk of objects stored in a Dets table and return a list of objects.
- `member(Name, Key) -> Bool | {error, Reason}`  
[page 81] Test for occurrence of a key in a Dets table.
- `next(Name, Key1) -> Key2 | '$end_of_table'`  
[page 81] Return the next key in a Dets table.
- `open_file(Filename) -> {ok, Reference} | {error, Reason}`  
[page 81] Open an existing Dets table.
- `open_file(Name, Args) -> {ok, Name} | {error, Reason}`  
[page 81] Open a Dets table.
- `pid2name(Pid) -> {ok, Name} | undefined`  
[page 83] Return the name of the Dets table handled by a pid.
- `repair_continuation(Continuation, MatchSpec) -> Continuation2`  
[page 83] Repair a continuation from `select/1` or `select/3`.
- `safe_fixtable(Name, Fix)`  
[page 83] Fix a Dets table for safe traversal.
- `select(Continuation) -> {Selection, Continuation2} | '$end_of_table' | {error, Reason}`  
[page 84] Apply a match specification to some objects stored in a Dets table.
- `select(Name, MatchSpec) -> Selection | {error, Reason}`  
[page 84] Apply a match specification to all objects stored in a Dets table.
- `select(Name, MatchSpec, N) -> {Selection, Continuation} | '$end_of_table' | {error, Reason}`  
[page 84] Apply a match specification to the first chunk of objects stored in a Dets table.
- `select_delete(Name, MatchSpec) -> N | {error, Reason}`  
[page 85] Delete all objects that match a given pattern from a Dets table.
- `slot(Name, I) -> '$end_of_table' | [Object] | {error, Reason}`  
[page 85] Return the list of objects associated with a slot of a Dets table.
- `sync(Name) -> ok | {error, Reason}`  
[page 85] Ensure that all updates made to a Dets table are written to disk.
- `table(Name [, Options]) -> QueryHandle`  
[page 86] Return a QLC query handle.
- `to_ets(Name, EtsTab) -> EtsTab | {error, Reason}`  
[page 86] Insert all objects of a Dets table into an Ets table.
- `traverse(Name, Fun) -> Return | {error, Reason}`  
[page 87] Apply a function to all or some objects stored in a Dets table.
- `update_counter(Name, Key, Increment) -> Result`  
[page 87] Update a counter object stored in a Dets table.

## dict

The following functions are exported:

- `append(Key, Value, Dict1) -> Dict2`  
[page 88] Append a value to keys in a dictionary

- `append_list(Key, ValList, Dict1) -> Dict2`  
[page 88] Append new values to keys in a dictionary
- `erase(Key, Dict1) -> Dict2`  
[page 88] Erase a key from a dictionary
- `fetch(Key, Dict) -> Value`  
[page 89] Look-up values in a dictionary
- `fetch_keys(Dict) -> Keys`  
[page 89] Return all keys in a dictionary
- `filter(Pred, Dict1) -> Dict2`  
[page 89] Choose elements which satisfy a predicate
- `find(Key, Dict) -> {ok, Value} | error`  
[page 89] Search for a key in a dictionary
- `fold(Fun, Acc0, Dict) -> Acc1`  
[page 89] Fold a function over a dictionary
- `from_list(List) -> Dict`  
[page 89] Convert a list of pairs to a dictionary
- `is_key(Key, Dict) -> bool()`  
[page 90] Test if a key is in a dictionary
- `map(Fun, Dict1) -> Dict2`  
[page 90] Map a function over a dictionary
- `merge(Fun, Dict1, Dict2) -> Dict3`  
[page 90] Merge two dictionaries
- `new() -> dictionary()`  
[page 90] Create a dictionary
- `store(Key, Value, Dict1) -> Dict2`  
[page 90] Store a value in a dictionary
- `to_list(Dict) -> List`  
[page 90] Convert a dictionary to a list of pairs
- `update(Key, Fun, Dict1) -> Dict2`  
[page 91] Update a value in a dictionary
- `update(Key, Fun, Initial, Dict1) -> Dict2`  
[page 91] Update a value in a dictionary
- `update_counter(Key, Increment, Dict1) -> Dict2`  
[page 91] Increment a value in a dictionary

## digraph

The following functions are exported:

- `add_edge(G, E, V1, V2, Label) -> edge() | {error, Reason}`  
[page 93] Add an edge to a digraph.
- `add_edge(G, V1, V2, Label) -> edge() | {error, Reason}`  
[page 93] Add an edge to a digraph.
- `add_edge(G, V1, V2) -> edge() | {error, Reason}`  
[page 93] Add an edge to a digraph.
- `add_vertex(G, V, Label) -> vertex()`  
[page 94] Add or modify a vertex of a digraph.

- `add_vertex(G, V) -> vertex()`  
[page 94] Add or modify a vertex of a digraph.
- `add_vertex(G) -> vertex()`  
[page 94] Add or modify a vertex of a digraph.
- `del_edge(G, E) -> true`  
[page 94] Delete an edge from a digraph.
- `del_edges(G, Edges) -> true`  
[page 94] Delete edges from a digraph.
- `del_path(G, V1, V2) -> true`  
[page 94] Delete paths from a digraph.
- `del_vertex(G, V) -> true`  
[page 95] Delete a vertex from a digraph.
- `del_vertices(G, Vertices) -> true`  
[page 95] Delete vertices from a digraph.
- `delete(G) -> true`  
[page 95] Delete a digraph.
- `edge(G, E) -> {E, V1, V2, Label} | false`  
[page 95] Return the vertices and the label of an edge of a digraph.
- `edges(G) -> Edges`  
[page 95] Return all edges of a digraph.
- `edges(G, V) -> Edges`  
[page 95] Return the edges emanating from or incident on a vertex of a digraph.
- `get_cycle(G, V) -> Vertices | false`  
[page 96] Find one cycle in a digraph.
- `get_path(G, V1, V2) -> Vertices | false`  
[page 96] Find one path in a digraph.
- `get_short_cycle(G, V) -> Vertices | false`  
[page 96] Find one short cycle in a digraph.
- `get_short_path(G, V1, V2) -> Vertices | false`  
[page 96] Find one short path in a digraph.
- `in_degree(G, V) -> integer()`  
[page 97] Return the in-degree of a vertex of a digraph.
- `in_edges(G, V) -> Edges`  
[page 97] Return all edges incident on a vertex of a digraph.
- `in_neighbours(G, V) -> Vertices`  
[page 97] Return all in-neighbours of a vertex of a digraph.
- `info(G) -> InfoList`  
[page 97] Return information about a digraph.
- `new() -> digraph()`  
[page 98] Return a protected empty digraph, where cycles are allowed.
- `new(Type) -> digraph() | {error, Reason}`  
[page 98] Create a new empty digraph.
- `no_edges(G) -> integer() >= 0`  
[page 98] Return the number of edges of the a digraph.
- `no_vertices(G) -> integer() >= 0`  
[page 98] Return the number of vertices of a digraph.

- `out_degree(G, V) -> integer()`  
[page 98] Return the out-degree of a vertex of a digraph.
- `out_edges(G, V) -> Edges`  
[page 98] Return all edges emanating from a vertex of a digraph.
- `out_neighbours(G, V) -> Vertices`  
[page 98] Return all out-neighbours of a vertex of a digraph.
- `vertex(G, V) -> {V, Label} | false`  
[page 99] Return the label of a vertex of a digraph.
- `vertices(G) -> Vertices`  
[page 99] Return all vertices of a digraph.

## digraph\_utils

The following functions are exported:

- `components(Digraph) -> [Component]`  
[page 101] Return the components of a digraph.
- `condensation(Digraph) -> CondensedDigraph`  
[page 101] Return a condensed graph of a digraph.
- `cyclic_strong_components(Digraph) -> [StrongComponent]`  
[page 101] Return the cyclic strong components of a digraph.
- `is_acyclic(Digraph) -> bool()`  
[page 101] Check if a digraph is acyclic.
- `loop_vertices(Digraph) -> Vertices`  
[page 101] Return the vertices of a digraph included in some loop.
- `postorder(Digraph) -> Vertices`  
[page 102] Return the vertices of a digraph in post-order.
- `preorder(Digraph) -> Vertices`  
[page 102] Return the vertices of a digraph in pre-order.
- `reachable(Vertices, Digraph) -> Vertices`  
[page 102] Return the vertices reachable from some vertices of a digraph.
- `reachable_neighbours(Vertices, Digraph) -> Vertices`  
[page 102] Return the neighbours reachable from some vertices of a digraph.
- `reaching(Vertices, Digraph) -> Vertices`  
[page 102] Return the vertices that reach some vertices of a digraph.
- `reaching_neighbours(Vertices, Digraph) -> Vertices`  
[page 102] Return the neighbours that reach some vertices of a digraph.
- `strong_components(Digraph) -> [StrongComponent]`  
[page 103] Return the strong components of a digraph.
- `subgraph(Digraph, Vertices [, Options]) -> Subgraph | {error, Reason}`  
[page 103] Return a subgraph of a digraph.
- `topsort(Digraph) -> Vertices | false`  
[page 103] Return a topological sorting of the vertices of a digraph.

## epp

The following functions are exported:

- `open(FileName, IncludePath) -> {ok,Epp} | {error, ErrorDescriptor}`  
[page 104] Open a file for preprocessing
- `open(FileName, IncludePath, PredefMacros) -> {ok,Epp} | {error, ErrorDescriptor}`  
[page 104] Open a file for preprocessing
- `close(Epp) -> ok`  
[page 104] Close the preprocessing of the file associated with Epp
- `parse_erl_form(Epp) -> {ok, AbsForm} | {eof, Line} | {error, ErrorInfo}`  
[page 104] Return the next Erlang form from the opened Erlang source file
- `parse_file(FileName, IncludePath, PredefMacro) -> {ok, [Form]} | {error, OpenError}`  
[page 104] Preprocess and parse an Erlang source file

## erl\_eval

The following functions are exported:

- `exprs(Expressions, Bindings) -> {value, Value, NewBindings}`  
[page 106] Evaluate expressions
- `exprs(Expressions, Bindings, LocalFunctionHandler) -> {value, Value, NewBindings}`  
[page 106] Evaluate expressions
- `exprs(Expressions, Bindings, LocalFunctionHandler, NonlocalFunctionHandler) -> {value, Value, NewBindings}`  
[page 106] Evaluate expressions
- `expr(Expression, Bindings) -> { value, Value, NewBindings }`  
[page 106] Evaluate expression
- `expr(Expression, Bindings, LocalFunctionHandler) -> { value, Value, NewBindings }`  
[page 106] Evaluate expression
- `expr(Expression, Bindings, LocalFunctionHandler, NonlocalFunctionHandler) -> { value, Value, NewBindings }`  
[page 106] Evaluate expression
- `expr_list(ExpressionList, Bindings) -> {ValueList, NewBindings}`  
[page 107] Evaluate a list of expressions
- `expr_list(ExpressionList, Bindings, LocalFunctionHandler) -> {ValueList, NewBindings}`  
[page 107] Evaluate a list of expressions
- `expr_list(ExpressionList, Bindings, LocalFunctionHandler, NonlocalFunctionHandler) -> {ValueList, NewBindings}`  
[page 107] Evaluate a list of expressions
- `new_bindings() -> BindingStruct`  
[page 107] Return a bindings structure

- `bindings(BindingStruct) -> Bindings`  
[page 107] Return bindings
- `binding(Name, BindingStruct) -> Binding`  
[page 107] Return bindings
- `add_binding(Name, Value, Bindings) -> BindingStruct`  
[page 107] Add a binding
- `del_binding(Name, Bindings) -> BindingStruct`  
[page 107] Delete a binding

## `erl_expand_records`

The following functions are exported:

- `module(AbsForms, CompileOptions) -> AbsForms`  
[page 109] Expand all records in a module

## `erl_id_trans`

The following functions are exported:

- `parse_transform(Forms, Options) -> Forms`  
[page 110] Transform Erlang forms

## `erl_internal`

The following functions are exported:

- `bif(Name, Arity) -> bool()`  
[page 111] Test for an Erlang BIF
- `guard_bif(Name, Arity) -> bool()`  
[page 111] Test for an Erlang BIF allowed in guards
- `type_test(Name, Arity) -> bool()`  
[page 111] Test for a valid type test
- `arith_op(OpName, Arity) -> bool()`  
[page 111] Test for an arithmetic operator
- `bool_op(OpName, Arity) -> bool()`  
[page 111] Test for a Boolean operator
- `comp_op(OpName, Arity) -> bool()`  
[page 112] Test for a comparison operator
- `list_op(OpName, Arity) -> bool()`  
[page 112] Test for a list operator
- `send_op(OpName, Arity) -> bool()`  
[page 112] Test for a send operator
- `op_type(OpName, Arity) -> Type`  
[page 112] Return operator type

## erl\_lint

The following functions are exported:

- `module(AbsForms) -> {ok,Warnings} | {error,Errors,Warnings}`  
[page 113] Check a module for errors
- `module(AbsForms, FileName) -> {ok,Warnings} | {error,Errors,Warnings}`  
[page 113] Check a module for errors
- `module(AbsForms, FileName, CompileOptions) -> {ok,Warnings} | {error,Errors,Warnings}`  
[page 113] Check a module for errors
- `is_guard_test(Expr) -> bool()`  
[page 114] Test for a guard test
- `format_error(ErrorDescriptor) -> Chars`  
[page 114] Format an error descriptor

## erl\_parse

The following functions are exported:

- `parse_form(Tokens) -> {ok, AbsForm} | {error, ErrorInfo}`  
[page 115] Parse an Erlang form
- `parse_exprs(Tokens) -> {ok, Expr_list} | {error, ErrorInfo}`  
[page 115] Parse Erlang expressions
- `parse_term(Tokens) -> {ok, Term} | {error, ErrorInfo}`  
[page 115] Parse an Erlang term
- `format_error(ErrorDescriptor) -> Chars`  
[page 116] Format an error descriptor
- `tokens(AbsTerm) -> Tokens`  
[page 116] Generate a list of tokens for an expression
- `tokens(AbsTerm, MoreTokens) -> Tokens`  
[page 116] Generate a list of tokens for an expression
- `normalise(AbsTerm) -> Data`  
[page 116] Convert abstract form to an Erlang term
- `abstract(Data) -> AbsTerm`  
[page 116] Convert an Erlang term into an abstract form

## erl\_pp

The following functions are exported:

- `form(Form) -> DeepCharList`  
[page 118] Pretty print a form
- `form(Form, HookFunction) -> DeepCharList`  
[page 118] Pretty print a form
- `attribute(Attribute) -> DeepCharList`  
[page 118] Pretty print an attribute

- `attribute(Attribute, HookFunction) -> DeepCharList`  
[page 118] Pretty print an attribute
- `function(Function) -> DeepCharList`  
[page 118] Pretty print a function
- `function(Function, HookFunction) -> DeepCharList`  
[page 118] Pretty print a function
- `guard(Guard) -> DeepCharList`  
[page 118] Pretty print a guard
- `guard(Guard, HookFunction) -> DeepCharList`  
[page 118] Pretty print a guard
- `exprs(Expressions) -> DeepCharList`  
[page 119] Pretty print Expressions
- `exprs(Expressions, HookFunction) -> DeepCharList`  
[page 119] Pretty print Expressions
- `exprs(Expressions, Indent, HookFunction) -> DeepCharList`  
[page 119] Pretty print Expressions
- `expr(Expression) -> DeepCharList`  
[page 119] Pretty print one Expression
- `expr(Expression, HookFunction) -> DeepCharList`  
[page 119] Pretty print one Expression
- `expr(Expression, Indent, HookFunction) -> DeepCharList`  
[page 119] Pretty print one Expression
- `expr(Expression, Indent, Precedence, HookFunction) ->-> DeepCharList`  
[page 119] Pretty print one Expression

## erl\_scan

The following functions are exported:

- `string(CharList, StartLine) -> {ok, Tokens, EndLine} | Error`  
[page 121] Scan a string and returns the Erlang tokens
- `string(CharList) -> {ok, Tokens, EndLine} | Error`  
[page 121] Scan a string and returns the Erlang tokens
- `tokens(Continuation, CharList, StartLine) -> Return`  
[page 121] Re-entrant scanner
- `reserved_word(Atom) -> bool()`  
[page 122] Test for a reserved word
- `format_error(ErrorDescriptor) -> string()`  
[page 122] Format an error descriptor

## erl\_tar

The following functions are exported:

- `add(TarDescriptor, Filename, Options) -> RetValue`  
[page 124] Add a file to an open tar file

- `add(TarDescriptor, Filename, NameInArchive, Options) -> RetValue`  
[page 124] Add a file to an open tar file
- `close(TarDescriptor)`  
[page 124] Close an open tar file
- `create(Name, FileList) ->RetValue`  
[page 124] Create a tar archive
- `create(Name, FileList, OptionList)`  
[page 125] Create a tar archive with options
- `extract(Name) -> RetValue`  
[page 125] Extract all files from a tar file
- `extract(Name, OptionList)`  
[page 125] Extract files from a tar file
- `format_error(Reason) -> string()`  
[page 126] Convert error term to a readable string
- `open(Name, OpenModeList) -> RetValue`  
[page 126] Open a tar file.
- `table(Name) -> RetValue`  
[page 127] Retrieve the name of all files in a tar file
- `table(Name, Options)`  
[page 127] Retrieve name and information of all files in a tar file
- `t(Name)`  
[page 127] Print the name of each file in a tar file
- `tt(Name)`  
[page 127] Print name and information for each file in a tar file

## ets

The following functions are exported:

- `all() -> [Tab]`  
[page 130] Return a list of all ETS tables.
- `delete(Tab) -> true`  
[page 130] Delete an entire ETS table.
- `delete(Tab, Key) -> true`  
[page 130] Delete all objects with a given key from an ETS table.
- `delete_all_objects(Tab) -> true`  
[page 130] Delete all objects in an ETS table.
- `delete_object(Tab, Object) -> true`  
[page 130] Deletes a specific from an ETS table.
- `file2tab(Filename) -> {ok, Tab} | {error, Reason}`  
[page 131] Read an ETS table from a file.
- `first(Tab) -> Key | '$end_of_table'`  
[page 131] Return the first key in an ETS table.
- `fixtable(Tab, true|false) -> true | false`  
[page 131] Fix an ETS table for safe traversal (obsolete).
- `foldl(Function, Acc0, Tab) -> Acc1`  
[page 131] Fold a function over an ETS table

- `foldr(Function, Acc0, Tab) -> Acc1`  
[page 131] Fold a function over an ETS table
- `from_dets(Tab, DetsTab) -> Tab`  
[page 132] Fill an ETS table with objects from a Dets table.
- `fun2ms(LiteralFun) -> MatchSpec`  
[page 132] Pseudo function that transforms fun syntax to a match\_spec.
- `i() -> void()`  
[page 133] Display information about all ETS tables on tty.
- `i(Tab) -> void()`  
[page 133] Browse an ETS table on tty.
- `info(Tab) -> [{Item, Value}] | undefined`  
[page 133] Return information about an ETS table.
- `info(Tab, Item) -> Value | undefined`  
[page 134] Return the information associated with given item for an ETS table.
- `init_table(Name, InitFun) -> true`  
[page 134] Replace all objects of an ETS table.
- `insert(Tab, ObjectOrObjects) -> true`  
[page 135] Insert an object into an ETS table.
- `insert_new(Tab, ObjectOrObjects) -> bool()`  
[page 135] Insert an object into an ETS table if the key is not already present.
- `is_compiled_ms(Term) -> bool()`  
[page 135] Checks if an Erlang term is the result of `ets:match_spec_compile`
- `last(Tab) -> Key | '$end_of_table'`  
[page 136] Return the last key in an ETS table of type `ordered_set`.
- `lookup(Tab, Key) -> [Object]`  
[page 136] Return all objects with a given key in an ETS table.
- `lookup_element(Tab, Key, Pos) -> Elem`  
[page 136] Return the Pos:th element of all objects with a given key in an ETS table.
- `match(Tab, Pattern) -> [Match]`  
[page 137] Match the objects in an ETS table against a pattern.
- `match(Tab, Pattern, Limit) -> {[Match], Continuation} | '$end_of_table'`  
[page 137] Match the objects in an ETS table against a pattern and returns part of the answers.
- `match(Continuation) -> {[Match], Continuation} | '$end_of_table'`  
[page 138] Continues matching objects in an ETS table.
- `match_delete(Tab, Pattern) -> true`  
[page 138] Delete all objects which match a given pattern from an ETS table.
- `match_object(Tab, Pattern) -> [Object]`  
[page 138] Match the objects in an ETS table against a pattern.
- `match_object(Tab, Pattern, Limit) -> {[Match], Continuation} | '$end_of_table'`  
[page 138] Match the objects in an ETS table against a pattern and returns part of the answers.
- `match_object(Continuation) -> {[Match], Continuation} | '$end_of_table'`  
[page 139] Continues matching objects in an ETS table.

- `match_spec_compile(MatchSpec) -> CompiledMatchSpec`  
[page 139] Compiles a match specification into its internal representation
- `match_spec_run(List, CompiledMatchSpec) -> list()`  
[page 139] Performs matching, using a compiled `match_spec`, on a list of tuples
- `member(Tab, Key) -> true | false`  
[page 140] Tests for occurrence of a key in an ETS table
- `new(Name, Options) -> tid()`  
[page 140] Create a new ETS table.
- `next(Tab, Key1) -> Key2 | '$end_of_table'`  
[page 141] Return the next key in an ETS table.
- `prev(Tab, Key1) -> Key2 | '$end_of_table'`  
[page 141] Return the previous key in an ETS table of type `ordered_set`.
- `rename(Tab, Name) -> Name`  
[page 142] Rename a named ETS table.
- `repair_continuation(Continuation, MatchSpec) -> Continuation`  
[page 142] Repair a continuation from `ets:select/1` or `ets:select/3` that has passed through external representation
- `safe_fixtable(Tab, true|false) -> true`  
[page 143] Fix an ETS table for safe traversal.
- `select(Tab, MatchSpec) -> [Match]`  
[page 144] Match the objects in an ETS table against a `match_spec`.
- `select(Tab, MatchSpec, Limit) -> {[Match], Continuation} | '$end_of_table'`  
[page 145] Match the objects in an ETS table against a `match_spec` and returns part of the answers.
- `select(Continuation) -> {[Match], Continuation} | '$end_of_table'`  
[page 145] Continue matching objects in an ETS table.
- `select_delete(Tab, MatchSpec) -> NumDeleted`  
[page 145] Match the objects in an ETS table against a `match_spec` and deletes objects where the `match_spec` returns 'true'
- `select_count(Tab, MatchSpec) -> NumMatched`  
[page 146] Match the objects in an ETS table against a `match_spec` and returns the number of objects for which the `match_spec` returned 'true'
- `slot(Tab, I) -> [Object] | '$end_of_table'`  
[page 146] Return all objects in a given slot of an ETS table.
- `tab2file(Tab, Filename) -> ok | {error, Reason}`  
[page 146] Dump an ETS table to a file.
- `tab2list(Tab) -> [Object]`  
[page 147] Return a list of all objects in an ETS table.
- `table(Tab [, Options]) -> QueryHandle`  
[page 147] Return a QLC query handle.
- `test_ms(Tuple, MatchSpec) -> {ok, Result} | {error, Errors}`  
[page 148] Test a `match_spec` for use in `ets:select/2`.
- `to_dets(Tab, DetsTab) -> Tab`  
[page 148] Fill a Dets table with objects from an ETS table.
- `update_counter(Tab, Key, {Pos, Incr, Threshold, SetValue}) -> Result`  
[page 148] Update a counter object in an ETS table.

- `update_counter(Tab, Key, {Pos,Incr}) -> Result`  
[page 148] Update a counter object in an ETS table.
- `update_counter(Tab, Key, Incr) -> Result`  
[page 148] Update a counter object in an ETS table.

## file\_sorter

The following functions are exported:

- `sort(FileName) -> Reply`  
[page 153] Sort terms on files.
- `sort(Input, Output) -> Reply`  
[page 153] Sort terms on files.
- `sort(Input, Output, Options) -> Reply`  
[page 153] Sort terms on files.
- `keysort(KeyPos, FileName) -> Reply`  
[page 153] Sort terms on files by key.
- `keysort(KeyPos, Input, Output) -> Reply`  
[page 153] Sort terms on files by key.
- `keysort(KeyPos, Input, Output, Options) -> Reply`  
[page 153] Sort terms on files by key.
- `merge(FileNames, Output) -> Reply`  
[page 153] Merge terms on files.
- `merge(FileNames, Output, Options) -> Reply`  
[page 153] Merge terms on files.
- `keymerge(KeyPos, FileNames, Output) -> Reply`  
[page 154] Merge terms on files by key.
- `keymerge(KeyPos, FileNames, Output, Options) -> Reply`  
[page 154] Merge terms on files by key.
- `check(FileName) -> Reply`  
[page 154] Check whether terms on files are sorted.
- `check(FileNames, Options) -> Reply`  
[page 154] Check whether terms on files are sorted.
- `keycheck(KeyPos, FileName) -> CheckReply`  
[page 154] Check whether terms on files are sorted by key.
- `keycheck(KeyPos, FileNames, Options) -> Reply`  
[page 154] Check whether terms on files are sorted by key.

## filelib

The following functions are exported:

- `ensure_dir(Name) -> ok | {error, Reason}`  
[page 155] Ensure that all parent directories for a file or directory exist.
- `file_size(Filename) -> integer()`  
[page 155] Return the size in bytes of the file.
- `fold_files(Dir, RegExp, Recursive, Fun, AccIn) -> AccOut`  
[page 155] Fold over all files matching a regular expression.

- `is_dir(Name) -> true | false`  
[page 155] Test whether Name refer to a directory or not
- `is_file(Name) -> true | false`  
[page 155] Test whether Name refer to a file or directory.
- `is_regular(Name) -> true | false`  
[page 156] Test whether Name refer to a (regular) file.
- `last_modified(Name) -> {{Year,Month,Day},{Hour,Min,Sec}}`  
[page 156] Return the local date and time when a file was last modified.
- `wildcard(Wildcard) -> list()`  
[page 156] Match filenames using Unix-style wildcards.
- `wildcard(Wildcard, Cwd) -> list()`  
[page 157] Match filenames using Unix-style wildcards startin at a specified directory.

## filename

The following functions are exported:

- `absname(Filename) -> string()`  
[page 158] Convert a filename to an absolute name, relative the working directory
- `absname(Filename, Dir) -> string()`  
[page 159] Convert a filename to an absolute name, relative a specified directory
- `absname_join(Dir, Filename) -> string()`  
[page 159] Join an absolute directory with a relative filename
- `basename(Filename) -> string()`  
[page 159] Return the last component of a filename
- `basename(Filename, Ext) -> string()`  
[page 159] Return the last component of a filename, stripped of the specified extension
- `dirname(Filename) -> string()`  
[page 160] Return the directory part of a path name
- `extension(Filename) -> string()`  
[page 160] Return the file extension
- `flatten(Filename) -> string()`  
[page 160] Convert a filename to a flat string
- `join(Components) -> string()`  
[page 161] Join a list of filename components with directory separators
- `join(Name1, Name2) -> string()`  
[page 161] Join two filename components with directory separators
- `native_name(Path) -> string()`  
[page 161] Return the native form of a file path
- `pathtype(Path) -> absolute | relative | volumerelative`  
[page 161] Return the type of a path
- `rootname(Filename) -> string()`  
[page 162] Remove a filename extension
- `rootname(Filename, Ext) -> string()`  
[page 162] Remove a filename extension

- `split(Filename) -> Components`  
[page 162] Split a filename into its path components
- `find_src(Beam) -> {SourceFile, Options}`  
[page 162] Find the filename and compiler options for a module
- `find_src(Beam, Rules) -> {SourceFile, Options}`  
[page 162] Find the filename and compiler options for a module

## gb\_sets

The following functions are exported:

- `add(Element, Set1) -> Set2`  
[page 165] Add a (possibly existing) element to a `gb_set`
- `add_element(Element, Set1) -> Set2`  
[page 165] Add a (possibly existing) element to a `gb_set`
- `balance(Set1) -> Set2`  
[page 165] Rebalance tree representation of a `gb_set`
- `delete(Element, Set1) -> Set2`  
[page 165] Remove an element from a `gb_set`
- `delete_any(Element, Set1) -> Set2`  
[page 165] Remove a (possibly non-existing) element from a `gb_set`
- `del_element(Element, Set1) -> Set2`  
[page 165] Remove a (possibly non-existing) element from a `gb_set`
- `difference(Set1, Set2) -> Set3`  
[page 165] Return the difference of two `gb_sets`
- `subtract(Set1, Set2) -> Set3`  
[page 166] Return the difference of two `gb_sets`
- `empty() -> Set`  
[page 166] Return an empty `gb_set`
- `new() -> Set`  
[page 166] Return an empty `gb_set`
- `filter(Pred, Set1) -> Set2`  
[page 166] Filter `gb_set` elements
- `fold(Function, Acc0, Set) -> Acc1`  
[page 166] Fold over `gb_set` elements
- `from_list(List) -> Set`  
[page 166] Convert a list into a `gb_set`
- `from_ordset(List) -> Set`  
[page 166] Make a `gb_set` from an ordset list
- `insert(Element, Set1) -> Set2`  
[page 166] Add a new element to a `gb_set`
- `intersection(Set1, Set2) -> Set3`  
[page 167] Return the intersection of two `gb_sets`
- `intersection(SetList) -> Set`  
[page 167] Return the intersection of a list of `gb_sets`
- `is_empty(Set) -> bool()`  
[page 167] Test for empty `gb_set`

- `is_member(Element, Set) -> bool()`  
[page 167] Test for membership of a `gb_set`
- `is_element(Element, Set) -> bool()`  
[page 167] Test for membership of a `gb_set`
- `is_set(Set) -> bool()`  
[page 167] Test for a `gb_set`
- `is_subset(Set1, Set2) -> bool()`  
[page 167] Test for subset
- `iterator(Set) -> Iter`  
[page 167] Return an iterator for a `gb_set`
- `largest(Set) -> term()`  
[page 168] Return largest element
- `next(Iter1) -> {Element, Iter2 | none}`  
[page 168] Traverse a `gb_set` with an iterator
- `singleton(Element) -> gb_set()`  
[page 168] Return a `gb_set` with one element
- `size(Set) -> int()`  
[page 168] Return the number of elements in a `gb_set`
- `smallest(Set) -> term()`  
[page 168] Return smallest element
- `take_largest(Set1) -> {Element, Set2}`  
[page 168] Extract largest element
- `take_smallest(Set1) -> {Element, Set2}`  
[page 168] Extract smallest element
- `to_list(Set) -> List`  
[page 169] Convert a `gb_set` into a list
- `union(Set1, Set2) -> Set3`  
[page 169] Return the union of two `gb_sets`
- `union(SetList) -> Set`  
[page 169] Return the union of a list of `gb_sets`

## gb\_trees

The following functions are exported:

- `balance(Tree1) -> Tree2`  
[page 170] Rebalance a tree
- `delete(Key, Tree1) -> Tree2`  
[page 170] Remove a node from a tree
- `delete_any(Key, Tree1) -> Tree2`  
[page 171] Remove a (possibly non-existing) node from a tree
- `empty() -> Tree`  
[page 171] Return an empty tree
- `enter(Key, Val, Tree1) -> Tree2`  
[page 171] Insert or update key with value in a tree
- `from_orddict(List) -> Tree`  
[page 171] Make a tree from an orddict

- `get(Key, Tree) -> Val`  
[page 171] Look up a key in a tree, if present
- `lookup(Key, Tree) -> {value, Val} | none`  
[page 171] Look up a key in a tree
- `insert(Key, Val, Tree1) -> Tree2`  
[page 172] Insert a new key and value in a tree
- `is_defined(Key, Tree) -> bool()`  
[page 172] Test for membership of a tree
- `is_empty(Tree) -> bool()`  
[page 172] Test for empty tree
- `iterator(Tree) -> Iter`  
[page 172] Return an iterator for a tree
- `keys(Tree) -> [Key]`  
[page 172] Return a list of the keys in a tree
- `largest(Tree) -> {Key, Val}`  
[page 172] Return largest key and value
- `next(Iter1) -> {Key, Val, Iter2}`  
[page 172] Traverse a tree with an iterator
- `size(Tree) -> int()`  
[page 173] Return the number of nodes in a tree
- `smallest(Tree) -> {Key, Val}`  
[page 173] Return smallest key and value
- `take_largest(Tree1) -> {Key, Val, Tree2}`  
[page 173] Extract largest key and value
- `take_smallest(Tree1) -> {Key, Val, Tree2}`  
[page 173] Extract smallest key and value
- `to_list(Tree) -> [{Key, Val}]`  
[page 173] Convert a tree into a list
- `update(Key, Val, Tree1) -> Tree2`  
[page 173] Update a key to new value in a tree
- `values(Tree) -> [Val]`  
[page 174] Return a list of the values in a tree

## gen\_event

The following functions are exported:

- `start_link() -> Result`  
[page 176] Create a generic event manager process in a supervision tree.
- `start_link(EventMgrName) -> Result`  
[page 176] Create a generic event manager process in a supervision tree.
- `start() -> Result`  
[page 176] Create a stand-alone event manager process.
- `start(EventMgrName) -> Result`  
[page 176] Create a stand-alone event manager process.
- `add_handler(EventMgrRef, Handler, Args) -> Result`  
[page 176] Add an event handler to a generic event manager.

- `add_sup_handler(EventMgrRef, Handler, Args) -> Result`  
[page 177] Add a supervised event handler to a generic event manager.
- `notify(EventMgrRef, Event) -> ok`  
[page 178] Notify an event manager about an event.
- `sync_notify(EventMgrRef, Event) -> ok`  
[page 178] Notify an event manager about an event.
- `call(EventMgrRef, Handler, Request) -> Result`  
[page 178] Make a synchronous call to a generic event manager.
- `call(EventMgrRef, Handler, Request, Timeout) -> Result`  
[page 178] Make a synchronous call to a generic event manager.
- `delete_handler(EventMgrRef, Handler, Args) -> Result`  
[page 179] Delete an event handler from a generic event manager.
- `swap_handler(EventMgrRef, {Handler1,Args1}, {Handler2,Args2}) -> Result`  
[page 179] Replace an event handler in a generic event manager.
- `swap_sup_handler(EventMgrRef, {Handler1,Args1}, {Handler2,Args2}) -> Result`  
[page 180] Replace an event handler in a generic event manager.
- `which_handlers(EventMgrRef) -> [Handler]`  
[page 180] Return all event handlers installed in a generic event manager.
- `stop(EventMgrRef) -> ok`  
[page 181] Terminate a generic event manager.
- `Module:init(InitArgs) -> {ok,State}`  
[page 181] Initialize an event handler.
- `Module:handle_event(Event, State) -> Result`  
[page 181] Handle an event.
- `Module:handle_call(Request, State) -> Result`  
[page 182] Handle a synchronous request.
- `Module:handle_info(Info, State) -> Result`  
[page 182] Handle an incoming message.
- `Module:terminate(Arg, State) -> term()`  
[page 183] Clean up before deletion.
- `Module:code_change(OldVsn, State, Extra) -> {ok, NewState}`  
[page 183] Update the internal state during upgrade/downgrade.

## gen\_fsm

The following functions are exported:

- `start_link(Module, Args, Options) -> Result`  
[page 186] Create a gen\_fsm process in a supervision tree.
- `start_link(FsmName, Module, Args, Options) -> Result`  
[page 186] Create a gen\_fsm process in a supervision tree.
- `start(Module, Args, Options) -> Result`  
[page 187] Create a stand-alone gen\_fsm process.
- `start(FsmName, Module, Args, Options) -> Result`  
[page 187] Create a stand-alone gen\_fsm process.

- `send_event(FsmRef, Event) -> ok`  
[page 187] Send an event asynchronously to a generic FSM.
- `send_all_state_event(FsmRef, Event) -> ok`  
[page 188] Send an event asynchronously to a generic FSM.
- `sync_send_event(FsmRef, Event) -> Reply`  
[page 188] Send an event synchronously to a generic FSM.
- `sync_send_event(FsmRef, Event, Timeout) -> Reply`  
[page 188] Send an event synchronously to a generic FSM.
- `sync_send_all_state_event(FsmRef, Event) -> Reply`  
[page 188] Send an event synchronously to a generic FSM.
- `sync_send_all_state_event(FsmRef, Event, Timeout) -> Reply`  
[page 188] Send an event synchronously to a generic FSM.
- `reply(Caller, Reply) -> true`  
[page 189] Send a reply to a caller.
- `send_event_after(Time, Event) -> Ref`  
[page 189] Send a delayed event internally in a generic FSM.
- `start_timer(Time, Msg) -> Ref`  
[page 189] Send a timeout event internally in a generic FSM.
- `cancel_timer(Ref) -> RemainingTime | false`  
[page 190] Cancel an internal timer in a generic FSM.
- `enter_loop(Module, Options, StateName, StateData)`  
[page 190] Enter the `gen_fsm` receive loop
- `enter_loop(Module, Options, StateName, StateData, FsmName)`  
[page 190] Enter the `gen_fsm` receive loop
- `enter_loop(Module, Options, StateName, StateData, Timeout)`  
[page 190] Enter the `gen_fsm` receive loop
- `enter_loop(Module, Options, StateName, StateData, FsmName, Timeout)`  
[page 190] Enter the `gen_fsm` receive loop
- `Module:init(Args) -> Result`  
[page 191] Initialize process and internal state name and state data.
- `Module:StateName(Event, StateData) -> Result`  
[page 192] Handle an asynchronous event.
- `Module:handle_event(Event, StateName, StateData) -> Result`  
[page 192] Handle an asynchronous event.
- `Module:StateName(Event, From, StateData) -> Result`  
[page 193] Handle a synchronous event.
- `Module:handle_sync_event(Event, From, StateName, StateData) -> Result`  
[page 193] Handle a synchronous event.
- `Module:handle_info(Info, StateName, StateData) -> Result`  
[page 194] Handle an incoming message.
- `Module:terminate(Reason, StateName, StateData)`  
[page 194] Clean up before termination.
- `Module:code_change(OldVsn, StateName, StateData, Extra) -> {ok, NextStateName, NewStateData}`  
[page 195] Update the internal state data during upgrade/downgrade.

## gen\_server

The following functions are exported:

- `start_link(Module, Args, Options) -> Result`  
[page 196] Create a `gen_server` process in a supervision tree.
- `start_link(ServerName, Module, Args, Options) -> Result`  
[page 196] Create a `gen_server` process in a supervision tree.
- `start(Module, Args, Options) -> Result`  
[page 197] Create a stand-alone `gen_server` process.
- `start(ServerName, Module, Args, Options) -> Result`  
[page 197] Create a stand-alone `gen_server` process.
- `call(ServerRef, Request) -> Reply`  
[page 198] Make a synchronous call to a generic server.
- `call(ServerRef, Request, Timeout) -> Reply`  
[page 198] Make a synchronous call to a generic server.
- `multi_call(Name, Request) -> Result`  
[page 199] Make a synchronous call to several generic servers.
- `multi_call(Nodes, Name, Request) -> Result`  
[page 199] Make a synchronous call to several generic servers.
- `multi_call(Nodes, Name, Request, Timeout) -> Result`  
[page 199] Make a synchronous call to several generic servers.
- `cast(ServerRef, Request) -> ok`  
[page 200] Send an asynchronous request to a generic server.
- `abcast(Name, Request) -> abcast`  
[page 200] Send an asynchronous request to several generic servers.
- `abcast(Nodes, Name, Request) -> abcast`  
[page 200] Send an asynchronous request to several generic servers.
- `reply(Client, Reply) -> true`  
[page 200] Send a reply to a client.
- `enter_loop(Module, Options, State)`  
[page 201] Enter the `gen_server` receive loop
- `enter_loop(Module, Options, State, ServerName)`  
[page 201] Enter the `gen_server` receive loop
- `enter_loop(Module, Options, State, Timeout)`  
[page 201] Enter the `gen_server` receive loop
- `enter_loop(Module, Options, State, ServerName, Timeout)`  
[page 201] Enter the `gen_server` receive loop
- `Module:init(Args) -> Result`  
[page 202] Initialize process and internal state.
- `Module:handle_call(Request, From, State) -> Result`  
[page 202] Handle a synchronous request.
- `Module:handle_cast(Request, State) -> Result`  
[page 203] Handle an asynchronous request.
- `Module:handle_info(Info, State) -> Result`  
[page 203] Handle an incoming message.

- `Module:terminate(Reason, State)`  
[page 203] Clean up before termination.
- `Module:code_change(OldVsn, State, Extra) -> {ok, NewState}`  
[page 204] Update the internal state during upgrade/downgrade.

## io

The following functions are exported:

- `put_chars([IoDevice,] IoData) -> ok`  
[page 205] Write a list of characters
- `nl([IoDevice]) -> ok`  
[page 205] Write a newline
- `get_chars([IoDevice,] Prompt, Count) -> string() | eof`  
[page 205] Read a specified number of characters
- `get_line([IoDevice,] Prompt) -> string() | eof`  
[page 206] Read a line
- `setopts([IoDevice,] Opts) -> ok | {error, Reason}`  
[page 206] Set options
- `write([IoDevice,] Term) -> ok`  
[page 206] Write a term
- `read([IoDevice,] Prompt) -> Result`  
[page 207] Read a term
- `read(IoDevice, Prompt, StartLine) -> Result`  
[page 207] Read a term
- `fwrite(Format) ->`  
[page 207] Write formatted output
- `fwrite([IoDevice,] Format, Data) -> ok`  
[page 207] Write formatted output
- `format(Format) ->`  
[page 207] Write formatted output
- `format([IoDevice,] Format, Data) -> ok`  
[page 207] Write formatted output
- `fread([IoDevice,] Prompt, Format) -> Result`  
[page 211] Read formatted input
- `scan_erl_exprs(Prompt) ->`  
[page 213] Read and tokenize Erlang expressions
- `scan_erl_exprs([IoDevice,] Prompt, StartLine) -> Result`  
[page 213] Read and tokenize Erlang expressions
- `scan_erl_form(Prompt) ->`  
[page 213] Read and tokenize an Erlang form
- `scan_erl_form([IoDevice,] Prompt, StartLine) -> Result`  
[page 213] Read and tokenize an Erlang form
- `parse_erl_exprs(Prompt) ->`  
[page 214] Read, tokenize and parse Erlang expressions
- `parse_erl_exprs([IoDevice,] Prompt, StartLine) -> Result`  
[page 214] Read, tokenize and parse Erlang expressions

- `parse_erl_form(Prompt) ->`  
[page 214] Read, tokenize and parse an Erlang form
- `parse_erl_form([IoDevice,] Prompt, StartLine) -> Result`  
[page 214] Read, tokenize and parse an Erlang form

## io\_lib

The following functions are exported:

- `nl() -> chars()`  
[page 216] Write a newline
- `write(Term) ->`  
[page 216] Write a term
- `write(Term, Depth) -> chars()`  
[page 216] Write a term
- `print(Term) ->`  
[page 216] Pretty print a term
- `print(Term, Column, LineLength, Depth) -> chars()`  
[page 216] Pretty print a term
- `fwrite(Format, Data) ->`  
[page 217] Write formatted output
- `format(Format, Data) -> chars()`  
[page 217] Write formatted output
- `fread(Format, String) -> Result`  
[page 217] Read formatted input
- `fread(Continuation, String, Format) -> Return`  
[page 217] Re-entrant formatted reader
- `write_atom(Atom) -> chars()`  
[page 218] Write an atom
- `write_string(String) -> chars()`  
[page 218] Write a string
- `write_char(Integer) -> chars()`  
[page 218] Write a character
- `indentation(String, StartIndent) -> int()`  
[page 218] Indentation after printing string
- `char_list(Term) -> bool()`  
[page 219] Test for a list of characters
- `deep_char_list(Term) -> bool()`  
[page 219] Test for a deep list of characters
- `printable_list(Term) -> bool()`  
[page 219] Test for a list of printable characters

## lib

The following functions are exported:

- `flush_receive() -> void()`  
[page 220] Flush messages
- `error_message(Format, Args) -> ok`  
[page 220] Print error message
- `progrname() -> atom()`  
[page 220] Return name of Erlang start script
- `nonl(String1) -> String2`  
[page 220] Remove last newline
- `send(To, Msg)`  
[page 220] Send a message
- `sendw(To, Msg)`  
[page 221] Send a message and wait for an answer

## lists

The following functions are exported:

- `all(Pred, List) -> bool()`  
[page 222] Return true if all elements in the list satisfy Pred
- `any(Pred, List) -> bool()`  
[page 222] Return true if any of the elements in the list satisfies Pred
- `append(ListOfLists) -> List1`  
[page 222] Append a list of lists
- `append(List1, List2) -> List3`  
[page 222] Append two lists
- `concat(Things) -> string()`  
[page 223] Concatenate a list of atoms
- `delete(Elem, List1) -> List2`  
[page 223] Delete an element from a list
- `dropwhile(Pred, List1) -> List2`  
[page 223] Drop elements from a list while a predicate is true
- `duplicate(N, Elem) -> List`  
[page 223] Make N copies of element
- `filter(Pred, List1) -> List2`  
[page 224] Choose elements which satisfy a predicate
- `flatlength(DeepList) -> int()`  
[page 224] Length of flattened deep list
- `flatmap(Fun, List1) -> List2`  
[page 224] Map and flatten in one pass
- `flatten(DeepList) -> List`  
[page 224] Flatten a deep list
- `flatten(DeepList, Tail) -> List`  
[page 224] Flatten a deep list

- `foldl(Fun, Acc0, List) -> Acc1`  
[page 224] Fold a function over a list
- `foldr(Fun, Acc0, List) -> Acc1`  
[page 225] Fold a function over a list
- `foreach(Fun, List) -> void()`  
[page 225] Apply a function to each element of a list
- `keydelete(Key, N, TupleList1) -> TupleList2`  
[page 225] Delete an element from a list of tuples
- `keymap(Fun, N, TupleList1) -> TupleList2`  
[page 226] Map a function over a list of tuples
- `keymember(Key, N, TupleList) -> bool()`  
[page 226] Test for membership of a list of tuples
- `keymerge(N, TupleList1, TupleList2) -> TupleList3`  
[page 226] Merge two key-sorted lists of tuples
- `keyreplace(Key, N, TupleList1, NewTuple) -> TupleList2`  
[page 226] Replace an element in a list of tuples
- `keysearch(Key, N, TupleList) -> {value, Tuple} | false`  
[page 227] Search for an element in a list of tuples
- `keysort(N, TupleList1) -> TupleList2`  
[page 227] Sort a list of tuples
- `last(List) -> Last`  
[page 227] Return last element in a list
- `map(Fun, List1) -> List2`  
[page 227] Map a function over a list
- `mapfoldl(Fun, Acc0, List1) -> {List2, Acc1}`  
[page 227] Map and fold in one pass
- `mapfoldr(Fun, Acc0, List1) -> {List2, Acc1}`  
[page 228] Map and fold in one pass
- `max(List) -> Max`  
[page 228] Return maximum element of a list
- `member(Elem, List) -> bool()`  
[page 228] Test for membership of a list
- `merge(ListOfLists) -> List1`  
[page 228] Merge a list of sorted lists
- `merge(List1, List2) -> List3`  
[page 228] Merge two sorted lists
- `merge(Fun, List1, List2) -> List3`  
[page 229] Merge two sorted list
- `merge3(List1, List2, List3) -> List4`  
[page 229] Merge three sorted lists
- `min(List) -> Min`  
[page 229] Return minimum element of a list
- `nth(N, List) -> Elem`  
[page 229] Return the Nth element of a list
- `nthtail(N, List1) -> Tail`  
[page 229] Return the Nth tail of a list

- `partition(Pred, List) -> {Satisfying, NonSatisfying}`  
[page 230] Partition a list into two lists based on a predicate
- `prefix(List1, List2) -> bool()`  
[page 230] Test for list prefix
- `reverse(List1) -> List2`  
[page 230] Reverse a list
- `reverse(List1, Tail) -> List2`  
[page 230] Reverse a list appending a tail
- `seq(From, To) -> Seq`  
[page 231] Generate a sequence of integers
- `seq(From, To, Incr) -> Seq`  
[page 231] Generate a sequence of integers
- `sort(List1) -> List2`  
[page 231] Sort a list
- `sort(Fun, List1) -> List2`  
[page 231] Sort a list
- `split(N, List1) -> {List2, List3}`  
[page 231] Split a list into two lists
- `splitwith(Pred, List) -> {List1, List2}`  
[page 231] Split a list into two lists based on a predicate
- `sublist(List1, Len) -> List2`  
[page 232] Return a sub-list of a certain length, starting at the first position
- `sublist(List1, Start, Len) -> List2`  
[page 232] Return a sub-list starting at a given position and with a given number of elements
- `subtract(List1, List2) -> List3`  
[page 232] Subtract the element in one list from another list
- `suffix(List1, List2) -> bool()`  
[page 233] Test for list suffix
- `sum(List) -> number()`  
[page 233] Return sum of elements in a list
- `takewhile(Pred, List1) -> List2`  
[page 233] Take elements from a list while a predicate is true
- `ukeymerge(N, TupleList1, TupleList2) -> TupleList3`  
[page 233] Merge two key-sorted lists of tuples, removing duplicates
- `ukeysort(N, TupleList1) -> TupleList2`  
[page 233] Sort a list of tuples, removing duplicates
- `umerge(ListOfLists) -> List1`  
[page 233] Merge a list of sorted lists, removing duplicates
- `umerge(List1, List2) -> List3`  
[page 234] Merge two sorted lists, removing duplicates
- `umerge(Fun, List1, List2) -> List3`  
[page 234] Merge two sorted lists, removing duplicates
- `umerge3(List1, List2, List3) -> List4`  
[page 234] Merge three sorted lists, removing duplicates
- `unzip(List1) -> {List2, List3}`  
[page 234] Unzip a list of two-tuples into two lists

- `unzip3(List1) -> {List2, List3, List4}`  
[page 234] Unzip a list of three-tuples into three lists
- `usort(List1) -> List2`  
[page 235] Sort a list, removing duplicates
- `usort(Fun, List1) -> List2`  
[page 235] Sort a list, removing duplicates
- `zip(List1, List2) -> List3`  
[page 235] Zip two lists into a list of two-tuples
- `zip3(List1, List2, List3) -> List4`  
[page 235] Zip three lists into a list of three-tuples
- `zipwith(Combine, List1, List2) -> List3`  
[page 236] Zip two lists into one list according to a fun
- `zipwith3(Combine, List1, List2, List3) -> List4`  
[page 236] Zip three lists into one list according to a fun

## log\_mf\_h

The following functions are exported:

- `init(Dir, MaxBytes, MaxFiles)`  
[page 237] Initiate the event handler
- `init(Dir, MaxBytes, MaxFiles, Pred) -> Args`  
[page 237] Initiate the event handler

## math

The following functions are exported:

- `pi() -> float()`  
[page 238] A useful number
- `sin(X)`  
[page 238] Diverse math functions
- `cos(X)`  
[page 238] Diverse math functions
- `tan(X)`  
[page 238] Diverse math functions
- `asin(X)`  
[page 238] Diverse math functions
- `acos(X)`  
[page 238] Diverse math functions
- `atan(X)`  
[page 238] Diverse math functions
- `atan2(Y, X)`  
[page 238] Diverse math functions
- `sinh(X)`  
[page 238] Diverse math functions
- `cosh(X)`  
[page 238] Diverse math functions

- `tanh(X)`  
[page 238] Diverse math functions
- `asinh(X)`  
[page 238] Diverse math functions
- `acosh(X)`  
[page 238] Diverse math functions
- `atanh(X)`  
[page 238] Diverse math functions
- `exp(X)`  
[page 238] Diverse math functions
- `log(X)`  
[page 238] Diverse math functions
- `log10(X)`  
[page 238] Diverse math functions
- `pow(X, Y)`  
[page 238] Diverse math functions
- `sqrt(X)`  
[page 238] Diverse math functions
- `erf(X) -> float()`  
[page 239] Error function.
- `erfc(X) -> float()`  
[page 239] Another error function

## ms\_transform

The following functions are exported:

- `parse_transform(Forms, Options) -> Forms`  
[page 249] Transforms Erlang abstract format containing calls to `ets/dbg:fun2ms` into literal match specifications.
- `transform_from_shell(Dialect, Clauses, BoundEnvironment) -> term()`  
[page 249] Used when transforming fun's created in the shell into `match_specifications`.
- `format_error(Errcode) -> ErrorMessage`  
[page 250] Error formatting function as required by the `parse_transform` interface.

## orddict

The following functions are exported:

- `append(Key, Value, Orddict1) -> Orddict2`  
[page 251] Append a value to keys in a dictionary
- `append_list(Key, ValList, Orddict1) -> Orddict2`  
[page 251] Append new values to keys in a dictionary
- `erase(Key, Orddict1) -> Orddict2`  
[page 251] Erase a key from a dictionary
- `fetch(Key, Orddict) -> Value`  
[page 252] Look-up values in a dictionary

- `fetch_keys(Orddict) -> Keys`  
[page 252] Return all keys in a dictionary
- `filter(Pred, Orddict1) -> Orddict2`  
[page 252] Choose elements which satisfy a predicate
- `find(Key, Orddict) -> {ok, Value} | error`  
[page 252] Search for a key in a dictionary
- `fold(Fun, Acc0, Orddict) -> Acc1`  
[page 252] Fold a function over a dictionary
- `from_list(List) -> Orddict`  
[page 252] Convert a list of pairs to a dictionary
- `is_key(Key, Orddict) -> bool()`  
[page 253] Test if a key is in a dictionary
- `map(Fun, Orddict1) -> Orddict2`  
[page 253] Map a function over a dictionary
- `merge(Fun, Orddict1, Orddict2) -> Orddict3`  
[page 253] Merge two dictionaries
- `new() -> ordered_dictionary()`  
[page 253] Create a dictionary
- `store(Key, Value, Orddict1) -> Orddict2`  
[page 253] Store a value in a dictionary
- `to_list(Orddict) -> List`  
[page 253] Convert a dictionary to a list of pairs
- `update(Key, Fun, Orddict1) -> Orddict2`  
[page 254] Update a value in a dictionary
- `update(Key, Fun, Initial, Orddict1) -> Orddict2`  
[page 254] Update a value in a dictionary
- `update_counter(Key, Increment, Orddict1) -> Orddict2`  
[page 254] Increment a value in a dictionary

## ordsets

The following functions are exported:

- `new() -> Ordset`  
[page 256] Return an empty set
- `is_set(Ordset) -> bool()`  
[page 256] Test for an Ordset
- `size(Ordset) -> int()`  
[page 256] Return the number of elements in a set
- `to_list(Ordset) -> List`  
[page 256] Convert an Ordset into a list
- `from_list(List) -> Ordset`  
[page 257] Convert a list into an Ordset
- `is_element(Element, Ordset) -> bool()`  
[page 257] Test for membership of an Ordset
- `add_element(Element, Ordset1) -> Ordset2`  
[page 257] Add an element to an Ordset

- `del_element(Element, Ordset1) -> Ordset2`  
[page 257] Remove an element from an Ordset
- `union(Ordset1, Ordset2) -> Ordset3`  
[page 257] Return the union of two Ordsets
- `union(OrdsetList) -> Ordset`  
[page 257] Return the union of a list of Ordsets
- `intersection(Ordset1, Ordset2) -> Ordset3`  
[page 257] Return the intersection of two Ordsets
- `intersection(OrdsetList) -> Ordset`  
[page 258] Return the intersection of a list of Ordsets
- `subtract(Ordset1, Ordset2) -> Ordset3`  
[page 258] Return the difference of two Ordsets
- `is_subset(Ordset1, Ordset2) -> bool()`  
[page 258] Test for subset
- `fold(Function, Acc0, Ordset) -> Acc1`  
[page 258] Fold over set elements
- `filter(Pred, Ordset1) -> Set2`  
[page 258] Filter set elements

## pg

The following functions are exported:

- `create(PgName) -> ok | {error, Reason}`  
[page 259] Create an empty group
- `create(PgName, Node) -> ok | {error, Reason}`  
[page 259] Create an empty group on another node
- `join(PgName, Pid) -> Members`  
[page 259] Join a pid to a process group
- `send(PgName, Msg) -> void()`  
[page 260] Send a message to all members of a process group
- `esend(PgName, Msg) -> void()`  
[page 260] Send a message to all members of a process group, except ourselves
- `members(PgName) -> Members`  
[page 260] Return a list of all members of a process group

## pool

The following functions are exported:

- `start(Name) ->`  
[page 261] >Start a new pool
- `start(Name, Args) -> Nodes`  
[page 261] >Start a new pool
- `attach(Node) -> already_attached | attached`  
[page 261] Ensure that a pool master is running
- `stop() -> stopped`  
[page 262] Stop the pool and kill all the slave nodes

- `get_nodes()` -> `Nodes`  
[page 262] Return a list of the current member nodes of the pool
- `pspawn(Mod, Fun, Args)` -> `pid()`  
[page 262] Spawn a process on the pool node with expected lowest future load
- `pspawn_link(Mod, Fun, Args)` -> `pid()`  
[page 262] Spawn and link to a process on the pool node with expected lowest future load
- `get_node()` -> `node()`  
[page 262] Return the node with the expected lowest future load

## proc\_lib

The following functions are exported:

- `spawn(Fun)` -> `pid()`  
[page 263] Spawn a new process.
- `spawn(Node, Fun)` -> `pid()`  
[page 263] Spawn a new process.
- `spawn(Module, Function, Args)` -> `pid()`  
[page 263] Spawn a new process.
- `spawn(Node, Module, Function, Args)` -> `pid()`  
[page 263] Spawn a new process.
- `spawn_link(Fun)` -> `pid()`  
[page 263] Spawn and link to a new process.
- `spawn_link(Node, Fun)` -> `pid()`  
[page 263] Spawn and link to a new process.
- `spawn_link(Module, Function, Args)` -> `pid()`  
[page 263] Spawn and link to a new process.
- `spawn_link(Node, Module, Function, Args)` -> `pid()`  
[page 264] Spawn and link to a new process.
- `spawn_opt(Fun, SpawnOpts)` -> `pid()`  
[page 264] Spawn a new process with given options.
- `spawn_opt(Node, Fun, SpawnOpts)` -> `pid()`  
[page 264] Spawn a new process with given options.
- `spawn_opt(Module, Function, Args, SpawnOpts)` -> `pid()`  
[page 264] Spawn a new process with given options.
- `spawn_opt(Node, Module, Func, Args, SpawnOpts)` -> `pid()`  
[page 264] Spawn a new process with given options.
- `start(Module, Function, Args)` -> `Ret`  
[page 264] Start a new process synchronously.
- `start(Module, Function, Args, Time)` -> `Ret`  
[page 264] Start a new process synchronously.
- `start(Module, Function, Args, Time, SpawnOpts)` -> `Ret`  
[page 264] Start a new process synchronously.
- `start_link(Module, Function, Args)` -> `Ret`  
[page 264] Start a new process synchronously.

- `start_link(Module, Function, Args, Time) -> Ret`  
[page 264] Start a new process synchronously.
- `start_link(Module, Function, Args, Time, SpawnOpts) -> Ret`  
[page 264] Start a new process synchronously.
- `init_ack(Parent, Ret) -> void()`  
[page 265] Used by a process when it has started.
- `init_ack(Ret) -> void()`  
[page 265] Used by a process when it has started.
- `format(CrashReport) -> string()`  
[page 266] Format a crash report.
- `initial_call(Process) -> {Module,Function,Args} | Fun | false`  
[page 266] Extract the initial call of a `proc_lib` spawned process.
- `translate_initial_call(Process) -> {Module,Function,Arity} | Fun`  
[page 266] Extract and translate the initial call of a `proc_lib` spawned process.
- `hibernate(Module, Function, Args)`  
[page 267] Hibernate a process until a message is sent to it

## proplists

The following functions are exported:

- `append_values(Key, List) -> List`  
[page 268]
- `compact(List) -> List`  
[page 268]
- `delete(Key, List) -> List`  
[page 268]
- `expand(Expansions, List) -> List`  
[page 268]
- `get_all_values(Key, List) -> [term()]`  
[page 269]
- `get_bool(Key, List) -> bool()`  
[page 269]
- `get_keys(List) -> [term()]`  
[page 269]
- `get_value(Key, List) -> term()`  
[page 270]
- `get_value(Key, List, Default) -> term()`  
[page 270]
- `is_defined(Key, List) -> bool()`  
[page 270]
- `lookup(Key, List) -> none | tuple()`  
[page 270]
- `lookup_all(Key, List) -> [tuple()]`  
[page 270]
- `normalize(List, Stages) -> List`  
[page 270]

- `property(Property) -> Property`  
[page 271]
- `property(Key, Value) -> Property`  
[page 271]
- `split(List, Keys) -> {Lists, Rest}`  
[page 271]
- `substitute_aliases(Aliases, List) -> List`  
[page 272]
- `substitute_negations(Negations, List) -> List`  
[page 272]
- `unfold(List) -> List`  
[page 272]

## qlc

The following functions are exported:

- `append(QHL) -> QH`  
[page 280] Return a query handle.
- `append(QH1, QH2) -> QH3`  
[page 280] Return a query handle.
- `cursor(QueryHandleOrList [, Options]) -> QueryCursor`  
[page 280] Create a query cursor.
- `delete_cursor(QueryCursor) -> ok`  
[page 281] Delete a query cursor.
- `eval(QueryHandleOrList [, Options]) -> Answers | Error`  
[page 281] Return all answers to a query.
- `e(QueryHandleOrList [, Options]) -> Answers`  
[page 281] Return all answers to a query.
- `fold(Function, Acc0, QueryHandleOrList [, Options]) -> Acc1 | Error`  
[page 281] Fold a function over the answers to a query.
- `format_error(Error) -> Chars`  
[page 281] Return an English description of a an error tuple.
- `info(QueryHandleOrList [, Options]) -> Info`  
[page 282] Return code describing a query handle.
- `keysort(KeyPos, QH1 [, SortOptions]) -> QH2`  
[page 283] Return a query handle.
- `next_answers(QueryCursor [, NumberOfAnswers]) -> Answers | Error`  
[page 283] Return some or all answers to a query.
- `q(QueryListComprehension [, Options]) -> QueryHandle`  
[page 283] Return a handle for a query list comprehension.
- `sort(QH1 [, SortOptions]) -> QH2`  
[page 286] Return a query handle.
- `string_to_handle(QueryString [, Options [, Bindings]]) -> QueryHandle | Error`  
[page 286] Return a handle for a query list comprehension.
- `table(TraverseFun, Options) -> QueryHandle`  
[page 287] Return a query handle for a table.

## queue

The following functions are exported:

- `cons(Item, Q1) -> Q2`  
[page 290] Insert an item at the head of a queue
- `daeh(Q) -> Item`  
[page 290] Return the last item of a queue
- `from_list(L) -> queue()`  
[page 290] Convert a list to a queue
- `head(Q) -> Item`  
[page 290] Return the item at the head of a queue
- `in(Item, Q1) -> Q2`  
[page 290] Insert an item at the tail of a queue
- `in_r(Item, Q1) -> Q2`  
[page 291] Insert an item at the head of a queue
- `init(Q1) -> Q2`  
[page 291] Remove the last item from a queue
- `is_empty(Q) -> true | false`  
[page 291] Test if a queue is empty
- `join(Q1, Q2) -> Q3`  
[page 291] Join two queues
- `lait(Q1) -> Q2`  
[page 291] Remove the last item from a queue
- `last(Q) -> Item`  
[page 291] Return the last item of a queue
- `len(Q) -> N`  
[page 291] Get the length of a queue
- `new() -> Q`  
[page 292] Create a new empty FIFO queue
- `out(Q1) -> Result`  
[page 292] Remove the head item from a queue
- `out_r(Q1) -> Result`  
[page 292] Remove the last item from a queue
- `reverse(Q1) -> Q2`  
[page 292] Reverse a queue
- `snoc(Q1, Item) -> Q2`  
[page 292] Insert an item at the end of a queue
- `split(N, Q1) -> {Q2,Q3}`  
[page 292] Split a queue in two
- `tail(Q1) -> Q2`  
[page 292] Remove the head item from a queue
- `to_list(Q) -> list()`  
[page 293] Convert a queue to a list

## random

The following functions are exported:

- `seed()` -> `ran()`  
[page 294] Seeds random number generation with default values
- `seed(A1, A2, A3)` -> `ran()`  
[page 294] Seeds random number generator
- `seed0()` -> `ran()`  
[page 294] Return default state for random number generation
- `uniform()` -> `float()`  
[page 294] Return a random float
- `uniform(N)` -> `int()`  
[page 294] Return a random integer
- `uniform_s(State0)` -> `{float(), State1}`  
[page 295] Return a random float
- `uniform_s(N, State0)` -> `{int(), State1}`  
[page 295] Return a random integer

## regexp

The following functions are exported:

- `match(String, RegExp)` -> `MatchRes`  
[page 296] Match a regular expression
- `first_match(String, RegExp)` -> `MatchRes`  
[page 296] Match a regular expression
- `matches(String, RegExp)` -> `MatchRes`  
[page 296] Match a regular expression
- `sub(String, RegExp, New)` -> `SubRes`  
[page 297] Substitute the first occurrence of a regular expression
- `gsub(String, RegExp, New)` -> `SubRes`  
[page 297] Substitute all occurrences of a regular expression
- `split(String, RegExp)` -> `SplitRes`  
[page 297] Split a string into fields
- `sh_to_awk(ShRegExp)` -> `AwkRegExp`  
[page 298] Convert an sh regular expression into an AWK one
- `parse(RegExp)` -> `ParseRes`  
[page 298] Parse a regular expression
- `format_error(ErrorDescriptor)` -> `Chars`  
[page 298] Format an error descriptor

## sets

The following functions are exported:

- `new()` -> Set  
[page 301] Return an empty set
- `is_set(Set)` -> bool()  
[page 301] Test for an Set
- `size(Set)` -> int()  
[page 301] Return the number of elements in a set
- `to_list(Set)` -> List  
[page 301] Convert an Set into a list
- `from_list(List)` -> Set  
[page 302] Convert a list into an Set
- `is_element(Element, Set)` -> bool()  
[page 302] Test for membership of an Set
- `add_element(Element, Set1)` -> Set2  
[page 302] Add an element to an Set
- `del_element(Element, Set1)` -> Set2  
[page 302] Remove an element from an Set
- `union(Set1, Set2)` -> Set3  
[page 302] Return the union of two Sets
- `union(SetList)` -> Set  
[page 302] Return the union of a list of Sets
- `intersection(Set1, Set2)` -> Set3  
[page 302] Return the intersection of two Sets
- `intersection(SetList)` -> Set  
[page 303] Return the intersection of a list of Sets
- `subtract(Set1, Set2)` -> Set3  
[page 303] Return the difference of two Sets
- `is_subset(Set1, Set2)` -> bool()  
[page 303] Test for subset
- `fold(Function, Acc0, Set)` -> Acc1  
[page 303] Fold over set elements
- `filter(Pred, Set1)` -> Set2  
[page 303] Filter set elements

## shell

The following functions are exported:

- `history(N)` -> integer()  
[page 312] Sets the number of previous commands to keep
- `results(N)` -> integer()  
[page 312] Sets the number of previous commands to keep
- `start_restricted(Module)` -> ok | {error, Reason}  
[page 313] Exits a normal shell and starts a restricted shell.
- `stop_restricted()` -> ok  
[page 313] Exits a restricted shell and starts a normal shell.

## shell\_default

No functions are exported.

## slave

The following functions are exported:

- `start(Host) ->`  
[page 315] Start a slave node on a host
- `start(Host, Name) ->`  
[page 315] Start a slave node on a host
- `start(Host, Name, Args) -> {ok, Node} | {error, Reason}`  
[page 315] Start a slave node on a host
- `start_link(Host) ->`  
[page 316] Start and link to a slave node on a host
- `start_link(Host, Name) ->`  
[page 316] Start and link to a slave node on a host
- `start_link(Host, Name, Args) -> {ok, Node} | {error, Reason}`  
[page 316] Start and link to a slave node on a host
- `stop(Node) -> ok`  
[page 317] Stop (kill) a node
- `pseudo([Master | ServerList]) -> ok`  
[page 317] Start a number of pseudo servers
- `pseudo(Master, ServerList) -> ok`  
[page 317] Start a number of pseudo servers
- `relay(Pid)`  
[page 317] Run a pseudo server

## sofs

The following functions are exported:

- `a_function(Tuples [, Type]) -> Function`  
[page 322] Create a function.
- `canonical_relation(SetOfSets) -> BinRel`  
[page 322] Return the canonical map.
- `composite(Function1, Function2) -> Function3`  
[page 322] Return the composite of two functions.
- `constant_function(Set, AnySet) -> Function`  
[page 322] Create the function that maps each element of a set onto another set.
- `converse(BinRel1) -> BinRel2`  
[page 323] Return the converse of a binary relation.
- `difference(Set1, Set2) -> Set3`  
[page 323] Return the difference of two sets.
- `digraph_to_family(Graph [, Type]) -> Family`  
[page 323] Create a family from a directed graph.

- `domain(BinRel) -> Set`  
[page 323] Return the domain of a binary relation.
- `drestriction(BinRel1, Set) -> BinRel2`  
[page 323] Return a restriction of a binary relation.
- `drestriction(SetFun, Set1, Set2) -> Set3`  
[page 324] Return a restriction of a relation.
- `empty_set() -> Set`  
[page 324] Return the untyped empty set.
- `extension(BinRel1, Set, AnySet) -> BinRel2`  
[page 324] Extend the domain of a binary relation.
- `family(Tuples [, Type]) -> Family`  
[page 325] Create a family of subsets.
- `family_difference(Family1, Family2) -> Family3`  
[page 325] Return the difference of two families.
- `family_domain(Family1) -> Family2`  
[page 325] Return a family of domains.
- `family_field(Family1) -> Family2`  
[page 325] Return a family of fields.
- `family_intersection(Family1) -> Family2`  
[page 326] Return the intersection of a family of sets of sets.
- `family_intersection(Family1, Family2) -> Family3`  
[page 326] Return the intersection of two families.
- `family_projection(SetFun, Family1) -> Family2`  
[page 326] Return a family of modified subsets.
- `family_range(Family1) -> Family2`  
[page 326] Return a family of ranges.
- `family_specification(Fun, Family1) -> Family2`  
[page 327] Select a subset of a family using a predicate.
- `family_to_digraph(Family [, GraphType]) -> Graph`  
[page 327] Create a directed graph from a family.
- `family_to_relation(Family) -> BinRel`  
[page 327] Create a binary relation from a family.
- `family_union(Family1) -> Family2`  
[page 328] Return the union of a family of sets of sets.
- `family_union(Family1, Family2) -> Family3`  
[page 328] Return the union of two families.
- `field(BinRel) -> Set`  
[page 328] Return the field of a binary relation.
- `from_external(ExternalSet, Type) -> AnySet`  
[page 328] Create a set.
- `from_sets(ListOfSets) -> Set`  
[page 328] Create a set out of a list of sets.
- `from_sets(TupleOfSets) -> Ordset`  
[page 328] Create an ordered set out of a tuple of sets.
- `from_term(Term [, Type]) -> AnySet`  
[page 329] Create a set.

- `image(BinRel, Set1) -> Set2`  
[page 330] Return the image of a set under a binary relation.
- `intersection(SetOfSets) -> Set`  
[page 330] Return the intersection of a set of sets.
- `intersection(Set1, Set2) -> Set3`  
[page 330] Return the intersection of two sets.
- `intersection_of_family(Family) -> Set`  
[page 330] Return the intersection of a family.
- `inverse(Function1) -> Function2`  
[page 330] Return the inverse of a function.
- `inverse_image(BinRel, Set1) -> Set2`  
[page 331] Return the inverse image of a set under a binary relation.
- `is_a_function(BinRel) -> Bool`  
[page 331] Test for a function.
- `is_disjoint(Set1, Set2) -> Bool`  
[page 331] Test for disjoint sets.
- `is_empty_set(AnySet) -> Bool`  
[page 331] Test for an empty set.
- `is_equal(AnySet1, AnySet2) -> Bool`  
[page 331] Test two sets for equality.
- `is_set(AnySet) -> Bool`  
[page 331] Test for an unordered set.
- `is_sofs_set(Term) -> Bool`  
[page 332] Test for an unordered set.
- `is_subset(Set1, Set2) -> Bool`  
[page 332] Test two sets for subset.
- `is_type(Term) -> Bool`  
[page 332] Test for a type.
- `join(Relation1, I, Relation2, J) -> Relation3`  
[page 332] Return the join of two relations.
- `multiple_relative_product(TupleOfBinRels, BinRel1) -> BinRel2`  
[page 332] Return the multiple relative product of a tuple of binary relations and a relation.
- `no_elements(ASet) -> NoElements`  
[page 333] Return the number of elements of a set.
- `partition(SetOfSets) -> Partition`  
[page 333] Return the coarsest partition given a set of sets.
- `partition(SetFun, Set) -> Partition`  
[page 333] Return a partition of a set.
- `partition(SetFun, Set1, Set2) -> {Set3, Set4}`  
[page 333] Return a partition of a set.
- `partition_family(SetFun, Set) -> Family`  
[page 334] Return a family indexing a partition.
- `product(TupleOfSets) -> Relation`  
[page 334] Return the Cartesian product of a tuple of sets.
- `product(Set1, Set2) -> BinRel`  
[page 334] Return the Cartesian product of two sets.

- `projection(SetFun, Set1) -> Set2`  
[page 335] Return a set of substituted elements.
- `range(BinRel) -> Set`  
[page 335] Return the range of a binary relation.
- `relation(Tuples [, Type]) -> Relation`  
[page 335] Create a relation.
- `relation_to_family(BinRel) -> Family`  
[page 335] Create a family from a binary relation.
- `relative_product(TupleOfBinRels [, BinRel1]) -> BinRel2`  
[page 336] Return the relative product of a tuple of binary relations and a binary relation.
- `relative_product(BinRel1, BinRel2) -> BinRel3`  
[page 336] Return the relative product of two binary relations.
- `relative_product1(BinRel1, BinRel2) -> BinRel3`  
[page 336] Return the relative\_product of two binary relations.
- `restriction(BinRel1, Set) -> BinRel2`  
[page 336] Return a restriction of a binary relation.
- `restriction(SetFun, Set1, Set2) -> Set3`  
[page 337] Return a restriction of a set.
- `set(Terms [, Type]) -> Set`  
[page 337] Create a set of atoms or any type of sets.
- `specification(Fun, Set1) -> Set2`  
[page 337] Select a subset using a predicate.
- `strict_relation(BinRel1) -> BinRel2`  
[page 337] Return the strict relation corresponding to a given relation.
- `substitution(SetFun, Set1) -> Set2`  
[page 338] Return a function with a given set as domain.
- `symdiff(Set1, Set2) -> Set3`  
[page 338] Return the symmetric difference of two sets.
- `symmetric_partition(Set1, Set2) -> {Set3, Set4, Set5}`  
[page 339] Return a partition of two sets.
- `to_external(AnySet) -> ExternalSet`  
[page 339] Return the elements of a set.
- `to_sets(ASet) -> Sets`  
[page 339] Return a list or a tuple of the elements of set.
- `type(AnySet) -> Type`  
[page 339] Return the type of a set.
- `union(SetOfSets) -> Set`  
[page 339] Return the union of a set of sets.
- `union(Set1, Set2) -> Set3`  
[page 339] Return the union of two sets.
- `union_of_family(Family) -> Set`  
[page 340] Return the union of a family.
- `weak_relation(BinRel1) -> BinRel2`  
[page 340] Return the weak relation corresponding to a given relation.

## string

The following functions are exported:

- `len(String) -> Length`  
[page 341] Return the length of a string
- `equal(String1, String2) -> bool()`  
[page 341] Test string equality
- `concat(String1, String2) -> String3`  
[page 341] Concatenate two strings
- `chr(String, Character) -> Index`  
[page 341] Return the index of the first/last occurrence of Character in String
- `rchr(String, Character) -> Index`  
[page 341] Return the index of the first/last occurrence of Character in String
- `str(String, SubString) -> Index`  
[page 341] Find the index of a substring
- `rstr(String, SubString) -> Index`  
[page 341] Find the index of a substring
- `span(String, Chars) -> Length`  
[page 342] Span characters at start of string
- `cspan(String, Chars) -> Length`  
[page 342] Span characters at start of string
- `substr(String, Start) -> SubString`  
[page 342] Return a substring of String
- `substr(String, Start, Length) -> Substring`  
[page 342] Return a substring of String
- `tokens(String, SeparatorList) -> Tokens`  
[page 342] Split string into tokens
- `chars(Character, Number) -> String`  
[page 342] Returns a string consisting of numbers of characters
- `chars(Character, Number, Tail) -> String`  
[page 342] Returns a string consisting of numbers of characters
- `copies(String, Number) -> Copies`  
[page 343] Copy a string
- `words(String) -> Count`  
[page 343] Count blank separated words
- `words(String, Character) -> Count`  
[page 343] Count blank separated words
- `sub_word(String, Number) -> Word`  
[page 343] Extract subword
- `sub_word(String, Number, Character) -> Word`  
[page 343] Extract subword
- `strip(String) -> Stripped`  
[page 343] Strip leading or trailing characters
- `strip(String, Direction) -> Stripped`  
[page 343] Strip leading or trailing characters

- `strip(String, Direction, Character) -> Stripped`  
[page 343] Strip leading or trailing characters
- `left(String, Number) -> Left`  
[page 344] Adjust left end of string
- `left(String, Number, Character) -> Left`  
[page 344] Adjust left end of string
- `right(String, Number) -> Right`  
[page 344] Adjust right end of string
- `right(String, Number, Character) -> Right`  
[page 344] Adjust right end of string
- `centre(String, Number) -> Centered`  
[page 344] Center a string
- `centre(String, Number, Character) -> Centered`  
[page 344] Center a string
- `sub_string(String, Start) -> SubString`  
[page 344] Extract a substring
- `sub_string(String, Start, Stop) -> SubString`  
[page 345] Extract a substring
- `to_float(String) -> {Float,Rest} | {error,Reason}`  
[page 345] Returns a float whose text representation is the integers (ASCII values) in String.
- `to_integer(String) -> {Int,Rest} | {error,Reason}`  
[page 345] Returns an integer whose text representation is the integers (ASCII values) in String.
- `to_lower(String) -> Result`  
[page 346] Convert case of string (ISO/IEC 8859-1)
- `to_lower(Char) -> CharResult`  
[page 346] Convert case of string (ISO/IEC 8859-1)
- `to_upper(String) -> Result`  
[page 346] Convert case of string (ISO/IEC 8859-1)
- `to_upper(Char) -> CharResult`  
[page 346] Convert case of string (ISO/IEC 8859-1)

## supervisor

The following functions are exported:

- `start_link(Module, Args) -> Result`  
[page 349] Create a supervisor process.
- `start_link(SupName, Module, Args) -> Result`  
[page 349] Create a supervisor process.
- `start_child(SupRef, ChildSpec) -> Result`  
[page 350] Dynamically add a child process to a supervisor.
- `terminate_child(SupRef, Id) -> Result`  
[page 350] Terminate a child process belonging to a supervisor.
- `delete_child(SupRef, Id) -> Result`  
[page 351] Delete a child specification from a supervisor.

- `restart_child(SupRef, Id) -> Result`  
[page 351] Restart a terminated child process belonging to a supervisor.
- `which_children(SupRef) -> [{Id,Child,Type,Modules}]`  
[page 352] Return information about all children specifications and child processes belonging to a supervisor.
- `check_childspecs([ChildSpec]) -> Result`  
[page 352] Check if child specifications are syntactically correct.
- `Module:init(Args) -> Result`  
[page 353] Return a supervisor specification.

## supervisor\_bridge

The following functions are exported:

- `start_link(Module, Args) -> Result`  
[page 354] Create a supervisor bridge process.
- `start_link(SupBridgeName, Module, Args) -> Result`  
[page 354] Create a supervisor bridge process.
- `Module:init(Args) -> Result`  
[page 355] Initialize process and start subsystem.
- `Module:terminate(Reason, State)`  
[page 355] Clean up and stop subsystem.

## sys

The following functions are exported:

- `log(Name,Flag)`  
[page 358] Log system events in memory
- `log(Name,Flag,Timeout) -> ok | {ok, [system_event()]}`  
[page 358] Log system events in memory
- `log_to_file(Name,Flag)`  
[page 358] Log system events to the specified file
- `log_to_file(Name,Flag,Timeout) -> ok | {error, open_file}`  
[page 358] Log system events to the specified file
- `statistics(Name,Flag)`  
[page 358] Enable or disable the collections of statistics
- `statistics(Name,Flag,Timeout) -> ok | {ok, Statistics}`  
[page 358] Enable or disable the collections of statistics
- `trace(Name,Flag)`  
[page 359] Print all system events on standard\_io
- `trace(Name,Flag,Timeout) -> void()`  
[page 359] Print all system events on standard\_io
- `no_debug(Name)`  
[page 359] Turn off debugging
- `no_debug(Name,Timeout) -> void()`  
[page 359] Turn off debugging

- `suspend(Name)`  
[page 359] Suspend the process
- `suspend(Name,Timeout) -> void()`  
[page 359] Suspend the process
- `resume(Name)`  
[page 359] Resume a suspended process
- `resume(Name,Timeout) -> void()`  
[page 359] Resume a suspended process
- `change_code(Name, Module, OldVsn, Extra)`  
[page 359] Send the code change system message to the process
- `change_code(Name, Module, OldVsn, Extra, Timeout) -> ok | {error, Reason}`  
[page 359] Send the code change system message to the process
- `get_status(Name)`  
[page 359] Get the status of the process
- `get_status(Name,Timeout) -> {status, Pid, {module, Mod}, [PDict, SysState, Parent, Dbg, Misc]}`  
[page 359] Get the status of the process
- `install(Name, {Func,FuncState})`  
[page 360] Install a debug function in the process
- `install(Name, {Func,FuncState},Timeout)`  
[page 360] Install a debug function in the process
- `remove(Name,Func)`  
[page 360] Remove a debug function from the process
- `remove(Name,Func,Timeout) -> void()`  
[page 360] Remove a debug function from the process
- `debug_options(Options) -> [dbg_opt()]`  
[page 361] Convert a list of options to a debug structure
- `get_debug(Item,Debug,Default) -> term()`  
[page 361] Get the data associated with a debug option
- `handle_debug([dbg_opt()],FormFunc,Extra,Event) -> [dbg_opt()]`  
[page 361] Generate a system event
- `handle_system_msg(Msg,From,Parent,Module,Debug,Misc)`  
[page 361] Take care of system messages
- `print_log(Debug) -> void()`  
[page 362] Print the logged events in the debug structure
- `Mod:system_continue(Parent, Debug, Misc)`  
[page 362] Called when the process should continue its execution
- `Mod:system_terminate(Reason, Parent, Debug, Misc)`  
[page 362] Called when the process should terminate
- `Mod:system_code_change(Misc, Module, OldVsn, Extra) -> {ok, NMisc}`  
[page 362] Called when the process should perform a code change

## timer

The following functions are exported:

- `start()` -> `ok`  
[page 364] Start a global timer server (named `timer_server`).
- `apply_after(Time, Module, Function, Arguments)` -> `{ok, TRef} | {error, Reason}`  
[page 364] Apply `Module:Function(Arguments)` after a specified `Time`.
- `send_after(Time, Pid, Message)` -> `{ok, TRef} | {error, Reason}`  
[page 364] Send `Message` to `Pid` after a specified `Time`.
- `send_after(Time, Message)` -> `{ok, TRef} | {error, Reason}`  
[page 364] Send `Message` to `Pid` after a specified `Time`.
- `exit_after(Time, Pid, Reason1)` -> `{ok, TRef} | {error, Reason2}`  
[page 365] Send an exit signal with `Reason` after a specified `Time`.
- `exit_after(Time, Reason1)` -> `{ok, TRef} | {error, Reason2}`  
[page 365] Send an exit signal with `Reason` after a specified `Time`.
- `kill_after(Time, Pid)`-> `{ok, TRef} | {error, Reason2}`  
[page 365] Send an exit signal with `Reason` after a specified `Time`.
- `kill_after(Time)` -> `{ok, TRef} | {error, Reason2}`  
[page 365] Send an exit signal with `Reason` after a specified `Time`.
- `apply_interval(Time, Module, Function, Arguments)` -> `{ok, TRef} | {error, Reason}`  
[page 365] Evaluate `Module:Function(Arguments)` repeatedly at intervals of `Time`.
- `send_interval(Time, Pid, Message)` -> `{ok, TRef} | {error, Reason}`  
[page 365] Send `Message` repeatedly at intervals of `Time`.
- `send_interval(Time, Message)` -> `{ok, TRef} | {error, Reason}`  
[page 365] Send `Message` repeatedly at intervals of `Time`.
- `cancel(TRef)` -> `{ok, cancel} | {error, Reason}`  
[page 365] Cancel a previously requested timeout identified by `TRef`.
- `sleep(Time)` -> `ok`  
[page 365] Suspend the calling process for `Time` amount of milliseconds.
- `tc(Module, Function, Arguments)` -> `{Time, Value}`  
[page 366] Measure the real time it takes to evaluate `apply(Module, Function, Arguments)`
- `now_diff(T2, T1)` -> `Tdiff`  
[page 366] Calculate time difference between `now/0` timestamps
- `seconds(Seconds)` -> `Milliseconds`  
[page 366] Convert `Seconds` to `Milliseconds`.
- `minutes(Minutes)` -> `Milliseconds`  
[page 366] Converts `Minutes` to `Milliseconds`.
- `hours(Hours)` -> `Milliseconds`  
[page 366] Convert `Hours` to `Milliseconds`.
- `hms(Hours, Minutes, Seconds)` -> `Milliseconds`  
[page 366] Convert `Hours+Minutes+Seconds` to `Milliseconds`.

## win32reg

The following functions are exported:

- `change_key(RegHandle, Key) -> ReturnValue`  
[page 369] Move to a key in the registry
- `change_key_create(RegHandle, Key) -> ReturnValue`  
[page 369] Move to a key, create it if it is not there
- `close(RegHandle)-> ReturnValue`  
[page 369] Close the registry.
- `current_key(RegHandle) -> ReturnValue`  
[page 369] Return the path to the current key.
- `delete_key(RegHandle) -> ReturnValue`  
[page 369] Delete the current key
- `delete_value(RegHandle, Name) -> ReturnValue`  
[page 370] Delete the named value on the current key.
- `expand(String) -> ExpandedString`  
[page 370] Expand a string with environment variables
- `format_error(ErrorId) -> ErrorString`  
[page 370] Convert an POSIX errorcode to a string
- `open(OpenModeList)-> ReturnValue`  
[page 370] Open the registry for reading or writing
- `set_value(RegHandle, Name, Value) -> ReturnValue`  
[page 370] Set value at the current registry key with specified name.
- `sub_keys(RegHandle) -> ReturnValue`  
[page 371] Get subkeys to the current key.
- `value(RegHandle, Name) -> ReturnValue`  
[page 371] Get the named value on the current key.
- `values(RegHandle) -> ReturnValue`  
[page 371] Get all values on the current key.

## zip

The following functions are exported:

- `zip(Name, FileList) -> RetValue`  
[page 373] Create a zip archive with options
- `zip(Name, FileList, Options) -> RetValue`  
[page 373] Create a zip archive with options
- `create(Name, FileList) -> RetValue`  
[page 373] Create a zip archive with options
- `create(Name, FileList, Options) -> RetValue`  
[page 373] Create a zip archive with options
- `unzip(Archive) -> RetValue`  
[page 374] Extract files from a zip archive
- `unzip(Archive, Options) -> RetValue`  
[page 374] Extract files from a zip archive
- `extract(Archive) -> RetValue`  
[page 374] Extract files from a zip archive
- `extract(Archive, Options) -> RetValue`  
[page 374] Extract files from a zip archive

- `list_dir(Archive) -> RetValue`  
[page 375] Retrieve the name of all files in a zip archive
- `list_dir(Archive, Options)`  
[page 375] Retrieve the name of all files in a zip archive
- `table(Archive) -> RetValue`  
[page 375] Retrieve the name of all files in a zip archive
- `table(Archive, Options)`  
[page 375] Retrieve the name of all files in a zip archive
- `t(Archive)`  
[page 375] Print the name of each file in a zip archive
- `tt(Archive)`  
[page 375] Print name and information for each file in a zip archive
- `zip_open(Archive) -> {ok, ZipHandle} | {error, Reason}`  
[page 375] Open an archive and return a handle to it
- `zip_open(Archive, Options) -> {ok, ZipHandle} | {error, Reason}`  
[page 376] Open an archive and return a handle to it
- `zip_list_dir(ZipHandle) -> Result | {error, Reason}`  
[page 376] Return a table of files in open zip archive
- `zip_get(ZipHandle) -> {ok, Result} | {error, Reason}`  
[page 376] Extract files from an open archive
- `zip_get(FileName, ZipHandle) -> {ok, Result} | {error, Reason}`  
[page 376] Extract files from an open archive
- `zip_close(ZipHandle) -> ok | {error, einval}`  
[page 376] Close an open archive

# STDLIB

---

## Application

The STDLIB is mandatory in the sense that the minimal system based on Erlang/OTP consists of Kernel and STDLIB. The STDLIB application contains no services.

## Configuration

The following configuration parameters are defined for the STDLIB application. See [app\(4\)](#) for more information about configuration parameters.

`shell_esc = icl | abort` This parameter can be used to alter the behaviour of the Erlang shell when `^G` is pressed.

`restricted_shell = module()` This parameter can be used to run the Erlang shell in restricted mode.

`shell_history_length = integer() >= 0` This parameter can be used to determine how many commands are saved by the Erlang shell.

`shell_saved_results = integer() >= 0` This parameter can be used to determine how many results are saved by the Erlang shell.

## See Also

[[app\(4\)](#)], [[application\(3\)](#)], [[shell\(3\)](#)] [[page 304](#)],

# base64

Erlang Module

Implements base 64 encode and decode, see RFC2045.

## Exports

`encode(Data) -> Base64`

`encode_to_string(Data) -> Base64String`

Types:

- `Data = string() | binary()`
- `Base64 = binary()`
- `Base64String = string()`

Encodes a plain ASCII string into base64. The result will be 33% larger than the data.

`decode(Base64) -> Data`

`decode_to_string(Base64) -> DataString`

`mime_decode(Base64) -> Data`

`mime_decode_string(Base64) -> DataString`

Types:

- `Base64 = string() | binary()`
- `Data = binary()`
- `DataString = string()`

Decodes a base64 encoded string to plain ASCII. The string should only consist of characters in the base64 set, see RFC4648. `mime_decode/1` and `mime_decode_to_string/1` strips away illegal characters, while `decode/1` and `decode_to_string/1` fails if an illegal character is found.

# beam\_lib

Erlang Module

`beam_lib` provides an interface to files created by the BEAM compiler (“BEAM files”). The format used, a variant of “EA IFF 1985” Standard for Interchange Format Files, divides data into chunks.

Chunk data can be returned as binaries or as compound terms. Compound terms are returned when chunks are referenced by names (atoms) rather than identifiers (strings). The names recognized and the corresponding identifiers are:

- `abstract_code` ("Abst")
- `attributes` ("Attr")
- `compile_info` ("CInf")
- `exports` ("ExpT")
- `labeled_exports` ("ExpT")
- `imports` ("ImpT")
- `indexed_imports` ("ImpT")
- `locals` ("LocT")
- `labeled_locals` ("LocT")
- `atoms` ("Atom")

## Debug Information/Abstract Code

The option `debug_info` can be given to the compiler (see [compile(3)]) in order to have debug information in the form of abstract code (see [The Abstract Format] in ERTS User’s Guide) stored in the `abstract_code` chunk. Tools such as Debugger and Xref require the debug information to be included.

### **Warning:**

Source code can be reconstructed from the debug information. Use encrypted debug information (see below) to prevent this.

The debug information can also be removed from BEAM files using `strip/1` [page 60], `strip_files/1` [page 60] and/or `strip_release/1` [page 61].

### *Reconstructing source code*

Here is an example of how to reconstruct source code from the debug information in a BEAM file `Beam`:

```
{ok, {_, [{abstract_code, {_, AC}}]}} = beam_lib:chunks(Beam, [abstract_code]).
io:fwrite("~s~n", [erl_prettypr:format(erl_syntax:form_list(AC))]).
```

### Encrypted debug information

The debug information can be encrypted in order to keep the source code secret, but still being able to use tools such as Xref or Debugger.

To use encrypted debug information, a key must be provided to the compiler and `beam_lib`. The key is given as a string and it is recommended that it contains at least 32 characters and that both upper and lower case letters as well as digits and special characters are used.

The default type – and currently the only type – of crypto algorithm is `des3_cbc`, three rounds of DES. The key string will be scrambled using `erlang:md5/1` to generate the actual keys used for `des3_cbc`.

### Note:

As far as we know when by the time of writing, it is infeasible to break `des3_cbc` encryption without any knowledge of the key. Therefore, as long as the key is kept safe and is unguessable, the encrypted debug information *should* be safe from intruders.

There are two ways to provide the key:

1. Use the compiler option `{debug_info, Key}`, see [\[compile\(3\)\]](#), and the function `crypto_key_fun/1` [\[page 61\]](#) to register a fun which returns the key whenever `beam_lib` needs to decrypt the debug information. If no such fun is registered, `beam_lib` will instead search for a `.erlang.crypt` file, see below.
2. Store the key in a text file named `.erlang.crypt`. In this case, the compiler option `encrypt_debug_info` can be used, see [\[compile\(3\)\]](#).

### `.erlang.crypt`

`beam_lib` searches for `.erlang.crypt` in the current directory and then the home directory for the current user. If the file is found and contains a key, `beam_lib` will implicitly create a crypto key fun and register it.

The `.erlang.crypt` file should contain a single list of tuples:

```
{debug_info, Mode, Module, Key}
```

`Mode` is the type of crypto algorithm; currently, the only allowed value thus is `des3_cbc`. `Module` is either an atom, in which case `Key` will only be used for the module `Module`, or `[]`, in which case `Key` will be used for all modules. `Key` is the non-empty key string.

The `Key` in the first tuple where both `Mode` and `Module` matches will be used.

Here is an example of an `.erlang.crypt` file that returns the same key for all modules:

```
[{debug_info, des3_cbc, [], "%>7}|pc/DM6Cga*68$Mw]L#&_Gejr]G^"}].
```

And here is a slightly more complicated example of an `.erlang.crypt` which provides one key for the module `t`, and another key for all other modules:

```
[{debug_info, des3_cbc, t, "My KEY"},
 {debug_info, des3_cbc, [], "%>7}|pc/DM6Cga*68$Mw]L#&_Gejr]G^"}].
```

**Note:**

Do not use any of the keys in these examples. Use your own keys.

## DATA TYPES

```
beam() -> Module | Filename | binary()
```

```
Module = atom()
```

```
Filename = string() | atom()
```

Each of the functions described below accept either the module name, the filename, or a binary containing the beam module.

```
chunkdata() = {ChunkId, DataB} | {ChunkName, DataT}
```

```
ChunkId = chunkid()
```

```
DataB = binary()
```

```
{ChunkName, DataT} =
```

```
    {abstract_code, AbstractCode}
```

```
    | {attributes, [{Attribute, [AttributeValue]}]}
```

```
    | {compile_info, [{InfoKey, [InfoValue]}]}
```

```
    | {exports, [{Function, Arity}]}
```

```
    | {labeled_exports, [{Function, Arity, Label}]}
```

```
    | {imports, [{Module, Function, Arity}]}
```

```
    | {indexed_imports, [{Index, Module, Function, Arity}]}
```

```
    | {locals, [{Function, Arity}]}
```

```
    | {labeled_locals, [{Function, Arity, Label}]}
```

```
    | {atoms, [{integer(), atom()}]}
```

```
AbstractCode = {AbstVersion, Forms} | no_abstract_code
```

```
AbstVersion = atom()
```

```
Attribute = atom()
```

```
AttributeValue = term()
```

```
Module = Function = atom()
```

```
Arity = int()
```

```
Label = int()
```

It is not checked that the forms conform to the abstract format indicated by `AbstVersion`. `no_abstract_code` means that the "Abst" chunk is present, but empty.

The list of attributes is sorted on `Attribute`, and each attribute name occurs once in the list. The attribute values occur in the same order as in the file. The lists of functions are also sorted.

```
chunkid() = "Abst" | "Attr" | "CInf"
           | "ExpT" | "ImpT" | "LocT"
           | "Atom"
```

```
chunkname() = abstract_code | attributes | compile_info
            | exports | labeled_exports
            | imports | indexed_imports
```

```

| locals | labeled_locals
| atoms

```

```
chunkref() = chunkname() | chunkid()
```

## Exports

```
chunks(Beam, [ChunkRef]) -> {ok, {Module, [ChunkData]}} | {error, beam_lib, Reason}
```

Types:

- Beam = beam()
- ChunkRef = chunkref()
- Module = atom()
- ChunkData = chunkdata()
- Reason = {unknown\_chunk, Filename, atom()}
- | {key\_missing\_or\_invalid, Filename, abstract\_code}
- | Reason1 – see info/1
- Filename = string()

Reads chunk data for selected chunks refs. The order of the returned list of chunk data is determined by the order of the list of chunks references.

```
chunks(Beam, [ChunkRef], [Option]) -> {ok, {Module, [ChunkResult]}} | {error, beam_lib, Reason}
```

Types:

- Beam = beam()
- ChunkRef = chunkref()
- Module = atom()
- Option = allow\_missing\_chunks
- ChunkResult = {chunkref(), ChunkContents} | {chunkref(), missing\_chunk}
- Reason = {missing\_chunk, Filename, atom()}
- | {key\_missing\_or\_invalid, Filename, abstract\_code}
- | Reason1 – see info/1
- Filename = string()

Reads chunk data for selected chunks refs. The order of the returned list of chunk data is determined by the order of the list of chunks references.

By default, if any requested chunk is missing in Beam, an error tuple is returned. However, if the option `allow_missing_chunks` has been given, a result will be returned even if chunks are missing. In the result list, any missing chunks will be represented as `{ChunkRef, missing_chunk}`. Note, however, that if the "Atom" chunk is missing, that is considered a fatal error and the return value will be an error tuple.

```
version(Beam) -> {ok, {Module, [Version]}} | {error, beam_lib, Reason}
```

Types:

- Beam = beam()
- Module = atom()

- Version = term()
- Reason – see chunks/2

Returns the module version(s). A version is defined by the module attribute `-vsn(Vsn)`. If this attribute is not specified, the version defaults to the checksum of the module.

Note that if the version `Vsn` is not a list, it is made into one, that is

`{ok, {Module, [Vsn]}}` is returned. If there are several `-vsn` module attributes, the result is the concatenated list of versions. Examples:

```
1> beam_lib:version(a). % -vsn(1).
{ok, {a, [1]}}
2> beam_lib:version(b). % -vsn([1]).
{ok, {b, [1]}}
3> beam_lib:version(c). % -vsn([1]). -vsn(2).
{ok, {c, [1,2]}}
4> beam_lib:version(d). % no -vsn attribute
{ok, {d, [275613208176997377698094100858909383631]}}
```

`md5(Beam) -> {ok, {Module, MD5}} | {error, beam_lib, Reason}`

Types:

- Beam = beam()
- Module = atom()
- MD5 = binary()
- Reason – see chunks/2

Calculates an MD5 redundancy check for the code of the module (compilation date and other attributes are not included).

`info(Beam) -> [{Item, Info}] | {error, beam_lib, Reason1}`

Types:

- Beam = beam()
- Item, Info – see below
- Reason1 = {chunk\_too\_big, Filename, ChunkId, ChunkSize, FileSize}
- | {invalid\_beam\_file, Filename, Pos}
- | {invalid\_chunk, Filename, ChunkId}
- | {missing\_chunk, Filename, ChunkId}
- | {not\_a\_beam\_file, Filename}
- | {file\_error, Filename, Posix}
- Filename = string()
- ChunkId = chunkid()
- ChunkSize = FileSize = int()
- Pos = int()
- Posix = posix() – see file(3)

Returns a list containing some information about a BEAM file as tuples `{Item, Info}`:

`{file, Filename}` | `{binary, Binary}` The name (string) of the BEAM file, or the binary from which the information was extracted.

`{module, Module}` The name (atom) of the module.

{chunks, [{ChunkId, Pos, Size}]} For each chunk, the identifier (string) and the position and size of the chunk data, in bytes.

cmp(Beam1, Beam2) -> ok | {error, beam\_lib, Reason}

Types:

- Beam1 = Beam2 = beam()
- Reason = {modules\_different, Module1, Module2}
- | {chunks\_different, ChunkId}
- | Reason1 – see info/1
- Module1 = Module2 = atom()
- ChunkId = chunkid()

Compares the contents of two BEAM files. If the module names are the same, and the chunks with the identifiers "Code", "ExpT", "ImpT", "StrT", and "Atom" have the same contents in both files, ok is returned. Otherwise an error message is returned.

cmp\_dirs(Dir1, Dir2) -> {Only1, Only2, Different} | {error, beam\_lib, Reason1}

Types:

- Dir1 = Dir2 = string() | atom()
- Different = [{Filename1, Filename2}]
- Only1 = Only2 = [Filename]
- Filename = Filename1 = Filename2 = string()
- Reason1 = {not\_a\_directory, term()} | – see info/1

The cmp\_dirs/2 function compares the BEAM files in two directories. Only files with extension ".beam" are compared. BEAM files that exist in directory Dir1 (Dir2) only are returned in Only1 (Only2). BEAM files that exist on both directories but are considered different by cmp/2 are returned as pairs {Filename1, Filename2} where Filename1 (Filename2) exists in directory Dir1 (Dir2).

diff\_dirs(Dir1, Dir2) -> ok | {error, beam\_lib, Reason1}

Types:

- Dir1 = Dir2 = string() | atom()
- Reason1 = {not\_a\_directory, term()} | – see info/1

The diff\_dirs/2 function compares the BEAM files in two directories the way cmp\_dirs/2 does, but names of files that exist in only one directory or are different are presented on standard output.

strip(Beam1) -> {ok, {Module, Beam2}} | {error, beam\_lib, Reason1}

Types:

- Beam1 = Beam2 = beam()
- Module = atom()
- Reason1 – see info/1

The strip/1 function removes all chunks from a BEAM file except those needed by the loader. In particular, the debug information (abstract\_code chunk) is removed.

strip\_files(Files) -> {ok, [{Module, Beam2}]} | {error, beam\_lib, Reason1}

Types:

- Files = [Beam1]
- Beam1 = beam()
- Module = atom()
- Beam2 = beam()
- Reason1 – see info/1

The `strip_files/1` function removes all chunks except those needed by the loader from BEAM files. In particular, the debug information (`abstract_code` chunk) is removed. The returned list contains one element for each given file name, in the same order as in Files.

```
strip_release(Dir) -> {ok, [{Module, Filename}]} | {error, beam_lib, Reason1}
```

Types:

- Dir = string() | atom()
- Module = atom()
- Filename = string()
- Reason1 = {not\_a\_directory, term()} | – see info/1

The `strip_release/1` function removes all chunks except those needed by the loader from the BEAM files of a release. `Dir` should be the installation root directory. For example, the current OTP release can be stripped with the call `beam_lib:strip_release(code:root_dir())`.

```
format_error(Reason) -> Chars
```

Types:

- Reason – see other functions
- Chars = [char() | Chars]

Given the error returned by any function in this module, the function `format_error` returns a descriptive string of the error in English. For file errors, the function `file:format_error(Posix)` should be called.

```
crypto_key_fun(CryptoKeyFun) -> ok | {error, Reason}
```

Types:

- CryptoKeyFun = fun() – see below
- Reason = badfun | exists | term()

The `crypto_key_fun/1` function registers a unary fun that will be called if `beam_lib` needs to read an `abstract_code` chunk that has been encrypted. The fun is held in a process that is started by the function.

If there already is a fun registered when attempting to register a fun, `{error, exists}` is returned.

The fun must handle the following arguments:

```
CryptoKeyFun(init) -> ok | {ok, NewCryptoKeyFun} | {error, Term}
```

Called when the fun is registered, in the process that holds the fun. Here the crypto key fun can do any necessary initializations. If `{ok, NewCryptoKeyFun}` is returned then `NewCryptoKeyFun` will be registered instead of `CryptoKeyFun`. If `{error, Term}` is returned, the registration is aborted and `crypto_key_fun/1` returns `{error, Term}` as well.

```
CryptoKeyFun({debug_info, Mode, Module, Filename}) -> Key
```

Called when the key is needed for the module `Module` in the file named `Filename`. `Mode` is the type of crypto algorithm; currently, the only possible value thus is `des3_cbc`. The call should fail (raise an exception) if there is no key available.

```
CryptoKeyFun(clear) -> term()
```

Called before the fun is unregistered. Here any cleaning up can be done. The return value is not important, but is passed back to the caller of `clear_crypto_key_fun/0` as part of its return value.

```
clear_crypto_key_fun() -> {ok, Result}
```

Types:

- `Result = undefined | term()`

Unregisters the crypto key fun and terminates the process holding it, started by `crypto_key_fun/1`.

The `clear_crypto_key_fun/1` either returns `{ok, undefined}` if there was no crypto key fun registered, or `{ok, Term}`, where `Term` is the return value from `CryptoKeyFun(clear)`, see `crypto_key_fun/1`.

# C

## Erlang Module

The `c` module enables users to enter the short form of some commonly used commands.

**Note:**

These functions are intended for interactive use in the Erlang shell only. The module prefix may be omitted.

## Exports

`bt(Pid) -> void()`

Types:

- `Pid = pid()`

Stack backtrace for a process. Equivalent to `erlang:process_display(Pid, backtrace)`.

`c(File) -> {ok, Module} | error`

`c(File, Options) -> {ok, Module} | error`

Types:

- `File = name()` – see `filename(3)`
- `Options = [Opt]` – see `compile:file/2`

`c/1,2` compiles and then purges and loads the code for a file. `Options` defaults to `[]`. Compilation is equivalent to:

```
compile:file(File, Options ++ [report_errors, report_warnings])
```

Note that purging the code means that any processes lingering in old code for the module are killed without warning. See `code/3` for more information.

`cd(Dir) -> void()`

Types:

- `Dir = name()` – see `filename(3)`

Changes working directory to `Dir`, which may be a relative name, and then prints the name of the new working directory.

```
2> cd("../erlang").  
/home/ron/erlang
```

`flush()` -> `void()`

Flushes any messages sent to the shell.

`help()` -> `void()`

Displays help information: all valid shell internal commands, and commands in this module.

`i()` -> `void()`

`ni()` -> `void()`

`i/0` displays information about the system, listing information about all processes. `ni/0` does the same, but for all nodes the network.

`i(X, Y, Z)` -> `void()`

Types:

- `X = Y = Z = int()`

Displays information about a process, Equivalent to `process_info(pid(X, Y, Z))`, but location transparent.

`l(Module)` -> `void()`

Types:

- `Module = atom()`

Purges and loads, or reloads, a module by calling `code:purge(Module)` followed by `code:load_file(Module)`.

Note that purging the code means that any processes lingering in old code for the module are killed without warning. See `code/3` for more information.

`lc(Files)` -> `ok`

Types:

- `Files = [File]`
- `File = name()` – see `filename(3)`

Compiles a list of files by calling `compile:file(File, [report_errors, report_warnings])` for each `File` in `Files`.

`ls()` -> `void()`

Lists files in the current directory.

`ls(Dir)` -> `void()`

Types:

- `Dir = name()` – see `filename(3)`

Lists files in directory `Dir`.

`m()` -> `void()`

Displays information about the loaded modules, including the files from which they have been loaded.

`m(Module)` -> `void()`

Types:

- `Module = atom()`

Displays information about `Module`.

`memory()` -> `[{Type, Size}]`

Types:

- `Type, Size` – see `erlang:memory/0`

Memory allocation information. Equivalent to `erlang:memory/0`.

`memory(Type)` -> `Size`

`memory([Type])` -> `[{Type, Size}]`

Types:

- `Type, Size` – see `erlang:memory/0`

Memory allocation information. Equivalent to `erlang:memory/1`.

`nc(File)` -> `{ok, Module} | error`

`nc(File, Options)` -> `{ok, Module} | error`

Types:

- `File = name()` – see `filename(3)`
- `Options = [Opt]` – see `compile:file/2`

Compiles and then loads the code for a file on all nodes. `Options` defaults to `[]`.

Compilation is equivalent to:

```
compile:file(File, Opts ++ [report_errors, report_warnings])
```

`nl(Module)` -> `void()`

Types:

- `Module = atom()`

Loads `Module` on all nodes.

`pid(X, Y, Z)` -> `pid()`

Types:

- `X = Y = Z = int()`

Converts `X, Y, Z` to the pid `<X.Y.Z>`. This function should only be used when debugging.

`pwd()` -> `void()`

Prints the name of the working directory.

`q()` -> `void()`

This function is shorthand for `init:stop()`, that is, it causes the node to stop in a controlled fashion.

`regs()` -> `void()`

`nregs()` -> `void()`

`regs/0` displays information about all registered processes. `nregs/0` does the same, but for all nodes in the network.

`xm(ModSpec)` -> `void()`

Types:

- `ModSpec` = `Module` | `Filename`
- `Module` = `atom()`
- `Filename` = `string()`

This function finds undefined functions, unused functions, and calls to deprecated functions in a module by calling `xref:m/1`.

`y(File)` -> `YeccRet`

Types:

- `File` = `name()` – see `filename(3)`
- `YeccRet` = – see `yecc:file/2`

Generates an LALR-1 parser. Equivalent to:

`yecc:file(File)`

`y(File, Options)` -> `YeccRet`

Types:

- `File` = `name()` – see `filename(3)`
- `Options, YeccRet` = – see `yecc:file/2`

Generates an LALR-1 parser. Equivalent to:

`yecc:file(File, Options)`

## See Also

[`compile(3)`], [`filename(3)`] [page 158], [`erlang(3)`], [`yecc(3)`], [`xref(3)`]

# calendar

## Erlang Module

This module provides computation of local and universal time, day-of-the-week, and several time conversion functions.

Time is local when it is adjusted in accordance with the current time zone and daylight saving. Time is universal when it reflects the time at longitude zero, without any adjustment for daylight saving. Universal Coordinated Time (UTC) time is also called Greenwich Mean Time (GMT).

The time functions `local_time/0` and `universal_time/0` provided in this module both return date and time. The reason for this is that separate functions for date and time may result in a date/time combination which is displaced by 24 hours. This happens if one of the functions is called before midnight, and the other after midnight. This problem also applies to the Erlang BIFs `date/0` and `time/0`, and their use is strongly discouraged if a reliable date/time stamp is required.

All dates conform to the Gregorian calendar. This calendar was introduced by Pope Gregory XIII in 1582 and was used in all Catholic countries from this year. Protestant parts of Germany and the Netherlands adopted it in 1698, England followed in 1752, and Russia in 1918 (the October revolution of 1917 took place in November according to the Gregorian calendar).

The Gregorian calendar in this module is extended back to year 0. For a given date, the *gregorian days* is the number of days up to and including the date specified. Similarly, the *gregorian seconds* for a given date and time, is the the number of seconds up to and including the specified date and time.

For computing differences between epochs in time, use the functions counting gregorian days or seconds. If epochs are given as local time, they must be converted to universal time, in order to get the correct value of the elapsed time between epochs. Use of the function `time_difference/2` is discouraged.

## DATA TYPES

```
date() = {Year, Month, Day}
  Year = int()
  Month = 1..12
  Day = 1..31
```

Year cannot be abbreviated. Example: 93 denotes year 93, not 1993.

Valid range depends on the underlying OS.

The date tuple must denote a valid date.

```
time() = {Hour, Minute, Second}
  Hour = 0..23
  Minute = Second = 0..59
```

## Exports

`date_to_gregorian_days(Date) -> Days`

`date_to_gregorian_days(Year, Month, Day) -> Days`

Types:

- `Date = date()`
- `Days = int()`

This function computes the number of gregorian days starting with year 0 and ending at the given date.

`datetime_to_gregorian_seconds({Date, Time}) -> Seconds`

Types:

- `Date = date()`
- `Time = time()`
- `Seconds = int()`

This function computes the number of gregorian seconds starting with year 0 and ending at the given date and time.

`day_of_the_week(Date) -> DayNumber`

`day_of_the_week(Year, Month, Day) -> DayNumber`

Types:

- `Date = date()`
- `DayNumber = 1..7`

This function computes the day of the week given `Year`, `Month` and `Day`. The return value denotes the day of the week as 1: Monday, 2: Tuesday, and so on.

`gregorian_days_to_date(Days) -> Date`

Types:

- `Days = int()`
- `Date = date()`

This function computes the date given the number of gregorian days.

`gregorian_seconds_to_datetime(Seconds) -> {Date, Time}`

Types:

- `Seconds = int()`
- `Date = date()`
- `Time = time()`

This function computes the date and time from the given number of gregorian seconds.

`is_leap_year(Year) -> bool()`

This function checks if a year is a leap year.

`last_day_of_the_month(Year, Month) -> int()`

This function computes the number of days in a month.

```
local_time() -> {Date, Time}
```

Types:

- Date = date()
- Time = time()

This function returns the local time reported by the underlying operating system.

```
local_time_to_universal_time({Date1, Time1}) -> {Date2, Time2}
```

This function converts from local time to Universal Coordinated Time (UTC). Date1 must refer to a local date after Jan 1, 1970.

**Warning:**

This function is deprecated. Use `local_time_to_universal_time_dst/1` instead, as it gives a more correct and complete result. Especially for the period that does not exist since it gets skipped during the switch *to* daylight saving time, this function still returns a result.

```
local_time_to_universal_time_dst({Date1, Time1}) -> [{Date, Time}]
```

Types:

- Date1 = Date = date()
- Time1 = Time = time()

This function converts from local time to Universal Coordinated Time (UTC). Date1 must refer to a local date after Jan 1, 1970.

The return value is a list of 0, 1 or 2 possible UTC times:

- [] For a local {Date1, Time1} during the period that is skipped when switching *to* daylight saving time, there is no corresponding UTC since the local time is illegal - it has never happened.
- [DstDateTimeUTC, DateTimeUTC] For a local {Date1, Time1} during the period that is repeated when switching *from* daylight saving time, there are two corresponding UTCs. One for the first instance of the period when daylight saving time is still active, and one for the second instance.
- [DateTimeUTC] For all other local times there is only one corresponding UTC.

```
now_to_local_time(Now) -> {Date, Time}
```

Types:

- Now – see `erlang:now/0`
- Date = date()
- Time = time()

This function returns local date and time converted from the return value from `erlang:now()`.

`now_to_universal_time(Now) -> {Date, Time}`

`now_to_datetime(Now) -> {Date, Time}`

Types:

- Now – see `erlang:now/0`
- Date = `date()`
- Time = `time()`

This function returns Universal Coordinated Time (UTC) converted from the return value from `erlang:now()`.

`seconds_to_daystime(Seconds) -> {Days, Time}`

Types:

- Seconds = Days = `int()`
- Time = `time()`

This function transforms a given number of seconds into days, hours, minutes, and seconds. The Time part is always non-negative, but Days is negative if the argument Seconds is.

`seconds_to_time(Seconds) -> Time`

Types:

- Seconds = `int()` < 86400
- Time = `time()`

This function computes the time from the given number of seconds. Seconds must be less than the number of seconds per day (86400).

`time_difference(T1, T2) -> {Days, Time}`

This function returns the difference between two `{Date, Time}` tuples. T2 should refer to an epoch later than T1.

### **Warning:**

This function is obsolete. Use the conversion functions for gregorian days and seconds instead.

`time_to_seconds(Time) -> Seconds`

Types:

- Time = `time()`
- Seconds = `int()`

This function computes the number of seconds since midnight up to the specified time.

`universal_time() -> {Date, Time}`

Types:

- Date = `date()`
- Time = `time()`

This function returns the Universal Coordinated Time (UTC) reported by the underlying operating system. Local time is returned if universal time is not available.

```
universal_time_to_local_time({Date1, Time1}) -> {Date2, Time2}
```

Types:

- Date1 = Date2 = date()
- Time1 = Time2 = time()

This function converts from Universal Coordinated Time (UTC) to local time. Date1 must refer to a date after Jan 1, 1970.

```
valid_date(Date) -> bool()
```

```
valid_date(Year, Month, Day) -> bool()
```

Types:

- Date = date()

This function checks if a date is a valid.

## Leap Years

The notion that every fourth year is a leap year is not completely true. By the Gregorian rule, a year Y is a leap year if either of the following rules is valid:

- Y is divisible by 4, but not by 100; or
- Y is divisible by 400.

Accordingly, 1996 is a leap year, 1900 is not, but 2000 is.

## Date and Time Source

Local time is obtained from the Erlang BIF `localtime/0`. Universal time is computed from the BIF `universaltime/0`.

The following facts apply:

- there are 86400 seconds in a day
- there are 365 days in an ordinary year
- there are 366 days in a leap year
- there are 1461 days in a 4 year period
- there are 36524 days in a 100 year period
- there are 146097 days in a 400 year period
- there are 719528 days between Jan 1, 0 and Jan 1, 1970.

# dets

Erlang Module

The module `dets` provides a term storage on file. The stored terms, in this module called *objects*, are tuples such that one element is defined to be the key. A Dets *table* is a collection of objects with the key at the same position stored on a file.

Dets is used by the Mnesia application, and is provided as is for users who are interested in an efficient storage of Erlang terms on disk only. Many applications just need to store some terms in a file. Mnesia adds transactions, queries, and distribution. The size of Dets files cannot exceed 2 GB. If larger tables are needed, Mnesia's table fragmentation can be used.

There are three types of Dets tables: *set*, *bag* and *duplicate\_bag*. A table of type *set* has at most one object with a given key. If an object with a key already present in the table is inserted, the existing object is overwritten by the new object. A table of type *bag* has zero or more different objects with a given key. A table of type *duplicate\_bag* has zero or more possibly matching objects with a given key.

Dets tables must be opened before they can be updated or read, and when finished they must be properly closed. If a table has not been properly closed, Dets will automatically repair the table. This can take a substantial time if the table is large. A Dets table is closed when the process which opened the table terminates. If several Erlang processes (users) open the same Dets table, they will share the table. The table is properly closed when all users have either terminated or closed the table. Dets tables are not properly closed if the Erlang runtime system is terminated abnormally.

**Note:**

A `^C` command abnormally terminates an Erlang runtime system in a Unix environment with a break-handler.

Since all operations performed by Dets are disk operations, it is important to realize that a single look-up operation involves a series of disk seek and read operations. For this reason, the Dets functions are much slower than the corresponding Ets functions, although Dets exports a similar interface.

Dets organizes data as a linear hash list and the hash list grows gracefully as more data is inserted into the table. Space management on the file is performed by what is called a buddy system. The current implementation keeps the entire buddy system in RAM, which implies that if the table gets heavily fragmented, quite some memory can be used up. The only way to defragment a table is to close it and then open it again with the `repair` option set to `force`.

It is worth noting that the `ordered_set` type present in Ets is not yet implemented by Dets, neither is the limited support for concurrent updates which makes a sequence of `first` and `next` calls safe to use on fixed Ets tables. Both these features will be implemented by Dets in a future release of Erlang/OTP. Until then, the Mnesia

application (or some user implemented method for locking) has to be used to implement safe concurrency. Currently, no library of Erlang/OTP has support for ordered disk based term storage.

Two versions of the format used for storing objects on file are supported by Dets. The first version, 8, is the format always used for tables created by OTP R7 and earlier. The second version, 9, is the default version of tables created by OTP R8 (and later OTP releases). OTP R8 can create version 8 tables, and convert version 8 tables to version 9, and vice versa, upon request.

All Dets functions return `{error, Reason}` if an error occurs (`first/1` and `next/2` are exceptions, they exit the process with the error tuple). If given badly formed arguments, all functions exit the process with a `badarg` message.

### Types

```
access() = read | read_write
auto_save() = infinity | int()
bindings_cont() = tuple()
bool() = true | false
file() = string()
int() = integer() >= 0
keypos() = integer() >= 1
name() = atom() | ref()
no_slots() = integer() >= 0 | default
object() = tuple()
object_cont() = tuple()
select_cont() = tuple()
type() = bag | duplicate_bag | set
version() = 8 | 9 | default
```

## Exports

`all()` -> [Name]

Types:

- Name = name()

Returns a list of the names of all open tables on this node.

`bchunk(Name, Continuation)` -> {Continuation2, Data} | '\$end\_of\_table' | {error, Reason}

Types:

- Name = name()
- Continuation = start | cont()
- Continuation2 = cont()
- Data = binary() | tuple()

Returns a list of objects stored in a table. The exact representation of the returned objects is not public. The lists of data can be used for initializing a table by giving the value `bchunk` to the `format` option of the `init_table/3` function. The Mnesia application uses this function for copying open tables.

Unless the table is protected using `safe_fixtable/2`, calls to `bchunk/2` may not work as expected if concurrent updates are made to the table.

The first time `bchunk/2` is called, an initial continuation, the atom `start`, must be provided.

The `bchunk/2` function returns a tuple `{Continuation2, Data}`, where `Data` is a list of objects. `Continuation2` is another continuation which is to be passed on to a subsequent call to `bchunk/2`. With a series of calls to `bchunk/2` it is possible to extract all objects of the table.

`bchunk/2` returns `'$end_of_table'` when all objects have been returned, or `{error, Reason}` if an error occurs.

```
close(Name) -> ok | {error, Reason}
```

Types:

- `Name = name()`

Closes a table. Only processes that have opened a table are allowed to close it.

All open tables must be closed before the system is stopped. If an attempt is made to open a table which has not been properly closed, Dets automatically tries to repair the table.

```
delete(Name, Key) -> ok | {error, Reason}
```

Types:

- `Name = name()`

Deletes all objects with the key `Key` from the table `Name`.

```
delete_all_objects(Name) -> ok | {error, Reason}
```

Types:

- `Name = name()`

Deletes all objects from a table in almost constant time. However, if the table is fixed, `delete_all_objects(T)` is equivalent to `match_delete(T, '_')`.

```
delete_object(Name, Object) -> ok | {error, Reason}
```

Types:

- `Name = name()`
- `Object = object()`

Deletes all instances of a given object from a table. If a table is of type `bag` or `duplicate_bag`, the `delete/2` function cannot be used to delete only some of the objects with a given key. This function makes this possible.

```
first(Name) -> Key | '$end_of_table'
```

Types:

- Key = term()
- Name = name()

Returns the first key stored in the table `Name` according to the table's internal order, or `'$end_of_table'` if the table is empty.

Unless the table is protected using `safe_fixtable/2`, subsequent calls to `next/2` may not work as expected if concurrent updates are made to the table.

Should an error occur, the process is exited with an error tuple `{error, Reason}`. The reason for not returning the error tuple is that it cannot be distinguished from a key.

There are two reasons why `first/1` and `next/2` should not be used: they are not very efficient, and they prevent the use of the key `'$end_of_table'` since this atom is used to indicate the end of the table. If possible, the `match`, `match_object`, and `select` functions should be used for traversing tables.

```
foldl(Function, Acc0, Name) -> Acc1 | {error, Reason}
```

Types:

- Function = fun(Object, AccIn) -> AccOut
- Acc0 = Acc1 = AccIn = AccOut = term()
- Name = name()
- Object = object()

Calls `Function` on successive elements of the table `Name` together with an extra argument `AccIn`. The order in which the elements of the table are traversed is unspecified. `Function` must return a new accumulator which is passed to the next call. `Acc0` is returned if the table is empty.

```
foldr(Function, Acc0, Name) -> Acc1 | {error, Reason}
```

Types:

- Function = fun(Object, AccIn) -> AccOut
- Acc0 = Acc1 = AccIn = AccOut = term()
- Name = name()
- Object = object()

Calls `Function` on successive elements of the table `Name` together with an extra argument `AccIn`. The order in which the elements of the table are traversed is unspecified. `Function` must return a new accumulator which is passed to the next call. `Acc0` is returned if the table is empty.

```
from_ets(Name, EtsTab) -> ok | {error, Reason}
```

Types:

- Name = name()
- EtsTab = -see ets(3)-

Deletes all objects of the table `Name` and then inserts all the objects of the Ets table `EtsTab`. The order in which the objects are inserted is not specified. Since `ets:safe_fixtable/2` is called the Ets table must be public or owned by the calling process.

```
info(Name) -> InfoList | undefined
```

Types:

- Name = name()
- InfoList = [{Item, Value}]

Returns information about the table Name as a list of {Item, Value} tuples:

- {file\_size, int()}, the size of the file in bytes.
- {filename, file()}, the name of the file where objects are stored.
- {keypos, keypos()}, the position of the key.
- {size, int()}, the number of objects stored in the table.
- {type, type()}, the type of the table.

info(Name, Item) -> Value | undefined

Types:

- Name = name()

Returns the information associated with Item for the table Name. In addition to the {Item, Value} pairs defined for info/1, the following items are allowed:

- {access, access()}, the access mode.
- {auto\_save, auto\_save()}, the auto save interval.
- {bchunk\_format, binary()}, an opaque binary describing the format of the objects returned by bchunk/2. The binary can be used as argument to is\_compatible\_chunk\_format/2. Only available for version 9 tables.
- {hash, Hash}. Describes which BIF is used to calculate the hash values of the objects stored in the Dets table. Possible values of Hash are hash, which implies that the erlang:hash/2 BIF is used, phash, which implies that the erlang:phash/2 BIF is used, and phash2, which implies that the erlang:phash2/1 BIF is used.
- {memory, int()}, the size of the file in bytes. The same value is associated with the item file\_size.
- {no\_keys, int()}, the number of different keys stored in the table. Only available for version 9 tables.
- {no\_objects, int()}, the number of objects stored in the table.
- {no\_slots, {Min, Used, Max}}, the number of slots of the table. Min is the minimum number of slots, Used is the number of currently used slots, and Max is the maximum number of slots. Only available for version 9 tables.
- {owner, pid()}, the pid of the process that handles requests to the Dets table.
- {ram\_file, bool()}, whether the table is kept in RAM.
- {safe\_fixed, SafeFixed}. If the table is fixed, SafeFixed is a tuple {FixedAtTime, [{Pid, RefCount}]}. FixedAtTime is the time when the table was first fixed, and Pid is the pid of the process that fixes the table RefCount times. There may be any number of processes in the list. If the table is not fixed, SafeFixed is the atom false.
- {version, int()}, the version of the format of the table.

init\_table(Name, InitFun [, Options]) -> ok | {error, Reason}

Types:

- Name = atom()
- InitFun = fun(Arg) -> Res
- Arg = read | close
- Res = end\_of\_input | {[object()], InitFun} | {Data, InitFun} | term()
- Data = binary() | tuple()

Replaces the existing objects of the table Name with objects created by calling the input function InitFun, see below. The reason for using this function rather than calling insert/2 is that of efficiency. It should be noted that the input functions are called by the process that handles requests to the Dets table, not by the calling process.

When called with the argument read the function InitFun is assumed to return end\_of\_input when there is no more input, or {Objects, Fun}, where Objects is a list of objects and Fun is a new input function. Any other value Value is returned as an error {error, {init\_fun, Value}}. Each input function will be called exactly once, and should an error occur, the last function is called with the argument close, the reply of which is ignored.

If the type of the table is set and there is more than one object with a given key, one of the objects is chosen. This is not necessarily the last object with the given key in the sequence of objects returned by the input functions. Extra objects should be avoided, or the file will be unnecessarily fragmented. This holds also for duplicated objects stored in tables of type duplicate\_bag.

It is important that the table has a sufficient number of slots for the objects. If not, the hash list will start to grow when init\_table/2 returns which will significantly slow down access to the table for a period of time. The minimum number of slots is set by the open\_file/2 option min\_no\_slots and returned by the info/2 item no\_slots. See also the min\_no\_slots option below.

The Options argument is a list of {Key, Val} tuples where the following values are allowed:

- {min\_no\_slots, no\_slots()}. Specifies the estimated number of different keys that will be stored in the table. The open\_file option with the same name is ignored unless the table is created, and in that case performance can be enhanced by supplying an estimate when initializing the table.
- {format, Format}. Specifies the format of the objects returned by the function InitFun. If Format is term (the default), InitFun is assumed to return a list of tuples. If Format is bchunk, InitFun is assumed to return Data as returned by bchunk/2. This option overrides the min\_no\_slots option.

```
insert(Name, Objects) -> ok | {error, Reason}
```

Types:

- Name = name()
- Objects = object() | [object()]

Inserts one or more objects into the table Name. If there already exists an object with a key matching the key of some of the given objects and the table type is set, the old object will be replaced.

```
insert_new(Name, Objects) -> Bool
```

Types:

- Name = name()
- Objects = object() | [object()]
- Bool = bool()

Inserts one or more objects into the table Name. If there already exists some object with a key matching the key of any of the given objects the table is not updated and `false` is returned, otherwise the objects are inserted and `true` returned.

`is_compatible_bchunk_format(Name, BchunkFormat) -> Bool`

Types:

- Name = name()
- BchunkFormat = binary()
- Bool = bool()

Returns `true` if it would be possible to initialize the table Name, using `init_table/3` with the option `{format,bchunk}`, with objects read with `bchunk/2` from some table T such that calling `info(T,bchunk_format)` returns BchunkFormat.

`is_dets_file(FileName) -> Bool | {error, Reason}`

Types:

- FileName = file()
- Bool = bool()

Returns `true` if the file FileName is a Dets table, `false` otherwise.

`lookup(Name, Key) -> [Object] | {error, Reason}`

Types:

- Key = term()
- Name = name()
- Object = object()

Returns a list of all objects with the key Key stored in the table Name. For example:

```
2> dets:open_file(abc, [{type, bag}]).
{ok,abc}
3> dets:insert(abc, {1,2,3}).
ok
4> dets:insert(abc, {1,3,4}).
ok
5> dets:lookup(abc, 1).
[[{1,2,3},{1,3,4}]
```

If the table is of type `set`, the function returns either the empty list or a list with one object, as there cannot be more than one object with a given key. If the table is of type `bag` or `duplicate_bag`, the function returns a list of arbitrary length.

Note that the order of objects returned is unspecified. In particular, the order in which objects were inserted is not reflected.

`match(Continuation) -> [{Match}, Continuation2] | '$end_of_table' | {error, Reason}`

Types:

- Continuation = Continuation2 = bindings\_cont()
- Match = [term()]

Matches some objects stored in a table and returns a non-empty list of the bindings that match a given pattern in some unspecified order. The table, the pattern, and the number of objects that are matched are all defined by Continuation, which has been returned by a prior call to match/1 or match/3.

When all objects of the table have been matched, '\$end\_of\_table' is returned.

```
match(Name, Pattern) -> [Match] | {error, Reason}
```

Types:

- Name = name()
- Pattern = tuple()
- Match = [term()]

Returns for each object of the table Name that matches Pattern a list of bindings in some unspecified order. See ets(3) [page 129] for a description of patterns. If the keypos'th element of Pattern is unbound, all objects of the table are matched. If the keypos'th element is bound, only the objects with the right key are matched.

```
match(Name, Pattern, N) -> {[Match], Continuation} | '$end_of_table' | {error, Reason}
```

Types:

- Name = name()
- Pattern = tuple()
- N = default | int()
- Match = [term()]
- Continuation = bindings\_cont()

Matches some or all objects of the table Name and returns a non-empty list of the bindings that match Pattern in some unspecified order. See ets(3) [page 129] for a description of patterns.

A tuple of the bindings and a continuation is returned, unless the table is empty, in which case '\$end\_of\_table' is returned. The continuation is to be used when matching further objects by calling match/1.

If the keypos'th element of Pattern is bound, all objects of the table are matched. If the keypos'th element is unbound, all objects of the table are matched, N objects at a time, until at least one object matches or the end of the table has been reached. The default, indicated by giving N the value default, is to let the number of objects vary depending on the sizes of the objects. If Name is a version 9 table, all objects with the same key are always matched at the same time which implies that more than N objects may sometimes be matched.

The table should always be protected using safe\_fixtable/2 before calling match/3, or errors may occur when calling match/1.

```
match_delete(Name, Pattern) -> N | {error, Reason}
```

Types:

- Name = name()
- N = int()

- `Pattern = tuple()`

Deletes all objects that match `Pattern` from the table `Name`, and returns the number of deleted objects. See `ets(3)` [page 129] for a description of patterns.

If the keypos'th element of `Pattern` is bound, only the objects with the right key are matched.

```
match_object(Continuation) -> {[Object], Continuation2} | '$end_of_table' | {error, Reason}
```

Types:

- `Continuation = Continuation2 = object_cont()`
- `Object = object()`

Returns a non-empty list of some objects stored in a table that match a given pattern in some unspecified order. The table, the pattern, and the number of objects that are matched are all defined by `Continuation`, which has been returned by a prior call to `match_object/1` or `match_object/3`.

When all objects of the table have been matched, `'$end_of_table'` is returned.

```
match_object(Name, Pattern) -> [Object] | {error, Reason}
```

Types:

- `Name = name()`
- `Pattern = tuple()`
- `Object = object()`

Returns a list of all objects of the table `Name` that match `Pattern` in some unspecified order. See `ets(3)` [page 129] for a description of patterns.

If the keypos'th element of `Pattern` is unbound, all objects of the table are matched. If the keypos'th element of `Pattern` is bound, only the objects with the right key are matched.

Using the `match_object` functions for traversing all objects of a table is more efficient than calling `first/1` and `next/2` or `slot/2`.

```
match_object(Name, Pattern, N) -> {[Object], Continuation} | '$end_of_table' | {error, Reason}
```

Types:

- `Name = name()`
- `Pattern = tuple()`
- `N = default | int()`
- `Object = object()`
- `Continuation = object_cont()`

Matches some or all objects stored in the table `Name` and returns a non-empty list of the objects that match `Pattern` in some unspecified order. See `ets(3)` [page 129] for a description of patterns.

A list of objects and a continuation is returned, unless the table is empty, in which case `'$end_of_table'` is returned. The continuation is to be used when matching further objects by calling `match_object/1`.

If the `keypos`'th element of `Pattern` is bound, all objects of the table are matched. If the `keypos`'th element is unbound, all objects of the table are matched, `N` objects at a time, until at least one object matches or the end of the table has been reached. The default, indicated by giving `N` the value `default`, is to let the number of objects vary depending on the sizes of the objects. If `Name` is a version 9 table, all matching objects with the same key are always returned in the same reply which implies that more than `N` objects may sometimes be returned.

The table should always be protected using `safe_fixtable/2` before calling `match_object/3`, or errors may occur when calling `match_object/1`.

```
member(Name, Key) -> Bool | {error, Reason}
```

Types:

- `Name = name()`
- `Key = term()`
- `Bool = bool()`

Works like `lookup/2`, but does not return the objects. The function returns `true` if one or more elements of the table has the key `Key`, `false` otherwise.

```
next(Name, Key1) -> Key2 | '$end_of_table'
```

Types:

- `Name = name()`
- `Key1 = Key2 = term()`

Returns the key following `Key1` in the table `Name` according to the table's internal order, or `'$end_of_table'` if there is no next key.

Should an error occur, the process is exited with an error tuple `{error, Reason}`.

Use `first/1` to find the first key in the table.

```
open_file(Filename) -> {ok, Reference} | {error, Reason}
```

Types:

- `FileName = file()`
- `Reference = ref()`

Opens an existing table. If the table has not been properly closed, the error `{error, need_repair}` is returned. The returned reference is to be used as the name of the table. This function is most useful for debugging purposes.

```
open_file(Name, Args) -> {ok, Name} | {error, Reason}
```

Types:

- `Name = atom()`

Opens a table. An empty Dets table is created if no file exists.

The atom `Name` is the name of the table. The table name must be provided in all subsequent operations on the table. The name can be used by other processes as well, and several process can share one table.

If two processes open the same table by giving the same name and arguments, then the table will have two users. If one user closes the table, it still remains open until the second user closes the table.

The `Args` argument is a list of `{Key, Val}` tuples where the following values are allowed:

- `{access, access()}`. It is possible to open existing tables in read-only mode. A table which is opened in read-only mode is not subjected to the automatic file reparation algorithm if it is later opened after a crash. The default value is `read_write`.
- `{auto_save, auto_save()}`, the auto save interval. If the interval is an integer `Time`, the table is flushed to disk whenever it is not accessed for `Time` milliseconds. A table that has been flushed will require no reparation when reopened after an uncontrolled emulator halt. If the interval is the atom `infinity`, auto save is disabled. The default value is 180000 (3 minutes).
- `{estimated_no_objects, int()}`. Equivalent to the `min_no_slots` option.
- `{file, file()}`, the name of the file to be opened. The default value is the name of the table.
- `{max_no_slots, no_slots()}`, the maximum number of slots that will be used. The default value is 2 M, and the maximal value is 32 M. Note that a higher value may increase the fragmentation of the table, and conversely, that a smaller value may decrease the fragmentation, at the expense of execution time. Only available for version 9 tables.
- `{min_no_slots, no_slots()}`. Application performance can be enhanced with this flag by specifying, when the table is created, the estimated number of different keys that will be stored in the table. The default value as well as the minimum value is 256.
- `{keypos, keypos()}`, the position of the element of each object to be used as key. The default value is 1. The ability to explicitly state the key position is most convenient when we want to store Erlang records in which the first position of the record is the name of the record type.
- `{ram_file, bool()}`, whether the table is to be kept in RAM. Keeping the table in RAM may sound like an anomaly, but can enhance the performance of applications which open a table, insert a set of objects, and then close the table. When the table is closed, its contents are written to the disk file. The default value is `false`.
- `{repair, Value}`. `Value` can be either a `bool()` or the atom `force`. The flag specifies whether the Dets server should invoke the automatic file reparation algorithm. The default is `true`. If `false` is specified, there is no attempt to repair the file and `{error, need_repair}` is returned if the table needs to be repaired. The value `force` means that a reparation will take place even if the table has been properly closed. This is how to convert tables created by older versions of STDLIB. An example is tables hashed with the deprecated `erlang:hash/2` BIF. Tables created with Dets from a STDLIB version of 1.8.2 and later use the `erlang:phash/2` function or the `erlang:phash2/1` function, which is preferred. The `repair` option is ignored if the table is already open.

- `{type, type()}`, the type of the table. The default value is `set`.
- `{version, version()}`, the version of the format used for the table. The default value is 9. Tables on the format used before OTP R8 can be created by giving the value 8. A version 8 table can be converted to a version 9 table by giving the options `{version,9}` and `{repair,force}`.

`pid2name(Pid) -> {ok, Name} | undefined`

Types:

- `Name = name()`
- `Pid = pid()`

Returns the name of the table given the pid of a process that handles requests to a table, or `undefined` if there is no such table.

This function is meant to be used for debugging only.

`repair_continuation(Continuation, MatchSpec) -> Continuation2`

Types:

- `Continuation = Continuation2 = select_cont()`
- `MatchSpec = match_spec()`

This function can be used to restore an opaque continuation returned by `select/3` or `select/1` if the continuation has passed through external term format (been sent between nodes or stored on disk).

The reason for this function is that continuation terms contain compiled match specifications and therefore will be invalidated if converted to external term format. Given that the original match specification is kept intact, the continuation can be restored, meaning it can once again be used in subsequent `select/1` calls even though it has been stored on disk or on another node.

See also `ets(3)` for further explanations and examples.

### Note:

This function is very rarely needed in application code. It is used by Mnesia to implement distributed `select/3` and `select/1` sequences. A normal application would either use Mnesia or keep the continuation from being converted to external format.

The reason for not having an external representation of compiled match specifications is performance. It may be subject to change in future releases, while this interface will remain for backward compatibility.

`safe_fixtable(Name, Fix)`

Types:

- `Name = name()`
- `Fix = bool()`

If `Fix` is true, the table `Name` is fixed (once more) by the calling process, otherwise the table is released. The table is also released when a fixing process terminates.

If several processes fix a table, the table will remain fixed until all processes have released it or terminated. A reference counter is kept on a per process basis, and `N` consecutive fixes require `N` releases to release the table.

It is not guaranteed that calls to `first/1`, `next/2`, `select` and `match` functions work as expected even if the table has been fixed; the limited support for concurrency implemented in Ets has not yet been implemented in Dets. Fixing a table currently only disables resizing of the hash list of the table.

If objects have been added while the table was fixed, the hash list will start to grow when the table is released which will significantly slow down access to the table for a period of time.

```
select(Continuation) -> {Selection, Continuation2} | '$end_of_table' | {error, Reason}
```

Types:

- Continuation = Continuation2 = `select_cont()`
- Selection = `[term()]`

Applies a match specification to some objects stored in a table and returns a non-empty list of the results. The table, the match specification, and the number of objects that are matched are all defined by `Continuation`, which has been returned by a prior call to `select/1` or `select/3`.

When all objects of the table have been matched, `'$end_of_table'` is returned.

```
select(Name, MatchSpec) -> Selection | {error, Reason}
```

Types:

- Name = `name()`
- MatchSpec = `match_spec()`
- Selection = `[term()]`

Returns the results of applying the match specification `MatchSpec` to all or some objects stored in the table `Name`. The order of the objects is not specified. See the ERTS User's Guide for a description of match specifications.

If the `keypos`'th element of `MatchSpec` is unbound, the match specification is applied to all objects of the table. If the `keypos`'th element is bound, the match specification is applied to the objects with the right key(s) only.

Using the `select` functions for traversing all objects of a table is more efficient than calling `first/1` and `next/2` or `slot/2`.

```
select(Name, MatchSpec, N) -> {Selection, Continuation} | '$end_of_table' | {error, Reason}
```

Types:

- Name = `name()`
- MatchSpec = `match_spec()`
- N = `default` | `int()`
- Selection = `[term()]`
- Continuation = `select_cont()`

Returns the results of applying the match specification `MatchSpec` to some or all objects stored in the table `Name`. The order of the objects is not specified. See the ERTS User's Guide for a description of match specifications.

A tuple of the results of applying the match specification and a continuation is returned, unless the table is empty, in which case `'$end_of_table'` is returned. The continuation is to be used when matching further objects by calling `select/1`.

If the `keypos`'th element of `MatchSpec` is bound, the match specification is applied to all objects of the table with the right key(s). If the `keypos`'th element of `MatchSpec` is unbound, the match specification is applied to all objects of the table, `N` objects at a time, until at least one object matches or the end of the table has been reached. The default, indicated by giving `N` the value `default`, is to let the number of objects vary depending on the sizes of the objects. If `Name` is a version 9 table, all objects with the same key are always handled at the same time which implies that the match specification may be applied to more than `N` objects.

The table should always be protected using `safe_fixtable/2` before calling `select/3`, or errors may occur when calling `select/1`.

```
select_delete(Name, MatchSpec) -> N | {error, Reason}
```

Types:

- Name = name()
- MatchSpec = match\_spec()
- N = int()

Deletes each object from the table `Name` such that applying the match specification `MatchSpec` to the object returns the value `true`. See the ERTS User's Guide for a description of match specifications. Returns the number of deleted objects.

If the `keypos`'th element of `MatchSpec` is bound, the match specification is applied to the objects with the right key(s) only.

```
slot(Name, I) -> '$end_of_table' | [Object] | {error, Reason}
```

Types:

- Name = name()
- I = int()
- Object = object()

The objects of a table are distributed among slots, starting with slot 0 and ending with slot `n`. This function returns the list of objects associated with slot `I`. If `I` is greater than `n` `'$end_of_table'` is returned.

```
sync(Name) -> ok | {error, Reason}
```

Types:

- Name = name()

Ensures that all updates made to the table `Name` are written to disk. This also applies to tables which have been opened with the `ram_file` flag set to `true`. In this case, the contents of the RAM file are flushed to disk.

Note that the space management data structures kept in RAM, the buddy system, is also written to the disk. This may take some time if the table is fragmented.

```
table(Name [, Options]) -> QueryHandle
```

Types:

- Name = name()
- QueryHandle = -a query handle, see `qlc(3)`-
- Options = [Option] | Option
- Option = {n\_objects, Limit} | {traverse, TraverseMethod}
- Limit = default | integer() >= 1
- TraverseMethod = first\_next | select | {select, MatchSpec}
- MatchSpec = match\_spec()

Returns a QLC (Query List Comprehension) query handle. The module `qlc` implements a query language aimed mainly at Mnesia but Ets tables, Dets tables, and lists are also recognized by QLC as sources of data. Calling `dets:table/1,2` is the means to make the Dets table `Name` usable to QLC.

When there are only simple restrictions on the key position QLC uses `dets:lookup/2` to look up the keys, but when that is not possible the whole table is traversed. The option `traverse` determines how this is done:

- `first_next`. The table is traversed one key at a time by calling `dets:first/1` and `dets:next/2`.
- `select`. The table is traversed by calling `dets:select/3` and `dets:select/1`. The option `n_objects` determines the number of objects returned (the third argument of `select/3`). The match specification (the second argument of `select/3`) is assembled by QLC: simple filters are translated into equivalent match specifications while more complicated filters have to be applied to all objects returned by `select/3` given a match specification that matches all objects.
- `{select, MatchSpec}`. As for `select` the table is traversed by calling `dets:select/3` and `dets:select/1`. The difference is that the match specification is explicitly given. This is how to state match specifications that cannot easily be expressed within the syntax provided by QLC.

The following example uses an explicit match specification to traverse the table:

```
1> dets:open_file(t, []),  
dets:insert(t, [{1,a},{2,b},{3,c},{4,d}]),  
MS = ets:fun2ms(fun({X,Y}) when (X > 1) or (X < 5) -> {Y} end),  
QH1 = dets:table(t, [{traverse, {select, MS}}]).
```

An example with implicit match specification:

```
2> QH2 = qlc:q([Y] || {X,Y} <- dets:table(t), (X > 1) or (X < 5)).
```

The latter example is in fact equivalent to the former which can be verified using the function `qlc:info/1`:

```
3> qlc:info(QH1) == qlc:info(QH2).  
true
```

`qlc:info/1` returns information about a query handle, and in this case identical information is returned for the two query handles.

```
to_ets(Name, EtsTab) -> EtsTab | {error, Reason}
```

Types:

- Name = name()
- EtsTab = -see ets(3)-

Inserts the objects of the Dets table Name into the Ets table EtsTab. The order in which the objects are inserted is not specified. The existing objects of the Ets table are kept unless overwritten.

`traverse(Name, Fun) -> Return | {error, Reason}`

Types:

- Fun = fun(Object) -> FunReturn
- FunReturn = continue | {continue, Val} | {done, Value}
- Val = Value = term()
- Name = name()
- Object = object()
- Return = [term()]

Applies Fun to each object stored in the table Name in some unspecified order. Different actions are taken depending on the return value of Fun. The following Fun return values are allowed:

`continue` Continue to perform the traversal. For example, the following function can be used to print out the contents of a table:

```
fun(X) -> io:format("~p~n", [X]), continue end.
```

`{continue, Val}` Continue the traversal and accumulate Val. The following function is supplied in order to collect all objects of a table in a list:

```
fun(X) -> {continue, X} end.
```

`{done, Value}` Terminate the traversal and return [Value | Acc].

Any other value returned by Fun terminates the traversal and is immediately returned.

`update_counter(Name, Key, Increment) -> Result`

Types:

- Name = name()
- Key = term()
- Increment = {Pos, Incr} | Incr
- Pos = Incr = Result = integer()

Updates the object with key Key stored in the table Name of type set by adding Incr to the element at the Pos:th position. The new counter value is returned. If no position is specified, the element directly following the key is updated.

This functions provides a way of updating a counter, without having to look up an object, update the object by incrementing an element and insert the resulting object into the table again.

## See Also

ets(3) [page 129], mnesia(3), qlc(3) [page 273]

# dict

Erlang Module

`Dict` implements a `Key - Value` dictionary. The representation of a dictionary is not defined.

This module provides exactly the same interface as the module `orddict`. One difference is that while this module considers two keys as different if they do not match (`:=`), `orddict` considers two keys as different if and only if they do not compare equal (`==`).

## DATA TYPES

`dictionary()`  
as returned by `new/0`

## Exports

`append(Key, Value, Dict1) -> Dict2`

Types:

- `Key = Value = term()`
- `Dict1 = Dict2 = dictionary()`

This function appends a new `Value` to the current list of values associated with `Key`. An exception is generated if the initial value associated with `Key` is not a list of values.

`append_list(Key, ValList, Dict1) -> Dict2`

Types:

- `ValList = [Value]`
- `Key = Value = term()`
- `Dict1 = Dict2 = dictionary()`

This function appends a list of values `ValList` to the current list of values associated with `Key`. An exception is generated if the initial value associated with `Key` is not a list of values.

`erase(Key, Dict1) -> Dict2`

Types:

- `Key = term()`
- `Dict1 = Dict2 = dictionary()`

This function erases all items with a given key from a dictionary.

`fetch(Key, Dict) -> Value`

Types:

- Key = Value = term()
- Dict = dictionary()

This function returns the value associated with `Key` in the dictionary `Dict`. `fetch` assumes that the `Key` is present in the dictionary and an exception is generated if `Key` is not in the dictionary.

`fetch_keys(Dict) -> Keys`

Types:

- Dict = dictionary()
- Keys = [term()]

This function returns a list of all keys in the dictionary.

`filter(Pred, Dict1) -> Dict2`

Types:

- Pred = fun(Key, Value) -> bool()
- Key = Value = term()
- Dict1 = Dict2 = dictionary()

`Dict2` is a dictionary of all keys and values in `Dict1` for which `Pred(Key, Value)` is true.

`find(Key, Dict) -> {ok, Value} | error`

Types:

- Key = Value = term()
- Dict = dictionary()

This function searches for a key in a dictionary. Returns `{ok, Value}` where `Value` is the value associated with `Key`, or `error` if the key is not present in the dictionary.

`fold(Fun, Acc0, Dict) -> Acc1`

Types:

- Fun = fun(Key, Value, AccIn) -> AccOut
- Key = Value = term()
- Acc0 = Acc1 = AccIn = AccOut = term()
- Dict = dictionary()

Calls `Fun` on successive keys and values of `Dict` together with an extra argument `Acc` (short for accumulator). `Fun` must return a new accumulator which is passed to the next call. `Acc0` is returned if the list is empty. The evaluation order is undefined.

`from_list(List) -> Dict`

Types:

- List = [{Key, Value}]

- Dict = dictionary()

This function converts the key/value list `List` to a dictionary.

`is_key(Key, Dict) -> bool()`

Types:

- Key = term()
- Dict = dictionary()

This function tests if `Key` is contained in the dictionary `Dict`.

`map(Fun, Dict1) -> Dict2`

Types:

- Fun = fun(Key, Value1) -> Value2
- Key = Value1 = Value2 = term()
- Dict1 = Dict2 = dictionary()

`map` calls `Func` on successive keys and values of `Dict` to return a new value for each key. The evaluation order is undefined.

`merge(Fun, Dict1, Dict2) -> Dict3`

Types:

- Fun = fun(Key, Value1, Value2) -> Value
- Key = Value1 = Value2 = Value3 = term()
- Dict1 = Dict2 = Dict3 = dictionary()

`merge` merges two dictionaries, `Dict1` and `Dict2`, to create a new dictionary. All the `Key - Value` pairs from both dictionaries are included in the new dictionary. If a key occurs in both dictionaries then `Fun` is called with the key and both values to return a new value. `merge` could be defined as:

```
merge(Fun, D1, D2) ->
  fold(fun (K, V1, D) ->
        update(K, fun (V2) -> Fun(K, V1, V2) end, V1, D)
        end, D2, D1).
```

but is faster.

`new() -> dictionary()`

This function creates a new dictionary.

`store(Key, Value, Dict1) -> Dict2`

Types:

- Key = Value = term()
- Dict1 = Dict2 = dictionary()

This function stores a `Key - Value` pair in a dictionary. If the `Key` already exists in `Dict1`, the associated value is replaced by `Value`.

`to_list(Dict) -> List`

Types:

- Dict = dictionary()
- List = [{Key, Value}]

This function converts the dictionary to a list representation.

`update(Key, Fun, Dict1) -> Dict2`

Types:

- Key = term()
- Fun = fun(Value1) -> Value2
- Value1 = Value2 = term()
- Dict1 = Dict2 = dictionary()

Update the a value in a dictionary by calling Fun on the value to get a new value. An exception is generated if Key is not present in the dictionary.

`update(Key, Fun, Initial, Dict1) -> Dict2`

Types:

- Key = Initial = term()
- Fun = fun(Value1) -> Value2
- Value1 = Value2 = term()
- Dict1 = Dict2 = dictionary()

Update the a value in a dictionary by calling Fun on the value to get a new value. If Key is not present in the dictionary then Initial will be stored as the first value. For example `append/3` could be defined as:

```
append(Key, Val, D) ->
    update(Key, fun (Old) -> Old ++ [Val] end, [Val], D).
```

`update_counter(Key, Increment, Dict1) -> Dict2`

Types:

- Key = term()
- Increment = number()
- Dict1 = Dict2 = dictionary()

Add Increment to the value associated with Key and store this value. If Key is not present in the dictionary then Increment will be stored as the first value.

This could be defined as:

```
update_counter(Key, Incr, D) ->
    update(Key, fun (Old) -> Old + Incr end, Incr, D).
```

but is faster.

## Notes

The functions `append` and `append_list` are included so we can store keyed values in a list *accumulator*. For example:

```
> D0 = dict:new(),
  D1 = dict:store(files, [], D0),
  D2 = dict:append(files, f1, D1),
  D3 = dict:append(files, f2, D2),
  D4 = dict:append(files, f3, D3),
  dict:fetch(files, D4).
[f1,f2,f3]
```

This saves the trouble of first fetching a keyed value, appending a new value to the list of stored values, and storing the result.

The function `fetch` should be used if the key is known to be in the dictionary, otherwise `find`.

## See Also

`gb_trees(3)` [page 170], `orddict(3)` [page 251]

# digraph

Erlang Module

The `digraph` module implements a version of labeled directed graphs. What makes the graphs implemented here non-proper directed graphs is that multiple edges between vertices are allowed. However, the customary definition of directed graphs will be used in the text that follows.

A *directed graph* (or just “digraph”) is a pair  $(V,E)$  of a finite set  $V$  of *vertices* and a finite set  $E$  of *directed edges* (or just “edges”). The set of edges  $E$  is a subset of  $VV$  (the Cartesian product of  $V$  with itself). In this module,  $V$  is allowed to be empty; the so obtained unique digraph is called the *empty digraph*. Both vertices and edges are represented by unique Erlang terms.

Digraphs can be annotated with additional information. Such information may be attached to the vertices and to the edges of the digraph. A digraph which has been annotated is called a *labeled digraph*, and the information attached to a vertex or an edge is called a *label*. Labels are Erlang terms.

An edge  $e=(v,w)$  is said to *emanate* from vertex  $v$  and to be *incident* on vertex  $w$ . The *out-degree* of a vertex is the number of edges emanating from that vertex. The *in-degree* of a vertex is the number of edges incident on that vertex. If there is an edge emanating from  $v$  and incident on  $w$ , then  $w$  is said to be an *out-neighbour* of  $v$ , and  $v$  is said to be an *in-neighbour* of  $w$ . A *path*  $P$  from  $v[1]$  to  $v[k]$  in a digraph  $(V, E)$  is a non-empty sequence  $v[1],v[2],\dots,v[k]$  of vertices in  $V$  such that there is an edge  $(v[i],v[i+1])$  in  $E$  for  $1\leq i\leq k-1$ . The *length* of the path  $P$  is  $k-1$ .  $P$  is *simple* if all vertices are distinct, except that the first and the last vertices may be the same.  $P$  is a *cycle* if the length of  $P$  is not zero and  $v[1] = v[k]$ . A *loop* is a cycle of length one. A *simple cycle* is a path that is both a cycle and simple. An *acyclic digraph* is a digraph that has no cycles.

## Exports

```
add_edge(G, E, V1, V2, Label) -> edge() | {error, Reason}
add_edge(G, V1, V2, Label) -> edge() | {error, Reason}
add_edge(G, V1, V2) -> edge() | {error, Reason}
```

Types:

- $G = \text{digraph}()$
- $E = \text{edge}()$
- $V1 = V2 = \text{vertex}()$
- $\text{Label} = \text{label}()$
- $\text{Reason} = \{\text{bad\_edge}, \text{Path}\} \mid \{\text{bad\_vertex}, V\}$
- $\text{Path} = [\text{vertex}()]$

`add_edge/5` creates (or modifies) the edge `E` of the digraph `G`, using `Label` as the (new) label [page 93] of the edge. The edge is emanating [page 93] from `V1` and incident [page 93] on `V2`. Returns `E`.

`add_edge(G, V1, V2, Label)` is equivalent to `add_edge(G, E, V1, V2, Label)`, where `E` is a created edge. Tuples on the form `['$e' | N]`, where `N` is an integer  $\geq 1$ , are used for representing the created edges.

`add_edge(G, V1, V2)` is equivalent to `add_edge(G, V1, V2, [])`.

If the edge would create a cycle in an acyclic digraph [page 93], then `{error, {bad_edge, Path}}` is returned. If either of `V1` or `V2` is not a vertex of the digraph `G`, then `{error, {bad_vertex, V}}` is returned,  $V=V1$  or  $V=V2$ .

`add_vertex(G, V, Label) -> vertex()`

`add_vertex(G, V) -> vertex()`

`add_vertex(G) -> vertex()`

Types:

- `G = digraph()`
- `V = vertex()`
- `Label = label()`

`add_vertex/3` creates (or modifies) the vertex `V` of the digraph `G`, using `Label` as the (new) label [page 93] of the vertex. Returns `V`.

`add_vertex(G, V)` is equivalent to `add_vertex(G, V, [])`.

`add_vertex/1` creates a vertex using the empty list as label, and returns the created vertex. Tuples on the form `['$v' | N]`, where `N` is an integer  $\geq 1$ , are used for representing the created vertices.

`del_edge(G, E) -> true`

Types:

- `G = digraph()`
- `E = edge()`

Deletes the edge `E` from the digraph `G`.

`del_edges(G, Edges) -> true`

Types:

- `G = digraph()`
- `Edges = [edge()]`

Deletes the edges in the list `Edges` from the digraph `G`.

`del_path(G, V1, V2) -> true`

Types:

- `G = digraph()`
- `V1 = V2 = vertex()`

Deletes edges from the digraph `G` until there are no paths [page 93] from the vertex `V1` to the vertex `V2`.

A sketch of the procedure employed: Find an arbitrary simple path [page 93] `v[1],v[2],...,v[k]` from `V1` to `V2` in `G`. Remove all edges of `G` emanating [page 93] from `v[i]` and incident [page 93] to `v[i+1]` for  $1 \leq i < k$  (including multiple edges). Repeat until there is no path between `V1` and `V2`.

`del_vertex(G, V) -> true`

Types:

- `G = digraph()`
- `V = vertex()`

Deletes the vertex `V` from the digraph `G`. Any edges emanating [page 93] from `V` or incident [page 93] on `V` are also deleted.

`del_vertices(G, Vertices) -> true`

Types:

- `G = digraph()`
- `Vertices = [vertex()]`

Deletes the vertices in the list `Vertices` from the digraph `G`.

`delete(G) -> true`

Types:

- `G = digraph()`

Deletes the digraph `G`. This call is important because digraphs are implemented with `Ets`. There is no garbage collection of `Ets` tables. The digraph will, however, be deleted if the process that created the digraph terminates.

`edge(G, E) -> {E, V1, V2, Label} | false`

Types:

- `G = digraph()`
- `E = edge()`
- `V1 = V2 = vertex()`
- `Label = label()`

Returns `{E, V1, V2, Label}` where `Label` is the label [page 93] of the edge `E` emanating [page 93] from `V1` and incident [page 93] on `V2` of the digraph `G`. If there is no edge `E` of the digraph `G`, then `false` is returned.

`edges(G) -> Edges`

Types:

- `G = digraph()`
- `Edges = [edge()]`

Returns a list of all edges of the digraph `G`, in some unspecified order.

`edges(G, V) -> Edges`

Types:

- `G = digraph()`
- `V = vertex()`
- `Edges = [edge()]`

Returns a list of all edges emanating [page 93] from or incident [page 93] on `V` of the digraph `G`, in some unspecified order.

`get_cycle(G, V) -> Vertices | false`

Types:

- `G = digraph()`
- `V1 = V2 = vertex()`
- `Vertices = [vertex()]`

If there is a simple cycle [page 93] of length two or more through the vertex `V`, then the cycle is returned as a list `[V, . . . , V]` of vertices, otherwise if there is a loop [page 93] through `V`, then the loop is returned as a list `[V]`. If there are no cycles through `V`, then `false` is returned.

`get_path/3` is used for finding a simple cycle through `V`.

`get_path(G, V1, V2) -> Vertices | false`

Types:

- `G = digraph()`
- `V1 = V2 = vertex()`
- `Vertices = [vertex()]`

Tries to find a simple path [page 93] from the vertex `V1` to the vertex `V2` of the digraph `G`. Returns the path as a list `[V1, . . . , V2]` of vertices, or `false` if no simple path from `V1` to `V2` of length one or more exists.

The digraph `G` is traversed in a depth-first manner, and the first path found is returned.

`get_short_cycle(G, V) -> Vertices | false`

Types:

- `G = digraph()`
- `V1 = V2 = vertex()`
- `Vertices = [vertex()]`

Tries to find an as short as possible simple cycle [page 93] through the vertex `V` of the digraph `G`. Returns the cycle as a list `[V, . . . , V]` of vertices, or `false` if no simple cycle through `V` exists. Note that a loop [page 93] through `V` is returned as the list `[V, V]`.

`get_short_path/3` is used for finding a simple cycle through `V`.

`get_short_path(G, V1, V2) -> Vertices | false`

Types:

- `G = digraph()`
- `V1 = V2 = vertex()`
- `Vertices = [vertex()]`

Tries to find an as short as possible simple path [page 93] from the vertex  $V_1$  to the vertex  $V_2$  of the digraph  $G$ . Returns the path as a list  $[V_1, \dots, V_2]$  of vertices, or `false` if no simple path from  $V_1$  to  $V_2$  of length one or more exists.

The digraph  $G$  is traversed in a breadth-first manner, and the first path found is returned.

`in_degree(G, V) -> integer()`

Types:

- $G = \text{digraph}()$
- $V = \text{vertex}()$

Returns the in-degree [page 93] of the vertex  $V$  of the digraph  $G$ .

`in_edges(G, V) -> Edges`

Types:

- $G = \text{digraph}()$
- $V = \text{vertex}()$
- $\text{Edges} = [\text{edge}()]$

Returns a list of all edges incident [page 93] on  $V$  of the digraph  $G$ , in some unspecified order.

`in_neighbours(G, V) -> Vertices`

Types:

- $G = \text{digraph}()$
- $V = \text{vertex}()$
- $\text{Vertices} = [\text{vertex}()]$

Returns a list of all in-neighbours [page 93] of  $V$  of the digraph  $G$ , in some unspecified order.

`info(G) -> InfoList`

Types:

- $G = \text{digraph}()$
- $\text{InfoList} = [\{\text{cyclicity}, \text{Cyclicity}\}, \{\text{memory}, \text{NoWords}\}, \{\text{protection}, \text{Protection}\}]$
- $\text{Cyclicity} = \text{cyclic} \mid \text{acyclic}$
- $\text{Protection} = \text{protected} \mid \text{private}$
- $\text{NoWords} = \text{integer}() \geq 0$

Returns a list of  $\{\text{Tag}, \text{Value}\}$  pairs describing the digraph  $G$ . The following pairs are returned:

- $\{\text{cyclicity}, \text{Cyclicity}\}$ , where  $\text{Cyclicity}$  is `cyclic` or `acyclic`, according to the options given to `new`.
- $\{\text{memory}, \text{NoWords}\}$ , where  $\text{NoWords}$  is the number of words allocated to the ets tables.
- $\{\text{protection}, \text{Protection}\}$ , where  $\text{Protection}$  is `protected` or `private`, according to the options given to `new`.

`new()` -> `digraph()`

Equivalent to `new([])`.

`new(Type)` -> `digraph()` | `{error, Reason}`

Types:

- `Type` = [`cyclic` | `acyclic` | `private` | `protected`]
- `Reason` = `{unknown_type, term()}`

Returns an empty digraph [page 93] with properties according to the options in `Type`:

`cyclic` Allow cycles [page 93] in the digraph (default).

`acyclic` The digraph is to be kept acyclic [page 93].

`protected` Other processes can read the digraph (default).

`private` The digraph can be read and modified by the creating process only.

If an unrecognized type option `T` is given, then `{error, {unknown_type, T}}` is returned.

`no_edges(G)` -> `integer()`  $\geq 0$

Types:

- `G` = `digraph()`

Returns the number of edges of the digraph `G`.

`no_vertices(G)` -> `integer()`  $\geq 0$

Types:

- `G` = `digraph()`

Returns the number of vertices of the digraph `G`.

`out_degree(G, V)` -> `integer()`

Types:

- `G` = `digraph()`
- `V` = `vertex()`

Returns the out-degree [page 93] of the vertex `V` of the digraph `G`.

`out_edges(G, V)` -> `Edges`

Types:

- `G` = `digraph()`
- `V` = `vertex()`
- `Edges` = [`edge()`]

Returns a list of all edges emanating [page 93] from `V` of the digraph `G`, in some unspecified order.

`out_neighbours(G, V)` -> `Vertices`

Types:

- `G` = `digraph()`

- `V = vertex()`
- `Vertices = [vertex()]`

Returns a list of all out-neighbours [page 93] of `V` of the digraph `G`, in some unspecified order.

`vertex(G, V) -> {V, Label} | false`

Types:

- `G = digraph()`
- `V = vertex()`
- `Label = label()`

Returns `{V, Label}` where `Label` is the label [page 93] of the vertex `V` of the digraph `G`, or `false` if there is no vertex `V` of the digraph `G`.

`vertices(G) -> Vertices`

Types:

- `G = digraph()`
- `Vertices = [vertex()]`

Returns a list of all vertices of the digraph `G`, in some unspecified order.

## See Also

`digraph_utils(3)` [page 100], `ets(3)` [page 129]

# digraph\_utils

Erlang Module

The `digraph_utils` module implements some algorithms based on depth-first traversal of directed graphs. See the `digraph` module for basic functions on directed graphs.

A *directed graph* (or just “digraph”) is a pair  $(V,E)$  of a finite set  $V$  of *vertices* and a finite set  $E$  of *directed edges* (or just “edges”). The set of edges  $E$  is a subset of  $VV$  (the Cartesian product of  $V$  with itself).

Digraphs can be annotated with additional information. Such information may be attached to the vertices and to the edges of the digraph. A digraph which has been annotated is called a *labeled digraph*, and the information attached to a vertex or an edge is called a *label*.

An edge  $e=(v,w)$  is said to *emanate* from vertex  $v$  and to be *incident* on vertex  $w$ . If there is an edge emanating from  $v$  and incident on  $w$ , then  $w$  is said to be an *out-neighbour* of  $v$ . A *path*  $P$  from  $v[1]$  to  $v[k]$  in a digraph  $(V, E)$  is a non-empty sequence  $v[1],v[2],\dots,v[k]$  of vertices in  $V$  such that there is an edge  $(v[i],v[i+1])$  in  $E$  for  $1 \leq i < k$ . The *length* of the path  $P$  is  $k-1$ .  $P$  is a *cycle* if the length of  $P$  is not zero and  $v[1] = v[k]$ . A *loop* is a cycle of length one. An *acyclic digraph* is a digraph that has no cycles.

A *depth-first traversal* of a directed digraph can be viewed as a process that visits all vertices of the digraph. Initially, all vertices are marked as unvisited. The traversal starts with an arbitrarily chosen vertex, which is marked as visited, and follows an edge to an unmarked vertex, marking that vertex. The search then proceeds from that vertex in the same fashion, until there is no edge leading to an unvisited vertex. At that point the process backtracks, and the traversal continues as long as there are unexamined edges. If there remain unvisited vertices when all edges from the first vertex have been examined, some hitherto unvisited vertex is chosen, and the process is repeated.

A *partial ordering* of a set  $S$  is a transitive, antisymmetric and reflexive relation between the objects of  $S$ . The problem of *topological sorting* is to find a total ordering of  $S$  that is a superset of the partial ordering. A digraph  $G=(V,E)$  is equivalent to a relation  $E$  on  $V$  (we neglect the fact that the version of directed graphs implemented in the `digraph` module allows multiple edges between vertices). If the digraph has no cycles of length two or more, then the reflexive and transitive closure of  $E$  is a partial ordering.

A *subgraph*  $G'$  of  $G$  is a digraph whose vertices and edges form subsets of the vertices and edges of  $G$ .  $G'$  is *maximal* with respect to a property  $P$  if all other subgraphs that include the vertices of  $G'$  do not have the property  $P$ . A *strongly connected component* is a maximal subgraph such that there is a path between each pair of vertices. A *connected component* is a maximal subgraph such that there is a path between each pair of vertices, considering all edges undirected.

## Exports

`components(Digraph) -> [Component]`

Types:

- `Digraph = digraph()`
- `Component = [vertex()]`

Returns a list of connected components [page 100]. Each component is represented by its vertices. The order of the vertices and the order of the components are arbitrary. Each vertex of the digraph `Digraph` occurs in exactly one component.

`condensation(Digraph) -> CondensedDigraph`

Types:

- `Digraph = CondensedDigraph = digraph()`

Creates a digraph where the vertices are the strongly connected components [page 100] of `Digraph` as returned by `strong_components/1`. If `X` and `Y` are strongly connected components, and there exist vertices `x` and `y` in `X` and `Y` respectively such that there is an edge emanating [page 100] from `x` and incident [page 100] on `y`, then an edge emanating from `X` and incident on `Y` is created.

The created digraph has the same type as `Digraph`. All vertices and edges have the default label [page 100] `[]`.

Each and every cycle [page 100] is included in some strongly connected component, which implies that there always exists a topological ordering [page 100] of the created digraph.

`cyclic_strong_components(Digraph) -> [StrongComponent]`

Types:

- `Digraph = digraph()`
- `StrongComponent = [vertex()]`

Returns a list of strongly connected components [page 100]. Each strongly component is represented by its vertices. The order of the vertices and the order of the components are arbitrary. Only vertices that are included in some cycle [page 100] in `Digraph` are returned, otherwise the returned list is equal to that returned by `strong_components/1`.

`is_acyclic(Digraph) -> bool()`

Types:

- `Digraph = digraph()`

Returns true if and only if the digraph `Digraph` is acyclic [page 100].

`loop_vertices(Digraph) -> Vertices`

Types:

- `Digraph = digraph()`
- `Vertices = [vertex()]`

Returns a list of all vertices of `Digraph` that are included in some loop [page 100].

`postorder(Digraph) -> Vertices`

Types:

- `Digraph = digraph()`
- `Vertices = [vertex()]`

Returns all vertices of the digraph `Digraph`. The order is given by a depth-first traversal [page 100] of the digraph, collecting visited vertices in postorder. More precisely, the vertices visited while searching from an arbitrarily chosen vertex are collected in postorder, and all those collected vertices are placed before the subsequently visited vertices.

`preorder(Digraph) -> Vertices`

Types:

- `Digraph = digraph()`
- `Vertices = [vertex()]`

Returns all vertices of the digraph `Digraph`. The order is given by a depth-first traversal [page 100] of the digraph, collecting visited vertices in pre-order.

`reachable(Vertices, Digraph) -> Vertices`

Types:

- `Digraph = digraph()`
- `Vertices = [vertex()]`

Returns an unsorted list of digraph vertices such that for each vertex in the list, there is a path [page 100] in `Digraph` from some vertex of `Vertices` to the vertex. In particular, since paths may have length zero, the vertices of `Vertices` are included in the returned list.

`reachable_neighbours(Vertices, Digraph) -> Vertices`

Types:

- `Digraph = digraph()`
- `Vertices = [vertex()]`

Returns an unsorted list of digraph vertices such that for each vertex in the list, there is a path [page 100] in `Digraph` of length one or more from some vertex of `Vertices` to the vertex. As a consequence, only those vertices of `Vertices` that are included in some cycle [page 100] are returned.

`reaching(Vertices, Digraph) -> Vertices`

Types:

- `Digraph = digraph()`
- `Vertices = [vertex()]`

Returns an unsorted list of digraph vertices such that for each vertex in the list, there is a path [page 100] from the vertex to some vertex of `Vertices`. In particular, since paths may have length zero, the vertices of `Vertices` are included in the returned list.

`reaching_neighbours(Vertices, Digraph) -> Vertices`

Types:

- Digraph = digraph()
- Vertices = [vertex()]

Returns an unsorted list of digraph vertices such that for each vertex in the list, there is a path [page 100] of length one or more from the vertex to some vertex of Vertices. As a consequence, only those vertices of Vertices that are included in some cycle [page 100] are returned.

`strong_components(Digraph) -> [StrongComponent]`

Types:

- Digraph = digraph()
- StrongComponent = [vertex()]

Returns a list of strongly connected components [page 100]. Each strongly component is represented by its vertices. The order of the vertices and the order of the components are arbitrary. Each vertex of the digraph Digraph occurs in exactly one strong component.

`subgraph(Digraph, Vertices [, Options]) -> Subgraph | {error, Reason}`

Types:

- Digraph = Subgraph = digraph()
- Options = [{type, SubgraphType}, {keep\_labels, bool()}]
- Reason = {invalid\_option, term()} | {unknown\_type, term()}]
- SubgraphType = inherit | type()
- Vertices = [vertex()]

Creates a maximal subgraph [page 100] of Digraph having as vertices those vertices of Digraph that are mentioned in Vertices.

If the value of the option `type` is `inherit`, which is the default, then the type of Digraph is used for the subgraph as well. Otherwise the option value of `type` is used as argument to `digraph:new/1`.

If the value of the option `keep_labels` is `true`, which is the default, then the labels [page 100] of vertices and edges of Digraph are used for the subgraph as well. If the value is `false`, then the default label, `[]`, is used for the subgraph's vertices and edges.

`subgraph(Digraph, Vertices)` is equivalent to `subgraph(Digraph, Vertices, [])`.

`topsort(Digraph) -> Vertices | false`

Types:

- Digraph = digraph()
- Vertices = [vertex()]

Returns a topological ordering [page 100] of the vertices of the digraph Digraph if such an ordering exists, `false` otherwise. For each vertex in the returned list, there are no out-neighbours [page 100] that occur earlier in the list.

## See Also

[digraph\(3\) \[page 93\]](#)

# epp

Erlang Module

The Erlang code preprocessor includes functions which are used by `compile` to preprocess macros and include files before the actual parsing takes place.

## Exports

`open(FileName, IncludePath) -> {ok, Epp} | {error, ErrorDescriptor}`

`open(FileName, IncludePath, PredefMacros) -> {ok, Epp} | {error, ErrorDescriptor}`

Types:

- `FileName` = `atom()` | `string()`
- `IncludePath` = `[DirectoryName]`
- `DirectoryName` = `atom()` | `string()`
- `PredefMacros` = `[{atom(), term()}]`
- `Epp` = `pid()` – handle to the epp server
- `ErrorDescriptor` = `term()`

Opens a file for preprocessing.

`close(Epp) -> ok`

Types:

- `Epp` = `pid()` – handle to the epp server

Closes the preprocessing of a file.

`parse_erl_form(Epp) -> {ok, AbsForm} | {eof, Line} | {error, ErrorInfo}`

Types:

- `Epp` = `pid()`
- `AbsForm` = `term()`
- `Line` = `integer()`
- `ErrorInfo` = see separate description below.

Returns the next Erlang form from the opened Erlang source file. The tuple `{eof, Line}` is returned at end-of-file. The first form corresponds to an implicit attribute `-file(File, 1) .`, where `File` is the name of the file.

`parse_file(FileName, IncludePath, PredefMacro) -> {ok, [Form]} | {error, OpenError}`

Types:

- `FileName` = `atom()` | `string()`

- IncludePath = [DirectoryName]
- DirectoryName = atom() | string()
- PredefMacros = [{atom(),term()}]
- Form = term() – same as returned by `erl_parse:parse_form`

Preprocesses and parses an Erlang source file. Note that the tuple `{eof, Line}` returned at end-of-file is included as a “form”.

## Error Information

The `ErrorInfo` mentioned above is the standard `ErrorInfo` structure which is returned from all IO modules. It has the following format:

```
{ErrorLine, Module, ErrorDescriptor}
```

A string which describes the error is obtained with the following call:

```
apply(Module, format_error, ErrorDescriptor)
```

## See Also

`erl_parse(3)` [page 115]

# erl\_eval

Erlang Module

This module provides an interpreter for Erlang expressions. The expressions are in the abstract syntax as returned by `erl_parse`, the Erlang parser, or a call to `io:parse_erl_exprs/2`.

## Exports

```
exprs(Expressions, Bindings) -> {value, Value, NewBindings}
exprs(Expressions, Bindings, LocalFunctionHandler) -> {value, Value, NewBindings}
exprs(Expressions, Bindings, LocalFunctionHandler, NonlocalFunctionHandler) ->
  {value, Value, NewBindings}
```

Types:

- Expressions = as returned by `erl_parse` or `io:parse_erl_exprs/2`
- Bindings = as returned by `bindings/1`
- LocalFunctionHandler = {value, Func} | {eval, Func} | none
- NonlocalFunctionHandler = {value, Func} | none

Evaluates Expressions with the set of bindings Bindings, where Expressions is a sequence of expressions (in abstract syntax) of a type which may be returned by `io:parse_erl_exprs/2`. See below for an explanation of how and when to use the arguments LocalFunctionHandler and NonlocalFunctionHandler.

Returns {value, Value, NewBindings}

```
expr(Expression, Bindings) -> { value, Value, NewBindings }
expr(Expression, Bindings, LocalFunctionHandler) -> { value, Value, NewBindings }
expr(Expression, Bindings, LocalFunctionHandler, NonlocalFunctionHandler) -> { value,
  Value, NewBindings }
```

Types:

- Expression = as returned by `io:parse_erl_form/2`, for example
- Bindings = as returned by `bindings/1`
- LocalFunctionHandler = {value, Func} | {eval, Func} | none
- NonlocalFunctionHandler = {value, Func} | none

Evaluates Expression with the set of bindings Bindings. Expression is an expression (in abstract syntax) of a type which may be returned by `io:parse_erl_form/2`. See below for an explanation of how and when to use the arguments LocalFunctionHandler and NonlocalFunctionHandler.

Returns {value, Value, NewBindings}.

```

expr_list(ExpressionList, Bindings) -> {ValueList, NewBindings}
expr_list(ExpressionList, Bindings, LocalFunctionHandler) -> {ValueList, NewBindings}
expr_list(ExpressionList, Bindings, LocalFunctionHandler, NonlocalFunctionHandler) ->
    {ValueList, NewBindings}

```

Evaluates a list of expressions in parallel, using the same initial bindings for each expression. Attempts are made to merge the bindings returned from each evaluation. This function is useful in the `LocalFunctionHandler`. See below.

Returns `{ValueList, NewBindings}`.

```
new_bindings() -> BindingStruct
```

Returns an empty binding structure.

```
bindings(BindingStruct) -> Bindings
```

Returns the list of bindings contained in the binding structure.

```
binding(Name, BindingStruct) -> Binding
```

Returns the binding of `Name` in `BindingStruct`.

```
add_binding(Name, Value, Bindings) -> BindingStruct
```

Adds the binding `Name = Value` to `Bindings`. Returns an updated binding structure.

```
del_binding(Name, Bindings) -> BindingStruct
```

Removes the binding of `Name` in `Bindings`. Returns an updated binding structure.

## Local Function Handler

During evaluation of a function, no calls can be made to local functions. An undefined function error would be generated. However, the optional argument `LocalFunctionHandler` may be used to define a function which is called when there is a call to a local function. The argument can have the following formats:

`{value,Func}` This defines a local function handler which is called with:

```
Func(Name, Arguments)
```

`Name` is the name of the local function (an atom) and `Arguments` is a list of the *evaluated* arguments. The function handler returns the value of the local function. In this case, it is not possible to access the current bindings. To signal an error, the function handler just calls `exit/1` with a suitable exit value.

`{eval,Func}` This defines a local function handler which is called with:

```
Func(Name, Arguments, Bindings)
```

`Name` is the name of the local function (an atom), `Arguments` is a list of the *unevaluated* arguments, and `Bindings` are the current variable bindings. The function handler returns:

```
{value,Value,NewBindings}
```

`Value` is the value of the local function and `NewBindings` are the updated variable bindings. In this case, the function handler must itself evaluate all the function arguments and manage the bindings. To signal an error, the function handler just calls `exit/1` with a suitable exit value.

`none` There is no local function handler.

## Non-local Function Handler

The optional argument `NonlocalFunctionHandler` may be used to define a function which is called in the following cases: a functional object (`fun`) is called; a built-in function is called; a function is called using the `M:F` syntax, where `M` and `F` are atoms or expressions; an operator `Op/A` is called (this is handled as a call to the function `erlang:Op/A`). Exceptions are calls to `erlang:apply/2,3`; neither of the function handlers will be called for such calls. The argument can have the following formats:

`{value,Func}` This defines a nonlocal function handler which is called with:

```
Func(FuncSpec, Arguments)
```

`FuncSpec` is the name of the function on the form `{Module,Function}` or a `fun`, and `Arguments` is a list of the *evaluated* arguments. The function handler returns the value of the function. To signal an error, the function handler just calls `exit/1` with a suitable exit value.

`none` There is no nonlocal function handler.

### Note:

For calls such as `erlang:apply(Fun, Args)` or `erlang:apply(Module, Function, Args)` the call of the non-local function handler corresponding to the call to `erlang:apply/2,3` itself—`Func({erlang, apply}, [Fun, Args])` or `Func({erlang, apply}, [Module, Function, Args])`—will never take place. The non-local function handler *will* however be called with the evaluated arguments of the call to `erlang:apply/2,3:Func(Fun, Args)` or `Func({Module, Function}, Args)` (assuming that `{Module, Function}` is not `{erlang, apply}`).

The nonlocal function handler argument is probably not used as frequently as the local function handler argument. A possible use is to call `exit/1` on calls to functions that for some reason are not allowed to be called.

## Bugs

The evaluator is not complete. `receive` cannot be handled properly.

Any undocumented functions in `erl_eval` should not be used.

# erl\_expand\_records

Erlang Module

## Exports

`module(AbsForms, CompileOptions) -> AbsForms`

Types:

- `AbsForms = [term()]`
- `CompileOptions = [term()]`

Expands all records in a module. The returned module has no references to records, neither attributes nor code.

## See Also

The `[abstract format]` documentation in ERTS User's Guide

# erl\_id\_trans

Erlang Module

This module performs an identity parse transformation of Erlang code. It is included as an example for users who may wish to write their own parse transformers. If the option `{parse_transform, Module}` is passed to the compiler, a user written function `parse_transform/2` is called by the compiler before the code is checked for errors.

## Exports

`parse_transform(Forms, Options) -> Forms`

Types:

- `Forms = [erlang_form()]`
- `Options = [compiler_options()]`

Performs an identity transformation on Erlang forms, as an example.

## Parse Transformations

Parse transformations are used if a programmer wants to use Erlang syntax, but with different semantics. The original Erlang code is then transformed into other Erlang code.

**Note:**

Programmers are strongly advised not to engage in parse transformations and no support is offered for problems encountered.

## See Also

`erl_parse(3)` [page 115], `compile(3)`.

# erl\_internal

Erlang Module

This module defines Erlang BIFs, guard tests and operators. This module is only of interest to programmers who manipulate Erlang code.

## Exports

`bif(Name, Arity) -> bool()`

Types:

- Name = atom()
- Arity = integer()

Returns true if Name/Arity is an Erlang BIF which is automatically recognized by the compiler, otherwise false.

`guard_bif(Name, Arity) -> bool()`

Types:

- Name = atom()
- Arity = integer()

Returns true if Name/Arity is an Erlang BIF which is allowed in guards, otherwise false.

`type_test(Name, Arity) -> bool()`

Types:

- Name = atom()
- Arity = integer()

Returns true if Name/Arity is a valid Erlang type test, otherwise false.

`arith_op(OpName, Arity) -> bool()`

Types:

- OpName = atom()
- Arity = integer()

Returns true if OpName/Arity is an arithmetic operator, otherwise false.

`bool_op(OpName, Arity) -> bool()`

Types:

- OpName = atom()

- Arity = integer()

Returns true if OpName/Arity is a Boolean operator, otherwise false.

comp\_op(OpName, Arity) -> bool()

Types:

- OpName = atom()
- Arity = integer()

Returns true if OpName/Arity is a comparison operator, otherwise false.

list\_op(OpName, Arity) -> bool()

Types:

- OpName = atom()
- Arity = integer()

Returns true if OpName/Arity is a list operator, otherwise false.

send\_op(OpName, Arity) -> bool()

Types:

- OpName = atom()
- Arity = integer()

Returns true if OpName/Arity is a send operator, otherwise false.

op\_type(OpName, Arity) -> Type

Types:

- OpName = atom()
- Arity = integer()
- Type = arith | bool | comp | list | send

Returns the Type of operator that OpName/Arity belongs to, or generates a `function_clause` error if it is not an operator at all.

# erl\_lint

## Erlang Module

This module is used to check Erlang code for illegal syntax and other bugs. It also warns against coding practices which are not recommended.

The errors detected include:

- redefined and undefined functions
- unbound and unsafe variables
- illegal record usage.

Warnings include:

- unused functions and imports
- unused variables
- variables imported into matches
- variables exported from `if/case/receive`
- variables shadowed in lambdas and list comprehensions.

Some of the warnings are optional, and can be turned on by giving the appropriate option, described below.

The functions in this module are invoked automatically by the Erlang compiler and there is no reason to invoke these functions separately unless you have written your own Erlang compiler.

## Exports

```
module(AbsForms) -> {ok,Warnings} | {error,Errors,Warnings}
module(AbsForms, FileName) -> {ok,Warnings} | {error,Errors,Warnings}
module(AbsForms, FileName, CompileOptions) -> {ok,Warnings} | {error,Errors,Warnings}
```

Types:

- AbsForms = [term()]
- FileName = FileName2 = atom() | string()
- Warnings = Errors = [{Filename2,[ErrorInfo]}]
- ErrorInfo = see separate description below.
- CompileOptions = [term()]

This function checks all the forms in a module for errors. It returns:

`{ok,Warnings}` There were no errors in the module.

`{error,Errors,Warnings}` There were errors in the module.

Since this module is of interest only to the maintainers of the compiler, and to avoid having the same description in two places to avoid the usual maintenance nightmare, the elements of `Options` that control the warnings are only described in `[compile(3)]`.

The `AbsForms` of a module which comes from a file that is read through `epp`, the Erlang pre-processor, can come from many files. This means that any references to errors must include the file name (see `epp(3)` [page 104], or parser `erl_parse(3)` [page 115]) The warnings and errors returned have the following format:

```
[{FileName2, [ErrorInfo]}]
```

The errors and warnings are listed in the order in which they are encountered in the forms. This means that the errors from one file may be split into different entries in the list of errors.

```
is_guard_test(Expr) -> bool()
```

Types:

- `Expr = term()`

This function tests if `Expr` is a legal guard test. `Expr` is an Erlang term representing the abstract form for the expression. `erl_parse:parse_exprs(Tokens)` can be used to generate a list of `Expr`.

```
format_error(ErrorDescriptor) -> Chars
```

Types:

- `ErrorDescriptor = errordesc()`
- `Chars = [char() | Chars]`

Takes an `ErrorDescriptor` and returns a string which describes the error or warning. This function is usually called implicitly when processing an `ErrorInfo` structure (see below).

## Error Information

The `ErrorInfo` mentioned above is the standard `ErrorInfo` structure which is returned from all IO modules. It has the following format:

```
{ErrorLine, Module, ErrorDescriptor}
```

A string which describes the error is obtained with the following call:

```
apply(Module, format_error, ErrorDescriptor)
```

## See Also

`erl_parse(3)` [page 115], `epp(3)` [page 104]

# erl\_parse

## Erlang Module

This module is the basic Erlang parser which converts tokens into the abstract form of either forms (i.e., top-level constructs), expressions, or terms. The Abstract Format is described in the ERTS User's Guide. Note that a token list must end with the *dot* token in order to be acceptable to the parse functions (see `erl_scan`).

## Exports

`parse_form(Tokens) -> {ok, AbsForm} | {error, ErrorInfo}`

Types:

- Tokens = [Token]
- Token = {Tag,Line} | {Tag,Line,term()}
- Tag = atom()
- AbsForm = term()
- ErrorInfo = see section Error Information below.

This function parses Tokens as if it were a form. It returns:

`{ok, AbsForm}` The parsing was successful. AbsForm is the abstract form of the parsed form.

`{error, ErrorInfo}` An error occurred.

`parse_exprs(Tokens) -> {ok, Expr_list} | {error, ErrorInfo}`

Types:

- Tokens = [Token]
- Token = {Tag,Line} | {Tag,Line,term()}
- Tag = atom()
- Expr\_list = [AbsExpr]
- AbsExpr = term()
- ErrorInfo = see section Error Information below.

This function parses Tokens as if it were a list of expressions. It returns:

`{ok, Expr_list}` The parsing was successful. Expr\_list is a list of the abstract forms of the parsed expressions.

`{error, ErrorInfo}` An error occurred.

`parse_term(Tokens) -> {ok, Term} | {error, ErrorInfo}`

Types:

- Tokens = [Token]
- Token = {Tag,Line} | {Tag,Line,term() }
- Tag = atom()
- Term = term()
- ErrorInfo = see section Error Information below.

This function parses Tokens as if it were a term. It returns:

{ok, Term} The parsing was successful. Term is the Erlang term corresponding to the token list.

{error, ErrorInfo} An error occurred.

format\_error(ErrorDescriptor) -> Chars

Types:

- ErrorDescriptor = errordesc()
- Chars = [char() | Chars]

Uses an ErrorDescriptor and returns a string which describes the error. This function is usually called implicitly when an ErrorInfo structure is processed (see below).

tokens(AbsTerm) -> Tokens

tokens(AbsTerm, MoreTokens) -> Tokens

Types:

- Tokens = MoreTokens = [Token]
- Token = {Tag,Line} | {Tag,Line,term() }
- Tag = atom()
- AbsTerm = term()
- ErrorInfo = see section Error Information below.

This function generates a list of tokens representing the abstract form AbsTerm of an expression. Optionally, it appends Moretokens.

normalise(AbsTerm) -> Data

Types:

- AbsTerm = Data = term()

Converts the abstract form AbsTerm of a term into a conventional Erlang data structure (i.e., the term itself). This is the inverse of abstract/1.

abstract(Data) -> AbsTerm

Types:

- Data = AbsTerm = term()

Converts the Erlang data structure Data into an abstract form of type AbsTerm. This is the inverse of normalise/1.

## Error Information

The `ErrorInfo` mentioned above is the standard `ErrorInfo` structure which is returned from all IO modules. It has the format:

```
{ErrorLine, Module, ErrorDescriptor}
```

A string which describes the error is obtained with the following call:

```
apply(Module, format_error, ErrorDescriptor)
```

## See Also

[io\(3\)](#) [page 205], [erl\\_scan\(3\)](#) [page 121], [ERTS User's Guide](#)

# erl\_pp

Erlang Module

The functions in this module are used to generate aesthetically attractive representations of abstract forms, which are suitable for printing. All functions return (possibly deep) lists of characters and generate an error if the form is wrong.

All functions can have an optional argument which specifies a hook that is called if an attempt is made to print an unknown form.

## Exports

```
form(Form) -> DeepCharList
```

```
form(Form, HookFunction) -> DeepCharList
```

Types:

- Form = term()
- HookFunction = see separate description below.
- DeepCharList = [char()|DeepCharList]

Pretty prints a Form which is an abstract form of a type which is returned by `erl_parse:parse_form`.

```
attribute(Attribute) -> DeepCharList
```

```
attribute(Attribute, HookFunction) -> DeepCharList
```

Types:

- Attribute = term()
- HookFunction = see separate description below.
- DeepCharList = [char()|DeepCharList]

The same as `form`, but only for the attribute `Attribute`.

```
function(Function) -> DeepCharList
```

```
function(Function, HookFunction) -> DeepCharList
```

Types:

- Function = term()
- HookFunction = see separate description below.
- DeepCharList = [char()|DeepCharList]

The same as `form`, but only for the function `Function`.

```
guard(Guard) -> DeepCharList
```

```
guard(Guard, HookFunction) -> DeepCharList
```

Types:

- Form = term()
- HookFunction = see separate description below.
- DeepCharList = [char()|DeepCharList]

The same as form, but only for the guard test Guard.

```
exprs(Expressions) -> DeepCharList
```

```
exprs(Expressions, HookFunction) -> DeepCharList
```

```
exprs(Expressions, Indent, HookFunction) -> DeepCharList
```

Types:

- Expressions = term()
- HookFunction = see separate description below.
- Indent = integer()
- DeepCharList = [char()|DeepCharList]

The same as form, but only for the sequence of expressions in Expressions.

```
expr(Expression) -> DeepCharList
```

```
expr(Expression, HookFunction) -> DeepCharList
```

```
expr(Expression, Indent, HookFunction) -> DeepCharList
```

```
expr(Expression, Indent, Precedence, HookFunction) ->-> DeepCharList
```

Types:

- Expression = term()
- HookFunction = see separate description below.
- Indent = integer()
- Precedence =
- DeepCharList = [char()|DeepCharList]

This function prints one expression. It is useful for implementing hooks (see below).

## Unknown Expression Hooks

The optional argument `HookFunction`, shown in the functions described above, defines a function which is called when an unknown form occurs where there should be a valid expression. It can have the following formats:

`Function` The hook function is called by:

```
Function(Expr,
         CurrentIndentation,
         CurrentPrecedence,
         HookFunction)
```

`none` There is no hook function

The called hook function should return a (possibly deep) list of characters. `expr/4` is useful in a hook.

If `CurrentIndentation` is negative, there will be no line breaks and only a space is used as a separator.

## Bugs

It should be possible to have hook functions for unknown forms at places other than expressions.

## See Also

[io\(3\)](#) [page 205], [erl\\_parse\(3\)](#) [page 115], [erl\\_eval\(3\)](#) [page 106]

# erl\_scan

Erlang Module

This module contains functions for tokenizing characters into Erlang tokens.

## Exports

`string(CharList,StartLine) -> {ok, Tokens, EndLine} | Error`

`string(CharList) -> {ok, Tokens, EndLine} | Error`

Types:

- CharList = string()
- StartLine = EndLine = Line = integer()
- Tokens = [{atom(),Line}|{atom(),Line,term()}]
- Error = {error, ErrorInfo, EndLine}

Takes the list of characters CharList and tries to scan (tokenize) them. Returns {ok, Tokens, EndLine}, where Tokens are the Erlang tokens from CharList. EndLine is the last line where a token was found.

StartLine indicates the initial line when scanning starts. string/1 is equivalent to string(CharList,1).

{error, ErrorInfo, EndLine} is returned if an error occurs. EndLine indicates where the error occurred.

`tokens(Continuation, CharList, StartLine) ->Return`

Types:

- Return = {done, Result, LeftOverChars} | {more, Continuation}
- Continuation = [] | string()
- CharList = string()
- StartLine = EndLine = integer()
- Result = {ok, Tokens, EndLine} | {eof, EndLine}
- Tokens = [{atom(),Line}|{atom(),Line,term()}]

This is the re-entrant scanner which scans characters until a *dot* (.' whitespace) has been reached. It returns:

{done, Result, LeftOverChars} This return indicates that there is sufficient input data to get an input. Result is:

{ok, Tokens, EndLine} The scanning was successful. Tokens is the list of tokens including *dot*.

{eof, EndLine} End of file was encountered before any more tokens.

`{error, ErrorInfo, EndLine}` An error occurred.  
`{more, Continuation}` More data is required for building a term. Continuation must be passed in a new call to `tokens/3` when more data is available.

`reserved_word(Atom) -> bool()`

Returns true if `Atom` is an Erlang reserved word, otherwise false.

`format_error(ErrorDescriptor) -> string()`

Types:

- `ErrorDescriptor = errordesc()`

Takes an `ErrorDescriptor` and returns a string which describes the error or warning. This function is usually called implicitly when processing an `ErrorInfo` structure (see below).

## Error Information

The `ErrorInfo` mentioned above is the standard `ErrorInfo` structure which is returned from all IO modules. It has the following format:

`{ErrorLine, Module, ErrorDescriptor}`

A string which describes the error is obtained with the following call:

`apply(Module, format_error, ErrorDescriptor)`

## Notes

The continuation of the first call to the re-entrant input functions must be `[]`. Refer to Armstrong, Viriding and Williams, 'Concurrent Programming in Erlang', Chapter 13, for a complete description of how the re-entrant input scheme works.

## See Also

`io(3)` [page 205], `erl_parse(3)` [page 115]

# erl\_tar

## Erlang Module

The `erl_tar` module archives and extract files to and from a tar file. The tar file format is the POSIX extended tar file format specified in IEEE Std 1003.1 and ISO/IEC9945-1. That is the same format as used by `tar` program on Solaris, but is not the same as used by the GNU tar program.

By convention, the name of a tar file should end in `".tar"`. To abide to the convention, you'll need to add `".tar"` yourself to the name.

Tar files can be created in one operation using the `create/2` [page 125] or `create/3` [page 125] function.

Alternatively, for more control, the `open` [page 127], `add/3,4` [page 124], and `close/1` [page 124] functions can be used.

To extract all files from a tar file, use the `extract/1` [page 125] function. To extract only some files or to be able to specify some more options, use the `extract/2` [page 126] function.

To return a list of the files in a tar file, use either the `table/1` [page 127] or `table/2` [page 127] function. To print a list of files to the Erlang shell, use either the `t/1` [page 127] or `tt/1` [page 128] function.

To convert an error term returned from one of the functions above to a readable message, use the `format_error/1` [page 126] function.

## LIMITATIONS

For maximum compatibility, it is safe to archive files with names up to 100 characters in length. Such tar files can generally be extracted by any `tar` program.

If filenames exceed 100 characters in length, the resulting tar file can only be correctly extracted by a POSIX-compatible `tar` program (such as Solaris `tar`), not by GNU `tar`.

File have longer names than 256 bytes cannot be stored at all.

The filename of the file a symbolic link points is always limited to 100 characters.

## Exports

`add(TarDescriptor, Filename, Options) -> RetValue`

Types:

- `TarDescriptor = term()`
- `Filename = filename()`
- `Options = [Option]`
- `Option = dereference|verbose`
- `RetValue = ok|{error,{Filename,Reason}}`
- `Reason = term()`

The `add/3` function adds a file to a tar file that has been opened for writing by `open/1` [page 127].

`dereference` By default, symbolic links will be stored as symbolic links in the tar file. Use the `dereference` option to override the default and store the file that the symbolic link points to into the tar file.

`verbose` Print an informational message about the file being added.

`add(TarDescriptor, Filename, NameInArchive, Options) -> RetValue`

Types:

- `TarDescriptor = term()`
- `Filename = filename()`
- `NameInArchive = filename()`
- `Options = [Option]`
- `Option = dereference|verbose`
- `RetValue = ok|{error,{Filename,Reason}}`
- `Reason = term()`

The `add/4` function adds a file to a tar file that has been opened for writing by `open/1` [page 127]. It accepts the same options as `add/3` [page 124].

`NameInArchive` is the name under which the file will be stored in the tar file. That is the name that the file will get when it will be extracted from the tar file.

`close(TarDescriptor)`

Types:

- `TarDescriptor = term()`

The `close/1` function closes a tar file opened by `open/1` [page 127].

`create(Name, FileList) ->RetValue`

Types:

- `Name = filename()`
- `FileList = [filename()]`
- `RetValue = ok|{error,{Name,Reason}}` <V>`Reason = term()`

The `create/2` function creates a tar file and archives the files whose names are given in `FileList` into it.

```
create(Name, FileList, OptionList)
```

Types:

- Name = filename()
- FileList = [filename()]
- OptionList = [Option]
- Option = compressed | cooked | dereference | verbose
- ReturnValue = ok | {error, {Name, Reason}} <V>Reason = term()

The `create/3` function creates a tar file and archives the files whose names are given in `FileList` into it.

The options in `OptionList` modify the defaults as follows.

`compressed` The entire tar file will be compressed, as if it has been run through the `gzip` program. To abide to the convention that a compressed tar file should end in `“.tar.gz”` or `“.tgz”`, you’ll need to add the appropriate extension yourself.

`cooked` By default, the `open/2` function will open the tar file in `raw` mode, which is faster but does not allow a remote (erlang) file server to be used. Adding `cooked` to the mode list will override the default and open the tar file without the `raw` option.

`dereference` By default, symbolic links will be stored as symbolic links in the tar file. Use the `dereference` option to override the default and store the file that the symbolic link points to into the tar file.

`verbose` Print an informational message about each file being added.

```
extract(Name) -> ReturnValue
```

Types:

- Name = filename()
- ReturnValue = ok | {error, {Name, Reason}}
- Reason = term()

The `extract/1` function extracts all files from a tar archive.

If the `Name` argument is given as `“{binary, Binary}”`, the contents of the binary is assumed to be a tar archive.

If the `Name` argument is given as `“{file, Fd}”`, `Fd` is assumed to be a file descriptor returned from the `file:open/2` function.

Otherwise, `Name` should be a filename.

```
extract(Name, OptionList)
```

Types:

- Name = filename() | {binary, Binary} | {file, Fd}
- Binary = binary()
- Fd = file\_descriptor()
- OptionList = [Option]
- Option = {cwd, Cwd} | {files, FileList} | keep\_old\_files | verbose
- Cwd = [dirname()]

- `FileList = [filename()]`
- `RetVal = ok | {error, {Name, Reason}}`
- `Reason = term()`

The `extract/2` function extracts files from a tar archive.

If the `Name` argument is given as `"{binary, Binary}"`, the contents of the binary is assumed to be a tar archive.

If the `Name` argument is given as `"{file, Fd}"`, `Fd` is assumed to be a file descriptor returned from the `file:open/2` function.

Otherwise, `Name` should be a filename.

The following options modify the defaults for the extraction as follows.

`{cwd, Cwd}` Files with relative filenames will by default be extracted to the current working directory. Given the `{cwd, Cwd}` option, the `extract/2` function will extract into the directory `Cwd` instead of to the current working directory.

`{files, FileList}` By default, all files will be extracted from the tar file. Given the `{files, Files}` option, the `extract/2` function will only extract the files whose names are included in `FileList`.

`compressed` Given the `compressed` option, the `extract/2` function will uncompress the file while extracting. If the tar file is not actually compressed, the `compressed` will effectively be ignored.

`cooked` By default, the `open/2` function will open the tar file in raw mode, which is faster but does not allow a remote (erlang) file server to be used. Adding `cooked` to the mode list will override the default and open the tar file without the raw option.

`keep_old_files` By default, all existing files with the same name as file in the tar file will be overwritten. Given the `keep_old_files` option, the `extract/2` function will not overwrite any existing files.

`verbose` Print an informational message as each file is being extracted.

`format_error(Reason) -> string()`

Types:

- `Reason = term()`

The `format_error/1` converts an error reason term to a human-readable error message string.

`open(Name, OpenModeList) -> RetValue`

Types:

- `Name = filename()`
- `OpenModeList = [OpenMode]`
- `Mode = read | write | compressed | cooked`
- `RetVal = {ok, TarDescriptor} | {error, {Name, Reason}}` <V> `TarDescriptor = term()`
- `Reason = term()`

The `open/2` function opens a tar file.

By convention, the name of a tar file should end in “.tar”. To abide to the convention, you’ll need to add “.tar” yourself to the name.

Note that there is currently no function for reading from an opened tar file, meaning that opening a tar file for reading is not very useful.

Except for `read` and `write` (which are mutually exclusive), the following atoms may be added to `OpenModeList`:

`compressed` The entire tar file will be compressed, as if it has been run through the `gzip` program. To abide to the convention that a compressed tar file should end in “.tar.gz” or “.tgz”, you’ll need to add the appropriate extension yourself.

`cooked` By default, the `open/2` function will open the tar file in `raw` mode, which is faster but does not allow a remote (erlang) file server to be used. Adding `cooked` to the mode list will override the default and open the tar file without the `raw` option.

Use the `add/3,4` [page 124] functions to add one file at the time into an opened tar file. When you are finished adding files, use the `close` [page 124] function to close the tar file.

### Warning:

The `TarDescriptor` term is not a file descriptor. You should not rely on the specific contents of the `TarDescriptor` term, as it may change in future versions as more features are added to the `erl_tar` module.

`table(Name) -> RetValue`

Types:

- `Name = filename()`
- `RetValue = {ok, [string()]} | {error, {Name, Reason}}`
- `Reason = term()`

The `table/1` function retrieves the names of all files in the tar file `Name`.

`table(Name, Options)`

Types:

- `Name = filename()`

The `table/2` function retrieves the names of all files in the tar file `Name`.

`t(Name)`

Types:

- `Name = filename()`

The `t/1` function prints the names of all files in the tar file `Name` to the Erlang shell. (Similar to “`tar`”.)

`tt(Name)`

Types:

- Name = filename()

The `tt/1` function prints names and information about all files in the tar file `Name` to the Erlang shell. (Similar to “`tar tv`”.)

# ets

## Erlang Module

This module is an interface to the Erlang built-in term storage BIFs. These provide the ability to store very large quantities of data in an Erlang runtime system, and to have constant access time to the data. (In the case of `ordered_set`, see below, access time is proportional to the logarithm of the number of objects stored).

Data is organized as a set of dynamic tables, which can store tuples. Each table is created by a process. When the process terminates, the table is automatically destroyed. Every table has access rights set at creation.

Tables are divided into four different types, `set`, `ordered_set`, `bag` and `duplicate_bag`. A `set` or `ordered_set` table can only have one object associated with each key. A `bag` or `duplicate_bag` can have many objects associated with each key.

The number of tables stored at one Erlang node is limited. The current default limit is approximately 1400 tables. The upper limit can be increased by setting the environment variable `ERL_MAX_ETS_TABLES` before starting the Erlang runtime system (i.e. with the `-env` option to `erl/werl`). The actual limit may be slightly higher than the one specified, but never lower.

Note that there is no automatic garbage collection for tables. Even if there are no references to a table from any process, it will not automatically be destroyed unless the owner process terminates. It can be destroyed explicitly by using `delete/1`.

Some implementation details:

- In the current implementation, every object insert and look-up operation results in one copy of the object.
- This module provides very limited support for concurrent updates. No locking is available, but the `safe_fixtable/2` function can be used to guarantee that a sequence of `first/1` and `next/2` calls will traverse the table without errors even if another process (or the same process) simultaneously deletes or inserts objects in the table.
- '`$end_of_table`' should not be used as a key since this atom is used to mark the end of the table when using `first/next`.

Also worth noting is the subtle difference between *matching* and *comparing equal*, which is demonstrated by the different table types `set` and `ordered_set`. Two Erlang terms *match* if they are of the same type and have the same value, so that `1` matches `1`, but not `1.0` (as `1.0` is a `float()` and not an `integer()`). Two Erlang terms *compare equal* if they either are of the same type and value, or if both are numeric types and extend to the same value, so that `1` compares equal to both `1` and `1.0`. The `ordered_set` works on the *Erlang term order* and there is no defined order between an `integer()` and a `float()` that extends to the same value, hence the key `1` and the key `1.0` are regarded as equal in an `ordered_set` table.

In general, the functions below will exit with reason `badarg` if any argument is of the wrong format, or if the table identifier is invalid.

## Match Specifications

Some of the functions uses a *match specification*, `match_spec`. A brief explanation is given in `select/2` [page 144]. For a detailed description, see the chapter “Match specifications in Erlang” in *ERTS User’s Guide*.

## DATA TYPES

`match_spec()`

a match specification, see above

`tid()`

a table identifier, as returned by `new/2`

## Exports

`all()` -> [Tab]

Types:

- Tab = tid() | atom()

Returns a list of all tables at the node. Named tables are given by their names, unnamed tables are given by their table identifiers.

`delete(Tab)` -> true

Types:

- Tab = tid() | atom()

Deletes the entire table Tab.

`delete(Tab, Key)` -> true

Types:

- Tab = tid() | atom()
- Key = term()

Deletes all objects with the key Key from the table Tab.

`delete_all_objects(Tab)` -> true

Types:

- Tab = tid() | atom()

Delete all objects in the ETS table Tab. The deletion is atomic.

`delete_object(Tab, Object)` -> true

Types:

- Tab = tid() | atom()
- Object = tuple()

Delete the exact object `Object` from the ETS table, leaving objects with the same key but other differences (useful for type bag).

```
file2tab(Filename) -> {ok,Tab} | {error,Reason}
```

Types:

- `Filename` = `string()` | `atom()`
- `Tab` = `tid()` | `atom()`
- `Reason` = `term()`

Reads a file produced by `tab2file/2` and creates the corresponding table `Tab`.

```
first(Tab) -> Key | '$end_of_table'
```

Types:

- `Tab` = `tid()` | `atom()`
- `Key` = `term()`

Returns the first key `Key` in the table `Tab`. If the table is of the `ordered_set` type, the first key in Erlang term order will be returned. If the table is of any other type, the first key according to the table's internal order will be returned. If the table is empty, `'$end_of_table'` will be returned.

Use `next/2` to find subsequent keys in the table.

```
fixtable(Tab, true|false) -> true | false
```

Types:

- `Tab` = `tid()` | `atom()`

**Warning:**

The function is retained for backwards compatibility only. Use `safe_fixtable/2` instead.

Fixes a table for safe traversal. The function is primarily used by the Mnesia DBMS to implement functions which allow write operations in a table, although the table is in the process of being copied to disk or to another node. It does not keep track of when and how tables are fixed.

```
foldl(Function, Acc0, Tab) -> Acc1
```

Types:

- `Function` = `fun(A, AccIn) -> AccOut`
- `Tab` = `tid()` | `atom()`
- `Acc0` = `Acc1` = `AccIn` = `AccOut` = `term()`

`Acc0` is returned if the table is empty. This function is similar to `lists:foldl/3`. The order in which the elements of the table are traversed is unspecified, except for tables of type `ordered_set`, for which they are traversed first to last.

```
foldr(Function, Acc0, Tab) -> Acc1
```

Types:

- Function = fun(A, AccIn) -> AccOut
- Tab = tid() | atom()
- Acc0 = Acc1 = AccIn = AccOut = term()

Acc0 is returned if the table is empty. This function is similar to `lists:foldr/3`. The order in which the elements of the table are traversed is unspecified, except for tables of type `ordered_set`, for which they are traversed last to first.

`from_dets(Tab, DetsTab) -> Tab`

Types:

- Tab = tid() | atom()
- DetsTab = atom()

Fills an already created ETS table with the objects in the already opened Dets table named `DetsTab`. The existing objects of the ETS table are kept unless overwritten.

`fun2ms(LiteralFun) -> MatchSpec`

Types:

- LiteralFun – see below
- MatchSpec = `match_spec()`

Pseudo function that by means of a `parse_transform` translates `LiteralFun` typed as parameter in the function call to a `match_spec` [page 130]. With “literal” is meant that the fun needs to textually be written as the parameter of the function, it cannot be held in a variable which in turn is passed to the function).

The parse transform is implemented in the module `ms_transform` and the source *must* include the file `ms_transform.hrl` in `stdlib` for this pseudo function to work. Failing to include the hrl file in the source will result in a runtime error, not a compile time ditto. The include file is easiest included by adding the line `-include_lib("stdlib/include/ms_transform.hrl").` to the source file.

The fun is very restricted, it can take only a single parameter (the object to match): a sole variable or a tuple. It needs to use the `is_XXX` guard tests. Language constructs that have no representation in a `match_spec` (like `if`, `case`, `receive` etc) are not allowed.

The return value is the resulting `match_spec`.

Example:

```
1> ets:fun2ms(fun({M,N}) when N > 3 -> M end).
[{{'$1', '$2'}, [{'>', '$2', 3}], ['$1']}
```

Variables from the environment can be imported, so that this works:

```
2> X=3.
3
3> ets:fun2ms(fun({M,N}) when N > X -> M end).
[{{'$1', '$2'}, [{'>', '$2', {const, 3}}, ['$1']}
```

The imported variables will be replaced by `match_spec` `const` expressions, which is consistent with the static scoping for Erlang funs. Local or global function calls can not be in the guard or body of the fun however. Calls to builtin `match_spec` functions of course is allowed:

```

4> ets:fun2ms(fun({M,N}) when N > X, is_atomm(M) -> M end).
Error: fun containing local Erlang function calls
('is_atomm' called in guard) cannot be translated into match_spec
{error,transform_error}
5> ets:fun2ms(fun({M,N}) when N > X, is_atom(M) -> M end).
[{{'$1','$2'},[{'>','$2',{const,3}},{is_atom,'$1'}]},{'$1'}]]

```

As can be seen by the example, the function can be called from the shell too. The fun needs to be literally in the call when used from the shell as well. Other means than the `parse_transform` are used in the shell case, but more or less the same restrictions apply (the exception being records, as they are not handled by the shell).

### Warning:

If the `parse_transform` is not applied to a module which calls this pseudo function, the call will fail in runtime (with a `badarg`). The module `ets` actually exports a function with this name, but it should never really be called except for when using the function in the shell. If the `parse_transform` is properly applied by including the `ms_transform.hrl` header file, compiled code will never call the function, but the function call is replaced by a literal `match_spec`.

For more information, see `ms_transform(3)` [page 240].

`i() -> void()`

Displays information about all ETS tables on tty.

`i(Tab) -> void()`

Types:

- `Tab = tid() | atom()`

Browses the table `Tab` on tty.

`info(Tab) -> [{Item, Value}] | undefined`

Types:

- `Tab = tid() | atom()`
- `Item = atom()`, see below
- `Value = term()`, see below

Returns information about the table `Tab` as a list of `{Item, Value}` tuples.

### Warning:

In Erlang/OTP R10B and earlier releases, this function erroneously returned a tuple. This has now been corrected.

- `Item=memory, Value=int()`  
The number of words allocated to the table.

- `Item=owner, Value=pid()`  
The pid of the owner of the table.
- `Item=name, Value=atom()`  
The name of the table.
- `Item=size, Value=int()`  
The number of objects inserted in the table.
- `Item=node, Value=atom()`  
The node where the table is stored. This field is no longer meaningful as tables cannot be accessed from other nodes.
- `Item=named_table, Value=true|false`  
Indicates if the table is named or not.
- `Item=type, Value=set|ordered_set|bag|duplicate_bag`  
The table type.
- `Item=keypos, Value=int()`  
The key position.
- `Item=protection, Value=public|protected|private`  
The table access rights.

`info(Tab, Item) -> Value | undefined`

Types:

- `Tab = tid() | atom()`
- `Item, Value` - see below

Returns the information associated with `Item` for the table `Tab`. In addition to the `{Item, Value}` pairs defined for `info/1`, the following items are allowed:

- `Item=fixed, Value=true|false`  
Indicates if the table is fixed by any process or not.
- `Item=safe_fixed, Value={FirstFixed, Info}|false`  
If the table has been fixed using `safe_fixtable/2`, the call returns a tuple where `FirstFixed` is the time when the table was first fixed by a process, which may or may not be one of the processes it is fixed by right now.  
`Info` is a possibly empty lists of tuples `{Pid, RefCount}`, one tuple for every process the table is fixed by right now. `RefCount` is the value of the reference counter, keeping track of how many times the table has been fixed by the process.  
If the table never has been fixed, the call returns `false`.

`init_table(Name, InitFun) -> true`

Types:

- `Name = atom()`
- `InitFun = fun(Arg) -> Res`
- `Arg = read | close`
- `Res = end_of_input | {[object()], InitFun} | term()`

Replaces the existing objects of the table `Tab` with objects created by calling the input function `InitFun`, see below. This function is provided for compatibility with the `dets` module, it is not more efficient than filling a table by using `ets:insert/2`.

When called with the argument `read` the function `InitFun` is assumed to return `end_of_input` when there is no more input, or `{Objects, Fun}`, where `Objects` is a list of objects and `Fun` is a new input function. Any other value `Value` is returned as an error `{error, {init_fun, Value}}`. Each input function will be called exactly once, and should an error occur, the last function is called with the argument `close`, the reply of which is ignored.

If the type of the table is `set` and there is more than one object with a given key, one of the objects is chosen. This is not necessarily the last object with the given key in the sequence of objects returned by the input functions. This holds also for duplicated objects stored in tables of type `duplicate_bag`.

```
insert(Tab, ObjectOrObjects) -> true
```

Types:

- `Tab = tid() | atom()`
- `ObjectOrObjects = tuple() | [tuple()]`

Inserts the object or all of the objects in the list `ObjectOrObjects` into the table `Tab`. If the table is a `set` and the key of the inserted objects *matches* the key of any object in the table, the old object will be replaced. If the table is an `ordered_set` and the key of the inserted object *compares equal* to the key of any object in the table, the old object is also replaced. If the list contains more than one object with *matching* keys and the table is a `set`, one will be inserted, which one is not defined. The same thing holds for `ordered_set`, but will also happen if the keys *compare equal*.

```
insert_new(Tab, ObjectOrObjects) -> bool()
```

Types:

- `Tab = tid() | atom()`
- `ObjectOrObjects = tuple() | [tuple()]`

This function works exactly like `insert/2`, with the exception that instead of overwriting objects with the same key (in the case of `set` or `ordered_set`) or adding more objects with keys already existing in the table (in the case of `bag` and `duplicate_bag`), it simply returns `false`. If `ObjectOrObjects` is a list, the function checks *every* key prior to inserting anything. Nothing will be inserted if not *all* keys present in the list are absent from the table.

```
is_compiled_ms(Term) -> bool()
```

Types:

- `Term = term()`

This function is used to check if a term is a valid compiled `match_spec` [page 130]. The compiled `match_spec` is an opaque datatype which can *not* be sent between Erlang nodes nor be stored on disk. Any attempt to create an external representation of a compiled `match_spec` will result in an empty binary (`<<<>>`). As an example, the following expression:

```
ets:is_compiled_ms(ets:match_spec_compile(['_', [], [true]]))
```

will yield `true`, while the following expressions:

```
MS = ets:match_spec_compile(['_', [], [true]]),
Broken = binary_to_term(term_to_binary(MS)),
ets:is_compiled_ms(Broken).
```

will yield false, as the variable `Broken` will contain a compiled `match_spec` that has passed through external representation.

**Note:**

The fact that compiled `match_specs` has no external representation is for performance reasons. It may be subject to change in future releases, while this interface will still remain for backward compatibility reasons.

```
last(Tab) -> Key | '$end_of_table'
```

Types:

- Tab = tid() | atom()
- Key = term()

Returns the last key `Key` according to Erlang term order in the table `Tab` of the `ordered_set` type. If the table is of any other type, the function is synonymous to `first/2`. If the table is empty, `'$end_of_table'` is returned.

Use `prev/2` to find preceding keys in the table.

```
lookup(Tab, Key) -> [Object]
```

Types:

- Tab = tid() | atom()
- Key = term()
- Object = tuple()

Returns a list of all objects with the key `Key` in the table `Tab`.

In the case of `set`, `bag` and `duplicate_bag`, an object is returned only if the given key *matches* the key of the object in the table. If the table is an `ordered_set` however, an object is returned if the key given *compares equal* to the key of an object in the table. The difference being the same as between `:=` and `==`. As an example, one might insert an object with the `integer()` 1 as a key in an `ordered_set` and get the object returned as a result of doing a `lookup/2` with the `float()` 1.0 as the key to search for.

If the table is of type `set` or `ordered_set`, the function returns either the empty list or a list with one element, as there cannot be more than one object with the same key. If the table is of type `bag` or `duplicate_bag`, the function returns a list of arbitrary length.

Note that the time order of object insertions is preserved; The first object inserted with the given key will be first in the resulting list, and so on.

Insert and look-up times in tables of type `set`, `bag` and `duplicate_bag` are constant, regardless of the size of the table. For the `ordered_set` data-type, time is proportional to the (binary) logarithm of the number of objects.

```
lookup_element(Tab, Key, Pos) -> Elem
```

Types:

- Tab = tid() | atom()
- Key = term()
- Pos = int()
- Elem = term() | [term()]

If the table Tab is of type `set` or `ordered_set`, the function returns the Pos:th element of the object with the key Key.

If the table is of type `bag` or `duplicate_bag`, the functions returns a list with the Pos:th element of every object with the key Key.

If no object with the key Key exists, the function will exit with reason `badarg`.

The difference between `set`, `bag` and `duplicate_bag` on one hand, and `ordered_set` on the other, regarding the fact that `ordered_set`'s view keys as equal when they *compare equal* whereas the other table types only regard them equal when they *match*, naturally holds for `lookup_element` as well as for `lookup`.

```
match(Tab, Pattern) -> [Match]
```

Types:

- Tab = tid() | atom()
- Pattern = tuple()
- Match = [term()]

Matches the objects in the table Tab against the pattern Pattern.

A pattern is a term that may contain:

- bound parts (Erlang terms),
- `'_'` which matches any Erlang term, and
- pattern variables: `'$N'` where N=0,1,...

The function returns a list with one element for each matching object, where each element is an ordered list of pattern variable bindings. An example:

```
6> ets:match(T, '$1'). % Matches every object in the table
[[{rufsen,dog,7}], [{brunte,horse,5}], [{ludde,dog,5}]]
7> ets:match(T, {'_',dog,'$1'}).
[[7], [5]]
8> ets:match(T, {'_',cow,'$1'}).
[]
```

If the key is specified in the pattern, the match is very efficient. If the key is not specified, i.e. if it is a variable or an underscore, the entire table must be searched. The search time can be substantial if the table is very large.

On tables of the `ordered_set` type, the result is in the same order as in a `first/next` traversal.

```
match(Tab, Pattern, Limit) -> {[Match],Continuation} | '$end_of_table'
```

Types:

- Tab = tid() | atom()
- Pattern = tuple()
- Match = [term()]

- Continuation = term()

Works like `ets:match/2` but only returns a limited (`Limit`) number of matching objects. The `Continuation` term can then be used in subsequent calls to `ets:match/1` to get the next chunk of matching objects. This is a space efficient way to work on objects in a table which is still faster than traversing the table object by object using `ets:first/1` and `ets:next/1`.

'\$end\_of\_table' is returned if the table is empty.

```
match(Continuation) -> {[Match],Continuation} | '$end_of_table'
```

Types:

- Match = [term()]
- Continuation = term()

Continues a match started with `ets:match/3`. The next chunk of the size given in the initial `ets:match/3` call is returned together with a new `Continuation` that can be used in subsequent calls to this function.

'\$end\_of\_table' is returned when there are no more objects in the table.

```
match_delete(Tab, Pattern) -> true
```

Types:

- Tab = tid() | atom()
- Pattern = tuple()

Deletes all objects which match the pattern `Pattern` from the table `Tab`. See `match/2` for a description of patterns.

```
match_object(Tab, Pattern) -> [Object]
```

Types:

- Tab = tid() | atom()
- Pattern = Object = tuple()

Matches the objects in the table `Tab` against the pattern `Pattern`. See `match/2` for a description of patterns. The function returns a list of all objects which match the pattern.

If the key is specified in the pattern, the match is very efficient. If the key is not specified, i.e. if it is a variable or an underscore, the entire table must be searched. The search time can be substantial if the table is very large.

On tables of the `ordered_set` type, the result is in the same order as in a `first/next` traversal.

```
match_object(Tab, Pattern, Limit) -> {[Match],Continuation} | '$end_of_table'
```

Types:

- Tab = tid() | atom()
- Pattern = tuple()
- Match = [term()]
- Continuation = term()

Works like `ets:match_object/2` but only returns a limited (`Limit`) number of matching objects. The `Continuation` term can then be used in subsequent calls to `ets:match_object/1` to get the next chunk of matching objects. This is a space efficient way to work on objects in a table which is still faster than traversing the table object by object using `ets:first/1` and `ets:next/1`.

'\$end\_of\_table' is returned if the table is empty.

```
match_object(Continuation) -> {[Match],Continuation} | '$end_of_table'
```

Types:

- `Match = [term()]`
- `Continuation = term()`

Continues a match started with `ets:match_object/3`. The next chunk of the size given in the initial `ets:match_object/3` call is returned together with a new `Continuation` that can be used in subsequent calls to this function.

'\$end\_of\_table' is returned when there are no more objects in the table.

```
match_spec_compile(MatchSpec) -> CompiledMatchSpec
```

Types:

- `MatchSpec = match_spec()`
- `CompiledMatchSpec = comp_match_spec()`

This function transforms a `match_spec` [page 130] into an internal representation that can be used in subsequent calls to `ets:match_spec_run/2`. The internal representation is opaque and can not be converted to external term format and then back again without losing its properties (meaning it can not be sent to a process on another node and still remain a valid compiled `match_spec`, nor can it be stored on disk). The validity of a compiled `match_spec` can be checked using `ets:is_compiled_ms/1`.

If the term `MatchSpec` can not be compiled (does not represent a valid `match_spec`), a `badarg` fault is thrown.

### Note:

This function has limited use in normal code, it is used by `Dets` to perform the `dets:select` operations.

```
match_spec_run(List,CompiledMatchSpec) -> list()
```

Types:

- `List = [ tuple() ]`
- `CompiledMatchSpec = comp_match_spec()`

This function executes the matching specified in a compiled `match_spec` [page 130] on a list of tuples. The `CompiledMatchSpec` term should be the result of a call to `ets:match_spec_compile/1` and is hence the internal representation of the `match_spec` one wants to use.

The matching will be executed on each element in `List` and the function returns a list containing all results. If an element in `List` does not match, nothing is returned for that element. The length of the result list is therefore equal or less than the length of the parameter `List`. The two calls in the following example will give the same result (but certainly not the same execution time...):

```
Table = ets:new...
MatchSpec = ....
% The following call...
ets:match_spec_run(ets:tab2list(Table),
ets:match_spec_compile(MatchSpec)),
% ...will give the same result as the more common (and more efficient)
ets:select(Table,MatchSpec),
```

### Note:

This function has limited use in normal code, it is used by Dets to perform the `dets:select` operations and by Mnesia during transactions.

`member(Tab, Key) -> true | false`

Types:

- `Tab = tid() | atom()`
- `Key = term()`

Works like `lookup/2`, but does not return the objects. The function returns `true` if one or more elements in the table has the key `Key`, `false` otherwise.

`new(Name, Options) -> tid()`

Types:

- `Name = atom()`
- `Options = [Option]`
- `Option = Type | Access | named_table | {keypos,Pos}`
- `Type = set | ordered_set | bag | duplicate_bag`
- `Access = public | protected | private`
- `Pos = int()`

Creates a new table and returns a table identifier which can be used in subsequent operations. The table identifier can be sent to other processes so that a table can be shared between different processes within a node.

The parameter `Options` is a list of atoms which specifies table type, access rights, key position and if the table is named or not. If one or more options are left out, the default values are used. This means that not specifying any options (`[]`) is the same as specifying `[set,protected,{keypos,1}]`.

- `set` The table is a `set` table - one key, one object, no order among objects. This is the default table type.
- `ordered_set` The table is a `ordered_set` table - one key, one object, ordered in Erlang term order, which is the order implied by the `<` and `>` operators. Tables of this type have a somewhat different behavior in some situations than tables of the other types. Most notably the `ordered_set` tables regard keys as equal when they *compare equal*, not only when they match. This means that to an `ordered_set`, the `integer() 1` and the `float() 1.0` are regarded as equal. This also means that the key used to lookup an element not necessarily *matches* the key in the elements returned, if `float()`'s and `integer()`'s are mixed in keys of a table.
- `bag` The table is a `bag` table which can have many objects, but only one instance of each object, per key.
- `duplicate_bag` The table is a `duplicate_bag` table which can have many objects, including multiple copies of the same object, per key.
- `public` Any process may read or write to the table.
- `protected` The owner process can read and write to the table. Other processes can only read the table. This is the default setting for the access rights.
- `private` Only the owner process can read or write to the table.
- `named_table` If this option is present, the name `Name` is associated with the table identifier. The name can then be used instead of the table identifier in subsequent operations.
- `{keypos, Pos}` Specifies which element in the stored tuples should be used as key. By default, it is the first element, i.e. `Pos=1`. However, this is not always appropriate. In particular, we do not want the first element to be the key if we want to store Erlang records in a table.  
Note that any tuple stored in the table must have at least `Pos` number of elements.

```
next(Tab, Key1) -> Key2 | '$end_of_table'
```

Types:

- `Tab = tid() | atom()`
- `Key1 = Key2 = term()`

Returns the next key `Key2`, following the key `Key1` in the table `Tab`. If the table is of the `ordered_set` type, the next key in Erlang term order is returned. If the table is of any other type, the next key according to the table's internal order is returned. If there is no next key, `'$end_of_table'` is returned.

Use `first/1` to find the first key in the table.

Unless a table of type `set`, `bag` or `duplicate_bag` is protected using `safe_fixtable/2`, see below, a traversal may fail if concurrent updates are made to the table. If the table is of type `ordered_set`, the function returns the next key in order, even if the object does no longer exist.

```
prev(Tab, Key1) -> Key2 | '$end_of_table'
```

Types:

- `Tab = tid() | atom()`
- `Key1 = Key2 = term()`

Returns the previous key `Key2`, preceding the key `Key1` according the Erlang term order in the table `Tab` of the `ordered_set` type. If the table is of any other type, the function is synonymous to `next/2`. If there is no previous key, `'$end_of_table'` is returned.

Use `last/1` to find the last key in the table.

```
rename(Tab, Name) -> Name
```

Types:

- `Tab = Name = atom()`

Renames the named table `Tab` to the new name `Name`. Afterwards, the old name can not be used to access the table. Renaming an unnamed table has no effect.

```
repair_continuation(Continuation, MatchSpec) -> Continuation
```

Types:

- `Continuation = term()`
- `MatchSpec = match_spec()`

This function can be used to restore an opaque continuation returned by `ets:select/3` or `ets:select/1` if the continuation has passed through external term format (been sent between nodes or stored on disk).

The reason for this function is that continuation terms contain compiled `match_specs` and therefore will be invalidated if converted to external term format. Given that the original `match_spec` is kept intact, the continuation can be restored, meaning it can once again be used in subsequent `ets:select/1` calls even though it has been stored on disk or on another node.

As an example, the following sequence of calls will fail:

```
T=ets:new(x, []),
...
{_,C} = ets:select(T,ets:fun2ms(fun({N,_}=A)
when (N rem 10) == 0 ->
A
end),10),
Broken = binary_to_term(term_to_binary(C)),
ets:select(Broken).
```

...while the following sequence will work:

```
T=ets:new(x, []),
...
MS = ets:fun2ms(fun({N,_}=A)
when (N rem 10) == 0 ->
A
end),
{_,C} = ets:select(T,MS,10),
Broken = binary_to_term(term_to_binary(C)),
ets:select(ets:repair_continuation(Broken,MS)).
```

...as the call to `ets:repair_continuation/2` will reestablish the (deliberately) invalidated continuation `Broken`.

**Note:**

This function is very rarely needed in application code. It is used by Mnesia to implement distributed `select/3` and `select/1` sequences. A normal application would either use Mnesia or keep the continuation from being converted to external format.

The reason for not having an external representation of a compiled `match_spec` is performance. It may be subject to change in future releases, while this interface will remain for backward compatibility.

```
safe_fixtable(Tab, true|false) -> true
```

Types:

- Tab = `tid()` | `atom()`

Fixes a table of the `set`, `bag` or `duplicate_bag` table type for safe traversal.

A process fixes a table by calling `safe_fixtable(Tab,true)`. The table remains fixed until the process releases it by calling `safe_fixtable(Tab,false)`, or until the process terminates.

If several processes fix a table, the table will remain fixed until all processes have released it (or terminated). A reference counter is kept on a per process basis, and N consecutive fixes requires N releases to actually release the table.

When a table is fixed, a sequence of `first/1` and `next/2` calls are guaranteed to succeed even if objects are removed during the traversal. An example:

```
clean_all_with_value(Tab,X) ->
  safe_fixtable(Tab,true),
  clean_all_with_value(Tab,X,ets:first(Tab)),
  safe_fixtable(Tab,false).

clean_all_with_value(Tab,X,'$end_of_table') ->
  true;
clean_all_with_value(Tab,X,Key) ->
  case ets:lookup(Tab,Key) of
    [{Key,X}] ->
      ets:delete(Tab,Key);
    _ ->
      true
  end,
  clean_all_with_value(Tab,X,ets:next(Tab,Key)).
```

Note that no deleted objects are actually removed from a fixed table until it has been released. If a process fixes a table but never releases it, the memory used by the deleted objects will never be freed. The performance of operations on the table will also degrade significantly.

Use `info/2` to retrieve information about which processes have fixed which tables. A system with a lot of processes fixing tables may need a monitor which sends alarms when tables have been fixed for too long.

Note that for tables of the `ordered_set` type, `safe_fixtable/2` is not necessary as calls to `first/1` and `next/2` will always succeed.

```
select(Tab, MatchSpec) -> [Match]
```

Types:

- `Tab = tid() | atom()`
- `Match = term()`
- `MatchSpec = match_spec()`

Matches the objects in the table `Tab` using a `match_spec` [page 130]. This is a more general call than the `ets:match/2` and `ets:match_object/2` calls. In its simplest forms the `match_specs` look like this:

- `MatchSpec = [MatchFunction]`
- `MatchFunction = {MatchHead, [Guard], [Result]}`
- `MatchHead = "Pattern as in ets:match"`
- `Guard = {"Guardtest name", ...}`
- `Result = "Term construct"`

This means that the `match_spec` is always a list of one or more tuples (of arity 3). The tuples first element should be a pattern as described in the documentation of `ets:match/2`. The second element of the tuple should be a list of 0 or more guard tests (described below). The third element of the tuple should be a list containing a description of the value to actually return. In almost all normal cases the list contains exactly one term which fully describes the value to return for each object.

The return value is constructed using the "match variables" bound in the `MatchHead` or using the special match variables `'$_'` (the whole matching object) and `'$$'` (all match variables in a list), so that the following `ets:match/2` expression:

```
ets:match(Tab, {'$1', '$2', '$3'})
```

is exactly equivalent to:

```
ets:select(Tab, [{{'$1', '$2', '$3'}, [], ['$$']})
```

- and the following `ets:match_object/2` call:

```
ets:match_object(Tab, {'$1', '$2', '$1'})
```

is exactly equivalent to

```
ets:select(Tab, [{{'$1', '$2', '$1'}, [], ['$_']})
```

Composite terms can be constructed in the `Result` part either by simply writing a list, so that this code:

```
ets:select(Tab, [{{'$1', '$2', '$3'}, [], ['$$']})
```

gives the same output as:

```
ets:select(Tab, [{{'$1', '$2', '$3'}, [], [['$1', '$2', '$3']]])
```

i.e. all the bound variables in the match head as a list. If tuples are to be constructed, one has to write a tuple of arity 1 with the single element in the tuple being the tuple one wants to construct (as an ordinary tuple could be mistaken for a `Guard`). Therefore the following call:

```
ets:select(Tab, [{{'$1', '$2', '$1'}, [], ['$_']})
```

gives the same output as:

```
ets:select(Tab, [{{'$1', '$2', '$1'}, [], [{{'$1', '$2', '$3'}]}])
```

- this syntax is equivalent to the syntax used in the trace patterns (see [dbg(3)]).

The Guards are constructed as tuples where the first element is the name of the test and the rest of the elements are the parameters of the test. To check for a specific type (say a list) of the element bound to the match variable '\$1', one would write the test as {is\_list, '\$1'}. If the test fails, the object in the table will not match and the next MatchFunction (if any) will be tried. Most guard tests present in Erlang can be used, but only the new versions prefixed is\_ are allowed (like is\_float, is\_atom etc).

The Guard section can also contain logic and arithmetic operations, which are written with the same syntax as the guard tests (prefix notation), so that a guard test written in Erlang looking like this:

```
is_integer(X), is_integer(Y), X + Y < 4711
```

is expressed like this (X replaced with '\$1' and Y with '\$2'):

```
{[is_integer, '$1'], [is_integer, '$2'], {'<', {'+', '$1', '$2'}, 4711]}
```

```
select(Tab, MatchSpec, Limit) -> {[Match], Continuation} | '$end_of_table'
```

Types:

- Tab = tid() | atom()
- Match = term()
- MatchSpec = match\_spec()
- Continuation = term()

Works like ets:select/2 but only returns a limited (Limit) number of matching objects. The Continuation term can then be used in subsequent calls to ets:select/1 to get the next chunk of matching objects. This is a space efficient way to work on objects in a table which is still faster than traversing the table object by object using ets:first/1 and ets:next/1.

'\$end\_of\_table' is returned if the table is empty.

```
select(Continuation) -> {[Match], Continuation} | '$end_of_table'
```

Types:

- Match = term()
- Continuation = term()

Continues a match started with ets:select/3. The next chunk of the size given in the initial ets:select/3 call is returned together with a new Continuation that can be used in subsequent calls to this function.

'\$end\_of\_table' is returned when there are no more objects in the table.

```
select_delete(Tab, MatchSpec) -> NumDeleted
```

Types:

- Tab = tid() | atom()
- Object = tuple()
- MatchSpec = match\_spec()
- NumDeleted = integer()

Matches the objects in the table `Tab` using a `match_spec` [page 130]. If the `match_spec` returns `true` for an object, that object is removed from the table. For any other result from the `match_spec` the object is retained. This is a more general call than the `ets:match_delete/2` call.

The function returns the number of objects actually deleted from the table.

**Note:**

The `match_spec` has to return the atom `true` if the object is to be deleted. No other return value will get the object deleted, why one can not use the same match specification for looking up elements as for deleting them.

`select_count(Tab, MatchSpec) -> NumMatched`

Types:

- `Tab = tid() | atom()`
- `Object = tuple()`
- `MatchSpec = match_spec()`
- `NumMatched = integer()`

Matches the objects in the table `Tab` using a `match_spec` [page 130]. If the `match_spec` returns `true` for an object, that object considered a match and is counted. For any other result from the `match_spec` the object is not considered a match and is therefore not counted.

The function could be described as a `match_delete/2` that does not actually delete any elements, but only counts them.

The function returns the number of objects matched.

`slot(Tab, I) -> [Object] | '$end_of_table'`

Types:

- `Tab = tid() | atom()`
- `I = int()`
- `Object = tuple()`

This function is mostly for debugging purposes, Normally one should use `first/next` or `last/prev` instead.

Returns all objects in the `I`:th slot of the table `Tab`. A table can be traversed by repeatedly calling the function, starting with the first slot `I=0` and ending when `'$end_of_table'` is returned. The function will fail with reason `badarg` if the `I` argument is out of range.

Unless a table of type `set`, `bag` or `duplicate_bag` is protected using `safe_fixtable/2`, see above, a traversal may fail if concurrent updates are made to the table. If the table is of type `ordered_set`, the function returns a list containing the `I`:th object in Erlang term order.

`tab2file(Tab, Filename) -> ok | {error,Reason}`

Types:

- `Tab = tid() | atom()`
- `Filename = string() | atom()`
- `Reason = term()`

Dumps the table `Tab` to the file `Filename`. The implementation of this function is not efficient.

`tab2list(Tab) -> [Object]`

Types:

- `Tab = tid() | atom()`
- `Object = tuple()`

Returns a list of all objects in the table `Tab`.

`table(Tab [, Options]) -> QueryHandle`

Types:

- `Tab = tid() | atom()`
- `QueryHandle = -a query handle, see qlc(3)-`
- `Options = [Option] | Option`
- `Option = {n_objects, NObjects} | {traverse, TraverseMethod}`
- `NObjects = default | integer() > 0`
- `TraverseMethod = first_next | last_prev | select | {select, MatchSpec}`
- `MatchSpec = match_spec()`

Returns a QLC (Query List Comprehension) query handle. The module `qlc` implements a query language aimed mainly at Mnesia but ETS tables, Dets tables, and lists are also recognized by QLC as sources of data. Calling `ets:table/1,2` is the means to make the ETS table `Tab` usable to QLC.

When there are only simple restrictions on the key position QLC uses `ets:lookup/2` to look up the keys, but when that is not possible the whole table is traversed. The option `traverse` determines how this is done:

- `first_next`. The table is traversed one key at a time by calling `ets:first/1` and `ets:next/2`.
- `last_prev`. The table is traversed one key at a time by calling `ets:last/1` and `ets:prev/2`.
- `select`. The table is traversed by calling `ets:select/3` and `ets:select/1`. The option `n_objects` determines the number of objects returned (the third argument of `select/3`); the default is to return 100 objects at a time. The `match_spec` [page 130] (the second argument of `select/3`) is assembled by QLC: simple filters are translated into equivalent `match_specs` while more complicated filters have to be applied to all objects returned by `select/3` given a `match_spec` that matches all objects.
- `{select, MatchSpec}`. As for `select` the table is traversed by calling `ets:select/3` and `ets:select/1`. The difference is that the `match_spec` is explicitly given. This is how to state `match_specs` that cannot easily be expressed within the syntax provided by QLC.

The following example uses an explicit `match_spec` to traverse the table:

```
9> ets:insert(Tab = ets:new(t, []), [{1,a},{2,b},{3,c},{4,d}],
MS = ets:fun2ms(fun({X,Y}) when (X > 1) or (X < 5) -> {Y} end),
QH1 = ets:table(Tab, [{traverse, {select, MS}}])).
```

An example with implicit `match_spec`:

```
10> QH2 = qlc:q([{Y} || {X,Y} <- ets:table(Tab), (X > 1) or (X < 5)]).
```

The latter example is in fact equivalent to the former which can be verified using the function `qlc:info/1`:

```
11> qlc:info(QH1) == qlc:info(QH2).
true
```

`qlc:info/1` returns information about a query handle, and in this case identical information is returned for the two query handles.

```
test_ms(Tuple, MatchSpec) -> {ok, Result} | {error, Errors}
```

Types:

- Tuple = tuple()
- MatchSpec = match\_spec()
- Result = term()
- Errors = [{warning|error, string()}]

This function is a utility to test a `match_spec` [page 130] used in calls to `ets:select/2`. The function both tests `MatchSpec` for “syntactic” correctness and runs the `match_spec` against the object `Tuple`. If the `match_spec` contains errors, the tuple `{error, Errors}` is returned where `Errors` is a list of natural language descriptions of what was wrong with the `match_spec`. If the `match_spec` is syntactically OK, the function returns `{ok, Term}` where `Term` is what would have been the result in a real `ets:select/2` call or `false` if the `match_spec` does not match the object `Tuple`.

This is a useful debugging and test tool, especially when writing complicated `ets:select/2` calls.

```
to_dets(Tab, DetsTab) -> Tab
```

Types:

- Tab = tid() | atom()
- DetsTab = atom()

Fills an already created/opened Dets table with the objects in the already opened ETS table named `Tab`. The Dets table is emptied before the objects are inserted.

```
update_counter(Tab, Key, {Pos,Incr,Threshold,SetValue}) -> Result
```

```
update_counter(Tab, Key, {Pos,Incr}) -> Result
```

```
update_counter(Tab, Key, Incr) -> Result
```

Types:

- Tab = tid() | atom()
- Key = term()
- Pos = Incr = Threshold = SetValue = Result = int()

This function provides an efficient way to update a counter, without the hassle of having to look up an object, update the object by incrementing an element and insert the resulting object into the table again. (The update is done atomically; i.e. no process can access the ets table in the middle of the operation.)

It will destructively update the object with key `Key` in the table `Tab` by adding `Incr` to the element at the `Pos:th` position. The new counter value is returned. If no position is specified, the element directly following the key (`<keypos>+1`) is updated.

If a `Threshold` is specified, the counter will be reset to the value `SetValue` if the following conditions occur:

- The `Incr` is not negative ( $\geq 0$ ) and the result would be greater than ( $>$ ) `Threshold`
- The `Incr` is negative ( $< 0$ ) and the result would be less than ( $<$ ) `Threshold`

The given `Key` is used to identify the object by either *matching* the key of an object in a `set` table, or *compare equal* to the key of an object in an `ordered_set` table (see `lookup/2` [page 136] and `new/2` [page 140] for details on the difference).

The function will fail with reason `badarg` if:

- the table is not of type `set` or `ordered_set`,
- no object with the right key exists,
- the object has the wrong arity,
- the element to update is not an integer,
- the element to update is also the key, or,
- any of `Pos`, `Incr`, `Threshold` or `SetValue` is not an integer

# file\_sorter

Erlang Module

The functions of this module sort terms on files, merge already sorted files, and check files for sortedness. Chunks containing binary terms are read from a sequence of files, sorted internally in memory and written on temporary files, which are merged producing one sorted file as output. Merging is provided as an optimization; it is faster when the files are already sorted, but it always works to sort instead of merge.

On a file, a term is represented by a header and a binary. Two options define the format of terms on files:

- `{header, HeaderLength}`. `HeaderLength` determines the number of bytes preceding each binary and containing the length of the binary in bytes. Default is 4. The order of the header bytes is defined as follows: if `B` is a binary containing a header only, the size `Size` of the binary is calculated as `<<Size:HeaderLength/unit:8>> = B`.
- `{format, Format}`. The format determines the function that is applied to binaries in order to create the terms that will be sorted. The default value is `binary_term`, which is equivalent to `funbinary_to_term/1`. The value `binary` is equivalent to `fun(X) -> X end`, which means that the binaries will be sorted as they are. This is the fastest format. If `Format` is `term`, `io:read/2` is called to read terms. In that case only the default value of the `header` option is allowed. The `format` option also determines what is written to the sorted output file: if `Format` is `term` then `io:format/3` is called to write each term, otherwise the binary prefixed by a header is written. Note that the binary written is the same binary that was read; the results of applying the `Format` function are thrown away as soon as the terms have been sorted. Reading and writing terms using the `io` module is very much slower than reading and writing binaries.

Other options are:

- `{order, Order}`. The default is to sort terms in ascending order, but that can be changed by the value `descending` or by giving an ordering function `Fun`. `Fun(A,B)` should return `true` if `A` comes before `B` in the ordering, `false` otherwise. Using an ordering function will slow down the sort considerably. The `keysort`, `keymerge` and `keycheck` functions do not accept ordering functions.
- `{unique, bool()}`. When sorting or merging files, only the first of a sequence of terms that compare equal is output if this option is set to `true`. The default value is `false` which implies that all terms that compare equal are output. When checking files for sortedness, a check that no pair of consecutive terms compares equal is done if this option is set to `true`.

- `{tmpdir, TempDirectory}`. The directory where temporary files are put can be chosen explicitly. The default, implied by the value `"`, is to put temporary files on the same directory as the sorted output file. If output is a function (see below), the directory returned by `file:get_cwd()` is used instead. The names of temporary files are derived from the Erlang nodename (`node()`), the process identifier of the current Erlang emulator (`os:getpid()`), and a timestamp (`erlang:now()`); a typical name would be `fs_mynode@myhost_1763_1043_337000_266005.17`, where 17 is a sequence number. Existing files will be overwritten. Temporary files are deleted unless some uncaught EXIT signal occurs.
- `{compressed, bool()}`. Temporary files and the output file may be compressed. The default value `false` implies that written files are not compressed. Regardless of the value of the `compressed` option, compressed files can always be read. Note that reading and writing compressed files is significantly slower than reading and writing uncompressed files.
- `{size, Size}`. By default approximately 512\*1024 bytes read from files are sorted internally. This option should rarely be needed.
- `{no_files, NoFiles}`. By default 16 files are merged at a time. This option should rarely be needed.

To summarize, here is the syntax of the options:

- `Options = [Option] | Option`
- `Option = {header, HeaderLength} | {format, Format} | {order, Order} | {unique, bool()} | {tmpdir, TempDirectory} | {compressed, bool()} | {size, Size} | {no_files, NoFiles}`
- `HeaderLength = int() > 0`
- `Format = binary_term | term | binary | FormatFun`
- `FormatFun = fun(Binary) -> Term`
- `Order = ascending | descending | OrderFun`
- `OrderFun = fun(Term, Term) -> bool()`
- `TempDirectory = "" | file_name()`
- `Size = int() >= 0`
- `NoFiles = int() > 1`

As an alternative to sorting files, a function of one argument can be given as input. When called with the argument `read` the function is assumed to return `end_of_input` or `{end_of_input, Value}` when there is no more input (`Value` is explained below), or `{Objects, Fun}`, where `Objects` is a list of binaries or terms depending on the format and `Fun` is a new input function. Any other value is immediately returned as value of the current call to `sort` or `keysort`. Each input function will be called exactly once, and should an error occur, the last function is called with the argument `close`, the reply of which is ignored.

A function of one argument can be given as output. The results of sorting or merging the input is collected in a non-empty sequence of variable length lists of binaries or terms depending on the format. The output function is called with one list at a time, and is assumed to return a new output function. Any other return value is immediately returned as value of the current call to the `sort` or `merge` function. Each output function is called exactly once. When some output function has been applied to all of the results or an error occurs, the last function is called with the argument `close`, and the reply is

returned as value of the current call to the sort or merge function. If a function is given as input and the last input function returns `{end_of_input, Value}`, the function given as output will be called with the argument `{value, Value}`. This makes it easy to initiate the sequence of output functions with a value calculated by the input functions.

As an example, consider sorting the terms on a disk log file. A function that reads chunks from the disk log and returns a list of binaries is used as input. The results are collected in a list of terms.

```
sort(Log) ->
  {ok, _} = disk_log:open([name,Log], {mode,read_only}),
  Input = input(Log, start),
  Output = output([]),
  Reply = file_sorter:sort(Input, Output, {format,term}),
  ok = disk_log:close(Log),
  Reply.
```

```
input(Log, Cont) ->
  fun(close) ->
    ok;
    (read) ->
      case disk_log:chunk(Log, Cont) of
        {error, Reason} ->
          {error, Reason};
        {Cont2, Terms} ->
          {Terms, input(Log, Cont2)};
        {Cont2, Terms, _Badbytes} ->
          {Terms, input(Log, Cont2)};
        eof ->
          end_of_input
      end
    end.
```

```
output(L) ->
  fun(close) ->
    lists:append(lists:reverse(L));
    (Terms) ->
      output([Terms | L])
    end.
```

Further examples of functions as input and output can be found at the end of the `file_sorter` module; the `term` format is implemented with functions.

The possible values of `Reason` returned when an error occurs are:

- `bad_object`, `{bad_object, FileName}`. Applying the format function failed for some binary, or the key(s) could not be extracted from some term.
- `{bad_term, FileName}`. `io:read/2` failed to read some term.
- `{file_error, FileName, Reason2}`. See `file(3)` for an explanation of `Reason2`.
- `{premature_eof, FileName}`. End-of-file was encountered inside some binary term.

### Types

```

Binary = binary()
FileName = file_name()
FileNames = [FileName]
ICommand = read | close
IReply = end_of_input | {end_of_input, Value} | {[Object], Infun} | InputReply
Infun = fun(ICommand) -> IReply
Input = FileNames | Infun
InputReply = Term
KeyPos = int() > 0 | [int() > 0]
OCommand = {value, Value} | [Object] | close
OReply = Outfun | OutputReply
Object = Term | Binary
Outfun = fun(OCommand) -> OReply
Output = FileName | Outfun
OutputReply = Term
Term = term()
Value = Term

```

## Exports

```

sort(FileName) -> Reply
sort(Input, Output) -> Reply
sort(Input, Output, Options) -> Reply

```

Types:

- Reply = ok | {error, Reason} | InputReply | OutputReply

Sorts terms on files.

sort(FileName) is equivalent to sort([FileName], FileName).

sort(Input, Output) is equivalent to sort(Input, Output, []).

```

keysort(KeyPos, FileName) -> Reply
keysort(KeyPos, Input, Output) -> Reply
keysort(KeyPos, Input, Output, Options) -> Reply

```

Types:

- Reply = ok | {error, Reason} | InputReply | OutputReply

Sorts tuples on files. The sort is performed on the element(s) mentioned in KeyPos. If two tuples compare equal on one element, next element according to KeyPos is compared. The sort is stable.

keysort(N, FileName) is equivalent to keysort(N, [FileName], FileName).

keysort(N, Input, Output) is equivalent to keysort(N, Input, Output, []).

```

merge(FileNames, Output) -> Reply
merge(FileNames, Output, Options) -> Reply

```

Types:

- Reply = ok | {error, Reason} | OutputReply

Merges terms on files. Each input file is assumed to be sorted.

`merge(FileNames, Output)` is equivalent to `merge(FileNames, Output, [])`.

`keymerge(KeyPos, FileNames, Output) -> Reply`

`keymerge(KeyPos, FileNames, Output, Options) -> Reply`

Types:

- `Reply = ok | {error, Reason} | OutputReply`

Merges tuples on files. Each input file is assumed to be sorted on `key(s)`.

`keymerge(KeyPos, FileNames, Output)` is equivalent to `keymerge(KeyPos, FileNames, Output, [])`.

`check(FileName) -> Reply`

`check(FileNames, Options) -> Reply`

Types:

- `Reply = {ok, [Result]} | {error, Reason}`
- `Result = {FileName, TermPosition, Term}`
- `TermPosition = int() > 1`

Checks files for sortedness. If a file is not sorted, the first out-of-order element is returned. The first term on a file has position 1.

`check(FileName)` is equivalent to `check([FileName], [])`.

`keycheck(KeyPos, FileName) -> CheckReply`

`keycheck(KeyPos, FileNames, Options) -> Reply`

Types:

- `Reply = {ok, [Result]} | {error, Reason}`
- `Result = {FileName, TermPosition, Term}`
- `TermPosition = int() > 1`

Checks files for sortedness. If a file is not sorted, the first out-of-order element is returned. The first term on a file has position 1.

`keycheck(KeyPos, FileName)` is equivalent to `keycheck(KeyPos, [FileName], [])`.

# filelib

Erlang Module

This module contains utilities on a higher level than the `file` module.

## Exports

`ensure_dir(Name) -> ok | {error, Reason}`

Types:

- `Name = filename() | dirname()`
- `Reason = posix()` – see `file(3)`

The `ensure_dir/1` function ensures that all parent directories for the given file or directory name `Name` exist, trying to create them if necessary.

Returns `ok` if all parent directories already exist or could be created, or `{error, Reason}` if some parent directory does not exist and could not be created for some reason.

`file_size(Filename) -> integer()`

The `file_size` function returns the size of the given file.

`fold_files(Dir, RegExp, Recursive, Fun, AccIn) -> AccOut`

Types:

- `Dir = dirname()`
- `RegExp = regexp()`
- `Recursive = true|false`
- `Fun = fun(F, AccIn) -> AccOut`
- `AccIn = AccOut = term()`

The `fold_files/5` function folds the function `Fun` over all (regular) files `F` in the directory `Dir` that match the regular expression `RegExp`. If `Recursive` is `true` all sub-directories to `Dir` are processed. The match is tried on just the filename without the directory part.

`is_dir(Name) -> true | false`

Types:

- `Name = filename() | dirname()`

The `is_dir/1` function returns `true` if `Name` refers to a directory, and `false` otherwise.

`is_file(Name) -> true | false`

Types:

- Name = filename() | dirname()

The `is_file/1` function returns `true` if Name refers to a file or a directory, and `false` otherwise.

`is_regular(Name) -> true | false`

Types:

- Name = filename()

The `is_regular/1` function returns `true` if Name refers to a file (regular file), and `false` otherwise.

`last_modified(Name) -> {{Year,Month,Day},{Hour,Min,Sec}}`

Types:

- Name = filename() | dirname()

The `last_modified/1` function returns the date and time the given file or directory was last modified.

`wildcard(Wildcard) -> list()`

Types:

- Wildcard = filename() | dirname()

The `wildcard/1` function returns a list of all files that match Unix-style wildcard-string Wildcard.

The wildcard string looks like an ordinary filename, except that certain “wildcard characters” are interpreted in a special way. The following characters are special:

? Matches one character.

\* Matches any number of characters up to the end of the filename, the next dot, or the next slash.

{Item,...} Alternation. Matches one of the alternatives.

Other characters represent themselves. Only filenames that have exactly the same character in the same position will match. (Matching is case-sensitive; i.e. “a” will not match “A”).

Note that multiple “\*” characters are allowed (as in Unix wildcards, but opposed to Windows/DOS wildcards).

Examples:

The following examples assume that the current directory is the top of an Erlang/OTP installation.

To find all `.beam` files in all applications, the following line can be used:

```
filelib:wildcard("lib/*/ebin/*.beam").
```

To find either `.erl` or `.hrl` in all applications `src` directories, the following

```
filelib:wildcard("lib/*/src/*.?rl")
```

or the following line

```
filelib:wildcard("lib/*/src/*.{erl,hr}")
```

can be used.

To find all `.hrl` files in either `src` or `include` directories, use:

```
filelib:wildcard("lib/*/{"src,include}/*.hrl").
```

To find all `.erl` or `.hrl` files in either `src` or `include` directories, use:

```
filelib:wildcard("lib/*/{"src,include}/*.{"erl,hrl}")
```

```
wildcard(Wildcard, Cwd) -> list()
```

Types:

- Wildcard = filename() | dirname()
- Cwd = dirname()

The `wildcard/2` function works like `wildcard/1`, except that instead of the actual working directory, `Cwd` will be used.

# filename

Erlang Module

The module `filename` provides a number of useful functions for analyzing and manipulating file names. These functions are designed so that the Erlang code can work on many different platforms with different formats for file names. With file name is meant all strings that can be used to denote a file. They can be short relative names like `foo.erl`, very long absolute name which include a drive designator and directory names like `D:\usr\local\bin\erl\lib\tools\foo.erl`, or any variations in between.

In Windows, all functions return file names with forward slashes only, even if the arguments contain back slashes. Use `join/1` to normalize a file name by removing redundant directory separators.

## DATA TYPES

```
name() = string() | atom() | DeepList
DeepList = [char() | atom() | DeepList]
```

## Exports

```
absname(Filename) -> string()
```

Types:

- `Filename = name()`

Converts a relative `Filename` and returns an absolute name. No attempt is made to create the shortest absolute name, because this can give incorrect results on file systems which allow links.

Unix examples:

```
1> pwd().
"/usr/local"
2> filename:absname("foo").
"/usr/local/foo"
3> filename:absname("../x").
"/usr/local/../x"
4> filename:absname("/").
"/"
```

Windows examples:

```
1> pwd().
"D:/usr/local"
2> filename:absname("foo").
"D:/usr/local/foo"
3> filename:absname("../x").
"D:/usr/local/../x"
4> filename:absname("/").
"D:/"
```

`absname(Filename, Dir) -> string()`

Types:

- `Filename = name()`
- `Dir = string()`

This function works like `absname/1`, except that the directory to which the file name should be made relative is given explicitly in the `Dir` argument.

`absname_join(Dir, Filename) -> string()`

Types:

- `Dir = string()`
- `Filename = name()`

Joins an absolute directory with a relative filename. Similar to `join/2`, but on platforms with tight restrictions on raw filename length and no support for symbolic links (read: VxWorks), leading parent directory components in `Filename` are matched against trailing directory components in `Dir` so they can be removed from the result - minimizing its length.

`basename(Filename) -> string()`

Types:

- `Filename = name()`

Returns the last component of `Filename`, or `Filename` itself if it does not contain any directory separators.

```
5> filename:basename("foo").
"foo"
6> filename:basename("/usr/foo").
"foo"
7> filename:basename("/").
[]
```

`basename(Filename, Ext) -> string()`

Types:

- `Filename = Ext = name()`

Returns the last component of `Filename` with the extension `Ext` stripped. This function should be used to remove a specific extension which might, or might not, be there. Use `rootname(basename(Filename))` to remove an extension that exists, but you are not sure which one it is.

```
8> filename:basename("~/src/kalle.erl", ".erl").
"kalle"
9> filename:basename("~/src/kalle.beam", ".erl").
"kalle.beam"
10> filename:basename("~/src/kalle.old.erl", ".erl").
"kalle.old"
11> filename:rootname(filename:basename("~/src/kalle.erl")).
"kalle"
12> filename:rootname(filename:basename("~/src/kalle.beam")).
"kalle"
```

`dirname(Filename) -> string()`

Types:

- `Filename = name()`

Returns the directory part of `Filename`.

```
13> filename:dirname("/usr/src/kalle.erl").
"/usr/src"
14> filename:dirname("kalle.erl").
"."
5> filename:dirname("\\usr\\src/kalle.erl"). % Windows
"/usr/src"
```

`extension(Filename) -> string()`

Types:

- `Filename = name()`

Returns the file extension of `Filename`, including the period. Returns an empty string if there is no extension.

```
15> filename:extension("foo.erl").
".erl"
16> filename:extension("beam.src/kalle").
[]
```

`flatten(Filename) -> string()`

Types:

- `Filename = name()`

Converts a possibly deep list filename consisting of characters and atoms into the corresponding flat string filename.

`join(Components) -> string()`

Types:

- `Components = [string()]`

Joins a list of file name `Components` with directory separators. If one of the elements of `Components` includes an absolute path, for example `"/xxx"`, the preceding elements, if any, are removed from the result.

The result is "normalized":

- Redundant directory separators are removed.
- In Windows, all directory separators are forward slashes and the drive letter is in lower case.

```
17> filename:join(["/usr", "local", "bin"]).
```

```
"/usr/local/bin"
```

```
18> filename:join(["a/b///c/"]).
```

```
"a/b/c"
```

```
6> filename:join(["B:a\\b///c/"]). % Windows
```

```
"b:a/b/c"
```

`join(Name1, Name2) -> string()`

Types:

- `Name1 = Name2 = string()`

Joins two file name components with directory separators. Equivalent to `join([Name1, Name2])`.

`nativename(Path) -> string()`

Types:

- `Path = string()`

Converts `Path` to a form accepted by the command shell and native applications on the current platform. On Windows, forward slashes is converted to backward slashes. On all platforms, the name is normalized as done by `join/1`.

```
19> filename:nativename("/usr/local/bin/"). % Unix
```

```
"/usr/local/bin"
```

```
7> filename:nativename("/usr/local/bin/"). % Windows
```

```
"\\usr\\local\\bin"
```

`pathtype(Path) -> absolute | relative | volumerelative`

Returns the type of path, one of `absolute`, `relative`, or `volumerelative`.

`absolute` The path name refers to a specific file on a specific volume.

Unix example: `/usr/local/bin`

Windows example: `D:/usr/local/bin`

`relative` The path name is relative to the current working directory on the current volume.

Example: `foo/bar`, `../src`

`volumerelative` The path name is relative to the current working directory on a specified volume, or it is a specific file on the current working volume.

Windows example: `D:bar.erl`, `/bar/foo.erl`

`rootname(Filename) -> string()`

`rootname(Filename, Ext) -> string()`

Types:

- `Filename = Ext = name()`

Remove a filename extension. `rootname/2` works as `rootname/1`, except that the extension is removed only if it is `Ext`.

```
20> filename:rootname("/beam.src/kalle").
/beam.src/kalle"
```

```
21> filename:rootname("/beam.src/foo.erl").
"/beam.src/foo"
```

```
22> filename:rootname("/beam.src/foo.erl", ".erl").
"/beam.src/foo"
```

```
23> filename:rootname("/beam.src/foo.beam", ".erl").
"/beam.src/foo.beam"
```

`split(Filename) -> Components`

Types:

- `Filename = name()`
- `Components = [string()]`

Returns a list whose elements are the path components of `Filename`.

```
24> filename:split("/usr/local/bin").
["/", "usr", "local", "bin"]
```

```
25> filename:split("foo/bar").
["foo", "bar"]
```

```
26> filename:split("a:\\msdev\\include").
["a:/", "msdev", "include"]
```

`find_src(Beam) -> {SourceFile, Options}`

`find_src(Beam, Rules) -> {SourceFile, Options}`

Types:

- `Beam = Module | Filename`
- `Module = atom()`
- `Filename = string() | atom()`
- `SourceFile = string()`
- `Options = [Opt]`
- `Opt = {i, string()} | {outdir, string()} | {d, atom()}`

Finds the source filename and compiler options for a module. The result can be fed to `compile:file/2` in order to compile the file again.

The `Beam` argument, which can be a string or an atom, specifies either the module name or the path to the source code, with or without the `.erl` extension. In either case, the module must be known by the code server, i.e. `code:which(Module)` must succeed.

`Rules` describes how the source directory can be found, when the object code directory is known. It is a list of tuples `{BinSuffix, SourceSuffix}` and is interpreted as follows: If the end of the directory name where the object is located matches `BinSuffix`, then the source code directory has the same name, but with `BinSuffix` replaced by `SourceSuffix`. `Rules` defaults to:

```
[{"", ""}, {"ebin", "src"}, {"ebin", "esrc"}]
```

If the source file is found in the resulting directory, then the function returns that location together with `Options`. Otherwise, the next rule is tried, and so on.

The function returns `{SourceFile, Options}`. `SourceFile` is the absolute path to the source file without the `.erl` extension. `Options` include the options which are necessary to recompile the file with `compile:file/2`, but excludes options such as `report` or `verbose` which do not change the way code is generated. The paths in the `{outdir, Path}` and `{i, Path}` options are guaranteed to be absolute.

# gb\_sets

Erlang Module

An implementation of ordered sets using Prof. Arne Andersson's General Balanced Trees. This can be much more efficient than using ordered lists, for larger sets, but depends on the application.

## Complexity note

The complexity on set operations is bounded by either  $O(|S|)$  or  $O(|T| * \log(|S|))$ , where  $S$  is the largest given set, depending on which is fastest for any particular function call. For operating on sets of almost equal size, this implementation is about 3 times slower than using ordered-list sets directly. For sets of very different sizes, however, this solution can be arbitrarily much faster; in practical cases, often between 10 and 100 times. This implementation is particularly suited for accumulating elements a few at a time, building up a large set (more than 100-200 elements), and repeatedly testing for membership in the current set.

As with normal tree structures, lookup (membership testing), insertion and deletion have logarithmic complexity.

## Compatibility

All of the following functions in this module also exist and do the same thing in the `sets` and `ordsets` modules. That is, by only changing the module name for each call, you can try out different set representations.

- `add_element/2`
- `del_element/2`
- `filter/2`
- `fold/3`
- `from_list/1`
- `intersection/1`
- `intersection/2`
- `is_element/2`
- `is_set/1`
- `is_subset/2`
- `new/0`
- `size/1`
- `subtract/2`

- `to_list/1`
- `union/1`
- `union/2`

## DATA TYPES

`gb_set()` = a GB set

## Exports

`add(Element, Set1) -> Set2`

`add_element(Element, Set1) -> Set2`

Types:

- `Element = term()`
- `Set1 = Set2 = gb_set()`

Returns a new `gb_set` formed from `Set1` with `Element` inserted. If `Element` is already an element in `Set1`, nothing is changed.

`balance(Set1) -> Set2`

Types:

- `Set1 = Set2 = gb_set()`

Rebalances the tree representation of `Set1`. Note that this is rarely necessary, but may be motivated when a large number of elements have been deleted from the tree without further insertions. Rebalancing could then be forced in order to minimise lookup times, since deletion only does not rebalance the tree.

`delete(Element, Set1) -> Set2`

Types:

- `Element = term()`
- `Set1 = Set2 = gb_set()`

Returns a new `gb_set` formed from `Set1` with `Element` removed. Assumes that `Element` is present in `Set1`.

`delete_any(Element, Set1) -> Set2`

`del_element(Element, Set1) -> Set2`

Types:

- `Element = term()`
- `Set1 = Set2 = gb_set()`

Returns a new `gb_set` formed from `Set1` with `Element` removed. If `Element` is not an element in `Set1`, nothing is changed.

`difference(Set1, Set2) -> Set3`

`subtract(Set1, Set2) -> Set3`

Types:

- `Set1 = Set2 = Set3 = gb_set()`

Returns only the elements of `Set1` which are not also elements of `Set2`.

`empty() -> Set`

`new() -> Set`

Types:

- `Set = gb_set()`

Returns a new empty `gb_set`.

`filter(Pred, Set1) -> Set2`

Types:

- `Pred = fun (E) -> bool()`
- `E = term()`
- `Set1 = Set2 = gb_set()`

Filters elements in `Set1` using predicate function `Pred`.

`fold(Function, Acc0, Set) -> Acc1`

Types:

- `Function = fun (E, AccIn) -> AccOut`
- `Acc0 = Acc1 = AccIn = AccOut = term()`
- `E = term()`
- `Set = gb_set()`

Folds `Function` over every element in `Set` returning the final value of the accumulator.

`from_list(List) -> Set`

Types:

- `List = [term()]`
- `Set = gb_set()`

Returns a `gb_set` of the elements in `List`, where `List` may be unordered and contain duplicates.

`from_ordset(List) -> Set`

Types:

- `List = [term()]`
- `Set = gb_set()`

Turns an ordered-set list `List` into a `gb_set`. The list must not contain duplicates.

`insert(Element, Set1) -> Set2`

Types:

- `Element = term()`

- `Set1 = Set2 = gb_set()`

Returns a new `gb_set` formed from `Set1` with `Element` inserted. Assumes that `Element` is not present in `Set1`.

`intersection(Set1, Set2) -> Set3`

Types:

- `Set1 = Set2 = Set3 = gb_set()`

Returns the intersection of `Set1` and `Set2`.

`intersection(SetList) -> Set`

Types:

- `SetList = [gb_set()]`
- `Set = gb_set()`

Returns the intersection of the non-empty list of `gb_sets`.

`is_empty(Set) -> bool()`

Types:

- `Set = gb_set()`

Returns true if `Set` is an empty set, and false otherwise.

`is_member(Element, Set) -> bool()`

`is_element(Element, Set) -> bool()`

Types:

- `Element = term()`
- `Set = gb_set()`

Returns true if `Element` is an element of `Set`, otherwise false.

`is_set(Set) -> bool()`

Types:

- `Set = gb_set()`

Returns true if `Set` appears to be a `gb_set`, otherwise false.

`is_subset(Set1, Set2) -> bool()`

Types:

- `Set1 = Set2 = gb_set()`

Returns true when every element of `Set1` is also a member of `Set2`, otherwise false.

`iterator(Set) -> Iter`

Types:

- `Set = gb_set()`
- `Iter = term()`

Returns an iterator that can be used for traversing the entries of `Set`; see `next/1`. The implementation of this is very efficient; traversing the whole set using `next/1` is only slightly slower than getting the list of all elements using `to_list/1` and traversing that. The main advantage of the iterator approach is that it does not require the complete list of all elements to be built in memory at one time.

`largest(Set) -> term()`

Types:

- `Set = gb_set()`

Returns the largest element in `Set`. Assumes that `Set` is nonempty.

`next(Iter1) -> {Element, Iter2 | none}`

Types:

- `Iter1 = Iter2 = Element = term()`

Returns `{Element, Iter2}` where `Element` is the smallest element referred to by the iterator `Iter1`, and `Iter2` is the new iterator to be used for traversing the remaining elements, or the atom `none` if no elements remain.

`singleton(Element) -> gb_set()`

Types:

- `Element = term()`

Returns a `gb_set` containing only the element `Element`.

`size(Set) -> int()`

Types:

- `Set = gb_set()`

Returns the number of elements in `Set`.

`smallest(Set) -> term()`

Types:

- `Set = gb_set()`

Returns the smallest element in `Set`. Assumes that `Set` is nonempty.

`take_largest(Set1) -> {Element, Set2}`

Types:

- `Set1 = Set2 = gb_set()`
- `Element = term()`

Returns `{Element, Set2}`, where `Element` is the largest element in `Set1`, and `Set2` is this set with `Element` deleted. Assumes that `Set1` is nonempty.

`take_smallest(Set1) -> {Element, Set2}`

Types:

- `Set1 = Set2 = gb_set()`

- `Element = term()`

Returns `{Element, Set2}`, where `Element` is the smallest element in `Set1`, and `Set2` is this set with `Element` deleted. Assumes that `Set1` is nonempty.

`to_list(Set) -> List`

Types:

- `Set = gb_set()`
- `List = [term()]`

Returns the elements of `Set` as a list.

`union(Set1, Set2) -> Set3`

Types:

- `Set1 = Set2 = Set3 = gb_set()`

Returns the merged (union) `gb_set` of `Set1` and `Set2`.

`union(SetList) -> Set`

Types:

- `SetList = [gb_set()]`
- `Set = gb_set()`

Returns the merged (union) `gb_set` of the list of `gb_sets`.

## SEE ALSO

[gb\\_trees\(3\)](#) [page 170], [ordsets\(3\)](#) [page 256], [sets\(3\)](#) [page 301]

# gb\_trees

Erlang Module

An efficient implementation of Prof. Arne Andersson's General Balanced Trees. These have no storage overhead compared to unbalanced binary trees, and their performance is in general better than AVL trees.

## Data structure

Data structure:

- {Size, Tree}, where 'Tree' is composed of nodes of the form:
  - {Key, Value, Smaller, Bigger}, and the "empty tree" node:
  - nil.

There is no attempt to balance trees after deletions. Since deletions do not increase the height of a tree, this should be OK.

Original balance condition  $h(T) \leq \text{ceil}(c * \log(|T|))$  has been changed to the similar (but not quite equivalent) condition  $2^h(T) \leq |T| \wedge c$ . This should also be OK.

Performance is comparable to the AVL trees in the Erlang book (and faster in general due to less overhead); the difference is that deletion works for these trees, but not for the book's trees. Behaviour is logarithmic (as it should be).

## DATA TYPES

`gb_tree()` = a GB tree

## Exports

`balance(Tree1) -> Tree2`

Types:

- `Tree1 = Tree2 = gb_tree()`

Rebalances `Tree1`. Note that this is rarely necessary, but may be motivated when a large number of nodes have been deleted from the tree without further insertions.

Rebalancing could then be forced in order to minimise lookup times, since deletion only does not rebalance the tree.

`delete(Key, Tree1) -> Tree2`

Types:

- Key = term()
- Tree1 = Tree2 = gb\_tree()

Removes the node with key `Key` from `Tree1`; returns new tree. Assumes that the key is present in the tree, crashes otherwise.

`delete_any(Key, Tree1) -> Tree2`

Types:

- Key = term()
- Tree1 = Tree2 = gb\_tree()

Removes the node with key `Key` from `Tree1` if the key is present in the tree, otherwise does nothing; returns new tree.

`empty() -> Tree`

Types:

- Tree = gb\_tree()

Returns a new empty tree

`enter(Key, Val, Tree1) -> Tree2`

Types:

- Key = Val = term()
- Tree1 = Tree2 = gb\_tree()

Inserts `Key` with value `Val` into `Tree1` if the key is not present in the tree, otherwise updates `Key` to value `Val` in `Tree1`. Returns the new tree.

`from_orddict(List) -> Tree`

Types:

- List = [{Key, Val}]
- Key = Val = term()
- Tree = gb\_tree()

Turns an ordered list `List` of key-value tuples into a tree. The list must not contain duplicate keys.

`get(Key, Tree) -> Val`

Types:

- Key = Val = term()
- Tree = gb\_tree()

Retrieves the value stored with `Key` in `Tree`. Assumes that the key is present in the tree, crashes otherwise.

`lookup(Key, Tree) -> {value, Val} | none`

Types:

- Key = Val = term()
- Tree = gb\_tree()

Looks up `Key` in `Tree`; returns `{value, Val}`, or `none` if `Key` is not present.

`insert(Key, Val, Tree1) -> Tree2`

Types:

- `Key = Val = term()`
- `Tree1 = Tree2 = gb_tree()`

Inserts `Key` with value `Val` into `Tree1`; returns the new tree. Assumes that the key is not present in the tree, crashes otherwise.

`is_defined(Key, Tree) -> bool()`

Types:

- `Tree = gb_tree()`

Returns `true` if `Key` is present in `Tree`, otherwise `false`.

`is_empty(Tree) -> bool()`

Types:

- `Tree = gb_tree()`

Returns `true` if `Tree` is an empty tree, and `false` otherwise.

`iterator(Tree) -> Iter`

Types:

- `Tree = gb_tree()`
- `Iter = term()`

Returns an iterator that can be used for traversing the entries of `Tree`; see `next/1`. The implementation of this is very efficient; traversing the whole tree using `next/1` is only slightly slower than getting the list of all elements using `to_list/1` and traversing that. The main advantage of the iterator approach is that it does not require the complete list of all elements to be built in memory at one time.

`keys(Tree) -> [Key]`

Types:

- `Tree = gb_tree()`
- `Key = term()`

Returns the keys in `Tree` as an ordered list.

`largest(Tree) -> {Key, Val}`

Types:

- `Tree = gb_tree()`
- `Key = Val = term()`

Returns `{Key, Val}`, where `Key` is the largest key in `Tree`, and `Val` is the value associated with this key. Assumes that the tree is nonempty.

`next(Iter1) -> {Key, Val, Iter2}`

Types:

- `Iter1 = Iter2 = Key = Val = term()`

Returns `{Key, Val, Iter2}` where `Key` is the smallest key referred to by the iterator `Iter1`, and `Iter2` is the new iterator to be used for traversing the remaining nodes, or the atom `none` if no nodes remain.

`size(Tree) -> int()`

Types:

- `Tree = gb_tree()`

Returns the number of nodes in `Tree`.

`smallest(Tree) -> {Key, Val}`

Types:

- `Tree = gb_tree()`
- `Key = Val = term()`

Returns `{Key, Val}`, where `Key` is the smallest key in `Tree`, and `Val` is the value associated with this key. Assumes that the tree is nonempty.

`take_largest(Tree1) -> {Key, Val, Tree2}`

Types:

- `Tree1 = Tree2 = gb_tree()`
- `Key = Val = term()`

Returns `{Key, Val, Tree2}`, where `Key` is the largest key in `Tree1`, `Val` is the value associated with this key, and `Tree2` is this tree with the corresponding node deleted. Assumes that the tree is nonempty.

`take_smallest(Tree1) -> {Key, Val, Tree2}`

Types:

- `Tree1 = Tree2 = gb_tree()`
- `Key = Val = term()`

Returns `{Key, Val, Tree2}`, where `Key` is the smallest key in `Tree1`, `Val` is the value associated with this key, and `Tree2` is this tree with the corresponding node deleted. Assumes that the tree is nonempty.

`to_list(Tree) -> [{Key, Val}]`

Types:

- `Tree = gb_tree()`
- `Key = Val = term()`

Converts a tree into an ordered list of key-value tuples.

`update(Key, Val, Tree1) -> Tree2`

Types:

- `Key = Val = term()`

- `Tree1 = Tree2 = gb_tree()`

Updates `Key` to value `Val` in `Tree1`; returns the new tree. Assumes that the key is present in the tree.

`values(Tree) -> [Val]`

Types:

- `Tree = gb_tree()`
- `Val = term()`

Returns the values in `Tree` as an ordered list, sorted by their corresponding keys. Duplicates are not removed.

## SEE ALSO

`gb_sets(3)` [page 164], `dict(3)` [page 88]

# gen\_event

Erlang Module

A behaviour module for implementing event handling functionality. The OTP event handling model consists of a generic event manager process with an arbitrary number of event handlers which are added and deleted dynamically.

An event manager implemented using this module will have a standard set of interface functions and include functionality for tracing and error reporting. It will also fit into an OTP supervision tree. Refer to *OTP Design Principles* for more information.

Each event handler is implemented as a callback module exporting a pre-defined set of functions. The relationship between the behaviour functions and the callback functions can be illustrated as follows:

gen_event module		Callback module
-----		-----
gen_event:start_link	----->	-
gen_event:add_handler		
gen_event:add_suphandler	----->	Module:init/1
gen_event:notify		
gen_event:sync_notify	----->	Module:handle_event/2
gen_event:call	----->	Module:handle_call/2
-	----->	Module:handle_info/2
gen_event:delete_handler	----->	Module:terminate/2
gen_event:swap_handler		
gen_event:swap_sup_handler	----->	Module1:terminate/2 Module2:init/1
gen_event:which_handlers	----->	-
gen_event:stop	----->	Module:terminate/2
-	----->	Module:code_change/3

Since each event handler is one callback module, an event manager will have several callback modules which are added and deleted dynamically. Therefore `gen_event` is more tolerant of callback module errors than the other behaviours. If a callback function for an installed event handler fails with `Reason`, or returns a bad value `Term`, the event manager will not fail. It will delete the event handler by calling the callback function

`Module:terminate/2` (see below), giving as argument `{error, {'EXIT', Reason}}` or `{error, Term}`, respectively. No other event handler will be affected.

The `sys` module can be used for debugging an event manager.

Note that an event manager *does* trap exit signals automatically.

Unless otherwise stated, all functions in this module fail if the specified event manager does not exist or if bad arguments are given.

## Exports

`start_link() -> Result`

`start_link(EventMgrName) -> Result`

Types:

- `EventMgrName = {local, Name} | {global, Name}`
- `Name = atom()`
- `Result = {ok, Pid} | {error, {already_started, Pid}}`
- `Pid = pid()`

Creates an event manager process as part of a supervision tree. The function should be called, directly or indirectly, by the supervisor. It will, among other things, ensure that the event manager is linked to the supervisor.

If `EventMgrName={local, Name}`, the event manager is registered locally as `Name` using `register/2`. If `EventMgrName={global, Name}`, the event manager is registered globally as `Name` using `global:register_name/2`. If no name is provided, the event manager is not registered.

If the event manager is successfully created the function returns `{ok, Pid}`, where `Pid` is the pid of the event manager. If there already exists a process with the specified `EventMgrName` the function returns `{error, {already_started, Pid}}`, where `Pid` is the pid of that process.

`start() -> Result`

`start(EventMgrName) -> Result`

Types:

- `EventMgrName = {local, Name} | {global, Name}`
- `Name = atom()`
- `Result = {ok, Pid} | {error, {already_started, Pid}}`
- `Pid = pid()`

Creates a stand-alone event manager process, i.e. an event manager which is not part of a supervision tree and thus has no supervisor.

See `start_link/0,1` for a description of arguments and return values.

`add_handler(EventMgrRef, Handler, Args) -> Result`

Types:

- `EventMgr = Name | {Name, Node} | {global, Name} | pid()`
- `Name = Node = atom()`
- `Handler = Module | {Module, Id}`

- `Module = atom()`
- `Id = term()`
- `Args = term()`
- `Result = ok | {'EXIT',Reason} | term()`
- `Reason = term()`

Adds a new event handler to the event manager `EventMgrRef`. The event manager will call `Module:init/1` to initiate the event handler and its internal state.

`EventMgrRef` can be:

- the `pid`,
- `Name`, if the event manager is locally registered,
- `{Name,Node}`, if the event manager is locally registered at another node, or
- `{global,Name}`, if the event manager is globally registered.

`Handler` is the name of the callback module `Module` or a tuple `{Module,Id}`, where `Id` is any term. The `{Module,Id}` representation makes it possible to identify a specific event handler when there are several event handlers using the same callback module.

`Args` is an arbitrary term which is passed as the argument to `Module:init/1`.

If `Module:init/1` returns a correct value, the event manager adds the event handler and this function returns `ok`. If `Module:init/1` fails with `Reason` or returns an unexpected value `Term`, the event handler is ignored and this function returns `{'EXIT',Reason}` or `Term`, respectively.

```
add_sup_handler(EventMgrRef, Handler, Args) -> Result
```

Types:

- `EventMgr = Name | {Name,Node} | {global,Name} | pid()`
- `Name = Node = atom()`
- `Handler = Module | {Module,Id}`
- `Module = atom()`
- `Id = term()`
- `Args = term()`
- `Result = ok | {'EXIT',Reason} | term()`
- `Reason = term()`

Adds a new event handler in the same way as `add_handler/3` but will also supervise the connection between the event handler and the calling process.

- If the calling process later terminates with `Reason`, the event manager will delete the event handler by calling `Module:terminate/2` with `{stop,Reason}` as argument.
- If the event handler later is deleted, the event manager sends a message `{gen_event_EXIT,Handler,Reason}` to the calling process. `Reason` is one of the following:
  - `normal`, if the event handler has been removed due to a call to `delete_handler/3`, or `remove_handler` has been returned by a callback function (see below).
  - `shutdown`, if the event handler has been removed because the event manager is terminating.

- {swapped,NewHandler,Pid}, if the process Pid has replaced the event handler with another event handler NewHandler using a call to swap\_handler/3 or swap\_sup\_handler/3.
- a term, if the event handler is removed due to an error. Which term depends on the error.

See add\_handler/3 for a description of the arguments and return values.

notify(EventMgrRef, Event) -> ok

sync\_notify(EventMgrRef, Event) -> ok

Types:

- EventMgrRef = Name | {Name,Node} | {global,Name} | pid()
- Name = Node = atom()
- Event = term()

Sends an event notification to the event manager EventMgrRef. The event manager will call Module:handle\_event/2 for each installed event handler to handle the event.

notify is asynchronous and will return immediately after the event notification has been sent. sync\_notify is synchronous in the sense that it will return ok after the event has been handled by all event handlers.

See add\_handler/3 for a description of EventMgrRef.

Event is an arbitrary term which is passed as one of the arguments to Module:handle\_event/2.

notify will not fail even if the specified event manager does not exist, unless it is specified as Name.

call(EventMgrRef, Handler, Request) -> Result

call(EventMgrRef, Handler, Request, Timeout) -> Result

Types:

- EventMgrRef = Name | {Name,Node} | {global,Name} | pid()
- Name = Node = atom()
- Handler = Module | {Module,Id}
- Module = atom()
- Id = term()
- Request = term()
- Timeout = int()>0 | infinity
- Result = Reply | {error,Error}
- Reply = term()
- Error = bad\_module | {'EXIT',Reason} | term()
- Reason = term()

Makes a synchronous call to the event handler `Handler` installed in the event manager `EventMgrRef` by sending a request and waiting until a reply arrives or a timeout occurs. The event manager will call `Module:handle_call/2` to handle the request.

See `add_handler/3` for a description of `EventMgrRef` and `Handler`.

`Request` is an arbitrary term which is passed as one of the arguments to `Module:handle_call/2`.

`Timeout` is an integer greater than zero which specifies how many milliseconds to wait for a reply, or the atom `infinity` to wait indefinitely. Default value is 5000. If no reply is received within the specified time, the function call fails.

The return value `Reply` is defined in the return value of `Module:handle_call/2`. If the specified event handler is not installed, the function returns `{error,bad_module}`. If the callback function fails with `Reason` or returns an unexpected value `Term`, this function returns `{error,{'EXIT',Reason}}` or `{error,Term}`, respectively.

```
delete_handler(EventMgrRef, Handler, Args) -> Result
```

Types:

- `EventMgrRef` = `Name` | `{Name,Node}` | `{global,Name}` | `pid()`
- `Name` = `Node` = `atom()`
- `Handler` = `Module` | `{Module,Id}`
- `Module` = `atom()`
- `Id` = `term()`
- `Args` = `term()`
- `Result` = `term()` | `{error,module_not_found}` | `{'EXIT',Reason}`
- `Reason` = `term()`

Deletes an event handler from the event manager `EventMgrRef`. The event manager will call `Module:terminate/2` to terminate the event handler.

See `add_handler/3` for a description of `EventMgrRef` and `Handler`.

`Args` is an arbitrary term which is passed as one of the arguments to `Module:terminate/2`.

The return value is the return value of `Module:terminate/2`. If the specified event handler is not installed, the function returns `{error,module_not_found}`. If the callback function fails with `Reason`, the function returns `{'EXIT',Reason}`.

```
swap_handler(EventMgrRef, {Handler1,Args1}, {Handler2,Args2}) -> Result
```

Types:

- `EventMgrRef` = `Name` | `{Name,Node}` | `{global,Name}` | `pid()`
- `Name` = `Node` = `atom()`
- `Handler1` = `Handler2` = `Module` | `{Module,Id}`
- `Module` = `atom()`
- `Id` = `term()`
- `Args1` = `Args2` = `term()`
- `Result` = `ok` | `{error,Error}`
- `Error` = `{'EXIT',Reason}` | `term()`
- `Reason` = `term()`

Replaces an old event handler with a new event handler in the event manager `EventMgrRef`.

See `add_handler/3` for a description of the arguments.

First the old event handler `Handler1` is deleted. The event manager calls `Module1:terminate(Args1, ...)`, where `Module1` is the callback module of `Handler1`, and collects the return value.

Then the new event handler `Handler2` is added and initiated by calling `Module2:init({Args2,Term})`, where `Module2` is the callback module of `Handler2` and `Term` the return value of `Module1:terminate/2`. This makes it possible to transfer information from `Handler1` to `Handler2`.

The new handler will be added even if the the specified old event handler is not installed in which case `Term=error`, or if `Module1:terminate/2` fails with `Reason` in which case `Term={'EXIT',Reason}`. The old handler will be deleted even if `Module2:init/1` fails.

If there was a supervised connection between `Handler1` and a process `Pid`, there will be a supervised connection between `Handler2` and `Pid` instead.

If `Module2:init/1` returns a correct value, this function returns `ok`. If `Module2:init/1` fails with `Reason` or returns an unexpected value `Term`, this this function returns `{error,{'EXIT',Reason}}` or `{error,Term}`, respectively.

```
swap_sup_handler(EventMgrRef, {Handler1,Args1}, {Handler2,Args2}) -> Result
```

Types:

- `EventMgrRef = Name | {Name,Node} | {global,Name} | pid()`
- `Name = Node = atom()`
- `Handler1 = Handler 2 = Module | {Module,Id}`
- `Module = atom()`
- `Id = term()`
- `Args1 = Args2 = term()`
- `Result = ok | {error,Error}`
- `Error = {'EXIT',Reason} | term()`
- `Reason = term()`

Replaces an event handler in the event manager `EventMgrRef` in the same way as `swap_handler/3` but will also supervise the connection between `Handler2` and the calling process.

See `swap_handler/3` for a description of the arguments and return values.

```
which_handlers(EventMgrRef) -> [Handler]
```

Types:

- `EventMgrRef = Name | {Name,Node} | {global,Name} | pid()`
- `Name = Node = atom()`
- `Handler = Module | {Module,Id}`
- `Module = atom()`
- `Id = term()`

Returns a list of all event handlers installed in the event manager `EventMgrRef`.

See `add_handler/3` for a description of `EventMgrRef` and `Handler`.

`stop(EventMgrRef) -> ok`

Types:

- `EventMgrRef = Name | {Name,Node} | {global,Name} | pid()`
- `Name = Node = atom()`

Terminates the event manager `EventMgrRef`. Before terminating, the event manager will call `Module:terminate(stop,...)` for each installed event handler.

See `add_handler/3` for a description of the argument.

## CALLBACK FUNCTIONS

The following functions should be exported from a `gen_event` callback module.

### Exports

`Module:init(InitArgs) -> {ok,State}`

Types:

- `InitArgs = Args | {Args,Term}`
- `Args = Term = term()`
- `State = term()`

Whenever a new event handler is added to an event manager, this function is called to initialize the event handler.

If the event handler is added due to a call to `gen_event:add_handler/3` or `gen_event:add_sup_handler/3`, `InitArgs` is the `Args` argument of these functions.

If the event handler is replacing another event handler due to a call to `gen_event:swap_handler/3` or `gen_event:swap_sup_handler/3`, or due to a swap return tuple from one of the other callback functions, `InitArgs` is a tuple `{Args,Term}` where `Args` is the argument provided in the function call/return tuple and `Term` is the result of terminating the old event handler, see `gen_event:swap_handler/3`.

The function should return `{ok,State}` where `State` is the initial internal state of the event handler.

`Module:handle_event(Event, State) -> Result`

Types:

- `Event = term()`
- `State = term()`
- `Result = {ok,NewState}`
- `| {swap_handler,Args1,NewState,Handler2,Args2} | remove_handler`
- `NewState = term()`
- `Args1 = Args2 = term()`
- `Handler2 = Module2 | {Module2,Id}`
- `Module2 = atom()`
- `Id = term()`

Whenever an event manager receives an event sent using `gen_event:notify/2` or `gen_event:sync_notify/2`, this function is called for each installed event handler to handle the event.

`Event` is the `Event` argument of `notify/sync_notify`.

`State` is the internal state of the event handler.

If the function returns `{ok, NewState}` the event handler will remain in the event manager with the possible updated internal state `NewState`.

If the function returns `{swap_handler, Args1, NewState, Handler2, Args2}` the event handler will be replaced by `Handler2` by first calling `Module:terminate(Args1, NewState)` and then `Module2:init({Args2, Term})` where `Term` is the return value of `Module:terminate/2`. See `gen_event:swap_handler/3` for more information.

If the function returns `remove_handler` the event handler will be deleted by calling `Module:terminate(remove_handler, State)`.

`Module:handle_call(Request, State) -> Result`

Types:

- `Request = term()`
- `State = term()`
- `Result = {ok, Reply, NewState}`
- `| {swap_handler, Reply, Args1, NewState, Handler2, Args2}`
- `| {remove_handler, Reply}`
- `Reply = term()`
- `NewState = term()`
- `Args1 = Args2 = term()`
- `Handler2 = Module2 | {Module2, Id}`
- `Module2 = atom()`
- `Id = term()`

Whenever an event manager receives a request sent using `gen_event:call/3, 4`, this function is called for the specified event handler to handle the request.

`Request` is the `Request` argument of `call`.

`State` is the internal state of the event handler.

The return values are the same as for `handle_event/2` except they also contain a term `Reply` which is the reply given back to the client as the return value of `call`.

`Module:handle_info(Info, State) -> Result`

Types:

- `Info = term()`
- `State = term()`
- `Result = {ok, NewState}`
- `| {swap_handler, Args1, NewState, Handler2, Args2} | remove_handler`
- `NewState = term()`
- `Args1 = Args2 = term()`
- `Handler2 = Module2 | {Module2, Id}`
- `Module2 = atom()`

- `Id = term()`

This function is called for each installed event handler when an event manager receives any other message than an event or a synchronous request (or a system message).

`Info` is the received message.

See `Module:handle_event/2` for a description of `State` and possible return values.

`Module:terminate(Arg, State) -> term()`

Types:

- `Arg = Args | {stop,Reason} | stop | remove_handler`
- `| {error,{ 'EXIT',Reason}} | {error,Term}`
- `Args = Reason = Term = term()`

Whenever an event handler is deleted from an event manager, this function is called. It should be the opposite of `Module:init/1` and do any necessary cleaning up.

If the event handler is deleted due to a call to `gen_event:delete_handler`, `gen_event:swap_handler/3` or `gen_event:swap_sup_handler/3`, `Arg` is the `Args` argument of this function call.

`Arg={stop,Reason}` if the event handler has a supervised connection to a process which has terminated with reason `Reason`.

`Arg=stop` if the event handler is deleted because the event manager is terminating.

`Arg=remove_handler` if the event handler is deleted because another callback function has returned `remove_handler` or `{remove_handler,Reply}`.

`Arg={error,Term}` if the event handler is deleted because a callback function returned an unexpected value `Term`, or `Arg={error,{ 'EXIT',Reason}}` if a callback function failed.

`State` is the internal state of the event handler.

The function may return any term. If the event handler is deleted due to a call to `gen_event:delete_handler`, the return value of that function will be the return value of this function. If the event handler is to be replaced with another event handler due to a swap, the return value will be passed to the `init` function of the new event handler. Otherwise the return value is ignored.

`Module:code_change(OldVsn, State, Extra) -> {ok, NewState}`

Types:

- `OldVsn = Vsn | {down, Vsn}`
- `Vsn = term()`
- `State = NewState = term()`
- `Extra = term()`

This function is called for an installed event handler which should update its internal state during a release upgrade/downgrade, i.e. when the instruction `{update,Module,Change,...}` where `Change={advanced,Extra}` is given in the `.appup` file. See *OTP Design Principles* for more information.

In the case of an upgrade, `OldVsn` is `Vsn`, and in the case of a downgrade, `OldVsn` is `{down,Vsn}`. `Vsn` is defined by the `vsn` attribute(s) of the old version of the callback module `Module`. If no such attribute is defined, the version is the checksum of the BEAM file.

`State` is the internal state of the event handler.

`Extra` is passed as-is from the `{advanced,Extra}` part of the update instruction.

The function should return the updated internal state.

## SEE ALSO

`supervisor(3)` [page 347], `sys(3)` [page 357]

# gen\_fsm

Erlang Module

A behaviour module for implementing a finite state machine. A generic finite state machine process (`gen_fsm`) implemented using this module will have a standard set of interface functions and include functionality for tracing and error reporting. It will also fit into an OTP supervision tree. Refer to [OTP Design Principles] for more information.

A `gen_fsm` assumes all specific parts to be located in a callback module exporting a pre-defined set of functions. The relationship between the behaviour functions and the callback functions can be illustrated as follows:

<code>gen_fsm</code> module	Callback module
-----	-----
<code>gen_fsm:start_link</code>	-----> <code>Module:init/1</code>
<code>gen_fsm:send_event</code>	-----> <code>Module:StateName/2</code>
<code>gen_fsm:send_all_state_event</code>	-----> <code>Module:handle_event/3</code>
<code>gen_fsm:sync_send_event</code>	-----> <code>Module:StateName/3</code>
<code>gen_fsm:sync_send_all_state_event</code>	-----> <code>Module:handle_sync_event/4</code>
-	-----> <code>Module:handle_info/3</code>
-	-----> <code>Module:terminate/3</code>
-	-----> <code>Module:code_change/4</code>

If a callback function fails or returns a bad value, the `gen_fsm` will terminate.

The `sys` module can be used for debugging a `gen_fsm`.

Note that a `gen_fsm` does not trap exit signals automatically, this must be explicitly initiated in the callback module.

Unless otherwise stated, all functions in this module fail if the specified `gen_fsm` does not exist or if bad arguments are given.

## Exports

`start_link(Module, Args, Options) -> Result`

`start_link(FsmName, Module, Args, Options) -> Result`

Types:

- `FsmName = {local,Name} | {global,GlobalName}`
- `Name = atom()`
- `GlobalName = term()`
- `Module = atom()`
- `Args = term()`
- `Options = [Option]`
- `Option = {debug,Dbgs} | {timeout,Time} | {spawn_opt,SOpts}`
- `Dbgs = [Dbg]`
- `Dbg = trace | log | statistics`
- `| {log_to_file,FileName} | {install,{Func,FuncState}}`
- `SOpts = [SOpt]`
- `SOpt - see erlang:spawn_opt/2,3,4,5`
- `Result = {ok,Pid} | ignore | {error,Error}`
- `Pid = pid()`
- `Error = {already_started,Pid} | term()`

Creates a `gen_fsm` process as part of a supervision tree. The function should be called, directly or indirectly, by the supervisor. It will, among other things, ensure that the `gen_fsm` is linked to the supervisor.

The `gen_fsm` process calls `Module:init/1` to initialize. To ensure a synchronized start-up procedure, `start_link/3,4` does not return until `Module:init/1` has returned.

If `FsmName={local,Name}`, the `gen_fsm` is registered locally as `Name` using `register/2`.

If `FsmName={global,GlobalName}`, the `gen_fsm` is registered globally as `GlobalName` using `global:register_name/2`. If no name is provided, the `gen_fsm` is not registered.

`Module` is the name of the callback module.

`Args` is an arbitrary term which is passed as the argument to `Module:init/1`.

If the option `{timeout,Time}` is present, the `gen_fsm` is allowed to spend `Time` milliseconds initializing or it will be terminated and the start function will return `{error,timeout}`.

If the option `{debug,Dbgs}` is present, the corresponding `sys` function will be called for each item in `Dbgs`. See `sys(3)` [page 357].

If the option `{spawn_opt,SOpts}` is present, `SOpts` will be passed as option list to the `spawn_opt` BIF which is used to spawn the `gen_fsm` process. See `[erlang(3)]`.

### Note:

Using the `spawn` option `monitor` is currently not allowed, but will cause the function to fail with reason `badarg`.

If the `gen_fsm` is successfully created and initialized the function returns `{ok,Pid}`, where `Pid` is the pid of the `gen_fsm`. If there already exists a process with the specified

`FsmName`, the function returns `{error, {already_started, Pid}}` where `Pid` is the pid of that process.

If `Module:init/1` fails with `Reason`, the function returns `{error, Reason}`. If `Module:init/1` returns `{stop, Reason}` or `ignore`, the process is terminated and the function returns `{error, Reason}` or `ignore`, respectively.

`start(Module, Args, Options) -> Result`

`start(FsmName, Module, Args, Options) -> Result`

Types:

- `FsmName = {local, Name} | {global, GlobalName}`
- `Name = atom()`
- `GlobalName = term()`
- `Module = atom()`
- `Args = term()`
- `Options = [Option]`
- `Option = {debug, Dbgs} | {timeout, Time} | {spawn_opt, SOpts}`
- `Dbgs = [Dbg]`
- `Dbg = trace | log | statistics`
- `| {log_to_file, FileName} | {install, {Func, FuncState}}`
- `SOpts = [term()]`
- `Result = {ok, Pid} | ignore | {error, Error}`
- `Pid = pid()`
- `Error = {already_started, Pid} | term()`

Creates a stand-alone `gen_fsm` process, i.e. a `gen_fsm` which is not part of a supervision tree and thus has no supervisor.

See [start\\_link/3,4](#) [page 186] for a description of arguments and return values.

`send_event(FsmRef, Event) -> ok`

Types:

- `FsmRef = Name | {Name, Node} | {global, GlobalName} | pid()`
- `Name = Node = atom()`
- `GlobalName = term()`
- `Event = term()`

Sends an event asynchronously to the `gen_fsm` `FsmRef` and returns `ok` immediately. The `gen_fsm` will call `Module:StateName/2` to handle the event, where `StateName` is the name of the current state of the `gen_fsm`.

`FsmRef` can be:

- the pid,
- `Name`, if the `gen_fsm` is locally registered,
- `{Name, Node}`, if the `gen_fsm` is locally registered at another node, or
- `{global, GlobalName}`, if the `gen_fsm` is globally registered.

`Event` is an arbitrary term which is passed as one of the arguments to `Module:StateName/2`.

```
send_all_state_event(FsmRef, Event) -> ok
```

Types:

- FsmRef = Name | {Name,Node} | {global,GlobalName} | pid()
- Name = Node = atom()
- GlobalName = term()
- Event = term()

Sends an event asynchronously to the gen\_fsm FsmRef and returns ok immediately. The gen\_fsm will call Module:handle\_event/3 to handle the event.

See send\_event/2 [page 187] for a description of the arguments.

The difference between send\_event and send\_all\_state\_event is which callback function is used to handle the event. This function is useful when sending events that are handled the same way in every state, as only one handle\_event clause is needed to handle the event instead of one clause in each state name function.

```
sync_send_event(FsmRef, Event) -> Reply
```

```
sync_send_event(FsmRef, Event, Timeout) -> Reply
```

Types:

- FsmRef = Name | {Name,Node} | {global,GlobalName} | pid()
- Name = Node = atom()
- GlobalName = term()
- Event = term()
- Timeout = int()>0 | infinity
- Reply = term()

Sends an event to the gen\_fsm FsmRef and waits until a reply arrives or a timeout occurs. The gen\_fsm will call Module:StateName/3 to handle the event, where StateName is the name of the current state of the gen\_fsm.

See send\_event/2 [page 187] for a description of FsmRef and Event.

Timeout is an integer greater than zero which specifies how many milliseconds to wait for a reply, or the atom infinity to wait indefinitely. Default value is 5000. If no reply is received within the specified time, the function call fails.

The return value Reply is defined in the return value of Module:StateName/3.

In the case where the gen\_fsm terminates during the handling of the event and the caller is linked to the gen\_fsm and trapping exits, the exit message is removed from the caller's receive queue before the function call fails.

This behaviour is retained for backwards compatibility only and may change in the future. Note that if the gen\_fsm crashes in between calls, a linked process must take care of the exit message anyway.

Warning: Under certain circumstances (e.g. FsmRef = {Name,Node}, and Node goes down) the exit message cannot be removed.

```
sync_send_all_state_event(FsmRef, Event) -> Reply
```

```
sync_send_all_state_event(FsmRef, Event, Timeout) -> Reply
```

Types:

- FsmRef = Name | {Name,Node} | {global,GlobalName} | pid()
- Name = Node = atom()

- GlobalName = term()
- Event = term()
- Timeout = int() > 0 | infinity
- Reply = term()

Sends an event to the `gen_fsm` `FsmRef` and waits until a reply arrives or a timeout occurs. The `gen_fsm` will call `Module:handle_sync_event/4` to handle the event.

See `send_event/2` [page 187] for a description of `FsmRef` and `Event`. See `sync_send_event/3` [page 188] for a description of `Timeout` and `Reply`.

See `send_all_state_event/2` [page 188] for a discussion about the difference between `sync_send_event` and `sync_send_all_state_event`.

`reply(Caller, Reply) -> true`

Types:

- Caller - see below
- Reply = term()

This function can be used by a `gen_fsm` to explicitly send a reply to a client process that called `sync_send_event/2,3` [page 188] or `sync_send_all_state_event/2,3` [page 188], when the reply cannot be defined in the return value of `Module:State/3` or `Module:handle_sync_event/4`.

`Caller` must be the `From` argument provided to the callback function. `Reply` is an arbitrary term, which will be given back to the client as the return value of `sync_send_event/2,3` or `sync_send_all_state_event/2,3`.

`send_event_after(Time, Event) -> Ref`

Types:

- Time = integer()
- Event = term()
- Ref = reference()

Sends a delayed event internally in the `gen_fsm` that calls this function after `Time` ms. Returns immediately a reference that can be used to cancel the delayed send using `cancel_timer/1` [page 190].

The `gen_fsm` will call `Module:StateName/2` to handle the event, where `StateName` is the name of the current state of the `gen_fsm` at the time the delayed event is delivered.

`Event` is an arbitrary term which is passed as one of the arguments to `Module:StateName/2`.

`start_timer(Time, Msg) -> Ref`

Types:

- Time = integer()
- Msg = term()
- Ref = reference()

Sends a timeout event internally in the `gen_fsm` that calls this function after `Time` ms. Returns immediately a reference that can be used to cancel the timer using `cancel_timer/1` [page 190].

The `gen_fsm` will call `Module:StateName/2` to handle the event, where `StateName` is the name of the current state of the `gen_fsm` at the time the timeout message is delivered.

`Msg` is an arbitrary term which is passed in the timeout message, `{timeout, Ref, Msg}`, as one of the arguments to `Module:StateName/2`.

```
cancel_timer(Ref) -> RemainingTime | false
```

Types:

- `Ref` = `reference()`
- `RemainingTime` = `integer()`

Cancels an internal timer referred by `Ref` in the `gen_fsm` that calls this function.

`Ref` is a reference returned from `send_event_after/2` [page 189] or `start_timer/2` [page 189].

If the timer has already timed out, but the event not yet been delivered, it is cancelled as if it had *not* timed out, so there will be no false timer event after returning from this function.

Returns the remaining time in ms until the timer would have expired if `Ref` referred to an active timer, `false` otherwise.

```
enter_loop(Module, Options, StateName, StateData)
enter_loop(Module, Options, StateName, StateData, FsmName)
enter_loop(Module, Options, StateName, StateData, Timeout)
enter_loop(Module, Options, StateName, StateData, FsmName, Timeout)
```

Types:

- `Module` = `atom()`
- `Options` = `[Option]`
- `Option` = `{debug,Dbgs}`
- `Dbgs` = `[Dbg]`
- `Dbg` = `trace | log | statistics`
- `| {log_to_file,FileName} | {install,{Func,FuncState}}`
- `StateName` = `atom()`
- `StateData` = `term()`
- `FsmName` = `{local,Name} | {global,GlobalName}`
- `Name` = `atom()`
- `GlobalName` = `term()`
- `Timeout` = `int() | infinity`

Makes an existing process into a `gen_fsm`. Does not return, instead the calling process will enter the `gen_fsm` receive loop and become a `gen_fsm` process. The process *must* have been started using one of the start functions in `proc_lib`, see `proc_lib(3)` [page 263]. The user is responsible for any initialization of the process, including registering a name for it.

This function is useful when a more complex initialization procedure is needed than the `gen_fsm` behaviour provides.

`Module`, `Options` and `FsmName` have the same meanings as when calling `start[_link]/3,4` [page 186]. However, if `FsmName` is specified, the process must have been registered accordingly *before* this function is called.

`StateName`, `StateData` and `Timeout` have the same meanings as in the return value of `Module:init/1` [page 191]. Also, the callback module `Module` does not need to export an `init/1` function.

Failure: If the calling process was not started by a `proc_lib` start function, or if it is not registered according to `FsmName`.

## CALLBACK FUNCTIONS

The following functions should be exported from a `gen_fsm` callback module.

In the description, the expression *state name* is used to denote a state of the state machine. *state data* is used to denote the internal state of the Erlang process which implements the state machine.

## Exports

`Module:init(Args) -> Result`

Types:

- `Args = term()`
- `Return = {ok,StateName,StateData} | {ok,StateName,StateData,Timeout}`
- `| {stop,Reason} | ignore`
- `StateName = atom()`
- `StateData = term()`
- `Timeout = int()>0 | infinity`
- `Reason = term()`

Whenever a `gen_fsm` is started using `gen_fsm:start/3,4` [page 187] or `gen_fsm:start_link/3,4` [page 186], this function is called by the new process to initialize.

`Args` is the `Args` argument provided to the start function.

If initialization is successful, the function should return `{ok,StateName,StateData}` or `{ok,StateName,StateData,Timeout}`, where `StateName` is the initial state name and `StateData` the initial state data of the `gen_fsm`.

If an integer timeout value is provided, a timeout will occur unless an event or a message is received within `Timeout` milliseconds. A timeout is represented by the atom `timeout` and should be handled by the `Module:StateName/2` callback functions. The atom `infinity` can be used to wait indefinitely, this is the default value.

If something goes wrong during the initialization the function should return `{stop, Reason}`, where Reason is any term, or ignore.

`Module:StateName(Event, StateData) -> Result`

Types:

- Event = timeout | term()
- StateData = term()
- Result = {next\_state, NextStateName, NewStateData} | {next\_state, NextStateName, NewStateData, Timeout} | {stop, Reason, NewStateData}
- NextStateName = atom()
- NewStateData = term()
- Timeout = int()>0 | infinity
- Reason = term()

There should be one instance of this function for each possible state name. Whenever a `gen_fsm` receives an event sent using `gen_fsm:send_event/2` [page 187], the instance of this function with the same name as the current state name `StateName` is called to handle the event. It is also called if a timeout occurs.

`Event` is either the atom `timeout`, if a timeout has occurred, or the `Event` argument provided to `send_event/2`.

`StateData` is the state data of the `gen_fsm`.

If the function returns `{next_state, NextStateName, NewStateData}` or `{next_state, NextStateName, NewStateData, Timeout}`, the `gen_fsm` will continue executing with the current state name set to `NextStateName` and with the possibly updated state data `NewStateData`. See `Module:init/1` for a description of `Timeout`.

If the function returns `{stop, Reason, NewStateData}`, the `gen_fsm` will call `Module:terminate(Reason, NewStateData)` and terminate.

`Module:handle_event(Event, StateName, StateData) -> Result`

Types:

- Event = term()
- StateName = atom()
- StateData = term()
- Result = {next\_state, NextStateName, NewStateData} | {next\_state, NextStateName, NewStateData, Timeout} | {stop, Reason, NewStateData}
- NextStateName = atom()
- NewStateData = term()
- Timeout = int()>0 | infinity
- Reason = term()

Whenever a `gen_fsm` receives an event sent using `gen_fsm:send_all_state_event/2` [page 188], this function is called to handle the event.

`StateName` is the current state name of the `gen_fsm`.

See `Module:StateName/2` for a description of the other arguments and possible return values.

Module:StateName(Event, From, StateData) -> Result

Types:

- Event = term()
- From = {pid(), Tag}
- StateData = term()
- Result = {reply, Reply, NextStateName, NewStateData} | {reply, Reply, NextStateName, NewStateData, Timeout}
- | {next\_state, NextStateName, NewStateData} | {next\_state, NextStateName, NewStateData, Timeout}
- | {stop, Reason, Reply, NewStateData} | {stop, Reason, NewStateData}
- Reply = term()
- NextStateName = atom()
- NewStateData = term()
- Timeout = int()>0 | infinity
- Reason = normal | term()

There should be one instance of this function for each possible state name. Whenever a gen\_fsm receives an event sent using gen\_fsm:sync\_send\_event/2,3 [page 188], the instance of this function with the same name as the current state name StateName is called to handle the event.

Event is the Event argument provided to sync\_send\_event.

From is a tuple {Pid, Tag} where Pid is the pid of the process which called sync\_send\_event/2,3 and Tag is a unique tag.

StateData is the state data of the gen\_fsm.

If the function returns {reply, Reply, NextStateName, NewStateData} or {reply, Reply, NextStateName, NewStateData, Timeout}, Reply will be given back to From as the return value of sync\_send\_event/2,3. The gen\_fsm then continues executing with the current state name set to NextStateName and with the possibly updated state data NewStateData. See Module:init/1 for a description of Timeout.

If the function returns {next\_state, NextStateName, NewStateData} or {next\_state, NextStateName, NewStateData, Timeout}, the gen\_fsm will continue executing in NextStateName with NewStateData. Any reply to From must be given explicitly using gen\_fsm:reply/2 [page 189].

If the function returns {stop, Reason, Reply, NewStateData}, Reply will be given back to From. If the function returns {stop, Reason, NewStateData}, any reply to From must be given explicitly using gen\_fsm:reply/2. The gen\_fsm will then call Module:terminate(Reason, NewStateData) and terminate.

Module:handle\_sync\_event(Event, From, StateName, StateData) -> Result

Types:

- Event = term()
- From = {pid(), Tag}
- StateName = atom()
- StateData = term()
- Result = {reply, Reply, NextStateName, NewStateData} | {reply, Reply, NextStateName, NewStateData, Timeout}

- | {next\_state,NextStateName,NewStateData} | {next\_state,NextStateName,NewStateData,Timeout}
- | {stop,Reason,Reply,NewStateData} | {stop,Reason,NewStateData}
- Reply = term()
- NextStateName = atom()
- NewStateData = term()
- Timeout = int()>0 | infinity
- Reason = term()

Whenever a gen\_fsm receives an event sent using gen\_fsm:sync\_send\_all\_state\_event/2,3 [page 188], this function is called to handle the event.

StateName is the current state name of the gen\_fsm.

See Module:StateName/3 for a description of the other arguments and possible return values.

Module:handle\_info(Info, StateName, StateData) -> Result

Types:

- Info = term()
- StateName = atom()
- StateData = term()
- Result = {next\_state,NextStateName,NewStateData} | {next\_state,NextStateName,NewStateData,Timeout} | {stop,Reason,NewStateData}
- NextStateName = atom()
- NewStateData = term()
- Timeout = int()>0 | infinity
- Reason = normal | term()

This function is called by a gen\_fsm when it receives any other message than a synchronous or asynchronous event (or a system message).

Info is the received message.

See Module:StateName/2 for a description of the other arguments and possible return values.

Module:terminate(Reason, StateName, StateData)

Types:

- Reason = normal | shutdown | term()
- StateName = atom()
- StateData = term()

This function is called by a gen\_fsm when it is about to terminate. It should be the opposite of Module:init/1 and do any necessary cleaning up. When it returns, the gen\_fsm terminates with Reason. The return value is ignored.

Reason is a term denoting the stop reason, StateName is the current state name, and StateData is the state data of the gen\_fsm.

Reason depends on why the gen\_fsm is terminating. If it is because another callback function has returned a stop tuple {stop, . . .}, Reason will have the value specified in that tuple. If it is due to a failure, Reason is the error reason.

If the `gen_fsm` is part of a supervision tree and is ordered by its supervisor to terminate, this function will be called with `Reason=shutdown` if the following conditions apply:

- the `gen_fsm` has been set to trap exit signals, and
- the shutdown strategy as defined in the supervisor's child specification is an integer timeout value, not `brutal_kill`.

Otherwise, the `gen_fsm` will be immediately terminated.

Note that for any other reason than `normal` or `shutdown`, the `gen_fsm` is assumed to terminate due to an error and an error report is issued using `[error_logger:format/2]`.

```
Module:code_change(OldVsn, StateName, StateData, Extra) -> {ok, NextStateName,
NewStateData}
```

Types:

- `OldVsn = Vsn | {down, Vsn}`
- `Vsn = term()`
- `StateName = NextStateName = atom()`
- `StateData = NewStateData = term()`
- `Extra = term()`

This function is called by a `gen_fsm` when it should update its internal state data during a release upgrade/downgrade, i.e. when the instruction `{update,Module,Change,...}` where `Change={advanced,Extra}` is given in the appup file. See [OTP Design Principles].

In the case of an upgrade, `OldVsn` is `Vsn`, and in the case of a downgrade, `OldVsn` is `{down,Vsn}`. `Vsn` is defined by the `vsn` attribute(s) of the old version of the callback module `Module`. If no such attribute is defined, the version is the checksum of the BEAM file.

`StateName` is the current state name and `StateData` the internal state data of the `gen_fsm`.

`Extra` is passed as-is from the `{advanced,Extra}` part of the update instruction.

The function should return the new current state name and updated internal data.

## SEE ALSO

`gen_event(3)` [page 175], `gen_server(3)` [page 196], `supervisor(3)` [page 347], `proc_lib(3)` [page 263], `sys(3)` [page 357]

# gen\_server

Erlang Module

A behaviour module for implementing the server of a client-server relation. A generic server process (`gen_server`) implemented using this module will have a standard set of interface functions and include functionality for tracing and error reporting. It will also fit into an OTP supervision tree. Refer to [OTP Design Principles] for more information.

A `gen_server` assumes all specific parts to be located in a callback module exporting a pre-defined set of functions. The relationship between the behaviour functions and the callback functions can be illustrated as follows:

<code>gen_server</code> module	Callback module
-----	-----
<code>gen_server:start_link</code>	-----> <code>Module:init/1</code>
<code>gen_server:call</code>	
<code>gen_server:multi_call</code>	-----> <code>Module:handle_call/3</code>
<code>gen_server:cast</code>	
<code>gen_server:abcast</code>	-----> <code>Module:handle_cast/2</code>
-	-----> <code>Module:handle_info/2</code>
-	-----> <code>Module:terminate/2</code>
-	-----> <code>Module:code_change/3</code>

If a callback function fails or returns a bad value, the `gen_server` will terminate.

The `sys` module can be used for debugging a `gen_server`.

Note that a `gen_server` does not trap exit signals automatically, this must be explicitly initiated in the callback module.

Unless otherwise stated, all functions in this module fail if the specified `gen_server` does not exist or if bad arguments are given.

## Exports

```
start_link(Module, Args, Options) -> Result
start_link(ServerName, Module, Args, Options) -> Result
```

Types:

- `ServerName` = `{local,Name}` | `{global,GlobalName}`
- `Name` = `atom()`

- GlobalName = term()
- Module = atom()
- Args = term()
- Options = [Option]
- Option = {debug,Dbgs} | {timeout,Time} | {spawn\_opt,SOpts}
- Dbgs = [Dbg]
- Dbg = trace | log | statistics | {log\_to\_file,FileName} | {install,{Func,FuncState}}
- SOpts = [term()]
- Result = {ok,Pid} | ignore | {error,Error}
- Pid = pid()
- Error = {already\_started,Pid} | term()

Creates a `gen_server` process as part of a supervision tree. The function should be called, directly or indirectly, by the supervisor. It will, among other things, ensure that the `gen_server` is linked to the supervisor.

The `gen_server` process calls `Module:init/1` to initialize. To ensure a synchronized start-up procedure, `start_link/3,4` does not return until `Module:init/1` has returned.

If `ServerName={local,Name}` the `gen_server` is registered locally as `Name` using `register/2`. If `ServerName={global,GlobalName}` the `gen_server` is registered globally as `GlobalName` using `global:register_name/2`. If no name is provided, the `gen_server` is not registered.

`Module` is the name of the callback module.

`Args` is an arbitrary term which is passed as the argument to `Module:init/1`.

If the option `{timeout,Time}` is present, the `gen_server` is allowed to spend `Time` milliseconds initializing or it will be terminated and the start function will return `{error,timeout}`.

If the option `{debug,Dbgs}` is present, the corresponding `sys` function will be called for each item in `Dbgs`. See `sys(3)` [page 357].

If the option `{spawn_opt,SOpts}` is present, `SOpts` will be passed as option list to the `spawn_opt` BIF which is used to spawn the `gen_server`. See `[erlang(3)]`.

### Note:

Using the spawn option `monitor` is currently not allowed, but will cause the function to fail with reason `badarg`.

If the `gen_server` is successfully created and initialized the function returns `{ok,Pid}`, where `Pid` is the pid of the `gen_server`. If there already exists a process with the specified `ServerName` the function returns `{error,{already_started,Pid}}`, where `Pid` is the pid of that process.

If `Module:init/1` fails with `Reason`, the function returns `{error,Reason}`. If `Module:init/1` returns `{stop,Reason}` or `ignore`, the process is terminated and the function returns `{error,Reason}` or `ignore`, respectively.

```
start(Module, Args, Options) -> Result
start(ServerName, Module, Args, Options) -> Result
```

Types:

- `ServerName = {local,Name} | {global,GlobalName}`
- `Name = atom()`
- `GlobalName = term()`
- `Module = atom()`
- `Args = term()`
- `Options = [Option]`
- `Option = {debug,Dbgs} | {timeout,Time} | {spawn_opt,SOpts}`
- `Dbgs = [Dbg]`
- `Dbg = trace | log | statistics | {log_to_file,FileName} | {install,{Func,FuncState}}`
- `SOpts = [term()]`
- `Result = {ok,Pid} | ignore | {error,Error}`
- `Pid = pid()`
- `Error = {already_started,Pid} | term()`

Creates a stand-alone `gen_server` process, i.e. a `gen_server` which is not part of a supervision tree and thus has no supervisor.

See [start\\_link/3,4](#) [page 196] for a description of arguments and return values.

```
call(ServerRef, Request) -> Reply
```

```
call(ServerRef, Request, Timeout) -> Reply
```

Types:

- `ServerRef = Name | {Name,Node} | {global,GlobalName} | pid()`
- `Node = atom()`
- `GlobalName = term()`
- `Request = term()`
- `Timeout = int()>0 | infinity`
- `Reply = term()`

Makes a synchronous call to the `gen_server` `ServerRef` by sending a request and waiting until a reply arrives or a timeout occurs. The `gen_server` will call `Module:handle_call/3` to handle the request.

`ServerRef` can be:

- the `pid`,
- `Name`, if the `gen_server` is locally registered,
- `{Name,Node}`, if the `gen_server` is locally registered at another node, or
- `{global,GlobalName}`, if the `gen_server` is globally registered.

`Request` is an arbitrary term which is passed as one of the arguments to `Module:handle_call/3`.

`Timeout` is an integer greater than zero which specifies how many milliseconds to wait for a reply, or the atom `infinity` to wait indefinitely. Default value is 5000. If no reply is received within the specified time, the function call fails.

The return value `Reply` is defined in the return value of `Module:handle_call/3`.

The call may fail for several reasons, including timeout and the called `gen_server` dying before or during the call.

There is a special case for backwards compatibility. If

- the client is linked to the gen server, and
- the client is trapping exits, and
- the gen\_server terminates while handling the request

then the exit message is removed from the client's receive queue before the function call fails. This special-case behaviour may be removed in the future because it is inconsistent with the behaviour when a gen\_server dies between calls and also because the exit message cannot be removed in some circumstances, for instance when `ServerRef = {Name,Node}` and `Node` goes down.

```
multi_call(Name, Request) -> Result
multi_call(Nodes, Name, Request) -> Result
multi_call(Nodes, Name, Request, Timeout) -> Result
```

Types:

- `Nodes = [Node]`
- `Node = atom()`
- `Name = atom()`
- `Request = term()`
- `Timeout = int()>=0 | infinity`
- `Result = {Replies,BadNodes}`
- `Replies = [{Node,Reply}]`
- `Reply = term()`
- `BadNodes = [Node]`

Makes a synchronous call to all gen\_servers locally registered as `Name` at the specified nodes by first sending a request to every node and then waiting for the replies. The gen\_servers will call `Module:handle_call/3` to handle the request.

The function returns a tuple `{Replies,BadNodes}` where `Replies` is a list of `{Node,Reply}` and `BadNodes` is a list of node that either did not exist, or where the gen\_server `Name` did not exist or did not reply.

`Nodes` is a list of node names to which the request should be sent. Default value is the list of all known nodes `[node()|nodes()]`.

`Name` is the locally registered name of each gen\_server.

`Request` is an arbitrary term which is passed as one of the arguments to `Module:handle_call/3`.

`Timeout` is an integer greater than zero which specifies how many milliseconds to wait for each reply, or the atom `infinity` to wait indefinitely. Default value is `infinity`. If no reply is received from a node within the specified time, the node is added to `BadNodes`.

When a reply `Reply` is received from the gen\_server at a node `Node`, `{Node,Reply}` is added to `Replies`. `Reply` is defined in the return value of `Module:handle_call/3`.

### Warning:

If one of the nodes is running Erlang/OTP R6B or older, and the gen\_server is not started when the requests are sent, but starts within 2 seconds, this function waits the whole `Timeout`, which may be infinity.

This problem does not exist if all nodes are running Erlang/OTP R7B or later.

This function does *not* read out any exit messages like `call/2,3` does.

The previously undocumented functions `safe_multi_call/2,3,4` were removed in OTP R7B/Erlang 5.0 since this function is now safe, except in the case mentioned above.

To avoid that late answers (after the timeout) pollutes the caller's message queue, a middleman process is used to do the actual calls. Late answers will then be discarded when they arrive to a terminated process.

```
cast(ServerRef, Request) -> ok
```

Types:

- `ServerRef` = `Name` | `{Name,Node}` | `{global,GlobalName}` | `pid()`
- `Node` = `atom()`
- `GlobalName` = `term()`
- `Request` = `term()`

Sends an asynchronous request to the `gen_server` `ServerRef` and returns `ok` immediately, ignoring if the destination node or `gen_server` does not exist. The `gen_server` will call `Module:handle_cast/2` to handle the request.

See `call/2,3` [page 198] for a description of `ServerRef`.

`Request` is an arbitrary term which is passed as one of the arguments to `Module:handle_cast/2`.

```
abcast(Name, Request) -> abcast
```

```
abcast(Nodes, Name, Request) -> abcast
```

Types:

- `Nodes` = `[Node]`
- `Node` = `atom()`
- `Name` = `atom()`
- `Request` = `term()`

Sends an asynchronous request to the `gen_servers` locally registered as `Name` at the specified nodes. The function returns immediately and ignores nodes that does not exist, or where the `gen_server` `Name` does not exist. The `gen_servers` will call `Module:handle_cast/2` to handle the request.

See `multi_call/2,3,4` [page 199] for a description of the arguments.

```
reply(Client, Reply) -> true
```

Types:

- `Client` - see below
- `Reply` = `term()`

This function can be used by a `gen_server` to explicitly send a reply to a client that called `call/2,3` or `multi_call/2,3,4`, when the reply cannot be defined in the return value of `Module:handle_call/3`.

`Client` must be the `From` argument provided to the callback function. `Reply` is an arbitrary term, which will be given back to the client as the return value of `call/2,3` or `multi_call/2,3,4`.

```
enter_loop(Module, Options, State)
enter_loop(Module, Options, State, ServerName)
enter_loop(Module, Options, State, Timeout)
enter_loop(Module, Options, State, ServerName, Timeout)
```

Types:

- Module = atom()
- Options = [Option]
- Option = {debug,Dbgs}
- Dbgs = [Dbg]
- Dbg = trace | log | statistics
- | {log\_to\_file,FileName} | {install,{Func,FuncState}}
- State = term()
- ServerName = {local,Name} | {global,GlobalName}
- Name = atom()
- GlobalName = term()
- Timeout = int() | infinity

Makes an existing process into a `gen_server`. Does not return, instead the calling process will enter the `gen_server` receive loop and become a `gen_server` process. The process *must* have been started using one of the start functions in `proc_lib`, see `proc_lib(3)` [page 263]. The user is responsible for any initialization of the process, including registering a name for it.

This function is useful when a more complex initialization procedure is needed than the `gen_server` behaviour provides.

`Module`, `Options` and `ServerName` have the same meanings as when calling `gen_server:start[_link]/3,4` [page 196]. However, if `ServerName` is specified, the process must have been registered accordingly *before* this function is called.

`State` and `Timeout` have the same meanings as in the return value of `Module:init/1` [page 202]. Also, the callback module `Module` does not need to export an `init/1` function.

Failure: If the calling process was not started by a `proc_lib` start function, or if it is not registered according to `ServerName`.

## CALLBACK FUNCTIONS

The following functions should be exported from a `gen_server` callback module.

## Exports

`Module:init(Args) -> Result`

Types:

- `Args = term()`
- `Result = {ok,State} | {ok,State,Timeout}`
- `| {stop,Reason} | ignore`
- `State = term()`
- `Timeout = int()>=0 | infinity`
- `Reason = term()`

Whenever a `gen_server` is started using `gen_server:start/3,4` [page 197] or `gen_server:start_link/3,4` [page 196], this function is called by the new process to initialize.

`Args` is the `Args` argument provided to the start function.

If the initialization is successful, the function should return `{ok,State}` or `{ok,State,Timeout}`, where `State` is the internal state of the `gen_server`.

If an integer timeout value is provided, a timeout will occur unless a request or a message is received within `Timeout` milliseconds. A timeout is represented by the atom `timeout` which should be handled by the `handle_info/2` callback function. The atom `infinity` can be used to wait indefinitely, this is the default value.

If something goes wrong during the initialization the function should return `{stop,Reason}` where `Reason` is any term, or `ignore`.

`Module:handle_call(Request, From, State) -> Result`

Types:

- `Request = term()`
- `From = {pid(),Tag}`
- `State = term()`
- `Result = {reply,Reply,NewState} | {reply,Reply,NewState,Timeout}`
- `| {noreply,NewState} | {noreply,NewState,Timeout}`
- `| {stop,Reason,Reply,NewState} | {stop,Reason,NewState}`
- `Reply = term()`
- `NewState = term()`
- `Timeout = int()>=0 | infinity`
- `Reason = term()`

Whenever a `gen_server` receives a request sent using `gen_server:call/2,3` [page 198] or `gen_server:multi_call/2,3,4` [page 199], this function is called to handle the request.

`Request` is the `Request` argument provided to `call` or `multi_call`.

`From` is a tuple `{Pid,Tag}` where `Pid` is the pid of the client and `Tag` is a unique tag.

`State` is the internal state of the `gen_server`.

If the function returns `{reply,Reply,NewState}` or `{reply,Reply,NewState,Timeout}`, `Reply` will be given back to `From` as the return value of `call/2,3` or included in the return value of `multi_call/2,3,4`. The `gen_server`

then continues executing with the possibly updated internal state `NewState`. See `Module:init/1` for a description of `Timeout`.

If the function returns `{noreply, NewState}` or `{noreply, NewState, Timeout}`, the `gen_server` will continue executing with `NewState`. Any reply to `From` must be given explicitly using `gen_server:reply/2` [page 200].

If the function returns `{stop, Reason, Reply, NewState}`, `Reply` will be given back to `From`. If the function returns `{stop, Reason, NewState}`, any reply to `From` must be given explicitly using `gen_server:reply/2`. The `gen_server` will then call `Module:terminate(Reason, NewState)` and terminate.

`Module:handle_cast(Request, State) -> Result`

Types:

- `Request = term()`
- `State = term()`
- `Result = {noreply, NewState} | {noreply, NewState, Timeout}`
- `| {stop, Reason, NewState}`
- `NewState = term()`
- `Timeout = int() >= 0 | infinity`
- `Reason = term()`

Whenever a `gen_server` receives a request sent using `gen_server:cast/2` [page 200] or `gen_server:abcast/2,3` [page 200], this function is called to handle the request.

See `Module:handle_call/3` for a description of the arguments and possible return values.

`Module:handle_info(Info, State) -> Result`

Types:

- `Info = timeout | term()`
- `State = term()`
- `Result = {noreply, NewState} | {noreply, NewState, Timeout}`
- `| {stop, Reason, NewState}`
- `NewState = term()`
- `Timeout = int() >= 0 | infinity`
- `Reason = normal | term()`

This function is called by a `gen_server` when a timeout occurs or when it receives any other message than a synchronous or asynchronous request (or a system message).

`Info` is either the atom `timeout`, if a timeout has occurred, or the received message.

See `Module:handle_call/3` for a description of the other arguments and possible return values.

`Module:terminate(Reason, State)`

Types:

- `Reason = normal | shutdown | term()`
- `State = term()`

This function is called by a `gen_server` when it is about to terminate. It should be the opposite of `Module:init/1` and do any necessary cleaning up. When it returns, the `gen_server` terminates with `Reason`. The return value is ignored.

`Reason` is a term denoting the stop reason and `State` is the internal state of the `gen_server`.

`Reason` depends on why the `gen_server` is terminating. If it is because another callback function has returned a stop tuple `{stop, . . .}`, `Reason` will have the value specified in that tuple. If it is due to a failure, `Reason` is the error reason.

If the `gen_server` is part of a supervision tree and is ordered by its supervisor to terminate, this function will be called with `Reason=shutdown` if the following conditions apply:

- the `gen_server` has been set to trap exit signals, and
- the shutdown strategy as defined in the supervisor's child specification is an integer timeout value, not `brutal_kill`.

Otherwise, the `gen_server` will be immediately terminated.

Note that for any other reason than `normal` or `shutdown`, the `gen_server` is assumed to terminate due to an error and an error report is issued using `[error_logger:format/2]`.

```
Module:code_change(OldVsn, State, Extra) -> {ok, NewState}
```

Types:

- `OldVsn = Vsn | {down, Vsn}`
- `Vsn = term()`
- `State = NewState = term()`
- `Extra = term()`

This function is called by a `gen_server` when it should update its internal state during a release upgrade/downgrade, i.e. when the instruction `{update, Module, Change, . . .}` where `Change={advanced, Extra}` is given in the appup file. See [OTP Design Principles] for more information.

In the case of an upgrade, `OldVsn` is `Vsn`, and in the case of a downgrade, `OldVsn` is `{down, Vsn}`. `Vsn` is defined by the `vsn` attribute(s) of the old version of the callback module `Module`. If no such attribute is defined, the version is the checksum of the BEAM file.

`State` is the internal state of the `gen_server`.

`Extra` is passed as-is from the `{advanced, Extra}` part of the update instruction.

The function should return the updated internal state.

## SEE ALSO

`gen_event(3)` [page 175], `gen_fsm(3)` [page 185], `supervisor(3)` [page 347], `proc_lib(3)` [page 263], `sys(3)` [page 357]

# io

Erlang Module

This module provides an interface to standard Erlang IO servers. The output functions all return `ok` if they are successful, or `exit` if they are not.

In the following description, all functions have an optional parameter `IoDevice`. If included, it must be the pid of a process which handles the IO protocols. Normally, it is the `IoDevice` returned by `[file:open/2]`.

For a description of the IO protocols refer to Armstrong, Virding and Williams, 'Concurrent Programming in Erlang', Chapter 13, unfortunately now very outdated, but the general principles still apply.

## DATA TYPES

`io_device()`

as returned by `file:open/2`, a process handling IO protocols

## Exports

`put_chars([IoDevice,] IoData) -> ok`

Types:

- `IoDevice = io_device()`
- `IoData = iodata()` – see `erlang(3)`

Writes the characters of `IoData` to the standard output (`IoDevice`).

`nl([IoDevice]) -> ok`

Types:

- `IoDevice = io_device()`

Writes new line to the standard output (`IoDevice`).

`get_chars([IoDevice,] Prompt, Count) -> string() | eof`

Types:

- `IoDevice = io_device()`
- `Prompt = atom() | string()`
- `Count = int()`

Reads `Count` characters from standard input (`IoDevice`), prompting it with `Prompt`. It returns:

String The input characters.  
 eof End of file was encountered.

```
get_line([IODevice,] Prompt) -> string() | eof
```

Types:

- IoDevice = io\_device()
- Prompt = atom() | string()

Reads a line from the standard input (IoDevice), prompting it with Prompt. It returns:

String The characters in the line terminated by a LF (or end of file).  
 eof End of file was encountered.

```
setopts([IODevice,] Opts) -> ok | {error, Reason}
```

Types:

- IoDevice = io\_device()
- Opts = [Opt]
- Opt = binary | list
- Reason = term()

Set options for standard input/output (IoDevice). Possible options are:

binary Makes get\_chars/2,3 and get\_line/1,2 return binaries instead of lists of chars.

list Makes get\_chars/2,3 and get\_line/1,2 return lists of chars, which is the default.

expand\_fun Provide a function for tab-completion (expansion) like the erlang shell. This function is called when the user presses the Tab key. The expansion is active when calling line-reading functions such as get\_line/1,2.

The function is called with the current line, upto the cursor, as a reversed string. It should return a three-tuple: {yes|no, string(), [string(), ...]}. The first element gives a beep if no, otherwise the expansion is silent, the second is a string that will be entered at the cursor position, and the third is a list of possible expansions. If this list is non-empty, the list will be printed and the current input line will be written once again.

Trivial example (beep on anything except empty line, which is expanded to "quit"):

```
fun("") -> {yes, "quit", []};
  (_) -> {no, "", ["quit"]} end
```

### Note:

The binary option does not work against IO servers on remote nodes running an older version of Erlang/OTP than R9C.

```
write([IODevice,] Term) -> ok
```

Types:

- IoDevice = io\_device()
- Term = term()

Writes the term Term to the standard output (IoDevice).

```
read([IoDevice,] Prompt) -> Result
```

Types:

- IoDevice = io\_device()
- Prompt = atom() | string()
- Result = {ok, Term} | eof | {error, ErrorInfo}
- Term = term()
- ErrorInfo – see section Error Information below

Reads a term Term from the standard input (IoDevice), prompting it with Prompt. It returns:

{ok, Term} The parsing was successful.

eof End of file was encountered.

{error, ErrorInfo} The parsing failed.

```
read(IoDevice, Prompt, StartLine) -> Result
```

Types:

- IoDevice = io\_device()
- Prompt = atom() | string()
- StartLine = int()
- Result = {ok, Term, EndLine} | {eof, EndLine} | {error, ErrorInfo, EndLine}
- Term = term()
- EndLine = int()
- ErrorInfo – see section Error Information below

Reads a term Term from IoDevice, prompting it with Prompt. Reading starts at line number StartLine. It returns:

{ok, Term, EndLine} The parsing was successful.

{eof, EndLine} End of file was encountered.

{error, ErrorInfo, EndLine} The parsing failed.

```
fwrite(Format) ->
```

```
fwrite([IoDevice,] Format, Data) -> ok
```

```
format(Format) ->
```

```
format([IoDevice,] Format, Data) -> ok
```

Types:

- IoDevice = io\_device()
- Format = atom() | string() | binary()
- Data = [term()]

Writes the items in `Data` (`[]`) on the standard output (`IoDevice`) in accordance with `Format`. `Format` contains plain characters which are copied to the output device, and control sequences for formatting, see below. If `Format` is an atom or a binary, it is first converted to a list with the aid of `atom_to_list/1` or `binary_to_list/1`.

```
1> io:fwrite("Hello world!~n", []).
Hello world!
ok
```

The general format of a control sequence is `~F.P.PadC`. The character `C` determines the type of control sequence to be used, `F` and `P` are optional numeric arguments. If `F`, `P`, or `Pad` is `*`, the next argument in `Data` is used as the numeric value of `F` or `P`.

`F` is the *field width* of the printed argument. A negative value means that the argument will be left justified within the field, otherwise it will be right justified. If no field width is specified, the required print width will be used. If the field width specified is too small, then the whole field will be filled with `*` characters.

`P` is the *precision* of the printed argument. A default value is used if no precision is specified. The interpretation of precision depends on the control sequences. Unless otherwise specified, the argument `within` is used to determine print width.

`Pad` is the *padding character*. This is the character used to pad the printed representation of the argument so that it conforms to the specified field width and precision. Only one padding character can be specified and, whenever applicable, it is used for both the field width and precision. The default padding character is `' '` (space).

The following control sequences are available:

`~` The character `~` is written.

`c` The argument is a number that will be interpreted as an ASCII code. The precision is the number of times the character is printed and it defaults to the field width, which in turn defaults to 1. The following example illustrates:

```
2> io:fwrite("|~10.5c|~-10.5c|~5c|~n", [$a, $b, $c]).
|   aaaaa|bbbbbb   |ccccc|
ok
```

`f` The argument is a float which is written as `[-]ddd.ddd`, where the precision is the number of digits after the decimal point. The default precision is 6 and it cannot be less than 1.

`e` The argument is a float which is written as `[-]d.ddde+-ddd`, where the precision is the number of digits written. The default precision is 6 and it cannot be less than 2.

`g` The argument is a float which is written as `f`, if it is  $\geq 0.1$  and  $< 10000.0$ . Otherwise, it is written in the `e` format. The precision is the number of significant digits. It defaults to 6 and should not be less than 2. If the absolute value of the float does not allow it to be written in the `f` format with the desired number of significant digits, it is also written in the `e` format.

`s` Prints the argument with the `string` syntax. The argument is an `[I/O list]`, a binary, or an atom. The characters are printed without quotes. In this format, the printed argument is truncated to the given precision and field width.

This format can be used for printing any object and truncating the output so it fits a specified field:

```

3> io:fwrite("|~10w|~n", [{hey, hey, hey}]).
|*****|
ok
4> io:fwrite("|~10s|~n", [io_lib:write({hey, hey, hey})]).
|{hey,hey,h|
ok

```

- w Writes data with the standard syntax. This is used to output Erlang terms. Atoms are printed within quotes if they contain embedded non-printable characters, and floats are printed in the default g format.
- p Writes the data with standard syntax in the same way as ~w, but breaks terms whose printed representation is longer than one line into many lines and indents each line sensibly. It also tries to detect lists of printable characters and to output these as strings. For example:

```

5> T = [{attributes, [{id, age, 1.50000}, {mode, explicit},
{typename, "INTEGER"}], [{id, cho}, {mode, explicit}, {typename, 'Cho'}]],
{typename, 'Person'}, {tag, {'PRIVATE', 3}}, {mode, implicit}].
...
6> io:fwrite("~w~n", [T]).
[{attributes, [{id, age, 1.50000}, {mode, explicit}, {typename,
[73,78,84,69,71,69,82]}], [{id, cho}, {mode, explicit}, {typena
me, 'Cho'}]], {typename, 'Person'}, {tag, {'PRIVATE', 3}}, {mode
, implicit}]
ok
7> io:fwrite("~62p~n", [T]).
[{attributes, [{id, age, 1.50000},
{mode, explicit},
{typename, "INTEGER"}],
[{id, cho}, {mode, explicit}, {typename, 'Cho'}]],
{typename, 'Person'},
{tag, {'PRIVATE', 3}},
{mode, implicit}]
ok

```

The field width specifies the maximum line length. It defaults to 80. The precision specifies the initial indentation of the term. It defaults to the number of characters printed on this line in the same call to `io:fwrite` or `io:format`. For example, using T above:

```

8> io:fwrite("Here T = ~62p~n", [T]).
Here T = [{attributes, [{id, age, 1.50000},
{mode, explicit},
{typename, "INTEGER"}],
[{id, cho},
{mode, explicit},
{typename, 'Cho'}]],
{typename, 'Person'},
{tag, {'PRIVATE', 3}},
{mode, implicit}]

```

ok

- W Writes data in the same way as `~w`, but takes an extra argument which is the maximum depth to which terms are printed. Anything below this depth is replaced with `...`. For example, using `T` above:

```
9> io:fwrite("~W~n", [T,9]).
[attributes,[[{id,age,1.50000},{mode,explicit},{typename,
...}],[{id,cho},{mode,...},{...}]]],{typename,'Person'},{t
ag,{'PRIVATE',3}},{mode,implicit}]
ok
```

If the maximum depth has been reached, then it is impossible to read in the resultant output. Also, the `,...` form in a tuple denotes that there are more elements in the tuple but these are below the print depth.

- P Writes data in the same way as `~p`, but takes an extra argument which is the maximum depth to which terms are printed. Anything below this depth is replaced with `...`. For example:

```
10> io:fwrite("~62P~n", [T,9]).
[attributes,[[{id,age,1.50000},
                {mode,explicit},
                {typename,...}],
                [{id,cho},{mode,...},{...}]]],
{typename,'Person'},
{tag,{'PRIVATE',3}},
{mode,implicit}]
ok
```

- B Writes an integer in base 2..36, the default base is 10. A leading dash is printed for negative integers.

The precision field selects base. For example:

```
11> io:fwrite("~.16B~n", [31]).
1F
ok
12> io:fwrite("~.2B~n", [-19]).
-10011
ok
13> io:fwrite("~.36B~n", [5*36+35]).
5Z
ok
```

- X Like B, but takes an extra argument that is a prefix to insert before the number, but after the leading dash, if any.

The prefix can be a possibly deep list of characters or an atom.

```

14> io:fwrite("~X~n", [31,"10#"]).
10#31
ok
15> io:fwrite("~.16X~n", [-31,"0x"]).
-0x1F
ok

```

# Like B, but prints the number with an Erlang style '#'-separated base prefix.

```

16> io:fwrite("~.10#~n", [31]).
10#31
ok
17> io:fwrite("~.16#~n", [-31]).
-16#1F
ok

```

- b Like B, but prints lowercase letters.
- x Like X, but prints lowercase letters.
- + Like #, but prints lowercase letters.
- n Writes a new line.
- i Ignores the next term.

Returns:

ok The formatting succeeded.

If an error occurs, there is no output. For example:

```

18> io:fwrite("~s ~w ~i ~w ~c ~n", ['abc def', 'abc def', {foo, 1},{foo, 1}, 65]).
abc def 'abc def' {foo,1} A
ok
19> io:fwrite("~s", [65]).
** exited: {badarg, [{io,format,[<0.22.0>,"~s","A"]},
                    {erl_eval,do_apply,5},
                    {shell,exprs,6},
                    {shell,eval_loop,3}]} **

```

In this example, an attempt was made to output the single character '65' with the aid of the string formatting directive "~s".

The two functions `fwrite` and `format` are identical. The old name `format` has been retained for backwards compatibility, while the new name `fwrite` has been added as a logical complement to `fread`.

`fread([IoDevice,] Prompt, Format) -> Result`

Types:

- IoDevice = `io_device()`
- Prompt = `atom()` | `string()`
- Format = `string()`

- Result = {ok, Terms} | eof | {error, What}
- Terms = [term()]
- What = term()

Reads characters from the standard input (IoDevice), prompting it with Prompt. Interprets the characters in accordance with Format. Format contains control sequences which directs the interpretation of the input.

Format may contain:

- White space characters (SPACE, TAB and NEWLINE) which cause input to be read to the next non-white space character.
- Ordinary characters which must match the next input character.
- Control sequences, which have the general format `~*FC`. The character `*` is an optional return suppression character. It provides a method to specify a field which is to be omitted. `F` is the `field width` of the input field and `C` determines the type of control sequence.

Unless otherwise specified, leading white-space is ignored for all control sequences. An input field cannot be more than one line wide. The following control sequences are available:

- `~` A single `~` is expected in the input.
- `d` A decimal integer is expected.
- `u` An unsigned integer in base 2..36 is expected. The field width parameter is used to specify base. Leading white-space characters are not skipped.
- `-` An optional sign character is expected. A sign character `'-'` gives the return value `-1`. Sign character `'+'` or none gives `1`. The field width parameter is ignored. Leading white-space characters are not skipped.
- `#` An integer in base 2..36 with Erlang-style base prefix (for example `"16#ffff"`) is expected.
- `f` A floating point number is expected. It must follow the Erlang floating point number syntax.
- `s` A string of non-white-space characters is read. If a field width has been specified, this number of characters are read and all trailing white-space characters are stripped. An Erlang string (list of characters) is returned.
- `a` Similar to `s`, but the resulting string is converted into an atom.
- `c` The number of characters equal to the field width are read (default is 1) and returned as an Erlang string. However, leading and trailing white-space characters are not omitted as they are with `s`. All characters are returned.
- `l` Returns the number of characters which have been scanned up to that point, including white-space characters.

It returns:

- `{ok, Terms}` The read was successful and `Terms` is the list of successfully matched and read items.
- `eof` End of file was encountered.
- `{error, What}` The read operation failed and the parameter `What` gives a hint about the error.

Examples:

```

20> io:fread('enter>', "~f~f~f").
enter>1.9 35.5e3 15.0
{ok, [1.90000, 3.55000e+4, 15.0000]}
21> io:fread('enter>', "~10f~d").
enter>      5.67899
{ok, [5.67800, 99]}
22> io:fread('enter>', ":~10s:~10c:").
enter>:   alan   :   joe   :
{ok, ["alan", "   joe   "]}

```

scan\_erl\_exprs(Prompt) ->

scan\_erl\_exprs([IODevice,] Prompt, StartLine) -> Result

Types:

- IoDevice = io\_device()
- Prompt = atom() | string()
- StartLine = int()
- Result = {ok, Tokens, EndLine} | {eof, EndLine} | {error, ErrorInfo, EndLine}
- Tokens – see erl\_scan(3)
- EndLine = int()
- ErrorInfo – see section Error Information below

Reads data from the standard input (IODevice), prompting it with Prompt. Reading starts at line number StartLine (1). The data is tokenized as if it were a sequence of Erlang expressions until a final '.' is reached. This token is also returned. It returns:

{ok, Tokens, EndLine} The tokenization succeeded.

{eof, EndLine} End of file was encountered.

{error, ErrorInfo, EndLine} An error occurred.

Example:

```

23> io:scan_erl_exprs('enter>').
enter>abc(), "hey".
{ok, [{atom, 1, abc}, {'(', 1}, {'}', 1}, {' ', 1}, {'string', 1, "hey"}, {dot, 1}], 2}
24> io:scan_erl_exprs('enter>').
enter>1.0er.
{error, {1, erl_scan, {illegal, float}}, 2}

```

scan\_erl\_form(Prompt) ->

scan\_erl\_form([IODevice,] Prompt, StartLine) -> Result

Types:

- IoDevice = io\_device()
- Prompt = atom() | string()
- StartLine = int()
- Result = {ok, Tokens, EndLine} | {eof, EndLine} | {error, ErrorInfo, EndLine}
- Tokens – see erl\_scan(3)
- EndLine = int()

- `ErrorInfo` – see section Error Information below

Reads data from the standard input (`IoDevice`), prompting it with `Prompt`. Starts reading at line number `StartLine` (1). The data is tokenized as if it were an Erlang form - one of the valid Erlang expressions in an Erlang source file - until a final `'.'` is reached. This last token is also returned. The return values are the same as for `scan_erl_exprs/1,2,3` above.

```
parse_erl_exprs(Prompt) ->
```

```
parse_erl_exprs([IoDevice,] Prompt, StartLine) -> Result
```

Types:

- `IoDevice` = `io_device()`
- `Prompt` = `atom()` | `string()`
- `StartLine` = `int()`
- `Result` = `{ok, Expr_list, EndLine}` | `{eof, EndLine}` | `{error, ErrorInfo, EndLine}`
- `Expr_list` – see `erl_parse(3)`
- `EndLine` = `int()`
- `ErrorInfo` – see section Error Information below

Reads data from the standard input (`IoDevice`), prompting it with `Prompt`. Starts reading at line number `StartLine` (1). The data is tokenized and parsed as if it were a sequence of Erlang expressions until a final `'.'` is reached. It returns:

```
{ok, Expr_list, EndLine} The parsing was successful.
```

```
{eof, EndLine} End of file was encountered.
```

```
{error, ErrorInfo, EndLine} An error occurred.
```

Example:

```
25> io:parse_erl_exprs('enter>').
enter>abc(), "hey".
{ok, [{call,1,{atom,1,abc},[]},{string,1,"hey"}],2}
26> io:parse_erl_exprs ('enter>').
enter>abc("hey".
{error,{1,erl_parse,["syntax error before: ",["'.'"]]},2}
```

```
parse_erl_form(Prompt) ->
```

```
parse_erl_form([IoDevice,] Prompt, StartLine) -> Result
```

Types:

- `IoDevice` = `io_device()`
- `Prompt` = `atom()` | `string()`
- `StartLine` = `int()`
- `Result` = `{ok, AbsForm, EndLine}` | `{eof, EndLine}` | `{error, ErrorInfo, EndLine}`
- `AbsForm` – see `erl_parse(3)`
- `EndLine` = `int()`
- `ErrorInfo` – see section Error Information below

Reads data from the standard input (`IODevice`), prompting it with `Prompt`. Starts reading at line number `StartLine` (1). The data is tokenized and parsed as if it were an Erlang form - one of the valid Erlang expressions in an Erlang source file - until a final `'` is reached. It returns:

```
{ok, AbsForm, EndLine} The parsing was successful.  
{eof, EndLine} End of file was encountered.  
{error, ErrorInfo, EndLine} An error occurred.
```

## Standard Input/Output

All Erlang processes have a default standard IO device. This device is used when no `IODevice` argument is specified in the above function calls. However, it is sometimes desirable to use an explicit `IODevice` argument which refers to the default IO device. This is the case with functions that can access either a file or the default IO device. The atom `standard_io` has this special meaning. The following example illustrates this:

```
27> io:read('enter>').  
enter>foo.  
{ok,foo}  
28> io:read(standard_io, 'enter>').  
enter>bar.  
{ok,bar}
```

There is always a process registered under the name of `user`. This can be used for sending output to the user.

## Error Information

The `ErrorInfo` mentioned above is the standard `ErrorInfo` structure which is returned from all IO modules. It has the format:

```
{ErrorLine, Module, ErrorDescriptor}
```

A string which describes the error is obtained with the following call:

```
apply(Module, format_error, ErrorDescriptor)
```

# io\_lib

Erlang Module

This module contains functions for converting to and from strings (lists of characters). They are used for implementing the functions in the `io` module. There is no guarantee that the character lists returned from some of the functions are flat, they can be deep lists. `lists:flatten/1` can be used for flattening deep lists.

## DATA TYPES

`chars()` = [`char()` | `chars()`]

## Exports

`nl()` -> `chars()`

Returns a character list which represents a new line character.

`write(Term)` ->

`write(Term, Depth)` -> `chars()`

Types:

- `Term` = `term()`
- `Depth` = `int()`

Returns a character list which represents `Term`. The `Depth` (-1) argument controls the depth of the structures written. When the specified depth is reached, everything below this level is replaced by "...". For example:

```
1> lists:flatten(io_lib:write({1, [2], [3], [4,5], 6,7,8,9})).
"{1, [2], [3], [4,5], 6,7,8,9}"
2> lists:flatten(io_lib:write({1, [2], [3], [4,5], 6,7,8,9}, 5)).
"{1, [2], [3], [...], ...}"
```

`print(Term)` ->

`print(Term, Column, LineLength, Depth)` -> `chars()`

Types:

- `Term` = `term()`
- `Column` = `LineLength` = `Depth` = `int()`

Also returns a list of characters which represents `Term`, but breaks representations which are longer than one line into many lines and indents each line sensibly. It also tries to detect and output lists of printable characters as strings. `Column` is the starting column (1), `LineLength` the maximum line length (80), and `Depth` (-1) the maximum print depth.

```
fwrite(Format, Data) ->
format(Format, Data) -> chars()
```

Types:

- `Format` = `atom()` | `string()` | `binary()`
- `Data` = [`term()`]

Returns a character list which represents `Data` formatted in accordance with `Format`. See `io:fwrite/1,2,3` [page 207] for a detailed description of the available formatting options. A fault is generated if there is an error in the format string or argument list.

```
fread(Format, String) -> Result
```

Types:

- `Format` = `String` = `string()`
- `Result` = {`ok`, `InputList`, `LeftOverChars`} | {`more`, `RestFormat`, `Nchars`, `InputStack`} | {`error`, `What`}
- `InputList` = `chars()`
- `LeftOverChars` = `string()`
- `RestFormat` = `string()`
- `Nchars` = `int()`
- `InputStack` = `chars()`
- `What` = `term()`

Tries to read `String` in accordance with the control sequences in `Format`. See `io:fread/3` [page 211] for a detailed description of the available formatting options. It is assumed that `String` contains whole lines. It returns:

{`ok`, `InputList`, `LeftOverChars`} The string was read. `InputList` is the list of successfully matched and read items, and `LeftOverChars` are the input characters not used.

{`more`, `RestFormat`, `Nchars`, `InputStack`} The string was read, but more input is needed in order to complete the original format string. `RestFormat` is the remaining format string, `NChars` the number of characters scanned, and `InputStack` is the reversed list of inputs matched up to that point.

{`error`, `What`} The read operation failed and the parameter `What` gives a hint about the error.

Example:

```
3> io_lib:fread("~f~f~f", "15.6 17.3e-6 24.5").
{ok, [15.6000, 1.73000e-5, 24.5000], []}
```

```
fread(Continuation, String, Format) -> Return
```

Types:

- Continuation = see below
- String = Format = string()
- Return = {done, Result, LeftOverChars} | {more, Continuation}
- Result = {ok, InputList} | eof | {error, What}
- InputList = chars()
- What = term()
- LeftOverChars = string()

This is the re-entrant formatted reader. The continuation of the first call to the functions must be []. Refer to Armstrong, Viriding, Williams, 'Concurrent Programming in Erlang', Chapter 13 for a complete description of how the re-entrant input scheme works.

The function returns:

{done, Result, LeftOverChars} The input is complete. The result is one of the following:

{ok, InputList} The string was read. InputList is the list of successfully matched and read items, and LeftOverChars are the remaining characters.

eof End of file has been encountered. LeftOverChars are the input characters not used.

{error, What} An error occurred and the parameter What gives a hint about the error.

{more, Continuation} More data is required to build a term. Continuation must be passed to fread/3, when more data becomes available.

write\_atom(Atom) -> chars()

Types:

- Atom = atom()

Returns the list of characters needed to print the atom Atom.

write\_string(String) -> chars()

Types:

- String = string()

Returns the list of characters needed to print String as a string.

write\_char(Integer) -> chars()

Types:

- Integer = int()

Returns the list of characters needed to print a character constant.

indentation(String, StartIndent) -> int()

Types:

- String = string()
- StartIndent = int()

Returns the indentation if `String` has been printed, starting at `StartIndent`.

`char_list(Term) -> bool()`

Types:

- `Term = term()`

Returns true if `Term` is a flat list of characters, otherwise it returns false.

`deep_char_list(Term) -> bool()`

Types:

- `Term = term()`

Returns true if `Term` is a, possibly deep, list of characters, otherwise it returns false.

`printable_list(Term) -> bool()`

Types:

- `Term = term()`

Returns true if `Term` is a flat list of printable characters, otherwise it returns false.

# lib

Erlang Module

**Warning:**

This module is retained for compatibility. It may disappear without warning in a future release.

## Exports

`flush_receive() -> void()`

Flushes the message buffer of the current process.

`error_message(Format, Args) -> ok`

Types:

- `Format = atom() | string() | binary()`
- `Args = [term()]`

Prints error message `Args` in accordance with `Format`. Similar to `io:format/2`, see [io\(3\)](#) [page 207].

`progrname() -> atom()`

Returns the name of the script that started the current Erlang session.

`nonl(String1) -> String2`

Types:

- `String1 = String2 = string()`

Removes the last newline character, if any, in `String1`.

`send(To, Msg)`

Types:

- `To = pid() | Name | {Name,Node}`
- `Name = Node = atom()`
- `Msg = term()`

This function to makes it possible to send a message using the `apply/3` BIF.

`sendw(To, Msg)`

Types:

- `To = pid() | Name | {Name,Node}`
- `Name = Node = atom()`
- `Msg = term()`

As `send/2`, but waits for an answer. It is implemented as follows:

```
sendw(To, Msg) ->
  To ! {self(),Msg},
  receive
    Reply -> Reply
  end.
```

The message returned is not necessarily a reply to the message sent.

# lists

Erlang Module

This module contains functions for list processing. The functions are organized in two groups: those in the first group perform a particular operation on one or more lists, whereas those in the second group are higher-order functions, using a fun as argument to perform an operation on one list.

Unless otherwise stated, all functions assume that position numbering starts at 1. That is, the first element of a list is at position 1.

## Exports

`all(Pred, List) -> bool()`

Types:

- `Pred = fun(Elem) -> bool()`
- `Elem = term()`
- `List = [term()]`

Returns true if `Pred(Elem)` returns true for all elements `Elem` in `List`, otherwise false.

`any(Pred, List) -> bool()`

Types:

- `Pred = fun(Elem) -> bool()`
- `Elem = term()`
- `List = [term()]`

Returns true if `Pred(Elem)` returns true for at least one element `Elem` in `List`.

`append(ListOfLists) -> List1`

Types:

- `ListOfLists = [List]`
- `List = List1 = [term()]`

Returns a list in which all the sub-lists of `ListOfLists` have been appended. For example:

```
> lists:append([[1, 2, 3], [a, b], [4, 5, 6]]).  
[1,2,3,a,b,4,5,6]
```

`append(List1, List2) -> List3`

Types:

- `List1 = List2 = List3 = [term()]`

Returns a new list `List3` which is made from the elements of `List1` followed by the elements of `List2`. For example:

```
> lists:append("abc", "def").  
"abcdef"
```

`lists:append(A, B)` is equivalent to `A ++ B`.

`concat(Things) -> string()`

Types:

- `Things = [Thing]`
- `Thing = atom() | integer() | float() | string()`

Concatenates the text representation of the elements of `Things`. The elements of `Things` can be atoms, integers, floats or strings.

```
> lists:concat([doc, '/', file, '.', 3]).  
"doc/file.3"
```

`delete(Elem, List1) -> List2`

Types:

- `Elem = term()`
- `List1 = List2 = [term()]`

Returns a copy of `List1` where the first element matching `Elem` is deleted, if there is such an element.

`dropwhile(Pred, List1) -> List2`

Types:

- `Pred = fun(Elem) -> bool()`
- `Elem = term()`
- `List1 = List2 = [term()]`

Drops elements `Elem` from `List1` while `Pred(Elem)` returns `true` and returns the remaining list.

`duplicate(N, Elem) -> List`

Types:

- `N = int()`
- `Elem = term()`
- `List = [term()]`

Returns a list which contains `N` copies of the term `Elem`. For example:

```
> lists:duplicate(5, xx).  
[xx,xx,xx,xx,xx]
```

```
filter(Pred, List1) -> List2
```

Types:

- Pred = fun(Elem) -> bool()
- Elem = term()
- List1 = List2 = [term()]

List2 is a list of all elements Elem in List1 for which Pred(Elem) returns true.

```
flatlength(DeepList) -> int()
```

Types:

- DeepList = [term() | DeepList]

Equivalent to `length(flatten(DeepList))`, but more efficient.

```
flatmap(Fun, List1) -> List2
```

Types:

- Fun = fun(A) -> [B]
- List1 = [A]
- List2 = [B]
- A = B = term()

Takes a function from As to lists of Bs, and a list of As (List1) and produces a list of Bs by applying the function to every element in List1 and appending the resulting lists.

That is, flatmap behaves as if it had been defined as follows:

```
flatmap(Fun, List1) ->  
  append(map(Fun, List1))
```

Example:

```
> lists:flatmap(fun(X)->[X,X] end, [a,b,c]).  
[a,a,b,b,c,c]
```

```
flatten(DeepList) -> List
```

Types:

- DeepList = [term() | DeepList]
- List = [term()]

Returns a flattened version of DeepList.

```
flatten(DeepList, Tail) -> List
```

Types:

- DeepList = [term() | DeepList]
- Tail = List = [term()]

Returns a flattened version of DeepList with the tail Tail appended.

```
foldl(Fun, Acc0, List) -> Acc1
```

Types:

- Fun = fun(Elem, AccIn) -> AccOut

- Elem = term()
- Acc0 = Acc1 = AccIn = AccOut = term()
- List = [term()]

Calls Fun(Elem, AccIn) on successive elements A of List, starting with AccIn == Acc0. Fun/2 must return a new accumulator which is passed to the next call. The function returns the final value of the accumulator. Acc0 is returned if the list is empty. For example:

```
> lists:foldl(fun(X, Sum) -> X + Sum end, 0, [1,2,3,4,5]).
15
> lists:foldl(fun(X, Prod) -> X * Prod end, 1, [1,2,3,4,5]).
120
```

foldr(Fun, Acc0, List) -> Acc1

Types:

- Fun = fun(Elem, AccIn) -> AccOut
- Elem = term()
- Acc0 = Acc1 = AccIn = AccOut = term()
- List = [term()]

Like foldl/3, but the list is traversed from right to left. For example:

```
> P = fun(A, AccIn) -> io:format("~p ", [A]), AccIn end.
#Fun<erl_eval.12.2225172>
> lists:foldl(P, void, [1,2,3]).
1 2 3 void
> lists:foldr(P, void, [1,2,3]).
3 2 1 void
```

foldl/3 is tail recursive and would usually be preferred to foldr/3.

foreach(Fun, List) -> void()

Types:

- Fun = fun(Elem) -> void()
- Elem = term()
- List = [term()]

Calls Fun(Elem) for each element Elem in List. This function is used for its side effects and the evaluation order is defined to be the same as the order of the elements in the list.

keydelete(Key, N, TupleList1) -> TupleList2

Types:

- Key = term()
- N = 1..size(Tuple)
- TupleList1 = TupleList2 = [Tuple]
- Tuple = tuple()

Returns a copy of `TupleList1` where the first occurrence of a tuple whose `N`th element compares equal to `Key` is deleted, if there is such a tuple.

`keymap(Fun, N, TupleList1) -> TupleList2`

Types:

- `Fun = fun(Term1) -> Term2`
- `Term1 = Term2 = term()`
- `N = 1..size(Tuple)`
- `TupleList1 = TupleList2 = [tuple()]`

Returns a list of tuples where, for each tuple in `TupleList1`, the `N`th element `Term1` of the tuple has been replaced with the result of calling `Fun(Term1)`.

Examples:

```
> Fun = fun(Atom) -> atom_to_list(Atom) end.
#Fun<erl_eval.6.10732646>
2> lists:keymap(Fun, 2, [{name,jane,22},{name,lizzie,20},{name,lydia,15}]).
[{name,"jane",22},{name,"lizzie",20},{name,"lydia",15}]
```

`keymember(Key, N, TupleList) -> bool()`

Types:

- `Key = term()`
- `N = 1..size(Tuple)`
- `TupleList = [Tuple]`
- `Tuple = tuple()`

Returns `true` if there is a tuple in `TupleList` whose `N`th element compares equal to `Key`, otherwise `false`.

`keymerge(N, TupleList1, TupleList2) -> TupleList3`

Types:

- `N = 1..size(Tuple)`
- `TupleList1 = TupleList2 = TupleList3 = [Tuple]`
- `Tuple = tuple()`

Returns the sorted list formed by merging `TupleList1` and `TupleList2`. The merge is performed on the `N`th element of each tuple. Both `TupleList1` and `TupleList2` must be key-sorted prior to evaluating this function. When two tuples compare equal, the tuple from `TupleList1` is picked before the tuple from `TupleList2`.

`keyreplace(Key, N, TupleList1, NewTuple) -> TupleList2`

Types:

- `Key = term()`
- `N = 1..size(Tuple)`
- `TupleList1 = TupleList2 = [Tuple]`
- `NewTuple = Tuple = tuple()`

Returns a copy of `TupleList1`, where the first occurrence of a tuple whose `N`th element compares equal to `Key` is replaced with `NewTuple`, if there is such a tuple.

`keysearch(Key, N, TupleList) -> {value, Tuple} | false`

Types:

- `Key = term()`
- `N = 1..size(Tuple)`
- `TupleList = [Tuple]`
- `Tuple = tuple()`

Searches the list of the tuples `TupleList` for a tuple whose `N`th element compares equal to `Key`. Returns `{value, Tuple}` if such a tuple is found, otherwise `false`.

`keysort(N, TupleList1) -> TupleList2`

Types:

- `N = 1..size(Tuple)`
- `TupleList1 = TupleList2 = [Tuple]`
- `Tuple = tuple()`

Returns a list containing the sorted elements of the list `TupleList1`. Sorting is performed on the `N`th element of the tuples.

`last(List) -> Last`

Types:

- `List = [term()], length(List) > 0`
- `Last = term()`

Returns the last element in `List`.

`map(Fun, List1) -> List2`

Types:

- `Fun = fun(A) -> B`
- `List1 = [A]`
- `List2 = [B]`
- `A = B = term()`

Takes a function from `As` to `Bs`, and a list of `As` and produces a list of `Bs` by applying the function to every element in the list. This function is used to obtain the return values. The evaluation order is implementation dependent.

`mapfoldl(Fun, Acc0, List1) -> {List2, Acc1}`

Types:

- `Fun = fun(A, AccIn) -> {B, AccOut}`
- `Acc0 = Acc1 = AccIn = AccOut = term()`
- `List1 = [A]`
- `List2 = [B]`
- `A = B = term()`

`mapfold` combines the operations of `map/2` and `foldl/3` into one pass. An example, summing the elements in a list and double them at the same time:

```
> lists:mapfoldl(fun(X, Sum) -> {2*X, X+Sum} end,
                 0, [1,2,3,4,5]).
{[2,4,6,8,10],15}
```

```
mapfoldr(Fun, Acc0, List1) -> {List2, Acc1}
```

Types:

- `Fun = fun(A, AccIn) -> {B, AccOut}`
- `Acc0 = Acc1 = AccIn = AccOut = term()`
- `List1 = [A]`
- `List2 = [B]`
- `A = B = term()`

`mapfold` combines the operations of `map/2` and `foldr/3` into one pass.

```
max(List) -> Max
```

Types:

- `List = [term()], length(List) > 0`
- `Max = term()`

Returns the first element of `List` that compares greater than or equal to all other elements of `List`.

```
member(Elem, List) -> bool()
```

Types:

- `Elem = term()`
- `List = [term()]`

Returns true if `Elem` matches some element of `List`, otherwise false.

```
merge(ListOfLists) -> List1
```

Types:

- `ListOfLists = [List]`
- `List = List1 = [term()]`

Returns the sorted list formed by merging all the sub-lists of `ListOfLists`. All sub-lists must be sorted prior to evaluating this function. When two elements compare equal, the element from the sub-list with the lowest position in `ListOfLists` is picked before the other element.

```
merge(List1, List2) -> List3
```

Types:

- `List1 = List2 = List3 = [term()]`

Returns the sorted list formed by merging `List1` and `List2`. Both `List1` and `List2` must be sorted prior to evaluating this function. When two elements compare equal, the element from `List1` is picked before the element from `List2`.

`merge(Fun, List1, List2) -> List3`

Types:

- `Fun = fun(A, B) -> bool()`
- `List1 = [A]`
- `List2 = [B]`
- `List3 = [A | B]`
- `A = B = term()`

Returns the sorted list formed by merging `List1` and `List2`. Both `List1` and `List2` must be sorted according to the ordering function `Fun` prior to evaluating this function. `Fun(A, B)` should return `true` if `A` comes before `B` in the ordering, `false` otherwise. When two elements compare equal, the element from `List1` is picked before the element from `List2`.

`merge3(List1, List2, List3) -> List4`

Types:

- `List1 = List2 = List3 = List4 = [term()]`

Returns the sorted list formed by merging `List1`, `List2` and `List3`. All of `List1`, `List2` and `List3` must be sorted prior to evaluating this function. When two elements compare equal, the element from `List1`, if there is such an element, is picked before the other element, otherwise the element from `List2` is picked before the element from `List3`.

`min(List) -> Min`

Types:

- `List = [term()], length(List) > 0`
- `Min = term()`

Returns the first element of `List` that compares less than or equal to all other elements of `List`.

`nth(N, List) -> Elem`

Types:

- `N = 1..length(List)`
- `List = [term()]`
- `Elem = term()`

Returns the `N`th element of `List`. For example:

```
> lists:nth(3, [a, b, c, d, e]).  
c
```

`nthtail(N, List1) -> Tail`

Types:

- $N = 0..length(List1)$
- $List1 = Tail = [term()]$

Returns the  $N$ th tail of  $List$ , that is, the sublist of  $List$  starting at  $N+1$  and continuing up to the end of the list. For example:

```
> lists:nthtail(3, [a, b, c, d, e]).
[d,e]
> tl(tl(tl([a, b, c, d, e])).
[d,e]
> lists:nthtail(0, [a, b, c, d, e]).
[a,b,c,d,e]
> lists:nthtail(5, [a, b, c, d, e]).
[]
```

`partition(Pred, List) -> {Satisfying, NonSatisfying}`

Types:

- $Pred = fun(Atom) -> bool()$
- $Atom = term()$
- $List = Satisfying = NonSatisfying = [term()]$

Partitions  $List$  into two lists, where the first list contains all elements for which  $Pred(Atom)$  returns true, and the second list contains all elements for which  $Pred(Atom)$  returns false.

Examples:

```
> lists:partition(fun(Atom) -> Atom rem 2 == 1 end, [1,2,3,4,5,6,7]).
{[1,3,5,7],[2,4,6]}
> lists:partition(fun(Atom) -> is_atom(Atom) end, [a,b,1,c,d,2,3,4,e]).
{[a,b,c,d,e],[1,2,3,4]}
```

See also `splitwith/2` for a different way to partition a list.

`prefix(List1, List2) -> bool()`

Types:

- $List1 = List2 = [term()]$

Returns true if  $List1$  is a prefix of  $List2$ , otherwise false.

`reverse(List1) -> List2`

Types:

- $List1 = List2 = [term()]$

Returns a list with the top level elements in  $List1$  in reverse order.

`reverse(List1, Tail) -> List2`

Types:

- $List1 = Tail = List2 = [term()]$

Returns a list with the top level elements in  $List1$  in reverse order, with the tail  $Tail$  appended. For example:

```
> lists:reverse([1, 2, 3, 4], [a, b, c]).
[4,3,2,1,a,b,c]
```

```
seq(From, To) -> Seq
```

```
seq(From, To, Incr) -> Seq
```

Types:

- From = To = Incr = int()
- Seq = [int()]

Returns a sequence of integers which starts with `From` and contains the successive results of adding `Incr` to the previous element, until `To` has been reached or passed (in the latter case, `To` is not an element of the sequence). `Incr` defaults to 1.

Failure: If `To < From` and `Incr` is positive, or if `To > From` and `Incr` is negative, or if `Incr == 0` and `From /= To`.

Examples:

```
> lists:seq(1, 10).
[1,2,3,4,5,6,7,8,9,10]
> lists:seq(1, 20, 3).
[1,4,7,10,13,16,19]
> lists:seq(1, 1, 0).
[1]
```

```
sort(List1) -> List2
```

Types:

- List1 = List2 = [term()]

Returns a list containing the sorted elements of `List1`.

```
sort(Fun, List1) -> List2
```

Types:

- Fun = fun(Elem1, Elem2) -> bool()
- Elem1 = Elem2 = term()
- List1 = List2 = [term()]

Returns a list containing the sorted elements of `List1`, according to the ordering function `Fun`. `Fun(A, B)` should return `true` if `A` comes before `B` in the ordering, `false` otherwise.

```
split(N, List1) -> {List2, List3}
```

Types:

- N = 0..length(List1)
- List1 = List2 = List3 = [term()]

Splits `List1` into `List2` and `List3`. `List2` contains the first `N` elements and `List3` the rest of the elements (the `N`th tail).

```
splitwith(Pred, List) -> {List1, List2}
```

Types:

- Pred = fun(Elem) -> bool()
- Elem = term()
- List = List1 = List2 = [term()]

Partitions List into two lists according to Pred. `splitwith/2` behaves as if it is defined as follows:

```
splitwith(Pred, List) ->
    {takewhile(Pred, List), dropwhile(Pred, List)}.
```

Examples:

```
> lists:splitwith(fun(A) -> A rem 2 == 1 end, [1,2,3,4,5,6,7]).
{[1],[2,3,4,5,6,7]}
> lists:splitwith(fun(A) -> is_atom(A) end, [a,b,1,c,d,2,3,4,e]).
{[a,b],[1,c,d,2,3,4,e]}
```

See also `partition/2` for a different way to partition a list.

```
sublist(List1, Len) -> List2
```

Types:

- List1 = List2 = [term()]
- Len = int()

Returns the sub-list of List1 starting at position 1 and with (max) Len elements. It is not an error for Len to exceed the length of the list – in that case the whole list is returned.

```
sublist(List1, Start, Len) -> List2
```

Types:

- List1 = List2 = [term()]
- Start = 1..(length(List1)+1)
- Len = int()

Returns the sub-list of List1 starting at Start and with (max) Len elements. It is not an error for Start+Len to exceed the length of the list.

```
> lists:sublist([1,2,3,4], 2, 2).
[2,3]
> lists:sublist([1,2,3,4], 2, 5).
[2,3,4]
> lists:sublist([1,2,3,4], 5, 2).
[]
```

```
subtract(List1, List2) -> List3
```

Types:

- List1 = List2 = List3 = [term()]

Returns a new list List3 which is a copy of List1, subjected to the following procedure: for each element in List2, its first occurrence in List1 is deleted. For example:

```
> lists.subtract("123212", "212").  
"312".
```

`lists.subtract(A,B)` is equivalent to `A -- B`.

`suffix(List1, List2) -> bool()`

Returns true if `List1` is a suffix of `List2`, otherwise false.

`sum(List) -> number()`

Types:

- `List = [number()]`

Returns the sum of the elements in `List`.

`takewhile(Pred, List1) -> List2`

Types:

- `Pred = fun(Elem) -> bool()`
- `Elem = term()`
- `List1 = List2 = [term()]`

Takes elements `Elem` from `List1` while `Pred(Elem)` returns true, that is, the function returns the longest prefix of the list for which all elements satisfy the predicate.

`ukeymerge(N, TupleList1, TupleList2) -> TupleList3`

Types:

- `N = 1..size(Tuple)`
- `TupleList1 = TupleList2 = TupleList3 = [Tuple]`
- `Tuple = tuple()`

Returns the sorted list formed by merging `TupleList1` and `TupleList2`. The merge is performed on the `N`th element of each tuple. Both `TupleList1` and `TupleList2` must be key-sorted without duplicates prior to evaluating this function. When two tuples compare equal, the tuple from `TupleList1` is picked and the one from `TupleList2` deleted.

`ukeysort(N, TupleList1) -> TupleList2`

Types:

- `N = 1..size(Tuple)`
- `TupleList1 = TupleList2 = [Tuple]`
- `Tuple = tuple()`

Returns a list containing the sorted elements of the list `TupleList1` where all but the first tuple of the tuples comparing equal have been deleted. Sorting is performed on the `N`th element of the tuples.

`umerge(ListOfLists) -> List1`

Types:

- `ListOfLists = [List]`

- `List = List1 = [term()]`

Returns the sorted list formed by merging all the sub-lists of `ListOfLists`. All sub-lists must be sorted and contain no duplicates prior to evaluating this function. When two elements compare equal, the element from the sub-list with the lowest position in `ListOfLists` is picked and the other one deleted.

`umerge(List1, List2) -> List3`

Types:

- `List1 = List2 = List3 = [term()]`

Returns the sorted list formed by merging `List1` and `List2`. Both `List1` and `List2` must be sorted and contain no duplicates prior to evaluating this function. When two elements compare equal, the element from `List1` is picked and the one from `List2` deleted.

`umerge(Fun, List1, List2) -> List3`

Types:

- `Fun = fun(A, B) -> bool()`
- `List1 = [A]`
- `List2 = [B]`
- `List3 = [A | B]`
- `A = B = term()`

Returns the sorted list formed by merging `List1` and `List2`. Both `List1` and `List2` must be sorted according to the ordering function `Fun` and contain no duplicates prior to evaluating this function. `Fun(A, B)` should return `true` if `A` comes before `B` in the ordering, `false` otherwise. When two elements compare equal, the element from `List1` is picked and the one from `List2` deleted.

`umerge3(List1, List2, List3) -> List4`

Types:

- `List1 = List2 = List3 = List4 = [term()]`

Returns the sorted list formed by merging `List1`, `List2` and `List3`. All of `List1`, `List2` and `List3` must be sorted and contain no duplicates prior to evaluating this function. When two elements compare equal, the element from `List1` is picked if there is such an element, otherwise the element from `List2` is picked, and the other one deleted.

`unzip(List1) -> {List2, List3}`

Types:

- `List1 = [{X, Y}]`
- `List2 = [X]`
- `List3 = [Y]`
- `X = Y = term()`

“Unzips” a list of two-tuples into two lists, where the first list contains the first element of each tuple, and the second list contains the second element of each tuple.

`unzip3(List1) -> {List2, List3, List4}`

Types:

- List1 = [{X, Y, Z}]
- List2 = [X]
- List3 = [Y]
- List4 = [Z]
- X = Y = Z = term()

“Unzips” a list of three-tuples into three lists, where the first list contains the first element of each tuple, the second list contains the second element of each tuple, and the third list contains the third element of each tuple.

`usort(List1) -> List2`

Types:

- List1 = List2 = [term()]

Returns a list containing the sorted elements of List1 where all but the first element of the elements comparing equal have been deleted.

`usort(Fun, List1) -> List2`

Types:

- Fun = fun(Elem1, Elem2) -> bool()
- Elem1 = Elem2 = term()
- List1 = List2 = [term()]

Returns a list which contains the sorted elements of List1 where all but the first element of the elements comparing equal according to the ordering function Fun have been deleted. Fun(A, B) should return true if A comes before B in the ordering, false otherwise.

`zip(List1, List2) -> List3`

Types:

- List1 = [X]
- List2 = [Y]
- List3 = [{X, Y}]
- X = Y = term()

“Zips” two lists of equal length into one list of two-tuples, where the first element of each tuple is taken from the first list and the second element is taken from corresponding element in the second list.

`zip3(List1, List2, List3) -> List4`

Types:

- List1 = [X]
- List2 = [Y]
- List3 = [Z]
- List4 = [{X, Y, Z}]
- X = Y = Z = term()

“Zips” three lists of equal length into one list of three-tuples, where the first element of each tuple is taken from the first list, the second element is taken from corresponding element in the second list, and the third element is taken from the corresponding element in the third list.

```
zipwith(Combine, List1, List2) -> List3
```

Types:

- Combine = fun(X, Y) -> T
- List1 = [X]
- List2 = [Y]
- List3 = [T]
- X = Y = T = term()

Combine the elements of two lists of equal length into one list. For each pair X, Y of list elements from the two lists, the element in the result list will be Combine(X, Y).

zipwith(fun(X, Y) -> {X,Y} end, List1, List2) is equivalent to zip(List1, List2).

Examples:

```
> lists:zipwith(fun(X, Y) -> X+Y end, [1,2,3], [4,5,6]).  
[5,7,9]
```

```
zipwith3(Combine, List1, List2, List3) -> List4
```

Types:

- Combine = fun(X, Y, Z) -> T
- List1 = [X]
- List2 = [Y]
- List3 = [Z]
- List4 = [T]
- X = Y = Z = T = term()

Combine the elements of three lists of equal length into one list. For each triple X, Y, Z of list elements from the three lists, the element in the result list will be Combine(X, Y, Z).

zipwith3(fun(X, Y, Z) -> {X,Y,Z} end, List1, List2, List3) is equivalent to zip3(List1, List2, List3).

Examples:

```
> lists:zipwith3(fun(X, Y, Z) -> X+Y+Z end, [1,2,3], [4,5,6], [7,8,9]).  
[12,15,18]  
> lists:zipwith3(fun(X, Y, Z) -> [X,Y,Z] end, [a,b,c], [x,y,z], [1,2,3]).  
[[a,x,1],[b,y,2],[c,z,3]]
```

# log\_mf\_h

Erlang Module

The `log_mf_h` is a `gen_event` handler module which can be installed in any `gen_event` process. It logs onto disk all events which are sent to an event manager. Each event is written as a binary which makes the logging very fast. However, a tool such as the `Report Browser (rb)` must be used in order to read the files. The events are written to multiple files. When all files have been used, the first one is re-used and overwritten. The directory location, the number of files, and the size of each file are configurable. The directory will include one file called `index`, and report files `1`, `2`, `...`

## Exports

```
init(Dir, MaxBytes, MaxFiles)
init(Dir, MaxBytes, MaxFiles, Pred) -> Args
```

Types:

- `Dir = string()`
- `MaxBytes = integer()`
- `MaxFiles = 0 < integer() < 256`
- `Pred = fun(Event) -> boolean()`
- `Event = term()`
- `Args = args()`

Initiates the event handler. This function returns `Args`, which should be used in a call to `gen_event:add_handler(EventMgr, log_mf_h, Args)`.

`Dir` specifies which directory to use for the log files. `MaxBytes` specifies the size of each individual file. `MaxFiles` specifies how many files are used. `Pred` is a predicate function used to filter the events. If no predicate function is specified, all events are logged.

## See Also

`gen_event(3)` [page 175], `rb(3)`

# math

Erlang Module

This module provides an interface to a number of mathematical functions.

**Note:**

Not all functions are implemented on all platforms. In particular, the `erf/1` and `erfc/1` functions are not implemented on Windows.

## Exports

`pi()` -> `float()`

A useful number.

`sin(X)`

`cos(X)`

`tan(X)`

`asin(X)`

`acos(X)`

`atan(X)`

`atan2(Y, X)`

`sinh(X)`

`cosh(X)`

`tanh(X)`

`asinh(X)`

`acosh(X)`

`atanh(X)`

`exp(X)`

`log(X)`

`log10(X)`

`pow(X, Y)`

`sqrt(X)`

Types:

- `X = Y = number()`

A collection of math functions which return floats. Arguments are numbers.

`erf(X)` -> `float()`

Types:

- `X = number()`

Returns the error function of `X`, where

$\text{erf}(X) = 2/\sqrt{\pi} \cdot \text{integral from } 0 \text{ to } X \text{ of } \exp(-t*t) dt.$

`erfc(X)` -> `float()`

Types:

- `X = number()`

`erfc(X)` returns  $1.0 - \text{erf}(X)$ , computed by methods that avoid cancellation for large `X`.

## Bugs

As these are the C library, the bugs are the same.

# ms\_transform

Erlang Module

This module implements the `parse_transform` that makes calls to `ets` and `dbg:fun2ms/1` translate into literal match specifications. It also implements the back end for the same functions when called from the Erlang shell.

The translations from fun's to `match_specs` is accessed through the two "pseudo functions" `ets:fun2ms/1` and `dbg:fun2ms/1`.

Actually this introduction is more or less an introduction to the whole concept of match specifications. Since everyone trying to use `ets:select` or `dbg` seems to end up reading this page, it seems in good place to explain a little more than just what this module does.

There are some caveats one should be aware of, please read through the whole manual page if it's the first time you're using the transformations.

Match specifications are used more or less as filters. They resemble usual Erlang matching in a list comprehension or in a fun used in conjunction with `lists:foldl` etc. The syntax of pure match specifications is somewhat awkward though, as they are made up purely by Erlang terms and there is no syntax in the language to make the match specifications more readable.

As the match specifications execution and structure is quite like that of a fun, it would for most programmers be more straight forward to simply write it using the familiar fun syntax and having that translated into a match specification automatically. Of course a real fun is more powerful than the match specifications allow, but bearing the match specifications in mind, and what they can do, it's still more convenient to write it all as a fun. This module contains the code that simply translates the fun syntax into `match_spec` terms.

Let's start with an `ets` example. Using `ets:select` and a match specification, one can filter out rows of a table and construct a list of tuples containing relevant parts of the data in these rows. Of course one could use `ets:foldl` instead, but the `select` call is far more efficient. Without the translation, one has to struggle with writing match specifications terms to accommodate this, or one has to resort to the less powerful `ets:match(_object)` calls, or simply give up and use the more inefficient method of `ets:foldl`. Using the `ets:fun2ms` transformation, a `ets:select` call is at least as easy to write as any of the alternatives.

As an example, consider a simple table of employees:

```
-record(emp, {empno,      %Employee number as a string, the key
             surname,   %Surname of the employee
             givenname, %Given name of employee
             dept,      %Department one of {dev,sales,prod,adm}
             empyear}). %Year the employee was employed
```

We create the table using:

```
ets:new(emp_tab, [{keypos, #emp.empno}, named_table, ordered_set]).
```

Let's also fill it with some randomly chosen data for the examples:

```
[{emp, "011103", "Black", "Alfred", sales, 2000},
 {emp, "041231", "Doe", "John", prod, 2001},
 {emp, "052341", "Smith", "John", dev, 1997},
 {emp, "076324", "Smith", "Ella", sales, 1995},
 {emp, "122334", "Weston", "Anna", prod, 2002},
 {emp, "535216", "Chalker", "Samuel", adm, 1998},
 {emp, "789789", "Harrysson", "Joe", adm, 1996},
 {emp, "963721", "Scott", "Juliana", dev, 2003},
 {emp, "989891", "Brown", "Gabriel", prod, 1999}]
```

Now, the amount of data in the table is of course too small to justify complicated ets searches, but on real tables, using `select` to get exactly the data you want will increase efficiency remarkably.

Let's say for example that we'd want the employee numbers of everyone in the sales department. One might use `ets:match` in such a situation:

```
1> ets:match(emp_tab, {'_', '$1', '_', '_'}, sales, '_').
["011103"], ["076324"]
```

Even though `ets:match` does not require a full match specification, but a simpler type, it's still somewhat unreadable, and one has little control over the returned result, it's always a list of lists. OK, one might use `ets:foldl` or `ets:foldr` instead:

```
ets:foldr(fun(#emp{empno = E, dept = sales}, Acc) -> [E | Acc];
          (_, Acc) -> Acc
          end,
          [],
          emp_tab).
```

Running that would result in `["011103", "076324"]`, which at least gets rid of the extra lists. The fun is also quite straightforward, so the only problem is that all the data from the table has to be transferred from the table to the calling process for filtering. That's inefficient compared to the `ets:match` call where the filtering can be done "inside" the emulator and only the result is transferred to the process. Remember that ets tables are all about efficiency, if it wasn't for efficiency all of ets could be implemented in Erlang, as a process receiving requests and sending answers back. One uses ets because one wants performance, and therefore one wouldn't want all of the table transferred to the process for filtering. OK, let's look at a pure `ets:select` call that does what the `ets:foldr` does:

```
ets:select(emp_tab, [{#emp{empno = '$1', dept = sales, _='_'}, [], ['$1']}).
```

Even though the record syntax is used, it's still somewhat hard to read and even harder to write. The first element of the tuple, `#emp{empno = '$1', dept = sales, _='_'}'` tells what to match, elements not matching this will not be returned at all, as in the `ets:match` example. The second element, the empty list is a list of guard expressions, which we need none, and the third element is the list of expressions constructing the return value (in ets this almost always is a list containing one single term). In our case `'$1'` is bound to the employee number in the head (first element of tuple), and hence it is the employee number that is returned. The result is `["011103", "076324"]`, just as in the `ets:foldr` example, but the result is retrieved much more efficiently in terms of execution speed and memory consumption.

We have one efficient but hardly readable way of doing it and one inefficient but fairly readable (at least to the skilled Erlang programmer) way of doing it. With the use of

ets:fun2ms, one could have something that is as efficient as possible but still is written as a filter using the fun syntax:

```
-include_lib("stdlib/include/ms_transform.hrl").

% ...

ets:select(emp_tab, ets:fun2ms(
    fun(#emp{empno = E, dept = sales}) ->
        E
    end)).
```

This may not be the shortest of the expressions, but it requires no special knowledge of match specifications to read. The fun's head should simply match what you want to filter out and the body returns what you want returned. As long as the fun can be kept within the limits of the match specifications, there is no need to transfer all data of the table to the process for filtering as in the ets:foldr example. In fact it's even easier to read than the ets:foldr example, as the select call in itself discards anything that doesn't match, while the fun of the foldr call needs to handle both the elements matching and the ones not matching.

It's worth noting in the above ets:fun2ms example that one needs to include ms\_transform.hrl in the source code, as this is what triggers the parse transformation of the ets:fun2ms call to a valid match specification. This also implies that the transformation is done at compile time (except when called from the shell of course) and therefore will take no resources at all in runtime. So although you use the more intuitive fun syntax, it gets as efficient in runtime as writing match specifications by hand.

Let's look at some more ets examples. Let's say one wants to get all the employee numbers of any employee hired before the year 2000. Using ets:match isn't an alternative here as relational operators cannot be expressed there. Once again, an ets:foldr could do it (slowly, but correct):

```
ets:foldr(fun(#emp{empno = E, empyear = Y}, Acc) when Y < 2000 -> [E | Acc];
    (_, Acc) -> Acc
    end,
    [],
    emp_tab).
```

The result will be ["052341", "076324", "535216", "789789", "989891"], as expected. Now the equivalent expression using a handwritten match specification would look something like this:

```
ets:select(emp_tab, [{#emp{empno = '$1', empyear = '$2', _='_'},
    [{'<', '$2', 2000}],
    ['$1']}]).
```

This gives the same result, the [{'<', '\$2', 2000}] is in the guard part and therefore discards anything that does not have a empyear (bound to '\$2' in the head) less than 2000, just as the guard in the foldl example. Lets jump on to writing it using ets:fun2ms

```
-include_lib("stdlib/include/ms_transform.hrl").

% ...

ets:select(emp_tab, ets:fun2ms(
    fun(#emp{empno = E, empyear = Y}) when Y < 2000 ->
        E
    end)).
```

Obviously readability is gained by using the parse transformation.

I'll show some more examples without the tiresome comparing-to-alternatives stuff. Let's say we'd want the whole object matching instead of only one element. We could of course assign a variable to every part of the record and build it up once again in the body of the fun, but it's easier to do like this:

```
ets:select(emp_tab, ets:fun2ms(
    fun(Obj = #emp{empno = E, empyear = Y})
        when Y < 2000 ->
            Obj
    end)).
```

Just as in ordinary Erlang matching, you can bind a variable to the whole matched object using a "match in then match", i.e. `a =`. Unfortunately this is not general in fun's translated to match specifications, only on the "top level", i.e. matching the *whole* object arriving to be matched into a separate variable, is it allowed. For the one's used to writing match specifications by hand, I'll have to mention that the variable `A` will simply be translated into `'$.'`. It's not general, but it has very common usage, why it is handled as a special, but useful, case. If this bothers you, the pseudo function `object` also returns the whole matched object, see the part about caveats and limitations below.

Let's do something in the fun's body too: Let's say that someone realizes that there are a few people having an employee number beginning with a zero (0), which shouldn't be allowed. All those should have their numbers changed to begin with a one (1) instead and one wants the list `[{<Old empno>, <New empno>}]` created:

```
ets:select(emp_tab, ets:fun2ms(
    fun(#emp{empno = [$0 | Rest] }) ->
        {[$0|Rest], [$1|Rest]}
    end)).
```

As a matter of fact, this query hit's the feature of partially bound keys in the table type `ordered_set`, so that not the whole table need be searched, only the part of the table containing keys beginning with 0 is in fact looked into.

The fun of course can have several clauses, so that if one could do the following: For each employee, if he or she is hired prior to 1997, return the tuple `{inventory, <employee number>}`, for each hired 1997 or later, but before 2001, return `{rookie, <employee number>}`, for all others return `{newbie, <employee number>}`. All except for the ones named `Smith` as they would be affronted by anything other than the tag `guru` and that is also what's returned for their numbers; `{guru, <employee number>}`:

```
ets:select(emp_tab, ets:fun2ms(
    fun(#emp{empno = E, surname = "Smith" }) ->
        {guru, E};
    (#emp{empno = E, empyear = Y}) when Y < 1997 ->
        {inventory, E};
```

```

    (#emp{empno = E, empyear = Y}) when Y > 2001 ->
        {newbie, E};
    (#emp{empno = E, empyear = Y}) -> % 1997 -- 2001
        {rookie, E}
end)).

```

The result will be:

```

[{{rookie,"011103"},
  {rookie,"041231"},
  {guru,"052341"},
  {guru,"076324"},
  {newbie,"122334"},
  {rookie,"535216"},
  {inventory,"789789"},
  {newbie,"963721"},
  {rookie,"989891"}}]

```

and so the Smith's will be happy..

So, what more can you do? Well, the simple answer would be; look in the documentation of match specifications in ERTS users guide. However let's briefly go through the most useful "built in functions" that you can use when the fun is to be translated into a match specification by `ets:fun2ms` (it's worth mentioning, although it might be obvious to some, that calling other functions than the one's allowed in match specifications cannot be done. No "usual" Erlang code can be executed by the fun being translated by `fun2ms`, the fun is after all limited exactly to the power of the match specifications, which is unfortunate, but the price one has to pay for the execution speed of an `ets:select` compared to `ets:fold1/foldr`).

The head of the fun is obviously a head matching (or mismatching) *one* parameter, one object of the table we `select` from. The object is always a single variable (can be `_`) or a tuple, as that's what's in `ets`, `dets` and `mnesia` tables (the match specification returned by `ets:fun2ms` can of course be used with `dets:select` and `mnesia:select` as well as with `ets:select`). The use of `=` in the head is allowed (and encouraged) on the top level.

The guard section can contain any guard expression of Erlang. Even the "old" type test are allowed on the toplevel of the guard (`integer(X)` instead of `is_integer(X)`). As the new type tests (the `is_` tests) are in practice just guard bif's they can also be called from within the body of the fun, but so they can in ordinary Erlang code. Also arithmetics is allowed, as well as ordinary guard bif's. Here's a list of bif's and expressions:

- The type tests: `is_atom`, `is_constant`, `is_float`, `is_integer`, `is_list`, `is_number`, `is_pid`, `is_port`, `is_reference`, `is_tuple`, `is_binary`, `is_function`, `is_record`
- The boolean operators: `not`, `and`, `or`, `andalso`, `orelse`
- The relational operators: `>`, `>=`, `<`, `=<`, `:=`, `==`, `=/=`, `/=`
- Arithmetics: `+`, `-`, `*`, `div`, `rem`
- Bitwise operators: `band`, `bor`, `bxor`, `bnot`, `bsl`, `bsr`
- The guard bif's: `abs`, `element`, `hd`, `length`, `node`, `round`, `size`, `tl`, `trunc`, `self`
- The obsolete type test (only in guards): `atom`, `constant`, `float`, `integer`, `list`, `number`, `pid`, `port`, `reference`, `tuple`, `binary`, `function`, `record`

Contrary to the fact with “handwritten” match specifications, the `is_record` guard works as in ordinary Erlang code.

Semicolons (;) in guards are allowed, the result will be (as expected) one “match\_spec-clause” for each semicolon-separated part of the guard. The semantics being identical to the Erlang semantics.

The body of the `fun` is used to construct the resulting value. When selecting from tables one usually just construct a suitable term here, using ordinary Erlang term construction, like tuple parentheses, list brackets and variables matched out in the head, possibly in conjunction with the occasional constant. Whatever expressions are allowed in guards are also allowed here, but there are no special functions except `object` and `bindings` (see further down), which returns the whole matched object and all known variable bindings respectively.

The `dbg` variants of match specifications have an imperative approach to the match specification body, the `ets` dialect hasn't. The `fun` body for `ets:fun2ms` returns the result without side effects, and as matching (=) in the body of the match specifications is not allowed (for performance reasons) the only thing left, more or less, is term construction...

Let's move on to the `dbg` dialect, the slightly different match specifications translated by `dbg:fun2ms`.

The same reasons for using the parse transformation applies to `dbg`, maybe even more so as filtering using Erlang code is simply not a good idea when tracing (except afterwards, if you trace to file). The concept is similar to that of `ets:fun2ms` except that you usually use it directly from the shell (which can also be done with `ets:fun2ms`).

Let's manufacture a toy module to trace on

```
-module(toy).

-export([start/1, store/2, retrieve/1]).

start(Args) ->
    toy_table = ets:new(toy_table,Args).

store(Key, Value) ->
    ets:insert(toy_table,{Key,Value}).

retrieve(Key) ->
    [{Key, Value}] = ets:lookup(toy_table,Key),
    Value.
```

During model testing, the first test bails out with a `{badmatch,16}` in `{toy,start,1}`, why?

We suspect the `ets` call, as we match hard on the return value, but want only the particular `new` call with `toy_table` as first parameter. So we start a default tracer on the node:

```
1> dbg:tracer().
{ok,<0.88.0>}
```

And so we turn on call tracing for all processes, we are going to make a pretty restrictive trace pattern, so there's no need to call `trace` only a few processes (it usually isn't):

```
2> dbg:p(all,call).
{ok,[{matched,nonode@nohost,25}]}
```

It's time to specify the filter. We want to view calls that resemble `ets:new(toy_table, <something>)`:

```
3> dbg:tp(ets,new,dbg:fun2ms(fun([toy_table,_] -> true end)).
{ok, [{matched,nonode@nohost,1},{saved,1}]})
```

As can be seen, the fun's used with `dbg:fun2ms` takes a single list as parameter instead of a single tuple. The list matches a list of the parameters to the traced function. A single variable may also be used of course. The body of the fun expresses in a more imperative way actions to be taken if the fun head (and the guards) matches. I return `true` here, but it's only because the body of a fun cannot be empty, the return value will be discarded.

When we run the test of our module now, we get the following trace output:

```
(<0.86.0>) call ets:new(toy_table,[ordered_set])
```

Let's play we haven't spotted the problem yet, and want to see what `ets:new` returns. We do a slightly different trace pattern:

```
4> dbg:tp(ets,new,dbg:fun2ms(fun([toy_table,_] -> return_trace() end)).
```

Resulting in the following trace output when we run the test:

```
(<0.86.0>) call ets:new(toy_table,[ordered_set])
(<0.86.0>) returned from ets:new/2 -> 24
```

The call to `return_trace`, makes a trace message appear when the function returns. It applies only to the specific function call triggering the match specification (and matching the head/guards of the match specification). This is the by far the most common call in the body of a `dbg` match specification.

As the test now fails with `{badmatch,24}`, it's obvious that the `badmatch` is because the atom `toy_table` does not match the number returned for an unnamed table. So we spotted the problem, the table should be named and the arguments supplied by our test program does not include `named_table`. We rewrite the start function to:

```
start(Args) ->
    toy_table = ets:new(toy_table,[named_table |Args]).
```

And with the same tracing turned on, we get the following trace output:

```
(<0.86.0>) call ets:new(toy_table,[named_table,ordered_set])
(<0.86.0>) returned from ets:new/2 -> toy_table
```

Very well. Let's say the module now passes all testing and goes into the system. After a while someone realizes that the table `toy_table` grows while the system is running and that for some reason there are a lot of elements with atom's as keys. You had expected only integer keys and so does the rest of the system. Well, obviously not all of the system. You turn on call tracing and try to see calls to your module with an atom as the key:

```
1> dbg:tracer().
{ok,<0.88.0>}
2> dbg:p(all,call).
{ok, [{matched,nonode@nohost,25}]}
3> dbg:tpl(toy,store,dbg:fun2ms(fun([A,_] when is_atom(A) -> true end)).
{ok, [{matched,nonode@nohost,1},{saved,1}]})
```

We use `dbg:tpl` here to make sure to catch local calls (let's say the module has grown since the smaller version and we're not sure this inserting of atoms is not done locally...). When in doubt always use local call tracing.

Let's say nothing happens when we trace in this way. Our function is never called with these parameters. We make the conclusion that someone else (some other module) is doing it and we realize that we must trace on `ets:insert` and want to see the calling function. The calling function may be retrieved using the match specification function `caller` and to get it into the trace message, one has to use the match spec function `message`. The filter call looks like this (looking for calls to `ets:insert`):

```
4> dbg:tpl(ets,insert,dbg:fun2ms(fun([toy_table,{A,_}] when is_atom(A) ->
                                message(caller())
                                end)).
{ok, [{matched,node@nohost,1},{saved,2}]}
```

The caller will now appear in the "additional message" part of the trace output, and so after a while, the following output comes:

```
(<0.86.0>) call ets:insert(toy_table,{garbage,can}) ({evil_mod,evil_fun,2})
```

You have found out that the function `evil_fun` of the module `evil_mod`, with arity 2, is the one causing all this trouble.

This was just a toy example, but it illustrated the most used calls in match specifications for `dbg`. The other, more esoteric calls are listed and explained in the *Users guide of the ERTS application*, they really are beyond the scope of this document.

To end this chatty introduction with something more precise, here follows some parts about caveats and restrictions concerning the `fun`'s used in conjunction with `ets:fun2ms` and `dbg:fun2ms`:

### Warning:

To use the pseudo functions triggering the translation, one *has to* include the header file `ms_transform.hrl` in the source code. Failure to do so will possibly result in runtime errors rather than compile time, as the expression may be valid as a plain Erlang program without translation.

### Warning:

The `fun` has to be literally constructed inside the parameter list to the pseudo functions. The `fun` cannot be bound to a variable first and then passed to `ets:fun2ms` or `dbg:fun2ms`, i.e. this will work: `ets:fun2ms(fun(A) -> A end)` but not this: `F = fun(A) -> A end, ets:fun2ms(F)`. The later will result in a compile time error if the header is included, otherwise a runtime error. Even if the later construction would ever appear to work, it really doesn't, so don't ever use it.

Several restrictions apply to the `fun` that is being translated into a `match_spec`. To put it simple you cannot use anything in the `fun` that you cannot use in a `match_spec`. This means that, among others, the following restrictions apply to the `fun` itself:

- Functions written in Erlang cannot be called, neither local functions, global functions or real `fun`'s

- Everything that is written as a function call will be translated into a `match_spec` call to a builtin function, so that the call `is_list(X)` will be translated to `{'is_list', '$1'}` (`'$1'` is just an example, the numbering may vary). If one tries to call a function that is not a `match_spec` builtin, it will cause an error.
- Variables occurring in the head of the `fun` will be replaced by `match_spec` variables in the order of occurrence, so that the fragment `fun({A,B,C})` will be replaced by `{'$1', '$2', '$3'}` etc. Every occurrence of such a variable later in the `match_spec` will be replaced by a `match_spec` variable in the same way, so that the `fun fun({A,B}) when is_atom(A) -> B end` will be translated into `[{'$1', '$2'}, [{is_atom, '$1'}], ['$2']]`.
- Variables that are not appearing in the head are imported from the environment and made into `match_spec` `const` expressions. Example from the shell:

```
1> X = 25.
25
2> ets:fun2ms(fun({A,B}) when A > X -> B end).
[{'$1', '$2'}, [{'>', '$1', {const, 25}}], ['$2']]
```

- Matching with `=` cannot be used in the body. It can only be used on the top level in the head of the `fun`. Example from the shell again:

```
1> ets:fun2ms(fun({A,[B|C]} = D) when A > B -> D end).
[{'$1', ['$2'|'$3']}, [{'>', '$1', '$2'}], ['$_']]
2> ets:fun2ms(fun({A,[B|C]=D}) when A > B -> D end).
Error: fun with head matching ('=' in head) cannot be translated into
match_spec
{error,transform_error}
3> ets:fun2ms(fun({A,[B|C]}) when A > B -> D = [B|C], D end).
Error: fun with body matching ('=' in body) is illegal as match_spec
{error,transform_error}
```

All variables are bound in the head of a `match_spec`, so the translator can not allow multiple bindings. The special case when matching is done on the top level makes the variable bind to `'$_'` in the resulting `match_spec`, it is to allow a more natural access to the whole matched object. The pseudo function `object()` could be used instead, see below. The following expressions are translated equally:

```
ets:fun2ms(fun({a,_} = A) -> A end).
ets:fun2ms(fun({a,_}) -> object() end).
```

- The special `match_spec` variables `'$_'` and `'$*'` can be accessed through the pseudo functions `object()` (for `'$_'`) and `bindings()` (for `'$*'`). as an example, one could translate the following `ets:match_object/2` call to a `ets:select` call:

```
ets:match_object(Table, {'$1', test, '$2'}).
```

...is the same as...

```
ets:select(Table, ets:fun2ms(fun({A,test,B}) -> object() end)).
```

(This was just an example, in this simple case the former expression is probably preferable in terms of readability). The `ets:select/2` call will conceptually look like this in the resulting code:

```
ets:select(Table, [{'$1', test, '$2'}, [], ['$_']]).
```

Matching on the top level of the `fun` head might feel like a more natural way to access `'$_'`, see above.

- Term constructions/literals are translated as much as is needed to get them into valid `match_specs`, so that tuples are made into `match_spec` tuple constructions (a one element tuple containing the tuple) and constant expressions are used when importing variables from the environment. Records are also translated into plain tuple constructions, calls to `element` etc. The guard test `is_record/2` is translated into `match_spec` code using the three parameter version that's built into `match_specs`, so that `is_record(A,t)` is translated into `{is_record,'$1',t,5}` given that the record size of record type `t` is 5.
- Language constructions like `case`, `if`, `catch` etc that are not present in `match_specs` are not allowed.
- If the header file `ms_transform.hrl` is not included, the fun won't be translated, which may result in a *runtime error* (depending on if the fun is valid in a pure Erlang context). Be absolutely sure that the header is included when using `ets` and `dbg:fun2ms/1` in compiled code.
- If the pseudo function triggering the translation is `ets:fun2ms/1`, the fun's head must contain a single variable or a single tuple. If the pseudo function is `dbg:fun2ms/1` the fun's head must contain a single variable or a single list.

The translation from fun's to `match_specs` is done at compile time, so runtime performance is not affected by using these pseudo functions. The compile time might be somewhat longer though.

For more information about `match_specs`, please read about them in *ERTS users guide*.

## Exports

```
parse_transform(Forms,_Options) -> Forms
```

Types:

- `Forms` = Erlang abstract code format, see the `erl_parse` module description
- `_Options` = Option list, required but not used

Implements the actual transformation at compile time. This function is called by the compiler to do the source code transformation if and when the `ms_transform.hrl` header file is included in your source code. See the `ets` and `dbg:fun2ms/1` function manual pages for documentation on how to use this `parse_transform`, see the `match_spec` chapter in *ERTS users guide* for a description of match specifications.

```
transform_from_shell(Dialect,Clauses,BoundEnvironment) -> term()
```

Types:

- `Dialect` = `ets` | `dbg`
- `Clauses` = Erlang abstract form for a single fun
- `BoundEnvironment` = `[{atom(), term()}, ...]`, list of variable bindings in the shell environment

Implements the actual transformation when the `fun2ms` functions are called from the shell. In this case the abstract form is for one single fun (parsed by the Erlang shell), and all imported variables should be in the key-value list passed as `BoundEnvironment`. The result is a term, normalized, i.e. not in abstract format.

`format_error(Errcode) -> ErrorMessage`

Types:

- `Errcode = term()`
- `ErrorMessage = string()`

Takes an error code returned by one of the other functions in the module and creates a textual description of the error. Fairly uninteresting function actually.

# orddict

Erlang Module

Orddict implements a Key - Value dictionary. An orddict is a representation of a dictionary, where a list of pairs is used to store the keys and values. The list is ordered after the keys.

This module provides exactly the same interface as the module dict but with a defined representation. One difference is that while dict considers two keys as different if they do not match (:=), this module considers two keys as different if and only if they do not compare equal (==).

## DATA TYPES

ordered\_dictionary()  
as returned by new/0

## Exports

append(Key, Value, Orddict1) -> Orddict2

Types:

- Key = Value = term()
- Orddict1 = Orddict2 = ordered\_dictionary()

This function appends a new Value to the current list of values associated with Key. An exception is generated if the initial value associated with Key is not a list of values.

append\_list(Key, ValList, Orddict1) -> Orddict2

Types:

- ValList = [Value]
- Key = Value = term()
- Orddict1 = Orddict2 = ordered\_dictionary()

This function appends a list of values ValList to the current list of values associated with Key. An exception is generated if the initial value associated with Key is not a list of values.

erase(Key, Orddict1) -> Orddict2

Types:

- Key = term()
- Orddict1 = Orddict2 = ordered\_dictionary()

This function erases all items with a given key from a dictionary.

`fetch(Key, Orddict) -> Value`

Types:

- Key = Value = term()
- Orddict = ordered\_dictionary()

This function returns the value associated with `Key` in the dictionary `Orddict`. `fetch` assumes that the `Key` is present in the dictionary and an exception is generated if `Key` is not in the dictionary.

`fetch_keys(Orddict) -> Keys`

Types:

- Orddict = ordered\_dictionary()
- Keys = [term()]

This function returns a list of all keys in the dictionary.

`filter(Pred, Orddict1) -> Orddict2`

Types:

- Pred = fun(Key, Value) -> bool()
- Key = Value = term()
- Orddict1 = Orddict2 = ordered\_dictionary()

`Orddict2` is a dictionary of all keys and values in `Orddict1` for which `Pred(Key, Value)` is true.

`find(Key, Orddict) -> {ok, Value} | error`

Types:

- Key = Value = term()
- Orddict = ordered\_dictionary()

This function searches for a key in a dictionary. Returns `{ok, Value}` where `Value` is the value associated with `Key`, or `error` if the key is not present in the dictionary.

`fold(Fun, Acc0, Orddict) -> Acc1`

Types:

- Fun = fun(Key, Value, AccIn) -> AccOut
- Key = Value = term()
- Acc0 = Acc1 = AccIn = AccOut = term()
- Orddict = ordered\_dictionary()

Calls `Fun` on successive keys and values of `Orddict` together with an extra argument `Acc` (short for accumulator). `Fun` must return a new accumulator which is passed to the next call. `Acc0` is returned if the list is empty. The evaluation order is undefined.

`from_list(List) -> Orddict`

Types:

- List = [{Key, Value}]

- Orddict = ordered\_dictionary()

This function converts the key/value list `List` to a dictionary.

`is_key(Key, Orddict) -> bool()`

Types:

- Key = term()
- Orddict = ordered\_dictionary()

This function tests if `Key` is contained in the dictionary `Orddict`.

`map(Fun, Orddict1) -> Orddict2`

Types:

- Fun = fun(Key, Value1) -> Value2
- Key = Value1 = Value2 = term()
- Orddict1 = Orddict2 = ordered\_dictionary()

`map` calls `Func` on successive keys and values of `Orddict` to return a new value for each key. The evaluation order is undefined.

`merge(Fun, Orddict1, Orddict2) -> Orddict3`

Types:

- Fun = fun(Key, Value1, Value2) -> Value
- Key = Value1 = Value2 = Value3 = term()
- Orddict1 = Orddict2 = Orddict3 = ordered\_dictionary()

`merge` merges two dictionaries, `Orddict1` and `Orddict2`, to create a new dictionary. All the `Key - Value` pairs from both dictionaries are included in the new dictionary. If a key occurs in both dictionaries then `Fun` is called with the key and both values to return a new value. `merge` could be defined as:

```
merge(Fun, D1, D2) ->
  fold(fun (K, V1, D) ->
    update(K, fun (V2) -> Fun(K, V1, V2) end, V1, D)
    end, D2, D1).
```

but is faster.

`new() -> ordered_dictionary()`

This function creates a new dictionary.

`store(Key, Value, Orddict1) -> Orddict2`

Types:

- Key = Value = term()
- Orddict1 = Orddict2 = ordered\_dictionary()

This function stores a `Key - Value` pair in a dictionary. If the `Key` already exists in `Orddict1`, the associated value is replaced by `Value`.

`to_list(Orddict) -> List`

Types:

- Orddict = ordered\_dictionary()
- List = [{Key, Value}]

This function converts the dictionary to a list representation.

```
update(Key, Fun, Orddict1) -> Orddict2
```

Types:

- Key = term()
- Fun = fun(Value1) -> Value2
- Value1 = Value2 = term()
- Orddict1 = Orddict2 = ordered\_dictionary()

Update the a value in a dictionary by calling Fun on the value to get a new value. An exception is generated if Key is not present in the dictionary.

```
update(Key, Fun, Initial, Orddict1) -> Orddict2
```

Types:

- Key = Initial = term()
- Fun = fun(Value1) -> Value2
- Value1 = Value2 = term()
- Orddict1 = Orddict2 = ordered\_dictionary()

Update the a value in a dictionary by calling Fun on the value to get a new value. If Key is not present in the dictionary then Initial will be stored as the first value. For example append/3 could be defined as:

```
append(Key, Val, D) ->  
  update(Key, fun (Old) -> Old ++ [Val] end, [Val], D).
```

```
update_counter(Key, Increment, Orddict1) -> Orddict2
```

Types:

- Key = term()
- Increment = number()
- Orddict1 = Orddict2 = ordered\_dictionary()

Add Increment to the value associated with Key and store this value. If Key is not present in the dictionary then Increment will be stored as the first value.

This could be defined as:

```
update_counter(Key, Incr, D) ->  
  update(Key, fun (Old) -> Old + Incr end, Incr, D).
```

but is faster.

## Notes

The functions `append` and `append_list` are included so we can store keyed values in a list *accumulator*. For example:

```
> D0 = orddict:new(),
  D1 = orddict:store(files, [], D0),
  D2 = orddict:append(files, f1, D1),
  D3 = orddict:append(files, f2, D2),
  D4 = orddict:append(files, f3, D3),
  orddict:fetch(files, D4).
[f1,f2,f3]
```

This saves the trouble of first fetching a keyed value, appending a new value to the list of stored values, and storing the result.

The function `fetch` should be used if the key is known to be in the dictionary, otherwise `find`.

## See Also

`dict(3)` [page 88], `gb_trees(3)` [page 170]

# ordsets

Erlang Module

Sets are collections of elements with no duplicate elements. An `ordset` is a representation of a set, where an ordered list is used to store the elements of the set. An ordered list is more efficient than an unordered list.

This module provides exactly the same interface as the module `sets` but with a defined representation. One difference is that while `sets` considers two elements as different if they do not match (`:=:`), this module considers two elements as different if and only if they do not compare equal (`==`).

## DATA TYPES

`ordered_set()`  
as returned by `new/0`

## Exports

`new()` -> `Ordset`

Types:

- `Ordset = ordered_set()`

Returns a new empty ordered set.

`is_set(Ordset)` -> `bool()`

Types:

- `Ordset = term()`

Returns true if `Ordset` is an ordered set of elements, otherwise false.

`size(Ordset)` -> `int()`

Types:

- `Ordset = term()`

Returns the number of elements in `Ordset`.

`to_list(Ordset)` -> `List`

Types:

- `Ordset = ordered_set()`
- `List = [term()]`

Returns the elements of `Ordset` as a list.

`from_list(List) -> Ordset`

Types:

- `List = [term()]`
- `Ordset = ordered_set()`

Returns an ordered set of the elements in `List`.

`is_element(Element, Ordset) -> bool()`

Types:

- `Element = term()`
- `Ordset = ordered_set()`

Returns true if `Element` is an element of `Ordset`, otherwise false.

`add_element(Element, Ordset1) -> Ordset2`

Types:

- `Element = term()`
- `Ordset1 = Ordset2 = ordered_set()`

Returns a new ordered set formed from `Ordset1` with `Element` inserted.

`del_element(Element, Ordset1) -> Ordset2`

Types:

- `Element = term()`
- `Ordset1 = Ordset2 = ordered_set()`

Returns `Ordset1`, but with `Element` removed.

`union(Ordset1, Ordset2) -> Ordset3`

Types:

- `Ordset1 = Ordset2 = Ordset3 = ordered_set()`

Returns the merged (union) set of `Ordset1` and `Ordset2`.

`union(OrdsetList) -> Ordset`

Types:

- `OrdsetList = [ordered_set()]`
- `Ordset = ordered_set()`

Returns the merged (union) set of the list of sets.

`intersection(Ordset1, Ordset2) -> Ordset3`

Types:

- `Ordset1 = Ordset2 = Ordset3 = ordered_set()`

Returns the intersection of `Ordset1` and `Ordset2`.

`intersection(OrdsetList) -> Ordset`

Types:

- `OrdsetList = [ordered_set()]`
- `Ordset = ordered_set()`

Returns the intersection of the non-empty list of sets.

`subtract(Ordset1, Ordset2) -> Ordset3`

Types:

- `Ordset1 = Ordset2 = Ordset3 = ordered_set()`

Returns only the elements of `Ordset1` which are not also elements of `Ordset2`.

`is_subset(Ordset1, Ordset2) -> bool()`

Types:

- `Ordset1 = Ordset2 = ordered_set()`

Returns true when every element of `Ordset1` is also a member of `Ordset2`, otherwise false.

`fold(Function, Acc0, Ordset) -> Acc1`

Types:

- `Function = fun (E, AccIn) -> AccOut`
- `Acc0 = Acc1 = AccIn = AccOut = term()`
- `Ordset = ordered_set()`

Fold `Function` over every element in `Ordset` returning the final value of the accumulator.

`filter(Pred, Ordset1) -> Set2`

Types:

- `Pred = fun (E) -> bool()`
- `Set1 = Set2 = ordered_set()`

Filter elements in `Set1` with boolean function `Fun`.

## See Also

[gb\\_sets\(3\)](#) [page 164], [sets\(3\)](#) [page 301]

# pg

## Erlang Module

This (experimental) module implements process groups. A process group is a group of processes that can be accessed by a common name. For example, a group named `foobar` can include a set of processes as members of this group and they can be located on different nodes.

When messages are sent to the named group, all members of the group receive the message. The messages are serialized. If the process `P1` sends the message `M1` to the group, and process `P2` simultaneously sends message `M2`, then all members of the group receive the two messages in the same order. If members of a group terminate, they are automatically removed from the group.

This module is not complete. The module is inspired by the ISIS system and the causal order protocol of the ISIS system should also be implemented. At the moment, all messages are serialized by sending them through a group master process.

## Exports

```
create(PgName) -> ok | {error, Reason}
```

Types:

- `PgName = term()`
- `Reason = already_created | term()`

Creates an empty group named `PgName` on the current node.

```
create(PgName, Node) -> ok | {error, Reason}
```

Types:

- `PgName = term()`
- `Node = node()`
- `Reason = already_created | term()`

Creates an empty group named `PgName` on the node `Node`.

```
join(PgName, Pid) -> Members
```

Types:

- `PgName = term()`
- `Pid = pid()`
- `Members = [pid()]`

Joins the pid `Pid` to the process group `PgName`. Returns a list of all old members of the group.

`send(PgName, Msg) -> void()`

Types:

- `PgName = Msg = term()`

Sends the tuple `{pg_message, From, PgName, Msg}` to all members of the process group `PgName`.

Failure: `{badarg, {PgName, Msg}}` if `PgName` is not a process group (a globally registered name).

`esend(PgName, Msg) -> void()`

Types:

- `PgName = Msg = term()`

Sends the tuple `{pg_message, From, PgName, Msg}` to all members of the process group `PgName`, except ourselves.

Failure: `{badarg, {PgName, Msg}}` if `PgName` is not a process group (a globally registered name).

`members(PgName) -> Members`

Types:

- `PgName = term()`
- `Members = [pid()]`

Returns a list of all members of the process group `PgName`.

# pool

Erlang Module

`pool` can be used to run a set of Erlang nodes as a pool of computational processors. It is organized as a master and a set of slave nodes and includes the following features:

- The slave nodes send regular reports to the master about their current load.
- Queries can be sent to the master to determine which node will have the least load.

The BIF `statistics(run_queue)` is used for estimating future loads. It returns the length of the queue of ready to run processes in the Erlang runtime system.

The slave nodes are started with the `slave` module. This effects, tty IO, file IO, and code loading.

If the master node fails, the entire pool will exit.

## Exports

`start(Name) ->`

`start(Name, Args) -> Nodes`

Types:

- `Name = atom()`
- `Args = string()`
- `Nodes = [node()]`

Starts a new pool. The file `.hosts.erlang` is read to find host names where the pool nodes can be started. See section Files [page 262] below. The start-up procedure fails if the file is not found.

The slave nodes are started with `slave:start/2,3`, passing along `Name` and, if provided, `Args`. `Name` is used as the first part of the node names, `Args` is used to specify command line arguments. See `slave(3)` [page 315].

Access rights must be set so that all nodes in the pool have the authority to access each other.

The function is synchronous and all the nodes, as well as all the system servers, are running when it returns a value.

`attach(Node) -> already_attached | attached`

Types:

- `Node = node()`

This function ensures that a pool master is running and includes `Node` in the pool master's pool of nodes.

`stop()` -> `stopped`

Stops the pool and kills all the slave nodes.

`get_nodes()` -> `Nodes`

Types:

- `Nodes = [node()]`

Returns a list of the current member nodes of the pool.

`pspawn(Mod, Fun, Args)` -> `pid()`

Types:

- `Mod = Fun = atom()`
- `Args = [term()]`

Spawns a process on the pool node which is expected to have the lowest future load.

`pspawn_link(Mod, Fun, Args)` -> `pid()`

Types:

- `Mod = Fun = atom()`
- `Args = [term()]`

Spawn links a process on the pool node which is expected to have the lowest future load.

`get_node()` -> `node()`

Returns the node with the expected lowest future load.

## Files

`.hosts.erlang` is used to pick hosts where nodes can be started. See `[net_adm(3)]` for information about format and location of this file.

`$HOME/.erlang.slave.out.HOST` is used for all additional IO that may come from the slave nodes on standard IO. If the start-up procedure does not work, this file may indicate the reason.

# proc\_lib

Erlang Module

This module is used to start processes adhering to the [OTP Design Principles]. Specifically, the functions in this module are used by the OTP standard behaviors (`gen_server`, `gen_fsm`, ...) when starting new processes. The functions can also be used to start *special processes*, user defined processes which comply to the OTP design principles. See [Sys and Proc.Lib] in OTP Design Principles for an example.

Some useful information is initialized when a process starts. The registered names, or the process identifiers, of the parent process, and the parent ancestors, are stored together with information about the function initially called in the process.

While in “plain Erlang” a process is said to terminate normally only for the exit reason `normal`, a process started using `proc_lib` is also said to terminate normally if it exits with reason `shutdown`. This is the reason used when an application (supervision tree) is stopped.

When a process started using `proc_lib` terminates abnormally – that is, with another exit reason than `normal` or `shutdown` – a *crash report* is generated, which is written to terminal by the default SASL event handler. That is, the crash report is normally only visible if the SASL application is started. See [sasl(6)] and [SASL User’s Guide].

The crash report contains the previously stored information such as ancestors and initial function, the termination reason, and information regarding other processes which terminate as a result of this process terminating.

## Exports

```
spawn(Fun) -> pid()
spawn(Node, Fun) -> pid()
spawn(Module, Function, Args) -> pid()
spawn(Node, Module, Function, Args) -> pid()
```

Types:

- Node = `node()`
- Fun = `fun() -> void()`
- Module = Function = `atom()`
- Args = [`term()`]

Spawns a new process and initializes it as described above. The process is spawned using the [spawn] BIFs.

```
spawn_link(Fun) -> pid()
spawn_link(Node, Fun) -> pid()
spawn_link(Module, Function, Args) -> pid()
```

`spawn_link(Node, Module, Function, Args) -> pid()`

Types:

- Node = `node()`
- Fun = `fun() -> void()`
- Module = Function = `atom()`
- Args = `[term()]`

Spawns a new process and initializes it as described above. The process is spawned using the `[spawn_link]` BIFs.

`spawn_opt(Fun, SpawnOpts) -> pid()`

`spawn_opt(Node, Fun, SpawnOpts) -> pid()`

`spawn_opt(Module, Function, Args, SpawnOpts) -> pid()`

`spawn_opt(Node, Module, Func, Args, SpawnOpts) -> pid()`

Types:

- Node = `node()`
- Fun = `fun() -> void()`
- Module = Function = `atom()`
- Args = `[term()]`
- SpawnOpts – see `erlang:spawn_opt/2,3,4,5`

Spawns a new process and initializes it as described above. The process is spawned using the `[spawn_opt]` BIFs.

**Note:**

Using the spawn option `monitor` is currently not allowed, but will cause the function to fail with reason `badarg`.

`start(Module, Function, Args) -> Ret`

`start(Module, Function, Args, Time) -> Ret`

`start(Module, Function, Args, Time, SpawnOpts) -> Ret`

`start_link(Module, Function, Args) -> Ret`

`start_link(Module, Function, Args, Time) -> Ret`

`start_link(Module, Function, Args, Time, SpawnOpts) -> Ret`

Types:

- Module = Function = `atom()`
- Args = `[term()]`
- Time = `int() >= 0 | infinity`
- SpawnOpts – see `erlang:spawn_opt/2,3,4,5`
- Ret = `term() | {error, Reason}`

Starts a new process synchronously. Spawns the process and waits for it to start. When the process has started, it *must* call `init_ack(Parent,Ret)` [page 265] or `init_ack(Ret)` [page 265], where `Parent` is the process that evaluates this function. At this time, `Ret` is returned.

If the `start_link/3,4,5` function is used and the process crashes before it has called `init_ack/1,2`, `{error, Reason}` is returned if the calling process traps exits.

If `Time` is specified as an integer, this function waits for `Time` milliseconds for the new process to call `init_ack`, or `{error, timeout}` is returned, and the process is killed.

The `SpawnOpts` argument, if given, will be passed as the last argument to the `spawn_opt/2,3,4,5` BIF.

### Note:

Using the spawn option `monitor` is currently not allowed, but will cause the function to fail with reason `badarg`.

```
init_ack(Parent, Ret) -> void()
```

```
init_ack(Ret) -> void()
```

Types:

- `Parent` = `pid()`
- `Ret` = `term()`

This function must be used by a process that has been started by a `start[_link]/3,4,5` [page 264] function. It tells `Parent` that the process has initialized itself, has started, or has failed to initialize itself.

The `init_ack/1` function uses the parent value previously stored by the `start` function used.

If this function is not called, the `start` function will return an error tuple (if a link and/or a timeout is used) or hang otherwise.

The following example illustrates how this function and `proc_lib:start_link/3` are used.

```
-module(my_proc).
-export([start_link/0]).
-export([init/1]).
```

```
start_link() ->
    proc_lib:start_link(my_proc, init, [self()]).
```

```
init(Parent) ->
    case do_initialization() of
    ok ->
        proc_lib:init_ack(Parent, {ok, self()});
    {error, Reason} ->
        exit(Reason)
    end,
    loop().
```

...

```
format(CrashReport) -> string()
```

Types:

- CrashReport = term()

This function can be used by a user defined event handler to format a crash report. The crash report is sent using `error_logger:error_report(crash_report, CrashReport)`. That is, the event to be handled is of the format `{error_report, GL, {Pid, crash_report, CrashReport}}` where GL is the group leader pid of the process Pid which sent the crash report.

```
initial_call(Process) -> {Module,Function,Args} | Fun | false
```

Types:

- Process = pid() | {X,Y,Z} | ProcInfo
- X = Y = Z = int()
- ProcInfo = term()
- Module = Function = atom()
- Args = [term()]
- Fun = fun() -> void()

Extracts the initial call of a process that was started using one of the spawn or start functions described above. Process can either be a pid, an integer tuple (from which a pid can be created), or the process information of a process Pid fetched through an `erlang:process_info(Pid)` function call.

```
translate_initial_call(Process) -> {Module,Function,Arity} | Fun
```

Types:

- Process = pid() | {X,Y,Z} | ProcInfo
- X = Y = Z = int()
- ProcInfo = term()
- Module = Function = atom()
- Arity = int()
- Fun = fun() -> void()

This function is used by the `c:i/0` and `c:regs/0` functions in order to present process information.

Extracts the initial call of a process that was started using one of the spawn or start functions described above, and translates it to more useful information. Process can either be a pid, an integer tuple (from which a pid can be created), or the process information of a process Pid fetched through an `erlang:process_info(Pid)` function call.

If the initial call is to one of the system defined behaviors such as `gen_server` or `gen_event`, it is translated to more useful information. If a `gen_server` is spawned, the returned Module is the name of the callback module and Function is `init` (the function that initiates the new server).

A supervisor and a supervisor\_bridge are also `gen_server` processes. In order to return information that this process is a supervisor and the name of the call-back module, Module is `supervisor` and Function is the name of the supervisor callback module. Arity is 1 since the `init/1` function is called initially in the callback module.

By default, `{proc_lib,init_p,5}` is returned if no information about the initial call can be found. It is assumed that the caller knows that the process has been spawned with the `proc_lib` module.

`hibernate(Module, Function, Args)`

Types:

- `Module = Function = atom()`
- `Args = [term()]`

This function does the same as (and does call) the BIF `[hibernate/3]`, but ensures that exception handling and logging continues to work as expected when the process wakes up. Always use this function instead of the BIF for processes started using `proc_lib` functions.

## SEE ALSO

`[error_logger(3)]`

# proplists

Erlang Module

Property lists are ordinary lists containing entries in the form of either tuples, whose first elements are keys used for lookup and insertion, or atoms, which work as shorthand for tuples `{Atom, true}`. (Other terms are allowed in the lists, but are ignored by this module.) If there is more than one entry in a list for a certain key, the first occurrence normally overrides any later (irrespective of the arity of the tuples).

Property lists are useful for representing inherited properties, such as options passed to a function where a user may specify options overriding the default settings, object properties, annotations, etc.

## Exports

`append_values(Key, List) -> List`

Types:

- Key = term()
- List = [term()]

Similar to `get_all_values/2`, but each value is wrapped in a list unless it is already itself a list, and the resulting list of lists is concatenated. This is often useful for “incremental” options; e.g., `append_values(a, [{a, [1,2]}, {b, 0}, {a, 3}, {c, -1}, {a, [4]}])` will return the list `[1,2,3,4]`.

`compact(List) -> List`

Types:

- List = [term()]

Minimizes the representation of all entries in the list. This is equivalent to `[property(P) || P <- List]`.

See also: `property/1`, `unfold/1`.

`delete(Key, List) -> List`

Types:

- Key = term()
- List = [term()]

Deletes all entries associated with `Key` from `List`.

`expand(Expansions, List) -> List`

Types:

- Key = term()
- Expansions = [{Property,[term()]}]
- Property = atom() | tuple()

Expands particular properties to corresponding sets of properties (or other terms). For each pair {Property, Expansion} in Expansions, if E is the first entry in List with the same key as Property, and E and Property have equivalent normal forms, then E is replaced with the terms in Expansion, and any following entries with the same key are deleted from List.

For example, the following expressions all return [fie, bar, baz, fum]:

```
expand([foo, [bar, baz]]),
[fie, foo, fum])
expand([foo, true], [bar, baz]),
[fie, foo, fum])
expand([foo, false], [bar, baz]),
[fie, {foo, false}, fum])
```

However, no expansion is done in the following call:

```
expand([foo, true], [bar, baz]),
[foo, false], fie, foo, fum])
```

because {foo, false} shadows foo.

Note that if the original property term is to be preserved in the result when expanded, it must be included in the expansion list. The inserted terms are not expanded recursively. If Expansions contains more than one property with the same key, only the first occurrence is used.

See also: `normalize/2`.

`get_all_values(Key, List) -> [term()]`

Types:

- Key = term()
- List = [term()]

Similar to `get_value/2`, but returns the list of values for *all* entries {Key, Value} in List. If no such entry exists, the result is the empty list.

See also: `get_value/2`.

`get_bool(Key, List) -> bool()`

Types:

- Key = term()
- List = [term()]

Returns the value of a boolean key/value option. If `lookup(Key, List)` would yield {Key, true}, this function returns true; otherwise false is returned.

See also: `get_value/2`, `lookup/2`.

`get_keys(List) -> [term()]`

Types:

- List = [term()]

Returns an unordered list of the keys used in `List`, not containing duplicates.

`get_value(Key, List) -> term()`

Types:

- `Key = term()`
- `List = [term()]`

Equivalent to `get_value(Key, List, undefined)`.

`get_value(Key, List, Default) -> term()`

Types:

- `Key = term()`
- `Default = term()`
- `List = [term()]`

Returns the value of a simple key/value property in `List`. If `lookup(Key, List)` would yield `{Key, Value}`, this function returns the corresponding `Value`, otherwise `Default` is returned.

See also: `get_all_values/2`, `get_bool/2`, `get_value/1`, `lookup/2`.

`is_defined(Key, List) -> bool()`

Types:

- `Key = term()`
- `List = [term()]`

Returns `true` if `List` contains at least one entry associated with `Key`, otherwise `false` is returned.

`lookup(Key, List) -> none | tuple()`

Types:

- `Key = term()`
- `List = [term()]`

Returns the first entry associated with `Key` in `List`, if one exists, otherwise returns `none`. For an atom `A` in the list, the tuple `{A, true}` is the entry associated with `A`.

See also: `get_bool/2`, `get_value/2`, `lookup_all/2`.

`lookup_all(Key, List) -> [tuple()]`

Types:

- `Key = term()`
- `List = [term()]`

Returns the list of all entries associated with `Key` in `List`. If no such entry exists, the result is the empty list.

See also: `lookup/2`.

`normalize(List, Stages) -> List`

Types:

- List = [term()]
- Stages = [Operation]
- Operation = {aliases, Aliases} | {negations, Negations} | {expand, Expansions}
- Aliases = [{Key, Key}]
- Negations = [{Key, Key}]
- Key = term()
- Expansions = [{Property, [term()]}]
- Property = atom() | tuple()

Passes List through a sequence of substitution/expansion stages. For an `aliases` operation, the function `substitute_aliases/2` is applied using the given list of aliases; for a `negations` operation, `substitute_negations/2` is applied using the given negation list; for an `expand` operation, the function `expand/2` is applied using the given list of expansions. The final result is automatically compacted (cf. `compact/1`).

Typically you want to substitute negations first, then aliases, then perform one or more expansions (sometimes you want to pre-expand particular entries before doing the main expansion). You might want to substitute negations and/or aliases repeatedly, to allow such forms in the right-hand side of aliases and expansion lists.

See also: `compact/1`, `expand/2`, `substitute_aliases/2`, `substitute_negations/2`.

`property(Property) -> Property`

Types:

- Property = atom() | tuple()

Creates a normal form (minimal) representation of a property. If Property is {Key, true} where Key is an atom, this returns Key, otherwise the whole term Property is returned.

See also: `property/2`.

`property(Key, Value) -> Property`

Types:

- Key = term()
- Value = term()
- Property = atom() | tuple()

Creates a normal form (minimal) representation of a simple key/value property. Returns Key if Value is true and Key is an atom, otherwise a tuple {Key, Value} is returned.

See also: `property/1`.

`split(List, Keys) -> {Lists, Rest}`

Types:

- List = [term()]
- Keys = [term()]
- Lists = [[term()]]
- Rest = [term()]

Partitions `List` into a list of sublists and a remainder. `Lists` contains one sublist for each key in `Keys`, in the corresponding order. The relative order of the elements in each sublist is preserved from the original `List`. `Rest` contains the elements in `List` that are not associated with any of the given keys, also with their original relative order preserved.

Example: `split([c, 2], [e, 1], a, [c, 3, 4], d, [b, 5], b), [a, b, c])`

returns

```
{[[a], [[b, 5], b],[c, 2], [c, 3, 4]], [[e, 1], d]}
```

`substitute_aliases(Aliases, List) -> List`

Types:

- `Aliases = [{Key, Key}]`
- `Key = term()`
- `List = [term()]`

Substitutes keys of properties. For each entry in `List`, if it is associated with some key `K1` such that `{K1, K2}` occurs in `Aliases`, the key of the entry is changed to `Key2`. If the same `K1` occurs more than once in `Aliases`, only the first occurrence is used.

Example: `substitute_aliases([color, colour], L)` will replace all tuples `{color, ...}` in `L` with `{colour, ...}`, and all atoms `color` with `colour`.

See also: `normalize/2`, `substitute_negations/2`.

`substitute_negations(Negations, List) -> List`

Types:

- `Negations = [{Key, Key}]`
- `Key = term()`
- `List = [term()]`

Substitutes keys of boolean-valued properties and simultaneously negates their values. For each entry in `List`, if it is associated with some key `K1` such that `{K1, K2}` occurs in `Negations`, then if the entry was `{K1, true}` it will be replaced with `{K2, false}`, otherwise it will be replaced with `{K2, true}`, thus changing the name of the option and simultaneously negating the value given by `get_bool(List)`. If the same `K1` occurs more than once in `Negations`, only the first occurrence is used.

Example: `substitute_negations([no_foo, foo], L)` will replace any atom `no_foo` or tuple `{no_foo, true}` in `L` with `{foo, false}`, and any other tuple `{no_foo, ...}` with `{foo, true}`.

See also: `get_bool/2`, `normalize/2`, `substitute_aliases/2`.

`unfold(List) -> List`

Types:

- `List = [term()]`

Unfolds all occurrences of atoms in `List` to tuples `{Atom, true}`.

# qlc

Erlang Module

The `qlc` module provides a query interface to Mnesia, ETS, Dets and other data structures that implement an iterator style traversal of objects.

## Overview

The `qlc` module implements a query interface to *QLC tables*. Typical QLC tables are ETS, Dets, and Mnesia tables. There is also support for user defined tables, see the [Implementing a QLC table \[page 278\]](#) section. A *query* is stated using *Query List Comprehensions* (QLCs). These are similar to ordinary list comprehensions as described in the Erlang Reference Manual and Programming Examples except that variables introduced in patterns cannot be used in list expressions. The answers to a query are determined by data in QLC tables that fulfill the constraints expressed by the QLCs of the query.

QLCs should not be confused with the language construct `query ListComprehension end` used by Mnesosyne. The `qlc` module recognizes the first argument of every call to `qlc:q/1,2` as QLCs, and nothing else. The semantics are very different: Mnesosyne uses ideas borrowed from Prolog while the QLCs introduced in this module are all Erlang. In fact, in the absence of optimizations and options such as `cache` and `unique` (see below), every QLC free of QLC tables evaluates to the same list of answers as the identical ordinary list comprehension. It is the aim of this module to replace Mnesosyne and to be more versatile by means of QLC tables.

While ordinary list comprehensions evaluate to lists, calling `qlc:q/1,2` [\[page 283\]](#) returns a *Query Handle*. To obtain all the answers to a query, `qlc:eval/1,2` [\[page 281\]](#) should be called with the query handle as first argument. Query handles are essentially functions created in the module calling `q/1,2`. As the functions refer to the module's code, one should be careful not to keep query handles too long if the module's code is to be replaced. Code replacement is described in the [\[Erlang Reference Manual\]](#). The list of answers can also be traversed in chunks by use of a *Query Cursor*. Query cursors are created by calling `qlc:cursor/1,2` [\[page 280\]](#) with a query handle as first argument. Query cursors are essentially Erlang processes. One answer at a time is sent from the query cursor process to the process that created the cursor.

## Syntax

Syntactically QLCs have the same parts as ordinary list comprehensions:

```
[Expression || Qualifier1, Qualifier2, ...]
```

Expression (the *template*) is an arbitrary Erlang expression. Qualifiers are either *filters* or *generators*. Filters are Erlang expressions returning `bool()`. Generators have the form `Pattern<-ListExpression`, where `ListExpression` is an expression evaluating to a query handle or a list. Query handles are returned from `qlc:table/2`, `qlc:append/1,2`, `qlc:sort/1,2`, `qlc:keysort/2,3`, `qlc:q/1,2`, and `qlc:string_to_handle/1,2,3`.

## Evaluation

The evaluation of a query handle begins by the inspection of options and the collection of information about tables. As a result qualifiers are modified during the optimization phase. Next all list expressions are evaluated. If a cursor has been created evaluation takes place in the cursor process. For those list expressions that are QLCs, the list expressions of the QLCs' generators are evaluated as well. One has to be careful if list expressions have side effects since the order in which list expressions are evaluated is unspecified. Finally the answers are found by evaluating the qualifiers from left to right, backtracking when some filter returns `false`, or collecting the template when all filters return `true`.

Filters that do not return `bool()` but fail are handled differently depending on their syntax: if the filter is a guard it returns `false`, otherwise the query evaluation fails. This behavior makes it possible for QLC to do some optimizations without affecting the meaning of a query. For example, when some position of a table is compared to one or more constants, only the objects with matching values are candidates for further evaluation. The other objects are guaranteed to make the filter return `false`, but never fail. The (small) set of candidate objects can often be found by looking up some key values of the table or by traversing the table using a match specification. It is necessary to place the guard filters immediately after the table's generator, otherwise it could happen that some table object that would make the query evaluation fail is excluded by looking up a key or running a match specification.

## Join

QLC supports fast join of two query handles. Fast join is possible if some position (P1) of one query handler is compared to or matched against some position (P2) of another query handle. Two fast join methods have been implemented:

- Lookup join traverses all objects of one query handle and finds objects of the other handle (a QLC table) such that the values at P1 and P2 match. QLC does not create any indices but looks up values using the key position and the indexed positions of the QLC table.
- Merge join sorts the objects of each query handle if necessary and filters out objects where the values at P1 and P2 do not compare equal. If there are many objects with the same value of P2 a temporary file will be used for the equivalence classes.

QLC warns at compile time if a query list comprehension combines QLC handles in such a way that more than one join is possible. In other words, there is no query planner that can choose a good order between possible join operations. It is up to the user to order the joins by introducing query handles.

The join is to be expressed as a guard filter. The filter must be placed immediately after the two joined generators, possibly after guard filters that use variables from no other generators but the two joined generators. QLC inspects the operands of `:=/2`, `==/2`,

`is_record/2`, `element/2`, and logical operators (`and/2`, `or/2`, `andalso/2`, `orelse/2`, `xor/2`) when determining which joins to consider.

## Common options

The following options are accepted by `cursor/2`, `eval/2`, `fold/4`, and `info/2`:

- `{cache_all, CacheAll}` where `CacheAll` is equal to `ets` or `list` adds a `{cache, CacheAll}` option to every list expression of the query except tables and lists. Default is `{cache_all, no}`. The option `cache_all` is equivalent to `{cache_all, ets}`.
- `{max_list_size, MaxListSize}` where `MaxListSize` is the size in bytes of terms on the external format. If the accumulated size of collected objects exceeds `MaxListSize` the objects are written onto a temporary file. This option is used by the `{cache, list}` option as well as by the merge join method. Default is `512*1024` bytes.
- `{tmpdir, TempDirectory}` sets the directory used by merge join for temporary files and by the `{cache, list}` option. The option also overrides the `<c>tmpdir` option of `keysort/3` and `sort/2`. The default value is `"` which means that the directory returned by `file:get_cwd()` is used.
- `{unique_all, true}` adds a `{unique, true}` option to every list expression of the query. Default is `{unique_all, false}`. The option `unique_all` is equivalent to `{unique_all, true}`.

## Common data types

- `QueryCursor` = `{qlc_cursor, term()}`
- `QueryHandle` = `{qlc_handle, term()}`
- `QueryHandleOrList` = `QueryHandle` | `list()`
- `Answers` = `[Answer]`
- `Answer` = `term()`
- `AbstractExpression` = `-parse trees for Erlang expressions, see the [ abstract format] documentation in ERTS User's Guide-`
- `MatchExpression` = `-matchspecifications, see the [ match specification] documentation in the ERTS User's Guide and ms_transform(3) [page 240]-`
- `SpawnOptions` = `default` | `spawn_options()`
- `SortOptions` = `[SortOption]` | `SortOption`
- `SortOption` = `{compressed, bool()}` | `{no_files, NoFiles}` | `{order, Order}` | `{size, Size}` | `{tmpdir, TempDirectory}` | `{unique, bool()}`  
-see `file_sorter(3)` [page 150]-
- `Order` = `ascending` | `descending` | `OrderFun`
- `OrderFun` = `fun(Term, Term) -> bool()`
- `TempDirectory` = `"` | `filename()`
- `Size` = `int() > 0`
- `NoFiles` = `int() > 1`

- `KeyPos = int() > 0 | [int() > 0]`
- `MaxListSize = int() >= 0`
- `bool() = true | false`
- `Cache = ets | list | no`
- `filename() = -see filename(3) [page 158]-`
- `spawn_options() = -see [erlang(3)]-`

## Getting started

As already mentioned queries are stated in the list comprehension syntax as described in the [Erlang Reference Manual]. In the following some familiarity with list comprehensions is assumed. There are examples in [Programming Examples] that can get you started. It should be stressed that list comprehensions do not add any computational power to the language; anything that can be done with list comprehensions can also be done without them. But they add a syntax for expressing simple search problems which is compact and clear once you get used to it.

Many list comprehension expressions can be evaluated by the `qlc` module. Exceptions are expressions such that variables introduced in patterns (or filters) are used in some generator later in the list comprehension. As an example consider an implementation of `lists:append(L): [X || Y <- L, X <- Y]`. `Y` is introduced in the first generator and used in the second. The ordinary list comprehension is normally to be preferred when there is a choice as to which to use. One difference is that `qlc:eval/1,2` collects answers in a list which is finally reversed, while list comprehensions collect answers on the stack which is finally unwound.

What the `qlc` module primarily adds to list comprehensions is that data can be read from QLC tables in small chunks. A QLC table is created by calling `qlc:table/2`. Usually `qlc:table/2` is not called directly from the query but via an interface function of some data structure. There are a few examples of such functions in Erlang/OTP: `mesia:table/1,2`, `ets:table/1,2`, and `dets:table/1,2`. For a given data structure there can be several functions that create QLC tables, but common for all these functions is that they return a query handle created by `qlc:table/2`. Using the QLC tables provided by OTP is probably sufficient in most cases, but for the more advanced user the section Implementing a QLC table [page 278] describes the implementation of a function calling `qlc:table/2`.

Besides `qlc:table/2` there are other functions that return query handles. They might not be used as often as tables, but are useful from time to time. `qlc:append` traverses objects from several tables or lists after each other. If, for instance, you want to traverse all answers to a query `QH` and then finish off by a term `{finished}`, you can do that by calling `qlc:append(QH, [{finished}])`. `append` first returns all objects of `QH`, then `{finished}`. If there is one tuple `{finished}` among the answers to `QH` it will be returned twice from `append`.

As another example, consider concatenating the answers to two queries `QH1` and `QH2` while removing all duplicates. The means to accomplish this is to use the `unique` option:

```
qlc:q([X || X <- qlc:append(QH1, QH2)], {unique, true})
```

The cost is substantial: every returned answer will be stored in an ETS table. Before returning an answer it is looked up in the ETS table to check if it has already been returned. Without the `unique` options all answers to QH1 would be returned followed by all answers to QH2. The `unique` options keeps the order between the remaining answers.

If the order of the answers is not important there is the alternative to sort the answers uniquely:

```
qlc:sort(qlc:q([X || X <- qlc:append(QH1, QH2)], {unique, true})).
```

This query also removes duplicates but the answers will be sorted. If there are many answers temporary files will be used. Note that in order to get the first unique answer all answers have to be found and sorted.

To return just a few answers cursors can be used. The following code returns no more than five answers using an ETS table for storing the unique answers:

```
C = qlc:cursor(qlc:q([X || X <- qlc:append(QH1, QH2)], {unique, true})),
R = qlc:next_answers(C, 5),
ok = qlc:delete_cursor(C),
R.
```

Query list comprehensions are convenient for stating constraints on data from two or more tables. An example that does a natural join on two query handles on position 2:

```
qlc:q([X1, X2, X3, Y1] ||
      {X1, X2, X3} <- QH1,
      {Y1, Y2} <- QH2,
      X2 == Y2])
```

QLC will evaluate this differently depending on the query handles QH1 and QH2. If, for example, X2 is matched against the key of a QLC table the lookup join method will traverse the objects of QH2 while looking up key values in the table. On the other hand, if neither X2 nor Y2 is matched against the key or an indexed position of a QLC table, the merge join method will make sure that QH1 and QH2 are both sorted on position 2 and next do the join by traversing the objects one by one.

The `join` option can be used to force QLC to use a certain join method. For the rest of this section it is assumed that the excessively slow join method called “nested loop” has been chosen:

```
qlc:q([X1, X2, X3, Y1] ||
      {X1, X2, X3} <- QH1,
      {Y1, Y2} <- QH2,
      X2 == Y2],
      {join, nested_loop})
```

In this case the filter will be applied to every possible pair of answers to QH1 and QH2, one at a time. If there are M answers to QH1 and N answers to QH2 the filter will be run M\*N times.

If QH2 is a call to the function for `gb_trees` as defined in the Implementing a QLC table [page 278] section, `gb_table:table/1`, the iterator for the gb-tree will be initiated for each answer to QH1 after which the objects of the gb-tree will be returned one by one. This is probably the most efficient way of traversing the table in that case since it takes minimal computational power to get the following object. But if QH2 is not a table but a more complicated QLC, it can be more efficient use some RAM memory for collecting the answers in a cache, particularly if there are only a few answers. It must then be assumed that evaluating QH2 has no side effects so that the

meaning of the query does not change if QH2 is evaluated only once. One way of caching the answers is to evaluate QH2 first of all and substitute the list of answers for QH2 in the query. Another way is to use the `cache` option. It is stated like this:

```
QH2' = qlc:q([X || X <- QH2], {cache, ets})
```

or just

```
QH2' = qlc:q([X || X <- QH2], cache)
```

The effect of the `cache` option is that when the generator QH2' is run the first time every answer is stored in an ETS table. When next answer of QH1 is tried, answers to QH2' are copied from the ETS table which is very fast. As for the `unique` option the cost is a possibly substantial amount of RAM memory. The `{cache,list}` option offers the possibility to store the answers in a list on the process heap. While this has the potential of being faster than ETS tables since there is no need to copy answers from the table it can often result in slower evaluation due to more garbage collections of the process' heap as well as increased RAM memory consumption due to bigger heaps. Another drawback with cache lists is that if the size of the list exceeds a limit a temporary file will be used. Reading the answers from a file is very much slower than copying them from an ETS table. But if the available RAM memory is scarce setting the limit [page 275] to some low value is an alternative.

There is an option `cache_all` that can be set to `ets` or `list` when evaluating a query. It adds a `cache` or `{cache,list}` option to every list expression except QLC tables and lists on all levels of the query. This can be used for testing if caching would improve efficiency at all. If the answer is yes further testing is needed to pinpoint the generators that should be cached.

## Implementing a QLC table

As an example of how to use the `qlc:table/2` [page 283] function the implementation of a QLC table for the `gb_trees` [page 170] module is given:

```
-module(gb_table).

-import(gb_trees, [iterator/1, lookup/2, next/1]).

-export([table/1]).

table(T) ->
  TF = fun() -> qlc_next(next(iterator(T))) end,
  InfoFun = fun(num_of_objects) -> size(T);
            (keypos) -> 1;
            (_) -> undefined
          end,
  LookupFun =
    fun(1, Ks) ->
      lists:flatmap(fun(K) ->
        case gb_trees:lookup(K, T) of
          {value, V} -> [{K,V}];
          none -> []
        end
      end, Ks)
    end,
```

```

FormatFun =
  fun(all) ->
    Vals = a_few(T),
    {gb_trees, from_orddict, [Vals]};
  ({lookup, 1, KeyValues}) ->
    ValsS = io_lib:format("gb_trees:from_orddict(~w)",
                          [a_few(T)]),
    io_lib:format("lists:flatmap(fun(K) -> "
                  "case gb_trees:lookup(K, ~s) of "
                  "{value, V} -> [{K,V}];none -> [] end "
                  "end, ~w)",
                  [ValsS, KeyValues])
  end,
qlc:table(TF, [{info_fun, InfoFun}, {format_fun, FormatFun},
              {lookup_fun, LookupFun}]).

qlc_next({X, V, S}) ->
  [{X,V} | fun() -> qlc_next(next(S)) end];
qlc_next(none) ->
  [].

a_few(T) ->
  a_few(iterator(T), 7).

a_few(_I, 0) ->
  more;
a_few(I0, N) ->
  case next(I0) of
    {X, V, I} ->
      [{X,V} | a_few(I, N-1)];
    none ->
      []
  end.

```

TF is the traversal function. The `qlc` module requires that there is a way of traversing all objects of the data structure; in `gb_trees` there is an iterator function suitable for that purpose. Note that for each object returned a new fun is created. As long as the list is not terminated by `[]` it is assumed that the tail of the list is a nullary function and that calling the function returns further objects (and functions).

The lookup function is optional. It is assumed that the lookup function always finds values much faster than it would take to traverse the table. The first argument is the position of the key. Since `qlc_next` returns the objects as `{Key,Value}` pairs the position is 1. Note that the lookup function should return `{Key,Value}` pairs, just as the traversal function does.

The format function is also optional. It is called by `qlc:info` to give feedback at runtime of how the query will be evaluated. One should try to give as good feedback as possible without showing too much details. In the example at most 7 objects of the table are shown. The format function handles two cases: `all` means that all objects of the table will be traversed; `{lookup,1,KeyValues}` means that the lookup function will be used for looking up key values.

Whether the whole table will be traversed or just some keys looked up depends on how the query is stated. If the query has the form

```
qlc:q([T || P <- LE, F])
```

and `P` is a tuple, the `qlc` module analyzes `P` and `F` in compile time to find positions of the tuple `P` that are matched or compared to constants. If such a position at runtime turns out to be the key position, the lookup function can be used, otherwise all objects of the table have to be traversed. It is the `info` function `InfoFun` that returns the key position. There can be indexed positions as well, also returned by the `info` function. An index is an extra table that makes lookup on some position fast. Mnesia maintains indices upon request, thereby introducing so called secondary keys. The key is always preferred before secondary keys regardless of the number of constants to look up.

## Exports

```
append(QHL) -> QH
```

Types:

- `QHL = [QueryHandleOrList]`
- `QH = QueryHandle`

Returns a query handle. When evaluating the query handle `QH` all answers to the first query handle in `QHL` is returned followed by all answers to the rest of the query handles in `QHL`.

```
append(QH1, QH2) -> QH3
```

Types:

- `QH1 = QH2 = QueryHandleOrList`
- `QH3 = QueryHandle`

Returns a query handle. When evaluating the query handle `QH3` all answers to `QH1` are returned followed by all answers to `QH2`.

`append(QH1, QH2)` is equivalent to `append([QH1, QH2])`.

```
cursor(QueryHandleOrList [, Options]) -> QueryCursor
```

Types:

- `Options = [Option] | Option`
- `Option = {cache_all, Cache} | cache_all | {max_list_size, MaxListSize} | {spawn_options, SpawnOptions} | {tmpdir, TempDirectory} | {unique_all, bool()} | unique_all`

Creates a query cursor and makes the calling process the owner of the cursor. The cursor is to be used as argument to `next_answers/1,2` and (eventually) `delete_cursor/1`. Calls `erlang:spawn_opt` to spawn and link a process which will evaluate the query handle. The value of the option `spawn_options` is used as last argument when calling `spawn_opt`. The default value is `[link]`.

```

1> QH = qlc:q([X,Y] || X <- [a,b], Y <- [1,2]),
QC = qlc:cursor(QH),
qlc:next_answers(QC, 1).
[ {a,1} ]
2> qlc:next_answers(QC, 1).
[ {a,2} ]
3> qlc:next_answers(QC, all_remaining).
[ {b,1}, {b,2} ]
4> qlc:delete_cursor(QC).
ok

```

`delete_cursor(QueryCursor) -> ok`

Deletes a query cursor. Only the owner of the cursor can delete the cursor.

`eval(QueryHandleOrList [, Options]) -> Answers | Error`  
`e(QueryHandleOrList [, Options]) -> Answers`

Types:

- Options = [Option] | Option
- Option = {cache\_all, Cache} | cache\_all | {max\_list\_size, MaxListSize} | {tmpdir, TempDirectory} | {unique\_all, bool()} | unique\_all
- Error = {error, module(), Reason}
- Reason =-as returned by `file_sorter(3)`-

Evaluates a query handle in the calling process and collects all answers in a list.

```

1> QH = qlc:q([X,Y] || X <- [a,b], Y <- [1,2]),
qlc:eval(QH).
[ {a,1}, {a,2}, {b,1}, {b,2} ]

```

`fold(Function, Acc0, QueryHandleOrList [, Options]) -> Acc1 | Error`

Types:

- Function = fun(Answer, AccIn) -> AccOut
- Acc0 = Acc1 = AccIn = AccOut = term()
- Options = [Option] | Option
- Option = {cache\_all, Cache} | cache\_all | {max\_list\_size, MaxListSize} | {tmpdir, TempDirectory} | {unique\_all, bool()} | unique\_all
- Error = {error, module(), Reason}
- Reason =-as returned by `file_sorter(3)`-

Calls Function on successive answers to the query handle together with an extra argument AccIn. The query handle and the function are evaluated in the calling process. Function must return a new accumulator which is passed to the next call. Acc0 is returned if there are no answers to the query handle.

```

1> QH = [1,2,3,4,5,6],
qlc:fold(fun(X, Sum) -> X + Sum end, 0, QH).
21

```

`format_error(Error) -> Chars`

Types:

- Error = {error, module(), term()}
- Chars = [char() | Chars]

Returns a descriptive string in English of an error tuple returned by some of the functions of the `qlc` module or the parse transform. This function is mainly used by the compiler invoking the parse transform.

```
info(QueryHandleOrList [, Options]) -> Info
```

Types:

- Options = [Option] | Option
- Option = EvalOption | ReturnOption
- EvalOption = {cache\_all, Cache} | cache\_all | {max\_list\_size, MaxListSize} | {tmpdir, TempDirectory} | {unique\_all, bool()} | unique\_all
- ReturnOption = {flat, bool()} | {format, Format} | {n\_elements, NElements}
- Format = abstract\_code | string
- NElements = infinity | int() > 0
- Info = AbstractExpression | string()

Returns information about a query handle. The information describes the simplifications and optimizations that are the results of preparing the query for evaluation. This function is probably useful mostly during debugging.

The information has the form of an Erlang expression where QLCs most likely occur. Depending on the format functions of mentioned QLC tables it may not be absolutely accurate.

The default is to return a sequence of QLCs in a block, but if the option `{flat, false}` is given, one single QLC is returned. The default is to return a string, but if the option `{format, abstract_code}` is given, abstract code is returned instead. The default is to return all elements in lists, but if the `{n_elements, NElements}` option is given, only a limited number of elements are returned.

```
1> QH = qlc:q([X,Y] || X <- [x,y], Y <- [a,b]),
io:format("~s~n", [qlc:info(QH, unique_all)]).
begin
  V1 = qlc:q([SQV || SQV <- [x,y]], [{unique,true}]),
  V2 = qlc:q([SQV || SQV <- [a,b]], [{unique,true}]),
  qlc:q([X,Y] || X <- V1, Y <- V2), [{unique,true}]
end
```

In this example two simple QLCs have been inserted just to hold the `{unique, true}` option.

```
1> E1 = ets:new(e1, []),
E2 = ets:new(e2, []),
true = ets:insert(E1, [{1,a},{2,b}]),
true = ets:insert(E2, [{a,1},{b,2}]),
Q = qlc:q([X,Z,W] ||
  {X, Z} <- ets:table(E1),
  {W, Y} <- ets:table(E2),
  X := Y),
io:format("~s~n", [qlc:info(Q)]).
begin
  V1 = qlc:q([P0 || P0 = {W,Y} <- ets:table(18)]),
  V2 =
```

```

qlc:q([[G1|G2] ||
      G2 <- V1,
      G1 <- ets:table(17),
      element(2, G1) := element(1, G2)],
      [{join,lookup}]),
qlc:q([X,Z,W] || [{X,Z}|{W,Y}] <- V2, X := Y])
end

```

In this example the query list comprehension `V2` has been inserted to show the joined generators and the join method chosen. A convention is used for lookup join: the first generator (`G2`) is the one traversed, the second one (`G1`) is the table where constants are looked up.

```
keysort(KeyPos, QH1 [, SortOptions]) -> QH2
```

Types:

- `QH1` = `QueryHandleOrList`
- `QH2` = `QueryHandle`

Returns a query handle. When evaluating the query handle `QH2` the answers to the query handle `QH1` are sorted by `file_sorter:keysort/4` [page 150] according to the options.

The sorter will use temporary files only if `QH1` does not evaluate to a list and the size of the binary representation of the answers exceeds `Size` bytes, where `Size` is the value of the `size` option.

```
next_answers(QueryCursor [, NumberOfAnswers]) -> Answers | Error
```

Types:

- `NumberOfAnswers` = `all_remaining` | `int() > 0`
- `Error` = `{error, module(), Reason}`
- `Reason` = -as returned by `file_sorter(3)`-

Returns some or all of the remaining answers to a query cursor. Only the owner of `Cursor` can retrieve answers.

The optional argument `NumberOfAnswers` determines the maximum number of answers returned. The default value is 10. If less than the requested number of answers is returned, subsequent calls to `next_answers` will return `[]`.

```
q(QueryListComprehension [, Options]) -> QueryHandle
```

Types:

- `QueryListComprehension` = -literal query list comprehension-
- `Options` = `[Option]` | `Option`
- `Option` = `{max_lookup, MaxLookup}` | `{cache, Cache}` | `cache` | `{join, Join}` | `{lookup, Lookup}` | `{unique, bool()}` | `unique`
- `MaxLookup` = `int() >= 0` | `infinity`
- `Join` = `any` | `lookup` | `merge` | `nested_loop`
- `Lookup` = `bool()` | `any`

Returns a query handle for a query list comprehension. The query list comprehension must be the first argument to `qlc:q/1,2` or it will be evaluated as an ordinary list comprehension. It is also necessary to add the line

```
-include_lib("stdlib/include/qlc.hrl").
```

to the source file. This causes a parse transform to substitute a fun for the query list comprehension. The (compiled) fun will be called when the query handle is evaluated.

When calling `qlc:q/1,2` from the Erlang shell the parse transform is automatically called. When this happens the fun substituted for the query list comprehension is not compiled but will be evaluated by `erl_eval(3)`. This is also true when expressions are evaluated by means of `file:eval/1,2` or in the debugger.

To be very explicit, this will not work:

```
...
A = [X || {X} <- [{1},{2}]],
QH = qlc:q(A),
...
```

The variable `A` will be bound to the evaluated value of the list comprehension (`[1,2]`). The compiler complains with an error message (“argument is not a query list comprehension”); the shell process stops with a `badarg` reason.

The `{cache,ets}` option can be used to cache the answers to a query list comprehension. The answers are stored in one ETS table for each cached query list comprehension. When a cached query list comprehension is evaluated again, answers are fetched from the table without any further computations. As a consequence, when all answers to a cached query list comprehension have been found, the ETS tables used for caching answers to the query list comprehension’s qualifiers can be emptied. The option `cache` is equivalent to `{cache,ets}`.

The `{cache,list}` option can be used to cache the answers to a query list comprehension just like `{cache,ets}`. The difference is that the answers are kept in a list (on the process heap). If the answers would occupy more than a certain amount of RAM memory a temporary file is used for storing the answers. The option `max_list_size` sets the limit in bytes and the temporary file is put on the directory set by the `tmpdir` option.

The `cache` option has no effect if it is known that the query list comprehension will be evaluated at most once. This is always true for the top-most query list comprehension and also for the list expression of the first generator in a list of qualifiers. Note that in the presence of side effects in filters or callback functions the answers to query list comprehensions can be affected by the `cache` option.

The `{unique,true}` option can be used to remove duplicate answers to a query list comprehension. The unique answers are stored in one ETS table for each query list comprehension. The table is emptied every time it is known that there are no more answers to the query list comprehension. The option `unique` is equivalent to `{unique,true}`. If the `unique` option is combined with the `{cache,ets}` option, two ETS tables are used, but the full answers are stored in one table only. If the `unique` option is combined with the `{cache,list}` option the answers are sorted twice using `keysort/3`; once to remove duplicates, and once to restore the order.

The `cache` and `unique` options apply not only to the query list comprehension itself but also to the results of looking up constants, running match specifications, and joining handles.

```
1> Q = qlc:q([A,X,Z,W] ||
      A <- [a,b,c],
      {X,Z} <- [{a,1},{b,4},{c,6}],
      {W,Y} <- [{2,a},{3,b},{4,c}],
      X := Y],
      {cache,list}),
```



```

    {'or',
     {':=', '$2', a},
     {':=', '$2', b}},
    {':=', '$2', c}]]],
  ['$1']]))

```

In this example using the `gb_table` module from the Implementing a QLC table [page 278] section there are six keys to look up: `{1,a}`, `{1,b}`, `{1,c}`, `{2,a}`, `{2,b}`, and `{2,c}`. The reason is that the two elements of the key `{X,Y}` are matched separately.

The `{lookup,true}` option can be used to ensure that QLC will look up constants in some QLC table. If there are more than one QLC table among the generators' list expressions, constants have to be looked up in at least one of the tables. The evaluation of the query fails if there are no constants to look up. This option is useful in situations when it would be unacceptable to traverse all objects in some table. Setting the `lookup` option to `false` ensures that no constants will be looked up (`{max_lookup,0}` has the same effect). The default value is `any` which means that constants will be looked up whenever possible.

The `{join,Join}` option can be used to ensure that a certain join method will be used: `{join,lookup}` invokes the lookup join method; `{join,merge}` invokes the merge join method; and `{join,nested_loop}` invokes the method of matching every pair of objects from two handles. The last method is mostly very slow. The evaluation of the query fails if QLC cannot carry out the chosen join method. The default value is `any` which means that some fast join method will be used if possible.

```
sort(QH1 [, SortOptions]) -> QH2
```

Types:

- QH1 = QueryHandleOrList
- QH2 = QueryHandle

Returns a query handle. When evaluating the query handle QH2 the answers to the query handle QH1 are sorted by `file_sorter:sort/3` [page 150] according to the options.

The sorter will use temporary files only if QH1 does not evaluate to a list and the size of the binary representation of the answers exceeds `Size` bytes, where `Size` is the value of the `size` option.

```
string_to_handle(QueryString [, Options [, Bindings]]) -> QueryHandle | Error
```

Types:

- QueryString = string()
- Options = [Option] | Option
- Option = {max\_lookup, MaxLookup} | {cache, Cache} | cache | {join, Join} | {lookup, Lookup} | {unique, bool()} | unique
- MaxLookup = int() >= 0 | infinity
- Join = any | lookup | merge | nested\_loop
- Lookup = bool() | any
- Bindings = -as returned by `erl_eval:bindings/1`-
- Error = {error, module(), Reason}
- Reason = -ErrorInfo as returned by `erl_scan:string/1` or `erl_parse:parse_exprs/1`-

A string version of `qlc:q/1,2`. When the query handle is evaluated the fun created by the parse transform is interpreted by `erl_eval(3)`. The query string is to be one single query list comprehension terminated by a period.

```
1> L = [1,2,3],
Bs = erl_eval:add_binding('L', L, erl_eval:new_bindings()),
QH = qlc:string_to_handle("[X+1 || X <- L].", [], Bs),
qlc:eval(QH).
[2,3,4]
```

This function is probably useful mostly when called from outside of Erlang, for instance from a driver written in C.

```
table(TraverseFun, Options) -> QueryHandle
```

Types:

- TraverseFun = TraverseFun0 | TraverseFun1
- TraverseFun0 = fun() -> TraverseResult
- TraverseFun1 = fun(MatchExpression) -> TraverseResult
- TraverseResult = Objects | term()
- Objects = [] | [term() | ObjectList]
- ObjectList = TraverseFun0 | Objects
- Options = [Option] | Option
- Option = {format\_fun, FormatFun} | {info\_fun, InfoFun} | {lookup\_fun, LookupFun} | {parent\_fun, ParentFun} | {post\_fun, PostFun} | {pre\_fun, PreFun}
- FormatFun = undefined | fun(SelectedObjects) -> FormattedTable
- SelectedObjects = all | {match\_spec, MatchExpression} | {lookup, {Position, Keys}}
- FormattedTable = {Mod, Fun, Args} | AbstractExpression | character\_list()
- InfoFun = undefined | fun(InfoTag) -> InfoValue
- InfoTag = indices | is\_unique\_objects | keypos | num\_of\_objects
- InfoValue = undefined | term()
- LookupFun = undefined | fun(Position, Keys) -> LookupResult
- LookupResult = [term()] | term()
- ParentFun = undefined | fun() -> ParentFunValue
- PostFun = undefined | fun() -> void()
- PreFun = undefined | fun([PreArg]) -> void()
- PreArg = {parent\_value, ParentFunValue} | {stop\_fun, StopFun}
- ParentFunValue = undefined | term()
- StopFun = undefined | fun() -> void()
- Position = int() > 0
- Keys = [term()]
- Mod = Fun = atom()
- Args = [term()]

Returns a query handle for a QLC table. In Erlang/OTP there is support for ETS, Dets and Mnesia tables, but it is also possible to turn many other data structures into QLC tables. The way to accomplish this is to let function(s) in the module implementing the data structure create a query handle by calling `qlc:table/2`. The different ways to traverse the table as well as properties of the table are handled by callback functions provided as options to `qlc:table/2`.

The callback function `TraverseFun` is used for traversing the table. It is to return a list of objects terminated by either `[]` or a nullary fun to be used for traversing the not yet traversed objects of the table. Any other return value is immediately returned as value of the query evaluation. Unary `TraverseFuns` are to accept a match specification as argument. The match specification is created by the parse transform by analyzing the pattern of the generator calling `qlc:table/2` and filters using variables introduced in the pattern. If the parse transform cannot find a match specification equivalent to the pattern and filters, `TraverseFun` will be called with a match specification returning every object. Modules that can utilize match specifications for optimized traversal of tables should call `qlc:table/2` with a unary `TraverseFun` while other modules can provide a nullary `TraverseFun`. `ets:table/2` is an example of the former; `gb_table:table/1` in the [Implementing a QLC table \[page 278\]](#) section is an example of the latter.

`PreFun` is a unary callback function that is called once before the table is read for the first time. If the call fails, the query evaluation fails. Similarly, the nullary callback function `PostFun` is called once after the table was last read. The return value, which is caught, is ignored. If `PreFun` has been called for a table, `PostFun` is guaranteed to be called for that table, even if the evaluation of the query fails for some reason. The order in which pre (post) functions for different tables are evaluated is not specified. Other table access than reading, such as calling `InfoFun`, is assumed to be OK at any time. The argument `PreArgs` is a list of tagged values. Currently there are two tags, `parent_value` and `stop_fun`, used by `Mnesia` for managing transactions. The value of `parent_value` is the value returned by `ParentFun`, or `undefined` if there is no `ParentFun`. `ParentFun` is called once just before the call of `PreFun` in the context of the process calling `eval`, `fold`, or `cursor`. The value of `stop_fun` is a nullary fun that deletes the cursor if called from the parent, or `undefined` if there is no cursor.

The binary callback function `LookupFun` is used for looking up objects in the table. The first argument `Position` is the key position or an indexed position and the second argument `Keys` is a sorted list of unique values. The return value is to be a list of all objects (tuples) such that the element at `Position` is a member of `Keys`. Any other return value is immediately returned as value of the query evaluation. `LookupFun` is called instead of traversing the table if the parse transform at compile time can find out that the filters match and compare the element at `Position` in such a way that only `Keys` need to be looked up in order to find all potential answers. The key position is obtained by calling `InfoFun(keypos)` and the indexed positions by calling `InfoFun(indices)`. If the key position can be used for lookup it is always chosen, otherwise the indexed position requiring the least number of lookups is chosen. If there is a tie between two indexed positions the one occurring first in the list returned by `InfoFun` is chosen. Positions requiring more than `max_lookup` [page 285] lookups are ignored.

The unary callback function `InfoFun` is to return information about the table. `undefined` should be returned if the value of some tag is unknown:

- `indices`. Returns a list of indexed positions, a list of positive integers.
- `is_unique_objects`. Returns `true` if the objects returned by `TraverseFun` are unique.
- `keypos`. Returns the position of the table's key, a positive integer.
- `is_sorted_key`. Returns `true` if the objects returned by `TraverseFun` are sorted on the key.
- `num_of_objects`. Returns the number of objects in the table, a non-negative integer.

The unary callback function `FormatFun` is used by `qlc:info/1,2` for displaying the call that created the table's query handle. The default value `undefined` is displayed as a call to `'$MOD': '$FUN'/0`, otherwise it is up to `FormatFun` to present the selected objects in a suitable way. If a character list is chosen for presentation it must be an Erlang expression that can be scanned and parsed (a trailing dot will be added by `qlc:info` though). The argument to `FormatFun` describes the optimizations done as a result of analyzing the filter(s). The possible values are:

- `{lookup, Position, Keys}`. `LookupFun` is used for looking up objects in the table.
- `{match_spec, MatchExpression}`. No way of finding all possible answers by looking up keys was found, but the filters could be transformed into a match specification. All answers are found by calling `TraverseFun(MatchExpression)`.
- `all`. No optimization was found. A match specification matching all objects will be used if `TraverseFun` is unary.

See `ets(3)` [page 147], `dets(3)` [page 86] and `[mnesia(3)]` for the various options recognized by `table/1,2` in respective module.

## See Also

`dets(3)` [page 72], [Erlang Reference Manual], `erl_eval(3)` [page 106], `[erlang(3)]`, `ets(3)` [page 129], `[file(3)]`, `file_sorter(3)` [page 150], `[mnemosyne(3)]`, `[mnesia(3)]`, [Programming Examples], `shell(3)` [page 304]

# queue

Erlang Module

This module implements FIFO queues in an efficient manner.

All operations has an amortised  $O(1)$  running time, except `len/1`, `reverse/1`, `join/2` and `split/2` that probably are  $O(n)$ .

## Exports

`cons(Item, Q1) -> Q2`

Types:

- `Item = term()`
- `Q1 = Q2 = queue()`

Inserts `Item` at the head of queue `Q1`. Returns the new queue `Q2`.

`daeh(Q) -> Item`

The same as `last(Q)` and the opposite of `head(Q)`.

`from_list(L) -> queue()`

Types:

- `L = list()`

Returns a queue containing the items in `L`, in the same order - the head item of the list will be the head item of the queue.

`head(Q) -> Item`

Types:

- `Item = term()`
- `Q = queue()`

Returns `Item` from the head of queue `Q`.

Fails with reason `empty` if `Q` is empty.

`in(Item, Q1) -> Q2`

Types:

- `Item = term()`
- `Q1 = Q2 = queue()`

Inserts `Item` at the tail of queue `Q1`. Returns a new queue `Q2`. This is the same as `snoc(Q1, Item)`.

`in_r(Item, Q1) -> Q2`

Types:

- `Item = term()`
- `Q1 = Q2 = queue()`

Inserts `Item` at the head of queue `Q1`. Returns a new queue `Q2`. This is the same as `cons(Item, Q1)`.

`init(Q1) -> Q2`

Types:

- `Item = term()`
- `Q1 = Q2 = queue()`

Returns a queue `Q2` that is the result of removing the last item from `Q1`. This is the opposite of `tail(Q1)`.

Fails with reason `empty` if `Q1` is empty.

`is_empty(Q) -> true | false`

Types:

- `Q = queue()`

Tests if `Q` is empty and returns `true` if so and `false` otherwise.

`join(Q1, Q2) -> Q3`

Types:

- `Q1 = Q2 = Q3 = queue()`

Returns a queue `Q3` that is the result of joining `Q1` and `Q2` with `Q1` before (at the head) `Q2`.

`lait(Q1) -> Q2`

The same as `init(Q1)` and the opposite of `tail(Q1)`.

`last(Q) -> Item`

Types:

- `Item = term()`
- `Q = queue()`

Returns the last item of queue `Q`. This is the opposite of `head(Q)`.

Fails with reason `empty` if `Q` is empty.

`len(Q) -> N`

Types:

- `Q = queue()`
- `N = integer()`

Calculates and returns the length of queue `Q`.

`new()` -> `Q`

Types:

- `Q = queue()`

Returns an empty queue.

`out(Q1)` -> `Result`

Types:

- `Result = {{value, Item}, Q2} | {empty, Q1}`
- `Q1 = Q2 = queue()`

Removes the head item from the queue `Q1`. Returns the tuple `{{value, Item}, Q2}`, where `Item` is the item removed and `Q2` is the new queue. If `Q1` is empty, the tuple `{empty, Q1}` is returned.

`out_r(Q1)` -> `Result`

Types:

- `Result = {{value, Item}, Q2} | {empty, Q1}`
- `Q1 = Q2 = queue()`

Removes the last item from the queue `Q1`. Returns the tuple `{{value, Item}, Q2}`, where `Item` is the item removed and `Q2` is the new queue. If `Q1` is empty, the tuple `{empty, Q1}` is returned.

`reverse(Q1)` -> `Q2`

Types:

- `Q1 = Q2 = queue()`

Returns a queue `Q2` that contains the items of `Q1` in the reverse order.

`snoc(Q1, Item)` -> `Q2`

Types:

- `Item = term()`
- `Q1 = Q2 = queue()`

Inserts `Item` as the last item of queue `Q1`. Returns the new queue `Q2`. This is the opposite of `cons(Item, Q1)`.

`split(N, Q1)` -> `{Q2, Q3}`

Types:

- `N = integer()`
- `Q1 = Q2 = Q3 = queue()`

Splits `Q1` into a queue `Q2` of length `N` with items from the head end, and a queue `Q3` with the rest of the items.

`tail(Q1)` -> `Q2`

Types:

- Item = term()
- Q1 = Q2 = queue()

Returns a queue Q2 that is the result of removing the head item from Q1.

Fails with reason `empty` if Q1 is empty.

`to_list(Q) -> list()`

Types:

- Q = queue()

Returns a list of the items in the queue, with the head item of the queue as the head of the list.

# random

Erlang Module

Random number generator. The method is attributed to B.A. Wichmann and I.D.Hill, in 'An efficient and portable pseudo-random number generator', Journal of Applied Statistics. AS183. 1982. Also Byte March 1987.

The current algorithm is a modification of the version attributed to Richard A O'Keefe in the standard Prolog library.

Every time a random number is requested, a state is used to calculate it, and a new state produced. The state can either be implicit (kept in the process dictionary) or be an explicit argument and return value. In this implementation, the state (the type `ran()`) consists of a tuple of three integers.

## Exports

`seed()` -> `ran()`

Seeds random number generation with default (fixed) values in the process dictionary, and returns the old state.

`seed(A1, A2, A3)` -> `ran()`

Types:

- `A1 = A2 = A3 = int()`

Seeds random number generation with integer values in the process dictionary, and returns the old state.

One way of obtaining a seed is to use the BIF `now/0`:

```
...
{A1,A2,A3} = now(),
random:seed(A1, A2, A3),
...
```

`seed0()` -> `ran()`

Returns the default state.

`uniform()`-> `float()`

Returns a random float uniformly distributed between 0.0 and 1.0, updating the state in the process dictionary.

`uniform(N)` -> `int()`

Types:

- `N = int()`

Given an integer `N >= 1`, `uniform/1` returns a random integer uniformly distributed between 1 and `N`, updating the state in the process dictionary.

`uniform_s(State0) -> {float(), State1}`

Types:

- `State0 = State1 = ran()`

Given a state, `uniform_s/1` returns a random float uniformly distributed between 0.0 and 1.0, and a new state.

`uniform_s(N, State0) -> {int(), State1}`

Types:

- `N = int()`
- `State0 = State1 = ran()`

Given an integer `N >= 1` and a state, `uniform_s/2` returns a random integer uniformly distributed between 1 and `N`, and a new state.

## Note

Some of the functions use the process dictionary variable `random_seed` to remember the current seed.

If a process calls `uniform/0` or `uniform/1` without setting a seed first, `seed/0` is called automatically.

# regexp

Erlang Module

This module contains functions for regular expression matching and substitution.

## Exports

`match(String, RegExp) -> MatchRes`

Types:

- `String = RegExp = string()`
- `MatchRes = {match,Start,Length} | nomatch | {error,errordesc()}`
- `Start = Length = integer()`

Finds the first, longest match of the regular expression `RegExp` in `String`. This function searches for the longest possible match and returns the first one found if there are several expressions of the same length. It returns as follows:

`{match,Start,Length}` if the match succeeded. `Start` is the starting position of the match, and `Length` is the length of the matching string.

`nomatch` if there were no matching characters.

`{error,Error}` if there was an error in `RegExp`.

`first_match(String, RegExp) -> MatchRes`

Types:

- `String = RegExp = string()`
- `MatchRes = {match,Start,Length} | nomatch | {error,errordesc()}`
- `Start = Length = integer()`

Finds the first match of the regular expression `RegExp` in `String`. This call is usually faster than `match` and it is also a useful way to ascertain that a match exists. It returns as follows:

`{match,Start,Length}` if the match succeeded. `Start` is the starting position of the match and `Length` is the length of the matching string.

`nomatch` if there were no matching characters.

`{error,Error}` if there was an error in `RegExp`.

`matches(String, RegExp) -> MatchRes`

Types:

- `String = RegExp = string()`

- MatchRes = {match, Matches} | {error, errordesc()}
- Matches = list()

Finds all non-overlapping matches of the expression `RegExp` in `String`. It returns as follows:

{match, Matches} if the regular expression was correct. The list will be empty if there was no match. Each element in the list looks like {Start, Length}, where `Start` is the starting position of the match, and `Length` is the length of the matching string.

{error, Error} if there was an error in `RegExp`.

`sub(String, RegExp, New) -> SubRes`

Types:

- String = RegExp = New = string()
- SubRes = {ok, NewString, RepCount} | {error, errordesc()}
- RepCount = integer()

Substitutes the first occurrence of a substring matching `RegExp` in `String` with the string `New`. A `&` in the string `New` is replaced by the matched substring of `String`. `\&` puts a literal `&` into the replacement string. It returns as follows:

{ok, NewString, RepCount} if `RegExp` is correct. `RepCount` is the number of replacements which have been made (this will be either 0 or 1).

{error, Error} if there is an error in `RegExp`.

`gsub(String, RegExp, New) -> SubRes`

Types:

- String = RegExp = New = string()
- SubRes = {ok, NewString, RepCount} | {error, errordesc()}
- RepCount = integer()

The same as `sub`, except that all non-overlapping occurrences of a substring matching `RegExp` in `String` are replaced by the string `New`. It returns:

{ok, NewString, RepCount} if `RegExp` is correct. `RepCount` is the number of replacements which have been made.

{error, Error} if there is an error in `RegExp`.

`split(String, RegExp) -> SplitRes`

Types:

- String = RegExp = string()
- SubRes = {ok, FieldList} | {error, errordesc()}
- Fieldlist = [string()]

`String` is split into fields (sub-strings) by the regular expression `RegExp`.

If the separator expression is " " (a single space), then the fields are separated by blanks and/or tabs and leading and trailing blanks and tabs are discarded. For all other values of the separator, leading and trailing blanks and tabs are not discarded. It returns:

`{ok, FieldList}` to indicate that the string has been split up into the fields of `FieldList`.  
`{error, Error}` if there is an error in `RegExp`.

`sh_to_awk(ShRegExp) -> AwkRegExp`

Types:

- `ShRegExp AwkRegExp = string()`
- `SubRes = {ok, NewString, RepCount} | {error, errordesc() }`
- `RepCount = integer()`

Converts the `sh` type regular expression `ShRegExp` into a full AWK regular expression. Returns the converted regular expression string. `sh` expressions are used in the shell for matching file names and have the following special characters:

- \* matches any string including the null string.
- ? matches any single character.
- [ . . . ] matches any of the enclosed characters. Character ranges are specified by a pair of characters separated by a -. If the first character after [ is a !, then any character not enclosed is matched.

It may sometimes be more practical to use `sh` type expansions as they are simpler and easier to use, even though they are not as powerful.

`parse(RegExp) -> ParseRes`

Types:

- `RegExp = string()`
- `ParseRes = {ok, RE} | {error, errordesc() }`

Parses the regular expression `RegExp` and builds the internal representation used in the other regular expression functions. Such representations can be used in all of the other functions instead of a regular expression string. This is more efficient when the same regular expression is used in many strings. It returns:

`{ok, RE}` if `RegExp` is correct and `RE` is the internal representation.  
`{error, Error}` if there is an error in `RegExpString`.

`format_error(ErrorDescriptor) -> Chars`

Types:

- `ErrorDescriptor = errordesc()`
- `Chars = [char() | Chars]`

Returns a string which describes the error `ErrorDescriptor` returned when there is an error in a regular expression.

## Regular Expressions

The regular expressions allowed here is a subset of the set found in `egrep` and in the AWK programming language, as defined in the book, *The AWK Programming Language*, by A. V. Aho, B. W. Kernighan, P. J. Weinberger. They are composed of the following characters:

**c** matches the non-metacharacter *c*.

`\c` matches the escape sequence or literal character *c*.

**.** matches any character.

**^** matches the beginning of a string.

**\$** matches the end of a string.

**[abc... ]** character class, which matches any of the characters *abc...* . Character ranges are specified by a pair of characters separated by a `-`.

**[^abc... ]** negated character class, which matches any character except *abc...*

**r1 | r2** alternation. It matches either *r1* or *r2*.

**r1r2** concatenation. It matches *r1* and then *r2*.

**r+** matches one or more *rs*.

**r\*** matches zero or more *rs*.

**r?** matches zero or one *rs*.

**(r)** grouping. It matches *r*.

The escape sequences allowed are the same as for Erlang strings:

`\b` backspace

`\f` form feed

`\n` newline (line feed)

`\r` carriage return

`\t` tab

`\e` escape

`\v` vertical tab

`\s` space

`\d` delete

`\ddd` the octal value *ddd*

`\c` any other character literally, for example `\\` for backslash, `\"` for `"`)

To make these functions easier to use, in combination with the function `io:get_line` which terminates the input line with a new line, the `$` characters also matches a string ending with `"... \n"`. The following examples define Erlang data types:

```
Atoms      [a-z] [0-9a-zA-Z_]*
```

```
Variables [A-Z_] [0-9a-zA-Z_]*
```

```
Floats    (\+|-)? [0-9]+\.[0-9]+((E|e)(\+|-)? [0-9]+)?
```

Regular expressions are written as Erlang strings when used with the functions in this module. This means that any `\` or `"` characters in a regular expression string must be written with `\` as they are also escape characters for the string. For example, the regular expression string for Erlang floats is:

```
"(\\+|-)?[0-9]+\\. [0-9]+((E|e)(\\+|-)?[0-9]+)?".
```

It is not really necessary to have the escape sequences as part of the regular expression syntax as they can always be generated directly in the string. They are included for completeness and can they can also be useful when generating regular expressions, or when they are entered other than with Erlang strings.

# sets

Erlang Module

Sets are collections of elements with no duplicate elements. The representation of a set is not defined.

This module provides exactly the same interface as the module `ordsets` but with a defined representation. One difference is that while this module considers two elements as different if they do not match (`:=:`), `ordsets` considers two elements as different if and only if they do not compare equal (`==`).

## DATA TYPES

`set()`  
as returned by `new/0`

## Exports

`new()` -> `Set`

Types:

- `Set = set()`

Returns a new empty set.

`is_set(Set)` -> `bool()`

Types:

- `Set = term()`

Returns true if `Set` is a set of elements, otherwise false.

`size(Set)` -> `int()`

Types:

- `Set = term()`

Returns the number of elements in `Set`.

`to_list(Set)` -> `List`

Types:

- `Set = set()`
- `List = [term()]`

Returns the elements of `Set` as a list.

`from_list(List) -> Set`

Types:

- `List = [term()]`
- `Set = set()`

Returns an set of the elements in `List`.

`is_element(Element, Set) -> bool()`

Types:

- `Element = term()`
- `Set = set()`

Returns true if `Element` is an element of `Set`, otherwise false.

`add_element(Element, Set1) -> Set2`

Types:

- `Element = term()`
- `Set1 = Set2 = set()`

Returns a new set formed from `Set1` with `Element` inserted.

`del_element(Element, Set1) -> Set2`

Types:

- `Element = term()`
- `Set1 = Set2 = set()`

Returns `Set1`, but with `Element` removed.

`union(Set1, Set2) -> Set3`

Types:

- `Set1 = Set2 = Set3 = set()`

Returns the merged (union) set of `Set1` and `Set2`.

`union(SetList) -> Set`

Types:

- `SetList = [set()]`
- `Set = set()`

Returns the merged (union) set of the list of sets.

`intersection(Set1, Set2) -> Set3`

Types:

- `Set1 = Set2 = Set3 = set()`

Returns the intersection of `Set1` and `Set2`.

`intersection(SetList) -> Set`

Types:

- `SetList = [set()]`
- `Set = set()`

Returns the intersection of the non-empty list of sets.

`subtract(Set1, Set2) -> Set3`

Types:

- `Set1 = Set2 = Set3 = set()`

Returns only the elements of `Set1` which are not also elements of `Set2`.

`is_subset(Set1, Set2) -> bool()`

Types:

- `Set1 = Set2 = set()`

Returns true when every element of `Set1` is also a member of `Set2`, otherwise false.

`fold(Function, Acc0, Set) -> Acc1`

Types:

- `Function = fun (E, AccIn) -> AccOut`
- `Acc0 = Acc1 = AccIn = AccOut = term()`
- `Set = set()`

Fold `Function` over every element in `Set` returning the final value of the accumulator.

`filter(Pred, Set1) -> Set2`

Types:

- `Pred = fun (E) -> bool()`
- `Set1 = Set2 = set()`

Filter elements in `Set1` with boolean function `Fun`.

## See Also

`ordsets(3)` [page 256], `gb_sets(3)` [page 164]

# shell

Erlang Module

The module `shell` implements an Erlang shell.

The shell is a user interface program for entering expression sequences. The expressions are evaluated and a value is returned. A history mechanism saves previous commands and their values, which can then be incorporated in later commands. How many commands and results to save can be determined by the user, either interactively, by calling `shell:history/1` and `shell:results/1`, or by setting the application configuration parameters `shell_history_length` and `shell_saved_results` for the application `stdlib`.

Variable bindings, and local process dictionary changes which are generated in user expressions are preserved, and the variables can be used in later commands to access their values. The bindings can also be forgotten so the variables can be re-used.

The special shell commands all have the syntax of (local) function calls. They are evaluated as normal function calls and many commands can be used in one expression sequence.

If a command (local function call) is not recognized by the shell, an attempt is first made to find the function in the module `user_default`, where customized local commands can be placed. If found, then the function is evaluated. Otherwise, an attempt is made to evaluate the function in the module `shell_default`. The module `user_default` must be explicitly loaded.

The shell also permits the user to start multiple concurrent jobs. A job can be regarded as a set of processes which can communicate with the shell.

There is some support for reading and printing records in the shell. During compilation record expressions are translated to tuple expressions. In runtime it is not known whether a tuple actually represents a record. Nor are the record definitions used by compiler available at runtime. So in order to read the record syntax and print tuples as records when possible, record definitions have to be maintained by the shell itself. The shell commands for reading, defining, forgetting, listing, and printing records are described below. Note that each job has its own set of record definitions. To facilitate matters record definitions in the modules `shell_default` and `user_default` (if loaded) are read each time a new job is started. For instance, adding the line

```
-include_lib("kernel/include/file.hrl").
```

to `user_default` makes the definition of `file_info` readily available in the shell.

The shell runs in two modes:

- Normal (possibly restricted) mode, in which commands can be edited and expressions evaluated.
- Job Control Mode JCL, in which jobs can be started, killed, detached and connected.

Only the currently connected job can 'talk' to the shell.

## Shell Commands

- `b()` Prints the current variable bindings.
- `f()` Removes all variable bindings.
- `f(X)` Removes the binding of variable `X`.
- `h()` Prints the history list.
- `history(N)` Sets the number of previous commands to keep in the history list to `N`. The previous number is returned. The default number is 20.
- `results(N)` Sets the number of results from previous commands to keep in the history list to `N`. The previous number is returned. The default number is 20.
- `e(N)` Repeats the command `N`, if `N` is positive. If it is negative, the `N`th previous command is repeated (i.e., `e(-1)` repeats the previous command).
- `v(N)` Uses the return value of the command `N` in the current command, if `N` is positive. If it is negative, the return value of the `N`th previous command is used (i.e., `v(-1)` uses the value of the previous command).
- `help()` Evaluates `shell_default:help()`.
- `c(File)` Evaluates `shell_default:c(File)`. This compiles and loads code in `File` and purges old versions of code, if necessary. Assumes that the file and module names are the same.
- `rd(RecordName, RecordDefinition)` Defines a record in the shell. `RecordName` is an atom and `RecordDefinition` lists the field names and the default values. Usually record definitions are made known to the shell by use of the `rr` commands described below, but sometimes it is handy to define records on the fly.
- `rf()` Removes all record definitions, then reads record definitions from the modules `shell_default` and `user_default` (if loaded). Returns the names of the records defined.
- `rf(RecordNames)` Removes selected record definitions. `RecordNames` is a record name or a list of record names. Use `'_'` to remove all record definitions.
- `rl()` Prints all record definitions.
- `rl(RecordNames)` Prints selected record definitions. `RecordNames` is a record name or a list of record names.
- `rp(Term)` Prints a term using the record definitions known to the shell. All of `Term` is printed; the depth is not limited as is the case when a return value is printed.
- `rr(Module)` Reads record definitions from a module's BEAM file. If there are no record definitions in the BEAM file, the source file is located and read instead. Returns the names of the record definitions read. `Module` is an atom.
- `rr(Wildcard)` Reads record definitions from files. Existing definitions of any of the record names read are replaced. `Wildcard` is a wildcard string as defined in `filelib(3)` but not an atom.
- `rr(WildcardOrModule, RecordNames)` Reads record definitions from files but discards record names not mentioned in `RecordNames` (a record name or a list of record names).
- `rr(WildcardOrModule, RecordNames, Options)` Reads record definitions from files. The compiler options `{i,Dir}`, `{d,Macro}`, and `{d,Macro,Value}` are recognized and used for setting up the include path and macro definitions. Use `'_'` as value of `RecordNames` to read all record definitions.

## Example

The following example is a long dialogue with the shell. Commands starting with > are inputs to the shell. All other lines are output from the shell. All commands in this example are explained at the end of the dialogue. .

```

strider 1> erl
Erlang (BEAM) emulator version 5.3 [hipe] [threads:0]

Eshell V5.3 (abort with ^G)
1> Str = "abcd".
"abcd"
2> L = length(Str).
4
3> Descriptor = {L, list_to_atom(Str)}.
{4,abcd}
4> L.
4
5> b().
Descriptor = {4,abcd}
L = 4
Str = "abcd"
ok
6> f(L).
ok
7> b().
Descriptor = {4,abcd}
Str = "abcd"
ok
8> f(L).
** 1: variable 'L' is unbound **
9> {L, _} = Descriptor.
{4,abcd}
10> L.
4
11> {P, Q, R} = Descriptor.
** exited: {{badmatch,{4,abcd}},[{erl_eval,expr,3}]} **
12> P.
** 1: variable 'P' is unbound **
13> Descriptor.
{4,abcd}
14> {P, Q} = Descriptor.
{4,abcd}
15> P.
4
16> f().
ok
17> put(aa, hello).
undefined
18> get(aa).
hello
19> Y = test1:demo(1).
11

```

```

20> get().
[aa,worked]
21> put(aa, hello).
worked
22> Z = test1:demo(2).

=ERROR REPORT==== 19-Feb-2003::10:04:14 ===
Error in process <0.40.0> with exit value: {{badmatch,1},{test1,demo,1},
{erl_eval,expr,4},{shell,eval_loop,2}}
** exited: {{badmatch,1},
              [{test1,demo,1},{erl_eval,expr,4},{shell,eval_loop,2}]} **
23> Z.
** 1: variable 'Z' is unbound **
24> get(aa).
hello
25> erase(), put(aa, hello).
undefined
26> spawn(test1, demo, [1]).
<0.57.0>
27> get(aa).
hello
28> io:format("hello hello\n").
hello hello
ok
29> e(28).
hello hello
ok
30> v(28).
ok
31> c(ex).
{ok,ex}
32> rr(ex).
[rec]
33> rl(rec).
-record(rec, {a,
              b = val()}).

ok
34> #rec{}.
** exited: {undef, [{shell_default,val,[]},
                    {erl_eval,do_apply,5},
                    {erl_eval,expr_list,6},
                    {erl_eval,expr,5},
                    {shell,eval_loop,2}]} **
35> #rec{b = 3}.
{rec,undefined,3}
36> rp(v(-1)).
#rec{a = undefined,
     b = 3}

ok
37> rd(rec, {f = orddict:new()}).
rec
38> rp(#rec{}).
#rec{f = []}

```

```

ok
39> rd(rec, {c}), A.
** 1: variable 'A' is unbound **
40> rp(#rec{c}).
#rec{c = undefined}
ok
41> test1:loop(0).
Hello Number: 0
Hello Number: 1
Hello Number: 2
Hello Number: 3

User switch command
--> i
--> c
.
.
.
Hello Number: 3374
Hello Number: 3375
Hello Number: 3376
Hello Number: 3377
Hello Number: 3378
** exited: killed **
42> halt().
strider 2>

```

## Comments

Command 1 sets the variable `Str` to the string "abcd".

Command 2 sets `L` to the length of the string evaluating the BIF `atom_to_list`.

Command 3 builds the tuple `Descriptor`.

Command 4 prints the value of the variable `L`.

Command 5 evaluates the internal shell command `b()`, which is an abbreviation of "bindings". This prints the current shell variables and their bindings. The `ok` at the end is the return value of the `b()` function.

Command 6 `f(L)` evaluates the internal shell command `f(L)` (abbreviation of "forget"). The value of the variable `L` is removed.

Command 7 prints the new bindings.

Command 8 shows that `L` is no longer bound to a value.

Command 9 performs a pattern matching operation on `Descriptor`, binding a new value to `L`.

Command 10 prints the current value of `L`.

Command 11 tries to match `{P, Q, R}` against `Descriptor` which is `{4, abc}`. The match fails and none of the new variables become bound. The printout starting with "`** exited:`" is not the value of the expression (the expression had no value because its evaluation failed), but rather a warning printed by the system to inform the user that an error has occurred. The values of the other variables (`L`, `Str`, etc.) are unchanged.

Commands 12 and 13 show that `P` is unbound because the previous command failed, and that `Descriptor` has not changed.

Commands 14 and 15 show a correct match where `P` and `Q` are bound.

Command 16 clears all bindings.

The next few commands assume that `test1:demo(X)` is defined in the following way:

```
demo(X) ->
  put(aa, worked),
  X = 1,
  X + 10.
```

Commands 17 and 18 set and inspect the value of the item `aa` in the process dictionary.

Command 19 evaluates `test1:demo(1)`. The evaluation succeeds and the changes made in the process dictionary become visible to the shell. The new value of the dictionary item `aa` can be seen in command 20.

Commands 21 and 22 change the value of the dictionary item `aa` to `hello` and call `test1:demo(2)`. Evaluation fails and the changes made to the dictionary in `test1:demo(2)`, before the error occurred, are discarded.

Commands 23 and 24 show that `Z` was not bound and that the dictionary item `aa` has retained its original value.

Commands 25, 26 and 27 show the effect of evaluating `test1:demo(1)` in the background. In this case, the expression is evaluated in a newly spawned process. Any changes made in the process dictionary are local to the newly spawned process and therefore not visible to the shell.

Commands 28, 29 and 30 use the history facilities of the shell.

Command 29 is `e(28)`. This re-evaluates command 28. Command 30 is `v(28)`. This uses the value (result) of command 28. In the cases of a pure function (a function with no side effects), the result is the same. For a function with side effects, the result can be different.

The next few commands show some record manipulation. It is assumed that `ex.er1` defines a record like this:

```
-record(rec, {a, b = val()}).
```

```
val() ->
  3.
```

Commands 31 and 32 compile the file `ex.er1` and reads the record definitions in `ex.beam`. If the compiler did not output any record definitions on the BEAM file, `rr(ex)` tries to read record definitions from the source file instead.

Command 33 prints the definition of the record named `rec`.

Command 34 tries to create a `rec` record, but fails since the function `val/0` is undefined. Command 35 shows the workaround: explicitly assign values to record fields that cannot otherwise be initialized.

Command 36 prints the newly created record using record definitions maintained by the shell.

Command 37 defines a record directly in the shell. The definition replaces the one read from the file `ex.beam`.

Command 38 creates a record using the new definition, and prints the result.

Command 39 and 40 show that record definitions are updated as side effects. The evaluation of the command fails but the definition of `rec` has been carried out.

For the next command, it is assumed that `test1:loop(N)` is defined in the following way:

```
loop(N) ->
    io:format("Hello Number: ~w~n", [N]),
    loop(N+1).
```

Command 41 evaluates `test1:loop(0)`, which puts the system into an infinite loop. At this point the user types `Control G`, which suspends output from the current process, which is stuck in a loop, and activates JCL mode. In JCL mode the user can start and stop jobs.

In this particular case, the `i` command (“interrupt”) is used to terminate the looping program, and the `c` command is used to connect to the shell again. Since the process was running in the background before we killed it, there will be more printouts before the “\*\* exited: killed \*\*” message is shown.

The `halt()` command exits the Erlang runtime system.

## JCL Mode

When the shell starts, it starts a single evaluator process. This process, together with any local processes which it spawns, is referred to as a job. Only the current job, which is said to be connected, can perform operations with standard IO. All other jobs, which are said to be detached, are blocked if they attempt to use standard IO.

All jobs which do not use standard IO run in the normal way.

The shell escape key `^G` (Control G) detaches the current job and activates JCL mode. The JCL mode prompt is “-->”. If “?” is entered at the prompt, the following help message is displayed:

```
--> ?
c [nn] - connect to job
i [nn] - interrupt job
k [nn] - kill job
j      - list all jobs
s      - start local shell
r [node] - start remote shell
q      - quit Erlang
? | h  - this message
```

The JCL commands have the following meaning:

- c [nn] Connects to job number <nn> or the current job. The standard shell is resumed. Operations which use standard IO by the current job will be interleaved with user inputs to the shell.
- i [nn] Stops the current evaluator process for job number nn or the current job, but does not kill the shell process. Accordingly, any variable bindings and the process dictionary will be preserved and the job can be connected again. This command can be used to interrupt an endless loop.

- k `[nn]` Kills job number `nn` or the current job. All spawned processes in the job are killed, provided they have not evaluated the `group_leader/1` BIF and are located on the local machine. Processes spawned on remote nodes will not be killed.
- j Lists all jobs. A list of all known jobs is printed. The current job name is prefixed with `'*'`.
- s Starts a new job. This will be assigned the new index `[nn]` which can be used in references.
- r `[node]` Starts a remote job on `node`. This is used in distributed Erlang to allow a shell running on one node to control a number of applications running on a network of nodes.
- q Quits Erlang. Note that this option is disabled if Erlang is started with the `ignore break, +Bi`, system flag (which may be useful e.g. when running a restricted shell, see below).
- ? Displays this message.

It is possible to alter the behavior of shell escape by means of the `stdlib` application variable `shell_esc`. The value of the variable can be either `jcl` (`erl -stdlib shell_esc jcl`) or `abort` (`erl -stdlib shell_esc abort`). The first option sets `^G` to activate JCL mode (which is also default behavior). The latter sets `^G` to terminate the current shell and start a new one. JCL mode cannot be invoked when `shell_esc` is set to `abort`.

If you want an Erlang node to have a remote job active from the start (rather than the default local job), you start Erlang with the `-remsh` flag. Example: `erl -sname this_node -remsh other_node@other_host`

## Restricted Shell

The shell may be started in a restricted mode. In this mode, the shell evaluates a function call only if allowed. This feature makes it possible to, for example, prevent a user from accidentally calling a function from the prompt that could harm a running system (useful in combination with the the system flag `+Bi`).

When the restricted shell evaluates an expression and encounters a function call or an operator application, it calls a callback function (with information about the function call in question). This callback function returns `true` to let the shell go ahead with the evaluation, or `false` to abort it. There are two possible callback functions for the user to implement:

```
local_allowed(Func, ArgList, State) -> {true,NewState} |
{false,NewState}
```

to determine if the call to the local function `Func` with arguments `ArgList` should be allowed.

```
non_local_allowed(FuncSpec, ArgList, State) -> {true,NewState} |
{false,NewState} | {{redirect,NewFuncSpec,NewArgList},NewState}
```

to determine if the call to non-local function `FuncSpec` (`{Module,Func}` or a fun) with arguments `ArgList` should be allowed. The return value `{redirect,NewFuncSpec,NewArgList}` can be used to let the shell evaluate some other function than the one specified by `FuncSpec` and `ArgList`.

These callback functions are in fact called from local and non-local evaluation function handlers, described in the `erl_eval` [page 106] manual page. (Arguments in `ArgList` are evaluated before the callback functions are called).

The `State` argument is a tuple `{ShellState, ExprState}`. The return value `NewState` has the same form. This may be used to carry a state between calls to the callback functions. Data saved in `ShellState` lives through an entire shell session. Data saved in `ExprState` lives only through the evaluation of the current expression.

There are two ways to start a restricted shell session:

- Use the stdlib application variable `restricted_shell` and specify, as its value, the name of the callback module. Example (with callback functions implemented in `callback_mod.erl`): `$ erl -stdlib restricted_shell callback_mod`
- From a normal shell session, call function `shell:start_restricted/1`. This exits the current evaluator and starts a new one in restricted mode.

*Notes:*

- When restricted shell mode is activated or deactivated, new jobs started on the node will run in restricted or normal mode respectively.
- If restricted mode has been enabled on a particular node, remote shells connecting to this node will also run in restricted mode.
- The callback functions cannot be used to allow or disallow execution of functions called from compiled code (only functions called from expressions entered at the shell prompt).

Errors when loading the callback module is handled in different ways depending on how the restricted shell is activated:

- If the restricted shell is activated by setting the kernel variable during emulator startup and the callback module cannot be loaded, a default restricted shell allowing only the commands `q()` and `init:stop()` is used as fallback.
- If the restricted shell is activated using `shell:start_restricted/1` and the callback module cannot be loaded, an error report is sent to the error logger and the call returns `{error, Reason}`.

## Exports

`history(N) -> integer()`

Types:

- `N = integer()`

Sets the number of previous commands to keep in the history list to `N`. The previous number is returned. The default number is 20.

`results(N) -> integer()`

Types:

- `N = integer()`

Sets the number of results from previous commands to keep in the history list to `N`. The previous number is returned. The default number is 20.

`start_restricted(Module) -> ok | {error, Reason}`

Types:

- `Module = atom()`
- `Reason = atom()`

Exits a normal shell and starts a restricted shell. `Module` specifies the callback module for the functions `local_allowed/3` and `non_local_allowed/3`. The function is meant to be called from the shell.

If the callback module cannot be loaded, an error tuple is returned. The `Reason` in the error tuple is the one returned by the code loader when trying to load the code of the callback module.

`stop_restricted() -> ok`

Exits a restricted shell and starts a normal shell. The function is meant to be called from the shell.

# shell\_default

Erlang Module

The functions in `shell_default` are called when no module name is given in a shell command.

Consider the following shell dialogue:

```
1 > lists:reverse("abc").
"cba"
2 > c(foo).
{ok, foo}
```

In command one, the module `lists` is called. In command two, no module name is specified. The shell searches the modules `user_default` followed by `shell_default` for the function `foo/1`.

`shell_default` is intended for “system wide” customizations to the shell. `user_default` is intended for “local” or individual user customizations.

## Hint

To add your own commands to the shell, create a module called `user_default` and add the commands you want. Then add the following line as the *first* line in your `.erlang` file in your home directory.

```
code:load_abs("$PATH/user_default").
```

`$PATH` is the directory where your `user_default` module can be found.

# slave

Erlang Module

This module provides functions for starting Erlang slave nodes. All slave nodes which are started by a master will terminate automatically when the master terminates. All TTY output produced at the slave will be sent back to the master node. File I/O is done via the master.

Slave nodes on other hosts than the current one are started with the program `rsh`. The user must be allowed to `rsh` to the remote hosts without being prompted for a password. This can be arranged in a number of ways (refer to the `rsh` documentation for details). A slave node started on the same host as the master inherits certain environment values from the master, such as the current directory and the environment variables. For what can be assumed about the environment when a slave is started on another host, read the documentation for the `rsh` program.

An alternative to the `rsh` program can be specified on the command line to `erl` as follows: `-rsh Program`.

The slave node should use the same file system at the master. At least, Erlang/OTP should be installed in the same place on both computers and the same version of Erlang should be used.

Currently, a node running on Windows NT can only start slave nodes on the host on which it is running.

The master node must be alive.

## Exports

```
start(Host) ->
```

```
start(Host, Name) ->
```

```
start(Host, Name, Args) -> {ok, Node} | {error, Reason}
```

Types:

- Host = Name = atom()
- Args = string()
- Node = node()
- Reason = timeout | no\_rsh | {already\_running, Node}

Starts a slave node on the host `Host`. Host names need not necessarily be specified as fully qualified names; short names can also be used. This is the same condition that applies to names of distributed Erlang nodes.

The name of the started node will be `Name@Host`. If no name is provided, the name will be the same as the node which executes the call (with the exception of the host name part of the node name).

The slave node resets its user process so that all terminal I/O which is produced at the slave is automatically relayed to the master. Also, the file process will be relayed to the master.

The `Args` argument is used to set `erl` command line arguments. If provided, it is passed to the new node and can be used for a variety of purposes. See `[erl(1)]`

As an example, suppose that we want to start a slave node at host `H` with the node name `Name@H`, and we also want the slave node to have the following properties:

- directory `Dir` should be added to the code path;
- the Mnesia directory should be set to `M`;
- the unix `DISPLAY` environment variable should be set to the display of the master node.

The following code is executed to achieve this:

```
E = " -env DISPLAY " ++ net_adm:localhost() ++ ":0 ",
Arg = "-mnesia_dir " ++ M ++ " -pa " ++ Dir ++ E,
slave:start(H, Name, Arg).
```

If successful, the function returns `{ok, Node}`, where `Node` is the name of the new node. Otherwise it returns `{error, Reason}`, where `Reason` can be one of:

`timeout` The master node failed to get in contact with the slave node. This can happen in a number of circumstances:

- Erlang/OTP is not installed on the remote host
- the file system on the other host has a different structure to the the master
- the Erlang nodes have different cookies.

`no_rsh` There is no `rsh` program on the computer.

`{already_running, Node}` A node with the name `Name@Host` already exists.

```
start_link(Host) ->
start_link(Host, Name) ->
start_link(Host, Name, Args) -> {ok, Node} | {error, Reason}
```

Types:

- `Host = Name = atom()`
- `Args = string()`
- `Node = node()`
- `Reason = timeout | no_rsh | {already_running, Node}`

Starts a slave node in the same way as `start/1,2,3`, except that the slave node is linked to the currently executing process. If that process terminates, the slave node also terminates.

See `start/1,2,3` for a description of arguments and return values.

`stop(Node) -> ok`

Types:

- `Node = node()`

Stops (kills) a node.

`pseudo([Master | ServerList]) -> ok`

Types:

- `Master = node()`
- `ServerList = [atom()]`

Calls `pseudo(Master, ServerList)`. If we want to start a node from the command line and set up a number of pseudo servers, an Erlang runtime system can be started as follows:

```
% erl -name abc -s slave pseudo klacke@super x --
```

`pseudo(Master, ServerList) -> ok`

Types:

- `Master = node()`
- `ServerList = [atom()]`

Starts a number of pseudo servers. A pseudo server is a server with a registered name which does absolutely nothing but pass on all message to the real server which executes at a master node. A pseudo server is an intermediary which only has the same registered name as the real server.

For example, if we have started a slave node `N` and want to execute `pxw` graphics code on this node, we can start the server `pxw_server` as a pseudo server at the slave node. The following code illustrates:

```
rpc:call(N, slave, pseudo, [node(), [pxw_server]]).
```

`relay(Pid)`

Types:

- `Pid = pid()`

Runs a pseudo server. This function never returns any value and the process which executes the function will receive messages. All messages received will simply be passed on to `Pid`.

# sofs

Erlang Module

The `sofs` module implements operations on finite sets and relations represented as sets. Intuitively, a set is a collection of elements; every element belongs to the set, and the set contains every element.

Given a set  $A$  and a sentence  $S(x)$ , where  $x$  is a free variable, a new set  $B$  whose elements are exactly those elements of  $A$  for which  $S(x)$  holds can be formed, this is denoted  $B = \{x \in A : S(x)\}$ . Sentences are expressed using the logical operators “for some” (or “there exists”), “for all”, “and”, “or”, “not”. If the existence of a set containing all the specified elements is known (as will always be the case in this module), we write  $B = \{x : S(x)\}$ .

The *unordered set* containing the elements  $a$ ,  $b$  and  $c$  is denoted  $\{a,b,c\}$ . This notation is not to be confused with tuples. The *ordered pair* of  $a$  and  $b$ , with first *coordinate*  $a$  and second coordinate  $b$ , is denoted  $(a,b)$ . An ordered pair is an *ordered set* of two elements. In this module ordered sets can contain one, two or more elements, and parentheses are used to enclose the elements. Unordered sets and ordered sets are orthogonal, again in this module; there is no unordered set equal to any ordered set.

The set that contains no elements is called the *empty set*. If two sets  $A$  and  $B$  contain the same elements, then  $A$  is *equal* to  $B$ , denoted  $A=B$ . Two ordered sets are equal if they contain the same number of elements and have equal elements at each coordinate. If a set  $A$  contains all elements that  $B$  contains, then  $B$  is a *subset* of  $A$ . The *union* of two sets  $A$  and  $B$  is the smallest set that contains all elements of  $A$  and all elements of  $B$ . The *intersection* of two sets  $A$  and  $B$  is the set that contains all elements of  $A$  that belong to  $B$ . Two sets are *disjoint* if their intersection is the empty set. The *difference* of two sets  $A$  and  $B$  is the set that contains all elements of  $A$  that do not belong to  $B$ . The *symmetric difference* of two sets is the set that contains those element that belong to either of the two sets, but not both. The *union* of a collection of sets is the smallest set that contains all the elements that belong to at least one set of the collection. The *intersection* of a non-empty collection of sets is the set that contains all elements that belong to every set of the collection.

The *Cartesian product* of two sets  $X$  and  $Y$ , denoted  $XY$ , is the set  $\{a : a = (x,y) \text{ for some } x \in X \text{ and for some } y \in Y\}$ . A *relation* is a subset of  $XY$ . Let  $R$  be a relation. The fact that  $(x,y)$  belongs to  $R$  is written as  $xRy$ . Since relations are sets, the definitions of the last paragraph (subset, union, and so on) apply to relations as well. The *domain* of  $R$  is the set  $\{x : xRy \text{ for some } y \in Y\}$ . The *range* of  $R$  is the set  $\{y : xRy \text{ for some } x \in X\}$ . The *converse* of  $R$  is the set  $\{a : a = (y,x) \text{ for some } (x,y) \in R\}$ . If  $A$  is a subset of  $X$ , then the *image* of  $A$  under  $R$  is the set  $\{y : xRy \text{ for some } x \in A\}$ , and if  $B$  is a subset of  $Y$ , then the *inverse image* of  $B$  is the set  $\{x : xRy \text{ for some } y \in B\}$ . If  $R$  is a relation from  $X$  to  $Y$  and  $S$  is a relation from  $Y$  to  $Z$ , then the *relative product* of  $R$  and  $S$  is the relation  $T$  from  $X$  to  $Z$  defined so that  $xTz$  if and only if there exists an element  $y$  in  $Y$  such that  $xRy$  and  $ySz$ . The *restriction* of  $R$  to  $A$  is the set  $S$  defined so that  $xSy$  if and only if there exists an element  $x$  in  $A$  such that  $xRy$ . If  $S$  is a restriction of  $R$  to  $A$ , then  $R$  is an *extension* of  $S$  to  $X$ . If  $X=Y$  then we call  $R$  a relation *in*  $X$ . The *field* of a relation  $R$  in  $X$  is the union of

the domain of  $R$  and the range of  $R$ . If  $R$  is a relation in  $X$ , and if  $S$  is defined so that  $xSy$  if  $xRy$  and not  $x=y$ , then  $S$  is the *strict* relation corresponding to  $R$ , and vice versa, if  $S$  is a relation in  $X$ , and if  $R$  is defined so that  $xRy$  if  $xSy$  or  $x=y$ , then  $R$  is the *weak* relation corresponding to  $S$ . A relation  $R$  in  $X$  is *reflexive* if  $xRx$  for every element  $x$  of  $X$ ; it is *symmetric* if  $xRy$  implies that  $yRx$ ; and it is *transitive* if  $xRy$  and  $yRz$  imply that  $xRz$ .

A *function*  $F$  is a relation, a subset of  $XY$ , such that the domain of  $F$  is equal to  $X$  and such that for every  $x$  in  $X$  there is a unique element  $y$  in  $Y$  with  $(x,y)$  in  $F$ . The latter condition can be formulated as follows: if  $xFy$  and  $xFz$  then  $y=z$ . In this module, it will not be required that the domain of  $F$  be equal to  $X$  for a relation to be considered a function. Instead of writing  $(x,y)$  in  $F$  or  $xFy$ , we write  $F(x)=y$  when  $F$  is a function, and say that  $F$  maps  $x$  onto  $y$ , or that the value of  $F$  at  $x$  is  $y$ . Since functions are relations, the definitions of the last paragraph (domain, range, and so on) apply to functions as well. If the converse of a function  $F$  is a function  $F'$ , then  $F'$  is called the *inverse* of  $F$ . The relative product of two functions  $F_1$  and  $F_2$  is called the *composite* of  $F_1$  and  $F_2$  if the range of  $F_1$  is a subset of the domain of  $F_2$ .

Sometimes, when the range of a function is more important than the function itself, the function is called a *family*. The domain of a family is called the *index set*, and the range is called the *indexed set*. If  $x$  is a family from  $I$  to  $X$ , then  $x[i]$  denotes the value of the function at index  $i$ . The notation “a family in  $X$ ” is used for such a family. When the indexed set is a set of subsets of a set  $X$ , then we call  $x$  a *family of subsets* of  $X$ . If  $x$  is a family of subsets of  $X$ , then the union of the range of  $x$  is called the *union of the family*  $x$ . If  $x$  is non-empty (the index set is non-empty), the *intersection of the family*  $x$  is the intersection of the range of  $x$ . In this module, the only families that will be considered are families of subsets of some set  $X$ ; in the following the word “family” will be used for such families of subsets.

A *partition* of a set  $X$  is a collection  $S$  of non-empty subsets of  $X$  whose union is  $X$  and whose elements are pairwise disjoint. A relation in a set is an *equivalence relation* if it is reflexive, symmetric and transitive. If  $R$  is an equivalence relation in  $X$ , and  $x$  is an element of  $X$ , the *equivalence class* of  $x$  with respect to  $R$  is the set of all those elements  $y$  of  $X$  for which  $xRy$  holds. The equivalence classes constitute a partitioning of  $X$ . Conversely, if  $C$  is a partition of  $X$ , then the relation that holds for any two elements of  $X$  if they belong to the same equivalence class, is an equivalence relation induced by the partition  $C$ . If  $R$  is an equivalence relation in  $X$ , then the *canonical map* is the function that maps every element of  $X$  onto its equivalence class.

Relations as defined above (as sets of ordered pairs) will from now on be referred to as *binary relations*. We call a set of ordered sets  $(x[1], \dots, x[n])$  an *(n-ary) relation*, and say that the relation is a subset of the Cartesian product  $X[1] \dots X[n]$  where  $x[i]$  is an element of  $X[i]$ ,  $1 \leq i \leq n$ . The *projection* of an  $n$ -ary relation  $R$  onto coordinate  $i$  is the set  $\{x[i]: (x[1], \dots, x[i], \dots, x[n]) \text{ in } R \text{ for some } x[j] \text{ in } X[j], 1 \leq j \leq n \text{ and not } i=j\}$ . The projections of a binary relation  $R$  onto the first and second coordinates are the domain and the range of  $R$  respectively. The relative product of binary relations can be generalized to  $n$ -ary relations as follows. Let  $TR$  be an ordered set  $(R[1], \dots, R[n])$  of binary relations from  $X$  to  $Y[i]$  and  $S$  a binary relation from  $(Y[1] \dots Y[n])$  to  $Z$ . The *relative product* of  $TR$  and  $S$  is the binary relation  $T$  from  $X$  to  $Z$  defined so that  $xTz$  if and only if there exists an element  $y[i]$  in  $Y[i]$  for each  $1 \leq i \leq n$  such that  $xR[i]y[i]$  and  $(y[1], \dots, y[n])S_z$ . Now let  $TR$  be a an ordered set  $(R[1], \dots, R[n])$  of binary relations from  $X[i]$  to  $Y[i]$  and  $S$  a subset of  $X[1] \dots X[n]$ . The *multiple relative product* of  $TR$  and  $S$  is defined to be the set  $\{z: z = ((x[1], \dots, x[n]), (y[1], \dots, y[n])) \text{ for some } (x[1], \dots, x[n]) \text{ in } S \text{ and for some } (x[i], y[i]) \text{ in } R[i], 1 \leq i \leq n\}$ . The *natural join* of an  $n$ -ary relation  $R$  and an  $m$ -ary relation  $S$  on coordinate  $i$  and  $j$  is defined to be the set  $\{z:$

$z = (x[1], \dots, x[n], y[1], \dots, y[j-1], y[j+1], \dots, y[m])$  for some  $(x[1], \dots, x[n]) \in R$  and for some  $(y[1], \dots, y[m]) \in S$  such that  $x[i] = y[j]$ .

The sets recognized by this module will be represented by elements of the relation `Sets`, defined as the smallest set such that:

- for every atom `T` except `'_'` and for every term `X`,  $(T, X)$  belongs to `Sets` (*atomic sets*);
- $(['_'], [])$  belongs to `Sets` (the *untyped empty set*);
- for every tuple  $T = \{T[1], \dots, T[n]\}$  and for every tuple  $X = \{X[1], \dots, X[n]\}$ , if  $(T[i], X[i])$  belongs to `Sets` for every  $1 \leq i \leq n$  then  $(T, X)$  belongs to `Sets` (*ordered sets*);
- for every term `T`, if `X` is the empty list or a non-empty sorted list  $[X[1], \dots, X[n]]$  without duplicates such that  $(T, X[i])$  belongs to `Sets` for every  $1 \leq i \leq n$ , then  $([T], X)$  belongs to `Sets` (*typed unordered sets*).

An *external set* is an element of the range of `Sets`. A *type* is an element of the domain of `Sets`. If `S` is an element  $(T, X)$  of `Sets`, then `T` is a *valid type* of `X`, `T` is the type of `S`, and `X` is the external set of `S`. `from_term/2` [page 329] creates a set from a type and an Erlang term turned into an external set.

The actual sets represented by `Sets` are the elements of the range of the function `Set` from `Sets` to Erlang terms and sets of Erlang terms:

- $\text{Set}(T, \text{Term}) = \text{Term}$ , where `T` is an atom;
- $\text{Set}(\{T[1], \dots, T[n]\}, \{X[1], \dots, X[n]\}) = (\text{Set}(T[1], X[1]), \dots, \text{Set}(T[n], X[n]))$ ;
- $\text{Set}([T], [X[1], \dots, X[n]]) = \{\text{Set}(T, X[1]), \dots, \text{Set}(T, X[n])\}$ ;
- $\text{Set}([T], []) = \{\}$ .

When there is no risk of confusion, elements of `Sets` will be identified with the sets they represent. For instance, if `U` is the result of calling `union/2` with `S1` and `S2` as arguments, then `U` is said to be the union of `S1` and `S2`. A more precise formulation would be that  $\text{Set}(U)$  is the union of  $\text{Set}(S1)$  and  $\text{Set}(S2)$ .

The types are used to implement the various conditions that sets need to fulfill. As an example, consider the relative product of two sets `R` and `S`, and recall that the relative product of `R` and `S` is defined if `R` is a binary relation to `Y` and `S` is a binary relation from `Y`. The function that implements the relative product, `relative_product/2` [page 336], checks that the arguments represent binary relations by matching  $\{[A, B]\}$  against the type of the first argument (`Arg1` say), and  $\{[C, D]\}$  against the type of the second argument (`Arg2` say). The fact that  $\{[A, B]\}$  matches the type of `Arg1` is to be interpreted as `Arg1` representing a binary relation from `X` to `Y`, where `X` is defined as all sets  $\text{Set}(x)$  for some element `x` in `Sets` the type of which is `A`, and similarly for `Y`. In the same way `Arg2` is interpreted as representing a binary relation from `W` to `Z`. Finally it is checked that `B` matches `C`, which is sufficient to ensure that `W` is equal to `Y`. The untyped empty set is handled separately: its type, `['_']`, matches the type of any unordered set.

A few functions of this module (`drestriction/3`, `family_projection/2`, `partition/2`, `partition_family/2`, `projection/2`, `restriction/3`, `substitution/2`) accept an Erlang function as a means to modify each element of a given unordered set. Such a function, called `SetFun` in the following, can be specified as a functional object (`fun`), a tuple  $\{\text{external}, \text{Fun}\}$ , or an integer. If `SetFun` is specified as a `fun`, the `fun` is applied to each element of the given set and the return value is

assumed to be a set. If SetFun is specified as a tuple {external, Fun}, Fun is applied to the external set of each element of the given set and the return value is assumed to be an external set. Selecting the elements of an unordered set as external sets and assembling a new unordered set from a list of external sets is in the present implementation more efficient than modifying each element as a set. However, this optimization can only be utilized when the elements of the unordered set are atomic or ordered sets. It must also be the case that the type of the elements matches some clause of Fun (the type of the created set is the result of applying Fun to the type of the given set), and that Fun does nothing but selecting, duplicating or rearranging parts of the elements. Specifying a SetFun as an integer I is equivalent to specifying {external, fun(X) -> element(I, X)}, but is to be preferred since it makes it possible to handle this case even more efficiently. Examples of SetFuns:

```
{sofs, union}
fun(S) -> sofs:partition(1, S) end
{external, fun(A) -> A end}
{external, fun({A,-,C}) -> {C,A} end}
{external, fun({-,{-,C}}) -> C end}
{external, fun({-,-,{-,E}=C}) -> {E,{E,C}} end}
2
```

The order in which a SetFun is applied to the elements of an unordered set is not specified, and may change in future versions of sofs.

The execution time of the functions of this module is dominated by the time it takes to sort lists. When no sorting is needed, the execution time is in the worst case proportional to the sum of the sizes of the input arguments and the returned value. A few functions execute in constant time: from\_external, is\_empty\_set, is\_set, is\_sofs\_set, to\_external, type.

The functions of this module exit the process with a badarg, bad\_function, or type\_mismatch message when given badly formed arguments or sets the types of which are not compatible.

### Types

```
anyset() = -an unordered, ordered or atomic set-
binary_relation() = -a binary relation-
bool() = true | false
external_set() = -an external set-
family() = -a family (of subsets)-
function() = -a function-
ordset() = -an ordered set-
relation() = -an n-ary relation-
set() = -an unordered set-
set_of_sets() = -an unordered set of set()-
set_fun() = integer() >= 1
           | {external, fun(external_set()) -> external_set()}
           | fun(anyset()) -> anyset()
spec_fun() = {external, fun(external_set()) -> bool()}
           | fun(anyset()) -> bool()
type() = -a type-
```

## Exports

`a_function(Tuples [, Type]) -> Function`

Types:

- Function = function()
- Tuples = [tuple()]
- Type = type()

Creates a function [page 319]. `a_function(F,T)` is equivalent to `from_term(F,T)`, if the result is a function. If no type [page 320] is explicitly given, `[{atom,atom}]` is used as type of the function.

`canonical_relation(SetOfSets) -> BinRel`

Types:

- BinRel = binary\_relation()
- SetOfSets = set\_of\_sets()

Returns the binary relation containing the elements (E,Set) such that Set belongs to SetOfSets and E belongs to Set. If SetOfSets is a partition [page 319] of a set X and R is the equivalence relation in X induced by SetOfSets, then the returned relation is the canonical map [page 319] from X onto the equivalence classes with respect to R.

```
1> Ss = sofs:from_term([[a,b],[b,c]]),
CR = sofs:canonical_relation(Ss),
sofs:to_external(CR).
[{{a,[a,b]},{b,[a,b]},{b,[b,c]},{c,[b,c]}}
```

`composite(Function1, Function2) -> Function3`

Types:

- Function1 = Function2 = Function3 = function()

Returns the composite [page 319] of the functions Function1 and Function2.

```
1> F1 = sofs:a_function([{{a,1},{b,2},{c,2}}],
F2 = sofs:a_function([{{1,x},{2,y},{3,z}}],
F = sofs:composite(F1, F2),
sofs:to_external(F).
[{{a,x},{b,y},{c,y}}
```

`constant_function(Set, AnySet) -> Function`

Types:

- AnySet = anyset()
- Function = function()
- Set = set()

Creates the function [page 319] that maps each element of the set Set onto AnySet.

```

1> S = sofs:set([a,b]),
E = sofs:from_term(1),
R = sofs:constant_function(S, E),
sofs:to_external(R).
[{a,1}],{b,1}]

```

converse(BinRel1) -> BinRel2

Types:

- BinRel1 = BinRel2 = binary\_relation()

Returns the converse [page 318] of the binary relation BinRel1.

```

1> R1 = sofs:relation([{1,a}],{2,b}],{3,a}]),
R2 = sofs:converse(R1),
sofs:to_external(R2).
[{a,1}],{a,3}],{b,2}]

```

difference(Set1, Set2) -> Set3

Types:

- Set1 = Set2 = Set3 = set()

Returns the difference [page 318] of the sets Set1 and Set2.

digraph\_to\_family(Graph [, Type]) -> Family

Types:

- Graph = digraph() -see digraph(3)-
- Family = family()
- Type = type()

Creates a family [page 319] from the directed graph Graph. Each vertex a of Graph is represented by a pair (a,{b[1],...,b[n]}) where the b[i]'s are the out-neighbours of a. If no type is explicitly given, [{atom,[atom]}] is used as type of the family. It is assumed that Type is a valid type [page 320] of the external set of the family.

If G is a directed graph, it holds that the vertices and edges of G are the same as the vertices and edges of family\_to\_digraph(digraph\_to\_family(G)).

domain(BinRel) -> Set

Types:

- BinRel = binary\_relation()
- Set = set()

Returns the domain [page 318] of the binary relation BinRel.

```

1> R = sofs:relation([{1,a}],{1,b}],{2,b}],{2,c}]),
S = sofs:domain(R),
sofs:to_external(S).
[1,2]

```

drestriction(BinRel1, Set) -> BinRel2

Types:

- BinRel1 = BinRel2 = binary\_relation()
- Set = set()

Returns the difference between the binary relation BinRel1 and the restriction [page 318] of BinRel1 to Set.

```
1> R1 = sofs:relation([1,a], [2,b], [3,c]),
S = sofs:set([2,4,6]),
R2 = sofs:drestriction(R1, S),
sofs:to_external(R2).
[1,a], [3,c]
```

drestriction(R,S) is equivalent to difference(R, restriction(R,S)).

drestriction(SetFun, Set1, Set2) -> Set3

Types:

- SetFun = set\_fun()
- Set1 = Set2 = Set3 = set()

Returns a subset of Set1 containing those elements that do not yield an element in Set2 as the result of applying SetFun.

```
1> SetFun = {external, fun({_A,B,C}) -> {B,C} end},
R1 = sofs:relation([a,aa,1], [b,bb,2], [c,cc,3]),
R2 = sofs:relation([bb,2], [cc,3], [dd,4]),
R3 = sofs:drestriction(SetFun, R1, R2),
sofs:to_external(R3).
[a,aa,1]
```

drestriction(F,S1,S2) is equivalent to difference(S1, restriction(F,S1,S2)).

empty\_set() -> Set

Types:

- Set = set()

Returns the untyped empty set [page 320]. empty\_set() is equivalent to from\_term([], ['\_']).

extension(BinRel1, Set, AnySet) -> BinRel2

Types:

- AnySet = anyset()
- BinRel1 = BinRel2 = binary\_relation()
- Set = set()

Returns the extension [page 318] of BinRel1 such that for each element E in Set that does not belong to the domain [page 318] of BinRel1, BinRel2 contains the pair (E,AnySet).

```
1> S = sofs:set([b,c]),
A = sofs:empty_set(),
R = sofs:family([a,[1,2]], [b,[3]]),
X = sofs:extension(R, S, A),
sofs:to_external(X).
[a,[1,2]], [b,[3]], [c,[]]
```

`family(Tuples [, Type]) -> Family`

Types:

- Family = family()
- Tuples = [tuple()]
- Type = type()

Creates a family of subsets [page 319]. `family(F,T)` is equivalent to `from_term(F,T)`, if the result is a family. If no type [page 320] is explicitly given, `[{atom, [atom]}]` is used as type of the family.

`family_difference(Family1, Family2) -> Family3`

Types:

- Family1 = Family2 = Family3 = family()

If Family1 and Family2 are families [page 319], then Family3 the family such that the index set is equal to the index set of Family1, and Family3[i] is the difference between Family1[i] and Family2[i] if Family2 maps i, Family1[i] otherwise.

```
1> F1 = sofs:family([a, [1,2]], {b, [3,4]}],
F2 = sofs:family([b, [4,5]], {c, [6,7]}],
F3 = sofs:family_difference(F1, F2),
sofs:to_external(F3).
[a, [1,2]], {b, [3]}
```

`family_domain(Family1) -> Family2`

Types:

- Family1 = Family2 = family()

If Family1 is a family [page 319] and Family1[i] is a binary relation for every i in the index set of Family1, then Family2 is the family with the same index set as Family1 such that Family2[i] is the domain [page 318] of Family1[i].

```
1> FR = sofs:from_term([a, [{1,a}, {2,b}, {3,c}], {b, []}, {c, [{4,d}, {5,e}]}],
F = sofs:family_domain(FR),
sofs:to_external(F).
[a, [1,2,3]], {b, []}, {c, [4,5]}
```

`family_field(Family1) -> Family2`

Types:

- Family1 = Family2 = family()

If Family1 is a family [page 319] and Family1[i] is a binary relation for every i in the index set of Family1, then Family2 is the family with the same index set as Family1 such that Family2[i] is the field [page 318] of Family1[i].

```
1> FR = sofs:from_term([a, [{1,a}, {2,b}, {3,c}], {b, []}, {c, [{4,d}, {5,e}]}],
F = sofs:family_field(FR),
sofs:to_external(F).
[a, [1,2,3,a,b,c]], {b, []}, {c, [4,5,d,e]}
```

`family_field(Family1)` is equivalent to `family_union(family_domain(Family1), family_range(Family1))`.

`family_intersection(Family1) -> Family2`

Types:

- `Family1 = Family2 = family()`

If `Family1` is a family [page 319] and `Family1[i]` is a set of sets for every `i` in the index set of `Family1`, then `Family2` is the family with the same index set as `Family1` such that `Family2[i]` is the intersection [page 318] of `Family1[i]`.

If `Family1[i]` is an empty set for some `i`, then the process exits with a `badarg` message.

```
1> F1 = sofs:from_term([a, [[1,2,3], [2,3,4]], {b, [[x,y,z], [x,y]]}]),
F2 = sofs:family_intersection(F1),
sofs:to_external(F2).
[a, [2,3]], {b, [x,y]}
```

`family_intersection(Family1, Family2) -> Family3`

Types:

- `Family1 = Family2 = Family3 = family()`

If `Family1` and `Family2` are families [page 319], then `Family3` is the family such that the index set is the intersection of `Family1`'s and `Family2`'s index sets, and `Family3[i]` is the intersection of `Family1[i]` and `Family2[i]`.

```
1> F1 = sofs:family([a, [1,2]], {b, [3,4]}, {c, [5,6]}),
F2 = sofs:family([b, [4,5]], {c, [7,8]}, {d, [9,10]}),
F3 = sofs:family_intersection(F1, F2),
sofs:to_external(F3).
[b, [4]], {c, []}
```

`family_projection(SetFun, Family1) -> Family2`

Types:

- `SetFun = set_fun()`
- `Family1 = Family2 = family()`
- `Set = set()`

If `Family1` is a family [page 319] then `Family2` is the family with the same index set as `Family1` such that `Family2[i]` is the result of calling `SetFun` with `Family1[i]` as argument.

```
1> F1 = sofs:from_term([a, [[1,2], [2,3]], {b, [[]]}),
F2 = sofs:family_projection({sofs, union}, F1),
sofs:to_external(F2).
[a, [1,2,3]], {b, []}
```

`family_range(Family1) -> Family2`

Types:

- `Family1 = Family2 = family()`

If `Family1` is a family [page 319] and `Family1[i]` is a binary relation for every `i` in the index set of `Family1`, then `Family2` is the family with the same index set as `Family1` such that `Family2[i]` is the range [page 318] of `Family1[i]`.

```
1> FR = sofs:from_term([a, [1,a], {2,b}, {3,c}], {b, []}, {c, [4,d], {5,e}}]),
F = sofs:family_range(FR),
sofs:to_external(F).
[a, [a,b,c]], {b, []}, {c, [d,e]}
```

family\_specification(Fun, Family1) -> Family2

Types:

- Fun = spec\_fun()
- Family1 = Family2 = family()

If Family1 is a family [page 319], then Family2 is the restriction [page 318] of Family1 to those elements  $i$  of the index set for which Fun applied to Family1[i] returns true. If Fun is a tuple {external, Fun2}, Fun2 is applied to the external set [page 320] of Family1[i], otherwise Fun is applied to Family1[i].

```
1> F1 = sofs:family([a, [1,2,3]], {b, [1,2]}, {c, [1]}),
SpecFun = fun(S) -> sofs:no_elements(S) == 2 end,
F2 = sofs:family_specification(SpecFun, F1),
sofs:to_external(F2).
[b, [1,2]]
```

family\_to\_digraph(Family [, GraphType]) -> Graph

Types:

- Graph = digraph()
- Family = family()
- GraphType = -see digraph(3)-

Creates a directed graph from the family [page 319] Family. For each pair (a, {b[1],...,b[n]}) of Family, the vertex a as well the edges (a,b[i]) for  $1 \leq i \leq n$  are added to a newly created directed graph.

If no graph type is given, digraph:new/1 is used for creating the directed graph, otherwise the GraphType argument is passed on as second argument to digraph:new/2.

If F is a family, it holds that F is a subset of digraph\_to\_family(family\_to\_digraph(F), type(F)). Equality holds if union\_of\_family(F) is a subset of domain(F).

Creating a cycle in an acyclic graph exits the process with a cyclic message.

family\_to\_relation(Family) -> BinRel

Types:

- Family = family()
- BinRel = binary\_relation()

If Family is a family [page 319], then BinRel is the binary relation containing all pairs (i,x) such that i belongs to the index set of Family and x belongs to Family[i].

```
1> F = sofs:family([a, []], {b, [1]}, {c, [2,3]}),
R = sofs:family_to_relation(F),
sofs:to_external(R).
[b,1], {c,2}, {c,3}
```

family\_union(Family1) -> Family2

Types:

- Family1 = Family2 = family()

If Family1 is a family [page 319] and Family1[i] is a set of sets for each i in the index set of Family1, then Family2 is the family with the same index set as Family1 such that Family2[i] is the union [page 318] of Family1[i].

```
1> F1 = sofs:from_term([[{a, [1,2]}, {b, [2,3]}], {b, [[]]}],
F2 = sofs:family_union(F1),
sofs:to_external(F2).
[{a, [1,2,3]}, {b, []}]
```

family\_union(F) is equivalent to family\_projection({sofs, union}, F).

family\_union(Family1, Family2) -> Family3

Types:

- Family1 = Family2 = Family3 = family()

If Family1 and Family2 are families [page 319], then Family3 is the family such that the index set is the union of Family1's and Family2's index sets, and Family3[i] is the union of Family1[i] and Family2[i] if both maps i, Family1[i] or Family2[i] otherwise.

```
1> F1 = sofs:family([[{a, [1,2]}, {b, [3,4]}, {c, [5,6]}]),
F2 = sofs:family([[{b, [4,5]}, {c, [7,8]}, {d, [9,10]}]),
F3 = sofs:family_union(F1, F2),
sofs:to_external(F3).
[{a, [1,2]}, {b, [3,4,5]}, {c, [5,6,7,8]}, {d, [9,10]}]
```

field(BinRel) -> Set

Types:

- BinRel = binary\_relation()
- Set = set()

Returns the field [page 318] of the binary relation BinRel.

```
1> R = sofs:relation([[{1,a}, {1,b}, {2,b}, {2,c}]]),
S = sofs:field(R),
sofs:to_external(S).
[1,2,a,b,c]
```

field(R) is equivalent to union(domain(R), range(R)).

from\_external(ExternalSet, Type) -> AnySet

Types:

- ExternalSet = external\_set()
- AnySet = anyset()
- Type = type()

Creates a set from the external set [page 320] ExternalSet and the type [page 320] Type. It is assumed that Type is a valid type [page 320] of ExternalSet.

from\_sets(ListOfSets) -> Set

Types:

- Set = set()
- ListOfSets = [anyset()]

Returns the unordered set [page 320] containing the sets of the list ListOfSets.

```
1> S1 = sofs:relation([a,1],b,2]),
S2 = sofs:relation([x,3],y,4]),
S = sofs:from_sets([S1,S2]),
sofs:to_external(S).
[[{a,1},{b,2}],[{x,3},{y,4}]]
```

from\_sets(TupleOfSets) -> Ordset

Types:

- Ordset = ordset()
- TupleOfSets = tuple-of(anyset())

Returns the ordered set [page 320] containing the sets of the non-empty tuple TupleOfSets.

from\_term(Term [, Type]) -> AnySet

Types:

- AnySet = anyset()
- Term = term()
- Type = type()

Creates an element of Sets [page 320] by traversing the term Term, sorting lists, removing duplicates and deriving or verifying a valid type [page 320] for the so obtained external set. An explicitly given type [page 320] Type can be used to limit the depth of the traversal; an atomic type stops the traversal, as demonstrated by this example where "foo" and {"foo"} are left unmodified:

```
1> S = sofs:from_term([{"foo"},[1,1]},{ "foo", [2,2] }, [atom,[atom] ]]),
sofs:to_external(S).
[{"foo"}, [1] ], {"foo", [2] ]]
```

from\_term can be used for creating atomic or ordered sets. The only purpose of such a set is that of later building unordered sets since all functions in this module that *do* anything operate on unordered sets. Creating unordered sets from a collection of ordered sets may be the way to go if the ordered sets are big and one does not want to waste heap by rebuilding the elements of the unordered set. An example showing that a set can be built "layer by layer":

```
1> A = sofs:from_term(a),
S = sofs:set([1,2,3]),
P1 = sofs:from_sets({A,S}),
P2 = sofs:from_term({b,[6,5,4]}),
Ss = sofs:from_sets([P1,P2]),
sofs:to_external(Ss).
[{a,[1,2,3]},{b,[4,5,6]}]
```

Other functions that create sets are `from_external/2` and `from_sets/1`. Special cases of `from_term/2` are `a_function/1,2`, `empty_set/0`, `family/1,2`, `relation/1,2`, and `set/1,2`.

`image(BinRel, Set1) -> Set2`

Types:

- `BinRel = binary_relation()`
- `Set1 = Set2 = set()`

Returns the image [page 318] of the set `Set1` under the binary relation `BinRel`.

```
1> R = sofs:relation([1,a], [2,b], [2,c], [3,d]),
S1 = sofs:set([1,2]),
S2 = sofs:image(R, S1),
sofs:to_external(S2).
[a,b,c]
```

`intersection(SetOfSets) -> Set`

Types:

- `Set = set()`
- `SetOfSets = set_of_sets()`

Returns the intersection [page 318] of the set of sets `SetOfSets`.

Intersecting an empty set of sets exits the process with a `badarg` message.

`intersection(Set1, Set2) -> Set3`

Types:

- `Set1 = Set2 = Set3 = set()`

Returns the intersection [page 318] of `Set1` and `Set2`.

`intersection_of_family(Family) -> Set`

Types:

- `Family = family()`
- `Set = set()`

Returns the intersection of the family [page 319] `Family`.

Intersecting an empty family exits the process with a `badarg` message.

```
1> F = sofs:family([a, [0,2,4]], [b, [0,1,2]], [c, [2,3]]),
S = sofs:intersection_of_family(F),
sofs:to_external(S).
[2]
```

`inverse(Function1) -> Function2`

Types:

- `Function1 = Function2 = function()`

Returns the inverse [page 319] of the function `Function1`.

```
1> R1 = sofs:relation([1,a},{2,b},{3,c}],
R2 = sofs:inverse(R1),
sofs:to_external(R2).
[1,a], [2,b], [3,c]
```

`inverse_image(BinRel, Set1) -> Set2`

Types:

- BinRel = binary\_relation()
- Set1 = Set2 = set()

Returns the inverse image [page 318] of Set1 under the binary relation BinRel.

```
1> R = sofs:relation([1,a},{2,b},{2,c},{3,d}],
S1 = sofs:set([c,d,e]),
S2 = sofs:inverse_image(R, S1),
sofs:to_external(S2).
[2,3]
```

`is_a_function(BinRel) -> Bool`

Types:

- Bool = bool()
- BinRel = binary\_relation()

Returns true if the binary relation BinRel is a function [page 319] or the untyped empty set, false otherwise.

`is_disjoint(Set1, Set2) -> Bool`

Types:

- Bool = bool()
- Set1 = Set2 = set()

Returns true if Set1 and Set2 are disjoint [page 318], false otherwise.

`is_empty_set(AnySet) -> Bool`

Types:

- AnySet = anyset()
- Bool = bool()

Returns true if Set is an empty unordered set, false otherwise.

`is_equal(AnySet1, AnySet2) -> Bool`

Types:

- AnySet1 = AnySet2 = anyset()
- Bool = bool()

Returns true if the AnySet1 and AnySet2 are equal [page 318], false otherwise.

`is_set(AnySet) -> Bool`

Types:

- AnySet = anyset()
- Bool = bool()

Returns `true` if AnySet is an unordered set [page 320], and `false` if AnySet is an ordered set or an atomic set.

`is_sofs_set(Term) -> Bool`

Types:

- Bool = bool()
- Term = term()

Returns `true` if Term is an unordered set [page 320], an ordered set or an atomic set, `false` otherwise.

`is_subset(Set1, Set2) -> Bool`

Types:

- Bool = bool()
- Set1 = Set2 = set()

Returns `true` if Set1 is a subset [page 318] of Set2, `false` otherwise.

`is_type(Term) -> Bool`

Types:

- Bool = bool()
- Term = term()

Returns `true` if the term Term is a type [page 320].

`join(Relation1, I, Relation2, J) -> Relation3`

Types:

- Relation1 = Relation2 = Relation3 = relation()
- I = J = integer() > 0

Returns the natural join [page 319] of the relations Relation1 and Relation2 on coordinates I and J.

```
1> R1 = sofs:relation([[a,x,1},{b,y,2}]),
R2 = sofs:relation([[1,f,g},{1,h,i},{2,3,4}]),
J = sofs:join(R1, 3, R2, 1),
sofs:to_external(J).
[[a,x,1,f,g},{a,x,1,h,i},{b,y,2,3,4}]
```

`multiple_relative_product(TupleOfBinRels, BinRel1) -> BinRel2`

Types:

- TupleOfBinRels = tuple-of(BinRel)
- BinRel = BinRel1 = BinRel2 = binary\_relation()

If TupleOfBinRels is a non-empty tuple  $\{R[1], \dots, R[n]\}$  of binary relations and BinRel1 is a binary relation, then BinRel2 is the multiple relative product [page 319] of the ordered set  $(R[i], \dots, R[n])$  and BinRel1.

```

1> Ri = sofs:relation([a,1],{b,2},{c,3}]),
R = sofs:relation([a,b],{b,c},{c,a}]),
MP = sofs:multiple_relative_product({Ri, Ri}, R),
sofs:to_external(sofs:range(MP)).
[[1,2],[2,3],[3,1]]

```

`no_elements(ASet) -> NoElements`

Types:

- ASet = set() | ordset()
- NoElements = integer() >= 0

Returns the number of elements of the ordered or unordered set ASet.

`partition(SetOfSets) -> Partition`

Types:

- SetOfSets = set\_of\_sets()
- Partition = set()

Returns the partition [page 319] of the union of the set of sets SetOfSets such that two elements are considered equal if they belong to the same elements of SetOfSets.

```

1> Sets1 = sofs:from_term([a,b,c],[d,e,f],[g,h,i]),
Sets2 = sofs:from_term([b,c,d],[e,f,g],[h,i,j]),
P = sofs:partition(sofs:union(Sets1, Sets2)),
sofs:to_external(P).
[[a],[b,c],[d],[e,f],[g],[h,i],[j]]

```

`partition(SetFun, Set) -> Partition`

Types:

- SetFun = set\_fun()
- Partition = set()
- Set = set()

Returns the partition [page 319] of Set such that two elements are considered equal if the results of applying SetFun are equal.

```

1> Ss = sofs:from_term([a],[b],[c,d],[e,f]),
SetFun = fun(S) -> sofs:from_term(sofs:no_elements(S)) end,
P = sofs:partition(SetFun, Ss),
sofs:to_external(P).
[[a],[b]],[[c,d],[e,f]]

```

`partition(SetFun, Set1, Set2) -> {Set3, Set4}`

Types:

- SetFun = set\_fun()
- Set1 = Set2 = Set3 = Set4 = set()

Returns a pair of sets that, regarded as constituting a set, forms a partition [page 319] of Set1. If the result of applying SetFun to an element of Set1 yields an element in Set2, the element belongs to Set3, otherwise the element belongs to Set4.

```

1> R1 = sofs:relation([[{1,a},{2,b},{3,c}]]),
S = sofs:set([2,4,6]),
{R2,R3} = sofs:partition(1, R1, S),
{sofs:to_external(R2),sofs:to_external(R3)}.
[[{2,b}],[{1,a},{3,c}]]

partition(F,S1,S2) is equivalent to {restriction(F,S1,S2),
drestriction(F,S1,S2)}.

```

partition\_family(SetFun, Set) -> Family

Types:

- Family = family()
- SetFun = set\_fun()
- Set = set()

Returns the family [page 319] Family where the indexed set is a partition [page 319] of Set such that two elements are considered equal if the results of applying SetFun are the same value i. This i is the index that Family maps onto the equivalence class [page 319].

```

1> S = sofs:relation([[{a,a,a,a},{a,a,b,b},{a,b,b,b}]]),
SetFun = {external, fun({A,-,C,-}) -> {A,C} end},
F = sofs:partition_family(SetFun, S),
sofs:to_external(F).
[[{a,a},{a,a,a,a}],[{a,b},{a,a,b,b},{a,b,b,b}]]

```

product(TupleOfSets) -> Relation

Types:

- Relation = relation()
- TupleOfSets = tuple-of(set())

Returns the Cartesian product [page 319] of the non-empty tuple of sets TupleOfSets. If (x[1],...,x[n]) is an element of the n-ary relation Relation, then x[i] is drawn from element i of TupleOfSets.

```

1> S1 = sofs:set([a,b]),
S2 = sofs:set([1,2]),
S3 = sofs:set([x,y]),
P3 = sofs:product({S1,S2,S3}),
sofs:to_external(P3).
[[{a,1,x},{a,1,y},{a,2,x},{a,2,y},{b,1,x},{b,1,y},{b,2,x},{b,2,y}]

```

product(Set1, Set2) -> BinRel

Types:

- BinRel = binary\_relation()
- Set1 = Set2 = set()

Returns the Cartesian product [page 318] of Set1 and Set2.

```

1> S1 = sofs:set([1,2]),
S2 = sofs:set([a,b]),
R = sofs:product(S1, S2),
sofs:to_external(R).
[[{1,a},{1,b},{2,a},{2,b}]

```

`product(S1,S2)` is equivalent to `product({S1,S2})`.

`projection(SetFun, Set1) -> Set2`

Types:

- `SetFun = set_fun()`
- `Set1 = Set2 = set()`

Returns the set created by substituting each element of `Set1` by the result of applying `SetFun` to the element.

If `SetFun` is a number  $i \geq 1$  and `Set1` is a relation, then the returned set is the projection [page 319] of `Set1` onto coordinate  $i$ .

```
1> S1 = sofs:from_term([1,a], [2,b], [3,a]),
   S2 = sofs:projection(2, S1),
   sofs:to_external(S2).
[a,b]
```

`range(BinRel) -> Set`

Types:

- `BinRel = binary_relation()`
- `Set = set()`

Returns the range [page 318] of the binary relation `BinRel`.

```
1> R = sofs:relation([1,a], [1,b], [2,b], [2,c]),
   S = sofs:range(R),
   sofs:to_external(S).
[a,b,c]
```

`relation(Tuples [, Type]) -> Relation`

Types:

- `N = integer()`
- `Type = N | type()`
- `Relation = relation()`
- `Tuples = [tuple()]`

Creates a relation [page 318]. `relation(R,T)` is equivalent to `from_term(R,T)`, if `T` is a type [page 320] and the result is a relation. If `Type` is an integer  $N$ , then `[{atom, ..., atom}]`, where the size of the tuple is  $N$ , is used as type of the relation. If no type is explicitly given, the size of the first tuple of `Tuples` is used if there is such a tuple. `relation([])` is equivalent to `relation([], 2)`.

`relation_to_family(BinRel) -> Family`

Types:

- `Family = family()`
- `BinRel = binary_relation()`

Returns the family [page 319] `Family` such that the index set is equal to the domain [page 318] of the binary relation `BinRel`, and `Family[i]` is the image [page 318] of the set of  $i$  under `BinRel`.

```

1> R = sofs:relation([[b,1],[c,2],[c,3]]),
F = sofs:relation_to_family(R),
sofs:to_external(F).
[[b,[1]],[c,[2,3]]]

```

`relative_product(TupleOfBinRels [, BinRel1]) -> BinRel2`

Types:

- `TupleOfBinRels = tuple-of(BinRel)`
- `BinRel = BinRel1 = BinRel2 = binary_relation()`

If `TupleOfBinRels` is a non-empty tuple  $\{R[1], \dots, R[n]\}$  of binary relations and `BinRel1` is a binary relation, then `BinRel2` is the relative product [page 319] of the ordered set  $\{R[i], \dots, R[n]\}$  and `BinRel1`.

If `BinRel1` is omitted, the relation of equality between the elements of the Cartesian product [page 319] of the ranges of  $R[i]$ , `rangeR[1]...rangeR[n]`, is used instead (intuitively, nothing is “lost”).

```

1> TR = sofs:relation([[1,a],[1,aa],[2,b]]),
R1 = sofs:relation([[1,u],[2,v],[3,c]]),
R2 = sofs:relative_product({TR, R1}),
sofs:to_external(R2).
[[1,{a,u}],[1,{aa,u}],[2,{b,v}]]

```

Note that `relative_product({R1}, R2)` is different from `relative_product(R1, R2)`; the tuple of one element is not identified with the element itself.

`relative_product(BinRel1, BinRel2) -> BinRel3`

Types:

- `BinRel1 = BinRel2 = BinRel3 = binary_relation()`

Returns the relative product [page 318] of the binary relations `BinRel1` and `BinRel2`.

`relative_product1(BinRel1, BinRel2) -> BinRel3`

Types:

- `BinRel1 = BinRel2 = BinRel3 = binary_relation()`

Returns the relative product [page 318] of the converse [page 318] of the binary relation `BinRel1` and the binary relation `BinRel2`.

```

1> R1 = sofs:relation([[1,a],[1,aa],[2,b]]),
R2 = sofs:relation([[1,u],[2,v],[3,c]]),
R3 = sofs:relative_product1(R1, R2),
sofs:to_external(R3).
[[a,u],[aa,u],[b,v]]

```

`relative_product1(R1, R2)` is equivalent to `relative_product(converse(R1), R2)`.

`restriction(BinRel1, Set) -> BinRel2`

Types:

- `BinRel1 = BinRel2 = binary_relation()`
- `Set = set()`

Returns the restriction [page 318] of the binary relation `BinRel1` to `Set`.

```

1> R1 = sofs:relation([1,a],2,b},{3,c}],
S = sofs:set([1,2,4]),
R2 = sofs:restriction(R1, S),
sofs:to_external(R2).
[1,a],2,b]

```

`restriction(SetFun, Set1, Set2) -> Set3`

Types:

- SetFun = set\_fun()
- Set1 = Set2 = Set3 = set()

Returns a subset of Set1 containing those elements that yield an element in Set2 as the result of applying SetFun.

```

1> S1 = sofs:relation([1,a],2,b},{3,c}],
S2 = sofs:set([b,c,d]),
S3 = sofs:restriction(2, S1, S2),
sofs:to_external(S3).
[2,b],3,c]

```

`set(Terms [, Type]) -> Set`

Types:

- Set = set()
- Terms = [term()]
- Type = type()

Creates an unordered set [page 320]. `set(L, T)` is equivalent to `from_term(L, T)`, if the result is an unordered set. If no type [page 320] is explicitly given, `[atom]` is used as type of the set.

`specification(Fun, Set1) -> Set2`

Types:

- Fun = spec\_fun()
- Set1 = Set2 = set()

Returns the set containing every element of Set1 for which Fun returns true. If Fun is a tuple `{external, Fun2}`, Fun2 is applied to the external set [page 320] of each element, otherwise Fun is applied to each element.

```

1> R1 = sofs:relation([a,1],b,2}],
R2 = sofs:relation([x,1],x,2},y,3}],
S1 = sofs:from_sets([R1,R2]),
S2 = sofs:specification({sofs,is_a_function}, S1),
sofs:to_external(S2).
[[a,1],b,2]]

```

`strict_relation(BinRel1) -> BinRel2`

Types:

- BinRel1 = BinRel2 = binary\_relation()

Returns the strict relation [page 319] corresponding to the binary relation BinRel1.

```

1> R1 = sofs:relation([[{1,1},{1,2},{2,1},{2,2}]]),
R2 = sofs:strict_relation(R1),
sofs:to_external(R2).
[{1,2},{2,1}]

```

substitution(SetFun, Set1) -> Set2

Types:

- SetFun = set\_fun()
- Set1 = Set2 = set()

Returns a function, the domain of which is Set1. The value of an element of the domain is the result of applying SetFun to the element.

```

1> L = [{a,1},{b,2}].
[{a,1},{b,2}]
2> sofs:to_external(sofs:projection(1,sofs:relation(L))).
[a,b]
3> sofs:to_external(sofs:substitution(1,sofs:relation(L))).
[{{a,1},a},{b,2},b]
4> SetFun = {external, fun({A,-}=E) -> {E,A} end},
sofs:to_external(sofs:projection(SetFun,sofs:relation(L))).
[{{a,1},a},{b,2},b]

```

The relation of equality between the elements of {a,b,c}:

```

1> I = sofs:substitution(fun(A) -> A end, sofs:set([a,b,c])),
sofs:to_external(I).
[{a,a},{b,b},{c,c}]

```

Let SetOfSets be a set of sets and BinRel a binary relation. The function that maps each element Set of SetOfSets onto the image [page 318] of Set under BinRel is returned by this function:

```

images(SetOfSets, BinRel) ->
  Fun = fun(Set) -> sofs:image(BinRel, Set) end,
  sofs:substitution(Fun, SetOfSets).

```

Here might be the place to reveal something that was more or less stated before, namely that external unordered sets are represented as sorted lists. As a consequence, creating the image of a set under a relation R may traverse all elements of R (to that comes the sorting of results, the image). In images/2, BinRel will be traversed once for each element of SetOfSets, which may take too long. The following efficient function could be used instead under the assumption that the image of each element of SetOfSets under BinRel is non-empty:

```

images2(SetOfSets, BinRel) ->
  CR = sofs:canonical_relation(SetOfSets),
  R = sofs:relative_product1(CR, BinRel),
  sofs:relation_to_family(R).

```

symdiff(Set1, Set2) -> Set3

Types:

- Set1 = Set2 = Set3 = set()

Returns the symmetric difference [page 318] (or the Boolean sum) of Set1 and Set2.

```

1> S1 = sofs:set([1,2,3]),
   S2 = sofs:set([2,3,4]),
   P = sofs:symdiff(S1, S2),
   sofs:to_external(P).
[1,4]

```

`symmetric_partition(Set1, Set2) -> {Set3, Set4, Set5}`

Types:

- Set1 = Set2 = Set3 = Set4 = Set5 = set()

Returns a triple of sets: Set3 contains the elements of Set1 that do not belong to Set2; Set4 contains the elements of Set1 that belong to Set2; Set5 contains the elements of Set2 that do not belong to Set1.

`to_external(AnySet) -> ExternalSet`

Types:

- ExternalSet = external\_set()
- AnySet = anyset()

Returns the external set [page 320] of an atomic, ordered or unordered set.

`to_sets(ASet) -> Sets`

Types:

- ASet = set() | ordset()
- Sets = tuple\_of(AnySet) | [AnySet]

Returns the elements of the ordered set ASet as a tuple of sets, and the elements of the unordered set ASet as a sorted list of sets without duplicates.

`type(AnySet) -> Type`

Types:

- AnySet = anyset()
- Type = type()

Returns the type [page 320] of an atomic, ordered or unordered set.

`union(SetOfSets) -> Set`

Types:

- Set = set()
- SetOfSets = set\_of\_sets()

Returns the union [page 318] of the set of sets SetOfSets.

`union(Set1, Set2) -> Set3`

Types:

- Set1 = Set2 = Set3 = set()

Returns the union [page 318] of Set1 and Set2.

```
union_of_family(Family) -> Set
```

Types:

- Family = family()
- Set = set()

Returns the union of the family [page 319] Family.

```
1> F = sofs:family([[a, [0,2,4]], {b, [0,1,2]}, {c, [2,3]}]),
S = sofs:union_of_family(F),
sofs:to_external(S).
[0,1,2,3,4]
```

```
weak_relation(BinRel1) -> BinRel2
```

Types:

- BinRel1 = BinRel2 = binary\_relation()

Returns a subset S of the weak relation [page 319] W corresponding to the binary relation BinRel1. Let F be the field [page 318] of BinRel1. The subset S is defined so that  $x S y$  if  $x W y$  for some  $x$  in F and for some  $y$  in F.

```
1> R1 = sofs:relation([[{1,1}], {1,2}], {3,1}]),
R2 = sofs:weak_relation(R1),
sofs:to_external(R2).
[[{1,1}], {1,2}], {2,2}], {3,1}], {3,3}]
```

## See Also

dict(3) [page 88], digraph(3) [page 93], orddict(3) [page 251], ordsets(3) [page 256], sets(3) [page 301]

# string

Erlang Module

This module contains functions for string processing.

## Exports

`len(String) -> Length`

Types:

- `String = string()`
- `Length = integer()`

Returns the number of characters in the string.

`equal(String1, String2) -> bool()`

Types:

- `String1 = String2 = string()`

Tests whether two strings are equal. Returns `true` if they are, otherwise `false`.

`concat(String1, String2) -> String3`

Types:

- `String1 = String2 = String3 = string()`

Concatenates two strings to form a new string. Returns the new string.

`chr(String, Character) -> Index`

`rchr(String, Character) -> Index`

Types:

- `String = string()`
- `Character = char()`
- `Index = integer()`

Returns the index of the first/last occurrence of `Character` in `String`. 0 is returned if `Character` does not occur.

`str(String, SubString) -> Index`

`rstr(String, SubString) -> Index`

Types:

- `String = SubString = string()`

- Index = integer()

Returns the position where the first/last occurrence of SubString begins in String. 0 is returned if SubString does not exist in String. For example:

```
> string:str(" Hello Hello World World ", "Hello World").  
8
```

span(String, Chars) -> Length

cspan(String, Chars) -> Length

Types:

- String = Chars = string()
- Length = integer()

Returns the length of the maximum initial segment of String, which consists entirely of characters from (not from) Chars.

For example:

```
> string:span("\t   abcdef", " \t").  
5  
> string:cspan("\t   abcdef", " \t").  
0
```

substr(String, Start) -> SubString

substr(String, Start, Length) -> Substring

Types:

- String = SubString = string()
- Start = Length = integer()

Returns a substring of String, starting at the position Start, and ending at the end of the string or at length Length.

For example:

```
> substr("Hello World", 4, 5).  
"lo Wo"
```

tokens(String, SeparatorList) -> Tokens

Types:

- String = SeparatorList = string()
- Tokens = [string()]

Returns a list of tokens in String, separated by the characters in SeparatorList.

For example:

```
> tokens("abc defxxghix jkl", "x ").  
["abc", "def", "ghi", "jkl"]
```

chars(Character, Number) -> String

chars(Character, Number, Tail) -> String

Types:

- Character = char()

- Number = integer()
- String = string()

Returns a string consisting of Number of characters Character. Optionally, the string can end with the string Tail.

`copies(String, Number) -> Copies`

Types:

- String = Copies = string()
- Number = integer()

Returns a string containing String repeated Number times.

`words(String) -> Count`

`words(String, Character) -> Count`

Types:

- String = string()
- Character = char()
- Count = integer()

Returns the number of words in String, separated by blanks or Character.

For example:

```
> words(" Hello old boy!", $o).  
4
```

`sub_word(String, Number) -> Word`

`sub_word(String, Number, Character) -> Word`

Types:

- String = Word = string()
- Character = char()
- Number = integer()

Returns the word in position Number of String. Words are separated by blanks or Characters.

For example:

```
> string:sub_word(" Hello old boy !",3,$o).  
"ld b"
```

`strip(String) -> Stripped`

`strip(String, Direction) -> Stripped`

`strip(String, Direction, Character) -> Stripped`

Types:

- String = Stripped = string()
- Direction = left | right | both
- Character = char()

Returns a string, where leading and/or trailing blanks or a number of Character have been removed. Direction can be left, right, or both and indicates from which direction blanks are to be removed. The function strip/1 is equivalent to strip(String, both).

For example:

```
> string:strip("...Hello....", both, $.).  
"Hello"
```

left(String, Number) -> Left

left(String, Number, Character) -> Left

Types:

- String = Left = string()
- Character = char
- Number = integer()

Returns the String with the length adjusted in accordance with Number. The left margin is fixed. If the length(String) < Number, String is padded with blanks or Characters.

For example:

```
> string:left("Hello",10,$.).  
"Hello....."
```

right(String, Number) -> Right

right(String, Number, Character) -> Right

Types:

- String = Right = string()
- Character = char
- Number = integer()

Returns the String with the length adjusted in accordance with Number. The right margin is fixed. If the length of (String) < Number, String is padded with blanks or Characters.

For example:

```
> string:right("Hello", 10, $.).  
".....Hello"
```

centre(String, Number) -> Centered

centre(String, Number, Character) -> Centered

Types:

- String = Centered = string()
- Character = char
- Number = integer()

Returns a string, where String is centred in the string and surrounded by blanks or characters. The resulting string will have the length Number.

sub\_string(String, Start) -> SubString

`sub_string(String, Start, Stop) -> SubString`

Types:

- `String = SubString = string()`
- `Start = Stop = integer()`

Returns a substring of `String`, starting at the position `Start` to the end of the string, or to and including the `Stop` position.

For example:

```
sub_string("Hello World", 4, 8).  
"lo Wo"
```

`to_float(String) -> {Float,Rest} | {error,Reason}`

Types:

- `String = string()`
- `Float = float()`
- `Rest = string()`
- `Reason = no_float | not_a_list`

Argument `String` is expected to start with a valid text represented float (the digits being ASCII values). Remaining characters in the string after the float are returned in `Rest`.

Example:

```
> {F1,Fs} = string:to_float("1.0-1.0e-1"),  
> {F2,[]} = string:to_float(Fs),  
> F1+F2.  
0.900000  
> string:to_float("3/2=1.5").  
{error,no_float}  
> string:to_float("-1.5eX").  
{-1.50000,"eX"}
```

`to_integer(String) -> {Int,Rest} | {error,Reason}`

Types:

- `String = string()`
- `Int = integer()`
- `Rest = string()`
- `Reason = no_integer | not_a_list`

Argument `String` is expected to start with a valid text represented integer (the digits being ASCII values). Remaining characters in the string after the integer are returned in `Rest`.

Example:

```
> {I1,Is} = string:to_integer("33+22"),
> {I2,[]} = string:to_integer(Is),
> I1-I2.
11
> string:to_integer("0.5").
{0,".5"}
> string:to_integer("x=2").
{error,no_integer}
```

```
to_lower(String) -> Result
to_lower(Char) -> CharResult
to_upper(String) -> Result
to_upper(Char) -> CharResult
```

Types:

- String = Result = string()
- Char = CharResult = integer()

The given string or character is case-converted. Note that the supported character set is ISO/IEC 8859-1 (a.k.a. Latin 1), all values outside this set is unchanged

## Notes

Some of the general string functions may seem to overlap each other. The reason for this is that this string package is the combination of two earlier packages and all the functions of both packages have been retained.

The regular expression functions have been moved to their own module `regexp` (see `regexp(3)` [page 296]). The old entry points still exist for backwards compatibility, but will be removed in a future release so that users are encouraged to use the module `regexp`.

### **Note:**

Any undocumented functions in `string` should not be used.

# supervisor

Erlang Module

A behaviour module for implementing a supervisor, a process which supervises other processes called child processes. A child process can either be another supervisor or a worker process. Worker processes are normally implemented using one of the `gen_event`, `gen_fsm`, or `gen_server` behaviours. A supervisor implemented using this module will have a standard set of interface functions and include functionality for tracing and error reporting. Supervisors are used to build an hierarchical process structure called a supervision tree, a nice way to structure a fault tolerant application. Refer to *OTP Design Principles* for more information.

A supervisor assumes the definition of which child processes to supervise to be located in a callback module exporting a pre-defined set of functions.

Unless otherwise stated, all functions in this module will fail if the specified supervisor does not exist or if bad arguments are given.

## Supervision Principles

The supervisor is responsible for starting, stopping and monitoring its child processes. The basic idea of a supervisor is that it should keep its child processes alive by restarting them when necessary.

The children of a supervisor is defined as a list of *child specifications*. When the supervisor is started, the child processes are started in order from left to right according to this list. When the supervisor terminates, it first terminates its child processes in reversed start order, from right to left.

A supervisor can have one of the following *restart strategies*:

- `one_for_one` - if one child process terminates and should be restarted, only that child process is affected.
- `one_for_all` - if one child process terminates and should be restarted, all other child processes are terminated and then all child processes are restarted.
- `rest_for_one` - if one child process terminates and should be restarted, the 'rest' of the child processes – i.e. the child processes after the terminated child process in the start order – are terminated. Then the terminated child process and all child processes after it are restarted.
- `simple_one_for_one` - a simplified `one_for_one` supervisor, where all child processes are dynamically added instances of the same process type, i.e. running the same code.

The functions `terminate_child/2`, `delete_child/2` and `restart_child/2` are invalid for `simple_one_for_one` supervisors and will return `{error, simple_one_for_one}` if the specified supervisor uses this restart strategy.

To prevent a supervisor from getting into an infinite loop of child process terminations and restarts, a *maximum restart frequency* is defined using two integer values `MaxR` and `MaxT`. If more than `MaxR` restarts occur within `MaxT` seconds, the supervisor terminates all child processes and then itself.

This is the type definition of a child specification:

```
child_spec() = {Id,StartFunc,Restart,Shutdown,Type,Modules}
  Id = term()
  StartFunc = {M,F,A}
    M = F = atom()
    A = [term()]
  Restart = permanent | transient | temporary
  Shutdown = brutal_kill | int()>=0 | infinity
  Type = worker | supervisor
  Modules = [Module] | dynamic
  Module = atom()
```

- `Id` is a name that is used to identify the child specification internally by the supervisor.
- `StartFunc` defines the function call used to start the child process. It should be a module-function-arguments tuple `{M,F,A}` used as `apply(M,F,A)`.

The start function *must create and link to* the child process, and should return `{ok,Child}` or `{ok,Child,Info}` where `Child` is the pid of the child process and `Info` an arbitrary term which is ignored by the supervisor.

The start function can also return `ignore` if the child process for some reason cannot be started, in which case the child specification will be kept by the supervisor but the non-existing child process will be ignored.

If something goes wrong, the function may also return an error tuple `{error,Error}`.

Note that the `start_link` functions of the different behaviour modules fulfill the above requirements.

- `Restart` defines when a terminated child process should be restarted. A `permanent` child process should always be restarted, a `temporary` child process should never be restarted and a `transient` child process should be restarted only if it terminates abnormally, i.e. with another exit reason than `normal`.
- `Shutdown` defines how a child process should be terminated. `brutal_kill` means the child process will be unconditionally terminated using `exit(Child,kill)`. An integer timeout value means that the supervisor will tell the child process to terminate by calling `exit(Child,shutdown)` and then wait for an exit signal with reason `shutdown` back from the child process. If no exit signal is received within the specified time, the child process is unconditionally terminated using `exit(Child,kill)`.

If the child process is another supervisor, `Shutdown` should be set to `infinity` to give the subtree ample time to shutdown.

*Important note on simple-one-for-one supervisors:* The dynamically created child processes of a simple-one-for-one supervisor are not explicitly killed, regardless of

shutdown strategy, but are expected to terminate when the supervisor does (that is, when an exit signal from the parent process is received).

Note that all child processes implemented using the standard OTP behavior modules automatically adhere to the shutdown protocol.

- `Type` specifies if the child process is a supervisor or a worker.
- `Modules` is used by the release handler during code replacement to determine which processes are using a certain module. As a rule of thumb `Modules` should be a list with one element `[Module]`, where `Module` is the callback module, if the child process is a supervisor, `gen_server` or `gen_fsm`. If the child process is an event manager (`gen_event`) with a dynamic set of callback modules, `Modules` should be `dynamic`. See *OTP Design Principles* for more information about release handling.
- Internally, the supervisor also keeps track of the pid `Child` of the child process, or undefined if no pid exists.

## Exports

```
start_link(Module, Args) -> Result
```

```
start_link(SupName, Module, Args) -> Result
```

Types:

- `SupName` = `{local,Name}` | `{global,Name}`
- `Name` = `atom()`
- `Module` = `atom()`
- `Args` = `term()`
- `Result` = `{ok,Pid}` | `ignore` | `{error,Error}`
- `Pid` = `pid()`
- `Error` = `{already_started,Pid}` | `shutdown` | `term()`

Creates a supervisor process as part of a supervision tree. The function will, among other things, ensure that the supervisor is linked to the calling process (its supervisor).

The created supervisor process calls `Module:init/1` to find out about restart strategy, maximum restart frequency and child processes. To ensure a synchronized start-up procedure, `start_link/2,3` does not return until `Module:init/1` has returned and all child processes have been started.

If `SupName={local,Name}` the supervisor is registered locally as `Name` using `register/2`. If `SupName={global,Name}` the supervisor is registered globally as `Name` using `global:register_name/2`. If no name is provided, the supervisor is not registered.

`Module` is the name of the callback module.

`Args` is an arbitrary term which is passed as the argument to `Module:init/1`.

If the supervisor and its child processes are successfully created (i.e. if all child process start functions return `{ok,Child}`, `{ok,Child,Info}`, or `ignore`) the function returns `{ok,Pid}`, where `Pid` is the pid of the supervisor. If there already exists a process with the specified `SupName` the function returns `{error,{already_started,Pid}}`, where `Pid` is the pid of that process.

If `Module:init/1` returns `ignore`, this function returns `ignore` as well and the supervisor terminates with reason `normal`. If `Module:init/1` fails or returns an

incorrect value, this function returns `{error, Term}` where `Term` is a term with information about the error, and the supervisor terminates with reason `Term`.

If any child process start function fails or returns an error tuple or an erroneous value, the function returns `{error, shutdown}` and the supervisor terminates all started child processes and then itself with reason `shutdown`.

`start_child(SupRef, ChildSpec) -> Result`

Types:

- `SupRef = Name | {Name, Node} | {global, Name} | pid()`
- `Name = Node = atom()`
- `ChildSpec = child_spec() | [term()]`
- `Result = {ok, Child} | {ok, Child, Info} | {error, Error}`
- `Child = pid() | undefined`
- `Info = term()`
- `Error = already_present | {already_started, Child} | term()`

Dynamically adds a child specification to the supervisor `SupRef` which starts the corresponding child process.

`SupRef` can be:

- the `pid`,
- `Name`, if the supervisor is locally registered,
- `{Name, Node}`, if the supervisor is locally registered at another node, or
- `{global, Name}`, if the supervisor is globally registered.

`ChildSpec` should be a valid child specification (unless the supervisor is a `simple_one_for_one` supervisor, see below). The child process will be started by using the start function as defined in the child specification.

If the case of a `simple_one_for_one` supervisor, the child specification defined in `Module:init/1` will be used and `ChildSpec` should instead be an arbitrary list of terms `List`. The child process will then be started by appending `List` to the existing start function arguments, i.e. by calling `apply(M, F, A++List)` where `{M, F, A}` is the start function defined in the child specification.

If there already exists a child specification with the specified `Id`, `ChildSpec` is discarded and the function returns `{error, already_present}` or `{error, {already_started, Child}}`, depending on if the corresponding child process is running or not.

If the child process start function returns `{ok, Child}` or `{ok, Child, Info}`, the child specification and `pid` is added to the supervisor and the function returns the same value.

If the child process start function returns `ignore`, the child specification is added to the supervisor, the `pid` is set to `undefined` and the function returns `{ok, undefined}`.

If the child process start function returns an error tuple or an erroneous value, or if it fails, the child specification is discarded and the function returns `{error, Error}` where `Error` is a term containing information about the error and child specification.

`terminate_child(SupRef, Id) -> Result`

Types:

- `SupRef = Name | {Name, Node} | {global, Name} | pid()`

- Name = Node = atom()
- Id = term()
- Result = ok | {error,Error}
- Error = not\_found | simple\_one\_for\_one

Tells the supervisor SupRef to terminate the child process corresponding to the child specification identified by Id. The process, if there is one, is terminated but the child specification is kept by the supervisor. This means that the child process may be later be restarted by the supervisor. The child process can also be restarted explicitly by calling `restart_child/2`. Use `delete_child/2` to remove the child specification.

See `start_child/2` for a description of SupRef.

If successful, the function returns `ok`. If there is no child specification with the specified Id, the function returns `{error,not_found}`.

`delete_child(SupRef, Id) -> Result`

Types:

- SupRef = Name | {Name,Node} | {global,Name} | pid()
- Name = Node = atom()
- Id = term()
- Result = ok | {error,Error}
- Error = running | not\_found | simple\_one\_for\_one

Tells the supervisor SupRef to delete the child specification identified by Id. The corresponding child process must not be running, use `terminate_child/2` to terminate it.

See `start_child/2` for a description of SupRef.

If successful, the function returns `ok`. If the child specification identified by Id exists but the corresponding child process is running, the function returns `{error,running}`. If the child specification identified by Id does not exist, the function returns `{error,not_found}`.

`restart_child(SupRef, Id) -> Result`

Types:

- SupRef = Name | {Name,Node} | {global,Name} | pid()
- Name = Node = atom()
- Id = term()
- Result = {ok,Child} | {ok,Child,Info} | {error,Error}
- Child = pid() | undefined
- Error = running | not\_found | simple\_one\_for\_one | term()

Tells the supervisor SupRef to restart a child process corresponding to the child specification identified by Id. The child specification must exist and the corresponding child process must not be running.

See `start_child/2` for a description of SupRef.

If the child specification identified by Id does not exist, the function returns `{error,not_found}`. If the child specification exists but the corresponding process is already running, the function returns `{error,running}`.

If the child process start function returns `{ok,Child}` or `{ok,Child,Info}`, the pid is added to the supervisor and the function returns the same value.

If the child process start function returns `ignore`, the `pid` remains set to `undefined` and the function returns `{ok,undefined}`.

If the child process start function returns an error tuple or an erroneous value, or if it fails, the function returns `{error,Error}` where `Error` is a term containing information about the error.

`which_children(SupRef) -> [{Id,Child,Type,Modules}]`

Types:

- `SupRef` = `Name` | `{Name,Node}` | `{global,Name}` | `pid()`
- `Name` = `Node` = `atom()`
- `Id` = `term()` | `undefined`
- `Child` = `pid()` | `undefined`
- `Type` = `worker` | `supervisor`
- `Modules` = `[Module]` | `dynamic`
- `Module` = `atom()`

Returns a list with information about all child specifications and child processes belonging to the supervisor `SupRef`.

See `start_child/2` for a description of `SupRef`.

The information given for each child specification/process is:

- `Id` - as defined in the child specification or `undefined` in the case of a `simple_one_for_one` supervisor.
- `Child` - the `pid` of the corresponding child process, or `undefined` if there is no such process.
- `Type` - as defined in the child specification.
- `Modules` - as defined in the child specification.

`check_childspecs([ChildSpec]) -> Result`

Types:

- `ChildSpec` = `child_spec()`
- `Result` = `ok` | `{error,Error}`
- `Error` = `term()`

This function takes a list of child specification as argument and returns `ok` if all of them are syntactically correct, or `{error,Error}` otherwise.

## CALLBACK FUNCTIONS

The following functions should be exported from a `supervisor` callback module.

## Exports

Module: `init(Args) -> Result`

Types:

- `Args = term()`
- `Result = {ok, {{RestartStrategy, MaxR, MaxT}, [ChildSpec]}} | ignore`
- `RestartStrategy = one_for_all | one_for_one | rest_for_one | simple_one_for_one`
- `MaxR = MaxT = int() >= 0`
- `ChildSpec = child_spec()`

Whenever a supervisor is started using `supervisor:start_link/2,3`, this function is called by the new process to find out about restart strategy, maximum restart frequency and child specifications.

`Args` is the `Args` argument provided to the start function.

`RestartStrategy` is the restart strategy and `MaxR` and `MaxT` defines the maximum restart frequency of the supervisor. `[ChildSpec]` is a list of valid child specifications defining which child processes the supervisor should start and monitor. See the discussion about Supervision Principles above.

Note that when the restart strategy is `simple_one_for_one`, the list of child specifications must be a list with one child specification only. (The `Id` is ignored). No child process is then started during the initialization phase, but all children are assumed to be started dynamically using `supervisor:start_child/2`.

The function may also return `ignore`.

## SEE ALSO

`gen_event(3)` [page 175], `gen_fsm(3)` [page 185], `gen_server(3)` [page 196], `sys(3)` [page 357]

# supervisor\_bridge

Erlang Module

A behaviour module for implementing a `supervisor_bridge`, a process which connects a subsystem not designed according to the OTP design principles to a supervision tree. The `supervisor_bridge` sits between a supervisor and the subsystem. It behaves like a real supervisor to its own supervisor, but has a different interface than a real supervisor to the subsystem. Refer to *OTP Design Principles* for more information.

A `supervisor_bridge` assumes the functions for starting and stopping the subsystem to be located in a callback module exporting a pre-defined set of functions.

The `sys` module can be used for debugging a `supervisor_bridge`.

Unless otherwise stated, all functions in this module will fail if the specified `supervisor_bridge` does not exist or if bad arguments are given.

## Exports

```
start_link(Module, Args) -> Result  
start_link(SupBridgeName, Module, Args) -> Result
```

Types:

- `SupBridgeName` = `{local,Name}` | `{global,Name}`
- `Name` = `atom()`
- `Module` = `atom()`
- `Args` = `term()`
- `Result` = `{ok,Pid}` | `ignore` | `{error,Error}`
- `Pid` = `pid()`
- `Error` = `{already_started,Pid}` | `term()`

Creates a `supervisor_bridge` process, linked to the calling process, which calls `Module:init/1` to start the subsystem. To ensure a synchronized start-up procedure, this function does not return until `Module:init/1` has returned.

If `SupBridgeName={local,Name}` the `supervisor_bridge` is registered locally as `Name` using `register/2`. If `SupBridgeName={global,Name}` the `supervisor_bridge` is registered globally as `Name` using `global:register_name/2`. If no name is provided, the `supervisor_bridge` is not registered. If there already exists a process with the specified `SupBridgeName` the function returns `{error,{already_started,Pid}}`, where `Pid` is the pid of that process.

`Module` is the name of the callback module.

`Args` is an arbitrary term which is passed as the argument to `Module:init/1`.

If the `supervisor_bridge` and the subsystem are successfully started the function returns `{ok,Pid}`, where `Pid` is the pid of the `supervisor_bridge`.

If `Module:init/1` returns `ignore`, this function returns `ignore` as well and the `supervisor_bridge` terminates with reason `normal`. If `Module:init/1` fails or returns an error tuple or an incorrect value, this function returns `{error, Term}` where `Term` is a term with information about the error, and the `supervisor_bridge` terminates with reason `Term`.

## CALLBACK FUNCTIONS

The following functions should be exported from a `supervisor_bridge` callback module.

### Exports

`Module:init(Args) -> Result`

Types:

- `Args = term()`
- `Result = {ok, Pid, State} | ignore | {error, Error}`
- `Pid = pid()`
- `State = term()`
- `Error = term()`

Whenever a `supervisor_bridge` is started using `supervisor_bridge:start_link/2,3`, this function is called by the new process to start the subsystem and initialize.

`Args` is the `Args` argument provided to the start function.

The function should return `{ok, Pid, State}` where `Pid` is the pid of the main process in the subsystem and `State` is any term.

If later `Pid` terminates with a reason `Reason`, the supervisor bridge will terminate with reason `Reason` as well. If later the `supervisor_bridge` is stopped by its supervisor with reason `Reason`, it will call `Module:terminate(Reason, State)` to terminate.

If something goes wrong during the initialization the function should return `{error, Error}` where `Error` is any term, or `ignore`.

`Module:terminate(Reason, State)`

Types:

- `Reason = shutdown | term()`
- `State = term()`

This function is called by the `supervisor_bridge` when it is about to terminate. It should be the opposite of `Module:init/1` and stop the subsystem and do any necessary cleaning up. The return value is ignored.

`Reason` is `shutdown` if the `supervisor_bridge` is terminated by its supervisor. If the `supervisor_bridge` terminates because a linked process (apart from the main process of the subsystem) has terminated with reason `Term`, `Reason` will be `Term`.

`State` is taken from the return value of `Module:init/1`.

**SEE ALSO**

supervisor(3) [page 347], sys(3) [page 357]

# sys

## Erlang Module

This module contains functions for sending system messages used by programs, and messages used for debugging purposes.

Functions used for implementation of processes should also understand system messages such as debugging messages and code change. These functions must be used to implement the use of system messages for a process; either directly, or through standard behaviours, such as `gen_server`.

The following types are used in the functions defined below:

- `Name = pid() | atom() | {global, atom()}`
- `Timeout = int() >= 0 | infinity`
- `system_event() = {in, Msg} | {in, Msg, From} | {out, Msg, To} | term()`

The default timeout is 5000 ms, unless otherwise specified. The `timeout` defines the time period to wait for the process to respond to a request. If the process does not respond, the function evaluates `exit({timeout, {M, F, A}})`.

The functions make reference to a debug structure. The debug structure is a list of `dbg_opt()`. `dbg_opt()` is an internal data type used by the `handle_system_msg/6` function. No debugging is performed if it is an empty list.

## System Messages

Processes which are not implemented as one of the standard behaviours must still understand system messages. There are three different messages which must be understood:

- Plain system messages. These are received as `{system, From, Msg}`. The content and meaning of this message are not interpreted by the receiving process module. When a system message has been received, the function `sys:handle_system_msg/6` is called in order to handle the request.
- Shutdown messages. If the process traps exits, it must be able to handle an shut-down request from its parent, the supervisor. The message `{'EXIT', Parent, Reason}` from the parent is an order to terminate. The process must terminate when this message is received, normally with the same `Reason` as `Parent`.

- There is one more message which the process must understand if the modules used to implement the process change dynamically during runtime. An example of such a process is the `gen_event` processes. This message is `{get_modules, From}`. The reply to this message is `From ! {modules, Modules}`, where `Modules` is a list of the currently active modules in the process.

This message is used by the release handler to find which processes execute a certain module. The process may at a later time be suspended and ordered to perform a code change for one of its modules.

## System Events

When debugging a process with the functions of this module, the process generates *system\_events* which are then treated in the debug function. For example, `trace` formats the system events to the `tty`.

There are three predefined system events which are used when a process receives or sends a message. The process can also define its own system events. It is always up to the process itself to format these events.

## Exports

```
log(Name,Flag)
```

```
log(Name,Flag,Timeout) -> ok | {ok, [system_event()]}
```

Types:

- `Flag = true | {true, N} | false | get | print`
- `N = integer() > 0`

Turns the logging of system events On or Off. If On, a maximum of `N` events are kept in the debug structure (the default is 10). If `Flag` is `get`, a list of all logged events is returned. If `Flag` is `print`, the logged events are printed to `standard_io`. The events are formatted with a function that is defined by the process that generated the event (with a call to `sys:handle_debug/4`).

```
log_to_file(Name,Flag)
```

```
log_to_file(Name,Flag,Timeout) -> ok | {error, open_file}
```

Types:

- `Flag = FileName | false`
- `FileName = string()`

Enables or disables the logging of all system events in textual format to the file. The events are formatted with a function that is defined by the process that generated the event (with a call to `sys:handle_debug/4`).

```
statistics(Name,Flag)
```

```
statistics(Name,Flag,Timeout) -> ok | {ok, Statistics}
```

Types:

- `Flag = true | false | get`

- Statistics = [{start\_time, {Date1, Time1}}, {current\_time, {Date, Time2}}, {reductions, integer()}, {messages\_in, integer()}, {messages\_out, integer()}]
- Date1 = Date2 = {Year, Month, Day}
- Time1 = Time2 = {Hour, Min, Sec}

Enables or disables the collection of statistics. If Flag is get, the statistical collection is returned.

trace(Name, Flag)

trace(Name, Flag, Timeout) -> void()

Types:

- Flag = boolean()

Prints all system events on standard\_io. The events are formatted with a function that is defined by the process that generated the event (with a call to sys:handle\_debug/4).

no\_debug(Name)

no\_debug(Name, Timeout) -> void()

Turns off all debugging for the process. This includes functions that have been installed explicitly with the install function, for example triggers.

suspend(Name)

suspend(Name, Timeout) -> void()

Suspends the process. When the process is suspended, it will only respond to other system messages, but not other messages.

resume(Name)

resume(Name, Timeout) -> void()

Resumes a suspended process.

change\_code(Name, Module, OldVsn, Extra)

change\_code(Name, Module, OldVsn, Extra, Timeout) -> ok | {error, Reason}

Types:

- OldVsn = undefined | term()
- Module = atom()
- Extra = term()

Tells the process to change code. The process must be suspended to handle this message. The Extra argument is reserved for each process to use as its own. The function Mod:system\_code\_change/4 is called. OldVsn is the old version of the Module.

get\_status(Name)

get\_status(Name, Timeout) -> {status, Pid, {module, Mod}, [PDict, SysState, Parent, Dbg, Misc]}

Types:

- PDict = [{Key, Value}]
- SysState = running | suspended
- Parent = pid()

- Dbg = [dbg\_opt()]
- Misc = term()

Gets the status of the process.

```
install(Name, {Func, FuncState})
```

```
install(Name, {Func, FuncState}, Timeout)
```

Types:

- Func = dbg\_fun()
- dbg\_fun() = fun(FuncState, Event, ProcState) -> done | NewFuncState
- FuncState = term()
- Event = system\_event()
- ProcState = term()
- NewFuncState = term()

This function makes it possible to install other debug functions than the ones defined above. An example of such a function is a trigger, a function that waits for some special event and performs some action when the event is generated. This could, for example, be turning on low level tracing.

Func is called whenever a system event is generated. This function should return done, or a new func state. In the first case, the function is removed. It is removed if the function fails.

```
remove(Name, Func)
```

```
remove(Name, Func, Timeout) -> void()
```

Types:

- Func = dbg\_fun()

Removes a previously installed debug function from the process. Func must be the same as previously installed.

## Process Implementation Functions

The following functions are used when implementing a special process. This is an ordinary process which does not use a standard behaviour, but a process which understands the standard system messages.

## Exports

`debug_options(Options) -> [dbg_opt()]`

Types:

- Options = [Opt]
- Opt = trace | log | statistics | {log\_to\_file, FileName} | {install, {Func, FuncState}}
- Func = dbg\_fun()
- FuncState = term()

This function can be used by a process that initiates a debug structure from a list of options. The values of the `Opt` argument are the same as the corresponding functions.

`get_debug(Item, Debug, Default) -> term()`

Types:

- Item = log | statistics
- Debug = [dbg\_opt()]
- Default = term()

This function gets the data associated with a debug option. `Default` is returned if the `Item` is not found. Can be used by the process to retrieve debug data for printing before it terminates.

`handle_debug([dbg_opt()], FormFunc, Extra, Event) -> [dbg_opt()]`

Types:

- FormFunc = dbg\_fun()
- Extra = term()
- Event = system\_event()

This function is called by a process when it generates a system event. `FormFunc` is a formatting function which is called as `FormFunc(Device, Event, Extra)` in order to print the events, which is necessary if tracing is activated. `Extra` is any extra information which the process needs in the format function, for example the name of the process.

`handle_system_msg(Msg, From, Parent, Module, Debug, Misc)`

Types:

- Msg = term()
- From = pid()
- Parent = pid()
- Module = atom()
- Debug = [dbg\_opt()]
- Misc = term()

This function is used by a process module that wishes to take care of system messages. The process receives a `{system, From, Msg}` message and passes the `Msg` and `From` to this function.

This function *never* returns. It calls the function `Module:system_continue(Parent, NDebug, Misc)` where the process continues the execution, or `Module:system_terminate(Reason, Parent, Debug, Misc)` if the process should terminate. The `Module` must export `system_continue/3`, `system_terminate/4`, and `system_code_change/4` (see below).

The `Misc` argument can be used to save internal data in a process, for example its state. It is sent to `Module:system_continue/3` or `Module:system_terminate/4`.

```
print_log(Debug) -> void()
```

Types:

- `Debug = [dbg_opt()]`

Prints the logged system events in the debug structure using `FormFunc` as defined when the event was generated by a call to `handle_debug/4`.

```
Mod:system_continue(Parent, Debug, Misc)
```

Types:

- `Parent = pid()`
- `Debug = [dbg_opt()]`
- `Misc = term()`

This function is called from `sys:handle_system_msg/6` when the process should continue its execution (for example after it has been suspended). This function never returns.

```
Mod:system_terminate(Reason, Parent, Debug, Misc)
```

Types:

- `Reason = term()`
- `Parent = pid()`
- `Debug = [dbg_opt()]`
- `Misc = term()`

This function is called from `sys:handle_system_msg/6` when the process should terminate. For example, this function is called when the process is suspended and its parent orders shut-down. It gives the process a chance to do a clean-up. This function never returns.

```
Mod:system_code_change(Misc, Module, OldVsn, Extra) -> {ok, NMisc}
```

Types:

- `Misc = term()`
- `OldVsn = undefined | term()`
- `Module = atom()`
- `Extra = term()`
- `NMisc = term()`

Called from `sys:handle_system_msg/6` when the process should perform a code change. The code change is used when the internal data structure has changed. This function converts the `Misc` argument to the new data structure. `OldVsn` is the `vsn` attribute of the old version of the `Module`. If no such attribute was defined, the atom `undefined` is sent.

# timer

Erlang Module

This module provides useful functions related to time. Unless otherwise stated, time is always measured in `milliseconds`. All timer functions return immediately, regardless of work carried out by another process.

Successful evaluations of the timer functions yield return values containing a timer reference, denoted `TRef` below. By using `cancel/1`, the returned reference can be used to cancel any requested action. A `TRef` is an Erlang term, the contents of which must not be altered.

The timeouts are not exact, but should be at least as long as requested.

## Exports

`start()` -> `ok`

Starts the timer server. Normally, the server does not need to be started explicitly. It is started dynamically if it is needed. This is useful during development, but in a target system the server should be started explicitly. Use configuration parameters for `kernel` for this.

`apply_after(Time, Module, Function, Arguments)` -> `{ok, TRef}` | `{error, Reason}`

Types:

- `Time = integer()` in Milliseconds
- `Module = Function = atom()`
- `Arguments = [term()]`

Evaluates `apply(M, F, A)` after `Time` amount of time has elapsed. Returns `{ok, TRef}`, or `{error, Reason}`.

`send_after(Time, Pid, Message)` -> `{ok, TRef}` | `{error, Reason}`

`send_after(Time, Message)` -> `{ok, TRef}` | `{error, Reason}`

Types:

- `Time = integer()` in Milliseconds
- `Pid = pid() | atom()`
- `Message = term()`
- `Result = {ok, TRef} | {error, Reason}`

`send_after/3` Evaluates `Pid ! Message` after `Time` amount of time has elapsed. (`Pid` can also be an atom of a registered name.) Returns `{ok, TRef}`, or `{error, Reason}`.

`send_after/2` Same as `send_after(Time, self(), Message)`.

`exit_after(Time, Pid, Reason1) -> {ok, TRef} | {error, Reason2}`

`exit_after(Time, Reason1) -> {ok, TRef} | {error, Reason2}`

`kill_after(Time, Pid) -> {ok, TRef} | {error, Reason2}`

`kill_after(Time) -> {ok, TRef} | {error, Reason2}`

Types:

- `Time = integer()` in milliseconds
- `Pid = pid() | atom()`
- `Reason1 = Reason2 = term()`

`exit_after/3` Send an exit signal with reason `Reason1` to `Pid`. Returns `{ok, TRef}`, or `{error, Reason2}`.

`exit_after/2` Same as `exit_after(Time, self(), Reason1)`.

`kill_after/2` Same as `exit_after(Time, Pid, kill)`.

`kill_after/1` Same as `exit_after(Time, self(), kill)`.

`apply_interval(Time, Module, Function, Arguments) -> {ok, TRef} | {error, Reason}`

Types:

- `Time = integer()` in milliseconds
- `Module = Function = atom()`
- `Arguments = [term()]`

Evaluates `apply(Module, Function, Arguments)` repeatedly at intervals of `Time`. Returns `{ok, TRef}`, or `{error, Reason}`.

`send_interval(Time, Pid, Message) -> {ok, TRef} | {error, Reason}`

`send_interval(Time, Message) -> {ok, TRef} | {error, Reason}`

Types:

- `Time = integer()` in milliseconds
- `Pid = pid() | atom()`
- `Message = term()`
- `Reason = term()`

`send_interval/3` Evaluates `Pid ! Message` repeatedly after `Time` amount of time has elapsed. (`Pid` can also be an atom of a registered name.) Returns `{ok, TRef}` or `{error, Reason}`.

`send_interval/2` Same as `send_interval(Time, self(), Message)`.

`cancel(TRef) -> {ok, cancel} | {error, Reason}`

Cancels a previously requested timeout. `TRef` is a unique timer reference returned by the timer function in question. Returns `{ok, cancel}`, or `{error, Reason}` when `TRef` is not a timer reference.

`sleep(Time) -> ok`

Types:

- Time = integer() in milliseconds

Suspends the process calling this function for Time amount of milliseconds and then returns ok. Naturally, this function does *not* return immediately.

tc(Module, Function, Arguments) -> {Time, Value}

Types:

- Module = Function = atom()
- Arguments = [term()]
- Time = integer() in microseconds
- Value = term()

Evaluates apply(Module, Function, Arguments) and measures the elapsed real time. Returns {Time, Value}, where Time is the elapsed real time in *microseconds*, and Value is what is returned from the apply.

now\_diff(T2, T1) -> Tdiff

Types:

- T1 = T2 = {MegaSecs, Secs, MicroSecs}
- Tdiff = MegaSecs = Secs = MicroSecs = integer()

Calculates the time difference Tdiff = T2 - T1 in *microseconds*, where T1 and T2 probably are timestamp tuples returned from erlang:now/0.

seconds(Seconds) -> Milliseconds

Returns the number of milliseconds in Seconds.

minutes(Minutes) -> Milliseconds

Return the number of milliseconds in Minutes.

hours(Hours) -> Milliseconds

Returns the number of milliseconds in Hours.

hms(Hours, Minutes, Seconds) -> Milliseconds

Returns the number of milliseconds in Hours + Minutes + Seconds.

## Examples

This example illustrates how to print out “Hello World!” in 5 seconds:

```
1> timer:apply_after(5000, io, format, ["~nHello World!~n", []]).
{ok, TRef}
Hello World!
2>
```

The following coding example illustrates a process which performs a certain action and if this action is not completed within a certain limit, then the process is killed.

```
Pid = spawn(mod, fun, [foo, bar]),
%% If pid is not finished in 10 seconds, kill him
{ok, R} = timer:kill_after(timer:seconds(10), Pid),
...
%% We change our mind...
timer:cancel(R),
...
```

## WARNING

A timer can always be removed by calling `cancel/1`.

An interval timer, i.e. a timer created by evaluating any of the functions `apply_interval/4`, `send_interval/3`, and `send_interval/2`, is linked to the process towards which the timer performs its task.

A one-shot timer, i.e. a timer created by evaluating any of the functions `apply_after/4`, `send_after/3`, `send_after/2`, `exit_after/3`, `exit_after/2`, `kill_after/2`, and `kill_after/1` is not linked to any process. Hence, such a timer is removed only when it reaches its timeout, or if it is explicitly removed by a call to `cancel/1`.

# win32reg

Erlang Module

`win32reg` provides read and write access to the registry on Windows. It is essentially a port driver wrapped around the Win32 API calls for accessing the registry.

The registry is a hierarchical database, used to store various system and software information in Windows. It is available in Windows 95 and Windows NT. It contains installation data, and is updated by installers and system programs. The Erlang installer updates the registry by adding data that Erlang needs.

The registry contains keys and values. Keys are like the directories in a file system, they form a hierarchy. Values are like files, they have a name and a value, and also a type.

Paths to keys are left to right, with sub-keys to the right and backslash between keys. (Remember that backslashes must be doubled in Erlang strings.) Case is preserved but not significant. Example:

"\\hkey\_local\_machine\\software\\Ericsson\\Erlang\\5.0" is the key for the installation data for the latest Erlang release.

There are six entry points in the Windows registry, top level keys. They can be abbreviated in the `win32reg` module as:

Abbrev.	Registry key
=====	=====
<code>hkcr</code>	<code>HKEY_CLASSES_ROOT</code>
<code>current_user</code>	<code>HKEY_CURRENT_USER</code>
<code>hkcu</code>	<code>HKEY_CURRENT_USER</code>
<code>local_machine</code>	<code>HKEY_LOCAL_MACHINE</code>
<code>hk1m</code>	<code>HKEY_LOCAL_MACHINE</code>
<code>users</code>	<code>HKEY_USERS</code>
<code>hku</code>	<code>HKEY_USERS</code>
<code>current_config</code>	<code>HKEY_CURRENT_CONFIG</code>
<code>hkcc</code>	<code>HKEY_CURRENT_CONFIG</code>
<code>dyn_data</code>	<code>HKEY_DYN_DATA</code>
<code>hkdd</code>	<code>HKEY_DYN_DATA</code>

The key above could be written as "\\hk1m\\software\\ericsson\\erlang\\5.0".

The `win32reg` module uses a current key. It works much like the current directory. From the current key, values can be fetched, sub-keys can be listed, and so on.

Under a key, any number of named values can be stored. They have name, and types, and data.

Currently, the `win32reg` module supports storing only the following types: `REG_DWORD`, which is an integer, `REG_SZ` which is a string and `REG_BINARY` which is a binary. Other types can be read, and will be returned as binaries.

There is also a "default" value, which has the empty string as name. It is read and written with the atom `default` instead of the name.

Some registry values are stored as strings with references to environment variables, e.g. "%SystemRoot%Windows". `SystemRoot` is an environment variable, and should be replaced with its value. A function `expand/1` is provided, so that environment variables surrounded in % can be expanded to their values.

For additional information on the Windows registry consult the Win32 Programmer's Reference.

## Exports

`change_key(RegHandle, Key) -> ReturnValue`

Types:

- `RegHandle = term()`
- `Key = string()`

Changes the current key to another key. Works like `cd`. The key can be specified as a relative path or as an absolute path, starting with `\`.

`change_key_create(RegHandle, Key) -> ReturnValue`

Types:

- `RegHandle = term()`
- `Key = string()`

Creates a key, or just changes to it, if it is already there. Works like a combination of `mkdir` and `cd`. Calls the Win32 API function `RegCreateKeyEx()`.

The registry must have been opened in write-mode.

`close(RegHandle)-> ReturnValue`

Types:

- `RegHandle = term()`

Closes the registry. After that, the `RegHandle` cannot be used.

`current_key(RegHandle) -> ReturnValue`

Types:

- `RegHandle = term()`
- `ReturnValue = {ok, string() }`

Returns the path to the current key. This is the equivalent of `pwd`.

Note that the current key is stored in the driver, and might be invalid (e.g. if the key has been removed).

`delete_key(RegHandle) -> ReturnValue`

Types:

- `RegHandle = term()`
- `ReturnValue = ok | {error, ErrorId}`

Deletes the current key, if it is valid. Calls the Win32 API function `RegDeleteKey()`. Note that this call does not change the current key, (unlike `change_key_create/2`.) This means that after the call, the current key is invalid.

`delete_value(RegHandle, Name) -> ReturnValue`

Types:

- `RegHandle` = `term()`
- `ReturnValue` = `ok` | `{error, ErrorId}`

Deletes a named value on the current key. The atom `default` is used for the the default value.

The registry must have been opened in write-mode.

`expand(String) -> ExpandedString`

Types:

- `String` = `string()`
- `ExpandedString` = `string()`

Expands a string containing environment variables between percent characters. Anything between two % is taken for a environment variable, and is replaced by the value. Two consecutive % is replaced by one %.

A variable name that is not in the environment, will result in an error.

`format_error(ErrorId) -> ErrorString`

Types:

- `ErrorId` = `atom()`
- `ErrorString` = `string()`

Convert an POSIX errorcode to a string (by calling `erl_posix_msg:message`).

`open(OpenModeList)-> ReturnValue`

Types:

- `OpenModeList` = `[OpenMode]`
- `OpenMode` = `read` | `write`

Opens the registry for reading or writing. The current key will be the root (`HKEY_CLASSES_ROOT`). The `read` flag in the mode list can be omitted.

Use `change_key/2` with an absolute path after `open`.

`set_value(RegHandle, Name, Value) -> ReturnValue`

Types:

- `Name` = `string()` | `default`
- `Value` = `string()` | `integer()` | `binary()`

Sets the named (or default) value to value. Calls the Win32 API function `RegSetValueEx()`. The value can be of three types, and the corresponding registry type will be used. Currently the types supported are: `REG_DWORD` for integers, `REG_SZ` for strings and `REG_BINARY` for binaries. Other types cannot currently be added or changed. The registry must have been opened in write-mode.

`sub_keys(RegHandle) -> ReturnValue`

Types:

- `ReturnValue = {ok, SubKeys} | {error, ErrorId}`
- `SubKeys = [SubKey]`
- `SubKey = string()`

Returns a list of subkeys to the current key. Calls the Win32 API function `EnumRegKeysEx()`.

Avoid calling this on the root keys, it can be slow.

`value(RegHandle, Name) -> ReturnValue`

Types:

- `Name = string() | default`
- `ReturnValue = {ok, Value}`
- `Value = string() | integer() | binary()`

Retrieves the named value (or default) on the current key. Registry values of type `REG_SZ`, are returned as strings. Type `REG_DWORD` values are returned as integers. All other types are returned as binaries.

`values(RegHandle) -> ReturnValue`

Types:

- `ReturnValue = {ok, ValuePairs}`
- `ValuePairs = [ValuePair]`
- `ValuePair = {Name, Value}`
- `Name = string | default`
- `Value = string() | integer() | binary()`

Retrieves a list of all values on the current key. The values have types corresponding to the registry types, see `value`. Calls the Win32 API function `EnumRegValuesEx()`.

## SEE ALSO

Win32 Programmer's Reference (from Microsoft)

`erl_posix_msg`

The Windows 95 Registry (book from O'Reilly)

# zip

Erlang Module

The `zip` module archives and extract files to and from a zip archive. The zip format is specified by the “ZIP Appnote.txt” file available on PKWare’s website [www.pkware.com](http://www.pkware.com).

The `zip` module supports zip archive versions up to 6.1. However, password-protection and Zip64 is not supported.

By convention, the name of a zip file should end in “.zip”. To abide to the convention, you’ll need to add “.zip” yourself to the name.

Zip archives are created with the `zip/2` [page 373] or the `zip/3` [page 373] function. (They are also available as `create`, to resemble the `erl_tar` module.)

To extract files from a zip archive, use the `unzip/1` [page 374] or the `unzip/2` [page 374] function. (They are also available as `extract`.)

To return a list of the files in a zip archive, use the `list_dir/1` [page 375] or the `list_dir/2` [page 375] function. (They are also available as `table`.)

To print a list of files to the Erlang shell, use either the `t/1` [page 375] or `tt/1` [page 375] function.

In some cases, it is desirable to open a zip archive, and to unzip files from it file by file, without having to reopen the archive. The functions `zip_open` [page 376], `zip_get` [page 376], `zip_list_dir` [page 376] and `zip_close` [page 376] do this.

## LIMITATIONS

Zip64 archives are not currently supported.

Password-protected and encrypted archives are not currently supported

Only the DEFLATE (zlib-compression) and the STORE (uncompressed data) zip methods are supported.

The size of the archive is limited to 2 G-byte (32 bits).

Comments for individual files is not supported when creating zip archives. The zip archive comment for the whole zip archive is supported.

There is currently no support for altering an existing zip archive. To add or remove a file from an archive, the whole archive must be recreated.

## DATA TYPES

`zip_file()`

The record `zip_file` contains the following fields.

`name = string()` the name of the file

`info = file_info()` file info as in `[file:read_file_info/1]`

`comment = string()` the comment for the file in the zip archive

`offset = integer()` the offset of the file in the zip archive (used internally)

`comp_size = integer()` the compressed size of the file (the uncompressed size is found in `info`)

`zip_comment`

The record `zip_comment` just contains the archive comment for a zip archive

`comment = string()` the comment for the zip archive

## Exports

`zip(Name, FileList) -> RetValue`

`zip(Name, FileList, Options) -> RetValue`

`create(Name, FileList) -> RetValue`

`create(Name, FileList, Options) -> RetValue`

Types:

- `Name = filename()`
- `FileList = [FileSpec]`
- `FileSpec = filename() | {filename(), binary()}`
- `Options = [Option]`
- `Option = memory | cooked | verbose | {comment, Comment} | {cwd, CWD}`
- `Comment = CWD = string()`
- `RetValue = {ok, Name} | {ok, {Name, binary}} | {error, Reason}`
- `Reason = term()`

The `zip` function creates a zip archive containing the files specified in `FileList`.

As synonyms, the functions `create/2` and `create/3` are provided, to make it resemble the `erl_tar` module.

The file-list is a list of files, with paths relative to the current directory, they will be stored with this path in the archive. Files may also be specified with data in binaries, to create an archive directly from data.

Files will be compressed using the DEFLATE compression, as described in the `Appnote.txt` file. However, files will be stored without compression if they already are compressed. The `zip/2` and `zip/3` checks the file extension to see whether the file should be stored without compression. Files with the following extensions are not compressed: `.Z`, `.zip`, `.zoo`, `.arc`, `.lzh`, `.arj`.

The following options are available:

`cooked` By default, the `open/2` function will open the zip file in raw mode, which is faster but does not allow a remote (erlang) file server to be used. Adding `cooked` to the mode list will override the default and open the zip file without the `raw` option. The same goes for the files added.

`verbose` Print an informational message about each file being added.

`memory` The output will not be to a file, but instead as a tuple `{FileName, binary()}`. The binary will be a full zip archive with header, and can be extracted with for instance `unzip/2`.

`{comment, Comment}` Add a comment to the zip-archive.

`{cwd, CWD}` Use the given directory as current directory, it will be prepended to file names when adding them, although it will not be in the zip-archive. (Acting like a `file:set_cwd/1`, but without changing the global `cwd` property.)

`unzip(Archive) -> RetValue`

`unzip(Archive, Options) -> RetValue`

`extract(Archive) -> RetValue`

`extract(Archive, Options) -> RetValue`

Types:

- `Name = filename() | binary()`
- `Options = [Option]`
- `Option = {files, FileList} | keep_old_files | verbose | memory | {file_filter, FileFilter} | {cwd, CWD}`
- `FileList = [filename()]`
- `FileFilter = fun(ZipFile) -> true | false`
- `CWD = string()`
- `ZipFile = zip_file()`
- `RetValue = ok | {error, Reason} | {error, {Name, Reason}}`
- `Reason = term()`

The `unzip/1` function extracts all files from a zip archive. The `unzip/2` function provides options to extract some files, and more.

If the `Archive` argument is given as a binary, the contents of the binary is assumed to be a zip archive, otherwise it should be a filename.

The following options are available:

`{files, FileList}` By default, all files will be extracted from the zip archive. With the `{files, Files}` option, the `unzip/2` function will only extract the files whose names are included in `FileList`.

`cooked` By default, the `open/2` function will open the zip file in raw mode, which is faster but does not allow a remote (erlang) file server to be used. Adding `cooked` to the mode list will override the default and open zip file without the `raw` option. The same goes for the files extracted.

`keep_old_files` By default, all existing files with the same name as file in the zip archive will be overwritten. With the `keep_old_files` option, the `unzip/2` function will not overwrite any existing files. Not that even with the `memory` option given, which means that no files will be overwritten, files existing will be excluded from the result.

`verbose` Print an informational message as each file is being extracted.

`memory` Instead of extracting to the current directory, the `memory` option will give the result as a list of tuples `{Filename, Binary}`, where `Binary` is a binary containing the extracted data of the file named `Filename` in the zip archive.

`{cwd, CWD}` Use the given directory as current directory, it will be prepended to file names when extracting them from the zip-archive. (Acting like a `file:set_cwd/1`, but without changing the global `cwd` property.)

`list_dir(Archive) -> RetValue`

`list_dir(Archive, Options)`

`table(Archive) -> RetValue`

`table(Archive, Options)`

Types:

- `Archive` = `filename()` | `binary()`
- `RetValue` = `{ok, [Comment, Files]}` | `{error, Reason}`
- `Comment` = `zip_comment()`
- `Files` = `[zip_file()]`
- `Options` = `[Option]`
- `Option` = `cooked`
- `Reason` = `term()`

The `list_dir/1` function retrieves the names of all files in the zip archive `Archive`. The `list_dir/2` function provides options.

As synonyms, the functions `table/2` and `table/3` are provided, to make it resemble the `erl_tar` module.

The result value is the tuple `{ok, List}`, where `List` contains the zip archive comment as the first element.

The following options are available:

`cooked` By default, the `open/2` function will open the zip file in raw mode, which is faster but does not allow a remote (erlang) file server to be used. Adding `cooked` to the mode list will override the default and open zip file without the raw option.

`t(Archive)`

Types:

- `Archive` = `filename()` | `binary()` | `ZipHandle`
- `ZipHandle` = `pid()`

The `t/1` function prints the names of all files in the zip archive `Archive` to the Erlang shell. (Similar to “`tar`”.)

`tt(Archive)`

Types:

- `Name` = `filename()` | `binary()`

The `tt/1` function prints names and information about all files in the zip archive `Archive` to the Erlang shell. (Similar to “`tar tv`”.)

`zip_open(Archive) -> {ok, ZipHandle} | {error, Reason}`

`zip_open(Archive, Options) -> {ok, ZipHandle} | {error, Reason}`

Types:

- Name = filename() | binary()
- Options = [Option]
- Options = cooked | memory | {cwd, CWD}
- CWD = string()
- ZipHandle = pid()

The `zip_open` function opens a zip archive, and reads and saves its directory. This means that subsequently reading files from the archive will be faster than unzipping files one at a time with `unzip`.

The archive must be closed with `zip_close/1`.

`zip_list_dir(ZipHandle) -> Result | {error, Reason}`

Types:

- Result = [ZipComment, ZipFile...]
- ZipComment = #zip\_comment{}
- ZipFile = #zip\_file{}
- ZipHandle = pid()

The `zip_list_dir/1` function returns the file list of an open zip archive.

`zip_get(ZipHandle) -> {ok, Result} | {error, Reason}`

`zip_get(FileName, ZipHandle) -> {ok, Result} | {error, Reason}`

Types:

- Name = filename() | binary() | ZipHandle
- ZipHandle = pid()

The `zip_get` function extracts one or all files from an open archive.

The files will be unzipped to memory or to file, depending on the options given to the `zip_open` function when the archive was opened.

`zip_close(ZipHandle) -> ok | {error, EINVAL}`

Types:

- ZipHandle = pid()

The `zip_close/1` function closes a zip archive, previously opened with `zip_open`. All resources are closed, and the handle should not be used after closing.

# Index of Modules and Functions

Modules are typed in *this* way.  
Functions are typed in *this* way.

a\_function/2  
    sofs, 322

abcast/2  
    gen\_server, 200

abcast/3  
    gen\_server, 200

absname/1  
    filename, 158

absname/2  
    filename, 159

absname\_join/2  
    filename, 159

abstract/1  
    erl\_parse, 116

acos/1  
    math, 238

acosh/1  
    math, 238

add/2  
    gb\_sets, 165

add/3  
    erl\_tar, 124

add/4  
    erl\_tar, 124

add\_binding/3  
    erl\_eval, 107

add\_edge/3  
    digraph, 93

add\_edge/4  
    digraph, 93

add\_edge/5  
    digraph, 93

add\_element/2  
    gb\_sets, 165  
    ordsets, 257  
    sets, 302

add\_handler/3  
    gen\_event, 176

add\_sup\_handler/3  
    gen\_event, 177

add\_vertex/1  
    digraph, 94

add\_vertex/2  
    digraph, 94

add\_vertex/3  
    digraph, 94

all/0  
    dets, 73  
    ets, 130

all/2  
    lists, 222

any/2  
    lists, 222

append/1  
    lists, 222  
    qlc, 280

append/2  
    lists, 222  
    qlc, 280

append/3  
    dict, 88  
    orddict, 251

append\_list/3  
    dict, 88  
    orddict, 251

append\_values/2  
    proplists, 268

apply\_after/4  
     *timer* , 364  
 apply\_interval/4  
     *timer* , 365  
 arith\_op/2  
     *erl\_internal* , 111  
 asin/1  
     *math* , 238  
 asinh/1  
     *math* , 238  
 atan/1  
     *math* , 238  
 atan2/2  
     *math* , 238  
 atanh/1  
     *math* , 238  
 attach/1  
     *pool* , 261  
 attribute/1  
     *erl\_pp* , 118  
 attribute/2  
     *erl\_pp* , 118  
 balance/1  
     *gb\_sets* , 165  
     *gb\_trees* , 170  
 base64  
     *decode*/1, 54  
     *decode\_to\_string*/1, 54  
     *encode*/1, 54  
     *encode\_to\_string*/1, 54  
     *mime\_decode*/1, 54  
     *mime\_decode\_string*/1, 54  
 basename/1  
     *filename* , 159  
 basename/2  
     *filename* , 159  
 bchunk/2  
     *dets* , 73  
 beam\_lib  
     *chunks*/2, 58  
     *chunks*/3, 58  
     *clear\_crypto\_key\_fun*/0, 62  
     *cmp*/2, 60  
     *cmp\_dirs*/2, 60  
     *crypto\_key\_fun*/1, 61  
     *diff\_dirs*/2, 60  
     *format\_error*/1, 61  
     *info*/1, 59  
     *md5*/1, 59  
     *strip*/1, 60  
     *strip\_files*/1, 60  
     *strip\_release*/1, 61  
     *version*/1, 58  
 bif/2  
     *erl\_internal* , 111  
 binding/2  
     *erl\_eval* , 107  
 bindings/1  
     *erl\_eval* , 107  
 bool\_op/2  
     *erl\_internal* , 111  
 bt/1  
     *c* , 63  
 c  
     *bt*/1, 63  
     *c*/1, 63  
     *c*/2, 63  
     *cd*/1, 63  
     *flush*/0, 64  
     *help*/0, 64  
     *i*/0, 64  
     *i*/3, 64  
     *l*/1, 64  
     *lc*/1, 64  
     *ls*/0, 64  
     *ls*/1, 64  
     *m*/0, 65  
     *m*/1, 65  
     *memory*/0, 65  
     *memory*/1, 65  
     *nc*/1, 65  
     *nc*/2, 65  
     *ni*/0, 64  
     *nl*/1, 65  
     *nregs*/0, 66  
     *pid*/3, 65  
     *pwd*/0, 66  
     *q*/0, 66  
     *regs*/0, 66  
     *xm*/1, 66  
     *y*/1, 66  
     *y*/2, 66  
 c/1  
     *c* , 63

- c/2
  - c , 63
- calendar
  - date\_to\_gregorian\_days/1, 68
  - date\_to\_gregorian\_days/3, 68
  - datetime\_to\_gregorian\_seconds/2, 68
  - day\_of\_the\_week/1, 68
  - day\_of\_the\_week/3, 68
  - gregorian\_days\_to\_date/1, 68
  - gregorian\_seconds\_to\_datetime/1, 68
  - is\_leap\_year/1, 68
  - last\_day\_of\_the\_month/2, 68
  - local\_time/0, 69
  - local\_time\_to\_universal\_time/2, 69
  - local\_time\_to\_universal\_time\_dst/2, 69
  - now\_to\_datetime/1, 70
  - now\_to\_local\_time/1, 69
  - now\_to\_universal\_time/1, 70
  - seconds\_to\_daystime/1, 70
  - seconds\_to\_time/1, 70
  - time\_difference/2, 70
  - time\_to\_seconds/1, 70
  - universal\_time/0, 70
  - universal\_time\_to\_local\_time/2, 71
  - valid\_date/1, 71
  - valid\_date/3, 71
- call/2
  - gen\_server , 198
- call/3
  - gen\_event , 178
  - gen\_server , 198
- call/4
  - gen\_event , 178
- cancel/1
  - timer , 365
- cancel\_timer/1
  - gen\_fsm , 190
- canonical\_relation/1
  - sofs , 322
- cast/2
  - gen\_server , 200
- cd/1
  - c , 63
- centre/2
  - string , 344
- centre/3
  - string , 344
- change\_code/4
  - sys , 359
- change\_code/5
  - sys , 359
- change\_key/2
  - win32reg , 369
- change\_key\_create/2
  - win32reg , 369
- char\_list/1
  - io\_lib , 219
- chars/2
  - string , 342
- chars/3
  - string , 342
- check/1
  - file\_sorter , 154
- check/2
  - file\_sorter , 154
- check\_childspecs/1
  - supervisor , 352
- chr/2
  - string , 341
- chunks/2
  - beam\_lib , 58
- chunks/3
  - beam\_lib , 58
- clear\_crypto\_key\_fun/0
  - beam\_lib , 62
- close/1
  - dets , 74
  - epp , 104
  - erl\_tar , 124
  - win32reg , 369
- cmp/2
  - beam\_lib , 60
- cmp\_dirs/2
  - beam\_lib , 60
- comp\_op/2
  - erl\_internal , 112
- compact/1
  - proplists , 268
- components/1
  - digraph\_utils , 101

composite/2  
     *sofs*, 322

concat/1  
     *lists*, 223

concat/2  
     *string*, 341

condensation/1  
     *digraph\_utils*, 101

cons/2  
     *queue*, 290

constant\_function/2  
     *sofs*, 322

converse/1  
     *sofs*, 323

copies/2  
     *string*, 343

cos/1  
     *math*, 238

cosh/1  
     *math*, 238

create/1  
     *pg*, 259

create/2  
     *erl\_tar*, 124  
     *pg*, 259  
     *zip*, 373

create/3  
     *erl\_tar*, 125  
     *zip*, 373

crypto\_key\_fun/1  
     *beam\_lib*, 61

cspan/2  
     *string*, 342

current\_key/1  
     *win32reg*, 369

cursor/2  
     *qlc*, 280

cyclic\_strong\_components/1  
     *digraph\_utils*, 101

daeh/1  
     *queue*, 290

date\_to\_gregorian\_days/1  
     *calendar*, 68

date\_to\_gregorian\_days/3  
     *calendar*, 68

datetime\_to\_gregorian\_seconds/2  
     *calendar*, 68

day\_of\_the\_week/1  
     *calendar*, 68

day\_of\_the\_week/3  
     *calendar*, 68

debug\_options/1  
     *sys*, 361

decode/1  
     *base64*, 54

decode\_to\_string/1  
     *base64*, 54

deep\_char\_list/1  
     *io\_lib*, 219

del\_binding/2  
     *erl\_eval*, 107

del\_edge/2  
     *digraph*, 94

del\_edges/2  
     *digraph*, 94

del\_element/2  
     *gb\_sets*, 165  
     *ordsets*, 257  
     *sets*, 302

del\_path/3  
     *digraph*, 94

del\_vertex/2  
     *digraph*, 95

del\_vertices/2  
     *digraph*, 95

delete/1  
     *digraph*, 95  
     *ets*, 130

delete/2  
     *dets*, 74  
     *ets*, 130  
     *gb\_sets*, 165  
     *gb\_trees*, 170  
     *lists*, 223  
     *proplists*, 268

delete\_all\_objects/1  
     *dets*, 74  
     *ets*, 130

- delete\_any/2
  - gb\_sets* , 165
  - gb\_trees* , 171
- delete\_child/2
  - supervisor* , 351
- delete\_cursor/1
  - qlc* , 281
- delete\_handler/3
  - gen\_event* , 179
- delete\_key/1
  - win32reg* , 369
- delete\_object/2
  - dets* , 74
  - ets* , 130
- delete\_value/2
  - win32reg* , 370
- dets*
  - all*/0, 73
  - bchunk*/2, 73
  - close*/1, 74
  - delete*/2, 74
  - delete\_all\_objects*/1, 74
  - delete\_object*/2, 74
  - first*/1, 74
  - foldl*/3, 75
  - foldr*/3, 75
  - from\_ets*/2, 75
  - info*/1, 75
  - info*/2, 76
  - init\_table*/3, 76
  - insert*/2, 77
  - insert\_new*/2, 77
  - is\_compatible\_bchunk\_format*/2, 78
  - is\_dets\_file*/1, 78
  - lookup*/2, 78
  - match*/1, 78
  - match*/2, 79
  - match*/3, 79
  - match\_delete*/2, 79
  - match\_object*/1, 80
  - match\_object*/2, 80
  - match\_object*/3, 80
  - member*/2, 81
  - next*/2, 81
  - open\_file*/1, 81
  - open\_file*/2, 81
  - pid2name*/1, 83
  - repair\_continuation*/2, 83
  - safe\_fixtable*/2, 83
  - select*/1, 84
  - select*/2, 84
  - select*/3, 84
  - select\_delete*/2, 85
  - slot*/2, 85
  - sync*/1, 85
  - table*/2, 86
  - to\_ets*/2, 86
  - traverse*/2, 87
  - update\_counter*/3, 87
- dict*
  - append*/3, 88
  - append\_list*/3, 88
  - erase*/2, 88
  - fetch*/2, 89
  - fetch\_keys*/1, 89
  - filter*/2, 89
  - find*/2, 89
  - fold*/3, 89
  - from\_list*/1, 89
  - is\_key*/2, 90
  - map*/2, 90
  - merge*/3, 90
  - new*/0, 90
  - store*/3, 90
  - to\_list*/1, 90
  - update*/3, 91
  - update*/4, 91
  - update\_counter*/3, 91
- diff\_dirs*/2
  - beam\_lib* , 60
- difference*/2
  - gb\_sets* , 165
  - sofs* , 323
- digraph*
  - add\_edge*/3, 93
  - add\_edge*/4, 93
  - add\_edge*/5, 93
  - add\_vertex*/1, 94
  - add\_vertex*/2, 94
  - add\_vertex*/3, 94
  - del\_edge*/2, 94
  - del\_edges*/2, 94
  - del\_path*/3, 94
  - del\_vertex*/2, 95
  - del\_vertices*/2, 95
  - delete*/1, 95
  - edge*/2, 95
  - edges*/1, 95
  - edges*/2, 95
  - get\_cycle*/2, 96

- get\_path/3, 96
- get\_short\_cycle/2, 96
- get\_short\_path/3, 96
- in\_degree/2, 97
- in\_edges/2, 97
- in\_neighbours/2, 97
- info/1, 97
- new/0, 98
- new/1, 98
- no\_edges/1, 98
- no\_vertices/1, 98
- out\_degree/2, 98
- out\_edges/2, 98
- out\_neighbours/2, 98
- vertex/2, 99
- vertices/1, 99
- digraph\_to\_family/2
  - sofs, 323
- digraph\_utils*
  - components/1, 101
  - condensation/1, 101
  - cyclic\_strong\_components/1, 101
  - is\_acyclic/1, 101
  - loop\_vertices/1, 101
  - postorder/1, 102
  - preorder/1, 102
  - reachable/2, 102
  - reachable\_neighbours/2, 102
  - reaching/2, 102
  - reaching\_neighbours/2, 102
  - strong\_components/1, 103
  - subgraph/3, 103
  - topsort/1, 103
- dirname/1
  - filename, 160
- domain/1
  - sofs, 323
- drestriction/2
  - sofs, 323
- drestriction/3
  - sofs, 324
- dropwhile/2
  - lists, 223
- duplicate/2
  - lists, 223
- e/2
  - qlc, 281
- edge/2
  - digraph, 95
- edges/1
  - digraph, 95
- edges/2
  - digraph, 95
- empty/0
  - gb\_sets, 166
  - gb\_trees, 171
- empty\_set/0
  - sofs, 324
- encode/1
  - base64, 54
- encode\_to\_string/1
  - base64, 54
- ensure\_dir/1
  - filelib, 155
- enter/3
  - gb\_trees, 171
- enter\_loop/3
  - gen\_server, 201
- enter\_loop/4
  - gen\_fsm, 190
  - gen\_server, 201
- enter\_loop/5
  - gen\_fsm, 190
  - gen\_server, 201
- enter\_loop/6
  - gen\_fsm, 190
- epp
  - close/1, 104
  - open/2, 104
  - open/3, 104
  - parse\_erl\_form/1, 104
  - parse\_file/3, 104
- equal/2
  - string, 341
- erase/2
  - dict, 88
  - orddict, 251
- erf/1
  - math, 239
- erfc/1
  - math, 239

*erl\_eval*

- add\_binding/3, 107
- binding/2, 107
- bindings/1, 107
- del\_binding/2, 107
- expr/2, 106
- expr/3, 106
- expr/4, 106
- expr\_list/2, 107
- expr\_list/3, 107
- expr\_list/4, 107
- exprs/2, 106
- exprs/3, 106
- exprs/4, 106
- new\_bindings/0, 107

*erl\_expand\_records*

- module/2, 109

*erl\_id\_trans*

- parse\_transform/2, 110

*erl\_internal*

- arith\_op/2, 111
- bif/2, 111
- bool\_op/2, 111
- comp\_op/2, 112
- guard\_bif/2, 111
- list\_op/2, 112
- op\_type/2, 112
- send\_op/2, 112
- type\_test/2, 111

*erl\_lint*

- format\_error/1, 114
- is\_guard\_test/1, 114
- module/1, 113
- module/2, 113
- module/3, 113

*erl\_parse*

- abstract/1, 116
- format\_error/1, 116
- normalise/1, 116
- parse\_exprs/1, 115
- parse\_form/1, 115
- parse\_term/1, 115
- tokens/1, 116
- tokens/2, 116

*erl\_pp*

- attribute/1, 118
- attribute/2, 118
- expr/1, 119
- expr/2, 119
- expr/3, 119

- expr/4, 119
- exprs/1, 119
- exprs/2, 119
- exprs/3, 119
- form/1, 118
- form/2, 118
- function/1, 118
- function/2, 118
- guard/1, 118
- guard/2, 118

*erl\_scan*

- format\_error/1, 122
- reserved\_word/1, 122
- string/1, 121
- string/2, 121
- tokens/3, 121

*erl\_tar*

- add/3, 124
- add/4, 124
- close/1, 124
- create/2, 124
- create/3, 125
- extract/1, 125
- extract/2, 125
- format\_error/1, 126
- open/2, 126
- t/1, 127
- table/1, 127
- table/2, 127
- tt/1, 127

*error\_message/2*

- lib*, 220

*esend/2*

- pg*, 260

*ets*

- all/0, 130
- delete/1, 130
- delete/2, 130
- delete\_all\_objects/1, 130
- delete\_object/2, 130
- file2tab/1, 131
- first/1, 131
- fixtable/2, 131
- foldl/3, 131
- foldr/3, 131
- from\_dets/2, 132
- fun2ms/1, 132
- i/0, 133
- i/1, 133
- info/1, 133

- info/2, 134
- init\_table/2, 134
- insert/2, 135
- insert\_new/2, 135
- is\_compiled\_ms/1, 135
- last/1, 136
- lookup/2, 136
- lookup\_element/3, 136
- match/1, 138
- match/2, 137
- match/3, 137
- match\_delete/2, 138
- match\_object/1, 139
- match\_object/2, 138
- match\_object/3, 138
- match\_spec\_compile/1, 139
- match\_spec\_run/2, 139
- member/2, 140
- new/2, 140
- next/2, 141
- prev/2, 141
- rename/2, 142
- repair\_continuation/2, 142
- safe\_fixtable/2, 143
- select/1, 145
- select/2, 144
- select/3, 145
- select\_count/2, 146
- select\_delete/2, 145
- slot/2, 146
- tab2file/2, 146
- tab2list/1, 147
- table/2, 147
- test\_ms/2, 148
- to\_dets/2, 148
- update\_counter/3, 148
- update\_counter/4, 148
- update\_counter/6, 148

- eval/2
  - qlc*, 281
- exit\_after/2
  - timer*, 365
- exit\_after/3
  - timer*, 365
- exp/1
  - math*, 238
- expand/1
  - win32reg*, 370
- expand/2
  - proplists*, 268
- expr/1
  - erl\_pp*, 119
- expr/2
  - erl\_eval*, 106
  - erl\_pp*, 119
- expr/3
  - erl\_eval*, 106
  - erl\_pp*, 119
- expr/4
  - erl\_eval*, 106
  - erl\_pp*, 119
- expr\_list/2
  - erl\_eval*, 107
- expr\_list/3
  - erl\_eval*, 107
- expr\_list/4
  - erl\_eval*, 107
- exprs/1
  - erl\_pp*, 119
- exprs/2
  - erl\_eval*, 106
  - erl\_pp*, 119
- exprs/3
  - erl\_eval*, 106
  - erl\_pp*, 119
- exprs/4
  - erl\_eval*, 106
- extension/1
  - filename*, 160
- extension/3
  - sofs*, 324
- extract/1
  - erl\_tar*, 125
  - zip*, 374
- extract/2
  - erl\_tar*, 125
  - zip*, 374
- family/2
  - sofs*, 325
- family\_difference/2
  - sofs*, 325
- family\_domain/1
  - sofs*, 325
- family\_field/1

- sofs* , 325
- family\_intersection/1
  - sofs* , 326
- family\_intersection/2
  - sofs* , 326
- family\_projection/2
  - sofs* , 326
- family\_range/1
  - sofs* , 326
- family\_specification/2
  - sofs* , 327
- family\_to\_digraph/2
  - sofs* , 327
- family\_to\_relation/1
  - sofs* , 327
- family\_union/1
  - sofs* , 328
- family\_union/2
  - sofs* , 328
- fetch/2
  - dict* , 89
  - orddict* , 252
- fetch\_keys/1
  - dict* , 89
  - orddict* , 252
- field/1
  - sofs* , 328
- file2tab/1
  - ets* , 131
- file\_size/1
  - filelib* , 155
- file\_sorter*
  - check/1, 154
  - check/2, 154
  - keycheck/2, 154
  - keycheck/3, 154
  - keymerge/3, 154
  - keymerge/4, 154
  - keysort/2, 153
  - keysort/3, 153
  - keysort/4, 153
  - merge/2, 153
  - merge/3, 153
  - sort/1, 153
  - sort/2, 153
  - sort/3, 153

- filelib*
  - ensure\_dir/1, 155
  - file\_size/1, 155
  - fold\_files/5, 155
  - is\_dir/1, 155
  - is\_file/1, 155
  - is\_regular/1, 156
  - last\_modified/1, 156
  - wildcard/1, 156
  - wildcard/2, 157
- filename*
  - absname/1, 158
  - absname/2, 159
  - absname\_join/2, 159
  - basename/1, 159
  - basename/2, 159
  - dirname/1, 160
  - extension/1, 160
  - find\_src/1, 162
  - find\_src/2, 162
  - flatten/1, 160
  - join/1, 161
  - join/2, 161
  - nativename/1, 161
  - pathtype/1, 161
  - rootname/1, 162
  - rootname/2, 162
  - split/1, 162
- filter/2
  - dict* , 89
  - gb\_sets* , 166
  - lists* , 224
  - orddict* , 252
  - ordsets* , 258
  - sets* , 303
- find/2
  - dict* , 89
  - orddict* , 252
- find\_src/1
  - filename* , 162
- find\_src/2
  - filename* , 162
- first/1
  - dets* , 74
  - ets* , 131
- first\_match/2
  - regexp* , 296
- fixtable/2
  - ets* , 131

- flatlength/1
  - lists*, 224
- flatmap/2
  - lists*, 224
- flatten/1
  - filename*, 160
  - lists*, 224
- flatten/2
  - lists*, 224
- flush/0
  - c*, 64
- flush\_receive/0
  - lib*, 220
- fold/3
  - dict*, 89
  - gb\_sets*, 166
  - orddict*, 252
  - ordsets*, 258
  - sets*, 303
- fold/4
  - qlc*, 281
- fold\_files/5
  - filelib*, 155
- foldl/3
  - dets*, 75
  - ets*, 131
  - lists*, 224
- foldr/3
  - dets*, 75
  - ets*, 131
  - lists*, 225
- foreach/2
  - lists*, 225
- form/1
  - erl\_pp*, 118
- form/2
  - erl\_pp*, 118
- format/1
  - io*, 207
  - proc\_lib*, 266
- format/2
  - io\_lib*, 217
- format/3
  - io*, 207
- format\_error/1
  - beam\_lib*, 61
  - erl\_lint*, 114
  - erl\_parse*, 116
  - erl\_scan*, 122
  - erl\_tar*, 126
  - ms\_transform*, 250
  - qlc*, 281
  - regexp*, 298
  - win32reg*, 370
- fread/2
  - io\_lib*, 217
- fread/3
  - io*, 211
  - io\_lib*, 217
- from\_dets/2
  - ets*, 132
- from\_ets/2
  - dets*, 75
- from\_external/2
  - sofs*, 328
- from\_list/1
  - dict*, 89
  - gb\_sets*, 166
  - orddict*, 252
  - ordsets*, 257
  - queue*, 290
  - sets*, 302
- from\_orddict/1
  - gb\_trees*, 171
- from\_ordset/1
  - gb\_sets*, 166
- from\_sets/1
  - sofs*, 328, 329
- from\_term/2
  - sofs*, 329
- fun2ms/1
  - ets*, 132
- function/1
  - erl\_pp*, 118
- function/2
  - erl\_pp*, 118
- fwrite/1
  - io*, 207
- fwrite/2
  - io\_lib*, 217

*fwrite*/3  
  *io*, 207

### *gb\_sets*

*add*/2, 165  
  *add\_element*/2, 165  
  *balance*/1, 165  
  *del\_element*/2, 165  
  *delete*/2, 165  
  *delete\_any*/2, 165  
  *difference*/2, 165  
  *empty*/0, 166  
  *filter*/2, 166  
  *fold*/3, 166  
  *from\_list*/1, 166  
  *from\_ordset*/1, 166  
  *insert*/2, 166  
  *intersection*/1, 167  
  *intersection*/2, 167  
  *is\_element*/2, 167  
  *is\_empty*/1, 167  
  *is\_member*/2, 167  
  *is\_set*/1, 167  
  *is\_subset*/2, 167  
  *iterator*/1, 167  
  *largest*/1, 168  
  *new*/0, 166  
  *next*/1, 168  
  *singleton*/1, 168  
  *size*/1, 168  
  *smallest*/1, 168  
  *subtract*/2, 166  
  *take\_largest*/1, 168  
  *take\_smallest*/1, 168  
  *to\_list*/1, 169  
  *union*/1, 169  
  *union*/2, 169

### *gb\_trees*

*balance*/1, 170  
  *delete*/2, 170  
  *delete\_any*/2, 171  
  *empty*/0, 171  
  *enter*/3, 171  
  *from\_orddict*/1, 171  
  *get*/2, 171  
  *insert*/3, 172  
  *is\_defined*/2, 172  
  *is\_empty*/1, 172  
  *iterator*/1, 172  
  *keys*/1, 172  
  *largest*/1, 172  
  *lookup*/2, 171

*next*/1, 172  
  *size*/1, 173  
  *smallest*/1, 173  
  *take\_largest*/1, 173  
  *take\_smallest*/1, 173  
  *to\_list*/1, 173  
  *update*/3, 173  
  *values*/1, 174

### *gen\_event*

*add\_handler*/3, 176  
  *add\_sup\_handler*/3, 177  
  *call*/3, 178  
  *call*/4, 178  
  *delete\_handler*/3, 179  
  Module:*code\_change*/3, 183  
  Module:*handle\_call*/2, 182  
  Module:*handle\_event*/2, 181  
  Module:*handle\_info*/2, 182  
  Module:*init*/1, 181  
  Module:*terminate*/2, 183  
  *notify*/2, 178  
  *start*/0, 176  
  *start*/1, 176  
  *start\_link*/0, 176  
  *start\_link*/1, 176  
  *stop*/1, 181  
  *swap\_handler*/5, 179  
  *swap\_sup\_handler*/5, 180  
  *sync\_notify*/2, 178  
  *which\_handlers*/1, 180

### *gen\_fsm*

*cancel\_timer*/1, 190  
  *enter\_loop*/4, 190  
  *enter\_loop*/5, 190  
  *enter\_loop*/6, 190  
  Module:*code\_change*/4, 195  
  Module:*handle\_event*/3, 192  
  Module:*handle\_info*/3, 194  
  Module:*handle\_sync\_event*/4, 193  
  Module:*init*/1, 191  
  Module:*StateName*/2, 192  
  Module:*StateName*/3, 193  
  Module:*terminate*/3, 194  
  *reply*/2, 189  
  *send\_all\_state\_event*/2, 188  
  *send\_event*/2, 187  
  *send\_event\_after*/2, 189  
  *start*/3, 187  
  *start*/4, 187  
  *start\_link*/3, 186  
  *start\_link*/4, 186  
  *start\_timer*/2, 189

- sync\_send\_all\_state\_event/2, 188
- sync\_send\_all\_state\_event/3, 188
- sync\_send\_event/2, 188
- sync\_send\_event/3, 188
- gen\_server*
  - abcast/2, 200
  - abcast/3, 200
  - call/2, 198
  - call/3, 198
  - cast/2, 200
  - enter\_loop/3, 201
  - enter\_loop/4, 201
  - enter\_loop/5, 201
  - Module:code\_change/3, 204
  - Module:handle\_call/3, 202
  - Module:handle\_cast/2, 203
  - Module:handle\_info/2, 203
  - Module:init/1, 202
  - Module:terminate/2, 203
  - multi\_call/2, 199
  - multi\_call/3, 199
  - multi\_call/4, 199
  - reply/2, 200
  - start/3, 197
  - start/4, 197
  - start\_link/3, 196
  - start\_link/4, 196
- get/2
  - gb\_trees*, 171
- get\_all\_values/2
  - proplists*, 269
- get\_bool/2
  - proplists*, 269
- get\_chars/3
  - io*, 205
- get\_cycle/2
  - digraph*, 96
- get\_debug/3
  - sys*, 361
- get\_keys/1
  - proplists*, 269
- get\_line/2
  - io*, 206
- get\_node/0
  - pool*, 262
- get\_nodes/0
  - pool*, 262
- get\_path/3
  - digraph*, 96
- get\_short\_cycle/2
  - digraph*, 96
- get\_short\_path/3
  - digraph*, 96
- get\_status/1
  - sys*, 359
- get\_status/2
  - sys*, 359
- get\_value/2
  - proplists*, 270
- get\_value/3
  - proplists*, 270
- gregorian\_days\_to\_date/1
  - calendar*, 68
- gregorian\_seconds\_to\_datetime/1
  - calendar*, 68
- gsub/3
  - regexp*, 297
- guard/1
  - erl\_pp*, 118
- guard/2
  - erl\_pp*, 118
- guard\_bif/2
  - erl\_internal*, 111
- handle\_debug/1
  - sys*, 361
- handle\_system\_msg/6
  - sys*, 361
- head/1
  - queue*, 290
- help/0
  - c*, 64
- hibernate/3
  - proc\_lib*, 267
- history/1
  - shell*, 312
- hms/3
  - timer*, 366
- hours/1
  - timer*, 366

- i/0
  - c, 64
  - ets, 133
- i/1
  - ets, 133
- i/3
  - c, 64
- image/2
  - sofs, 330
- in/2
  - queue, 290
- in\_degree/2
  - digraph, 97
- in\_edges/2
  - digraph, 97
- in\_neighbours/2
  - digraph, 97
- in\_r/2
  - queue, 291
- indentation/2
  - io\_lib, 218
- info/1
  - beam\_lib, 59
  - dets, 75
  - digraph, 97
  - ets, 133
- info/2
  - dets, 76
  - ets, 134
  - qlc, 282
- init/1
  - queue, 291
- init/3
  - log\_mf\_h, 237
- init/4
  - log\_mf\_h, 237
- init\_ack/1
  - proc\_lib, 265
- init\_ack/2
  - proc\_lib, 265
- init\_table/2
  - ets, 134
- init\_table/3
  - dets, 76
- initial\_call/1
  - proc\_lib, 266
- insert/2
  - dets, 77
  - ets, 135
  - gb\_sets, 166
- insert/3
  - gb\_trees, 172
- insert\_new/2
  - dets, 77
  - ets, 135
- install/3
  - sys, 360
- install/4
  - sys, 360
- intersection/1
  - gb\_sets, 167
  - ordsets, 258
  - sets, 303
  - sofs, 330
- intersection/2
  - gb\_sets, 167
  - ordsets, 257
  - sets, 302
  - sofs, 330
- intersection\_of\_family/1
  - sofs, 330
- inverse/1
  - sofs, 330
- inverse\_image/2
  - sofs, 331
- io
  - format/1, 207
  - format/3, 207
  - fread/3, 211
  - fwrite/1, 207
  - fwrite/3, 207
  - get\_chars/3, 205
  - get\_line/2, 206
  - nl/1, 205
  - parse\_erl\_exprs/1, 214
  - parse\_erl\_exprs/3, 214
  - parse\_erl\_form/1, 214
  - parse\_erl\_form/3, 214
  - put\_chars/2, 205
  - read/2, 207
  - read/3, 207
  - scan\_erl\_exprs/1, 213

- scan\_erl\_exprs/3, 213
- scan\_erl\_form/1, 213
- scan\_erl\_form/3, 213
- setopts/2, 206
- write/2, 206
- io\_lib*
  - char\_list/1, 219
  - deep\_char\_list/1, 219
  - format/2, 217
  - fread/2, 217
  - fread/3, 217
  - fwrite/2, 217
  - indentation/2, 218
  - nl/0, 216
  - print/1, 216
  - print/4, 216
  - printable\_list/1, 219
  - write/1, 216
  - write/2, 216
  - write\_atom/1, 218
  - write\_char/1, 218
  - write\_string/1, 218
- is\_a\_function/1
  - sofs, 331
- is\_acyclic/1
  - digraph\_utils, 101
- is\_compatible\_bchunk\_format/2
  - dets, 78
- is\_compiled\_ms/1
  - ets, 135
- is\_defined/2
  - gb\_trees, 172
  - proplists, 270
- is\_dets\_file/1
  - dets, 78
- is\_dir/1
  - filelib, 155
- is\_disjoint/2
  - sofs, 331
- is\_element/2
  - gb\_sets, 167
  - ordsets, 257
  - sets, 302
- is\_empty/1
  - gb\_sets, 167
  - gb\_trees, 172
  - queue, 291
- is\_empty\_set/1
  - sofs, 331
- is\_equal/2
  - sofs, 331
- is\_file/1
  - filelib, 155
- is\_guard\_test/1
  - erl\_lint, 114
- is\_key/2
  - dict, 90
  - orddict, 253
- is\_leap\_year/1
  - calendar, 68
- is\_member/2
  - gb\_sets, 167
- is\_regular/1
  - filelib, 156
- is\_set/1
  - gb\_sets, 167
  - ordsets, 256
  - sets, 301
  - sofs, 331
- is\_sofs\_set/1
  - sofs, 332
- is\_subset/2
  - gb\_sets, 167
  - ordsets, 258
  - sets, 303
  - sofs, 332
- is\_type/1
  - sofs, 332
- iterator/1
  - gb\_sets, 167
  - gb\_trees, 172
- join/1
  - filename, 161
- join/2
  - filename, 161
  - pg, 259
  - queue, 291
- join/4
  - sofs, 332
- keycheck/2
  - file\_sorter, 154

- keycheck/3
  - file\_sorter* , 154
- keydelete/3
  - lists* , 225
- keymap/3
  - lists* , 226
- keymember/3
  - lists* , 226
- keymerge/3
  - file\_sorter* , 154
  - lists* , 226
- keymerge/4
  - file\_sorter* , 154
- keyreplace/4
  - lists* , 226
- keys/1
  - gb\_trees* , 172
- keysearch/3
  - lists* , 227
- keysort/2
  - file\_sorter* , 153
  - lists* , 227
- keysort/3
  - file\_sorter* , 153
  - qlc* , 283
- keysort/4
  - file\_sorter* , 153
- kill\_after/1
  - timer* , 365
- kill\_after/2
  - timer* , 365
- l/1
  - c* , 64
- lait/1
  - queue* , 291
- largest/1
  - gb\_sets* , 168
  - gb\_trees* , 172
- last/1
  - ets* , 136
  - lists* , 227
  - queue* , 291
- last\_day\_of\_the\_month/2
  - calendar* , 68
- last\_modified/1
  - filelib* , 156
- lc/1
  - c* , 64
- left/2
  - string* , 344
- left/3
  - string* , 344
- len/1
  - queue* , 291
  - string* , 341
- lib
  - error\_message/2* , 220
  - flush\_receive/0* , 220
  - nonl/1* , 220
  - progname/0* , 220
  - send/2* , 220
  - sendw/2* , 221
- list\_dir/1
  - zip* , 375
- list\_dir/2
  - zip* , 375
- list\_op/2
  - erl\_internal* , 112
- lists
  - all/2* , 222
  - any/2* , 222
  - append/1* , 222
  - append/2* , 222
  - concat/1* , 223
  - delete/2* , 223
  - dropwhile/2* , 223
  - duplicate/2* , 223
  - filter/2* , 224
  - flatlength/1* , 224
  - flatmap/2* , 224
  - flatten/1* , 224
  - flatten/2* , 224
  - foldl/3* , 224
  - foldr/3* , 225
  - foreach/2* , 225
  - keydelete/3* , 225
  - keymap/3* , 226
  - keymember/3* , 226
  - keymerge/3* , 226
  - keyreplace/4* , 226
  - keysearch/3* , 227
  - keysort/2* , 227
  - last/1* , 227

- map/2, 227
- mapfoldl/3, 227
- mapfoldr/3, 228
- max/1, 228
- member/2, 228
- merge/1, 228
- merge/2, 228
- merge/3, 229
- merge3/3, 229
- min/1, 229
- nth/2, 229
- nthtail/2, 229
- partition/2, 230
- prefix/2, 230
- reverse/1, 230
- reverse/2, 230
- seq/2, 231
- seq/3, 231
- sort/1, 231
- sort/2, 231
- split/2, 231
- splitwith/2, 231
- sublist/2, 232
- sublist/3, 232
- subtract/2, 232
- suffix/2, 233
- sum/1, 233
- takewhile/2, 233
- ukeymerge/3, 233
- ukeysort/2, 233
- umerge/1, 233
- umerge/2, 234
- umerge/3, 234
- umerge3/3, 234
- unzip/1, 234
- unzip3/1, 234
- usort/1, 235
- usort/2, 235
- zip/2, 235
- zip3/3, 235
- zipwith/3, 236
- zipwith3/4, 236

- local\_time/0
  - calendar*, 69
- local\_time\_to\_universal\_time/2
  - calendar*, 69
- local\_time\_to\_universal\_time\_dst/2
  - calendar*, 69
- log/1
  - math*, 238
- log/2
  - sys*, 358
- log/3
  - sys*, 358
- log10/1
  - math*, 238
- log\_mf.h*
  - init*/3, 237
  - init*/4, 237
- log\_to\_file/2
  - sys*, 358
- log\_to\_file/3
  - sys*, 358
- lookup/2
  - dets*, 78
  - ets*, 136
  - gb\_trees*, 171
  - proplists*, 270
- lookup\_all/2
  - proplists*, 270
- lookup\_element/3
  - ets*, 136
- loop\_vertices/1
  - digraph\_utils*, 101
- ls/0
  - c*, 64
- ls/1
  - c*, 64
- m/0
  - c*, 65
- m/1
  - c*, 65
- map/2
  - dict*, 90
  - lists*, 227
  - orddict*, 253
- mapfoldl/3
  - lists*, 227
- mapfoldr/3
  - lists*, 228
- match/1
  - dets*, 78
  - ets*, 138
- match/2

- dets* , 79
  - ets* , 137
  - regexp* , 296
- match/3
  - dets* , 79
  - ets* , 137
- match\_delete/2
  - dets* , 79
  - ets* , 138
- match\_object/1
  - dets* , 80
  - ets* , 139
- match\_object/2
  - dets* , 80
  - ets* , 138
- match\_object/3
  - dets* , 80
  - ets* , 138
- match\_spec\_compile/1
  - ets* , 139
- match\_spec\_run/2
  - ets* , 139
- matches/2
  - regexp* , 296
- math*
  - acos*/1, 238
  - acosh*/1, 238
  - asin*/1, 238
  - asinh*/1, 238
  - atan*/1, 238
  - atan2*/2, 238
  - atanh*/1, 238
  - cos*/1, 238
  - cosh*/1, 238
  - erf*/1, 239
  - erfc*/1, 239
  - exp*/1, 238
  - log*/1, 238
  - log10*/1, 238
  - pi*/0, 238
  - pow*/2, 238
  - sin*/1, 238
  - sinh*/1, 238
  - sqrt*/1, 238
  - tan*/1, 238
  - tanh*/1, 238
- max/1
  - lists* , 228
- md5/1
  - beam\_lib* , 59
- member/2
  - dets* , 81
  - ets* , 140
  - lists* , 228
- members/1
  - pg* , 260
- memory/0
  - c* , 65
- memory/1
  - c* , 65
- merge/1
  - lists* , 228
- merge/2
  - file\_sorter* , 153
  - lists* , 228
- merge/3
  - dict* , 90
  - file\_sorter* , 153
  - lists* , 229
  - orddict* , 253
- merge3/3
  - lists* , 229
- mime\_decode/1
  - base64* , 54
- mime\_decode\_string/1
  - base64* , 54
- min/1
  - lists* , 229
- minutes/1
  - timer* , 366
- Mod:system\_code\_change/4
  - sys* , 362
- Mod:system\_continue/3
  - sys* , 362
- Mod:system\_terminate/4
  - sys* , 362
- module/1
  - erl\_lint* , 113
- module/2
  - erl\_expand\_records* , 109
  - erl\_lint* , 113
- module/3

- erl\_lint* , 113
- Module:code\_change/3
  - gen\_event* , 183
  - gen\_server* , 204
- Module:code\_change/4
  - gen\_fsm* , 195
- Module:handle\_call/2
  - gen\_event* , 182
- Module:handle\_call/3
  - gen\_server* , 202
- Module:handle\_cast/2
  - gen\_server* , 203
- Module:handle\_event/2
  - gen\_event* , 181
- Module:handle\_event/3
  - gen\_fsm* , 192
- Module:handle\_info/2
  - gen\_event* , 182
  - gen\_server* , 203
- Module:handle\_info/3
  - gen\_fsm* , 194
- Module:handle\_sync\_event/4
  - gen\_fsm* , 193
- Module:init/1
  - gen\_event* , 181
  - gen\_fsm* , 191
  - gen\_server* , 202
  - supervisor* , 353
  - supervisor\_bridge* , 355
- Module:StateName/2
  - gen\_fsm* , 192
- Module:StateName/3
  - gen\_fsm* , 193
- Module:terminate/2
  - gen\_event* , 183
  - gen\_server* , 203
  - supervisor\_bridge* , 355
- Module:terminate/3
  - gen\_fsm* , 194
- ms\_transform*
  - format\_error*/1, 250
  - parse\_transform*/2, 249
  - transform\_from\_shell*/3, 249
- multi\_call/2
  - gen\_server* , 199
- multi\_call/3
  - gen\_server* , 199
- multi\_call/4
  - gen\_server* , 199
- multiple\_relative\_product/2
  - sofs* , 332
- nativename/1
  - filename* , 161
- nc/1
  - c* , 65
- nc/2
  - c* , 65
- new/0
  - dict* , 90
  - digraph* , 98
  - gb\_sets* , 166
  - orddict* , 253
  - ordsets* , 256
  - queue* , 292
  - sets* , 301
- new/1
  - digraph* , 98
- new/2
  - ets* , 140
- new\_bindings/0
  - erLeval* , 107
- next/1
  - gb\_sets* , 168
  - gb\_trees* , 172
- next/2
  - dets* , 81
  - ets* , 141
- next\_answers/2
  - qlc* , 283
- ni/0
  - c* , 64
- nl/0
  - io\_lib* , 216
- nl/1
  - c* , 65
  - io* , 205
- no\_debug/1
  - sys* , 359
- no\_debug/2

- sys, 359
- no\_edges/1
  - digraph*, 98
- no\_elements/1
  - sofs*, 333
- no\_vertices/1
  - digraph*, 98
- nonl/1
  - lib*, 220
- normalise/1
  - erl\_parse*, 116
- normalize/2
  - proplists*, 270
- notify/2
  - gen\_event*, 178
- now\_diff/2
  - timer*, 366
- now\_to\_datetime/1
  - calendar*, 70
- now\_to\_local\_time/1
  - calendar*, 69
- now\_to\_universal\_time/1
  - calendar*, 70
- nregs/0
  - c*, 66
- nth/2
  - lists*, 229
- nthtail/2
  - lists*, 229
- op\_type/2
  - erl\_internal*, 112
- open/1
  - win32reg*, 370
- open/2
  - epp*, 104
  - erl\_tar*, 126
- open/3
  - epp*, 104
- open\_file/1
  - dets*, 81
- open\_file/2
  - dets*, 81

- orddict*
  - append/3, 251
  - append\_list/3, 251
  - erase/2, 251
  - fetch/2, 252
  - fetch\_keys/1, 252
  - filter/2, 252
  - find/2, 252
  - fold/3, 252
  - from\_list/1, 252
  - is\_key/2, 253
  - map/2, 253
  - merge/3, 253
  - new/0, 253
  - store/3, 253
  - to\_list/1, 253
  - update/3, 254
  - update/4, 254
  - update\_counter/3, 254
- ordsets*
  - add\_element/2, 257
  - del\_element/2, 257
  - filter/2, 258
  - fold/3, 258
  - from\_list/1, 257
  - intersection/1, 258
  - intersection/2, 257
  - is\_element/2, 257
  - is\_set/1, 256
  - is\_subset/2, 258
  - new/0, 256
  - size/1, 256
  - subtract/2, 258
  - to\_list/1, 256
  - union/1, 257
  - union/2, 257
- out/1
  - queue*, 292
- out\_degree/2
  - digraph*, 98
- out\_edges/2
  - digraph*, 98
- out\_neighbours/2
  - digraph*, 98
- out\_r/1
  - queue*, 292
- parse/1
  - regexp*, 298

- parse\_erl\_exprs/1
  - io*, 214
- parse\_erl\_exprs/3
  - io*, 214
- parse\_erl\_form/1
  - epp*, 104
  - io*, 214
- parse\_erl\_form/3
  - io*, 214
- parse\_exprs/1
  - erl\_parse*, 115
- parse\_file/3
  - epp*, 104
- parse\_form/1
  - erl\_parse*, 115
- parse\_term/1
  - erl\_parse*, 115
- parse\_transform/2
  - erl\_id\_trans*, 110
  - ms.transform*, 249
- partition/1
  - sofs*, 333
- partition/2
  - lists*, 230
  - sofs*, 333
- partition/3
  - sofs*, 333
- partition\_family/2
  - sofs*, 334
- pathtype/1
  - filename*, 161
- pg*
  - create*/1, 259
  - create*/2, 259
  - esend*/2, 260
  - join*/2, 259
  - members*/1, 260
  - send*/2, 260
- pi/0
  - math*, 238
- pid/3
  - c*, 65
- pid2name/1
  - dets*, 83

- pool*
  - attach*/1, 261
  - get\_node*/0, 262
  - get\_nodes*/0, 262
  - pspawn*/3, 262
  - pspawn\_link*/3, 262
  - start*/1, 261
  - start*/2, 261
  - stop*/0, 262
- postorder/1
  - digraph\_utils*, 102
- pow/2
  - math*, 238
- prefix/2
  - lists*, 230
- preorder/1
  - digraph\_utils*, 102
- prev/2
  - ets*, 141
- print/1
  - io\_lib*, 216
- print/4
  - io\_lib*, 216
- print\_log/1
  - sys*, 362
- printable\_list/1
  - io\_lib*, 219
- proc\_lib*
  - format*/1, 266
  - hibernate*/3, 267
  - init\_ack*/1, 265
  - init\_ack*/2, 265
  - initial\_call*/1, 266
  - spawn*/1, 263
  - spawn*/2, 263
  - spawn*/3, 263
  - spawn*/4, 263
  - spawn\_link*/1, 263
  - spawn\_link*/2, 263
  - spawn\_link*/3, 263
  - spawn\_link*/4, 264
  - spawn\_opt*/2, 264
  - spawn\_opt*/3, 264
  - spawn\_opt*/4, 264
  - spawn\_opt*/5, 264
  - start*/3, 264
  - start*/4, 264
  - start*/5, 264

- start\_link/3, 264
- start\_link/4, 264
- start\_link/5, 264
- translate\_initial\_call/1, 266
- product/1
  - sofs, 334
- product/2
  - sofs, 334
- programe/0
  - lib, 220
- projection/2
  - sofs, 335
- property/1
  - proplists, 271
- property/2
  - proplists, 271
- proplists
  - append\_values/2, 268
  - compact/1, 268
  - delete/2, 268
  - expand/2, 268
  - get\_all\_values/2, 269
  - get\_bool/2, 269
  - get\_keys/1, 269
  - get\_value/2, 270
  - get\_value/3, 270
  - is\_defined/2, 270
  - lookup/2, 270
  - lookup\_all/2, 270
  - normalize/2, 270
  - property/1, 271
  - property/2, 271
  - split/2, 271
  - substitute\_aliases/2, 272
  - substitute\_negations/2, 272
  - unfold/1, 272
- pseudo/1
  - slave, 317
- pseudo/2
  - slave, 317
- pspawn/3
  - pool, 262
- pspawn\_link/3
  - pool, 262
- put\_chars/2
  - io, 205
- pwd/0

- c, 66
- q/0
  - c, 66
- q/2
  - qlc, 283
- qlc
  - append/1, 280
  - append/2, 280
  - cursor/2, 280
  - delete\_cursor/1, 281
  - e/2, 281
  - eval/2, 281
  - fold/4, 281
  - format\_error/1, 281
  - info/2, 282
  - keysort/3, 283
  - next\_answers/2, 283
  - q/2, 283
  - sort/2, 286
  - string\_to\_handle/3, 286
  - table/2, 287
- queue
  - cons/2, 290
  - daeh/1, 290
  - from\_list/1, 290
  - head/1, 290
  - in/2, 290
  - in\_r/2, 291
  - init/1, 291
  - is\_empty/1, 291
  - join/2, 291
  - lait/1, 291
  - last/1, 291
  - len/1, 291
  - new/0, 292
  - out/1, 292
  - out\_r/1, 292
  - reverse/1, 292
  - snoc/2, 292
  - split/2, 292
  - tail/1, 292
  - to\_list/1, 293
- random
  - seed/0, 294
  - seed/3, 294
  - seed0/0, 294
  - uniform/0, 294
  - uniform/1, 294
  - uniform\_s/1, 295

- uniform\_s/2, 295
- range/1
  - sofs, 335
- rchr/2
  - string, 341
- reachable/2
  - digraph\_utils, 102
- reachable\_neighbours/2
  - digraph\_utils, 102
- reaching/2
  - digraph\_utils, 102
- reaching\_neighbours/2
  - digraph\_utils, 102
- read/2
  - io, 207
- read/3
  - io, 207
- regexp
  - first\_match/2, 296
  - format\_error/1, 298
  - gsub/3, 297
  - match/2, 296
  - matches/2, 296
  - parse/1, 298
  - sh\_to\_awk/1, 298
  - split/2, 297
  - sub/3, 297
- regs/0
  - c, 66
- relation/2
  - sofs, 335
- relation\_to\_family/1
  - sofs, 335
- relative\_product/2
  - sofs, 336
- relative\_product1/2
  - sofs, 336
- relay/1
  - slave, 317
- remove/2
  - sys, 360
- remove/3
  - sys, 360
- rename/2
  - ets, 142
- repair\_continuation/2
  - dets, 83
  - ets, 142
- reply/2
  - gen\_fsm, 189
  - gen\_server, 200
- reserved\_word/1
  - erl\_scan, 122
- restart\_child/2
  - supervisor, 351
- restriction/2
  - sofs, 336
- restriction/3
  - sofs, 337
- results/1
  - shell, 312
- resume/1
  - sys, 359
- resume/2
  - sys, 359
- reverse/1
  - lists, 230
  - queue, 292
- reverse/2
  - lists, 230
- right/2
  - string, 344
- right/3
  - string, 344
- rootname/1
  - filename, 162
- rootname/2
  - filename, 162
- rstr/2
  - string, 341
- safe\_fixtable/2
  - dets, 83
  - ets, 143
- scan\_erl\_exprs/1
  - io, 213
- scan\_erl\_exprs/3
  - io, 213

scan\_erl\_form/1  
     *io*, 213  
 scan\_erl\_form/3  
     *io*, 213  
 seconds/1  
     *timer*, 366  
 seconds\_to\_daystime/1  
     *calendar*, 70  
 seconds\_to\_time/1  
     *calendar*, 70  
 seed/0  
     *random*, 294  
 seed/3  
     *random*, 294  
 seed0/0  
     *random*, 294  
 select/1  
     *dets*, 84  
     *ets*, 145  
 select/2  
     *dets*, 84  
     *ets*, 144  
 select/3  
     *dets*, 84  
     *ets*, 145  
 select\_count/2  
     *ets*, 146  
 select\_delete/2  
     *dets*, 85  
     *ets*, 145  
 send/2  
     *lib*, 220  
     *pg*, 260  
 send\_after/2  
     *timer*, 364  
 send\_after/3  
     *timer*, 364  
 send\_all\_state\_event/2  
     *gen\_fsm*, 188  
 send\_event/2  
     *gen\_fsm*, 187  
 send\_event\_after/2  
     *gen\_fsm*, 189  
 send\_interval/2  
     *timer*, 365  
 send\_interval/3  
     *timer*, 365  
 send\_op/2  
     *erl\_internal*, 112  
 sendw/2  
     *lib*, 221  
 seq/2  
     *lists*, 231  
 seq/3  
     *lists*, 231  
 set/2  
     *sofs*, 337  
 set\_value/3  
     *win32reg*, 370  
 setopts/2  
     *io*, 206  
 sets  
     add\_element/2, 302  
     del\_element/2, 302  
     filter/2, 303  
     fold/3, 303  
     from\_list/1, 302  
     intersection/1, 303  
     intersection/2, 302  
     is\_element/2, 302  
     is\_set/1, 301  
     is\_subset/2, 303  
     new/0, 301  
     size/1, 301  
     subtract/2, 303  
     to\_list/1, 301  
     union/1, 302  
     union/2, 302  
 sh\_to\_awk/1  
     *regexp*, 298  
 shell  
     history/1, 312  
     results/1, 312  
     start\_restricted/1, 313  
     stop\_restricted/0, 313  
 sin/1  
     *math*, 238  
 singleton/1  
     *gb\_sets*, 168  
 sinh/1

- math* , 238
- size/1
  - gb\_sets* , 168
  - gb\_trees* , 173
  - ordsets* , 256
  - sets* , 301
- slave*
  - pseudo*/1, 317
  - pseudo*/2, 317
  - relay*/1, 317
  - start*/1, 315
  - start*/2, 315
  - start*/3, 315
  - start\_link*/1, 316
  - start\_link*/2, 316
  - start\_link*/3, 316
  - stop*/1, 317
- sleep/1
  - timer* , 365
- slot/2
  - dets* , 85
  - ets* , 146
- smallest/1
  - gb\_sets* , 168
  - gb\_trees* , 173
- snoc/2
  - queue* , 292
- sofs*
  - a\_function*/2, 322
  - canonical\_relation*/1, 322
  - composite*/2, 322
  - constant\_function*/2, 322
  - converse*/1, 323
  - difference*/2, 323
  - digraph\_to\_family*/2, 323
  - domain*/1, 323
  - drestriction*/2, 323
  - drestriction*/3, 324
  - empty\_set*/0, 324
  - extension*/3, 324
  - family*/2, 325
  - family\_difference*/2, 325
  - family\_domain*/1, 325
  - family\_field*/1, 325
  - family\_intersection*/1, 326
  - family\_intersection*/2, 326
  - family\_projection*/2, 326
  - family\_range*/1, 326
  - family\_specification*/2, 327
  - family\_to\_digraph*/2, 327
  - family\_to\_relation*/1, 327
  - family\_union*/1, 328
  - family\_union*/2, 328
  - field*/1, 328
  - from\_external*/2, 328
  - from\_sets*/1, 328, 329
  - from\_term*/2, 329
  - image*/2, 330
  - intersection*/1, 330
  - intersection*/2, 330
  - intersection\_of\_family*/1, 330
  - inverse*/1, 330
  - inverse\_image*/2, 331
  - is\_a\_function*/1, 331
  - is\_disjoint*/2, 331
  - is\_empty\_set*/1, 331
  - is\_equal*/2, 331
  - is\_set*/1, 331
  - is\_sofs\_set*/1, 332
  - is\_subset*/2, 332
  - is\_type*/1, 332
  - join*/4, 332
  - multiple\_relative\_product*/2, 332
  - no\_elements*/1, 333
  - partition*/1, 333
  - partition*/2, 333
  - partition*/3, 333
  - partition\_family*/2, 334
  - product*/1, 334
  - product*/2, 334
  - projection*/2, 335
  - range*/1, 335
  - relation*/2, 335
  - relation\_to\_family*/1, 335
  - relative\_product*/2, 336
  - relative\_product1*/2, 336
  - restriction*/2, 336
  - restriction*/3, 337
  - set*/2, 337
  - specification*/2, 337
  - strict\_relation*/1, 337
  - substitution*/2, 338
  - syndiff*/2, 338
  - symmetric\_partition*/2, 339
  - to\_external*/1, 339
  - to\_sets*/1, 339
  - type*/1, 339
  - union*/1, 339
  - union*/2, 339
  - union\_of\_family*/1, 340
  - weak\_relation*/1, 340

sort/1  
     *file\_sorter* , 153  
     *lists* , 231

sort/2  
     *file\_sorter* , 153  
     *lists* , 231  
     *qlc* , 286

sort/3  
     *file\_sorter* , 153

span/2  
     *string* , 342

spawn/1  
     *proc\_lib* , 263

spawn/2  
     *proc\_lib* , 263

spawn/3  
     *proc\_lib* , 263

spawn/4  
     *proc\_lib* , 263

spawn\_link/1  
     *proc\_lib* , 263

spawn\_link/2  
     *proc\_lib* , 263

spawn\_link/3  
     *proc\_lib* , 263

spawn\_link/4  
     *proc\_lib* , 264

spawn\_opt/2  
     *proc\_lib* , 264

spawn\_opt/3  
     *proc\_lib* , 264

spawn\_opt/4  
     *proc\_lib* , 264

spawn\_opt/5  
     *proc\_lib* , 264

specification/2  
     *sofs* , 337

split/1  
     *filename* , 162

split/2  
     *lists* , 231  
     *proplists* , 271  
     *queue* , 292  
     *regexp* , 297

splitwith/2  
     *lists* , 231

sqrt/1  
     *math* , 238

start/0  
     *gen\_event* , 176  
     *timer* , 364

start/1  
     *gen\_event* , 176  
     *pool* , 261  
     *slave* , 315

start/2  
     *pool* , 261  
     *slave* , 315

start/3  
     *gen\_fsm* , 187  
     *gen\_server* , 197  
     *proc\_lib* , 264  
     *slave* , 315

start/4  
     *gen\_fsm* , 187  
     *gen\_server* , 197  
     *proc\_lib* , 264

start/5  
     *proc\_lib* , 264

start\_child/2  
     *supervisor* , 350

start\_link/0  
     *gen\_event* , 176

start\_link/1  
     *gen\_event* , 176  
     *slave* , 316

start\_link/2  
     *slave* , 316  
     *supervisor* , 349  
     *supervisor\_bridge* , 354

start\_link/3  
     *gen\_fsm* , 186  
     *gen\_server* , 196  
     *proc\_lib* , 264  
     *slave* , 316  
     *supervisor* , 349  
     *supervisor\_bridge* , 354

start\_link/4  
     *gen\_fsm* , 186  
     *gen\_server* , 196  
     *proc\_lib* , 264

- start\_link/5
  - proc\_lib* , 264
- start\_restricted/1
  - shell* , 313
- start\_timer/2
  - gen\_fsm* , 189
- statistics/2
  - sys* , 358
- statistics/3
  - sys* , 358
- stop/0
  - pool* , 262
- stop/1
  - gen\_event* , 181
  - slave* , 317
- stop\_restricted/0
  - shell* , 313
- store/3
  - dict* , 90
  - orddict* , 253
- str/2
  - string* , 341
- strict\_relation/1
  - sofs* , 337
- string*
  - centre/2, 344
  - centre/3, 344
  - chars/2, 342
  - chars/3, 342
  - chr/2, 341
  - concat/2, 341
  - copies/2, 343
  - cspan/2, 342
  - equal/2, 341
  - left/2, 344
  - left/3, 344
  - len/1, 341
  - rchr/2, 341
  - right/2, 344
  - right/3, 344
  - rstr/2, 341
  - span/2, 342
  - str/2, 341
  - strip/1, 343
  - strip/2, 343
  - strip/3, 343
  - sub\_string/2, 344
  - sub\_string/3, 345
  - sub\_word/2, 343
  - sub\_word/3, 343
  - substr/2, 342
  - substr/3, 342
  - to\_float/1, 345
  - to\_integer/1, 345
  - to\_lower/1, 346
  - to\_upper/1, 346
  - tokens/2, 342
  - words/1, 343
  - words/2, 343
- string/1
  - erl\_scan* , 121
- string/2
  - erl\_scan* , 121
- string\_to\_handle/3
  - qlc* , 286
- strip/1
  - beam\_lib* , 60
  - string* , 343
- strip/2
  - string* , 343
- strip/3
  - string* , 343
- strip\_files/1
  - beam\_lib* , 60
- strip\_release/1
  - beam\_lib* , 61
- strong\_components/1
  - digraph\_utils* , 103
- sub/3
  - regex* , 297
- sub\_keys/1
  - win32reg* , 371
- sub\_string/2
  - string* , 344
- sub\_string/3
  - string* , 345
- sub\_word/2
  - string* , 343
- sub\_word/3
  - string* , 343
- subgraph/3
  - digraph\_utils* , 103
- sublist/2

- lists*, 232
- sublist/3
  - lists*, 232
- substitute\_aliases/2
  - proplists*, 272
- substitute\_negations/2
  - proplists*, 272
- substitution/2
  - sofs*, 338
- substr/2
  - string*, 342
- substr/3
  - string*, 342
- subtract/2
  - gb\_sets*, 166
  - lists*, 232
  - ordsets*, 258
  - sets*, 303
- suffix/2
  - lists*, 233
- sum/1
  - lists*, 233
- supervisor*
  - check\_childspecs*/1, 352
  - delete\_child*/2, 351
  - Module:init*/1, 353
  - restart\_child*/2, 351
  - start\_child*/2, 350
  - start\_link*/2, 349
  - start\_link*/3, 349
  - terminate\_child*/2, 350
  - which\_children*/1, 352
- supervisor\_bridge*
  - Module:init*/1, 355
  - Module:terminate*/2, 355
  - start\_link*/2, 354
  - start\_link*/3, 354
- suspend/1
  - sys*, 359
- suspend/2
  - sys*, 359
- swap\_handler/5
  - gen\_event*, 179
- swap\_sup\_handler/5
  - gen\_event*, 180
- syndiff/2
  - sofs*, 338
- symmetric\_partition/2
  - sofs*, 339
- sync/1
  - dets*, 85
- sync\_notify/2
  - gen\_event*, 178
- sync\_send\_all\_state\_event/2
  - gen\_fsm*, 188
- sync\_send\_all\_state\_event/3
  - gen\_fsm*, 188
- sync\_send\_event/2
  - gen\_fsm*, 188
- sync\_send\_event/3
  - gen\_fsm*, 188
- sys*
  - change\_code*/4, 359
  - change\_code*/5, 359
  - debug\_options*/1, 361
  - get\_debug*/3, 361
  - get\_status*/1, 359
  - get\_status*/2, 359
  - handle\_debug*/1, 361
  - handle\_system\_msg*/6, 361
  - install*/3, 360
  - install*/4, 360
  - log*/2, 358
  - log*/3, 358
  - log\_to\_file*/2, 358
  - log\_to\_file*/3, 358
  - Mod:system\_code\_change*/4, 362
  - Mod:system\_continue*/3, 362
  - Mod:system\_terminate*/4, 362
  - no\_debug*/1, 359
  - no\_debug*/2, 359
  - print\_log*/1, 362
  - remove*/2, 360
  - remove*/3, 360
  - resume*/1, 359
  - resume*/2, 359
  - statistics*/2, 358
  - statistics*/3, 358
  - suspend*/1, 359
  - suspend*/2, 359
  - trace*/2, 359
  - trace*/3, 359

t/1

- erl\_tar* , 127
- zip* , 375
- tab2file/2
  - ets* , 146
- tab2list/1
  - ets* , 147
- table/1
  - erl\_tar* , 127
  - zip* , 375
- table/2
  - dets* , 86
  - erl\_tar* , 127
  - ets* , 147
  - qlc* , 287
  - zip* , 375
- tail/1
  - queue* , 292
- take\_largest/1
  - gb\_sets* , 168
  - gb\_trees* , 173
- take\_smallest/1
  - gb\_sets* , 168
  - gb\_trees* , 173
- takewhile/2
  - lists* , 233
- tan/1
  - math* , 238
- tanh/1
  - math* , 238
- tc/3
  - timer* , 366
- terminate\_child/2
  - supervisor* , 350
- test\_ms/2
  - ets* , 148
- time\_difference/2
  - calendar* , 70
- time\_to\_seconds/1
  - calendar* , 70
- timer*
  - apply\_after*/4, 364
  - apply\_interval*/4, 365
  - cancel*/1, 365
  - exit\_after*/2, 365
  - exit\_after*/3, 365
  - hms*/3, 366
  - hours*/1, 366
  - kill\_after*/1, 365
  - kill\_after*/2, 365
  - minutes*/1, 366
  - now\_diff*/2, 366
  - seconds*/1, 366
  - send\_after*/2, 364
  - send\_after*/3, 364
  - send\_interval*/2, 365
  - send\_interval*/3, 365
  - sleep*/1, 365
  - start*/0, 364
  - tc*/3, 366
- to\_dets*/2
  - ets* , 148
- to\_ets*/2
  - dets* , 86
- to\_external*/1
  - sofs* , 339
- to\_float*/1
  - string* , 345
- to\_integer*/1
  - string* , 345
- to\_list*/1
  - dict* , 90
  - gb\_sets* , 169
  - gb\_trees* , 173
  - orddict* , 253
  - ordsets* , 256
  - queue* , 293
  - sets* , 301
- to\_lower*/1
  - string* , 346
- to\_sets*/1
  - sofs* , 339
- to\_upper*/1
  - string* , 346
- tokens*/1
  - erl\_parse* , 116
- tokens*/2
  - erl\_parse* , 116
  - string* , 342
- tokens*/3
  - erl\_scan* , 121
- topsort*/1
  - digraph\_utils* , 103

trace/2  
     sys, 359  
 trace/3  
     sys, 359  
 transform\_from\_shell/3  
     ms\_transform, 249  
 translate\_initial\_call/1  
     proc\_lib, 266  
 traverse/2  
     dets, 87  
 tt/1  
     erl\_tar, 127  
     zip, 375  
 type/1  
     sofs, 339  
 type\_test/2  
     erl\_internal, 111  
  
 ukeymerge/3  
     lists, 233  
 ukeysort/2  
     lists, 233  
 umerge/1  
     lists, 233  
 umerge/2  
     lists, 234  
 umerge/3  
     lists, 234  
 umerge3/3  
     lists, 234  
 unfold/1  
     proplists, 272  
 uniform/0  
     random, 294  
 uniform/1  
     random, 294  
 uniform\_s/1  
     random, 295  
 uniform\_s/2  
     random, 295  
 union/1  
     gb\_sets, 169  
     ordsets, 257  
     sets, 302  
     sofs, 339  
 union/2  
     gb\_sets, 169  
     ordsets, 257  
     sets, 302  
     sofs, 339  
 union\_of\_family/1  
     sofs, 340  
 universal\_time/0  
     calendar, 70  
 universal\_time\_to\_local\_time/2  
     calendar, 71  
 unzip/1  
     lists, 234  
     zip, 374  
 unzip/2  
     zip, 374  
 unzip3/1  
     lists, 234  
 update/3  
     dict, 91  
     gb\_trees, 173  
     orddict, 254  
 update/4  
     dict, 91  
     orddict, 254  
 update\_counter/3  
     dets, 87  
     dict, 91  
     ets, 148  
     orddict, 254  
 update\_counter/4  
     ets, 148  
 update\_counter/6  
     ets, 148  
 usort/1  
     lists, 235  
 usort/2  
     lists, 235  
 valid\_date/1  
     calendar, 71  
 valid\_date/3  
     calendar, 71  
 value/2

- win32reg , 371
- values/1
  - gb\_trees , 174
  - win32reg , 371
- version/1
  - beam\_lib , 58
- vertex/2
  - digraph , 99
- vertices/1
  - digraph , 99
- weak\_relation/1
  - sofs , 340
- which\_children/1
  - supervisor , 352
- which\_handlers/1
  - gen\_event , 180
- wildcard/1
  - filelib , 156
- wildcard/2
  - filelib , 157
- win32reg
  - change\_key/2, 369
  - change\_key\_create/2, 369
  - close/1, 369
  - current\_key/1, 369
  - delete\_key/1, 369
  - delete\_value/2, 370
  - expand/1, 370
  - format\_error/1, 370
  - open/1, 370
  - set\_value/3, 370
  - sub\_keys/1, 371
  - value/2, 371
  - values/1, 371
- words/1
  - string , 343
- words/2
  - string , 343
- write/1
  - io\_lib , 216
- write/2
  - io , 206
  - io\_lib , 216
- write\_atom/1
  - io\_lib , 218
- write\_char/1
  - io\_lib , 218
- write\_string/1
  - io\_lib , 218
- xm/1
  - c , 66
- y/1
  - c , 66
- y/2
  - c , 66
- zip
  - create/2, 373
  - create/3, 373
  - extract/1, 374
  - extract/2, 374
  - list\_dir/1, 375
  - list\_dir/2, 375
  - t/1, 375
  - table/1, 375
  - table/2, 375
  - tt/1, 375
  - unzip/1, 374
  - unzip/2, 374
  - zip/2, 373
  - zip/3, 373
  - zip\_close/1, 376
  - zip\_get/1, 376
  - zip\_get/2, 376
  - zip\_list\_dir/1, 376
  - zip\_open/1, 375
  - zip\_open/2, 376
- zip/2
  - lists , 235
  - zip , 373
- zip/3
  - zip , 373
- zip3/3
  - lists , 235
- zip\_close/1
  - zip , 376
- zip\_get/1
  - zip , 376
- zip\_get/2
  - zip , 376
- zip\_list\_dir/1

*zip* , 376  
zip\_open/1  
    *zip* , 375  
zip\_open/2  
    *zip* , 376  
zipwith/3  
    *lists* , 236  
zipwith3/4  
    *lists* , 236

