

Linux SDK for UPnP Devices v1.4

Contents

1	Introduction	5
2	License	6
3	About Callbacks	7
4	The API	8
4.1	Error codes	8
4.1.1	UPNP_E_SUCCESS [0]	9
4.1.2	UPNP_E_INVALID_HANDLE [-100]	9
4.1.3	UPNP_E_INVALID_PARAM [-101]	10
4.1.4	UPNP_E_OUTOF_HANDLE [-102]	10
4.1.5	UPNP_E_OUTOF_MEMORY [-104]	10
4.1.6	UPNP_E_INIT [-105]	10
4.1.7	UPNP_E_INVALID_DESC [-107]	10
4.1.8	UPNP_E_INVALID_URL [-108]	11
4.1.9	UPNP_E_INVALID_SERVICE [-111]	11
4.1.10	UPNP_E_BAD_RESPONSE [-113]	11
4.1.11	UPNP_E_INVALID_ACTION [-115]	11
4.1.12	UPNP_E_FINISH [-116]	11
4.1.13	UPNP_E_INIT_FAILED [-117]	12
4.1.14	UPNP_E_BAD_	

4.2.9	Upnp_State_Var_Complete — <i>Represents the reply for the current value of a state variable in an asynchronous call.</i>	30
4.2.10	Upnp_Event — <i>Returned along with a UPNP_EVENT_RECEIVED callback.</i>	31
4.2.11	Upnp_Discovery — <i>Returned in a UPNP_DISCOVERY_RESULT callback.</i>	32
4.2.12	Upnp_Event_Subscribe — <i>Returned along with a UPNP_EVENT_SUBSCRIBE_COMPLETE or UPNP_EVENT_UNSUBSCRIBE_COMPLETE callback.</i>	35
4.2.13	Upnp_Subscription_Request — <i>Returned along with a UPNP_EVENT_SUBSCRIPTION_REQUEST callback.</i>	37
4.2.14	UpnpVirtualDirCallbacks — <i>The UpnpVirtualDirCallbacks structure contains the pointers to file-related callback functions a device application can register to virtualize URLs.</i>	38
4.3	Initialization and Registration	41
4.4	Discovery	51
4.5	Control	52
4.6	Eventing	61
4.7	Control Point HTTP API	80
4.8	Web Server API	92
5	Optional Tool APIs	97

Linux SDK for UPnP Devices Version 1.4

Copyright (C) 2000-2003 Intel Corporation ALL RIGHTS RESERVED

Revision 1.4.1 (Tue 04 Jul 2006 04:58:51 PM EEST)

Introduction

This document gives a brief description of the Linux SDK for UPnP Devices API. Section 1 covers the license under which the SDK is distributed. Section 2 talks about the callback functions used in many parts of the API. Finally, section 3 details the structures and functions that comprise the API.

The Linux SDK for UPnP Devices version 1.2 supports the following platforms:

- Linux* running on an Intel Architecture processor
- Linux running on an Intel StrongARM or XScale processor

* Other brands and names are the property of their respective owners.

License

Copyright (c) 2000-2003 Intel Corporation All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither name of Intel Corporation nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL INTEL OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

About Callbacks

The Linux SDK for UPnP Devices contains functions that generate asynchronous callbacks. To simplify the application callback functions, these callbacks are executed on a thread owned by the SDK itself. The SDK executes the application's callback function in a thread context so the application can allocate memory and preserve the information it needs. The application can also use standard thread synchronization methods to ensure data integrity. Due to the possibility of deadlock, the application cannot call back into the SDK during these callbacks unless explicitly noted. There is no restriction in calling into the operating system or any other application interfaces.

4

The API

Names

4.1	Error codes	8
4.2	Constants, Structures, and Types	16
4.3	Initialization and Registration	41
4.4	Discovery	51
4.5	Control	52
4.6	Eventing	61
4.7	Control Point HTTP API	80
4.8	Web Server API	92

4.1

Error codes

Names

4.1.1	UPNP_E_SUCCESS [0]	9
4.1.2	UPNP_E_INVALID_HANDLE [-100]	9
4.1.3	UPNP_E_INVALID_PARAM [-101]	10
4.1.4	UPNP_E_OUTOF_HANDLE [-102]	10
4.1.5	UPNP_E_OUTOF_MEMORY [-104]	10
4.1.6	UPNP_E_INIT [-105]	10
4.1.7	UPNP_E_INVALID_DESC [-107]	10
4.1.8	UPNP_E_INVALID_URL [-108]	11
4.1.9	UPNP_E_INVALID_SERVICE [-111]	11
4.1.10	UPNP_E_BAD_RESPONSE [-113]	11
4.1.11	UPNP_E_INVALID_ACTION [-115]	11
4.1.12	UPNP_E_FINISH [-116]	11
4.1.13	UPNP_E_INIT_FAILED [-117]	12
4.1.14	UPNP_E_BAD_HTTPMSG [-119]	

4.1.19	UPNP_E_SOCKET_BIND [-203]	13
4.1.20	UPNP_E_SOCKET_CONNECT [-204]	13
4.1.21	UPNP_E_OUTOF_SOCKET [-205]	13
4.1.22	UPNP_E_LISTEN [-206]	13
4.1.23	UPNP_E_TIMEOUT [-207]	14
4.1.24	UPNP_E_SOCKET_ERROR [-208]	14
4.1.25	UPNP_E_CANCELED [-210]	14
4.1.26	UPNP_E_SUBSCRIBE_UNACCEPTED [-301]	14
4.1.27	UPNP_E_UNSUBSCRIBE_UNACCEPTED [-302]	14
4.1.28	UPNP_E_NOTIFY_UNACCEPTED [-303]	14
4.1.29	UPNP_E_INVALID_ARGUMENT [-501]	15
4.1.30	UPNP_E_FILE_NOT_FOUND [-502]	15
4.1.31	UPNP_E_FILE_READ_ERROR [-503]	15
4.1.32	UPNP_E_EXT_NOT_XML [-504]	15
4.1.33	UPNP_E_NOT_FOUND [-507]	15
4.1.34	UPNP_E_INTERNAL_ERROR [-911]	15

The functions in the SDK API can return a variety of error codes to describe problems encountered during execution. This section lists the error codes and provides a brief description of what each error code means. Refer to the documentation for each function for a description of what an error code means in that context.

4.1.1

UPNP_E_SUCCESS [0]

UPNP_E_SUCCESS signifies that the operation completed successfully. For asynchronous functions, this only means that the packet generated by the operation was successfully transmitted on the network. The result of the entire operation comes as part of the callback for that operation.

4.1.2

UPNP_E_INVALID_HANDLE [-100]

UPNP_E_INVALID_HANDLE signifies that the handle passed to a function is not a recognized as a valid handle.

4.1.3**UPNP_E_INVALID_PARAM [-101]**

UPNP_E_INVALID_PARAM signifies that one or more of the parameters passed to the function is not valid. Refer to the documentation for each function for more information on the valid ranges of the parameters.

4.1.4**UPNP_E_OUTOF_HANDLE [-102]**

UPNP_E_OUTOF_HANDLE signifies that the SDK does not have any more space for additional handles. The SDK allocates space for only a few handles in order to conserve memory.

4.1.5**UPNP_E_OUTOF_MEMORY [-104]**

UPNP_E_OUTOF_MEMORY signifies that not enough resources are currently available to complete the operation. Most operations require some free memory in order to complete their work.

4.1.6**UPNP_E_INIT [-105]**

UPNP_E_INIT signifies that the SDK has already been initialized. The SDK needs to be initialized only once per process. Any additional initialization attempts simply return this error with no other ill effects.

4.1.7**UPNP_E_INVALID_DESC [-107]**

UPNP_E_INVALID_DESC signifies that the description document passed to **UpnpRegisterRootDevice** or **UpnpRegisterRootDevice2** is an invalid description document.

4.1.8**UPNP_E_INVALID_URL [-108]**

UPNP_E_INVALID_URL signifies that a URL passed into the function is invalid. The actual cause is function specific, but in general, the URL itself might be malformed (e.g. have invalid characters in it) or the host might be unreachable.

4.1.9**UPNP_E_INVALID_SERVICE [-111]**

UPNP_E_INVALID_SERVICE is returned only by **UpnpNotify**, **UpnpNotifyExt**, **UpnpAcceptSubscription**, and **UpnpAcceptSubscriptionExt** to signify that the device ID/service ID pair does not refer to a valid service.

4.1.10**UPNP_E_BAD_RESPONSE [-113]**

UPNP_E_BAD_RESPONSE signifies that the response received from the remote side of a connection is not correct for the protocol. This applies to the GENA, SOAP, and HTTP protocols.

4.1.11**UPNP_E_INVALID_ACTION [-115]**

UPNP_E_INVALID_ACTION signifies that the SOAP action message is invalid. This can be because the DOM document passed to the function was malformed or the action message is not correct for the given action.

4.1.12**UPNP_E_FINISH [-116]**

UPNP_E_FINISH signifies that **UpnpInit** has not been called, or that **UpnpFinish** has already been called. None of the API functions operate until **UpnpInit** successfully completes.

4.1.13**UPNP_E_INIT_FAILED [-117]**

UPNP_E_INIT_FAILED signifies that **UpnpInit** cannot complete. The typical reason is failure to allocate sufficient resources.

4.1.14**UPNP_E_BAD_HTTPMSG [-119]**

UPNP_E_BAD_HTTPMSG signifies that the HTTP message contains invalid message headers. The error always refers to the HTTP message header received from the remote host. The main areas where this occurs are in SOAP control messages (e.g. **UpnpSendAction**), GENA subscription message (e.g. **UpnpSubscribe**), GENA event notifications (e.g. **UpnpNotify**), and HTTP transfers (e.g. **UpnpDownloadXmlDoc**).

4.1.15**UPNP_E_ALREADY_REGISTERED [-120]**

UPNP_E_ALREADY_REGISTERED signifies that a client or a device is already registered. The SDK currently has a limit of one registered client and one registered device per process.

4.1.16**UPNP_E_NETWORK_ERROR [-200]**

UPNP_E_NETWORK_ERROR signifies that a network error occurred. It is the generic error code for network problems that are not covered under one of the more specific error codes. The typical meaning is the SDK failed to read the local IP address or had problems configuring one of the sockets.

4.1.17**UPNP_E_SOCKET_WRITE [-201]**

UPNP_E_SOCKET_WRITE signifies an error writing to a socket. This occurs in any function that makes network connections, such as discovery (e.g. **UpnpSearchAsync** or **UpnpSendAdvertisement**), control (e.g. **UpnpSendAction**), eventing (e.g. **UpnpNotify**), and HTTP functions (e.g. **UpnpDownloadXmlDoc**).

4.1.18**UPNP_E_SOCKET_READ [-202]**

UPNP_E_SOCKET_READ signifies an error reading from a socket. This occurs in any function that makes network connections, such as discovery (e.g. **UpnpSearchAsync** or **UpnpSendAdvertisement**), control (e.g. **UpnpSendAction**), eventing (e.g. **UpnpNotify**), and HTTP functions (e.g. **UpnpDownloadXmlDoc**).

4.1.19**UPNP_E_SOCKET_BIND [-203]**

UPNP_E_SOCKET_BIND signifies that the SDK had a problem binding a socket to a network interface. This occurs in any function that makes network connections, such as discovery (e.g. **UpnpSearchAsync** or **UpnpSendAdvertisement**), control (e.g. **UpnpSendAction**), eventing (e.g. **UpnpNotify**), and HTTP functions (e.g. **UpnpDownloadXmlDoc**).

4.1.20**UPNP_E_SOCKET_CONNECT [-204]**

UPNP_E_SOCKET_CONNECT signifies that the SDK had a problem connecting to a remote host. This occurs in any function that makes network connections, such as discovery (e.g. **UpnpSearchAsync** or **UpnpSendAdvertisement**), control (e.g. **UpnpSendAction**), eventing (e.g. **UpnpNotify**), and HTTP functions (e.g. **UpnpDownloadXmlDoc**).

4.1.21**UPNP_E_OUTOF_SOCKET [-205]**

UPNP_E_OUTOF_SOCKET signifies that the SDK cannot create any more sockets. This occurs in any function that makes network connections, such as discovery (e.g. **UpnpSearchAsync** or **UpnpSendAdvertisement**), control (e.g. **UpnpSendAction**), eventing (e.g. **UpnpNotify**), and HTTP functions (e.g. **UpnpDownloadXmlDoc**).

4.1.22**UPNP_E_LISTEN [-206]**

UPNP_E_LISTEN signifies that the SDK had a problem setting the socket to listen for incoming connections. This error only happens during initialization (i.e. **UpnpInit**).

4.1.23**UPNP_E_TIMEDOUT [-207]**

UPNP_E_TIMEDOUT signifies that too much time elapsed before the required number of bytes were sent or received over a socket. This error can be returned by any function that performs network operations.

4.1.24**UPNP_E_SOCKET_ERROR [-208]**

UPNP_E_SOCKET_ERROR is the generic socket error code for conditions not covered by other error codes. This error can be returned by any function that performs network operations.

4.1.25**UPNP_E_CANCELED [-210]**

UPNP_E_CANCELED signifies that the operation was canceled. This error can be returned by any function that allows for external cancelation.

4.1.26**UPNP_E_SUBSCRIBE_UNACCEPTED [-301]**

UPNP_E_SUBSCRIBE_UNACCEPTED signifies that a subscription request was rejected from the remote side.

4.1.27**UPNP_E_UNSUBSCRIBE_UNACCEPTED [-302]**

UPNP_E_UNSUBSCRIBE_UNACCEPTED signifies that an unsubscribe request was rejected from the remote side.

4.1.28**UPNP_E_NOTIFY_UNACCEPTED [-303]**

UPNP_E_NOTIFY_UNACCEPTED signifies that the remote host did not accept the notify sent from the local device.

4.1.29**UPNP_E_INVALID_ARGUMENT [-501]**

UPNP_E_INVALID_ARGUMENT signifies that one or more of the parameters passed to a function is invalid. Refer to the individual function descriptions for the acceptable ranges for parameters.

4.1.30**UPNP_E_FILE_NOT_FOUND [-502]**

UPNP_E_FILE_NOT_FOUND signifies that the filename passed to one of the device registration functions was not found or was not accessible.

4.1.31**UPNP_E_FILE_READ_ERROR [-503]**

UPNP_E_FILE_READ_ERROR signifies an error when reading a file.

4.1.32**UPNP_E_EXT_NOT_XML [-504]**

UPNP_E_EXT_NOT_XML signifies that the file name of the description document passed to **UpnpRegisterRootDevice2** does not end in ".xml".

4.1.33**UPNP_E_NOT_FOUND [-507]**

UPNP_E_NOT_FOUND signifies that the response to a SOAP request did not contain the required XML constructs.

4.1.34**UPNP_E_INTERNAL_ERROR [-911]**

UPNP_E_INTERNAL_ERROR is the generic error code for internal conditions not covered by other error codes.

4.2

Constants, Structures, and Types

Names

4.2.1	typedef int	UpnpClient_Handle	<i>Returned when a control point application registers with UpnpRegisterClient.</i> ..	17
4.2.2	typedef int	UpnpDevice_Handle	<i>Returned when a device application registers with UpnpRegisterRootDevice or UpnpRegisterRootDevice2.</i>	17
4.2.3	enum	UPnP_EventType	<i>The reason code for an event callback.</i>	17
4.2.4	typedef char	Upnp_SID[44]	<i>The Upnp_SID holds the subscription identifier for a subscription between a client and a device.</i>	22
4.2.5	enum	Upnp_SType	<i>Represents the different types of searches that can be performed using the SDK for UPnP Devices API.</i>	22
4.2.6	enum	Upnp_DescType	<i>Specifies the type of description in UpnpRegisterRootDevice2.</i>	24
4.2.7	struct	Upnp_Action_Request	<i>Returned as part of a UPNP_CONTROL_ACTION_COMPLETE callback.</i>	25
4.2.8	struct	Upnp_State_Var_Request	<i>Represents the request for current value of a state variable in a service state table.</i>	28
4.2.9	struct	Upnp_State_Var_Complete	<i>Represents the reply for the current value of a state variable in an asynchronous call.</i>	30
4.2.10	struct	Upnp_Event	<i>Returned along with a UPNP_EVENT_RECEIVED callback.</i>	31
4.2.11	struct	Upnp_Discovery	<i>Returned in a UPNP_DISCOVERY_RESULT callback.</i>	32
4.2.12	struct	Upnp_Event_Subscribe	<i>Returned along with a UPNP_EVENT_SUBSCRIBE_COMPLETE or UPNP_EVENT_UNSUBSCRIBE_COMPLETE callback.</i>	35
4.2.13	struct	Upnp_Subscription_Request	<i>Returned along with a UPNP_EVENT_SUBSCRIPTION_REQUEST callback.</i>	37
4.2.14	struct	UpnpVirtualDirCallbacks		

		<i>The UpnpVirtualDirCallbacks structure contains the pointers to file-related callback functions a device application can register to virtualize URLs.</i>	38
4.2.15	typedef int	(*Upnp_FunPtr) (IN Upnp_EventType EventType, IN void* Event, IN void* Cookie) <i>All callback functions share the same prototype, documented below.</i>	41

4.2.1

```
typedef int UpnpClient_Handle
```

*Returned when a control point application registers with **UpnpRegisterClient**.*

Returned when a control point application registers with **UpnpRegisterClient**. Client handles can only be used with functions that operate with a client handle.

4.2.2

```
typedef int UpnpDevice_Handle
```

*Returned when a device application registers with **UpnpRegisterRootDevice** or **UpnpRegisterRootDevice2**.*

Returned when a device application registers with **UpnpRegisterRootDevice** or **UpnpRegisterRootDevice2**. Device handles can only be used with functions that operate with a device handle.

4.2.3

```
enum UPnP_EventType
```

The reason code for an event callback.

Names

4.2.3.1	UPNP_CONTROL_ACTION_REQUEST	<i>Received by a device when a control point issues a control request.</i>	19
4.2.3.2	UPNP_CONTROL_ACTION_COMPLETE		

	<i>A UpnpSendActionAsync call completed.</i>	19
4.2.3.3	UPNP_CONTROL_GET_VAR_REQUEST <i>Received by a device when a query for a single service variable arrives.</i>	19
4.2.3.4	UPNP_CONTROL_GET_VAR_COMPLETE <i>A UpnpGetServiceVarStatus call completed.</i>	19
4.2.3.5	UPNP_DISCOVERY_ADVERTISEMENT_ALIVE <i>Received by a control point when a new device or service is available.</i>	19
4.2.3.6	UPNP_DISCOVERY_ADVERTISEMENT_BYEBYE <i>Received by a control point when a device or service shuts down.</i>	20
4.2.3.7	UPNP_DISCOVERY_SEARCH_RESULT <i>Received by a control point when a matching device or service responds.</i>	20
4.2.3.8	UPNP_DISCOVERY_SEARCH_TIMEOUT <i>Received by a control point when the search timeout expires.</i>	20
4.2.3.9	UPNP_EVENT_SUBSCRIPTION_REQUEST <i>Received by a device when a subscription arrives.</i>	20
4.2.3.10	UPNP_EVENT_RECEIVED <i>Received by a control point when an event arrives.</i>	21
4.2.3.11	UPNP_EVENT_RENEWAL_COMPLETE <i>A UpnpRenewSubscriptionAsync call completed.</i>	21
4.2.3.12	UPNP_EVENT_SUBSCRIBE_COMPLETE <i>A UpnpSubscribeAsync call completed.</i>	21
4.2.3.13	UPNP_EVENT_UNSUBSCRIBE_COMPLETE <i>A UpnpUnSubscribeAsync call completed.</i>	21
4.2.3.14	UPNP_EVENT_AUTORENEWAL_FAILED <i>The auto-renewal of a client subscription failed.</i>	22
4.2.3.15	UPNP_EVENT_SUBSCRIPTION_EXPIRED <i>A client subscription has expired.</i>	22

The **Event** parameter will be different depending on the reason for the callback. The descriptions for each event type describe the contents of the **Event** parameter.

4.2.3.1

UPNP_CONTROL_ACTION_REQUEST

Received by a device when a control point issues a control request.

Received by a device when a control point issues a control request. The **Event** parameter contains a pointer to a **Upnp_Action_Request** structure containing the action. The application stores the results of the action in this structure.

4.2.3.2

UPNP_CONTROL_ACTION_COMPLETE

*A **UpnpSendActionAsync** call completed.*

A **UpnpSendActionAsync** call completed. The **Event** parameter contains a pointer to a **Upnp_Action_Complete** structure with the results of the action.

4.2.3.3

UPNP_CONTROL_GET_VAR_REQUEST

Received by a device when a query for a single service variable arrives.

Received by a device when a query for a single service variable arrives. The **Event** parameter contains a pointer to a **Upnp_State_Var_Request** structure containing the name of the variable and value.

4.2.3.4

UPNP_CONTROL_GET_VAR_COMPLETE

*A **UpnpGetServiceVarStatus** call completed.*

A **UpnpGetServiceVarStatus** call completed. The **Event** parameter contains a pointer to a **Upnp_State_Var_Complete** structure containing the value for the variable.

4.2.3.5

UPNP_DISCOVERY_ADVERTISEMENT_ALIVE

Received by a control point when a new device or service is available.

Received by a control point when a new device or service is available. The **Event** parameter contains a pointer to a **Upnp_Discovery** structure with the information about the device or service.

4.2.3.6**UPNP_DISCOVERY_ADVERTISEMENT_BYEBYE**

Received by a control point when a device or service shuts down.

Received by a control point when a device or service shuts down. The **Event** parameter contains a pointer to a **Upnp_Discovery** structure containing the information about the device or service.

4.2.3.7**UPNP_DISCOVERY_SEARCH_RESULT**

Received by a control point when a matching device or service responds.

Received by a control point when a matching device or service responds. The **Event** parameter contains a pointer to a **Upnp_Discovery** structure containing the information about the reply to the search request.

4.2.3.8**UPNP_DISCOVERY_SEARCH_TIMEOUT**

Received by a control point when the search timeout expires.

Received by a control point when the search timeout expires. The SDK generates no more callbacks for this search after this event. The **Event** parameter is NULL.

4.2.3.9**UPNP_EVENT_SUBSCRIPTION_REQUEST**

Received by a device when a subscription arrives.

Received by a device when a subscription arrives. The **Event** parameter contains a pointer to a **Upnp_Subscription_Request** structure. At this point, the subscription has already been accepted. **UpnpAcceptSubscription** needs to be called to confirm the subscription and transmit the initial state table. This can be done during this callback. The SDK generates no events for a subscription unless the device application calls **UpnpAcceptSubscription**.

4.2.3.10**UPNP_EVENT_RECEIVED**

Received by a control point when an event arrives.

Received by a control point when an event arrives. The **Event** parameter contains a **Upnp_Event** structure with the information about the event.

4.2.3.11**UPNP_EVENT_RENEWAL_COMPLETE**

*A **UpnpRenewSubscriptionAsync** call completed.*

A **UpnpRenewSubscriptionAsync** call completed. The status of the renewal is in the **Event** parameter as a **Upnp_Event_Subscription** structure.

4.2.3.12**UPNP_EVENT_SUBSCRIBE_COMPLETE**

*A **UpnpSubscribeAsync** call completed.*

A **UpnpSubscribeAsync** call completed. The status of the subscription is in the **Event** parameter as a **Upnp_Event_Subscription** structure.

4.2.3.13**UPNP_EVENT_UNSUBSCRIBE_COMPLETE**

*A **UpnpUnSubscribeAsync** call completed.*

A **UpnpUnSubscribeAsync** call completed. The status of the subscription is in the **Event** parameter as a **Upnp_Event_Subscribe** structure.

4.2.3.14**UPNP_EVENT_AUTORENEWAL_FAILED**

The auto-renewal of a client subscription failed.

The auto-renewal of a client subscription failed. The **Event** parameter is a **Upnp_Event_Subscribe** structure with the error code set appropriately. The subscription is no longer valid.

4.2.3.15**UPNP_EVENT_SUBSCRIPTION_EXPIRED**

A client subscription has expired.

A client subscription has expired. This will only occur if auto-renewal of subscriptions is disabled. The **Event** parameter is a **Upnp_Event_Subscribe** structure. The subscription is no longer valid.

4.2.4

```
typedef char Upnp_SID[44]
```

*The **Upnp_SID** holds the subscription identifier for a subscription between a client and a device.*

The **Upnp_SID** holds the subscription identifier for a subscription between a client and a device. The SID is a string representation of a globally unique id (GUID) and should not be modified.

4.2.5

```
enum Upnp_SType
```

Represents the different types of searches that can be performed using the SDK for UPnP Devices API.

Names

4.2.5.1	UPNP_S_ALL	<i>Search for all devices and services on the network.</i>	23
4.2.5.2	UPNP_S_ROOT	<i>Search for all root devices on the network.</i>	23
4.2.5.3	UPNP_S_DEVICE	<i>Search for a particular device type or a particular device instance.</i>	23
4.2.5.4	UPNP_S_SERVICE	<i>Search for a particular service type, possibly on a particular device type or device instance.</i>	24

By specifying these different values to **UpnpSearchAsync**, the control point application can control the scope of the search from all devices to specific devices or services.

4.2.5.1**UPNP_S_ALL**

Search for all devices and services on the network.

Search for all devices and services on the network.

4.2.5.2**UPNP_S_ROOT**

Search for all root devices on the network.

Search for all root devices on the network.

4.2.5.3**UPNP_S_DEVICE**

Search for a particular device type or a particular device instance.

Search for a particular device type or a particular device instance.

4.2.5.4

UPNP_S_SERVICE

Search for a particular service type, possibly on a particular device type or device instance.

Search for a particular service type, possibly on a particular device type or device instance.

4.2.6

enum **Upnp_DescType**

*Specifies the type of description in **UpnpRegisterRootDevice2**.*

Names

4.2.6.1	UPNPREG_URL_DESC	<i>The description is the URL to the description document.</i>	24
4.2.6.2	UPNPREG_FILENAME_DESC	<i>The description is a file name on the local file system containing the description of the device.</i>	25
4.2.6.3	UPNPREG_BUF_DESC	<i>The description is a pointer to a character array containing the XML description document.</i>	25

These values control how **UpnpRegisterRootDevice2** interprets the **description** parameter.

4.2.6.1

UPNPREG_URL_DESC

The description is the URL to the description document.

The description is the URL to the description document.

4.2.6.2

UPNPREG_FILENAME_DESC

The description is a file name on the local file system containing the description of the device.

The description is a file name on the local file system containing the description of the device.

4.2.6.3

UPNPREG_BUF_DESC

The description is a pointer to a character array containing the XML description document.

The description is a pointer to a character array containing the XML description document.

4.2.7

struct Upnp_Action_Request

Returned as part of a UPNP_CONTROL_ACTION_COMPLETE callback.

Members

4.2.7.1	int	ErrCode	<i>The result of the operation.</i>	26
4.2.7.2	int	Socket	<i>The socket number of the connection to the requestor.</i>	26
4.2.7.3	char	ErrStr [LINE_SIZE]	<i>The error string in case of error.</i>	26
4.2.7.4	char	ActionName [NAME_SIZE]	<i>The Action Name.</i>	26
4.2.7.5	char	DevUDN [NAME_SIZE]	<i>The unique device ID.</i>	27
4.2.7.6	char	ServiceID [NAME_SIZE]	<i>The service ID.</i>	27
4.2.7.7	IXML_Document*	ActionRequest	<i>The DOM document describing the action.</i>	27
4.2.7.8	IXML_Document*	ActionResult	<i>The DOM document describing the result of the action.</i>	27
4.2.7.9	struct	in_addr		

	CtrlPtIPAddr	<i>IP address of the control point requesting this action.</i>	27
4.2.7.10	IXML_Document*		
	SoapHeader	<i>The DOM document containing the information from the the SOAP header.</i>	28

Returned as part of a **UPNP_CONTROL_ACTION_COMPLETE** callback.

4.2.7.1

int **ErrCode**

The result of the operation.

The result of the operation.

4.2.7.2

int **Socket**

The socket number of the connection to the requestor.

The socket number of the connection to the requestor.

4.2.7.3

char **ErrStr** [LINE_SIZE]

The error string in case of error.

The error string in case of error.

4.2.7.4

char **ActionName** [NAME_SIZE]

The Action Name.

The Action Name.

4.2.7.5

```
char DevUDN [NAME_SIZE]
```

The unique device ID.

The unique device ID.

4.2.7.6

```
char ServiceID [NAME_SIZE]
```

The service ID.

The service ID.

4.2.7.7

```
IXML_Document* ActionRequest
```

The DOM document describing the action.

The DOM document describing the action.

4.2.7.8

```
IXML_Document* ActionResult
```

The DOM document describing the result of the action.

The DOM document describing the result of the action.

4.2.7.9

```
struct in_addr CtrlPtIPAddr
```

IP address of the control point requesting this action.

IP address of the control point requesting this action.

4.2.7.10

IXML_Document* **SoapHeader**

The DOM document containing the information from the the SOAP header.

The DOM document containing the information from the the SOAP header.

4.2.8

struct Upnp_State_Var_Request

Represents the request for current value of a state variable in a service state table.

Members

4.2.8.1	int	ErrCode	<i>The result of the operation.</i>	28
4.2.8.2	int	Socket	<i>The socket number of the connection to the requestor.</i>	29
4.2.8.3	char	ErrStr [LINE_SIZE]	<i>The error string in case of error.</i>	29
4.2.8.4	char	DevUDN [NAME_SIZE]	<i>The unique device ID.</i>	29
4.2.8.5	char	ServiceID [NAME_SIZE]	<i>The service ID.</i>	29
4.2.8.6	char	StateVarName [NAME_SIZE]	<i>The name of the variable.</i>	29
4.2.8.7	struct in_addr	CtrlPtIPAddr	<i>IP address of sender requesting the state variable.</i>	30
4.2.8.8	DOMString	CurrentVal	<i>The current value of the variable.</i>	30

Represents the request for current value of a state variable in a service state table.

4.2.8.1

int ErrCode

The result of the operation.

The result of the operation.

4.2.8.2

`int Socket`

The socket number of the connection to the requestor.

The socket number of the connection to the requestor.

4.2.8.3

`char ErrStr [LINE_SIZE]`

The error string in case of error.

The error string in case of error.

4.2.8.4

`char DevUDN [NAME_SIZE]`

The unique device ID.

The unique device ID.

4.2.8.5

`char ServiceID [NAME_SIZE]`

The service ID.

The service ID.

4.2.8.6

`char StateVarName [NAME_SIZE]`

The name of the variable.

The name of the variable.

4.2.8.7

```
struct in_addr CtrlPtIPAddr
```

IP address of sender requesting the state variable.

IP address of sender requesting the state variable.

4.2.8.8

```
DOMString CurrentVal
```

The current value of the variable.

The current value of the variable. This needs to be allocated by the caller. When finished with it, the SDK frees this **DOMString**.

4.2.9

```
struct Upnp_State_Var_Complete
```

Represents the reply for the current value of a state variable in an asynchronous call.

Members

4.2.9.1	int	ErrCode	<i>The result of the operation.</i>	30
4.2.9.2	char	CtrlUrl [NAME_SIZE]	<i>The control URL for the service.</i>	31
4.2.9.3	char	StateVarName [NAME_SIZE]	<i>The name of the variable.</i>	31
4.2.9.4	DOMString	CurrentVal	<i>The current value of the variable or error string in case of error.</i>	31

Represents the reply for the current value of a state variable in an asynchronous call.

4.2.9.1

```
int ErrCode
```

The result of the operation.

The result of the operation.

4.2.9.2

```
char CtrlUrl [NAME_SIZE]
```

The control URL for the service.

The control URL for the service.

4.2.9.3

```
char StateVarName [NAME_SIZE]
```

The name of the variable.

The name of the variable.

4.2.9.4

```
DOMString CurrentVal
```

The current value of the variable or error string in case of error.

The current value of the variable or error string in case of error.

4.2.10

```
struct Upnp_Event
```

*Returned along with a **UPNP_EVENT_RECEIVED** callback.*

Members

4.2.10.1	Upnp_SID	Sid	<i>The subscription ID for this subscription.</i>	
			32
4.2.10.2	int	EventKey	<i>The event sequence number.</i>	32
4.2.10.3	IXML_Document*	ChangedVariables	<i>The DOM tree representing the changes generating the event.</i>	32

Returned along with a **UPNP_EVENT_RECEIVED** callback.

4.2.10.1**Upnp_SID Sid**

The subscription ID for this subscription.

			<i>The service type.</i>	34
4.2.11.6	char	ServiceVer [LINE_SIZE]	<i>The service version.</i>	34
4.2.11.7	char	Location [LINE_SIZE]	<i>The URL to the UPnP description document for the device.</i>	34
4.2.11.8	char	Os [LINE_SIZE]	<i>The operating system the device is running.</i>	34
4.2.11.9	char	Date [LINE_SIZE]	<i>Date when the response was generated. .</i>	35
4.2.11.10	char	Ext [LINE_SIZE]	<i>Confirmation that the MAN header was understood by the device.</i>	35
4.2.11.11	SOCKADDRIN*	DestAddr	<i>The host address of the device responding to the search.</i>	35

Returned in a **UPNP_DISCOVERY_RESULT** callback.

4.2.11.1

int **ErrCode**

*The result code of the **UpnpSearchAsync** call.*

The result code of the **UpnpSearchAsync** call.

4.2.11.2

int **Expires**

The expiration time of the advertisement.

The expiration time of the advertisement.

4.2.11.3

char **DeviceId** [LINE_SIZE]

The unique device identifier.

The unique device identifier.

4.2.11.4

`char DeviceType [LINE_SIZE]`

The device type.

The device type.

4.2.11.5

`char ServiceType [LINE_SIZE]`

The service type.

The service type.

4.2.11.6

`char ServiceVer [LINE_SIZE]`

The service version.

The service version.

4.2.11.7

`char Location [LINE_SIZE]`

The URL to the UPnP description document for the device.

The URL to the UPnP description document for the device.

4.2.11.8

`char Os [LINE_SIZE]`

The operating system the device is running.

The operating system the device is running.

4.2.11.9

```
char Date [LINE_SIZE]
```

Date when the response was generated.

Date when the response was generated.

4.2.11.10

```
char Ext [LINE_SIZE]
```

Confirmation that the MAN header was understood by the device.

Confirmation that the MAN header was understood by the device.

4.2.11.11

```
SOCKADDRIN* DestAddr
```

The host address of the device responding to the search.

The host address of the device responding to the search.

4.2.12

```
struct Upnp_Event_Subscribe
```

*Returned along with a **UPNP_EVENT_SUBSCRIBE_COMPLETE** or **UPNP_EVENT_UNSUBSCRIBE_COMPLETE** callback.*

Members

4.2.12.1	Upnp_SID	Sid	<i>The SID for this subscription.</i>	36
4.2.12.2	int	ErrCode	<i>The result of the operation.</i>	36
4.2.12.3	char	PublisherUrl [NAME_SIZE]	<i>The event URL being subscribed to or removed from.</i>	36
4.2.12.4	int	TimeOut	<i>The actual subscription time (for subscriptions only).</i>	36

Returned along with a **UPNP_EVENT_SUBSCRIBE_COMPLETE** or **UPNP_EVENT_UNSUBSCRIBE_COMPLETE** callback.

4.2.12.1

`Upnp_SID Sid`

The SID for this subscription.

The SID for this subscription. For subscriptions, this only contains a valid SID if the **Upnp_EventSubscribe.result** field contains a UPNP_E_SUCCESS result code. For unsubscriptions, this contains the SID from which the subscription is being unsubscribed.

4.2.12.2

`int ErrCode`

The result of the operation.

The result of the operation.

4.2.12.3

`char PublisherUrl [NAME_SIZE]`

The event URL being subscribed to or removed from.

The event URL being subscribed to or removed from.

4.2.12.4

`int TimeOut`

The actual subscription time (for subscriptions only).

The actual subscription time (for subscriptions only).

4.2.13

```
struct Upnp_Subscription_Request
```

*Returned along with a **UPNP_EVENT_SUBSCRIPTION_REQUEST** callback.*

Members

4.2.13.1	char*	ServiceId	<i>The identifier for the service being subscribed to.</i>	37
4.2.13.2	char*	UDN	<i>Universal device name.</i>	37
4.2.13.3	Upnp_SID	Sid	<i>The assigned subscription ID for this subscription.</i>	37

Returned along with a **UPNP_EVENT_SUBSCRIPTION_REQUEST** callback.

4.2.13.1

```
char* ServiceId
```

The identifier for the service being subscribed to.

The identifier for the service being subscribed to.

4.2.13.2

```
char* UDN
```

Universal device name.

Universal device name.

4.2.13.3

```
Upnp_SID Sid
```

The assigned subscription ID for this subscription.

The assigned subscription ID for this subscription.

4.2.14

```
struct UpnpVirtualDirCallbacks
```

The **UpnpVirtualDirCallbacks** structure contains the pointers to file-related callback functions a device application can register to virtualize URLs.

Members

4.2.14.1	int	(*get_info) (IN const char* filename, OUT struct File_Info* info) <i>Called by the web server to query information on a file.</i>	38
4.2.14.2	UpnpWebFileHandle	(*open) (IN const char* filename, IN enum UpnpOpenFileMode Mode) <i>Called by the web server to open a file. .</i>	39
4.2.14.3	int	(*read) (IN UpnpWebFileHandle fileHnd, OUT char* buf, IN size_t buflen) <i>Called by the web server to perform a sequential read from an open file.</i>	39
4.2.14.4	int	(*write) (IN UpnpWebFileHandle fileHnd, IN char* buf, IN size_t buflen) <i>Called by the web server to perform a sequential write to an open file.</i>	40
4.2.14.5	int	(*seek) (IN UpnpWebFileHandle fileHnd, IN long offset, IN int origin) <i>Called by the web server to move the file pointer, or offset, into an open file. ...</i>	40
4.2.14.6	int	(*close) (IN UpnpWebFileHandle fileHnd) <i>Called by the web server to close a file opened via the open callback.</i>	40

The **UpnpVirtualDirCallbacks** structure contains the pointers to file-related callback functions a device application can register to virtualize URLs.

4.2.14.1

```
int (*get_info) ( IN const char* filename, OUT struct File_Info* info )
```

Called by the web server to query information on a file.

Called by the web server to query information on a file. The callback should return 0 on success or -1 on an error.

Parameters:

filename	The name of the file to query.
info	Pointer to a structure to store the information on the file.

4.2.14.2

```
UpnpWebFileHandle (*open) ( IN const char* filename, IN enum Upnp-
                             pOpenFileMode Mode )
```

Called by the web server to open a file.

Called by the web server to open a file. The callback should return a valid handle if the file can be opened. Otherwise, it should return NULL to signify an error.

Parameters:

<code>filename</code>	The name of the file to open.
<code>Mode</code>	The mode in which to open the file. Valid values are UPNP_READ or UPNP_WRITE.

4.2.14.3

```
int (*read) ( IN UpnpWebFileHandle fileHnd, OUT char* buf, IN size_t
              buflen )
```

Called by the web server to perform a sequential read from an open file.

Called by the web server to perform a sequential read from an open file. The callback should copy **buflen** bytes from the file into the buffer.

Return Value:

<code>[int]</code>	An integer representing one of the following:
--------------------	---

- 0: The file contains no more data (EOF).
- >0: A successful read of the number of bytes in the return code.
- <0: An error occurred reading the file.

Parameters:

<code>fileHnd</code>	The handle of the file to read.
<code>buf</code>	The buffer in which to place the data.
<code>buflen</code>	The size of the buffer (i.e. the number of bytes to read).

4.2.14.4

```
int (*write) ( IN UpnpWebFileHandle fileHnd, IN char* buf, IN size_t
               buflen )
```

Called by the web server to perform a sequential write to an open file.

Called by the web server to perform a sequential write to an open file. The callback should write **buflen** bytes into the file from the buffer. It should return the actual number of bytes written, which might be less than **buflen** in the case of a write error.

Parameters:

<code>fileHnd</code>	The handle of the file to write.
<code>buf</code>	The buffer with the bytes to write.
<code>buflen</code>	The number of bytes to write.

4.2.14.5

```
int (*seek) ( IN UpnpWebFileHandle fileHnd, IN long offset, IN int origin
              )
```

Called by the web server to move the file pointer, or offset, into an open file.

Called by the web server to move the file pointer, or offset, into an open file. The **origin** parameter determines where to start moving the file pointer. A value of `SEEK_CUR` moves the file pointer relative to where it is. The **offset** parameter can be either positive (move forward) or negative (move backward). `SEEK_END` moves relative to the end of the file. A positive **offset** extends the file. A negative **offset** moves backward in the file. Finally, `SEEK_SET` moves to an absolute position in the file. In this case, **offset** must be positive. The callback should return 0 on a successful seek or a non-zero value on an error.

Parameters:

<code>fileHnd</code>	The handle of the file to move the file pointer.
<code>offset</code>	The number of bytes to move in the file. Positive values move forward and negative values move backward. Note that this must be positive if the origin is <code>SEEK_SET</code> .
<code>origin</code>	The position to move relative to. It can be <code>SEEK_CUR</code> to move relative to the current position, <code>SEEK_END</code> to move relative to the end of the file, or <code>SEEK_SET</code> to specify an absolute offset.

4.2.14.6

```
int (*close) ( IN UpnpWebFileHandle fileHnd )
```

*Called by the web server to close a file opened via the **open** callback.*

Called by the web server to close a file opened via the **open** callback. It should return 0 on success, or a non-zero value on an error.

Parameters:

<code>fileHnd</code>	The handle of the file to close.
----------------------	----------------------------------

4.2.15

```
typedef int (*Upnp_FunPtr) ( IN Upnp_EventType EventType, IN void*
                             Event, IN void* Cookie )
```

All callback functions share the same prototype, documented below.

All callback functions share the same prototype, documented below. Note that any memory passed to the callback function is valid only during the callback and should be copied if it needs to persist. This callback function needs to be thread safe. The context of the callback is always on a valid thread context and standard synchronization methods can be used. Note, however, because of this the callback cannot call SDK functions unless explicitly noted.

```
int CallbackFxn( Upnp_EventType EventType, void* Event, void* Cookie );
```

where **EventType** is the event that triggered the callback, **Event** is a structure that denotes event-specific information for that event, and **Cookie** is the user data passed when the callback was registered.

See **Upnp_EventType** for more information on the callback values and the associated **Event** parameter.

The return value of the callback is currently ignored. It may be used in the future to communicate results back to the SDK.

4.3

Initialization and Registration

Names

- | | | | | |
|-------|----------------------------|--|---|----|
| 4.3.1 | EXPORT_SPEC int | UpnpInit (IN const char* HostIP,
IN unsigned short DestPort) | <i>Initializes the Linux SDK for UPnP Devices.</i> | 43 |
| 4.3.2 | EXPORT_SPEC int | UpnpFinish () | <i>Terminates the Linux SDK for UPnP Devices.</i> | 44 |
| 4.3.3 | EXPORT_SPEC unsigned short | UpnpGetServerPort (void) | <i>If '0' is used as the port number in UpnpInit, then this function can be used to retrieve the actual port allocated to the SDK.</i> | 44 |
| 4.3.4 | EXPORT_SPEC char* | | | |

	UpnpGetServerIpAddress (void)	<i>If NULL is used as the IP address in UpnpInit, then this function can be used to retrieve the actual interface address on which device is running.</i>	44
4.3.5	EXPORT_SPEC int UpnpRegisterClient (IN Upnp_FunPtr Callback, IN const void* Cookie, OUT UpnpClient_Handle* Hnd) UpnpRegisterClient registers a control point application with the SDK.		45
4.3.6	EXPORT_SPEC int UpnpRegisterRootDevice (IN const char* DescUrl, IN Upnp_FunPtr Callback, IN const void* Cookie, OUT UpnpDevice_Handle* Hnd) UpnpRegisterRootDevice registers a device application with the SDK.		45
4.3.7	EXPORT_SPEC int UpnpRegisterRootDevice2 (IN Upnp_DescType descriptionType, IN const char* description, IN size_t bufferLen, IN int config_baseURL, IN Upnp_FunPtr Fun, IN const void* Cookie, OUT UpnpDevice_Handle* Hnd) UpnpRegisterRootDevice2 is similar to UpnpRegisterRootDevice , except that it also allows the description docu- ment to be specified as a file or a memory buffer.		47
4.3.8	EXPORT_SPEC int UpnpUnRegisterClient (IN UpnpClient_Handle Hnd) UpnpUnRegisterClient unregisters a control point application, unsubscribing all active subscriptions.		49
4.3.9	EXPORT_SPEC int UpnpUnRegisterRootDevice (IN UpnpDevice_Handle) <i>Unregisters a root device registered with UpnpRegisterRootDevice or UpnpRegisterRootDevice2.</i>		50
4.3.10	EXPORT_SPEC int UpnpSetContentLength (IN UpnpClient_Handle Hnd, IN int contentLength) <i>OBSOLETE METHOD : use UpnpSet- MaxContentLength instead.</i>		50
4.3.11	EXPORT_SPEC int		

UpnpSetMaxContentLength (IN size_t contentLength)
Sets the maximum content-length that the SDK will process on an incoming SOAP requests or responses. 50

4.3.1

EXPORT_SPEC int UpnpInit (IN const char* HostIP, IN unsigned short DestPort)

Initializes the Linux SDK for UPnP Devices.

Initializes the Linux SDK for UPnP Devices. This function must be called before any other API function can be called. It should be called only once. Subsequent calls to this API return a UPNP_E_INIT error code.

Optionally, the application can specify a host IP address (in the case of a multi-homed configuration) and a port number to use for all UPnP operations. Since a port number can be used only by one process, multiple processes using the SDK must specify different port numbers.

If unspecified, the SDK will use the first adapter's IP address and an arbitrary port.

This call is synchronous.

Return Value: [int] An integer representing one of the following:

- UPNP_E_SUCCESS: The operation completed successfully.
- UPNP_E_OUTOF_MEMORY: Insufficient resources exist to initialize the SDK.
- UPNP_E_INIT: The SDK is already initialized.
- UPNP_E_INIT_FAILED: The SDK initialization failed for an unknown reason.
- UPNP_E_SOCKET_BIND: An error occurred binding a socket.
- UPNP_E_LISTEN: An error occurred listening to a socket.
- UPNP_E_OUTOF_SOCKET: An error occurred creating a socket.
- UPNP_E_INTERNAL_ERROR: An internal error occurred.

Parameters:

HostIP	The host IP address to use, in string format, for example "192.168.0.1", or NULL to use the first adapter's IP address.
DestPort	The destination port number to use. 0 will pick an arbitrary free port.

4.3.2

```
EXPORT_SPEC int UpnpFinish ()
```

Terminates the Linux SDK for UPnP Devices.

Terminates the Linux SDK for UPnP Devices. This function must be the last API function called. It should be called only once. Subsequent calls to this API return a UPNP_E_FINISH error code.

Return Value: [int] An integer representing one of the following:

- UPNP_E_SUCCESS: The operation completed successfully.
- UPNP_E_FINISH: The SDK is already terminated or it is not initialized.

4.3.3

```
EXPORT_SPEC unsigned short UpnpGetServerPort (void)
```

If '0' is used as the port number in UpnpInit, then this function can be used to retrieve the actual port allocated to the SDK.

If '0' is used as the port number in **UpnpInit**, then this function can be used to retrieve the actual port allocated to the SDK. If **UpnpInit** has not succeeded then 0 is returned.

Return Value: [unsigned short] The port on which an internal server is listening for UPnP related requests.

4.3.4

```
EXPORT_SPEC char* UpnpGetServerIpAddress (void)
```

If NULL is used as the IP address in UpnpInit, then this function can be used to retrieve the actual interface address on which device is running.

If NULL is used as the IP address in **UpnpInit**, then this function can be used to retrieve the actual interface address on which device is running.

4.3.5

```
EXPORT_SPEC int UpnpRegisterClient ( IN Upnp_FunPtr Callback,
                                     IN const void* Cookie, OUT
                                     UpnpClient_Handle* Hnd )
```

UpnpRegisterClient registers a control point application with the SDK.

UpnpRegisterClient registers a control point application with the SDK. A control point application cannot make any other API calls until it registers using this function.

UpnpRegisterClient is a synchronous call and generates no callbacks. Callbacks can occur as soon as this function returns.

Return Value: [int] An integer representing one of the following:

- UPNP_E_SUCCESS: The operation completed successfully.
- UPNP_E_FINISH: The SDK is already terminated or is not initialized.
- UPNP_E_INVALID_PARAM: Either **Callback** or **Hnd** is not a valid pointer.
- UPNP_E_OUTOF_MEMORY: Insufficient resources exist to register this control point.

Parameters:

Callback	Pointer to a function for receiving asynchronous events.
Cookie	Pointer to user data returned with the callback function when invoked.
Hnd	Pointer to a variable to store the new control point handle.

4.3.6

```
EXPORT_SPEC int UpnpRegisterRootDevice ( IN const char* DescUrl,
                                           IN Upnp_FunPtr
                                           Callback, IN const void*
                                           Cookie, OUT UpnpDevice_Handle* Hnd )
```

UpnpRegisterRootDevice registers a device application with the SDK.

UpnpRegisterRootDevice registers a device application with the SDK. A device application cannot make any other API calls until it registers using this function. Device applications can

also register as control points (see **UpnpRegisterClient** to get a control point handle to perform control point functionality).

UpnpRegisterRootDevice is synchronous and does not generate any callbacks. Callbacks can occur as soon as this function returns.

Return Value: [int] An integer representing one of the following:

- **UPNP_E_SUCCESS**: The operation completed successfully.
- **UPNP_E_FINISH**: The SDK is already terminated or is not initialized.
- **UPNP_E_INVALID_DESC**: The description document was not a valid device description.
- **UPNP_E_INVALID_URL**: The URL for the description document is not valid.
- **UPNP_E_INVALID_PARAM**: Either **Callback** or **Hnd** is not a valid pointer or **DescURL** is NULL.
- **UPNP_E_NETWORK_ERROR**: A network error occurred.
- **UPNP_E_SOCKET_WRITE**: An error or timeout occurred writing to a socket.
- **UPNP_E_SOCKET_READ**: An error or timeout occurred reading from a socket.
- **UPNP_E_SOCKET_BIND**: An error occurred binding a socket.
- **UPNP_E_SOCKET_CONNECT**: An error occurred connecting the socket.
- **UPNP_E_OUTOF_SOCKET**: Too many sockets are currently allocated.
- **UPNP_E_OUTOF_MEMORY**: There are insufficient resources to register this root device.

Parameters:

DescUrl	Pointer to a string containing the description URL for this root device instance.
Callback	Pointer to the callback function for receiving asynchronous events.
Cookie	Pointer to user data returned with the callback function when invoked.
Hnd	Pointer to a variable to store the new device handle.

4.3.7

```
EXPORT_SPEC int UpnpRegisterRootDevice2 ( IN  Upnp_DescType
                                           descriptionType,  IN
                                           const char* description,
                                           IN size_t bufferLen, IN
                                           int    config_baseURL,
                                           IN      Upnp_FunPtr
                                           Fun,  IN const void*
                                           Cookie, OUT Upn-
                                           pDevice_Handle* Hnd
                                           )
```

UpnpRegisterRootDevice2 *is similar to UpnpRegisterRootDevice, except that it also allows the description document to be specified as a file or a memory buffer.*

UpnpRegisterRootDevice2 is similar to **UpnpRegisterRootDevice**

Return Value:**[int]** An integer representing one of the following:

- **UPNP_E_SUCCESS**: The operation completed successfully.
- **UPNP_E_FINISH**: The SDK is already terminated or is not initialized.
- **UPNP_E_INVALID_DESC**: The description document is not a valid device description.
- **UPNP_E_INVALID_PARAM**: Either **Callback** or **Hnd** is not a valid pointer or **DescURL** is NULL.
- **UPNP_E_NETWORK_ERROR**: A network error occurred.
- **UPNP_E_SOCKET_WRITE**: An error or timeout occurred writing to a socket.
- **UPNP_E_SOCKET_READ**: An error or timeout occurred reading from a socket.
- **UPNP_E_SOCKET_BIND**: An error occurred binding a socket.
- **UPNP_E_SOCKET_CONNECT**: An error occurred connecting the socket.
- **UPNP_E_OUTOF_SOCKET**: Too many sockets are currently allocated.
- **UPNP_E_OUTOF_MEMORY**: There are insufficient resources to register this root device.
- **UPNP_E_URL_TOO_BIG**: Length of the URL is bigger than the internal buffer.
- **UPNP_E_FILE_NOT_FOUND**: The description file could not be found.
- **UPNP_E_FILE_READ_ERROR**: An error occurred reading the description file.
- **UPNP_E_INVALID_URL**: The URL to the description document is invalid.
- **UPNP_E_EXT_NOT_XML**: The URL to the description document or file should have a .xml extension.
- **UPNP_E_NO_WEB_SERVER**: The internal web server has been compiled out; the SDK cannot configure itself from the description document.

Parameters:	<code>descriptionType</code>	The type of the description document.
	<code>description</code>	Treated as a URL, file name or memory buffer depending on description type.
	<code>bufferLen</code>	The length of memory buffer if passing a description in a buffer, otherwise it is ignored.
	<code>config_baseURL</code>	If nonzero, URLBase of description document is configured and the description is served using the internal web server.
	<code>Fun</code>	Pointer to the callback function for receiving asynchronous events.
	<code>Cookie</code>	Pointer to user data returned with the callback function when invoked.
	<code>Hnd</code>	Pointer to a variable to store the new device handle.

4.3.8

```
EXPORT_SPEC int UpnpUnRegisterClient ( IN UpnpClient_Handle
                                         Hnd )
```

UpnpUnRegisterClient *unregisters a control point application, unsubscribing all active subscriptions.*

UpnpUnRegisterClient unregisters a control point application, unsubscribing all active subscriptions. After this call, the **UpnpClient_Handle** is no longer valid.

UpnpUnRegisterClient is a synchronous call and generates no callbacks. The SDK generates no more callbacks after this function returns.

Return Value: `[int]` An integer representing one of the following:

- **UPNP_E_SUCCESS:** The operation completed successfully.
- **UPNP_E_INVALID_HANDLE:** The handle is not a valid control point handle.

Parameters: `Hnd` The handle of the control point instance to unregister.

4.3.9

```
EXPORT_SPEC int UpnpUnRegisterRootDevice ( IN UpnpDevice_Handle )
```

*Unregisters a root device registered with **UpnpRegisterRootDevice** or **UpnpRegisterRootDevice2**.*

Unregisters a root device registered with **UpnpRegisterRootDevice** or **UpnpRegisterRootDevice2**. After this call, the **UpnpDevice_Handle** is no longer valid. For all advertisements that have not yet expired, the SDK sends a device unavailable message automatically.

UpnpUnRegisterRootDevice is a synchronous call and generates no callbacks. Once this call returns, the SDK will no longer generate callbacks to the application.

Return Value: [int] An integer representing one of the following:

- **UPNP_E_SUCCESS**: The operation completed successfully.
- **UPNP_E_INVALID_HANDLE**: The handle is not a valid device handle.

Parameters: UpnpDevice_Handle The handle of the root device instance to unregister.

4.3.10

```
EXPORT_SPEC int UpnpSetContentLength ( IN UpnpClient_Handle
                                         Hnd, IN int contentLength
                                         )
```

*OBSOLETE METHOD : use **UpnpSetMaxContentLength** instead.*

OBSOLETE METHOD : use **UpnpSetMaxContentLength** instead. Warning: the Handle argument provided here is not used, so the effect of this function is global to the SDK (= same as **UpnpSetMaxContentLength**).

4.3.11

```
EXPORT_SPEC int UpnpSetMaxContentLength ( IN size_t contentLength )
```

Sets the maximum content-length that the SDK will process on an incoming SOAP requests or responses.

Sets the maximum content-length that the SDK will process on an incoming SOAP requests or responses. This API allows devices that have memory constraints to exhibit consistent behaviour if the size of the incoming SOAP message exceeds the memory that device can allocate. The default maximum content-length is **DEFAULT_SOAP_CONTENT_LENGTH** = 16K bytes.

Return Value: [int] An integer representing one of the following:

- **UPNP_E_SUCCESS**: The operation completed successfully.

Parameters:	contentLength	The maximum permissible content length for incoming SOAP actions, in bytes.
--------------------	---------------	---

4.4

Discovery

Names

4.4.1 EXPORT_SPEC int

```

UpnpSearchAsync ( IN UpnpClient.Handle Hnd,  IN int Mx,
                  IN const char* Target,
                  IN const void* Cookie )
    UpnpSearchAsync searches for devices
    matching the given search target. ....

```

51

4.4.2 EXPORT_SPEC int

UpnpSendAdvertisement (IN UpnpDevice_Handle Hnd, IN int Exp)	
UpnpSendAdvertisement <i>sends out the discovery announcements for all de- vices and services for a device.</i>	52

4.4.1

```
EXPORT_SPEC int UpnpSearchAsync ( IN UpnpClient_Handle Hnd, IN
                                     int Mx, IN const char* Target,
                                     IN const void* Cookie )
```

UpnpSearchAsync *searches for devices matching the given search target.*

UpnpSearchAsync searches for devices matching the given search target. The function returns immediately and the SDK calls the default callback function, registered during the **UpnpRegisterClient** call, for each matching root device, device, or service. The application specifies the search type by the **Target** parameter.

Note that there is no way for the SDK to distinguish which client instance issued a particular search. Therefore, the client can get search callbacks that do not match the original criteria of the search. Also, the application will receive multiple callbacks for each search.

Return Value: [int] An integer representing one of the following:

- **UPNP_E_SUCCESS:** The operation completed successfully.
- **UPNP_E_INVALID_HANDLE:** The handle is not a valid control point handle.
- **UPNP_E_INVALID_PARAM:** **Target** is NULL.

Parameters:	Hnd	The handle of the client performing the search.
	Mx	The time, in seconds, to wait for responses. If the time is greater than MAX_SEARCH_TIME then the time is set to MAX_SEARCH_TIME. If the time is less than MIN_SEARCH_TIME then the time is set to MIN_SEARCH_TIME.
	Target	The search target as defined in the UPnP Device Architecture v1.0 specification.
	Cookie	The user data to pass when the callback function is invoked.

4.4.2

```
EXPORT_SPEC int UpnpSendAdvertisement ( IN UpnpDevice_Handle
                                         Hnd, IN int Exp )
```

UpnpSendAdvertisement *sends out the discovery announcements for all devices and services for a device.*

UpnpSendAdvertisement sends out the discovery announcements for all devices and services for a device. Each announcement is made with the same expiration time.

UpnpSendAdvertisement is a synchronous call.

Return Value: [int] An integer representing one of the following:

- UPNP_E_SUCCESS: The operation completed successfully.
- UPNP_E_INVALID_HANDLE: The handle is not a valid device handle.
- UPNP_E_OUTOF_MEMORY: There are insufficient resources to send future advertisements.

Parameters:

Hnd	The device handle for which to send out the announcements.
Exp	The expiration age, in seconds, of the announcements.

4.5

Control

Names

4.5.1 EXPORT_SPEC int

		UpnpGetServiceVarStatus (IN UpnpClient_Handle Hnd, IN const char* ActionURL, IN const char* VarName, OUT DOMString* StVarVal) UpnpGetServiceVarStatus <i>queries the state of a state variable of a service on another device.</i>	54
4.5.2	EXPORT_SPEC int	UpnpGetServiceVarStatusAsync (IN UpnpClient_Handle Hnd, IN const char* ActionURL, IN const char* VarName, IN Upnp_FunPtr Fun, IN const void* Cookie) UpnpGetServiceVarStatusAsync <i>queries the state of a variable of a service, generating a callback when the operation is complete.</i>	55
4.5.3	EXPORT_SPEC int	UpnpSendAction (IN UpnpClient_Handle Hnd, IN const char* ActionURL, IN const char* ServiceType, IN const char* DevUDN, IN IXML_Document* Action, OUT IXML_Document** RespNode) UpnpSendAction <i>sends a message to change a state variable in a service.</i>	56
4.5.4	EXPORT_SPEC int	UpnpSendActionEx (IN UpnpClient_Handle Hnd, IN const char* ActionURL, IN const char* ServiceType, IN const char* DevUDN, IN IXML_Document* Header, IN IXML_Document* Action, OUT IXML_Document** RespNode) UpnpSendActionEx <i>sends a message to change a state variable in a service.</i>	57
4.5.5	EXPORT_SPEC int	UpnpSendActionAsync (IN UpnpClient_Handle Hnd, IN const char* ActionURL, IN const char* ServiceType, IN const char* DevUDN, IN IXML_Document* Action, IN Upnp_FunPtr Fun, IN const void* Cookie) UpnpSendActionAsync <i>sends a message to change a state variable in a service, generating a callback when the operation is complete.</i>	58
4.5.6	EXPORT_SPEC int		

```

UpnpSendActionExAsync ( IN UpnpClient_Handle Hnd,
                        IN const char* ActionURL,
                        IN const char* ServiceType,
                        IN const char* DevUDN,
                        IN IXML_Document* Header,
                        IN IXML_Document* Action,
                        IN Upnp_FunPtr Fun,
                        IN const void* Cookie )

```

UpnpSendActionExAsync sends a message to change a state variable in a service, generating a callback when the operation is complete. 60

4.5.1

```

EXPORT_SPEC int UpnpGetServiceVarStatus (      IN      Upnp-
                                                pClient_Handle  Hnd,
                                                IN const char* Ac-
tionURL,      IN const
char* VarName, OUT
DOMString* StVarVal
)

```

UpnpGetServiceVarStatus queries the state of a state variable of a service on another device.

UpnpGetServiceVarStatus queries the state of a state variable of a service on another device. This is a synchronous call. A positive return value indicates a SOAP error code, whereas a negative return code indicates an SDK error code. **Note that the use of this function is deprecated by the UPnP Forum.**

Return Value:	[int]	An integer representing one of the following: <ul style="list-style-type: none"> • <code>UPNP_E_SUCCESS</code>: The operation completed successfully. • <code>UPNP_E_INVALID_HANDLE</code>: The handle is not a valid control point handle. • <code>UPNP_E_INVALID_URL</code>: ActionUrl is not a valid URL. • <code>UPNP_E_INVALID_DESC</code>: The XML document was not found or it does not contain a valid XML description. • <code>UPNP_E_INVALID_PARAM</code>: StVarVal is not a valid pointer or VarName or ActionUrl is NULL. • <code>UPNP_E_OUTOF_MEMORY</code>: Insufficient resources exist to complete this operation. • <code>UPNP_SOAP_E_INVALID_VAR</code>: The given variable is invalid according to the device.
Parameters:	Hnd ActionURL VarName StVarVal	The handle of the control point. The URL of the service. The name of the variable to query. The pointer to store the value for VarName . The SDK allocates this string and the caller needs to free it using ixmlFreeDOMString .

4.5.2

```
EXPORT_SPEC int UpnpGetServiceVarStatusAsync ( IN UpnpClient_Handle Hnd, IN const char* ActionURL, IN const char* VarName, IN Upnp_FunPtr Fun, IN const void* Cookie )
```

UpnpGetServiceVarStatusAsync *queries the state of a variable of a service, generating a callback when the operation is complete.*

UpnpGetServiceVarStatusAsync queries the state of a variable of a service, generating a callback when the operation is complete. **Note that the use of this function is deprecated by the UPnP Forum.**

Return Value:	[int]	An integer representing one of the following: <ul style="list-style-type: none"> • UPNP_E_SUCCESS: The operation completed successfully. • UPNP_E_INVALID_HANDLE: The handle is not a valid control point handle. • UPNP_E_INVALID_URL: The ActionUrl is not a valid URL. • UPNP_E_INVALID_PARAM: VarName, Fun or ActionUrl is not a valid pointer. • UPNP_E_OUTOF_MEMORY: Insufficient resources exist to complete this operation.
Parameters:	Hnd	The handle of the control point.
	ActionURL	The URL of the service.
	VarName	The name of the variable to query.
	Fun	Pointer to a callback function to be invoked when the operation is complete.
	Cooki e	Pointer to user data to pass to the callback function when invoked.

4.5.3

```
EXPORT_SPEC int UpnpSendAction ( IN UpnpClient_Handle Hnd, IN
                                const char* ActionURL, IN const
                                char* ServiceType, IN const char*
                                DevUDN, IN IXML_Document*
                                Action, OUT IXML_Document**
                                RespNode )
```

UpnpSendAction sends a message to change a state variable in a service.

UpnpSendAction sends a message to change a state variable in a service. This is a synchronous call that does not return until the action is complete.

Note that a positive return value indicates a SOAP-protocol error code. In this case, the error description can be retrieved from **RespNode**. A negative return value indicates an SDK error.

Return Value:	[int]	<p>An integer representing one of the following:</p> <ul style="list-style-type: none"> • UPNP_E_SUCCESS: The operation completed successfully. • UPNP_E_INVALID_HANDLE: The handle is not a valid control point handle. • UPNP_E_INVALID_URL: ActionUrl is not a valid URL. • UPNP_E_INVALID_ACTION: This action is not valid. • UPNP_E_INVALID_DEVICE: DevUDN is not a valid device. • UPNP_E_INVALID_PARAM: ServiceType, Action, ActionUrl, or RespNode is not a valid pointer. • UPNP_E_OUTOF_MEMORY: Insufficient resources exist to complete this operation.
Parameters:	Hnd	The handle of the control point sending the action.
	ActionURL	The action URL of the service.
	ServiceType	The type of the service.
	DevUDN	This parameter is ignored and must be NULL.
	Action	The DOM document for the action.
	RespNode	The DOM document for the response to the action. The SDK allocates this document and the caller needs to free it.

4.5.4

```
EXPORT_SPEC int UpnpSendActionEx ( IN UpnpClient_Handle Hnd,
                                   IN const char* ActionURL,
                                   IN const char* ServiceType,
                                   IN const char* DevUDN, IN
                                   IXML_Document* Header,
                                   IN IXML_Document* Action,
                                   OUT IXML_Document** RespNode )
```

UpnpSendActionEx sends a message to change a state variable in a service.

UpnpSendActionEx sends a message to change a state variable in a service. This is a synchronous call that does not return until the action is complete.

Note that a positive return value indicates a SOAP-protocol error code. In this case, the error description can be retrieved from **RespNode**. A negative return value indicates an SDK error.

Return Value:	[int]	An integer representing one of the following: <ul style="list-style-type: none"> • UPNP_E_SUCCESS: The operation completed successfully. • UPNP_E_INVALID_HANDLE: The handle is not a valid control point handle. • UPNP_E_INVALID_URL: ActionUrl is not a valid URL. • UPNP_E_INVALID_ACTION: This action is not valid. • UPNP_E_INVALID_DEVICE: DevUDN is not a valid device. • UPNP_E_INVALID_PARAM: ServiceType, Action, ActionUrl, or RespNode is not a valid pointer. • UPNP_E_OUTOF_MEMORY: Insufficient resources exist to complete this operation.
Parameters:	Hnd	The handle of the control point sending the action.
	ActionURL	The action URL of the service.
	ServiceType	The type of the service.
	DevUDN	This parameter is ignored and must be NULL.
	Header	The DOM document for the SOAP header. This may be NULL if the header is not required.
	Action	The DOM document for the action.
	RespNode	The DOM document for the response to the action. The SDK allocates this document and the caller needs to free it.

4.5.5

```
EXPORT_SPEC int UpnpSendActionAsync ( IN UpnpClient_Handle
                                     Hnd, IN const char*
                                     ActionURL, IN const
                                     char* ServiceType, IN
                                     const char* DevUDN, IN
                                     IXML_Document* Action,
                                     IN Upnp_FunPtr Fun, IN
                                     const void* Cookie )
```

UpnpSendActionAsync sends a message to change a state variable in a service, generating a callback when the operation is complete.

UpnpSendActionAsync sends a message to change a state variable in a service, generating

a callback when the operation is complete. See **UpnpSendAction** for comments on positive return values. These positive return values are sent in the event struct associated with the `UPNP_CONTROL_ACTION_COMPLETE` event.

Return Value: `[int]` An integer representing one of the following:

- `UPNP_E_SUCCESS`: The operation completed successfully.
- `UPNP_E_INVALID_HANDLE`: The handle is not a valid control point handle.
- `UPNP_E_INVALID_URL`: **ActionUrl** is an invalid URL.
- `UPNP_E_INVALID_DEVICE`: **DevUDN** is an invalid device.
- `UPNP_E_INVALID_PARAM`: Either **Fun** is not a valid callback function or **ServiceType**, **Act**, or **ActionUrl** is NULL.
- `UPNP_E_INVALID_ACTION`: This action is not valid.
- `UPNP_E_OUTOF_MEMORY`: Insufficient resources exist to complete this operation.

Parameters:

<code>Hnd</code>	The handle of the control point sending the action.
<code>ActionURL</code>	The action URL of the service.
<code>ServiceType</code>	The type of the service.
<code>DevUDN</code>	This parameter is ignored and must be NULL.
<code>Action</code>	The DOM document for the action to perform on this device.
<code>Fun</code>	Pointer to a callback function to be invoked when the operation completes.
<code>Cookie</code>	Pointer to user data that to be passed to the callback when invoked.

4.5.6

```

EXPORT_SPEC int UpnpSendActionExAsync ( IN UpnpClient_Handle
                                         Hnd, IN const char*
                                         ActionURL, IN const
                                         char* ServiceType, IN
                                         const char* DevUDN,
                                         IN IXML_Document*
                                         Header, IN
                                         IXML_Document* Ac-
                                         tion, IN Upnp_FunPtr
                                         Fun, IN const void*
                                         Cookie )

```

UpnpSendActionExAsync sends a message to change a state variable in a service, generating a callback when the operation is complete.

UpnpSendActionExAsync sends a message to change a state variable in a service, generating a callback when the operation is complete. See **UpnpSendAction** for comments on positive return values. These positive return values are sent in the event struct associated with the UPNP_CONTROL_ACTION_COMPLETE event.

Return Value: [int] An integer representing one of the following:

- UPNP_E_SUCCESS: The operation completed successfully.
- UPNP_E_INVALID_HANDLE: The handle is not a valid control point handle.
- UPNP_E_INVALID_URL: **ActionUrl** is an invalid URL.
- UPNP_E_INVALID_DEVICE: **DevUDN** is an invalid device.
- UPNP_E_INVALID_PARAM: Either **Fun** is not a valid callback function or **ServiceType**, **Act**, or **ActionUrl** is NULL.
- UPNP_E_INVALID_ACTION: This action is not valid.
- UPNP_E_OUTOF_MEMORY: Insufficient resources exist to complete this operation.

Parameters:	Hnd	The handle of the control point sending the action.
	ActionURL	The action URL of the service.
	ServiceType	The type of the service.
	DevUDN	This parameter is ignored and must be NULL.
	Header	The DOM document for the SOAP header. This may be NULL if the header is not required.
	Action	The DOM document for the action to perform on this device.
	Fun	Pointer to a callback function to be invoked when the operation completes.
	Cookie	Pointer to user data that to be passed to the callback when invoked.

4.6

Eventing

Names

4.6.1 EXPORT_SPEC int

UpnpAcceptSubscription (IN UpnpDevice_Handle Hnd,
 IN const char* DevID,
 IN const char* ServID,
 IN const char** VarName,
 IN const char** NewVal,
 IN int cVariables,
 IN Upnp_SID SubsId)

UpnpAcceptSubscription *accepts a subscription request and sends out the current state of the eventable variables for a service.*

64

4.6.2 EXPORT_SPEC int

UpnpAcceptSubscriptionExt (IN UpnpDevice_Handle Hnd,
 IN const char* DevID,
 IN const char* ServID,
 IN IXML_Document* PropSet,
 IN Upnp_SID SubsId)

UpnpAcceptSubscriptionExt *is similar to UpnpAcceptSubscription except that it takes a DOM document for the variables to event rather than an array of strings.*

64

4.6.3 EXPORT_SPEC int

		UpnpNotify (IN UpnpDevice_Handle, IN const char* DevID, IN const char* ServID, IN const char** VarName, IN const char** NewVal, IN int cVariables) <i>UpnpNotify sends out an event change notification to all control points subscribed to a particular service.</i>	65
4.6.4	EXPORT_SPEC int	UpnpNotifyExt (IN UpnpDevice_Handle, IN const char* DevID, IN const char* ServID, IN IXML_Document* PropSet) <i>UpnpNotifyExt is similar to UpnpNo- tify except that it takes a DOM docu- ment for the event rather than an array of strings.</i>	66
4.6.5	EXPORT_SPEC int	UpnpRenewSubscription (IN UpnpClient_Handle Hnd, INOUT int* TimeOut, IN Upnp_SID SubsId) <i>UpnpRenewSubscription renews a subscription that is about to expire.</i>	67
4.6.6	EXPORT_SPEC int	UpnpRenewSubscriptionAsync (IN UpnpClient_Handle Hnd, IN int TimeOut, IN Upnp_SID SubsId, IN Upnp_FunPtr Fun, IN const void* Cookie) <i>UpnpRenewSubscriptionAsync re- news a subscription that is about to expire, generating a callback when the operation is complete.</i>	68
4.6.7	EXPORT_SPEC int	UpnpSetMaxSubscriptions (IN UpnpDevice_Handle Hnd, IN int MaxSubscriptions) <i>UpnpSetMaxSubscriptions sets the maximum number of subscriptions ac- cepted per service.</i>	71
4.6.8	EXPORT_SPEC int	UpnpSetMaxSubscriptionTimeOut (IN UpnpDevice_Handle Hnd, IN int MaxSub- scriptionTimeOut) <i>UpnpSetMaxSubscriptionTimeOut sets the maximum time-out accepted for a subscription request or renewal.</i>	71
4.6.9	EXPORT_SPEC int		

-
- UpnpSubscribe** (IN UpnpClient_Handle Hnd,
IN const char* PublisherUrl,
INOUT int* TimeOut,
OUT Upnp_SID SubsId)
UpnpSubscribe registers a control point to receive event notifications from another device. 72
- 4.6.10 EXPORT_SPEC int
UpnpSubscribeAsync (IN UpnpClient_Handle Hnd,
IN const char* PublisherUrl,
IN int TimeOut,
IN Upnp_FunPtr Fun,
IN const void* Cookie)
UpnpSubscribeAsync performs the same operation as UpnpSubscribe, but returns immediately and calls the registered callback function when the operation is complete. 74
- 4.6.11 EXPORT_SPEC int
UpnpUnSubscribe (IN UpnpClient_Handle Hnd,
IN Upnp_SID SubsId)
UpnpUnSubscribe removes the subscription of a control point from a service previously subscribed to using UpnpSubscribe or UpnpSubscribeAsync. 76
- 4.6.12 EXPORT_SPEC int
UpnpUnSubscribeAsync (IN UpnpClient_Handle Hnd,
IN Upnp_SID SubsId,
IN Upnp_FunPtr Fun,
IN const void* Cookie)
UpnpUnSubscribeAsync removes a subscription of a control point from a service previously subscribed to using UpnpSubscribe or UpnpSubscribeAsync, generating a callback when the operation is complete. 77

4.6.1

EXPORT_SPEC int **UpnpAcceptSubscription** (IN UpnpDevice_Handle
Hnd, IN const char*
DevID, IN const char*
ServID, IN const char**
VarName, IN const
char** NewVal, IN int
cVariables, IN Upnp_SID
SubsId)

UpnpAcceptSubscription *accepts a subscription request and sends out the current state of the eventable variables for a service.*

UpnpAcceptSubscription accepts a subscription request and sends out the current state of the eventable variables for a service. The device application should call this function when it receives a `UPNP_EVENT_SUBSCRIPTION_REQUEST` callback. This function is synchronous and generates no callbacks.

UpnpAcceptSubscription can be called during the execution of a callback function.

Return Value: `[int]` An integer representing one of the following:

- `UPNP_E_SUCCESS`: The operation completed successfully.
- `UPNP_E_INVALID_HANDLE`: The handle is not a valid device handle.
- `UPNP_E_INVALID_SERVICE`: The **DevId/ServId** pair refers to an invalid service.
- `UPNP_E_INVALID_SID`: The specified subscription ID is not valid.
- `UPNP_E_INVALID_PARAM`: Either **VarName**, **NewVal**, **DevID**, or **ServID** is not a valid pointer or **cVariables** is less than zero.
- `UPNP_E_OUTOF_MEMORY`: Insufficient resources exist to complete this operation.

Parameters:

<code>Hnd</code>	The handle of the device.
<code>DevID</code>	The device ID of the subdevice of the service generating the event.
<code>ServID</code>	The unique service identifier of the service generating the event.
<code>VarName</code>	Pointer to an array of event variables.
<code>NewVal</code>	Pointer to an array of values for the event variables.
<code>cVariables</code>	The number of event variables in VarName .
<code>SubsId</code>	The subscription ID of the newly registered control point.

4.6.2

```
EXPORT_SPEC int UpnpAcceptSubscriptionExt ( IN UpnpDevice_Handle Hnd, IN const char* DevID, IN const char* ServID, IN IXML_Document* PropSet, IN Upnp_SID SubsId )
```

UpnpAcceptSubscriptionExt *is similar to UpnpAcceptSubscription except that it takes a DOM document for the variables to event rather than an array of strings.*

UpnpAcceptSubscriptionExt is similar to **UpnpAcceptSubscription** except that it takes

a DOM document for the variables to event rather than an array of strings. This function is synchronous and generates no callbacks.

UpnpAcceptSubscriptionExt can be called during the execution of a callback function.

Return Value:	[int]	An integer representing one of the following: <ul style="list-style-type: none"> • UPNP_E_SUCCESS: The operation completed successfully. • UPNP_E_INVALID_HANDLE: The handle is not a valid device handle. • UPNP_E_INVALID_SERVICE: The DevId/ServId pair refers to an invalid service. • UPNP_E_INVALID_SID: The specified subscription ID is not valid. • UPNP_E_INVALID_PARAM: Either VarName, NewVal, DevID, ServID, or PropSet is not a valid pointer. • UPNP_E_OUTOF_MEMORY: Insufficient resources exist to complete this operation.
Parameters:	<div>Hnd</div> <div>DevID</div> <div>ServID</div> <div>PropSet</div> <div>SubsId</div>	<div>The handle of the device.</div> <div>The device ID of the subdevice of the service generating the event.</div> <div>The unique service identifier of the service generating the event.</div> <div>The DOM document for the property set. Property set documents must conform to the XML schema defined in section 4.3 of the Universal Plug and Play Device Architecture specification.</div> <div>The subscription ID of the newly registered control point.</div>

4.6.3

```
EXPORT_SPEC int UpnpNotify ( IN UpnpDevice_Handle, IN const char*
                               DevID, IN const char* ServID, IN const
                               char** VarName, IN const char** New-
                               Val, IN int cVariables )
```

UpnpNotify sends out an event change notification to all control points subscribed to a particular service.

UpnpNotify sends out an event change notification to all control points subscribed to a particular service. This function is synchronous and generates no callbacks.

UpnpNotify may be called during a callback function to send out a notification.

Return Value:	[int]	An integer representing one of the following: <ul style="list-style-type: none"> • UPNP_E_SUCCESS: The operation completed successfully. • UPNP_E_INVALID_HANDLE: The handle is not a valid device handle. • UPNP_E_INVALID_SERVICE: The DevId/ServId pair refers to an invalid service. • UPNP_E_INVALID_PARAM: Either VarName, NewVal, DevID, or ServID is not a valid pointer or cVariables is less than zero. • UPNP_E_OUTOF_MEMORY: Insufficient resources exist to complete this operation.
Parameters:	UpnpDevice_Handle	The handle to the device sending the event.
	DevID	The device ID of the subdevice of the service generating the event.
	ServID	The unique identifier of the service generating the event.
	VarName	Pointer to an array of variables that have changed.
	NewVal	Pointer to an array of new values for those variables.
	cVariables	The count of variables included in this notification.

4.6.4

```
EXPORT_SPEC int UpnpNotifyExt ( IN UpnpDevice_Handle, IN
                                const char* DevID, IN const
                                char* ServID, IN IXML_Document*
                                PropSet )
```

UpnpNotifyExt is similar to **UpnpNotify** except that it takes a DOM document for the event rather than an array of strings.

UpnpNotifyExt is similar to **UpnpNotify** except that it takes a DOM document for the event rather than an array of strings. This function is synchronous and generates no callbacks.

UpnpNotifyExt may be called during a callback function to send out a notification.

Return Value: [int] An integer representing one of the following:

- **UPNP_E_SUCCESS:** The operation completed successfully.
- **UPNP_E_INVALID_HANDLE:** The handle is not a valid device handle.
- **UPNP_E_INVALID_SERVICE:** The **DevId/ServId** pair refers to an invalid service.
- **UPNP_E_INVALID_PARAM:** Either **VarName**, **NewVal**, **DevID**, **ServID**, or **PropSet** is not a valid pointer or **cVariables** is less than zero.
- **UPNP_E_OUTOF_MEMORY:** Insufficient resources exist to complete this operation.

Parameters:

UpnpDevice_Handle	The handle to the device sending the event.
DevID	The device ID of the subdevice of the service generating the event.
ServID	The unique identifier of the service generating the event.
PropSet	The DOM document for the property set. Property set documents must conform to the XML schema defined in section 4.3 of the Universal Plug and Play Device Architecture specification.

4.6.5

```
EXPORT_SPEC int UpnpRenewSubscription ( IN UpnpClient_Handle
                                         Hnd, INOUT int* Time-
                                         Out, IN Upnp_SID Sub-
                                         sId )
```

UpnpRenewSubscription *renews a subscription that is about to expire.*

UpnpRenewSubscription renews a subscription that is about to expire. This function is synchronous.

Return Value:	[int]	An integer representing one of the following: <ul style="list-style-type: none"> • UPNP_E_SUCCESS: The operation completed successfully. • UPNP_E_INVALID_HANDLE: The handle is not a valid control point handle. • UPNP_E_INVALID_PARAM: Timeout is not a valid pointer. • UPNP_E_INVALID_SID: The SID being passed to this function is not a valid subscription ID. • UPNP_E_NETWORK_ERROR: A network error occurred. • UPNP_E_SOCKET_WRITE: An error or timeout occurred writing to a socket. • UPNP_E_SOCKET_READ: An error or timeout occurred reading from a socket. • UPNP_E_SOCKET_BIND: An error occurred binding a socket. • UPNP_E_SOCKET_CONNECT: An error occurred connecting to PublisherUrl. • UPNP_E_OUTOF_SOCKET: An error occurred creating a socket. • UPNP_E_BAD_RESPONSE: An error occurred in response from the publisher. • UPNP_E_SUBSCRIBE_UNACCEPTED: The publisher refused the subscription renew. • UPNP_E_OUTOF_MEMORY: Insufficient resources exist to complete this operation.
Parameters:	Hnd	The handle of the control point that is renewing the subscription.
	TimeOut	Pointer to a variable containing the requested subscription time. Upon return, it contains the actual renewal time.
	SubsId	The ID for the subscription to renew.

4.6.6

```
EXPORT_SPEC int UpnpRenewSubscriptionAsync ( IN UpnpClient_Handle Hnd, IN int TimeOut, IN Upnp_SID SubsId, IN Upnp_FunPtr Fun, IN const void* Cookie )
```

UpnpRenewSubscriptionAsync *renews a subscription that is about to expire, generating a callback when the operation is complete.*

UpnpRenewSubscriptionAsync renews a subscription that is about to expire, generating a callback when the operation is complete.

Note that many of the error codes for this function are returned in the **Upnp_Event_Subscribe** structure. In those cases, the function returns `UPNP_E_SUCCESS` and the appropriate error code will be in the **Upnp_Event_Subscribe.ErrCode** field in the **Event** structure passed to the callback.

Return Value:

Parameters:	Hnd	The handle of the control point that is renewing the subscription.
	TimeOut	The requested subscription time. The actual timeout value is returned when the callback function is called.
	SubsId	The ID for the subscription to renew.
	Fun	Pointer to a callback function to be invoked when the renewal is complete.
	Cooki e	Pointer to user data passed to the callback function when invoked.

4.6.7

```
EXPORT_SPEC int UpnpSetMaxSubscriptions (    IN    UpnpDe-
                                              vice_Handle Hnd,  IN
                                              int MaxSubscriptions )
```

UpnpSetMaxSubscriptions sets the maximum number of subscriptions accepted per service.

UpnpSetMaxSubscriptions sets the maximum number of subscriptions accepted per service. The default value accepts as many as system resources allow. If the number of current subscriptions for a service is greater than the requested value, the SDK accepts no new subscriptions or renewals, however, the SDK does not remove any current subscriptions.

Return Value: [int] An integer representing one of the following:

- **UPNP_E_SUCCESS:** The operation completed successfully.
- **UPNP_E_INVALID_HANDLE:** The handle is not a valid device handle.

Parameters:	Hnd	The handle of the device for which the maximum number of subscriptions is being set.
	MaxSubscriptions	The maximum number of subscriptions to be allowed per service.

4.6.8

```
EXPORT_SPEC int UpnpSetMaxSubscriptionTimeout ( IN UpnpDe-
                                              vice_Handle Hnd,  IN int MaxSubscriptionTimeout )
```

UpnpSetMaxSubscriptionTimeout sets the maximum time-out accepted for a subscription request or renewal.

UpnpSetMaxSubscriptionTimeout sets the maximum time-out accepted for a subscription

request or renewal. The default value accepts the time-out set by the control point. If a control point requests a subscription time-out less than or equal to the maximum, the SDK grants the value requested by the control point. If the time-out is greater, the SDK returns the maximum value.

Return Value: [int] An integer representing one of the following:

- `UPNP_E_SUCCESS`: The operation completed successfully.
- `UPNP_E_INVALID_HANDLE`: The handle is not a valid device handle.

Parameters:

<code>Hnd</code>	The handle of the device for which the maximum subscription time-out is being set.
<code>MaxSubscriptionTimeout</code>	The maximum subscription time-out to be accepted.

4.6.9

```
EXPORT_SPEC int UpnpSubscribe ( IN UpnpClient_Handle Hnd, IN
                                const char* PublisherUrl, INOUT
                                int* Timeout, OUT Upnp_SID Sub-
                                sId )
```

UpnpSubscribe registers a control point to receive event notifications from another device.

UpnpSubscribe registers a control point to receive event notifications from another device. This operation is synchronous.

Return Value:	[int]	An integer representing one of the following: <ul style="list-style-type: none"> • UPNP_E_SUCCESS: The operation completed successfully. • UPNP_E_INVALID_HANDLE: The handle is not a valid control point handle. • UPNP_E_INVALID_URL: PublisherUrl is not a valid URL. • UPNP_E_INVALID_PARAM: Timeout is not a valid pointer or SubsId or PublisherUrl is NULL. • UPNP_E_NETWORK_ERROR: A network error occurred. • UPNP_E_SOCKET_WRITE: An error or timeout occurred writing to a socket. • UPNP_E_SOCKET_READ: An error or timeout occurred reading from a socket. • UPNP_E_SOCKET_BIND: An error occurred binding a socket. • UPNP_E_SOCKET_CONNECT: An error occurred connecting to PublisherUrl. • UPNP_E_OUTOF_SOCKET: An error occurred creating a socket. • UPNP_E_BAD_RESPONSE: An error occurred in response from the publisher. • UPNP_E_SUBSCRIBE_UNACCEPTED: The publisher refused the subscription request. • UPNP_E_OUTOF_MEMORY: Insufficient resources exist to complete this operation.
Parameters:	Hnd	The handle of the control point.
	PublisherUrl	The URL of the service to subscribe to.
	Timeout	Pointer to a variable containing the requested subscription time. Upon return, it contains the actual subscription time returned from the service.
	SubsId	Pointer to a variable to receive the subscription ID (SID).

4.6.10

```
EXPORT_SPEC int UpnpSubscribeAsync ( IN UpnpClient_Handle
                                     Hnd, IN const char* PublisherUrl,
                                     IN int Timeout,
                                     IN Upnp_FunPtr Fun, IN
                                     const void* Cookie )
```

UpnpSubscribeAsync *performs the same operation as **UpnpSubscribe**, but returns immediately and calls the registered callback function when the operation is complete.*

UpnpSubscribeAsync performs the same operation as **UpnpSubscribe**, but returns immediately and calls the registered callback function when the operation is complete.

Note that many of the error codes for this function are returned in the **Upnp_Event_Subscribe** structure. In those cases, the function returns `UPNP_E_SUCCESS` and the appropriate error code will be in the **Upnp_Event_Subscribe.ErrCode** field in the **Event** structure passed to the callback.

Return Value:**[int]** An integer representing one of the following:

- **UPNP_E_SUCCESS**: The operation completed successfully.
- **UPNP_E_INVALID_HANDLE**: The handle is not a valid control point handle.
- **UPNP_E_INVALID_URL**: The **PublisherUrl** is not a valid URL.
- **UPNP_E_INVALID_PARAM**: Either **Timeout** or **Fun** or **PublisherUrl** is not a valid pointer.
- **UPNP_E_OUTOF_MEMORY**: Insufficient resources exist to complete this operation.
- **UPNP_E_NETWORK_ERROR**: A network error occurred (returned in the **Upnp_Event_Subscribe.ErrCode** field as part of the callback).
- **UPNP_E_SOCKET_WRITE**: An error or timeout occurred writing to a socket (returned in the **Upnp_Event_Subscribe.ErrCode** field as part of the callback).
- **UPNP_E_SOCKET_READ**: An error or timeout occurred reading from a socket (returned in the **Upnp_Event_Subscribe.ErrCode** field as part of the callback).
- **UPNP_E_SOCKET_BIND**: An error occurred binding the socket (returned in the **Upnp_Event_Subscribe.ErrCode** field as part of the callback).
- **UPNP_E_SOCKET_CONNECT**: An error occurred connecting to **PublisherUrl** (returned in the **Upnp_Event_Subscribe.ErrCode** field as part of the callback).
- **UPNP_E_OUTOF_SOCKET**: An error occurred creating the socket (returned in the **Upnp_Event_Subscribe.ErrCode** field as part of the callback).
- **UPNP_E_BAD_RESPONSE**: An error occurred in response from the publisher (returned in the **Upnp_Event_Subscribe.ErrCode** field as part of the callback).
- **UPNP_E_SUBSCRIBE_UNACCEPTED**: The publisher refused the subscription request (returned in the **Upnp_Event_Subscribe.ErrCode** field as part of the callback).

Parameters:	Hnd	The handle of the control point that is subscribing.
	Pu b l i s h e r U r l	The URL of the service to subscribe to.
	T i m e O u t	The requested subscription time. Upon return, it contains the actual subscription time returned from the service.
	F u n	Pointer to the callback function for this subscribe request.
	C o o k i e	A user data value passed to the callback function when invoked.

4.6.11

```
EXPORT_SPEC int UpnpUnSubscribe ( IN UpnpClient_Handle Hnd, IN
                                   Upnp_SID SubsId )
```

UpnpUnSubscribe *removes the subscription of a control point from a service previously subscribed to using **UpnpSubscribe** or **UpnpSubscribeAsync**.*

UpnpUnSubscribe removes the subscription of a control point from a service previously subscribed to using **UpnpSubscribe** or **UpnpSubscribeAsync**. This is a synchronous call.

Return Value:	[int]	An integer representing one of the following: <ul style="list-style-type: none"> • UPNP_E_SUCCESS: The operation completed successfully. • UPNP_E_INVALID_HANDLE: The handle is not a valid control point handle. • UPNP_E_INVALID_SID: The SubsId is not a valid subscription ID. • UPNP_E_NETWORK_ERROR: A network error occurred. • UPNP_E_SOCKET_WRITE: An error or timeout occurred writing to a socket. • UPNP_E_SOCKET_READ: An error or timeout occurred reading from a socket. • UPNP_E_SOCKET_BIND: An error occurred binding a socket. • UPNP_E_SOCKET_CONNECT: An error occurred connecting to PublisherUrl. • UPNP_E_OUTOF_SOCKET: An error occurred creating a socket. • UPNP_E_BAD_RESPONSE: An error occurred in response from the publisher. • UPNP_E_UNSUBSCRIBE_UNACCEPTED: The publisher refused the unsubscribe request (the client is still unsubscribed and no longer receives events). • UPNP_E_OUTOF_MEMORY: Insufficient resources exist to complete this operation.
Parameters:	Hnd	The handle of the subscribed control point.
	SubsId	The ID returned when the control point subscribed to the service.

4.6.12

```
EXPORT_SPEC int UpnpUnSubscribeAsync ( IN UpnpClient_Handle
                                         Hnd, IN Upnp_SID SubsId,
                                         IN Upnp_FunPtr Fun,
                                         IN const void* Cookie )
```

UpnpUnSubscribeAsync *removes a subscription of a control point from a service previously subscribed to using **UpnpSubscribe** or **UpnpSubscribeAsync**, generating a callback when the operation is complete.*

UpnpUnSubscribeAsync removes a subscription of a control point from a service previously subscribed to using **UpnpSubscribe** or **UpnpSubscribeAsync**, generating a callback when the operation is complete.

Note that many of the error codes for this function are returned in the **Upnp_Event_Subscribe** structure. In those cases, the function returns `UPNP_E_SUCCESS` and the appropriate error code will be in the **Upnp_Event_Subscribe.ErrCode** field in the **Event** structure passed to the callback.

Return Value:

[int] An integer representing one of the following:

- **UPNP_E_SUCCESS**: The operation completed successfully.
- **UPNP_E_INVALID_HANDLE**: The handle is not a valid control point handle.
- **UPNP_E_INVALID_SID**: The **SubsId** is not a valid SID.
- **UPNP_E_INVALID_PARAM**: **Fun** is not a valid callback function pointer.
- **UPNP_E_OUTOF_MEMORY**: Insufficient resources exist to complete this operation.
- **UPNP_E_NETWORK_ERROR**: A network error occurred (returned in the **Upnp_Event_Subscribe.ErrCode** field as part of the callback).
- **UPNP_E_SOCKET_WRITE**: An error or timeout occurred writing to a socket (returned in the **Upnp_Event_Subscribe.ErrCode** field as part of the callback).
- **UPNP_E_SOCKET_READ**: An error or timeout occurred reading from a socket (returned in the **Upnp_Event_Subscribe.ErrCode** field as part of the callback).
- **UPNP_E_SOCKET_BIND**: An error occurred binding the socket (returned in the **Upnp_Event_Subscribe.ErrCode** field as part of the callback).
- **UPNP_E_SOCKET_CONNECT**: An error occurred connecting to **PublisherUrl** (returned in the **Upnp_Event_Subscribe.ErrCode** field as part of the callback).
- **UPNP_E_OUTOF_SOCKET**: An error occurred creating a socket (returned in the **Upnp_Event_Subscribe.ErrCode** field as part of the callback).
- **UPNP_E_BAD_RESPONSE**: An error occurred in response from the publisher (returned in the **Upnp_Event_Subscribe.ErrCode** field as part of the callback).
- **UPNP_E_UNSUBSCRIBE_UNACCEPTED**: The publisher refused the subscription request (returned in the **Upnp_Event_Subscribe.ErrCode** field as part of the callback).

Parameters:	Hnd	The handle of the subscribed control point.
	SubsId	The ID returned when the control point subscribed to the service.
	Fun	Pointer to a callback function to be called when the operation is complete.
	Cookie	Pointer to user data to pass to the callback function when invoked.

4.7

Control Point HTTP API

Names

- 4.7.1 EXPORT_SPEC int
UpnpDownloadUrlItem (IN const char* url,
OUT char** outBuf,
OUT char* contentType)
UpnpDownloadUrlItem *downloads a file specified in a URL.* 82
- 4.7.2 EXPORT_SPEC int
UpnpOpenHttpGet (IN const char* url,
IN OUT void** handle,
IN OUT char** contentType,
IN OUT int* contentLength,
IN OUT int* httpStatus,
IN int timeout)
UpnpOpenHttpGet *gets a file specified in a URL.* 83
- 4.7.3 EXPORT_SPEC int
UpnpOpenHttpGetProxy (IN const char* url,
IN const char* proxy_str,
IN OUT void** handle,
IN OUT char** contentType,
IN OUT int* contentLength,
IN OUT int* httpStatus,
IN int timeout)
UpnpOpenHttpGetProxy *gets a file specified in a URL through the specified proxy.* 85
- 4.7.4 EXPORT_SPEC int

		UpnpOpenHttpGetEx (IN const char* url, IN OUT void** handle, IN OUT char** contentType, IN OUT int* contentLength, IN OUT int* httpStatus, IN int lowRange, IN int highRange, IN int timeout) UpnpOpenHttpGetEx gets specified number of bytes from a file specified in the URL.	86
4.7.5	EXPORT_SPEC int	UpnpReadHttpGet (IN void* handle, IN OUT char* buf, IN OUT unsigned int* size, IN int timeout) UpnpReadHttpGet gets specified num- ber of bytes from a file specified in a URL.	87
4.7.6	EXPORT_SPEC int	UpnpHttpGetProgress (IN void* handle, OUT unsigned int* length, OUT unsigned int* total) UpnpHttpGetProgress retrieve progress information of a http-get trans- fer.	88
4.7.7	EXPORT_SPEC int	UpnpCancelHttpGet (IN void* handle) UpnpCancelHttpGet set the cancel flag of the handle parameter.	88
4.7.8	EXPORT_SPEC int	UpnpCloseHttpGet (IN void* handle) UpnpCloseHttpGet closes the connec- tion and frees memory that was allocated for the handle parameter.	89
4.7.9	EXPORT_SPEC int	UpnpOpenHttpPost (IN const char* url, IN OUT void** handle, IN const char* contentType, IN int contentLength, IN int timeout) UpnpOpenHttpPost makes an HTTP POST request message, opens a connec- tion to the server and sends the POST re- quest to the server if the connection to the server succeeds.	89
4.7.10	EXPORT_SPEC int	UpnpWriteHttpPost (IN void* handle, IN char* buf, IN unsigned int* size, IN int timeout) UpnpWriteHttpPost sends a request to a server to copy the contents of a buffer to the URI specified in the UpnpOpen- HttpPost call.	90
4.7.11	EXPORT_SPEC int		

UpnpCloseHttpPost (IN void* handle,
 IN OUT int* httpStatus,
 IN int timeout)
UpnpCloseHttpPost *sends and receives any pending data, closes the connection with the server, and frees memory allocated during the call.* 91

4.7.12 EXPORT_SPEC int

UpnpDownloadXmlDoc (IN const char* url,
 OUT IXML_Document** xmlDoc)
UpnpDownloadXmlDoc *downloads an XML document specified in a URL.* 91

4.7.1

EXPORT_SPEC int **UpnpDownloadUrlItem** (IN const char* url, OUT
 char** outBuf, OUT char*
 contentType)

UpnpDownloadUrlItem *downloads a file specified in a URL.*

UpnpDownloadUrlItem downloads a file specified in a URL. The SDK allocates the memory for **outBuf** and the application is responsible for freeing this memory. Note that the item is passed as a single buffer. Large items should not be transferred using this function.

Return Value:	[int]	An integer representing one of the following: <ul style="list-style-type: none"> • UPNP_E_SUCCESS: The operation completed successfully. • UPNP_E_INVALID_PARAM: Either url, outBuf or contentType is not a valid pointer. • UPNP_E_INVALID_URL: The url is not a valid URL. • UPNP_E_OUTOF_MEMORY: Insufficient resources exist to download this file. • UPNP_E_NETWORK_ERROR: A network error occurred. • UPNP_E_SOCKET_WRITE: An error or timeout occurred writing to a socket. • UPNP_E_SOCKET_READ: An error or timeout occurred reading from a socket. • UPNP_E_SOCKET_BIND: An error occurred binding a socket. • UPNP_E_SOCKET_CONNECT: An error occurred connecting a socket. • UPNP_E_OUTOF_SOCKET: Too many sockets are currently allocated.
Parameters:	url	URL of an item to download.
	outBuf	Buffer to store the downloaded item.
	contentType	HTTP header value content type if present. It should be at least <code>LINE_SIZE</code> bytes in size.

4.7.2

```
EXPORT_SPEC int UpnpOpenHttpGet ( IN const char* url, IN OUT
                                void** handle, IN OUT char**
                                contentType, IN OUT int* con-
                                tentLength, IN OUT int* http-
                                Status, IN int timeout )
```

UpnpOpenHttpGet gets a file specified in a URL.

UpnpOpenHttpGet gets a file specified in a URL. The SDK allocates the memory for **handle** and **contentType**, the application is responsible for freeing this memory.

Return Value:

[int] An integer representing one of the following:

- UPNP_E_SUCCESS: The operation completed successfully.
- UPNP_E_INVALID_PARAM: Either **url**, **handle**, **contentType**, **contentLength** or **httpStatus** is not a valid pointer.
- UPNP_E_INVALID_URL: The **url** is not a valid URL.
- UPNP_E_OUTOF_MEMORY: Insufficient resources exist to download this file.
- UPNP_E_NETWORK_ERROR: A network error occurred.
- UPNP_E_SOCKET_WRITE: An error or timeout occurred writing to a socket.
- UPNP_E_SOCKET_READ: An error or timeout occurred reading from a socket.
- UPNP_E_SOCKET_BIND: An error occurred binding a socket.
- UPNP_E_SOCKET_CONNECT: An error occurred connecting a socket.
- UPNP_E_OUTOF_SOCKET: Too many sockets are currently allocated.
- UPNP_E_BAD_RESPONSE: A bad response was received from the remote server.

Parameters:

url	The URL of an item to get.
handle	A pointer to store the handle for this connection.
contentType	A buffer to store the media type of the item.
contentLength	A pointer to store the length of the item.
httpStatus	The status returned on receiving a response message.
timeout	The time out value sent with the request during which a response is expected from the server, failing which, an error is reported back to the user.

4.7.3

```
EXPORT_SPEC int UpnpOpenHttpGetProxy ( IN const char* url,
                                         IN const char* proxy_str,
                                         IN OUT void** handle,
                                         IN OUT char** content-
                                         Type, IN OUT int* con-
                                         tentLength,  IN OUT
                                         int* httpStatus, IN int
                                         timeout )
```

UpnpOpenHttpGetProxy gets a file specified in a URL through the specified proxy.

UpnpOpenHttpGetProxy gets a file specified in a URL through the specified proxy. The SDK allocates the memory for **handle** and **contentType**, the application is responsible for freeing this memory.

Return Value:

[int] An integer representing one of the following:

- **UPNP_E_SUCCESS**: The operation completed successfully.
- **UPNP_E_INVALID_PARAM**: Either **url**, **handle**, **contentType**, **contentLength** or **httpStatus** is not a valid pointer.
- **UPNP_E_INVALID_URL**: The **url** is not a valid URL.
- **UPNP_E_OUTOF_MEMORY**: Insufficient resources exist to download this file.
- **UPNP_E_NETWORK_ERROR**: A network error occurred.
- **UPNP_E_SOCKET_WRITE**: An error or timeout occurred writing to a socket.
- **UPNP_E_SOCKET_READ**: An error or timeout occurred reading from a socket.
- **UPNP_E_SOCKET_BIND**: An error occurred binding a socket.
- **UPNP_E_SOCKET_CONNECT**: An error occurred connecting a socket.
- **UPNP_E_OUTOF_SOCKET**: Too many sockets are currently allocated.
- **UPNP_E_BAD_RESPONSE**: A bad response was received from the remote server.

Parameters:

url	The URL of an item to get.
proxy_str	The URL of the proxy.
handle	A pointer to store the handle for this connection.
contentType	A buffer to store the media type of the item.
contentLength	A pointer to store the length of the item.
httpStatus	The status returned on receiving a response message.
timeout	The time out value sent with the request during which a response is expected from the server, failing which, an error is reported back to the user.

4.7.4

```
EXPORT_SPEC int UpnpOpenHttpGetEx ( IN const char* url, IN
                                     OUT void** handle, IN
                                     OUT char** contentType,
                                     IN OUT int* contentLength,
                                     IN OUT int* httpStatus, IN
                                     int lowRange, IN int high-
                                     Range, IN int timeout )
```

UpnpOpenHttpGetEx gets specified number of bytes from a file specified in the URL.

UpnpOpenHttpGetEx gets specified number of bytes from a file specified in the URL. The number of bytes is specified through a low count and a high count which are passed as a range of bytes for the request. The SDK allocates the memory for **handle** and **contentType**, the application is responsible for freeing this memory.

Return Value:

[int] An integer representing one of the following:

- UPNP_E_SUCCESS: The operation completed successfully.
- UPNP_E_INVALID_PARAM: Either **url**, **handle**, **contentType**, **contentLength** or **httpStatus** is not a valid pointer.
- UPNP_E_INVALID_URL: The **url** is not a valid URL.
- UPNP_E_OUTOF_MEMORY: Insufficient resources exist to download this file.
- UPNP_E_NETWORK_ERROR: A network error occurred.
- UPNP_E_SOCKET_WRITE: An error or timeout occurred writing to a socket.
- UPNP_E_SOCKET_READ: An error or timeout occurred reading from a socket.
- UPNP_E_SOCKET_BIND: An error occurred binding a socket.
- UPNP_E_SOCKET_CONNECT: An error occurred connecting a socket.
- UPNP_E_OUTOF_SOCKET: Too many sockets are currently allocated.
- UPNP_E_BAD_RESPONSE: A bad response was received from the remote server.

Parameters:	<code>url</code>	The URL of the item to get.
	<code>handle</code>	A pointer to store the handle for this connection.
	<code>contentType</code>	A buffer to store the media type of the item.
	<code>contentLength</code>	A buffer to store the length of the item.
	<code>httpStatus</code>	The status returned on receiving a response message from the remote server.
	<code>lowRange</code>	An integer value representing the low end of a range to retrieve.
	<code>highRange</code>	An integer value representing the high end of a range to retrieve.
	<code>timeout</code>	A time out value sent with the request during which a response is expected from the server, failing which, an error is reported back to the user.

4.7.5

```
EXPORT_SPEC int UpnpReadHttpGet ( IN void* handle, IN OUT
                                   char* buf, IN OUT unsigned
                                   int* size, IN int timeout )
```

UpnpReadHttpGet gets specified number of bytes from a file specified in a URL.

UpnpReadHttpGet gets specified number of bytes from a file specified in a URL.

Return Value:	<code>[int]</code>	An integer representing one of the following: <ul style="list-style-type: none"> • <code>UPNP_E_SUCCESS</code>: The operation completed successfully. • <code>UPNP_E_INVALID_PARAM</code>: Either handle, buf or size is not a valid pointer. • <code>UPNP_E_BAD_RESPONSE</code>: A bad response was received from the remote server. • <code>UPNP_E_BAD_HTTPMSG</code>: Either the request or response was in the incorrect format. • <code>UPNP_E_CANCELED</code>: another thread called <code>UpnpCancelHttpGet</code>.
----------------------	--------------------	--

Note: In case of return values, the status code parameter of the passed in handle value may provide additional information on the return value.

Parameters:	<code>handle</code>	The token created by the call to UpnpOpenHttpGet .
	<code>buf</code>	The buffer to store the read item.
	<code>size</code>	The size of the buffer to be read.
	<code>timeout</code>	The time out value sent with the request during which a response is expected from the server, failing which, an error is reported back to the user.

4.7.6

```
EXPORT_SPEC int UpnpHttpGetProgress ( IN void* handle, OUT un-
                                         signed int* length, OUT un-
                                         signed int* total )
```

UpnpHttpGetProgress *retrieve progress information of a http-get transfer.*

UpnpHttpGetProgress retrieve progress information of a http-get transfer.

Return Value: [int] An integer representing one of the following:

- **UPNP_E_SUCCESS**: The operation completed successfully.
- **UPNP_E_INVALID_PARAM**: Either **handle**, **length** or **total** is not a valid pointer.

Parameters:

handle	The token created by the call to UpnpOpenHttpGet .
length	The number of bytes received.
total	The content length.

4.7.7

```
EXPORT_SPEC int UpnpCancelHttpGet (IN void* handle)
```

UpnpCancelHttpGet *set the cancel flag of the **handle** parameter.*

UpnpCancelHttpGet set the cancel flag of the **handle** parameter.

Return Value: [int] An integer representing one of the following:

- **UPNP_E_SUCCESS**: The operation completed successfully.
- **UPNP_E_INVALID_PARAM**: **handle** is not a valid pointer.

4.7.8

```
EXPORT_SPEC int UpnpCloseHttpGet (IN void* handle)
```

UpnpCloseHttpGet *closes the connection and frees memory that was allocated for the **handle** parameter.*

UpnpCloseHttpGet closes the connection and frees memory that was allocated for the **handle** parameter.

Return Value: [int] An integer representing one of the following:

- **UPNP_E_SUCCESS**: The operation completed successfully.
- **UPNP_E_INVALID_PARAM**: **handle** is not a valid pointer.

4.7.9

```
EXPORT_SPEC int UpnpOpenHttpPost ( IN const char* url, IN
                                   OUT void** handle, IN const
                                   char* contentType, IN int con-
                                   tentLength, IN int timeout )
```

UpnpOpenHttpPost makes an HTTP POST request message, opens a connection to the server and sends the POST request to the server if the connection to the server succeeds.

UpnpOpenHttpPost makes an HTTP POST request message, opens a connection to the server and sends the POST request to the server if the connection to the server succeeds. The SDK allocates the memory for **handle** and **contentType**, the application is responsible for freeing this memory.

Return Value: [int] An integer representing one of the following:

- **UPNP_E_SUCCESS**: The operation completed successfully.
- **UPNP_E_INVALID_PARAM**: Either **url**, **handle** or **contentType** is not a valid pointer.
- **UPNP_E_INVALID_URL**: The **url** is not a valid URL.
- **UPNP_E_OUTOF_MEMORY**: Insufficient resources exist to download this file.
- **UPNP_E_SOCKET_ERROR**: Error occurred allocating a socket and resources or an error occurred binding a socket.
- **UPNP_E_SOCKET_WRITE**: An error or timeout occurred writing to a socket.
- **UPNP_E_SOCKET_CONNECT**: An error occurred connecting a socket.
- **UPNP_E_OUTOF_SOCKET**: Too many sockets are currently allocated.

Parameters:	<code>url</code>	The URL in which to send the POST request.
	<code>handle</code>	A pointer in which to store the handle for this connection. This handle is required for further operations over this connection.
	<code>contentType</code>	A buffer to store the media type of content being sent.
	<code>contentLength</code>	The length of the content, in bytes, being posted.
	<code>timeout</code>	The time out value sent with the request during which a response is expected from the receiver, failing which, an error is reported.

4.7.10

```
EXPORT_SPEC int UpnpWriteHttpPost ( IN void* handle, IN char*
                                     buf, IN unsigned int* size, IN
                                     int timeout )
```

UpnpWriteHttpPost sends a request to a server to copy the contents of a buffer to the URI specified in the **UpnpOpenHttpPost** call.

UpnpWriteHttpPost sends a request to a server to copy the contents of a buffer to the URI specified in the **UpnpOpenHttpPost** call.

Return Value: `[int]` An integer representing one of the following:

- **UPNP_E_SUCCESS**: The operation completed successfully.
- **UPNP_E_INVALID_PARAM**: Either **handle**, **buf** or **size** is not a valid pointer.
- **UPNP_E_SOCKET_WRITE**: An error or timeout occurred writing to a socket.
- **UPNP_E_OUTOF_SOCKET**: Too many sockets are currently allocated.

Parameters:

<code>handle</code>	The handle of the connection created by the call to UpnpOpenHttpPost .
<code>buf</code>	The buffer to be posted.
<code>size</code>	The size, in bytes of buf .
<code>timeout</code>	A timeout value sent with the request during which a response is expected from the server, failing which, an error is reported.

4.7.11

```
EXPORT_SPEC int UpnpCloseHttpPost ( IN void* handle, IN OUT
                                     int* httpStatus, IN int time-
                                     out )
```

UpnpCloseHttpPost sends and receives any pending data, closes the connection with the server, and frees memory allocated during the call.

UpnpCloseHttpPost sends and receives any pending data, closes the connection with the server, and frees memory allocated during the call.

Return Value: [int] An integer representing one of the following:

- **UPNP_E_SUCCESS**: The operation completed successfully.
- **UPNP_E_INVALID_PARAM**: Either **handle**, or **httpStatus** is not a valid pointer.
- **UPNP_E_SOCKET_READ**: An error or timeout occurred reading from a socket.
- **UPNP_E_OUTOF_SOCKET**: Too many sockets are currently allocated.

Parameters:

handle	The handle of the connection to close, created by the call to UpnpOpenHttpPost .
httpStatus	A pointer to a buffer to store the final status of the connection.
timeout	A time out value sent with the request during which a response is expected from the server, failing which, an error is reported.

4.7.12

```
EXPORT_SPEC int UpnpDownloadXmlDoc ( IN const char* url,
                                      OUT IXMLDocument**
                                      xmlDoc )
```

UpnpDownloadXmlDoc downloads an XML document specified in a URL.

UpnpDownloadXmlDoc downloads an XML document specified in a URL. The SDK parses the document and returns it in the form of a DOM document. The application is responsible for freeing the DOM document.

Return Value:	[int]	An integer representing one of the following: <ul style="list-style-type: none"> • UPNP_E_SUCCESS: The operation completed successfully. • UPNP_E_INVALID_PARAM: Either url or xmlDoc is not a valid pointer. • UPNP_E_INVALID_DESC: The XML document was not found or it does not contain a valid XML description. • UPNP_E_INVALID_URL: The url is not a valid URL. • UPNP_E_OUTOF_MEMORY: There are insufficient resources to download the XML document. • UPNP_E_NETWORK_ERROR: A network error occurred. • UPNP_E_SOCKET_WRITE: An error or timeout occurred writing to a socket. • UPNP_E_SOCKET_READ: An error or timeout occurred reading from a socket. • UPNP_E_SOCKET_BIND: An error occurred binding a socket. • UPNP_E_SOCKET_CONNECT: An error occurred connecting the socket. • UPNP_E_OUTOF_SOCKET: Too many sockets are currently allocated.
Parameters:	url	URL of the XML document.
	xmlDoc	A pointer in which to store the XML document.

4.8

Web Server API

Names

4.8.1	EXPORT_SPEC int	UpnpSetWebServerRootDir (IN const char* rootDir)	
		UpnpSetWebServerRootDir sets the document root directory for the internal web server.	93
4.8.2	EXPORT_SPEC int		

		UpnpSetVirtualDirCallbacks (IN struct UpnpVirtualDirCallbacks* callbacks) UpnpSetVirtualDirCallbacks sets the callback function to be used to access a vir- tual directory.	94
4.8.3	EXPORT_SPEC int	UpnpEnableWebserver (IN int enable) UpnpEnableWebServer enables or dis- ables the webserver.	94
4.8.4	EXPORT_SPEC int	UpnpIsWebserverEnabled () UpnpIsWebServerEnabled returns TRUE if the webserver is enabled, or FALSE if it is not.	95
4.8.5	EXPORT_SPEC int	UpnpAddVirtualDir (IN const char* dirName) UpnpAddVirtualDir adds a virtual di- rectory mapping.	95
4.8.6	EXPORT_SPEC int	UpnpRemoveVirtualDir (IN const char* dirName) UpnpRemoveVirtualDir removes a virtual directory mapping made with UpnpAddVirtualDir	95
4.8.7	EXPORT_SPEC void	UpnpRemoveAllVirtualDirs () UpnpRemoveAllVirtualDirs removes all virtual directory mappings.	96

4.8.1

EXPORT_SPEC int **UpnpSetWebServerRootDir** (IN const char* root-
Dir)

UpnpSetWebServerRootDir sets the document root directory for the internal web server.

UpnpSetWebServerRootDir sets the document root directory for the internal web server. This directory is considered the root directory (i.e. "/") of the web server.

This function also activates or deactivates the web server. To disable the web server, pass NULL for **rootDir**; to activate, pass a valid directory string.

Note that this function is not available when the web server is not compiled into the SDK.

Return Value: [int] An integer representing one of the following:

- UPPN_E_SUCCESS: The operation completed successfully.
- UPPN_E_INVALID_ARGUMENT: **rootDir** is an invalid directory.

Parameters: rootDir Path of the root directory of the web server.

4.8.2

```
EXPORT_SPEC int UpnpSetVirtualDirCallbacks ( IN struct UpnpVirtualDirCallbacks* callbacks )
```

UpnpSetVirtualDirCallbacks sets the callback function to be used to access a virtual directory.

UpnpSetVirtualDirCallbacks sets the callback function to be used to access a virtual directory. Refer to the description of **UpnpVirtualDirCallbacks** for a description of the functions.

Return Value: [int] An integer representing one of the following:

- UPPN_E_SUCCESS: The operation completed successfully.
- UPPN_E_INVALID_ARGUMENT: **callbacks** is not a valid pointer.

Parameters: callbacks Pointer to a structure containing points to the virtual interface functions.

4.8.3

```
EXPORT_SPEC int UpnpEnableWebserver ( IN int enable )
```

UpnpEnableWebServer enables or disables the webserver.

UpnpEnableWebServer enables or disables the webserver. A value of TRUE enables the webserver, FALSE disables it.

Return Value: [int] An integer representing one of the following:

- UPPN_E_SUCCESS: The operation completed successfully.
- UPPN_E_INVALID_ARGUMENT: **enable** is not valid.

Parameters: enable TRUE to enable, FALSE to disable.

4.8.4

```
EXPORT_SPEC int UpnpIsWebserverEnabled ( )
```

UpnpIsWebServerEnabled returns TRUE if the webserver is enabled, or FALSE if it is not.

UpnpIsWebServerEnabled returns TRUE if the webserver is enabled, or FALSE if it is not.

Return Value: [int] An integer representing one of the following:

- TRUE: The webserver is enabled.
- FALSE: The webserver is not enabled

4.8.5

```
EXPORT_SPEC int UpnpAddVirtualDir ( IN const char* dirName )
```

UpnpAddVirtualDir adds a virtual directory mapping.

UpnpAddVirtualDir adds a virtual directory mapping.

All webserver requests containing the given directory are read using functions contained in a **UpnpVirtualDirCallbacks** structure registered via **UpnpSetVirtualDirCallbacks**.

Return Value: [int] An integer representing one of the following:

- UPPN_E_SUCCESS: The operation completed successfully.
- UPPN_E_INVALID_ARGUMENT: **dirName** is not valid.

Parameters: dirName The name of the new directory mapping to add.

4.8.6

```
EXPORT_SPEC int UpnpRemoveVirtualDir ( IN const char* dirName
                                         )
```

UpnpRemoveVirtualDir removes a virtual directory mapping made with **UpnpAddVirtualDir**.

UpnpRemoveVirtualDir removes a virtual directory mapping made with **UpnpAddVirtualDir**.

Return Value: [int] An integer representing one of the following:

- UPPN_E_SUCCESS: The operation completed successfully.
- UPPN_E_INVALID_ARGUMENT: **dirName** is not valid.

Parameters: dirName The name of the virtual directory mapping to remove.

4.8.7

```
EXPORT_SPEC void UpnpRemoveAllVirtualDirs ( )
```

UpnpRemoveAllVirtualDirs *removes all virtual directory mappings.*

UpnpRemoveAllVirtualDirs removes all virtual directory mappings.

Return Value: [void] This function does not return a value.

5 Optional Tool APIs

Names

- 5.1 EXPORT_SPEC int
UpnpResolveURL (IN const char* BaseURL,
 IN const char* RelURL,
 OUT char* AbsURL)
UpnpResolveURL combines a base URL and a relative URL into a single absolute URL. 98
- 5.2 EXPORT_SPEC IXML_Document*
UpnpMakeAction (IN const char* ActionName,
 IN const char* ServType,
 IN int NumArg, IN const char* Arg,
 IN ...)
UpnpMakeAction creates an action request packet based on its input parameters (status variable name and value pair). . 99
- 5.3 EXPORT_SPEC int
UpnpAddToAction (IN OUT IXML_Document** ActionDoc,
 IN const char* ActionName,
 IN const char* ServType,
 IN const char* ArgName,
 IN const char* ArgVal)
UpnpAddToAction creates an action request packet based on its input parameters (status variable name and value pair). 100
- 5.4 EXPORT_SPEC IXML_Document*
UpnpMakeActionResponse (IN const char* ActionName,
 IN const char* ServType,
 IN int NumArg,
 IN const char* Arg, IN ...)
UpnpMakeActionResponse creates an action response packet based on its output parameters (status variable name and value pair). 100
- 5.5 EXPORT_SPEC int

		UpnpAddToActionResponse (IN OUT IXML_Document** ActionResponse, IN const char* ActionName, IN const char* ServType, IN const char* ArgName, IN const char* ArgVal) UpnpAddToActionResponse creates an action response packet based on its out- put parameters (status variable name and value pair). 101
5.6	EXPORT_SPEC int	UpnpAddToPropertySet (IN OUT IXML_Document** PropSet, IN const char* ArgName, IN const char* ArgVal) UpnpAddToPropertySet can be used when an application needs to transfer the status of many variables at once. 101
5.7	EXPORT_SPEC IXML_Document*	UpnpCreatePropertySet (IN int NumArg, IN const char* Arg, IN ...) UpnpCreatePropertySet creates a property set message packet. 102
5.8	EXPORT_SPEC const char*	UpnpGetErrorMessage (int errorcode) UpnpGetErrorMessage converts an SDK error code into a string error mes- sage suitable for display. 102

The Linux SDK for UPnP Devices contains some additional, optional utility APIs that can be helpful in writing applications using the SDK. These additional APIs can be compiled out in order to save code size in the SDK. Refer to the README for details.

5.1

```
EXPORT_SPEC int UpnpResolveURL ( IN const char* BaseURL, IN
                                const char* RelURL, OUT char*
                                AbsURL )
```

UpnpResolveURL combines a base URL and a relative URL into a single absolute URL.

UpnpResolveURL combines a base URL and a relative URL into a single absolute URL. The memory for **AbsURL** needs to be allocated by the caller and must be large enough to hold the **BaseURL** and **RelURL** combined.

Return Value: [int] An integer representing one of the following:

- **UPNP_E_SUCCESS:** The operation completed successfully.
- **UPNP_E_INVALID_PARAM:** **RelURL** is NULL.
- **UPNP_E_INVALID_URL:** The **BaseURL** / **RelURL** combination does not form a valid URL.
- **UPNP_E_OUTOF_MEMORY:** Insufficient resources exist to complete this operation.

Parameters:

BaseURL	The base URL to combine.
RelURL	The relative URL to BaseURL .
AbsURL	A pointer to a buffer to store the absolute URL.

5.2

```
EXPORT_SPEC IXML_Document* UpnpMakeAction ( IN const char*
ActionName, IN const char* ServType, IN int NumArg, IN const char*
Arg, IN ... )
```

UpnpMakeAction creates an action request packet based on its input parameters (status variable name and value pair).

UpnpMakeAction creates an action request packet based on its input parameters (status variable name and value pair). Any number of input parameters can be passed to this function but every input variable name should have a matching value argument.

Return Value: [IXML_Document*] The action node of **Upnp_Document** type or NULL if the operation failed.

Parameters:

ActionName	The action name.
ServType	The service type.
NumArg	Number of argument pairs to be passed.
Arg	Status variable name and value pair.

5.3

```
EXPORT_SPEC int UpnpAddToAction ( IN OUT IXML_Document**
ActionDoc, IN const char*
ActionName, IN const char*
ServType, IN const char*
ArgName, IN const char*
ArgVal )
```

UpnpAddToAction *creates an action request packet based on its input parameters (status variable name and value pair).*

UpnpAddToAction creates an action request packet based on its input parameters (status variable name and value pair). This API is specially suitable inside a loop to add any number input parameters into an existing action. If no action document exists in the beginning then a **Upnp_Document** variable initialized with NULL should be passed as a parameter.

Return Value: [int] An integer representing one of the following:

- UPNP_E_SUCCESS: The operation completed successfully.
- UPNP_E_INVALID_PARAM: One or more of the parameters are invalid.
- UPNP_E_OUTOF_MEMORY: Insufficient resources exist to complete this operation.

Parameters:

ActionDoc	A pointer to store the action document node.
ActionName	The action name.
ServType	The service type.
ArgName	The status variable name.
ArgVal	The status variable value.

5.4

```
EXPORT_SPEC IXML_Document* UpnpMakeActionResponse ( IN
const char* ActionName, IN const char* ServType, IN int NumArg,
IN const char* Arg, IN ... )
```

UpnpMakeActionResponse *creates an action response packet based on its output parameters (status variable name and value pair).*

UpnpMakeActionResponse creates an action response packet based on its output parameters (status variable name and value pair). Any number of input parameters can be passed to this function but every output variable name should have a matching value argument.

Return Value: [IXML_Document*] The action node of **Upnp_Document** type or NULL if the operation failed.

Parameters:

ActionName	The action name.
ServType	The service type.
NumArg	The number of argument pairs passed.
Arg	The status variable name and value pair.

5.5

```
EXPORT_SPEC int UpnpAddToActionResponse ( IN OUT
IXML_Document** ActionResponse, IN const char* ActionName,
IN const char* ServType, IN const char* ArgName, IN const char*
ArgVal )
```

UpnpAddToActionResponse *creates an action response packet based on its output parameters (status variable name and value pair).*

UpnpAddToActionResponse creates an action response packet based on its output parameters (status variable name and value pair). This API is especially suitable inside a loop to add any number of input parameters into an existing action response. If no action document exists in the beginning, a **Upnp_Document** variable initialized with NULL should be passed as a parameter.

Return Value: [int] An integer representing one of the following:

- UPNP_E_SUCCESS: The operation completed successfully.
- UPNP_E_INVALID_PARAM: One or more of the parameters are invalid.
- UPNP_E_OUTOF_MEMORY: Insufficient resources exist to complete this operation.

Parameters:	ActionResponse	Pointer to a document to store the action document node.
	ActionName	The action name.
	ServType	The service type.
	ArgName	The status variable name.
	ArgVal	The status variable value.

5.6

```
EXPORT_SPEC int UpnpAddToPropertySet ( IN OUT
IXML_Document**
PropSet, IN const char*
ArgName, IN const
char* ArgVal )
```

UpnpAddToPropertySet *can be used when an application needs to transfer the status of many variables at once.*

UpnpAddToPropertySet can be used when an application needs to transfer the status of many variables at once. It can be used (inside a loop) to add some extra status variables into an existing property set. If the application does not already have a property set document, the application should create a variable initialized with NULL and pass that as the first parameter.

